### WATERING OF LANDSCAPE PLANTS USING WASTEWATER TREATED WITH TERMINALIA CATAPPA

### NURFARHAIN BINTI MOHAMED RUSLI

A report submitted in partial fulfillment of the requirements for the award of the degree of Master of Engineering

> Faculty of Civil Engineering Universiti Teknologi Malaysia

> > JUNE 2009

"To my loves family....." Mama, Ablong, Kak Aitul, Abngah, Jiejah, Farah and Fathin... Thanks for your support, To my loves one, thanks for your love, care and encouragement.... All friends..... Thank you for everything.....

Our Loves Never Ends

### ACKNOWLEDGEMENT

"In the name of God, the most gracious, the most compassionate"

First of all, thank god for giving me the strength to complete this thesis within the time.

Then, I would like to express my deep appreciation to my beloved family members:, mother, and my siblings who always providing me the encouragement and spiritual support to choose the way of life which I believe on.

My thesis supervisor, Dr Shamila Azman is an important figure in guiding and counseling me towards the thesis accomplishment. Her generosity, patience, tolerance and helping character nourished me more than what I gained through the successful completion of thesis. Thanks a lot, Dr Shamila!

I am also very appreciation to all environmental lab personnel, Pak Usop, En Ramli, En Azreen, Kak Ros who have contributed their assistance and views at various occasions.

Last but not least, I would like to convey my special thanks to all friends, and those whoever lending a helping hand either directly or indirectly, that led to the completion of this thesis. Thank You!

### ABSTRACT

This study was conducted to identify the antibacterial properties of Terminalia cattapa (TC) leaves and also to explore the feasibility of using it with domestic wastewater effluent for reuse purposes. Previous study conducted in UTM have shown the potential of using domestic wastewater in watering landscape plants where chlorine was use to disinfect the wastewater. Since chlorine application produce residual effect, TC leaves offers another potential to be applied together with the domestic wastewater in order to eliminate bacterial contamination. From analysis conducted, TC leaves in blended form with wastewater yield better results compared to cut and original leave form. In this study, effluent from domestic wastewater oxidation pond was collected and applied daily to two landscape gardens with a surface area of 1.5 m x 1.0 m x 0.3 m where both plots were planted with five different plants. The difference between the two plots are one is applied with wastewater and TC leaves meanwhile the other one is applied with wastewater only and stand as a control. Wastewater effluents collected were analysed for BOD, COD, E. coli, phosphorus, ammoniacal nitrogen and pH. From the result obtained all samples treated using TC leaves shows 98% removal of E. coli numbers after 5 days treatment. In order to compare bacterial removal, analysis on residual chlorine was also carried out, result obtained shows that even though chlorine is effective in eliminating bacteria it has residue effect which is harmful to human or plants and insects. Treated sewage effluent applied to landscape plants produce better growth when compared to untreated wastewater. The results obtained showed positive growth increment for wastewater with TC leaves in terms of height and width for all plants except for *Elephantopus scaber (Es)* which thrive more when applied with wastewater.

### ABSTRAK

Kajian ini dijalankan adalah untuk mengenalpasti sifat anti-bakteria dan juga untuk mengkaji kebolehgunaan daun ketapang dalam merawat air sisa domestik untuk tujuan guna semula. Hasil kajian lepas yang dijalankan di UTM, menunjukkan penggunaan air sisa domestik berpontensi digunakan semula untuk menyiram tumbuhan landskap. Dalam rawatan tersebut, klorin telah digunakan untuk merawat air sisa tersebut serta bertindak sebagai agen anti-bakteria. Oleh kerana penggunaan klorin meninggalkan sisa, TC menunjukkan potensi untuk digunakan dalam merawat air sisa domestik. Daripada analisis yang dijalankan, daun ketapang yang dikisar dengan air sisa menunjukkan keputusan jauh lebih baik berbanding dengan daun yang dipotong atau dalam keadaan biasa. Dalam kajian ini, efluen dari kolam pengoksidaan telah digunakan dua kali sehari pada dua taman landskap yang berbeza dengan lima jenis tumbuhan di tanam di atas landskap bersaiz 1.5 m x 1.0 m x 0.3 m. Perbezaan antara plot tanaman tersebut ialah satu akan disiram air sisa domestik yang di rawat dengan daun ketapang dan yang satu lagi bertindak sebagai kawalan dan disiram dengan air sisa domestik sahaja. Air sisa domestik yang diambil telah di analisis untuk parameter BOD, COD, E. coli, fosforus, ammonia nitrogen dan pH. Dari keputusan yang diperolehi, semua sampel yang dirawat dengan daun ketapang menunjukkan penurunan E. coli sebanyak 98% selepas 5 hari. Dalam perbandingan penyingkiran bakteria, analisis terhadap sisa klorin turut di jalankan dan hasil menunjukkan walaupun klorin berkesan untuk membunuh bakteria, ia meninggalkan kesan sisa yang boleh membahayakan manusia, tumbuhan dan juga serangga. Air sisa domestik yang dirawat dan diaplikasikan ke tanaman landskap menghasilkan pertumbuhan baik berbanding dengan air sisa yang tidak dirawat. Keputusan menunjukkan pertumbuhan positif berlaku dalam pertumbuhan tinggi dan lebar daun untuk semua tanaman kecuali pada elephantopus scaber (Es), yang tumbuh subur dengan air sisa domestik yang tidak di rawat.

# TABLE OF CONTENTS

CHAPTER		TITLE	PAGE
	DEC	CLARATION	ii
	DED	DICATION	iii
	ACK	KNOWLEDGEMENTS	iv
	ABS	TRACT	v
	ABS	TRAK	vi
	TAB	LE OF CONTENTS	vii
	LIST	Г OF TABLES	xii
	LIST	r of figures	xiv
	LIST OF ABREVATIONS		xviii
	LIST	Γ OF APPENDICES	xix
1		RODUCTION	1
	1.1	Introduction	1
	1.2	Problem Statement	3
	1.3	Objective of the Study	5
	1.4	Scope of the Study	6
	1.5	Significance of Study	6
2	LITI	ERATURE REVIEW	8
	2.1	Introduction	8

2.2 Domestic Wastewater 9

0.0		1.4
2.3	Characteristics of Domestic Wastewater	14
	2.3.1 Physical Characteristics	15
	2.3.2 Chemical Characteristics	18
	2.3.3 Biological Characteristics	23
	2.3.4 Nutrients	25
2.4	Oxidation Pond (OP)	28
2.5	Wastewater Reuse Applications	30
2.6	Potential Risks from Using Recycled Water	33
2.7	Agricultural Reuse	33
2.8	Sustainable Environment and Development	36
2.9	Global Warming and Climate Change	38
2.10	Carbon Footprint	41
2.11	Water Reuse Problem	43
2.12	Wastewater Treatment	44
2.13	Wastewater Treatment in Malaysia	45
	2.13.1 Environmental Regulations and Standards in	45
	Malaysia	
2.14	Wastewater Treatment Method	46
	2.14.1 Aluminium Sulphate (Alum)	47
	2.14.2 Ferric Chloride	48
	2.14.3 Ozonation	48
	2.14.4 Ultraviolet (UV)	49
	2.14.5 Disinfection	50
2.15	Previous Study	51
2.16	Terminalia catappa	52
	2.16.1 Characteristics of Terminalia catappa	53
	2.16.2 The Uses of Terminalia catappa	55
	2.16.3 Tannin	58
2.17	Escherichia coli	59
2.18	NPK Ratio	60
	2.18.1 The Secondary Macronutrients	62

**METHODOLOGY OF RESEARCH** 64 3.1 Introduction 64 3.2 Jar Test 67 3.3 67 Leaf Condition Analysis 3.3.1 Optimum Dosage of *Terminalia catappa* Leaves 68 (Tannin Concentration) 3.4 Extraction of *Terminalia catappa* Leaves 69 3.5 Wastewater Collection 70 3.6 Sample Handling Procedure 71 3.7 Apparatus and Chemicals 71 3.8 Wastewater Treatment using Terminalia catappa Leaves 73 3.9 73 Water Quality Analysis 3.9.1 pH 74 3.9.2 Biochemical Oxygen Demand (BOD) 75 3.9.3 Chemical Oxygen Demand (COD) 75 3.9.4 Ammoniacal Nitrogen (AN) 76 3.9.5 Phosphorus 77 3.9.6 Tannin 77 3.9.7 Escherichia coli 77 3.10 79 Disinfection of Effluent 3.10.1 Iodometric Method for Determinataion of 80 **Residual Chlorine** 3.11 Landscape Design 81 3.12 Plants Growth Determination 83 3.13 Preparation of Agar Nutrient (EMB Agar) 84 3.13.1 Plate Colony Counting 86 3.13.2 Serial Dilutions for Plate Counting 87 3.14 **Microbiology Sampling Procedures** 89 3.15 Determination of NPK Ratio 90

3

4

<b>RESULT AND ANALYSIS</b>		
4.1	Introduction	91

4.2	Optim	um Dosage of Terminalia catappa (TC) Leaves	91
	4.2.1	Analysis of Tannin Concentration	92
	4.2.2.	Analysis of pH	93
	4.2.3	Soxhlet Extraction	95
4.3	Waste	water Treatment Analysis	96
	4.3.1	pH	96
	4.3.2	Biochemical Oxygen Demand (BOD)	97
	4.3.3	Chemical Oxygen Demand (COD)	99
	4.3.4	Ammoniacal Nitrogen	100
	4.3.5	Phosphorus	101
	4.3.6	Escherichia coli	102
4.4	Analy	sis of Coliform on Leaves and Grass	103
	4.4.1	Coleus artopurpureus (Ca)	104
	4.4.2	Cyperus dubius rottb (Cd)	105
	4.4.3	Nyctanthes arbo-tristis L (Na)	106
	4.4.4	Panicaum maximum cv. colonio (Pm)	107
	4.4.5	Vinca rosea (Vr)	109
	4.4.6	Elephantopus scaber (Es)	110
4.5	Analy	sis of Coliform on Soil from landscape plots	111
4.6	Waste	water Influence on Plant Growth	112
4.7	Growt	th Rate of Plants	116
	4.7.1	Growth Rate of Vinca rosea (Vr)	116
	4.7.2	Growth Rate of Coleus artopurpureus (Ca)	118
	4.7.3	Growth Rate of Nyctanthes arbo-tristis L (Na)	119
	4.7.4	Growth Rate of Panicaum maximum cv. colonio	121
		( <i>Pm</i> )	
	4.7.5	Growth Rate of Cyperus dubius rottb (Cd)	122
	4.76	Growth rate of <i>Elephantopus scaber</i> (Es)	124
4.8	Nitrog	gen-Phosphorus-Potassium Ratio (NPK)	125
4.9	Disinf	Tection	126

5.2	Recommendation	131
REFERENCES		133
APPENDIXES		144

# LIST OF TABLES

TABLE NO.

## TITLE

PAGE

Parameter Limits of Effluent of Standard A and B	11
(Environment Quality Act, 1974)	
Composition of Typical Untreated Domestic Wastewater	15
(Burks and Minnis, 2006)	
Typical Composition of Untreated Domestic Wastewater	21
(Metcalf and Eddy, 2004)	
Typical of Organisms of Untreated Domestic Wastewater	26
(Metcalf and Eddy, 2007)	
Typical and Number of Microorganism of Untreated	27
domestic (Metcalf and Eddy, 2007)	
Effluents of Oxidation Pond (Indah Water Consortium, 2008)	29
Advantages and Disadvantages of Wastewater Reuse	31
(Kumar <i>et al.</i> , 2006)	
Standards of Treated Wastewater for Irrigation in India	35
(Kumar <i>et al.</i> , 2006)	
List of Apparatus and Chemicals for each Ttest	72
Concentration of Tannin and pH for Terminalia catappa Leaves	95
extracted with Soxhlet Apparatus	
Average growth rate of plants from experiment and control	113
landscape garden	
pH values for different soil samples collected from landscape	115
garden	
NPK ratio of different soil in landscape garden	125
	<ul> <li>Parameter Limits of Effluent of Standard A and B</li> <li>(Environment Quality Act, 1974)</li> <li>Composition of Typical Untreated Domestic Wastewater</li> <li>(Burks and Minnis, 2006)</li> <li>Typical Composition of Untreated Domestic Wastewater</li> <li>(Metcalf and Eddy, 2004)</li> <li>Typical of Organisms of Untreated Domestic Wastewater</li> <li>(Metcalf and Eddy, 2007)</li> <li>Typical and Number of Microorganism of Untreated</li> <li>domestic (Metcalf and Eddy, 2007)</li> <li>Effluents of Oxidation Pond (Indah Water Consortium, 2008)</li> <li>Advantages and Disadvantages of Wastewater Reuse</li> <li>(Kumar <i>et al.</i>, 2006)</li> <li>Standards of Treated Wastewater for Irrigation in India</li> <li>(Kumar <i>et al.</i>, 2006)</li> <li>List of Apparatus and Chemicals for each Ttest</li> <li>Concentration of Tannin and pH for <i>Terminalia catappa</i> Leaves</li> <li>extracted with Soxhlet Apparatus</li> <li>Average growth rate of plants from experiment and control</li> <li>landscape garden</li> <li>pH values for different soil samples collected from landscape</li> <li>garden</li> <li>NPK ratio of different soil in landscape garden</li> </ul>

4.5	Effect of chlorine dosage and contact time towards E. coli	126
	survival rate	
4.6	Total residue of chlorination using Iodometric Method	128

## LIST OF FIGURES

FIGURE NO.

## TITLE

# PAGE

1.1	Percentage of Activity Contribute to Water Pollution (DOE, 2005)	4
2.1	The increasing concentration of greenhouse gases from the year 0	39
	to 2005 (IPCC, 2007)	
2.2	The greenhouse effect is where most infrared radiation is	40
	absorbed by the atmosphere and re-emitted in all directions by	
	greenhouse gas (GHG) molecules and clouds (IPCC, 2007)	
2.3	Terminalia catappa tree	53
2.4	Illustration of Terminalia catappa Leaves	53
2.5	Terminalia catappa leaves Before Falling	54
2.6	Terminalia catappa leaves After Falling	54
2.7	Terminalia catappa Flowers	54
2.8	Terminalia catappa Fruits	54
2.9	Escherichia coli (E. coli) (Gerard et al., 2004)	60
3.1	Design Framework of Part One for this study	65
3.2	Design Framework of Part One for this study	66
3.3	Jar Test Analysis	67
3.4	Jar Test analysis for optimum dosage of tannin concentration	68
3.5	Example of Soxhlet Extraction carried out at Organic Research	69
	Laboratory, Faculty of Science (UTM)	
3.6	Example of Soxhlet Extractor with Terminalia catappa Leaves	70
3.7	Oxidation pond near Kolej Tunku Canselor, UTM	71
3.8	Treatment of wastewater using Terminalia catappa Leaves in the	73
	tank	

3.9	Meter pH model Orion 420 A	74
3.10	BODTrak Apparatus	75
3.11	COD Reactor HACH DRB200	76
3.12	HACH DR5000 Spectrophotometer	77
3.13	Analysis of E. coli using Quanty-Tray/2000	78
3.14 (a)	Quanti-Tray Sealer Model 2x	78
3.14 (b)	Thermolyne Type 142300 Incubator	78
3.15	Chlorination process using magnetic stirrer (Chemix model CL 6)	79
3.16	Landscape Garden Side View	81
3.17	Landscape Garden Plan View	82
3.18 (a)	Landscape Garden with Coleus artopurpureus (Ca)	82
3.18 (b)	Landscape Garden with Nyctanthes arbo-tristis L (Na)	82
3.19 (a)	Landscape Garden with Five Different types of plants	83
3.19 (b)	Landscape Garden with Vinca rosea (Vr)	83
3.20	Width Growth Determination	84
3.21	Height Growth Determination	84
3.22 (a)	Figure of preparation of agar nutrient	86
3.22 (b)	Figure of agar was poured in petri dishes	86
3.23 (a)	Figure indicates that the agar nutrient in petri dish (before)	87
3.23 (b)	Figure indicates that the agar nutrient in petri dish (after)	87
3.24	Plate Counts and Serial Dilutions (Gerard et al., 2004)	88
3.25 (a)	Figure shows that cotton buds that were used to swab the leaves	89
3.25 (b)	Figure shows that (Bunsen burner that will used to heat up the	89
	cotton bud before use	
4.1	Concentration of tannin from Terminalia catappa leaves in	92
	different forms i.e. original leaf, cut and blended in distilled water	
4.2	pH measurement of TC leaves from 30 g to 70 g of	94
	immersion in distilled water after 7 days	
4.3	pH measurement for distilled water added with 70 g TC leaves	94
	in original, cut and blended form	
4.4	pH of domestic wastewater before and after treatment with	97
	TC leaves for 5 days	
4.5	Concentration of BOD in wastewater samples before and after	98

	treatment with TC leaves for 5 days	
4.6	Concentration of COD in wastewater samples collected on 2 <sup>nd</sup>	99
	May to $2^{nd}$ Jun 2009 before and after treatment with TC leaves	
4.7 :	Concentration of ammoniacal nitrogen in wastewater samples	100
	collected on 2 <sup>nd</sup> May to 2 <sup>nd</sup> Jun 2009 before and after treatment wi	th
	TC leaves for 5 days	
4.8	Concentration of phosphorus in wastewater samples collected on	101
	$2^{nd}$ May to $2^{nd}$ Jun 2009 before and after treatment with TC leaves	
4.9	E. coli numbers in domestic wastewater effluent before and after	103
	treated with TC leaves	
4.10	E. coli on Coleus artopurpureus (Ca) plant during different	104
	sampling time intervals	
4.11	E. coli on Cyperus dubius rottb (Cd) plant during different	105
	sampling time intervals	
4.12 (a)	Cyperus dubius rottb (Cd) plant	106
4.12 (b)	Coleus artopurpureus (Ca) with different surface leaves area	106
4.13	E. coli on Nyctanthes arbo-tristis L (Na) plant during different	107
	sampling time intervals	
4.14	E. coli on Panicaum maximum cv. colonio (Pm) plant during	108
	different sampling time intervals	
4.15	E.coli on Vinca rosea (Vr) plant during different sampling	109
	time intervals	
4.16	E. coli on Elephantopus scaber (Es) plant during different	110
	sampling time intervals	
4.17	<i>E. coli</i> in soil samples analysed on $11^{\text{th}}$ May to $2^{\text{nd}}$ June 2009	112
4.18	Flowers watered with wastewater and $TC$ is more radiant and	114
	shining compared to the control plants	
4.19	Growth rate of Vinca rosea (Vr) plant in terms of height for	116
	experimental plot and control plot garden	
4.20	Growth rate of Vinca rosea (Vr) plant in terms of width	116
	(leaves) for experimental plot and control plot garden	
4.21	Growth rate of Coleus artopurpureus (Ca) plant in terms	117
	of height for experimental plot and control plot garden	
4.22	Growth rate of <i>Coleus artopurpureus</i> ( <i>Ca</i> ) plant in terms	118

	of width (leaves) for experimental plot and control plot garden	
4.23	Growth rate of Nyctanthes arbo-tristis L (Na) plant in terms	119
	of height for experimental plot and control plot garden	
4.24	Growth rate of Nyctanthes arbo-tristis L (Na) plant in terms	119
	of width (leaves) for experimental plot and control plot garden	
4.25	Growth rate of Panicaum maximum cv. colonio (Pm) plant in	121
	terms of height for experimental plot and control plot garden	
4.26	Growth rate of Panicaum maximum cv. colonio (Pm) plant in	121
	terms of width (leaves) for experimental plot and control plot ga	rden
4.27	Cyperus dubius rottb (Cd) plant with small leaves surface area	122
4.28	Growth rate of Cyperus dubius rottb (Cd) plant in terms of	122
	height for experimental plot and control plot garden	
4.29	Growth rate of Elephantopus scaber (Es) plant in terms of	123
	width for experimental plot and control plot garden	
4.30	Bacteria removal after disinfection process with	126
	different chlorine dosage and contact times	
4.31	Chlorine residue after disinfection process with different	127
	chlorine dosage	

# LIST OF ABREVATIONS

°C	degree celcius
BOD	biochemical oxygen demand
COD	chemical oxygen demand
DO	dissolved oxygen
DOE	Department of Environment
GHG	greenhouse gases
GWP	global warming potential
IPCC	Intergovernmental Panel on Climate Changes
m	meter
mg/L	miligram per litre
OP	oxidation pond
SS	suspended solids
TC	Terminalia catappa
UTM	Universiti Teknologi Malaysia

# LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Determination of Biochemical Oxygen Demand	144
	(BOD) Using HACH DR5000 Spectrophotometer	
В	Determination of Chemical Oxygen Demand (COD)	151
	Using HACH DR5000 Spectrophotometer	
С	Determination of Ammoniacal Nitrogen Using	156
	HACH DR5000 Spectrophotometer	
D	Determination of Phosphorus Using HACH DR5000	159
	Spectrophotometer	
Е	Determination of Tannin Using HACH DR5000	162
	Spectrophotometer	
F	Determination of E. coli	165

### **CHAPTER 1**

#### **INTRODUCTION**

#### 1.1 Introduction

Water is a common substance that is essential for the survival of all known forms of life. In typical usage, water refers only to its liquid form or state, but the substance also has a solid state, ice, and a gaseous state, water vapor or steam (Metcalf and Eddy, 2004). Water covers 71% of the Earth's surface, it is found mostly in oceans and other large water bodies, with 1.6% of water underground in aquifers and 0.001% in the air as vapor, clouds (formed of solid and liquid water particles suspended in air), and precipitation (Marks, 2001). Water is a tasteless, odorless liquid at standard temperature and pressure. The color of water and ice is, intrinsically, a very light blue hue, although water appears colorless in small quantities. Ice also appears colorless, and water vapor is clearly invisible as a gas (Environmental Protection Agency, 2006).

According to Malaysia Water Industry Guide (2007), the increased demand for clean water has led to competition in water use among the various water user sectors and the continued economic growth will magnify this even more acutely. The practicable limit of surface water resources development has been reached in regions of high demand, and it has become necessary to consider interbasin and interstate water transfers. The current approaches towards water supply in cities are supply driven when there's a "shortage", new sources are developed.

Fresh water is vital to sustain human life. However, only 3% of total water on earth is fresh water and two-thirds of that is in frozen forms such as the polar ice caps, glaciers and icebergs. The remaining 1% of the total fresh water is either surface water or groundwater where groundwater consists of two-thirds of this amount. The United States annually receives rainfall in a quantity sufficient to cover the entire country to a depth of 30 inches that is known as the U.S. water budget (Environmental Protection Agency, 2006). However, the annual precipitation is not evenly distributed around the country. The eastern half of the country receives more precipitation than the western half.

Water is the earth's most ubiquitous and most effective dissolving agent, playing a key role in human civilization. It quenches the thirst and enables the growth of food and fibre for 6.1 billion human inhabitants. Humans now use half of the readily available freshwater, which is in short supply, less than 1% of earth's water resources goes for domestic, agricultural, horticultural, and industrial needs.

The world population in 2008 was estimated at 7.7 billion with an annual growth rate of 3.5 percent or 83 million people per year. To put the recent growth in perspective, the world population in the year 1900 was only 1.6 billion and in 1950 it was 2.5 billion. It is projected that the world population in 2050 will be between 7.9 billion and 10.3 billion (United Nations, 2008). The rate of growth in industrialized countries is well under one percent per year. In developing countries, the growth rate exceeds six percent per year, and in some parts of Malaysia, China andSingapore which the growth rate increase 6.3 percent in 2008 for Malaysia. As a result, over 90 percent of all future population increses will occur in the developing world (United Nations, 2008).

#### **1.2 Problem Statement**

The water demands are increasing due to the increasing population and the rapid development in our country (Blumenthal *et al.*, 2000). Devamany a/l S. Krishnasamy (Utusan Malaysia 30 Mac 2005), reported that 12.5-14 billion meter cubic water is used by the humans in the world every year and the usage for a year are 9000 meter cubic per capita global. Increase in population, rapid industrialization and agricultural activities have increased the water demand to a greater extent.

In 2006, the Department of Environment (DOE) registered 18,956 water pollution point sources comprising mainly sewage treatment plants (9,060: 47.79% inclusive of 601 Network Pump Stations), manufacturing industries (8,543: 45.07%), animal farms (869: 4.58%) and agro-based industries (484: 2.55%) represents the distribution of industrial water pollution sources from agro-based and manufacturing industries compiled by the DOE in 2006 through field surveys and questionnaires. A total of 9,027 sources were identified with Selangor having the highest number of water pollution sources (1,850: 20.49%), followed by Johor (1,774: 19.65%).

According to statistics compiled by the Veterinary Department of Malaysia, the total standing pig population for 2006 was about 1.67 million, a decrease of 1.76 percent compared to 1.7 million in 2005. Correspondingly, the number of pig farms decreased to 869 farms compared to 898 in the previous year. The number of sewage treatment plants under the management of Indah Water Consortium Sdn. Bhd. (IWK) had increased to 9,060 in 2006 compared to 8,782 plants in 2005. Selangor had the largest number of sewage treatment plants (2,563: 28.3%), Perak (1,343: 14.8%), Johor (1,010: 11.1%) and Negeri Sembilan (928: 10.2%)

Although the effluents from the sewerage treatment plant are treated, the effluents affect the water pollution in our country particularly when the effluents are

discharged to the river, lake or stream (DOE, 2008). High nutrient concentration in the effluent can contribute to water pollution which can destroy the aquatic life and environment. Therefore, nowadays there are a lot of water pollution issues everywhere around the world.

Water pollution occurs when a body of water is adversely affected due to the addition of large amounts of materials to the water (Metcalf and Eddy, 2004). When it is unfit for its intended use, water is considered polluted. Figure 1.1 below shows the percentage of the activity that contribute to water pollution, and the higher percentages are from sewerage treatment plant compared to other activity. Therefore, an alternative water conversation method needs to be carry out to prevent the problem.



Figure 1.1: Percentage of Activity Contributes to Water Pollution (DOE, 2005)

The best alternative that could be practice is reuse of the effluent in our daily activities. In the recent year, human are more concern and aware of the serious ness on reuse and reclamation water in the world. In many locations where the available supply of fresh water has become inadequate to meet water needs, it is clear that the once-used water collected from communities and municipalities must be viewed not as a waste to be disposed of but as a resource that must be reused. The concept of reuse is becoming accepted more widely as other parts of the world which is experiencing water shortage (Metcalf and Eddy, 2004).

The use of dual water systems, such as now used in St. Petersburg in Florida and Rancho Viejo in California, is expected to increase in the future (Metcalf and Eddy, 2004). Most of the reuse of wastewater occurs in the arid and semiarid western and southwestern states of the United States. However, the number of reuse projects is increasing in the south especially in Florida and South Carolina (Metcalf & Eddy, 2004). In Malaysia, recycled wastewater is also used for horticultural irrigation, residential garden irrigation and toilet flushing. Typically wastewater is produced in a larger quantity in the cities but used for agriculture in the countryside. Malaysia faces a particularly pressing water resources challenge. It has a largely agricultural population heavily reliant on the over exploitation of groundwater for its survival.

#### **1.2** Objective of the Study

The objectives of this study are:-

- (i) To identify the antibacterial properties of *Terminalia catappa* leaves
- (ii) To compare the usage of *Terminalia catappa* leaves with chlorination process to kill bacteria in domestic effluent
- (iii) To identify the feasibility of reusing domestic effluent treated with *Terminalia catappa* to water landscape plants.

#### **1.4** Scope of the Study

Wastewater samples were collected from oxidation pond at Universiti Teknologi Malaysia (UTM) Skudai. The plant is a major treatment facility in UTM, which processed an average 250 000 m<sup>3</sup>/day of wastewater originating from campus and hostels area. The study explores the feasibility of using effluent from domestic wastewater treatment plant to waters landscape plants. Thus, the study will aim at obtaining and analyzing the coliform bacteria data in order to investigate the fecal contamination occurring on plants in the landscape garden.

*Terminalia catappa* leaf was used as disinfection agent to kill bacteria to ensure public also health. The feasibility of the wastewater reuse practice in Malaysia was also evaluated by comparing the data with other regulations. An openair landscape garden of 1.5 m x 1.0 m x 0.3 m was designed and constructed with five different shrubs was planted covering the area. The plants are *Coleus artopurpureus* (*Ca*), *Cyperus dubius Rottb* (*Cd*), *Nyctanthes arbo-tristis L* (*Na*), *Panicaum maximum cv. Colonio* (*Pm*) and *Vinca rosea* (*Vr*). Grass type *Elephantopus Scaber* (*Es*) was also planted in the middle region of the garden.

### 1.5 Significance of Study

Chlorination is by far the most common method of wastewater disinfection and is used worldwide for the disinfection of pathogens before being discharge into receiving streams, rivers or oceans. Although chlorine has always been used to treat polluted water, it still causes problem in terms of residue. One disadvantage is that chlorination of residual organic material can generate chlorinated organic compounds that may also be carcinogenic and harmful to the environment. Residual chlorine or chloramines may also be capable of chlorinating organic material in the natural aquatic environment. Furthermore, because residual chlorine is toxic to aquatic species, the treated effluent must also be chemically dechlorinated, adding to the complexity and cost of treatment.

Chlorination requires high cost compared to *Terminalia catappa* leaf which is cheaper since it is easily obtain and the process of the producing tannin extract is simpler. Moreover, there are quite a number of *Terminalia catappa* trees in Malaysia. Last but not least, the cost to treat residue will be cut off since it produces lesser residues and is environmentally friendly.