
**APPLICATION OF ARTIFICIAL NEURAL NETWORK IN BRIDGE DECK
CONDITION RATING**

NORHISHAM BIN BAKHARY

A thesis submitted in fulfilment
of the requirements for the award
of degree of Masters of Engineering (Structure)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

AUGUST, 2001

or Mak, Ayah and Nana

id

ACKNOWLEDGMENTS

I wish to express my sincere thanks to my supervisors: Dr Azlan Adnan in Faculty of Civil Engineering, UTM Johor Bahru and Assoc. Prof. Dr Arshad Ahmad in Faculty of Chemical Engineering and Natural Resource Engineering, UTM Johor Bahru for their assistance, encouragement and guidance during years of my study.

I also would like to express my thanks to Prof. Dr Jamshid Mohammadi in Illinois Institute of Technology, for being my external supervisor who had spent most of his time in assisting and guiding me through this research when I was in Illinois Institute of Technology.

I also would like to thank the staff of Unit Jambatan, Ibu Pejabat Jabatan Kerja Raya, Kuala Lumpur and staff of California Department of Transportation, USA for providing me the data and information for this research.

My thanks are also to my employer, UTM for granting me the study leave and financial support during the study. Also to Illinois Institute of Technology for accepting me as a special student in a very prestigious school.

ABSTRACT

Currently bridges are evaluated through either a visual inspection process or structural analysis. When bridge evaluation is conducted by visual inspection a subjective rating is assigned to the bridge components. With analytical evaluation, the rating is computed based on the load applied and the resistance capacity of bridge component. Visual inspection is subjective and depends primarily on the experience of the inspector in assigning the rating. Analytical rating is unable to represent the condition of bridge component since the rating is computed based on the load and bridge capacity only. If a relationship between analytical rating and subjective rating can be found, the estimation of bridges condition can be made only by determining the bridge analytical rating. Several attempts to correlate both methods using the conventional statistical analyses, as well as fuzzy logic have not been very successful in providing the relationship between those rating methods. However, an attempt to utilize Artificial Neural Network (ANN) to correlate the analytical rating for railroad and bridge parameter with bridge subjective rating in Chicago has produced successful results. This study describes the application of ANN in developing the correlation between load rating and subjective rating as well as bridge parameter for highway bridges. The subjective rating in this study is limited to deck rating only. The data provided by California Department of Transportation (CALTRAN) is utilized for training and testing session. The results obtained in the first part showed that additional variables are needed along with load rating variable to provide acceptable prediction performance. After several rounds of improvement process the best result obtained exhibits 77% of the data used for testing are predicted within the acceptable range. Generally, this study showed that the ANN has a potential to be used to predict the subjective rating if the proper input variables are applied.

ABSTRAK

Pada masa kini, penilaian jambatan dilakukan sama ada melalui pemeriksaan visual atau melalui analisis struktur. Apabila penilaian jambatan dilakukan menggunakan kaedah visual, nilai subjektif diberikan kepada setiap komponen jambatan. Melalui kaedah analitikal, nilai ini dikira berdasarkan beban yang ditanggung dan keupayaan galas setiap komponen jambatan yang hendak dinilai. Kaedah pengkelasan secara visual dipengaruhi oleh pengalaman pemeriksa jambatan manakala kaedah secara analitikal pula tidak dapat menggambarkan keadaan sebenar sesuatu komponen jambatan disebabkan nilai analitikal dikira berdasarkan beban dan keupayaan komponen sahaja. Sekiranya nilai subjektif dan analitikal dapat dihubungkan, keadaan jambatan dapat dianggarkan melalui data-data analitikal sahaja. Terdapat berbagai percubaan untuk menghubungkan antara pengkelasan secara subjektif dan secara analitikal, antaranya ialah percubaan untuk menggunakan analisis statistik dan *fuzzy logic* namun begitu ianya kurang berjaya. Walaubagaimanapun, percubaan menggunakan *Artificial Neural Network (ANN)* untuk nilai analitikal dan nilai subjektif bagi jambatan laluan keretapi di Chicago memberikan keputusan yang memuaskan. Kajian ini membentangkan satu percubaan untuk menggunakan ANN bagi mendapatkan hubungan antara nilai analitikal dan nilai subjektif jambatan bagi jalanraya. Nilai subjektif dihadkan kepada geladak sahaja. Data yang digunakan diperolehi dari California Department of Transportation (CALTRAN), Amerika Syarikat. Keputusan yang diperolehi dalam bahagian pertama menunjukkan data masukan tambahan diperlukan selain dari data analitikal untuk menghasilkan ramalan yang baik. Bahagian kedua pula menunjukkan 77% dari data yang digunakan berjaya diramalkan dalam julat yang boleh diterima. Secara amnya, kajian ini menunjukkan bahawa ANN berpotensi untuk digunakan bagi meramalkan nilai subjektif jambatan sekiranya data masukan yang sesuai digunakan.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiii
	LIST OF SYMBOLS	xvii
	LIST OF APPENDICES	xviii

CHAPTER 1: INTRODUCTION

1.0	General	1
1.1	Background	2
1.2	Problem Statement	8
1.3	Objectives	8
	1.3.1 Scope of Study/Work	9
1.5	Thesis Organization	9

CHAPTER 2: LITERATURE REVIEW

d

2.0	Introduction	10
2.1	History of Bridge Rating in USA	10
2.1.1	Bridge Rating in USA	11
2.1.2	Bridge Inspection and Maintenance in Malaysia	12
2.2	Implementation of Computerization	
	Method in Bridge Assessment	15
2.3	Neural Network	17
2.3.1	Advantages of Neural Network	19
2.4	Application of Neural Network in Various Fields	20
2.4.1	Neural Network Application in Civil Engineering	21
2.5	Backpropagation Training Algorithm and	
	Generalized Delta-rule (GDR)	23
2.6	Awareness of Using Neural Network	25
2.7	Closing Remarks	26

CHAPTER 3: THEORETICAL BACKGROUND

3.0	General	27
3.1	Bridge Condition Evaluation	27
3.1.1	Bridge Subjective Rating	28
3.1.2	Analytical Rating (Load Rating)	28
3.2	The Basics of Neural Network	30
3.3	Backpropagation Network	35
3.3.1	Vanilla Backpropagation Algorithm	37
3.3.2	Generalized Delta-Rule Algorithm	40

CHAPTER 4: RESEARCH METHODOLOGY

4.0	General	43
4.1	Identification and Significance of The Research	44
4.2	Neural Network and Bridge Rating Study	45
4.3	Data Collection	45
4.4	Development of Neural Network Model	46
4.4.1	Data Analysis	46
4.4.2	Selection of Variables	47
4.4.3	Network Architecture Determination	48
4.4.4	Training	50
4.4.5	Testing	52
4.5	Improvement of Neural Network Performance	52
4.5.1	Uniform Distribution	53
4.5.2	Generalized Delta-rule Algorithm (GDR)	53
4.6	Neuroshell 2 Software	54
4.7	Summary	56

CHAPTER 5: ARTIFICIAL NEURAL NETWORK APPLICATION IN DECK CONDITIONAL RATING

5.0	General	57
5.1	Limitation and Assumption	58
5.2	Artificial Neural Network Used in the Study	58
5.3	Data	59
5.3.1	Data Characteristic	60
5.3.2	Data Preprocessing	67
5.4	Application of Neural Network in Prediction of Subjective Rating	68

5.4.1	Testing and Training Data	68
5.4.2	Data Normalization	75
5.4.3	Creating Neural Network Model	76
5.5	Results and Discussion	85

CHAPTER 6: IMPROVEMENT OF NEURAL NETWORK PERFORMANCE

6.0	General	93
6.1	Data transformation	94
6.2	Neural Network Model	100
6.3	Application of Generalized Delta-rules Algorithm (GDR)	104
6.3.1	Result	106
6.4	Discussion	110
6.5	Applicability of Neural Network Using Local Data	112
6.5.1	Data Characteristic	113
6.5.2	Data Transformation	113
6.5.3	Training and Testing Session	115
6.5.4	Discussion	122

CHAPTER 7: CONCLUSIONS AND RECOMMENDATIONS

7.1	Conclusion	123
7.2	Recommendation for future research	126

REFERENCES

128

APPENDICES

LIST OF TABLES

TABLE NO.	TITLE	PAGE
1.1	Description of rating scale used by Federal Highway Administrations (FHWA)	4
1.2	Description of rating scale for railway uses by American Railway Engineering Association (AREA)	5
5.1	Correlation coefficient between input variables and deck rating	67
5.2	Summarize for training result	87
5.3	Summarize for testing result	90
6.1	Summarize training result using uniform distribution data	102
6.2	Summarize of testing result using uniform distribution data	103
6.3	Training performance for different combination of learning rate and momentum coefficient	107
6.4	Testing performance for different combination of learning rate and momentum coefficient	107
6.5	Summarize of training result using GDR	109
6.6	Summarize of testing result using GDR	110
6.7	Fitted distributions for five input variables for local data	114
6.8	Neural network performance for different combination of learning rate and momentum coefficient for local data	120
6.9	Neural network performance for different combination of learning rate and momentum coefficient for local data	121

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Bridge condition rating after two maintenance jobs (Mohammadi, Guralnick and Yan, 1996)	5
2.1	Shematic drawing of biological neuron (Hagan and Demuth, 1998)	18
3.1	A simple neural network with one hidden layer	30
3.2	Typical processing element internal	31
3.3	Typical processing element internal function	32
3.4	Hard limit transfer function	33
3.5	Linear transfer function	33
3.6	Sigmoid transfer function	34
3.7	The ANN network mapping for single processing element	34
3.8	A multilayer perceptron with one hidden layer	36
3.9	A multilayer perceptron with one output	38
4.1	Steps in conducting the research	44
4.2	Steps in creating neural network model using Neuroshell 2	54
5.1	Distribution of Average Annual Daily Traffic data	61
5.2	Distribution of Material Type data	62
5.3	Distribution of Design Type data	63
5.4	Distribution of Road Width data	64
5.5	Distribution of Bridge Age data	64
5.6	Distribution of Inventory Rating data	65
5.7	Distribution of Operating Rating data	65
5.8	Distribution of Deck Rating data	66
5.9	Distribution of training and testing data for Average Annual Daily Traffic (AADT)	69

5.10	Distribution of training and testing data for Material Type	70
5.11	Distribution of training and testing data for Design Type	71
5.12	Distribution of training and testing data for Road Width	72
5.13	Distribution of training and testing data for Bridge Age	72
5.14	Distribution of training and testing data for Inventory Rating	73
5.15	Distribution of training and testing data for Operating Rating	74
5.16	Distribution of training and testing data for Deck Rating	74
5.17	ANN topology with 1 hidden layer for 2 input variables	76
5.18	Training and testing performance of different number of neurons using load rating data as input variables	78
5.19	Training and testing performance with different number of neurons using entire variables	80
5.20	Training and testing performance with different number of neurons using data set without Road width variable	80
5.21	Training and testing performance with different number of neuron using data set without Bridge age variable	81
5.22	Training and testing performance with different number of neuron using data set without Material Type variable	82
5.23	Training and testing performance with different number of neuron using data set without Design Type variable	83
5.24	Training and testing performance with different number of neuron using data set without AADT variable	83
5.25	Summarize of testing performance using different variables	84
5.26	ANN topology using 4 input variables	85
5.27	Training and testing performance for different number of neuron using operating rating, inventory rating, bridge age and road width as the input variables	86
5.28	Plotted actual rating value and predicted rating value for training	86
5.29	Percentage of deck rating prediction for training	88
5.30	Plotted actual rating value and predicted rating value for testing	89
5.31	Percentage of deck rating prediction for testing	91

6.1	Comparison between Inventory rating distribution and Logistic distribution	95
6.2	Comparison between Operating rating distribution and Logistic distribution	95
6.3	Comparison of Road Width data distribution and Beta distribution	96
6.4	Comparison of bridge age distribution and Logistic distribution	96
6.5	Comparison of transformed inventory rating data and uniform distribution	98
6.6	Comparison of transformed Operating rating data and uniform Distribution	98
6.7	Comparison transformed Road Width data and uniform distribution	99
6.8	Comparison transformed Bridge age data and uniform distribution	99
6.9	Training and testing performance for the different number of neuron using uniform distribution data	101
6.10	Plotted actual rating value and prediction value for training using uniform distribution data	101
6.11	Plotted actual rating values and prediction values for testing using uniform distribution	103
6.12	Plotted actual rating values and prediction values for training using GDR	108
6.13	Plotted actual rating values and prediction values for testing using GDR	108
6.14	Neural network topology	115
6.15	Training and testing performance using entire variable for local Data	116
6.16	Summarize of testing performance using different combination of input variable for local data	117
6.17	Training and testing performance using bridge age as the input variable for local data	118
6.18	Training and testing performance using maximum span and bridge age as the input using local data	119
6.19	Training and testing performance without clear width using local data	119

6.20	Plotted actual rating value and prediction rating values using local data	121
------	---	-----

LIST OF SYMBOLS

D_L	-	Dead load
L_L	-	Live load
RF	-	The rating factor for live-load carrying capacity
C	-	The capacity of the member
D	-	Dead load effect on member
L	-	Live load effect on member
I	-	The impact factor to be used with the live load effect (or the dynamic allowance)
A_1	-	Factor for dead load
A_2	-	Factor for live load
RT	-	Bridge member rating in tons
W	-	Weight (tons) of minimal truck used in determining the live load effect
I_{ik}	-	input to the k^{th} processing element from the i^{th} processing element
H	-	Hidden layer
O	-	Output
V, W	-	Connection weight
d_n	-	Desired output
C_n	-	Calculated value
E	-	Total squared error
β_c	-	Positive constant controlling the learning rate in output layer
η	-	Learning rate
α	-	Momentum coefficient
r	-	Linear correlation coefficient

LIST OF APPENDICES

APPENDIX A

Appendix A

<u>TABLE NO.</u>	<u>TITLE</u>
A-1	List of Data
A-2	Training Data
A-3	Testing Data
A-4	Normalized Training Data
A-5	Normalized Testing Data

Appendix B

<u>TABLE NO.</u>	<u>TITLE</u>
B-1	Transformed Training Data
B-2	Transformed Testing Data
B-3	Training Data (Local data)
B-4	Testing Data (Local data)
B-5	Malaysian Rating System

<u>FIGURE NO.</u>	<u>TITLE</u>
B-1:	Distribution of Number of Span for Training and Testing for Local Data
B-2:	Distribution of Total Length for Training and Testing for Local Data
B-3:	Distribution of Maximum Span for Training and Testing for Local Data
B-4:	Distribution of Clear Width for Training and Testing for Local Data
B-5:	Distribution of Bridge Age for Training and Testing for Local Data
B-6:	Distribution of Deck Rating for Training and Testing for Local Data

CHAPTER I

INTRODUCTION

1.0 General

Bridges are among the most important structures in the highway network of any nation. A bridge provides the vital link to any transportation system. Bridges constitute a unique class of structures in the sense that they undergo such dynamic loads as truck weight that changes with time. Usually the reason for the changes is due to government regulations and the demand by the public to increase the legal truck weight. Aside from the truck load, bridges are also exposed to variety of environmental conditions that may cause a rapid deterioration on their components.

Due to the variety of loading situations, environmental conditions and continuous use, bridges are vulnerable to a more severe deterioration process than most other structures. Because of their vulnerability to a rapid deterioration, most transportation agencies have stringent requirements for bridge maintenance and repair. It is only through a rigorous inspection and repair program that the service life of a bridge can be extended and its safe operation maintained. As part of an effective maintenance and repair program for bridges, condition assessment of bridges ranges from simply a structural analysis combined with visual inspection to a more severe program involving non-destructive tests. Availability of new technologies such as advanced computerized life cycle cost analysis, stress analysis and Artificial Neural Network (ANN) analysis can help reduce the effort needed in bridge condition

assessment. In particular, the ANN analysis can effectively be used to develop a scheme by which the condition of a bridge can be assessed using the information available for other bridges. More precisely, the data on past inspection records can be used in training an ANN system to predict the condition of a given bridge. Although the result from the ANN system may only be approximate, nevertheless such information may be helpful in determining what bridge or group of bridges need to be prioritized for immediate inspection and/or repair. This can reduce the cost associated with the management of a network of highway bridges.

1.1 Background

A significant issue in bridge maintenance today is the method of evaluating bridge conditions. The demand for the type of maintenance and repair depends on the outcome of the bridge condition assessment. An effective method, that has been used extensively, is based on visual inspections. Analytical methods using load rating has also been used either independently or along with a visual inspection process.

Usually, upon conducting a visual inspection, a rating value is assigned to individual components of the bridge. The rating assigned represents the bridge deterioration level normally known as bridge condition rating. Depending on the agencies responsible for the bridge, different rating schemes are used. For example, for highway bridges, most agencies use a scale of 0 to 9. A scale of 0 indicates that a bridge is in an extremely critical situation and must be immediately replaced, whereas, a scale of 9 indicates that the bridge is in good condition and thus not required any action at least until the next inspection cycle. Table 1.1 presents a complete description of the ten scales used by most federal and state agencies in USA that are responsible for maintenance of highway bridges.

Most agencies responsible for railroad bridges use different rating scheme. This type of rating is either ranging between 1 to 5 or from 1 to 4. For example, the American Railway Engineering Association (AREA) uses a scale of 1 to 5 as summarized in Table 1.2.

Most highway and railway bridges are inspected every 2 years. The rating process if conducted by experienced inspector and on a systematic basis, provides an effective way of monitoring the deterioration trend in bridge components. In highway bridges, the individual component ratings are combined to arrive at an overall rating for bridge sub-systems such as the deck, superstructure and substructure. Those ratings and its change overtime are often used in constructing the bridge condition profile (Mohammadi, Guralnick and Yan, 1996).

As seen in Figure 1.1, any repair administered on the bridge improves the condition rating. However, the improved rating is never reaching the maximum value of 9. In fact, the improved rating after each repair is less than the previous one. After certain age, any repair done to the bridge will not improve the condition by any meaningful amount. This is when the bridge must be replaced. Information such as that in Figure 1.1 is of value for estimating the condition of bridges that are similar in geometry and traffic usage to those for which inspection rating results are available.

Table 1.1: Description of rating scale used by Federal Highway Engineering Administrations (FHWA).

Rating	Condition
9	Excellent condition
8	Very good condition , no problem noted
7	Good condition , some minor problems
6	Satisfactory condition , structural elements show some minor deterioration
5	Fair condition , all primary structural elements are sound but may have section loss, cracking, spalling or scour.
4	Poor condition , advance section loss, deterioration, spalling or scour.
3	Serious condition , loss of section, deterioration, spalling, scour have seriously affected primary structural members, local failures are possible; fatigue cracks in steel or shear cracks in concrete may be presented.
2	Critical condition , advance deterioration of primary structural members, fatigue cracks in steel or shear cracks in concrete may be presented or scour may have removed substructure support. Unless closely monitored, it may be necessary to close the bridge until corrective actions is taken.
1	Imminent failure condition , major deterioration or section loss present very critical structural components or affecting structural stability. Bridge is closed to traffic but corrective measures may put the bridge back in light service.
0	Failed condition , out of service, beyond corrective action.

Table 1.2: Description of rating scale for railway uses by American Railway Engineering Association (AREA)

Rating	Condition
5	Good condition , no visible defects, no repairs necessary
4	Fair condition , slightly defective or deteriorated member, no repair necessary, keep under observation.
3	Marginal condition , moderate defective or deteriorated member that will progress to a serious defect, repair or rehabilitate within 3 years.
2	Poor condition , heavily defective or deteriorate that will progress quickly to a severe and serious condition, repair or rehabilitate within 1 year
1	Critical condition , extensive and dangerous defects in need of immediate repair.




Figure 1.1. Bridge condition rating after two maintenance jobs (Mohammadi, Guralnick and Yan, 1996)

A different rating method used for bridges is the analytical rating. For highway bridges this method is known as Load rating. In this method, the analytical rating is primarily based on the results of a structural analysis. The rating can be done for any member and any type of load effect (such as the bending moment, shear force, etc.). In essence, the rating can be written in the following general form (ASSHTO, 1994):

$$Rating = \frac{Capacity - D_L}{L_L \times impact} \quad (1.1)$$

Where:

D_L = Dead load

L_L = Live load

Different versions of Equation 1.1 have been used by various organizations. The American Association of State Highway and Transportation Officials (ASSHTO) describes the rating process based on Equation 1.1 for various bridge components and for two levels of component capacities. These are: (1) the operating rating, and (2) the inventory rating (ASSHTO, 1994). The difference between the two ratings is in the capacity values used in Equation 1.1.

The American Railway Engineering Association (AREA) uses a slightly different version of Equation 1.1. The AREA uses a multiplier in the equation also (AREA, 1997). The AREA rating method is referred to as the Cooper rating.

Analytical rating methods have been intended as means to determine the safety level of bridges through calculations. For example, the Cooper Rating method (outlined in the American Railway Engineering Association specifications) is used in railroad bridges to determine the value that represents the condition of railroad bridge and its deficiency in carrying the bending moment and shear forces. Analytical rating method considers dead load, live load and impact load to produce the rating value for a bridge without directly considering the effect of component deterioration that may occur overtime. The calculated rating is unable to represent the actual condition of the

bridge components, but it still can be used as a preliminary assessment tool especially in prioritizing bridges for further evaluations. The analytical rating on the other hand is less uncertain but it is unable to provide a reliable measure for a bridge actual condition.

As discussed earlier, subjective rating is conducted by assigning the rating value to individual bridge components. The rating assigned depends on the defects present. This method is conducted in the field by bridge inspectors and will be primarily influenced by the inspector's individual experience. This will cause inconsistencies on the bridge rating values. This occurrence is due to the fact that only experienced inspectors are able to assign proper evaluation compared to an inexperienced inspector. This is to say that inspection results based on visual inspections are subject to uncertainties. The subjective rating method also requires inspection to every bridge, this is time and labor consuming.

However, it is obvious that subjective and analytical ratings both are needed in bridge condition assessment. One effective method to use the available rating results in estimating the condition of a bridge is through statistical analysis of data. Such analysis may include simple correlation analysis or more advanced techniques such as fuzzy logic and ANN methods.

There has been a growing interest in neural network computing technique in civil engineering in recent years for its capabilities in learning and generalizing from given examples, to produce a meaningful solution to problems even when input data contain errors and may be incomplete (Flood et al, 1994). The method can adapt solution overtime to compensate for changing situation (Shi, 2000).

Neural network will be the method of choice in this research to establish the relation between the bridge condition and subjective rating. An attempt to correlate the rating (in railway bridges) using conventional least square analysis and fuzzy logic resulted no specific relation between these two bridge assessment methods (Chen, 1991). Cattani and Mohammadi (1997) established the relationship between bridge parameters and Cooper rating with subjective rating for railroad bridge through a series of logical steps in neural network. The research results show that neural

network has the capability in establishing the unknown relationships between a set of input and output values.

1.2 Problem Statement

Conventional methods in assessing the bridge condition are time and labor consuming. Both methods also have their own weakness in assessing the bridge condition. Attempts to utilize conventional least-squares analysis and fuzzy logic to establish relation between condition assessment and bridge parameter resulted unsuccessful to provide a solution for the problem mentioned. The technique based on an artificial neural network (ANN) is utilized to predict the subjective rating using analytical rating and bridge parameter data as the input data. If the ANN is successful to predict the subjective rating, then fewer inspections are needed because an overall estimate of a bridge condition can readily be made just through analytical determination. This can provide cost-effective method for screening those bridges, which are critical and need to be prioritized for inspection. Furthermore, when the rating can be predicted using ANN, approximation of maintenance cost also can be done.

1.3 Objectives

The objectives of this research are

- a) To predict the bridge deck condition rating using ANN
- b) To evaluate the ANN performance in the assessment of bridge condition
- c) To proposed improvement in ANN modelling for bridge condition assessment

1.3.1 Scope of work/study

The study consist of two parts:

- a) Designing the best ANN topology to predict the deck condition rating. ANN using Vanilla Backpropagation Algorithm will be utilized to train the network. The process also will involve the trial and error process to find out the suitable combination of input variables available in the data set to predict the deck condition rating. The data is obtained from California Department of Transportation (CALTRAN).
- b) Two methods applied to improve the ANN prediction performance. Uniform distribution method will be applied to improve the distribution of the original data. Generalized delta rule algorithm will be used to speed up the training process to enhance the ANN performance. An attempt to apply the local data provided by Public Work Department of Johor will be conducted.

1.4 Thesis Organization

The thesis contains a total of 7 chapters and 2 appendices. In Chapter 2 a brief discussion of existing research and publications on artificial neural network in civil engineering is presented. In this chapter, the literature on bridge assessment is also discussed. Chapter 3 includes a discussion of the overview and review of the methodology used in application of artificial neural networks and bridge condition rating as recommended by transportation agencies. Chapter 4 explains the basic theoretical background for bridge assessment and neural network.

In Chapter 5, backpropagation artificial neural network is used to achieve the objective of the thesis work. In Chapter 6 attempts to improve the neural network performance are applied. The conclusions of the study and recommendations for future development are given in Chapter 7.

REFERENCES

- and Welkowitz, W. (1992). "Neural Networks for the Diagnosis of Artery Disease." Proceedings of the International Joint Conference Neural Maryland.
- A.M. and Qudrah, A. (1998). "Artificial Neural Network Approach for Maintenance." Journal of Computing in Civil Engineering, Vol. 12, No. 4, 5.
- Association of State Highway and Transportation Officials (AASHTO), "Manual for Condition Evaluation of Bridges, Second Edition." Washington
- Railway and Engineering Association (AREA) (1997). "Manual for Engineering." Washington.
- W.W., Stein, R. B., Kostov, A., Thomas, M., Baudin, P., Gervais and P., D. (1993). "Application of Adaptive Logic Networks and Dynamics to and Control of Human Movement." Second Int'l Symp. on 3D Analysis of Movement, Poitiers, pp. 81 - 84.
- N., and Doi, K. (1990). "Potential Usefulness of an Artificial Neural Network Differential Diagnosis of Interstitial Lung Disease: Pilot Study." *Radiology*, Vol. pg. 857.
- A.A. and Aziz A.A. (1995). "Structural Integrity Assessment of A Concrete Bridge." 4th International Conference on Inspection, Appraisal, and Maintenance of Buildings and Structures Hong Kong

). "Analyzing Financial Health: Integrating Neural Networks and
" Neural Networks in Finance and Investing, Probus Publishing: 85-

Silvert, W., Krost, P. and Angel, D.L. (1998). "Assessing Benthic
Fish Farming with An Expert System Based on Neural Networks." Bull.
Society on Theoretical Biology (in press)

P.R., (1994). " Data Reduction And Error Analysis For Physical
" McGraw Hill Inc New York

P. (1990). " An Introduction of Neural Nets " Chemical Engineering
American Institute of Chemical Engineers, New York

R. and Drosen, J. (1994). "Neural Network Computing " McGraw Hill Inc
York.

M. and McAvory, T.J. (1990) "Use of neural nets for dynamic modeling and
of chemical process systems." Computers and Chemical Engineering, Vol 15,
5, pg. 573.

S., (1996). " Neural Networks for Forecasting Construction Duration of Pre-
Buildings." Third National Convention on Civil Engineering, Engineering
of Thailand, Proc.: CMT 4-1 - CMT 4-9.

C.M., (1995). " Neural Networks for Pattern Recognition " Clarendon Press,

, J. G. and Cunningham, P. (1996). "Neural Networks and Currency Exchange
Prediction." Foresight Business Journal, Art. No. 5

R.J. and Rupert, D. (1988). "Transformation and Weighting in Regression."
and Hall.

-). "Bridge Rating and Condition Assessment Using Neural Networks." Illinois Institute of Technology, Illinois.
- Mohammadi, J. (1997). "Analysis of Bridge Rating Data Using Neural Network." *Journal of Microcomputer in Civil Engineering*: Vol. 12, pp.419-429.
- M., (1990). "Experts Network: Neural Network PC Tools: A Practical Approach." McGraw-Hill Press, San Diego.
- (1991). "An Integrated Computer System for Commuter Railroad Bridge Evaluation and Rating." MS thesis, Department of Civil Engineering, Illinois Institute of Technology, Chicago, Illinois.
- H. and Beale M. (1996). "Neural Network Toolbox for Use with MATLAB." MathWorks Inc., Massachusetts.
- , A.M., Nosair, I.A., Mohieldin, Y.A., and Mohamed, A G (1997). "Estimating Resource Requirements at Conceptual Design Stage Using Neural Networks." *Journal of Computing in Civil Engineering ASCE*, Proc Paper 11485, 11, 17-223.
- y M.F. and Chang K C. (1994). "Neural Networks Trained by Analytically Determined Damage States." *Journal of Computing in Civil Engineering* Vol. 7, No. 2, 130-144.
- I., Kartam, N.A., Tongthong, T (1994). "The Application of Artificial Neural Networks to Civil Engineering." *Proc. of the ASCE First Congress on Computing in Civil Engineering*, Washington, DC, pp 668-675, June 1994.
- Department of Malaysia (1995). "Annual Bridge Inspection Manual." Unit 1, Jabatan Kerja Raya Malaysia, Kuala Lumpur.
- M.T., Demuth B.H. and Beale M. (1998). "Neural Network Design." PWS Publishing Company, Boston.

- Johnson, J.D., and Raina, D. (1993). "Artificial Neural Systems; A Decision-making." Neural Networks in Finance and Publishing: 27-46.
-). "Neural Networks: A Comprehensive Foundation" Macmillan,
- J.C. and Himmelblau, D.M. (1991). "Fault Diagnosis in Complex Chemical Artificial Neural Networks " American Institute of Chemical Journal, Vol. 37, pp. 137-141.
- and Mao, J.C, and Mohiuddin, K.M. (1996). "Artificial Neural Networks ", Computer, 29, 3: 31-44.
- M. (1995). "Why the Logistic Function? A Tutorial Discussion on and Neural Networks." Computational Cognitive Science Technical 9503, MIT, USA.
- K., and Pallas J (1993). "Roles, Benefits and Objectives of Neural in Building Construction Project Practice " Neural Networks and Optimization in Civil and Structural Engineering, Civil-Comp Press
- H.N.D. (1992) "Neural Network Structure Generation for the on of Remotely Sensed Data Using Simulated Annealing " M Eng Thesis, Institute of Technology, Bangkok.
- , J. (1993). "Predicting and Controlling Chaotic and Chemical Reactions With Network Models " Proceedings of the World Congress on Neural Networks, OR, 11-15 July 1993, Vol. 1, pg. 470.
- W.W. (1992). "Concept Generalization with Neural Network " M Eng Asian Institute of Technology, Bangkok.

- Muhammadi, J. (2001). "Fundamental of Systems Engineering with Probability and Statistics." Prentice Hall, Upper Saddle River, New Jersey.
- ..., T.M., and Lanning, D.L. (1995). "A Neural Network Approach for Analysis of Program Modules Having High Risk in the Maintenance Phase." *Systems Software*, 9, 1: 85-91.
- ..., S. (1995). "Neural Networks Technology." Engineering Institute of Thailand, Proc. EE371-EE384.
- ..., C.C. (1993). "Applying Neural Networks." *Neural Networks in Finance and Investing*, Probus Publishing, 47-72.
- ..., (1987). "Bridge Analysis and Rating with Microcomputers". *Journal of Civil Engineering*, Vol 113, 4: 21634.
- ..., M., Miyamoto, A and Kinoshita, K. (1997). "Development of Bridge rating Expert System with Machine Learning." *Journal of Computing in Civil Engineering*, Vol 11, A: 1205.
- ..., R.P. (1987). "An Introduction to Computing with Neural Nets." *IEE Magazine*, April 1987 p 4-22.
- ..., L., Turban, E., and Trippi, R.R. (1993). "Neural Network Fundamentals for Financial Analysis." *Neural Networks in Finance and Investing*, Probus Publishing, 3-12.
- ..., L. (1993). "Preprocessing Data for Neural Network." *Technical Analysis of Stocks & Commodities Magazine*, California.
- ..., J. Guralnick, S.A. and Yan, L. (1996). "Incorporating Life-Cycle Costs into Bridge Planning and Design." *Journal of Transportation Engineering*, No. 5.

- 1990). "A Practical Guide to Neural Nets." Addison-Wesley, Massachusetts.
- ...n (1993). "Palisade Decision Tool User Guide Version 2.0d."
- ..., Camp, C.V., and Karprapu, S. (1996). "Geophysical Log Interpretation Network." Journal of Computing in Civil Engineering ASCE, Proc. 9984, 10, 2: 136-142.
- D.E., (1986). "Parallel Distributed Processing." A Bradford Book,
- D.R. (1984). "Comparison of Bridge Rating Methods." Journal of structural Eng., Vol. 110 pp.1447-1465.
- and Ortiago, J. (1998). "Modular Neural Networks for Predicting Settlements Tunnelling." Journal of Geotechnical and Geoenvironment Engineering 124, No. 5.
- J. (2000). "Reducing Prediction Error by Transforming Input Data for Neural " Journal of Computing in Civil Engineering, Vol 14, No. 2.
- W. and Baptist, M. (2000). "Can Neural Networks be used in Data-Poor ons?" Proc. of Int. Workshop on Applications of Artificial Neural Networks to cal Modelling, Toulouse.
- n, P.K. (1990). "Artificial Neural Systems." Pergamon Press, New York.
- D.M. (1996). "Building Neural Networks." Addison-Wesley Publication New York.
- M. (1993). "Neural Networks for Statistical Modeling." Van Nostrand, New York.

- C.L., Quah, T.S. and Teh H.H. (1996). "An Artificial Neural Network that Imitates Human Decision Making." *Computer*, 29, 3: 64-70.
- Intelligent Systems Group (1996). "Neuroshell 2 User Guide, Release 2" Maryland, USA
- William, T.P. (1994). "Prediction Changes In Construction Cost Indexes Using Artificial Neural Network." *Journal of Construction Engineering and Management*: Vol. 120, No. 3, 306-319.
- Wu, X. and Lim, S.Y. (1993). "Prediction of Maximum Scour Depth at Spur Dikes Using Adaptive Neural Networks." *Neural Networks and Combinatorial Optimization in Civil and Structural Engineering*, Civil-Comp Press: 61-66.
- Yeh, I.C. (1999). "Design of high-performance Concrete Mixture Using Neural Networks and Nonlinear Programming." *Journal of Computing in Civil Engineering*: Vol. 13, No. 1.