# IDENTIFICATION OF DIFFERENT FREQUENCY SOUND RESPONSE FROM EEG SIGNAL

ALICE KOH CHEE

A project report submitted in partial fulfillment of the requirements for the award of the degree of Master of Engineering (Electrical – Computer and Microelectronics System)

> Faculty of Electrical Engineering Universiti Teknologi Malaysia

> > November 2009

## ABSTRACT

In recent years, a lot of research has been carried out to study on human brain response when listening to different kinds of music, as well as different quality of sound waves. High frequency component and low frequency component, either audible or inaudible, contained in a sound wave is proven to as a cognitive factor to human acoustic system and can be shown through human brain signal. Electroencephalographic (EEG) technology has enabled effective measurement of human brain activity, as functional and physiological changes within the brain may be registered by EEG signals. In this project, electrical activity of human brain due to sound waves of different frequency is studied based on EEG signals. Collection of EEG signals from 5 healthy adults is done using Neurofax EEG-9100 device. Subjects are exposed to different frequency sound waves of 40 Hz, 500 Hz, 5000 Hz and 15000 Hz. The EEG signals are then processed using signal processing algorithms in Matlab, i.e. Principle Component Analysis, Discrete Wavelet Transform, Fast Fourier Transform etc. Useful information is extracted from the processing of EEG signal, and algorithm to identify the different frequency sound response from the EEG signals is developed using artificial intelligent techniques, i.e. neural network, fuzzy logic, and adaptive neuro-fuzzy system. The result from this project has shown that the characteristics of EEG signals differ with respect to different frequency of sound waves, and yet different frequency sound response from EEG signal can be identified by using suitable A.I. algorithms.

## ABSTRAK

Kajian terhadap tindakbalas otak manusia ketika mendengar muzik dan bunyi yang berlainan jenis dan kualiti telah banyak dijalankan sejak tahun kebelakangan ini. Komponen frekuensi tinggi dan rendah yang terkandung gelombang bunyi, sama ada di dalam had pendengaran manusia, ataupun di luar had pendengaran manusia telah terbukti sebagai satu faktor kognitif terhadap sistem pendengaran manuasia. Fakta ini tertunjuk melalui isyarat otak manusia. Aktiviti otak manusia boleh diukur secara berkesan dengan teknologi Electroencephalograhic (EEG). EEG boleh mengesan perubahan fisiologi dan fungsi yang terkesan di dalam otak manusia. Dalam projek ini, kajian terhadap aktiviti elektrik di dalam otak manusia terhadap bunyi yang berlainan frekuensi dijalankan berdasarkan isyarat EEG. Isyarat EEG daripada 5 subjek yang sihat direkod dengan menggunakan mesin Neurofax EEG-9100. Subjek dikehendaki mendengar gelombang bunyi dengan frekuensi 40 Hz, 500 Hz, 5000 Hz and 15000 Hz semasa experimen dijalankan. Pemprosesan isyarat EEG dijalankan dengan menggunakan modul pemprosesan isyarat yang terkandung dalam perisian Matlab, seperti 'Principle Component Analysis', 'Discrete Wavelet Transform', 'Fast Fourier Transform' dan sebagainya. Infomasi yang penting boleh diekstrak melalui pemprosesan isyarat EEG. Seterusnya, perisian untuk frekuensi pengesahan daripada isyarat EEG direka dengan menggunakan teknik kecerdikan buatan, seperti rangkaian neural, "fuzzy logic" dan sistem penyesuaian neuro-fuzzy. Keputusan daripada projek ini menunjukkan isyarat EEG mempunyai ciri-ciri yang berbeza terhadap bunyi dengan frekuensi yang berlainan. Akan tetapi, frekuensi pengesahan daripada isyarat EEG secara berkesan dapat dijalankan dengan menggunakan teknik kecerdikan buatan yang sesuai.

# **TABLE OF CONTENTS**

CHAPTER	TITLE			I	PAGE		
	DEC	DECLARATION					ii
	DED	ICATIC	N				iii
	ACK	NOWL	EDGEMENT				iv
	ABS	ГRACT					v
	ABS	ГRAK					vi
	TAB	LE OF (	CONTENTS				vii
	LIST	OF TA	BLES				X
	LIST	OF FIG	GURES				xi
	LIST	OF AB	BREVIATIO	NS			xiv
	LIST	OF AP	PENDICES				XV
1	INTI	RODUC	ΓΙΟΝ				1
	1.1	Projec	t Background				1
	1.2	Proble	m Statement				2
	1.3	Object	ives				2
	1.4	Scope	s of Study				3
	1.5	Organ	zation of the R	Report			4
2	LITE	ERATUI	RE REVIEW				6
	2.1	EEG F	Research on Hu	man Audi	tory/Acous	tic	
		Percep	tion				7
	2.2	EEG S	ignal Processi	ng			9
		2.2.1	Artifact Filt	tering us	ing Empi	rical mode	
			decomposition	n (EMD)			10
		2.2.2	Artifact filt	ering by	using	Independent	
			Component A	analysis (IC	CA)		12

	2.2.3 Filtering by Optimal Project (FOP) for Artifacts			
	Removal	13		
	2.2.4 Processing EEG Signal using Wavelet			
	Transform	14		
2.3	EEG Signal Classification Using Artificial Intelligent			
	Techniques	15		
	2.3.1 Artificial Neural Network for EEG Signal			
	Classification	15		
	2.3.2 Fuzzy Logic for EEG Signal Classification	18		
МЕТ	THODOLOGY	20		
3.1	Project Planning	20		
3.2	Methods for Project Design and Implementation			
3.3	Hardware Involved in the Project			
3.4	Software involved in the project	24		
EEG	DATA COLLECTION	25		
4.1	Experiment Setup	25		
	4.1.1 EEG Machine and Environment Setup	25		
	4.1.2 Collection of Monotone Sound Waves	27		
	4.1.3 Preparing the Subjects for EEG Signals			
	Recording.	27		
4.2	EEG Data Recording	28		
4.3	Selection of EEG Data	28		
EEG	SIGNAL PROCESSING	29		
5.1	EEG Signal Filtering	29		
5.2	EEG Feature Extraction Using Discrete Wavelet			
	Transform (DWT)	32		
5.3	EEG Feature Extraction Using Fast Fourier Transform			
	(FFT)			
	5.3.1 Smoothing of FFT Signal	38		
5.4	Preliminary Analysis of the EEG Signals	39		

6	EEG S	SIGNAL CLASSIFICATION	42		
	6.1	Artificial Neural Network (ANN) System as Classifier			
		6.1.1 Concept of ANN	43		
		6.1.2 Designing an ANN for EEG Signal			
		Classification	43		
	6.2	Fuzzy System as Classifier	48		
		6.2.1 Concept of Fuzzy Logic	49		
		6.2.2 Designing a Fuzzy System for EEG Signal			
		Classification	50		
	6.3	Adaptive Neuro-Fuzzy Inference System (ANFIS) as			
		Classifier	53		
		6.3.1 Concept of ANFIS	53		
		6.3.2 Designing a ANFIS for EEG Signals			
		Classification	54		
	6.4	Graphical User Interface of the EEG Classifier	58		
7	<b>RESULT AND DISCUSSION</b>				
	7.1	Performance of the A.I. Classifiers	61		
		7.1.1 Performance of ANN for EEG Signal			
		Classification	62		
		7.1.2 Performance of Fuzzy System for EEG Signal			
		Classification	63		
		7.1.3 Performance of ANFIS for EEG Signal			
		Classification	64		
	7.2	Performance Comparison for Different Type of			
		Classifiers	65		
8	CONCLUSION AND RECOMMENDATION				
	8.1	Conclusion	67		
	8.2	Recommendation for Future Work	68		
DEEDENO			70		
Annerdises A	ED C	70	70		
Appendices A	- U	12	19		

# LIST OF TABLES

TABLE NO.	TITLE	PAGE
3.1	Project 1 Gantt Chart	21
3.2	Project 2 Gantt Chart	21
5.1	Parameters for "wmspca" analysis	31
5.2	Decomposed frequency components for different DWT sub- bands	34
6.1	Architecture of the ANN for EEG signal classification	45
6.2	Inputs of the fuzzy system	50
6.3	Statistic of the ANFIS simulation outputs with respect to the target outputs (for 102 sets of training data)	58
7.1	Distribution of the test data	61
7.2	Output of ANN mapped to target frequency	62
7.3	Statistic of the ANFIS simulation outputs with respect to the target outputs (for 30 sets of test data)	65

# LIST OF FIGURES

FIGURE NO	. TITLE	PAGE
2.1	Clean EEG signal and Artifact signals	10
2.2	The second IMF and Fourier spectrum, filtered IMF and	
	Fourier spectrum.	12
2.3	An example of Neural Network with one hidden layer	17
2.4	The spatial combiner in relation to EV detection	19
3.1	Work breakdown chart for the project	22
3.2	Design and implementation procedure for EEG signals	
	classification	23
3.3	EEG machine in Medical Electronic Laboratory (a) laptop	
	with Neurofax EEG-9000 software, (b) EEG Electro-Cap	
	Electrode System I, (c) EEG Acquisition Set.	24
4.1	International 10/20 placement on the electro-cap	26
4.2	Electro-cap placed on a subject's scalp	28
5.1	Raw EEG signal collected from EEG machine	30
5.2	Concept of retained information after "wmspca" analysis	31
5.3	Original EEG (left) at different channels comparing to the	
	simplified EEG signal (right) using multiscale PCA.	32

5.5	Several levels of filter bank for multi-level DWT	
	decomposition	34
5.6	Detail and approximation coefficient of sub-band 3-6 of the EEG signal	35
5.7	Power spectrum of the EEG signals at channel T3, T4, T5, T6	36
5.8	Power spectrum of the EEG signals at channel T3, T4, T5, T6 (in logarithm of base 10)	37
5.9	Overall power spectrum of the EEG signals (average of power spectrum from channel T3, T4, T5, T6)	38
5.11	Power spectrum of the EEG signal (subject 1) with respect to 40 Hz, 500 Hz, 5000 Hz, and 15000 Hz	40
5.12	Power spectrum of the EEG signals with respect to 40 Hz, 500 Hz, and 5000 Hz for subject 1 and 2	41
6.1	Structure of an ANN akin to the vast network of neuron in human brain	43
6.2	Structure of the designed ANN for EEG signal classification	44
6.3	ANN performance plot from Matlab Neural Network Toolbox	47
6.4	Regression plot from Matlab Neural Network Toolbox	47
6.5	Operation of a fuzzy system	49
6.6	Fuzzy sets of the inputs (a) mean, (b) fftmean, (c) fftmax	51
6.7	Fuzzy sets of the output	51
6.8	Defuzzification process using MOM method	52
6.9	ANFIS GUI from Matlab	55
6.10	FIS Structure generated from ANFIS	56

6.11	Training error vs. number of epoch during ANFIS training	56
6.12	Desired output versus training output from the ANFIS	57
6.13	GUI combining 3 types of classifiers designed (ANN, fuzzy system and ANFIS classifier)	59
7.1	Defuzzication process for a wrongly identified EEG signal	63
7.2	Desired output vs. ANFIS output for 30 sets of test data	64
7.3	Performance comparisons of 3 types of A.I. classifiers	65

# **CHAPTER 1**

# INTRODUCTION

# 1.1 Project Background

Hearing is one of the human five senses. The sense of hearing is performed by human auditory system: vibrations are detected by the ears and transduced into nerve impulses that are perceived by brain, primarily in the temporal lobe of human brain. Ideally, a healthy human can hear sounds within the range of 20 Hz - 20 kHz. Hearing different quality of sound, i.e. loud or soft, high pitch or low pitch, audible or inaudible etc., will have different effects to our brain. The ability to differentiate the quality of a specific sound is due to human brain response to different qualities of sound. The human brain do produces different electrical activity due to the different frequency of sound waves.

One of the common methods to measure human brain activity is by using Electroencephalography (EEG) technology. Electroencephalography (EEG) is an electrical waveform that is recorded from the brain by using electrodes appropriately placed on the head/scalp. To visualize this EEG signal, this signal is amplified and displayed through a computer or other suitable instrument. EEG signal consists of a wave that varies in time, much like a sound signal, or a vibration. As such, it contains a great deal of information that can be used to characterize the EEG signals for clinical and research purposes.

The useful information contained in the raw EEG signal cannot be visualized with just bare eyes. On top of that, raw EEG signals usually contain artifacts that will complicate the analysis of EEG signal. There have been a lot of research work on EEG signal processing, as well as classification of EEG signal. All these methodologies from previous work provide good references for future research and exploration on EEG technology.

#### **1.2 Problem Statement**

When listening to sound waves or tones of different frequencies, ranges from 20 - 20 kHz (human hearing range), our brain will react differently and produce EEG signals with different qualities/characteristics. Based on this understanding, ideally we can reverse the process, where if a series of EEG signals are given (the EEG signal is recorded when a subject is listening to sound wave of different frequency), we should be able to identify the frequency of the sound wave.

However, EEG data captured over the scalp usually contain artifacts or noise. These artifacts or noise maybe caused by the instrument or biological response, e.g. eyes movement, certain concentration or distraction etc. In order to analyze and classify the EEG signal correctly, the EEG signals need to be processed, and the artifacts to be filtered. Characteristics of the signals are to be extracted, and classification will be done based on these characteristics or qualities of the EEG signals. The characteristics of these EEG signals may have slight differences as each one of us is a unique entity. Therefore, there is a need for a proper algorithm to identify the different frequency sound response from EEG signal.

#### 1.3 Objectives

The main objective of this project is to develop an algorithm to identify different frequency sound response from EEG signal. Generally, the electrical activity of human brain due to sound waves of different frequency is to be studied based on the EEG signals. Later on, with the understanding on the EEG signals, research on signal processing and artificial intelligent algorithm is to be carried out to identify the suitable signal processing and classification methods for EEG signals. Lastly, an algorithm for classification of EEG signals with respect to different frequency sound response using artificial intelligent techniques is to be developed.

## 1.4 Scopes of Study

This project involves a series of research work on EEG signal processing and artificial intelligent algorithms in order to develop a software that is capable of performing EEG signal processing for identification of different frequency sound response. Basically, the scope of study can be categorized as below:

- EEG data collection using EEG machine in Medical Electronic Laboratory in Uninversiti Teknologi Malaysia. Subjects are to be identified to perform the testing, i.e. listening to sound waves of different frequencies (i.e. 40 Hz, 500 Hz, 5000 Hz and 15000 Hz) and EEG data are collected from 4 locations at temporal lobe (T3, T4, T5, T6) using a single electro-cap connected to the electrode board adapter.
- EEG signal processing. Raw EEG signal is to be filtered for noise and artifact removal. EEG signal in time-domain is to be transformed into frequency domain using suitable signal processing techniques. With proper signal processing, important information can be extracted from the EEG signals, and to be used in the next step.
- 3. Characterization of EEG signals. The EEG spectrum is observed to fall into different frequency bands, i.e. Delta (< 4 Hz), Theta (4-8 Hz), Alpha (8-13 Hz), Beta (13-30 Hz) and Gamma band (> 30 Hz). With the different characteristic observed from the signal, EEG signals can be classified effectively.

4. Artificial intelligent (A.I.) techniques. Proper classification using A.I. techniques are used to achieve the objective of the study, i.e. to identify different frequency sound response from EEG signal. A.I. technique is simpler and easier to apply for signal with a lot of non-linear components, as compared to conventional modeling approaches.

## **1.5** Organization of the Report

This report consists of eight chapters with the brief description of each chapter as stated below:

Chapter 1 presents the introduction to this project, includes the background of the project, problem statements, objectives of the project and scopes of the study.

Chapter 2 provides literature reviews from previous research work from other researches on EEG signals on human acoustic system, EEG signal processing techniques, and some well-known A.I. technique for EEG related research.

Chapter 3 discusses about the methodology applied in this project, including the project planning and schedule, design and implementation workflow, hardware and software involved in this project.

Chapter 4 describes the procedure of EEG data collection. This chapter discuss about the experiment setup and EEG data recording procedure in this project.

Chapter 5 describes the methodology used for EEG data processing, starting from EEG noise removal, followed by feature extraction from EEG signals, and lastly some preliminary analysis on the EEG signals. Chapter 6 describes the implementation of EEG identification algorithm using A.I. techniques like artificial neural network, fuzzy system and adaptive neurofuzzy inference system.

Chapter 7 discusses the result from the identification algorithm using various A.I. techniques. The performance of each algorithm is compared against each other.

Chapter 8 concludes the overall work done in this project. Shortcoming of the system designed in this project is discussed, and recommendation for future work is discussed as well.

#### REFERENCES

- Boudet, S., Peyrodie, L., Gallois, P. and Vasseur, C. (2007). Filtering by Optimal Projection and application to automatic artifact removal from EEG. *Signal Processing*. 87(8), 1978-1992.
- Delorme, A., Sejnowski, T. and Makeig, S. (2007). Enhanced detection of artifacts in EEG data using higher-order statistics and independent component analysis. *NeuroImage*. 34, 1443 – 1449.
- Jahankhani, P., Kodogiannis, P. and Revett, K. (2006). EEG Signal Classification Using Wavelet Feature Extraction and Neural Networks. Proceedings of IEEE John Vincent Atanasoff 2006 International Symposium on Modern Computing (JVA'06). 3-6 October. Sofia, Bulgaria: IEEE, 120-124.
- James, C. J., Jones, R. D., Bones, P. J. and Carroll, G. J. (1998). Spatial Analysis of Multi-channel EEG Recordings through a Fuzzy Rule Based System in the Detection of Epileptiform Events. *Preceeding of the 20th Annual International Conference of the IEEE Engineering in Medicine and Biology Society.* 29 Oct-1 Nov. Hong Kong, China: IEEE, 2715-2718.
- Huisheng Lu, Mingshi Wang and Hongqiang Yu (2005). EEG Model and Location in Brain when Enjoying Music. Proceedings of the 2005 IEEE in Engineering in Medicine and Biology 27th Annual Conference. 1-4 September. Shanghai, China: IEEE, 191-195.
- Li, Y. and Zhang, S. (1996). Apply Wavelet Transform to Analyze EEG Signal. Proceeding of the 18th Annual International Conference of the IEEE Engineering in Medicine and Biology Society. 31 Oct-3 Nov. Amsterdam: IEEE, 1007-1008.

- Lin, W., Chiu, H. and Hsu, C. (2005). Discovering EEG signals response to musical signal stimuli by time-frequency analysis and Independent Component Analysis. Proceedings of the 2005 IEEE on Engineering in Medicine and Biology 27<sup>th</sup> Annual Conference. 1-4 September. Shanghai, China: IEEE, 2765 – 2768.
- Maan M. Shaker (2006). EEG Waves Classifier using Wavelet Transform and Fourier Transform. International Journal of Biological, Biomedical and Medical Sciences. 1(2), 85-90.
- Sanei, S. and Chambers, J.A. (2007). *EEG Signal Processing*. (1st ed.) West Sussex, England: John Wiley & Sons Ltd.
- Subasia, A. and Ercelebi, E. (2005). Classification of EEG Signals using Neural Network and Logistic Regression. *Computer Methods and Programs in Biomedicine*. 78,87-99. Elsevier.
- Ungureanu, M., Bigan, C., Strungaru, R. and Lararescu, V. (2004). Independent Component Analysis Applied in Biomedical Signal Processing. *Measurement Science Review*. 4(2), 1 – 4.
- Yagi, R., Nishina, E., Honda, M., and Oshashi, T. (2003). Modulatory Effect of Inaudible High-frequency Sounds on Human Acoustic Perception. *Neuroscience Letters*. 351, 191 – 195. Elsevier.
- Zhang De-xiang, Wu Xiao-pei and Guo Xiao-jing (2008). The EEG Signal Preprocessing Based on Empirical Mode Decomposition. Proceedings of the 2<sup>nd</sup> Conference of Bioinformatics and Biomedical Engineering. 16 – 18 May. Shanghai, China: ICBBE, 2131 – 2134.