

NONLINEAR SEISMIC PERFORMANCE OF INTEGRAL PRESTRESSED
CONCRETE BOXGIRDER BRIDGE IN MALAYSIA

MELDI

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Civil Engineering)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

JANUARY 2011

*I dedicate with love and gratitude
to my father, mother, brothers and sister,
for being with me till the very end of my thesis completion.*

ACKNOWLEDGEMENTS

In the name of Allah, the Most Gracious, the Most Merciful. I am praised to Allah, Lord of the universe for making me able to undertake this research work.

I would like to express my sincere appreciation to my supervisor Prof. Dr. Azlan bin Adnan, and Dato' Prof. Ir. Dr. Ismail Mohamed Taib for their encouragement, invaluable suggestions, earnest guidance, and motivation.

Special thanks to all SEER members and my dear friends; Ir. Dr. Hendriyawan, Patrick, Reni, Reza, Suryana, Sophia, Suhana, Ahmed Budiea, Kikin, Suzana and Uncle Galingan for their help and support and also being my family and friends during my study years.

I am deeply indebted to my father, mother, brothers, sisters, my uncle, Dr. Dasrilisyah Syahril and Khadijah C. Alih for providing me the peace of mind to pursue knowledge and at the same time being close at hand to render love, comfort and support to achieve and succeed.

Finally, I want to gratefully acknowledge the technical staffs, especially Mr. Amtral, Mr. Azam and Mr Zul from the Faculty of Civil Engineering for their support throughout my experimental work.

ABSTRACT

Currently integral and continuous concrete box-girder bridges are becoming popular system in Malaysia. The problem occurs in such system is the rigidity connection of column and deck will lead to potential hinge failure. In this research, nonlinear seismic performance for this type of bridge was studied by applying soil – pile interaction and fixed base support system. The study covers numerical and experimental approach. The numerical approach has four steps as follows: (1) investigating material properties of integral prestressed concrete box-girder bridge; (2) modelling integral prestressed concrete boxgirder bridge by considering the interaction of structure, substructure and site condition; (3) studying the soil and pile interaction by applying bridge finite element modelling. (4) Validating experimental modelling with Finite element Modelling. As for the result validation, the four steps in the experimental approach involved: (1) scaling the integral concrete box-girder bridge by implementing Buckingham PI theorem; (2) setting the shaking table, shaker controller, LVDT, strain gauge and accelerometer; (3) analyzing finite element modelling of the scaled integral concrete box-girder bridge and (4) Validating the results by comparing the acceleration, displacement of structure response from instrument and finite element modelling. In this study, it was found that the behaviour and response of integral prestressed boxgirder bridge under seismic loading do not reach the yield level for low intensity earthquake. However, for moderate and high seismic intensity, the bridge response reached the yield level but still was under immediate occupancy level. Furthermore, the effect of soil-pile interaction for integral prestressed concrete box-girder bridge showed that the total displacement at the top of pier is 80% higher than fixed base support under longitudinal earthquake direction, while 87% higher under transversal direction. By conducting experimental shaking table test for integral concrete boxgirder bridge model, the seismic bridge response from finite element modelling (numerical approach) presented the approximate behaviour of integral concrete boxgirder bridge under earthquake loading. The findings in this research suggest that seismic loading effects should be considered in the design of integral prestressed concrete box-girder bridge due to higher displacement value compared to the one of the thermal loading.

ABSTRAK

Dewasa ini, jambatan integral dan bersambung gegalang kotak konkrit prategang menjadi pilihan di Malaysia. Namun, kegagalan engsel ekor sambungan kaku pada tiang dan lantai jambatan sering terhasil. Dalam kajian ini, perilaku seismik tidak linear jambatan integral gegalang kotak konkrit prategang diselidiki dengan mengambil kira keadaan tiang bawah tanah and penyokong dasar tegar. Kajian ini meliputi pendekatan numerikal dan eksperimental. Empat langkah yang digunakan dalam pendekatan numerikal :(1) Menyelidik sifat bahan dari jambatan integral gegalang kotak konkrit prategang; (2) Memodelkan jambatan integral gegalang kotak konkrit prategang dengan mengambilkira hubungkait antara struktur, substruktur dan keadaan tanah; (3) Mengkaji hubungan tanah dan tiang bawah tanah dengan melakukan analisis unsur terhingga terhadap model jambatan. (4) Mengesahkan model hasil ujikaji dengan model kaedah unsur terhingga. Bagi pengesahan hasil kajian, empat langkah telah digunakan: (1) Menjalankan proses pengecilan dimensi jambatan integral gegalang kotak konkrit prategang dengan menggunakan teori PI Buckingham; (2) Menyelaraskan meja gempa, pengendali penggerak, LVDT, meter terikan dan akselerometer; (3) Menganalisis model kaedah unsur terhingga jambatan integral gegalang kotak konkrit yang telah melalui proses pengecilan dimensi; (4) Mengesahkan hasil kajian dengan membandingkan perilaku kecepatan dan pergerakan struktur dari alat pengesan dan model kaedah unsur terhingga. Sifat dan perilaku jambatan jenis ini di bawah beban gempa tidak mencapai takat alah bagi gempa berintensiti rendah. Namun, untuk gempa berintensiti sederhana dan tinggi, perilaku jambatan telah mencapai takat alah meskipun di bawah takat penghunian segera. Daripada kajian ini, pengaruh hubungan tanah dan tiang bawah tanah untuk jambatan ini menunjukkan jumlah pergerakan pada atas tiang melebihi jenis penyokong dasar tegar kira-kira 0.8 kali untuk arah gempa longitudinal dan 0.87 kali untuk arah gempa transversal. Hasil penemuan dalam kajian ini mencadangkan agar pembinaan jambatan jenis ini sebaiknya mengambilkira kesan beban gempa kerana nilai pergerakan yang lebih tinggi berbanding dengan nilai pergerakan disebabkan oleh beban termal.

TABLE OF CONTENTS

| CHAPTER | TITLE | PAGE |
|----------|--|--------------|
| | TITLE | i |
| | DECLARATION | ii |
| | DEDICATION | iii |
| | ACKNOWLEDGEMENTS | iv |
| | ABSTRACT | v |
| | ABSTRAK | vi |
| | TABLE OF CONTENTS | vii |
| | LIST OF TABLES | xiii |
| | LIST OF FIGURES | xv |
| | LIST OF SYMBOLS/ABBREVIATIONS | xxvii |
| | LIST OF APPENDICES | xxxi |
| | | |
| 1 | INTRODUCTION | 1 |
| | 1.1 General | 1 |
| | 1.2 Problem Background | 5 |
| | 1.3 Problem Statement | 9 |
| | 1.4 Objectives | 10 |
| | 1.5 Research Finding/ Expected Outcome | 10 |
| | 1.6 Scope and Limitations | 11 |
| | 1.7 Methodology | 12 |
| | 1.7.1 Data Collection | 14 |
| | 1.7.2 The Analysis and Experimental Work | 15 |
| | 1.7.2.1 Mechanical Material Properties Laboratory Test | 15 |

| | | |
|----------|---|-----------|
| 1.7.2.2 | Soil - Pile Interaction | 15 |
| 1.7.2.3 | Bridge Modelling | 16 |
| 1.7.2.4 | Nonlinear Seismic Analysis | 16 |
| 1.7.2.5 | Shaking Table Experimental Work | 17 |
| 1.7.2.6 | Numerical Study of Casting Bridge Model | 17 |
| 1.8 | Organisation of Theses | 17 |
| 2 | LITERATURE REVIEW | 21 |
| 2.1 | Introduction | 21 |
| 2.2 | Integral Bridge | 21 |
| 2.2.1 | Deck Continuity | 23 |
| 2.2.2 | Comparisons of Pier- Deck Connections | 23 |
| 2.2.3 | Integral Abutment | 25 |
| 2.3 | Nonlinear Seismic Performance Based Design | 28 |
| 2.3.1 | Nonlinear Push-over Analysis | 30 |
| 2.3.1.1 | Performance Objective | 37 |
| 2.3.2 | Nonlinear Time History Analysis | 38 |
| 2.3.2.1 | Earthquake Record Scaling | 42 |
| 2.4 | Soil-Pile Integration | 43 |
| 2.5 | Integral Prestressed Concrete Box-girder Bridge Modelling | 51 |
| 2.6 | Previous Dynamic Shaking Table Test Study | 55 |
| 2.7 | Overall Literatures Study | 57 |
| 2.6 | Concluding Remarks | 58 |
| 3 | THEORETICAL BACKGROUND | 59 |
| 3.1 | Introduction | 59 |
| 3.2 | Linear Response of Bridges due to Earthquake | 59 |
| 3.2.1 | Single Degree of Freedom (SDOF) System | 63 |
| 3.2.1.1 | Free Vibration Analysis (Eigen value Analysis) | 63 |
| 3.2.1.2 | Time History Analysis | 64 |
| 3.2.2 | Multi Degree of Freedom (MDOF) System | 66 |
| 3.2.2.1 | Free Vibration Analysis | 66 |
| 3.2.2.2 | Time History Analysis | 67 |
| 3.2.3 | SAP2000 Bridge V14.2 Computer Applications | 69 |

| | | |
|----------|--|------------|
| | | ix |
| | 3.2.3.1 Free Vibration Analysis | 69 |
| | 3.2.3.2 Time History Analysis | 70 |
| | 3.3 Nonlinear Response of Bridges due to Earthquake | 70 |
| | 3.3.1 Single Degree of Freedom | 73 |
| | 3.3.1.1 Free Vibration Analysis | 73 |
| | 3.3.1.2 Time History Analysis | 74 |
| | 3.4 Finite Element Method Procedure for Linear and Nonlinear Analysis | 75 |
| | 3.5 Performance Based Design for Bridges | 79 |
| | 3.6 Concluding Remarks | 89 |
| 4 | MECHANICAL PROPERTIES OF MATERIAL FOR PRESTRESSED CONCRETE BOXGIRDER BRIDGE | 90 |
| | 4.1 Introduction | 90 |
| | 4.2 Mix Design | 91 |
| | 4.3 Test for Fresh Concrete | 92 |
| | 4.4 Test for Hardened Concrete | 94 |
| | 4.4.1 Compressive Strength Test | 95 |
| | 4.4.2 Flexural Strength Test | 97 |
| | 4.4.3 Static Modulus of Elasticity | 98 |
| | 4.4.4 Poisson's Ratio | 101 |
| | 4.5 Material Properties of Reinforcement Steel and Prestressing Strand | 103 |
| | 4.5.1 Stress-Strain Relationship of Steel Reinforcement | 104 |
| | 4.5.2 Stress-Strain Relationship of Prestressing Strand (Tendon) | 105 |
| | 4.6 Concluding Remarks | 106 |
| 5 | NONLINEAR RESPONSE OF INTEGRAL PRESTRESSED CONCRETE BOXGIRDER BRIDGE UNDER EARTHQUAKE LOADING | 108 |
| | 5.1 Introduction | 108 |
| | 5.2 Scope of Case Study | 109 |
| | 5.3 Seismic Loading | 110 |
| | 5.4 Period and Displacement of Bridge Performance | 113 |

| | | |
|----------|--|------------|
| 5.4.1 | Continuous Integral Supported Bridge | 114 |
| 5.4.2 | continuous Bearing Supported Bridge | 119 |
| 5.5 | Deck Continuity Bearing Supported Bridge System | 123 |
| 5.5.1 | Soil-Pile Interaction Properties | 123 |
| 5.5.2 | Finite Element Modelling | 125 |
| 5.5.3 | Hinge Properties | 126 |
| 5.5.4 | Push-over Analysis | 129 |
| 5.5.5 | Inelastic Time History Analysis | 133 |
| 5.6 | Deck Continuity and Monolithic Deck Pier System | 135 |
| 5.6.1 | Soil-Pile Interaction Properties | 135 |
| 5.6.2 | Finite Element Modelling | 135 |
| 5.6.3 | Hinge Properties | 137 |
| 5.6.4 | Push-over Analysis | 140 |
| 5.6.5 | Inelastic Time History Analysis | 142 |
| 5.7 | Damage Levels Vs Peak Ground Acceleration (PGA) | 145 |
| 5.8 | Concluding Remarks | 149 |
| 6 | THE EFFECT OF SOIL-PILE INTERACTION FOR INTEGRAL PRESTRESSED CONCRETE BOXGIRDER BRIDGE UNDER EARTHQUAKE LOADING | 153 |
| 6.1 | Introduction | 153 |
| 6.2 | Inelastic Nonlinear Seismic Analysis | 154 |
| 6.2.1 | Nonlinear Push-over Analysis | 155 |
| 6.2.2 | Nonlinear Time History Analysis | 157 |
| 6.3 | Local Soil Site Effect Analysis | 157 |
| 6.3.1 | Dynamic Soil Properties Analysis | 159 |
| 6.3.2 | Ground Response Analysis | 163 |
| 6.3.3 | Design Response Spectra | 164 |
| 6.4 | Soil-Structure Interaction | 169 |
| 6.4.1 | N-spt Correlation | 170 |
| 6.4.2 | Soil Stiffness Spring | 173 |
| 6.5 | Kampung Sawah Bridge | 173 |
| 6.5.1 | Nonlinear Time History Analysis | 175 |
| 6.5.2 | Nonlinear Push-over Analysis | 189 |

| | | |
|----------|--|------------|
| 6.5.2.1 | Demand Spectrum | 190 |
| 6.5.2.2 | Capacity Spectrum | 190 |
| 6.5.2.3 | Bridge Performance Evaluation | 192 |
| 6.5.3 | The Comparison of Nonlinear Time History Analysis and Nonlinear Push-over Analysis | 192 |
| 6.6 | Concluding Remarks | 193 |
| 7 | EXPERIMENTAL INVESTIGATION – TESTING OF BRIDGE MODELING USING SHAKING TABLE | 195 |
| 7.1 | Introduction | 195 |
| 7.2 | Shaking Table Specification and Capability | 196 |
| 7.2.1 | System Description | 197 |
| 7.2.2 | Table Capabilities and Characteristics | 197 |
| 7.2.3 | Data Acquisition and Control Characteristics | 198 |
| 7.3 | Preparation of Shaking Table and Bridge Model | 199 |
| 7.3.1 | Preparation of Shaking Table | 201 |
| 7.3.2 | Preparation of Bridge Model | 202 |
| 7.4 | Material Properties of Bridge Model | 203 |
| 7.4.1 | Laboratory Testing of Concrete Specimens | 204 |
| 7.4.2 | Reinforcement Steel | 206 |
| 7.5 | Parameter Measurement of Bridge Model | 207 |
| 7.6 | Calibration of Parameter Measurement | 208 |
| 7.7 | Shaking Table Testing | 210 |
| 7.7.1 | Earthquake Motion Excitation | 211 |
| 7.7.2 | Finite Element Bridge Modelling | 212 |
| 7.7.3 | Acceleration Responses of Bridge Model | 213 |
| 7.7.4 | Displacement Responses of Bridge Model | 216 |
| 7.7.5 | Strain Responses of Bridge Model | 219 |
| 7.7.6 | Cracking of Column Base | 220 |
| 7.8 | Concluding Remarks | 220 |
| 8 | CONCLUSIONS AND RECOMMENDATIONS | 222 |
| 8.1 | Introduction | 222 |
| 8.2 | Nonlinear Seismic Analysis of Integral Prestressed Concrete | |

| | |
|---|-----------|
| | xii |
| Box-girder Bridge | 222 |
| 8.3 Seismic Performance of Integral Prestressed Concrete Box-girder Bridge in Malaysia | 224 |
| 8.4 Recommendation for Further Work | 224 |
| REFERENCES | 226 |
| Appendices A - D | 240 - 250 |

LIST OF TABLES

| TABLE NO | TITLE | PAGE |
|----------|--|------|
| 2.1. | Comparison of Monolithic system and Bearing Supported system | 24 |
| 2.2 | Seismic bridge analysis tools (Priestley et al, 1996) | 29 |
| 2.3 | Finite element modeling techniques used by several researchers for box-girder bridge superstructure | 54 |
| 2.4. | Previous research work for seismic performance of bridges | 55 |
| 2.5. | The main literatures of each topic for the study | 57 |
| 3.1. | K factors for different structure type | 86 |
| 4.1. | Mix design proportion for concrete box girder bridge deck used for The experimental study | 92 |
| 4.2. | Concrete mix characteristic for class P | 92 |
| 4.3. | Result of compressive test for 7 days strength | 96 |
| 4.4. | Result of compressive test for 28 days strength | 96 |
| 4.5. | Flexural strength test results | 97 |
| 4.6. | The comparison of modulus elasticity empirical formula based on Eurocode and AASHTO LRFD Bridge Design Specification. | 101 |
| 6.1. | Seismic performance criteria (ATC/MCEER, 2001) | 155 |
| 6.2. | Foundation modelling Method (MCEER, 2001) | 157 |
| 6.3. | Empirical correlation between G _{max} and N-SPT value | 160 |
| 6.4. | Classification of subsoil classes in IBC2000/UBC1997 (2000) | 160 |
| 6.5. | Values of Site Coefficient F _a as a Function of Site Class and Mapped Spectral Response Acceleration at Short Periods, S _S (IBC 2000) | 166 |
| 6.6. | Values of Site Coefficient F _v as a Function of Site Class and Mapped Spectral Response Acceleration at 1 second Periods, S ₁ (IBC 2000) | 167 |
| 6.7. | Modified amplification factors for 2000 IBC (Soil Type: S _E) | 167 |
| 6.8. | Classification of sand based on N-SPT value (Bowles, 1984) | 171 |
| 6.9. | Classification of Clay based on N-spt value (Bowles, 1984) | 172 |

| | | |
|-------|--|-----|
| 6.10. | Representative Values of ϵ_{50} for Clays (Reese et al, 2006) | 172 |
| 6.11. | Representative Values of K_{py} for Clays (Reese et al, 2006) | 172 |
| 6.12. | Representative Values of K_{py} for Sands (Reese et al, 2006) | 172 |
| 6.13. | Dynamic characteristics of the bridge | 175 |
| 6.14. | Structure displacement for 100%X+30%Y earthquake direction combination | 180 |
| 6.15. | Structure displacement for 30%X+100%Y earthquake direction combination | 185 |
| 6.16. | Structure displacement: soil-pile interaction support versus fixed base support | 186 |
| 6.17. | Bridge pier force responses | 192 |
| 6.18. | The comparison force response at the bridge pier | 192 |
| 7.1. | The calculation of scaled modified Rapid KL Bridge model | 199 |
| 7.2. | Result of compressive test for 28 days strength | 204 |
| 7.3. | Strain gauge technical specification | 207 |
| 7.4. | Accelerometer technical specification | 207 |
| 7.5. | LVDT technical specification | 208 |
| 7.6. | The comparison of bridge model acceleration response by experiment and finite element analysis (Rapid KL adopted bridge model) | 215 |
| 7.3. | The comparison of bridge model displacement response by experiment and finite element analysis (Rapid KL adopted bridge model) | 218 |

LIST OF FIGURES

| FIGURE NO | TITLE | PAGE |
|-----------|---|------|
| 1.1 | First Penang Bridge | 1 |
| 1.2 | Unseating bridge deck of shoowa Bridge in 1964 (Moehle and Eberhad, 2000) | 2 |
| 1.3 | Nishinomiya-ko Bridge bearing failure in 1995 (Moehle and Eberhad, 2000) | 2 |
| 1.4 | Sultan Mahmud Bridge, Terengganu | 3 |
| 1.5 | Santubong Bridge, Kuching Sarawak | 4 |
| 1.6 | Permas Jaya Bridge, Johor | 5 |
| 1.7 | Chin (1988) vs Azlan et al (2006) for Design Response spectrum for first Penang Bridge | 7 |
| 1.8 | Potential Hinge location (Patty et al, 2002) | 8 |
| 1.9 | Methodology of research | 13 |
| 1.10 | Implementation of the methodology in the organization of thesis | 18 |
| 2.1 | The structural component of an integral Bridge (David et al, 2005) | 22 |
| 2.2 | The factor affecting construction of elastic response spectrum | 24 |
| 2.3 | Prestress effect with integral bridge deck (Hewson, 2008) | 27 |
| 2.4 | The factor affecting construction of elastic response spectrum (FEMA440, 2005) | 28 |
| 2.5 | Performance and structural deformation for structures (Applied Technology Council 40, 1996) | 24 |

| | | |
|------|---|----|
| 2.6 | Hinge develops at structure component. | 32 |
| 2.7 | Base shear versus bridge displacement curve (Kawashima, 2006 and ATC40, 1996) | 33 |
| 2.8 | The force deformation criteria for hinges (FEMA356, 2000) | 34 |
| 2.9 | Simple Push-over method of evaluation (ATC40, 1996) | 36 |
| 2.10 | Static nonlinear push-over analysis procedures | 37 |
| 2.11 | Example of Spectral matching analysis for 500 year for second Penang Bridge | 43 |
| 2.12 | Beam on non-linear Winkler foundation model (Liyanapathir, and Poulos, 2005) | 44 |
| 2.13 | Idealized nonlinear model of a pile foundation (after Earthquake Resistant Design Codes in Japan, 2000) | 45 |
| 2.14 | Structural model for viaducts (Earthquake Resistant Design Codes in Japan, 2000) | 46 |
| 2.15 | Model for ground resistance (Boris and Radomir, 2008) | 46 |
| 2.16 | Scheme of dynamic nonlinear p-y element for soil–pile structure Interaction (Boris and Radomir, 2008) | 47 |
| 2.17 | Assumptions for evaluation of equivalent upright beam: soil-grouped pile (left), sliced elements (right) (Tahgihighi and Konagai, 2006) | 47 |
| 2.18 | Model of soil–pile system for separation (Maheshwari and Watanabe, 2000) | 48 |
| 2.19 | Foundation bridge model for parametric study (Finn, 2004) | 49 |
| 2.20 | Winkler model of horizontal soil; support to substructure (Basu et al, 2005) | 50 |
| 2.21 | Analytical model for lateral load analysis (Dicleli, 1998) | 51 |
| 2.22 | Modeling of bridge structural component (Aviram et al, 2008) | 52 |

| | | |
|------|---|----|
| 2.23 | Model of MMB and selected AMB (Wang, 2009) | 53 |
| 2.24 | Bridge finite element modeling for Egnatia Motorway Bridge by using SAP2000 (Kappos and Sextos, 2009) | 53 |
| 2.25 | Comparison of analytical and experimental acceleration for Sylmar record (Ersoy et al, 2001) | 56 |
| 2.26 | Comparison of analytical and experimental displacement for Sylmar record (Ersoy et al, 2001) | 56 |
| 3.1 | The equivalent static force | 60 |
| 3.2 | Four way logarithmic plot of response spectrum, El Centro ground Motion (After Hudson, 1979) | 62 |
| 3.3 | (a) idealized pergola; (b) Idealized water tank; (c) Free vibration due to initial displacement (Chopra, 1995) | 63 |
| 3.4 | Solution for free vibration analysis of a single degree of freedom (SDOF) in linear elastic system | 64 |
| 3.5 | Solution for the free vibration analysis of a multi degree of freedom (MDOF) in linear elastic system | 68 |
| 3.6 | Comparison of base shear coefficients from elastic design spectrum and Uniform Building Code (Chopra, 1995) | 71 |
| 3.7 | Free- deformation relations for a structural steel component (Krawinkterm et al, 1971) | 73 |
| 3.8 | The earthquake performance level versus earthquake design level | 79 |
| 3.9 | Performance based design | 80 |
| 3.10 | α_i of various mode shapes | 82 |
| 3.11 | Capacity curve of structure and SDOF capacity spectrum | 82 |
| 3.12 | The conversion of Spectral acceleration versus period to spectral acceleration versus spectral displacement | 83 |

| | | |
|------|--|-----|
| 3.13 | The reduction of elastic demand spectrum to inelastic demand spectrum | 83 |
| 3.14 | Hysteretic damping | 84 |
| 3.15 | Elastic strain energy | 85 |
| 3.16 | Demand spectrum | 86 |
| 3.17 | FEMA acceleration and demand response spectra | 87 |
| 3.18 | FEMA 356 process | 88 |
| 4.1 | The process of Slump test measurement | 93 |
| 4.2 | Hardened concrete after opening the mould for 24 hours | 94 |
| 4.3 | Hardened cube concretes for 7 and 28 days curing | 95 |
| 4.4 | The process of Compressive strength test | 96 |
| 4.5 | Hardened prism for flexural testing after curing for 28 days | 97 |
| 4.6 | The process of flexural strength test | 98 |
| 4.7 | Hardened cylinder concrete samples | 99 |
| 4.8 | Static modulus of elasticity test | 100 |
| 4.9 | Stress versus vertical strain | 100 |
| 4.10 | Stress versus horizontal strain | 103 |
| 4.11 | Tensile strength laboratory test | 104 |
| 4.12 | Stress-strain curve for reinforcement steel | 105 |
| 4.13 | Stress-strain curve for prestressing strand | 106 |
| 5.1 | The scaling of time histories loading for Integral and Non-integral Bridge | 111 |
| 5.2 | The scaling of demand spectrum loading for Integral and Non-integral Bridge | 113 |
| 5.3 | The concrete casting of integral prestressed concrete box-girder bridge deck for Kampung Sawah Bridge (21/09/09) | 114 |

| | | |
|------|--|-----|
| 5.4 | Integral Bridges with 3, 4 and 5 spans | 115 |
| 5.5 | Mode shape 1 for 3-spans Integral Bridge (T=7.74 sec) | 116 |
| 5.6 | Mode shape 2 for 3-spans Integral Bridge (T=6.30 sec) | 116 |
| 5.7 | Mode shape 3 for 3-spans Integral Bridge (T=5.87 sec) | 117 |
| 5.8 | Mode shape 4 for 3-spans Integral Bridge (T=2.17 sec) | 117 |
| 5.9 | Comparison of Integral Bridge structure's period based on the numbers of spans | 118 |
| 5.10 | Comparison of Integral abutment's displacement based on numbers of spans | 118 |
| 5.11 | Prestressed concrete box-girder Nordin Bridge | 119 |
| 5.12 | Deck cross section of Nordin Bridge | 119 |
| 5.13 | Non-integral Bridges with 3, 4 and 5 spans | 120 |
| 5.14 | Mode shape 1 of the Non-integral Bridge (T=1.28 sec) | 121 |
| 5.15 | Mode shape 2 of the Non-integral Bridge (T=0.98 sec) | 121 |
| 5.16 | Mode shape 3 of the Non-integral Bridge (T=0.53 sec) | 121 |
| 5.17 | Mode shape 4 of the Non-integral Bridge (T=0.42 sec) | 122 |
| 5.18 | Comparison of Non-integral Bridge structure's period based on the numbers of spans | 122 |
| 5.19 | Comparison of Non-integral abutment's displacement based on numbers of span | 123 |
| 5.20 | Lateral force and soil deflection relationship for Non-integral Bridge | 124 |
| 5.21 | Finite Element modelling of Nordin Bridge (Non-integral type) | 126 |
| 5.22 | Pier plastic hinges curve in SAP2000 program for Non-integral Bridge | 127 |
| 5.23 | The cross section of pier for cross section analysis for Non-Integral Bridge | 127 |

| | | |
|------|---|-----|
| 5.24 | Moment-curvature analysis for Non- integral Bridge | 128 |
| 5.25 | Fiber method for concrete box-girder deck for Non-integral Bridge | 129 |
| 5.26 | Damage level at 0.15g at x-direction for Non-integral Bridge under push-over analysis | 130 |
| 5.27 | Damage level at 0.25g at x-direction for Non-integral Bridge under push-over analysis | 131 |
| 5.28 | Damage level at 0.35g at x-direction for Non-integral Bridge under push-over analysis | 131 |
| 5.29 | Damage level at 0.15g at x-direction for Non-integral Bridge under push-over analysis | 132 |
| 5.30 | Damage level at 0.15g at x-direction for Non-integral Bridge under push-over analysis | 132 |
| 5.31 | Damage level at 0.15g, 0.25g, 0.35g at y-direction for Non-integral Bridge under push-over analysis | 132 |
| 5.32 | Damage level at 0.25g at x-direction for Non-integral Bridge under time history analysis | 133 |
| 5.33 | Damage level at 0.55g at x-direction for Non-integral Bridge under time history analysis | 133 |
| 5.34 | Damage level at 0.65g at x-direction for Non-integral Bridge under time history analysis | 133 |
| 5.35 | Damage level at 0.25g at y-direction for Non-integral Bridge under time history analysis | 134 |
| 5.36 | Damage level at 0.45g at y-direction for Non-integral Bridge under time history analysis | 134 |
| 5.37 | Damage level at 0.55g at y-direction for Non-integral Bridge under time history analysis | 134 |
| 5.38 | Damage level at 0.65g at y-direction (10.7 sec) for Non-integral Bridge under time history analysis | 134 |

| | | |
|------|---|-----|
| 5.39 | Damage level at 0.65g at y-direction (11.1 sec) for Non-integral Bridge under time history analysis | 134 |
| 5.40 | Lateral force and soil deflection relationship for Integral Bridge | 135 |
| 5.41 | Finite element modelling of bridge structure for Integral Bridge | 137 |
| 5.42 | Pier plastic hinges for Integral Bridge | 138 |
| 5.43 | The cross section of pier for cross section analysis for Integral Bridge | 138 |
| 5.44 | Moment-curvature analysis for Integral Bridge | 139 |
| 5.45 | Fiber method for concrete box-girder deck for Integral Bridge | 139 |
| 5.46 | No plastic hinge develops at bridge pier at 0.15g, 0.25g, and 0.35g at x-direction for Integral Bridge under push-over analysis | 140 |
| 5.47 | Damage level at 0.45g at x-direction for Integral Bridge under push-over analysis | 140 |
| 5.48 | Damage level at 0.55g at x-direction for Integral Bridge under push-over analysis | 141 |
| 5.49 | Damage level at 0.85g at x-direction for Integral Bridge under push-over analysis | 141 |
| 5.50 | Damage level at 1.35g at x-direction for Integral Bridge under push-over analysis | 141 |
| 5.51 | Damage level at 1.55g at x-direction for Integral Bridge under push-over analysis | 142 |
| 5.52 | No plastic hinge develops at bridge pier at 0.15g, 0.25g, and 0.35g at y-direction for Integral Bridge under push-over analysis | 142 |
| 5.53 | Damage level at 0.55g at x-direction for Integral Bridge under time history analysis | 143 |
| 5.54 | Damage level at 0.95g at x-direction for Integral Bridge under time history analysis | 143 |

| | | |
|------|---|-----|
| 5.55 | Damage level at 1.05g at x-direction for Integral Bridge under time history analysis | 143 |
| 5.56 | Damage level at 1.45g at x-direction for Integral Bridge under time history analysis | 144 |
| 5.57 | Damage level at 0.75g at y-direction for Integral Bridge under time history analysis | 144 |
| 5.58 | Damage level at 1.05g at y-direction for Integral Bridge under time history analysis | 144 |
| 5.59 | Damage level at 1.35g at y-direction for Integral Bridge under time history analysis | 145 |
| 5.60 | Damage level vs Peak ground Acceleration at y-direction for Non-integral Bridge under time history analysis | 145 |
| 5.61 | Damage level vs Peak ground Acceleration at x-direction for Non-integral Bridge under time history analysis | 146 |
| 5.62 | Damage level vs Peak ground Acceleration at y-direction for integral Bridge under time history analysis | 146 |
| 5.63 | Damage level vs Peak ground Acceleration at x-direction for integral Bridge under time history analysis | 147 |
| 5.64 | Damage level vs Peak ground Acceleration at y-direction for Non-integral Bridge under push-over analysis | 147 |
| 5.65 | Damage level vs Peak ground Acceleration at x-direction for Non-integral Bridge under push-over analysis | 148 |
| 5.66 | Damage level vs Peak ground Acceleration at y-direction for Integral Bridge under push-over analysis | 148 |
| 5.67 | Damage level vs Peak ground Acceleration at x-direction for Integral Bridge under push-over analysis | 149 |
| 6.1 | Approximate relationship between peak accelerations on rock and soft soil sites (after Idriss, 1990) | 158 |

| | | |
|------|---|-----|
| 6.2 | Average normalised response spectra (5% damping) for different local site conditions (after Seed et al., 1976) | 159 |
| 6.3 | Macrozonation Map for 500 years return period at T=0.2 second (Azlan et al, 2006) | 161 |
| 6.4 | Macrozonation Map for 500 years return period at T=1.0 second (Azlan et al, 2006) | 161 |
| 6.5 | Macrozonation Map for 2500 years return period at T=0.2 second (Azlan et al, 2006) | 162 |
| 6.6 | Macrozonation Map for 2500 years return period at T=1.0 second (Azlan et al, 2006) | 162 |
| 6.7 | Three synthetic time history of second Penang Bridge seismic hazard assessment | 164 |
| 6.8 | 2000 IBC design response spectrum (International Code Council, 2000) | 166 |
| 6.9 | Response spectra and Recommended design response spectra at the bridge location (TR=500, Soil type Se) | 167 |
| 6.10 | Time history at surface 500 years (PGA= 0.129g) for case study of Kampung Sawah Bridge | 168 |
| 6.11 | Spectral matching analysis for producing earthquake time history loading for case study of Kampung Sawah Bridge | 169 |
| 6.12 | Correlation of N-SPT and cohesion, c(KPa) Note : c is equal to Su | 170 |
| 6.13 | Correlation of N-SPT and soil angle friction(ϕ) (Terzaghi) | 171 |
| 6.14 | Finite element modelling of Kampung Sawah Bridge | 173 |
| 6.15 | Solid finite element modelling of Kampung Sawah Bridge | 174 |
| 6.16 | Various depth of soil stiffness curve model for Kampung Sawah Bridge piers | 174 |
| 6.17 | Mode shapes for fixed base support and Soil- pile interaction | |

| | | |
|------|---|-----|
| | Support of Kampung Sawah Bridge | 175 |
| 6.18 | Longitudinal and transversal displacement response for top of pier under TH1, TH2, and TH3 loading (Fixed base support with $100\%X+30\%Y$ earthquake direction) of Kampung Sawah Bridge | 176 |
| 6.19 | Longitudinal and transversal displacement response for middle of deck under TH1, TH2, and TH3 loading (Fixed base support with $100\%X+30\%Y$ earthquake direction) of Kampung Sawah Bridge | 177 |
| 6.20 | Longitudinal and transversal displacement response for top of pier under TH1, TH2, and TH3 loading (Soil Structure interaction with $100\%X+30\%Y$ earthquake direction) of Kampung Sawah Bridge | 178 |
| 6.21 | Longitudinal and transversal displacement response for middle of deck under TH1, TH2, and TH3 loading (Soil Structure interaction with $100\%X+30\%Y$ earthquake direction) of Kampung Sawah Bridge | 179 |
| 6.22 | Longitudinal and transversal displacement response for top of pier under TH1, TH2, and TH3 loading (Fixed base support with $30\%X+100\%Y$ earthquake direction) of Kampung Sawah Bridge | 181 |
| 6.23 | Longitudinal and transversal displacement response for middle of deck under TH1, TH2, and TH3 loading (Fixed base support with $30\%X+100\%$ earthquake direction) of Kampung Sawah Bridge | 182 |
| 6.24 | Longitudinal and transversal displacement response for top of pier under TH1, TH2, and TH3 loading (Soil Structure interaction with $30\%X+100\%Y$ earthquake direction) | 183 |
| 6.25 | Longitudinal and transversal displacement response for middle of deck under TH1, TH2, and TH3 loading (Soil Structure interaction with $30\%X+100\%Y$ earthquake direction) of Kampung Sawah Bridge | 184 |
| 6.26 | Deck response for fixed base supports under both earthquake | |

| | | |
|------|--|-----|
| | direction (Kampung Sawah Bridge) | 187 |
| 6.27 | Pier response for fixed base supports under both earthquake direction (Kampung Sawah Bridge) | 187 |
| 6.28 | Deck response for soil pile interaction under both earthquake direction (Kampung Sawah Bridge) | 188 |
| 6.29 | Pier response for soil pile interaction under both earthquake direction (Kampung Sawah Bridge) | 188 |
| 6.30 | Demand spectrum for Kampung Sawah Bridge location | 190 |
| 6.31 | The performance point as the intersection of the bridge's seismic capacity curve and seismic demand curve (Kampung Sawah Bridge) | 191 |
| 6.32 | The pier's plastic hinge at 0.156m displacement (Kampung Sawah Bridge) | 191 |
| 7.1 | Table top grid of R-51 hydraulic shaking table | 196 |
| 7.2 | Existing Hydraulic shaking Table in Structure and Material Laboratory, Faculty of Civil Engineering, Universiti Teknologi Malaysia | 197 |
| 7.3 | Cross section of box-girder bridge deck model (Rapid KL Bridge) | 200 |
| 7.4 | Box-girder bridge model dimension (Rapid KL Bridge) | 200 |
| 7.5 | The process steps of constructing bigger additional table for shaking table | 201 |
| 7.6 | The process steps of constructing Rapid KL adopted bridge model | 202 |
| 7.7 | The concrete sample for testing material properties | 203 |
| 7.8 | Crushing of concrete cube after compression test | 204 |
| 7.9 | The concrete cylinder specimens for producing stress-strain relationship | 204 |
| 7.10 | Concrete testing to produce stress-strain curve relationship | 205 |
| 7.11 | Crushing cylinder after testing | 205 |

| | | |
|------|---|-----|
| 7.12 | Concrete stress-strain curve relationship for bridge model | 205 |
| 7.13 | The steel sample for testing material properties | 206 |
| 7.14 | The stress-strain curve of link steel | 206 |
| 7.15 | (a) accelerometer, (b) strain gauge, (c) LVDT | 208 |
| 7.16 | Acc Dytran 3110A s/n= 114 | 209 |
| 7.17 | Acc Dytran 3110A s/n= 111 | 209 |
| 7.18 | Reference shaker: Kistler 8921 | 210 |
| 7.19 | Monolithic pier deck system bridge model | 210 |
| 7.20 | Response data recorder position (accelerometer, LVDT and strain gauge) | 211 |
| 7.21 | El-centro earthquake record used for numerical and experimental study | 212 |
| 7.22 | Finite element modelling of bridge model (modified Rapid KL Bridge) | 213 |
| 7.23 | Acceleration response for Channel 7 | 214 |
| 7.24 | Acceleration response of bridge model channel 8 (Rapid KL adopted Bridge model) | 214 |
| 7.25 | Displacement response of bridge model for Channel 5 | 217 |
| 7.26 | Displacement response of bridge model for Channel 6 under shaking table test and finite element analysis for modified Rapid KL Bridge model | 217 |
| 7.27 | Strain response of bridge model by experimental test and finite element analysis at PGA = 0.18g (Rapid KL adopted bridge model) | 219 |
| 7.28 | The column bases cracking at 0.15g | 220 |

LIST OF SYMBOLS/ABBREVIATIONS

| | | |
|---------------------------|---|---|
| \ddot{D}_n | - | Acceleration at n^{th} mode |
| $[k]_i$ | - | Element i global stiffness matrix |
| DSHA | - | Deterministic Seismic Hazard Assessment |
| $[k]_i$ | - | Element i local stiffness matrix |
| \dot{D}_n | - | Velocity at n^{th} mode |
| ζ | - | Damping ratio |
| α_1 and α_2 | - | Constants that can be obtained based on the damping ratio |
| g | - | Gravity = 9.81 m/s^2 |
| gal | - | cm/sec^2 |
| E | - | Modulus of elasticity |
| α_i | - | Participation factor |
| $[K]$ | - | System global stiffness matrix |
| $[M]$ | - | System mass matrix |
| $\{\phi\}_i$ | - | Eigenvector i |
| $\{\mathbf{1}\}$ | - | A unit vector |
| fb | - | Flexural tensile strength |
| $\{F\}$ | - | Vector of equivalent nodal forces |
| MPa | - | Mega Pascal |
| $\{U_o\}$ | - | Vector of amplitudes for various degrees of freedom |
| PGA | - | Peak Ground Acceleration (at Bedrock) |
| PSA | - | Peak Surface Acceleration |
| PSHA | - | Probabilistic Seismic Hazard Assessment |
| \ddot{z} | - | Acceleration of the ground |
| $[L]_i$ | - | Element i transformation matrix |
| \mathbf{a} | - | Acceleration vector |
| a | - | Acceleration |

| | | |
|-----------------------------------|---|--|
| A | - | Acceleration coefficient |
| $A(\mathbf{t})$ | - | Pseudo- acceleration |
| $\alpha_g(\mathbf{t})$ | - | Ground acceleration at time, t |
| A_n | - | Pseudo- acceleration response spectrum |
| $\alpha^{\mathbf{t}}(\mathbf{t})$ | - | Total acceleration at time, t |
| s_u | - | Undrained shear strength |
| S_v | - | Spectral Velocity |
| T_n | - | Natural period |
| T_R | - | Return Period |
| V_s | - | Shear wave velocity |
| V_{S-30} | - | The mean shear wave velocity of the top 30 m |
| Z | - | Seismic zone factor |
| σ | - | Compressive strength |
| ρ | - | Mass density |
| ω | - | Angular frequency = $2\pi f$ |
| \mathbf{c} | - | Damping matrix |
| c | - | Damping |
| C | - | Damping matrix |
| C_i | - | i^{th} element of the generalized damping matrix $[\mathbf{C}]$ |
| D_n | - | Displacement at n^{th} mode |
| ϕ | - | Matrix of corresponding eigenvectors |
| ϕ_n | - | Mode shape |
| f_s | - | Resisting force |
| F_x | - | Force in global x- direction |
| F_y | - | Force in global y- direction |
| F_z | - | Force in global z- direction |
| \mathbf{K} | - | Stiffness matrix |
| k | - | Stiffness |
| K | - | Stiffness matrix |
| K_i | - | i^{th} element of the generalized stiffness matrix $[\mathbf{K}]$ |
| $\mathbf{1}$ | - | Influence vector |
| \mathbf{m} | - | Mass matrix |
| m | - | Mass |

| | | |
|--------------|---|---|
| M | - | Diagonal mass matrix |
| M_2 | - | Moment in local axis-2 direction |
| M_3 | - | Moment in local axis-3 direction |
| $M_b(t)$ | - | Base moment |
| M_i | - | i^{th} element for the generalized mass matrix $[M]$ |
| $M_p(-)$ | - | Negative plastic moment |
| $M_p(+)$ | - | Positive plastic moment |
| M_X | - | Moment in global x-direction |
| M_{XX} | - | Bending force in x-plane and x-direction |
| M_{XY} | - | Bending force in x-plane and y-direction |
| M_Y | - | Moment in global y-direction |
| $M_y(-)$ | - | Negative yield moment |
| $M_y(+)$ | - | Positive yield moment |
| M_{YY} | - | Bending force in y-plane and y-direction |
| M_Z | - | Moment in global z-direction |
| P | - | Axial force in local axis direction |
| $P_{eff}(t)$ | - | Effective force time history |
| $q_n(t)$ | - | Displacement function at time, t |
| R_X | - | Rotation in global x-direction |
| R_Y | - | Rotation in global y-direction |
| R_Z | - | Rotation in global z-direction |
| S_d | - | Spectral displacement |
| S_{MAX} | - | Maximum membrane force |
| S_{MIN} | - | Minimum membrane force |
| S_v | - | Spectral pseudo- velocity |
| S_{VM} | - | Von Misses membrane force |
| S_{XX} | - | Membrane force in x-plane and x-direction |
| S_{XY} | - | Membrane force in x-plane and y-direction |
| S_{YY} | - | Membrane force in y-plane and y-direction |
| t | - | Time |
| T | - | Torsion in local axis direction |
| T_n | - | Natural period |
| u | - | Relative displacement with time |

| | |
|-----------------|--|
| \mathbf{u} | - Displacement vector |
| $\mathbf{u}(t)$ | - Displacement vector at time, t |
| $u(t)$ | - Deformation response history |
| u_0 | - Peak value |
| u_g | - Ground acceleration |
| U_x | - Displacement in global x-direction |
| u_y | - Yield deformation |
| U_y | - Displacement in global y-direction |
| U_z | - Displacement in global z-direction |
| \mathbf{v} | - Velocity vector |
| v | - Velocity |
| V_2 | - Shear force in local axis-2 direction |
| V_3 | - Shear force in local axis-3 direction |
| $V_b(t)$ | - Base shear |
| V_r | - Shear range |
| w | - Natural angular frequency of vibration |
| w_1 and w_2 | - First and second natural frequencies |
| w_n | - Natural frequency i |
| w_i | - Natural angular frequency |
| $\psi(x)$ | - Shape function |
| $Z(\dot{t})$ | - Amplitude of motion |
| ζ_n | - Damping ratio at n th mode |

LIST OF APPENDICES

| APPENDIX | TITLE | PAGE |
|-----------------|---|-------------|
| A | The soil dynamic properties for Nordin prestressed concrete Box-girder Bridge | 240 |
| B | The soil dynamic properties for Kampung Sawah prestressed concrete Box-girder Bridge | 243 |
| C | Box-girder section properties | 247 |
| D | List of publication | 249 |

CHAPTER 1

INTRODUCTION

1.1 General

In Malaysia, structural engineers have begun to consider some seismic design considerations ever since tremor effects were felt on local bridge structures. Figure 1.1 shows the 13.6 km length cable stayed box-girder bridge type in Penang. This bridge was the first bridge in Malaysia in which seismic loading was considered during the structural design. Chin (1988) in his reports entitled “The Penang Bridge Planning, Design and Construction Report “(P.15), recognised that the nearest earthquakes source locations to Malaysia were:

1. 4N 99E depth 150km magnitude 6.25; (earthquake occurred on January 20th 1931) and
2. 4N 99E depth 200km magnitude 6.5 (earthquake occurred on July 4th, 1936)



Figure 1.1 First Penang Bridge

According to Chin (1988), a great earthquake in Malaysia is very rare. So, it is more economical to design the structure to resist the maximum seismic input with damage. In other words, the design philosophies should undergo lower level of structural strength at lesser cost to pay for the necessary repairs in the unlikely event of a maximum credible earthquake occurred.

Therefore, it is more preferable for a country like Malaysia to construct a box-girder bridge type compared to the other type of bridge since it has many advantages. The advantages are:

1. Box-girder Bridge has no expansion joint. Normally when earthquake happens, the expansion joint will be damaged due to the movement of the deck and unseating of simple spans will occur (Figure 1.2).



Figure 1.2 Unseating of the bridge deck of Shoowa Bridge in 1964 Niigata earthquake (Moehle and Eberhad, 2000)

2. No bearing for integral bridge type. Normally when earthquake happens, the bearing failure always occurs (Figure 1.3).



Figure 1.3 Nishinomiya-ko Bridge bearing failure in 1995 (Moehle and Eberhad, 2000)

In Malaysia, the concrete box-girder bridge has been constructed in many states. There are two types of concrete box-girder bridge namely continuous box girder and integral box-girder bridge. Some of the existing continuous box-girder bridge types in Malaysia are listed below:

1. Sultan Abdullah Bridge. This is one of the earliest concrete box-girder bridges to be constructed in Malaysia. This bridge crosses the Pahang River near Jerantut on federal Route 64. It has five spans with a total length of 486m. The maximum span length is 115m.
2. Sultan Yussuf Bridge. This bridge which was constructed in 1988 is located on Federal Route 5 near the town of Teluk Intan. The bridge crosses the Perak River and has a total length of 1.3km. It has three spans over water, of prestressed concrete box girder design, with a central navigational span of 160m and two side spans of 95m each.
3. Sultan Azlan Shah Bridge. The bridge crosses Sungai Perak and is part of the North- South Expressway. It is 360m long and comprises five concrete box girder bridge spans.
4. Sultan Mahmud Bridge. Figure 1.4 shows the bridge location at the estuary of Sungai Terengganu, connecting the northern and southern sectors of Kuala Terengganu municipality. It comprises three separate structures, the longest of which is the south bridge, 1195m long, connecting the southern bank to Pulau Duyong. The other two structures are the North bridge 1 and 2 which are 220m and 320m long respectively. The five central spans of the south bridge are of balanced cantilever concrete box-girder construction, comprising three 65m long spans and two 40m long spans. The rest of the spans are made up of 40m long prestressed T- beams.




Figure 1.4 Sultan Mahmud Bridge, Terengganu

5. Tanjung Lumpur Bridge. This bridge crosses Sungai Kuantan connecting Padang Lalang and Tanjung Lumpur which provides a direct crossing to the parts of the river from Kuantan Town. The bridge has a total length of 424m comprising of three balanced cantilever double box girder central spans totalling 186m (50m-86m-50m) and three 40m prestressed concrete beam approach spans on each side.

Some of the existing integral box-girder bridges that have been constructed in Malaysia are as follow:

1. Santubong Bridge (Figure 1.5). The main spans of this bridge are of prestressed concrete balanced cantilever box-girder with a central span of 146m. The total span length inclusive of the precast I- beam approach span is 593m. The bridge which is located near Kuching Sarawak was completed in 1988.




Figure 1.5 Santubong Bridge, Kuching Sarawak

2. Permas Jaya Bridge. Figure 1.6 shows the bridge location over Sungai Tebrau in Johor Bahru which forms the main access to the Permas Jaya New Town. It has a total length of 600m with a central and side spans of 186m and 90m respectively, employing double cantilever box-girder construction method. The symmetrical approach spans on both ends consist of 3 spans of 33m and one span of 27m prestressed beams. The bridge was opened to traffic in 1994.



Figure 1.6 Permas Jaya Bridge, Johor

3. Kampung Sawah Bridge. This bridge is located in Kuala Langat in Selangor and is one of the main bridges in Selangor. The bridge is a prestressed box-girder concrete type still under construction, at the casting of the concrete box-girder deck phase. The concrete box-girder bridge is made up of 79m + 110m + 79m (total 268m) span and concrete beam approach spans on each side.

1.2 Problem Background

In recent years, Malaysians are more aware of and concern for the seismic effect on their bridges because the tremors were repeatedly felt over the centuries from the earthquake events around Malaysia. For example, the First Penang Bridge had experienced some minor damage due to Aceh earthquake on 24 December 2004. Fortunately, the First Penang Bridge was designed under seismic consideration.

The seismic consideration for first Penang Bridge has followed the steps as mentioned by Idriss (1985), who identified three presently used methods of obtaining the design ground motion parameters: (1) Use of local codes, (2) Conducting quasi-deterministic seismic hazard evaluation, and (3) Conducting a probabilistic seismic hazard evaluation. Based on Mohammad (1986), in Malaysia, only method (2) is made available with simplified quasi-deterministic seismic hazard evaluation version.

Idriss (1985) also describes the current practice of a quasi- deterministic seismic hazard evaluation as consisting of the following steps:

1. Conducting a geologic and seismologic evaluation to define the sources (faults) relevant to the site.
2. Estimating the maximum magnitude, m_1 , on each source. This is the “maximum credible earthquake”. The closest distance from the fault zone to the site is then determined.
3. Deriving recurrence relationships for each source using historical seismicity as well as geologic data, and select an earthquake with a magnitude $m_2 < m_1$ for each source such that the recurrence $N(m)$ for $m > m_2$ is the same for all sources; if, for example $N(m^2) = 0.01$ per year is used, corresponding to a recurrence interval of 100 years, this earthquake is then designated the 100 year earthquake.
4. Determining parameters for each source (e.g. peak ground acceleration), using appropriate attenuation relationships, for the maximum earthquake and for the earthquake use the magnitude and distance producing the largest ground motion parameter of interest for design and analyses.

However, based on Chin (1982), there are some data that are collected based on judgmental evaluations probably due to the unavailability or incompleteness of data. The seismic hazard evaluation procedure for the first Penang Bridge can be regarded as a simplified version of the quasi-deterministic approach, in which steps (1) and (2) were followed, but steps (3) and (4) were replaced with judgmental evaluations.

This statement is supported by Mohammad (1986). He reported that the current practice of seismic hazard evaluation in Malaysia is rather subjective, and is limited by the lack of organised data. Research has to be conducted to assemble data and obtain reliable relationships required for rational seismic hazard evaluations.

In 2005, Structural Earthquake Engineering Research (SEER) of Universiti Teknologi Malaysia has carried out seismic zone mapping for peninsular Malaysia and east Malaysia. Azlan et al (2006) has done proper seismic hazard assessment for

Penang Bridge using Deterministic Seismic Hazard Analysis (DSHA) and Probabilistic Seismic Hazard Analysis (PSHA).

From Figure 1.7, the spectral acceleration for the design of the response spectrum of the Penang Bridge carried out by Azlan et al (2006) is two times higher compared to Chin (1988) at period 0.5 – 1.0 second and three times at period 2.0 – 2.5 second. The low values in Chin's result were due to the limitation of organised data in 1980s and the improper deterministic method. Figure 1.7 shows the significance of taking into account the seismic effect in bridge design in Malaysia.




Figure 1.7 Chin (1988) vs Azlan et al (2006) for Design Response spectrum for first Penang Bridge

Seismic performance of existing bridges in Malaysia is very important, particularly for the concrete box-girder type. This type of bridge has good performance for neglecting the effect of earthquake like bearing failure and unseating

simple span. Unfortunately, the other problem of this type of bridge that always occurs due to seismic force is plastic hinge failure (secondary stress). The problem occurs into this system after considering the seismic effect where rigid connection of column and deck will produce potential hinge failure. Therefore, the performance of the integral and continuous prestressed concrete box-girder bridges under nonlinear seismic study should be investigated.

Based on Burke (2009), bridge engineers are still willing to relinquish some of their control of secondary stresses for integral prestressed concrete box-girder bridges. It is because integral prestressed concrete box-girder bridge achieves simpler construction, more cost-effective, greater overall integrity, and durability.

Currently integral and continuous concrete box-girder bridges are now becoming a popular choice of system in Malaysia, as the benefit of this system reduces the cost of bridge maintenances. Figure 1.8 shows the problem occurs in such systems when considering the seismic effect where rigid connection of column and deck will produce potential hinge failure (secondary stress).




Figure 1.8 Potential Hinge locations (Patty et al, 2002)

In Malaysia, the design of the foundation for integral concrete box-girder bridge abutments have accounted for the expansion and contraction of the bridge due to thermal movement. The resulting soil pressures due to thermal expansion and restraining effects due to jointless construction of the bridge have been recognised as the controlling load for design of integral abutments and piles. Designing and detailing of integral abutments to handle these forces is critical for the proper performance of integral abutments. Based on Kerokoski and Laaksoneen (2005), the passive earth pressure on the integral abutment is estimated to be mobilized after a quite small abutment displacement in the range of 0.005 to 0.05 times height of the

wall is adequate. While according to a group of German researcher (Kerokoski, 2006), the displacement equal to $0.025 \times H$ is enough to mobilise half of the passive earth pressure, and that is also the recommended maximum displacement. Due to Weakley (2005), total movement at abutment of fully integral and semi-integral bridge is between 1.5 and 2.25 inch.

Therefore, the seismic performance study of integral concrete box-girder bridge is very important. For low and moderate seismicity areas like Malaysia, the movement of structure due to earthquake loading may possibly be larger than the movement due to thermal loading. In this study, the continuous concrete box-girder bridges are considered since many of this bridge type are constructed in Malaysia.

1.3 Problem Statement

Seismic performance of prestressed concrete box-girder bridge is needed in order to know the level of resistance in existing structures due to ground motion and also the effect of integral system on the bridge. The research will consider the local site response study as part of earthquake loading determination and soil- pile interaction. The performance result of the bridge will be useful for future prestressed box-girder bridge seismic design considerations.

Furthermore, research for determining the level of resistance toward earthquake hazard on the parameters of integral prestressed concrete box-girder bridge such as loading, span etc has not been carried out yet. There were no studies done on the effects of earthquake on integral bridges in Malaysia that are located near high seismic zone countries. Therefore, analysis is required to observe the effect and performance of prestressed integral concrete box-girder bridge toward seismic hazard.

Generally, the overall problems of this study are:

1. Unknown integral prestressed concrete box-girder bridge performance under earthquake loading with respect to Malaysia conditions.
2. Unknown soil-pile interaction effect versus fixed base support effect under earthquake loading for integral prestressed concrete box-girder bridge.
3. How correct is the current nonlinear Finite Element Analysis to perform the actual bridge performance under earthquake loading.

1.4 Objectives

The objectives of this research are as follow:

1. To perform 3D modelling for Integral and Non Integral prestressed concrete box-girder bridges for determining the nonlinear behaviour of bridge component under seismic loading.
2. To perform soil structure interaction effect as a major element in the seismic analysis and forces response impact by considering it.
3. To validate the results of numerical approach by conducting shaking table dynamic test.

1.5 Research Finding/ Expected Outcome

There are three expected outcome in this study. First, the performance of Integral prestressed concrete box-girder bridge can be decided whether the movement due to thermal loading can resist movement due to earthquake loading or vice versa. Second is the impact for considering pile in the integral bridge model and third is the effectiveness of finite element analysis to represent the actual bridge behaviour.

1.6 Scope and limitations

There are many parameters that may have effects on the results of analysis. Therefore the analysis is limited to the following scope:

1. Data collection and preparation:
 - a. Identifying existing continuous and integral prestressed concrete box-girder bridge.
 - b. Obtaining selected bridge drawing and soil data from Public Work department (PWD) and private C&S consultancy companies.
 - c. Obtaining material samples from only one Malaysian precast concrete factory.

2. Mechanical material properties study.
 - a. Conducting the laboratory tests: compressive strength, flexural strength, modulus elasticity, Poisson's ratio and nonlinear stress-strain curves relationship.

3. Parametric study.
 - a. Conducting the nonlinear seismic study for Kampung Sawah Bridge and Nordin Bridge
 - b. Implementing the nonlinear seismic analyses: nonlinear push-over analysis and nonlinear time history analysis by using SAP2000 V14.2.

4. Case study.
 - a. Conducting the case study for Kampung Sawah Bridge only.
 - b. Considering only P-y relationship (lateral soil resistance versus deflection relationship) for soil-pile interaction produced by using LPILE program.
 - c. Analysing soil dynamic properties on Kampung Sawah Bridge location.
 - d. Analysing one dimensional shearwave propagation analysis on Kampung Sawah Bridge Location by using NERA program.

- e. Generating artificial time histories for Kampung Sawah Bridge location for 500 years return period by using EZ-frisk and Simqke.
- f. Implementing the nonlinear seismic analyses: nonlinear pushover analysis and nonlinear time history analysis by using SAP2000 V14.2.

5. Bridge Model Verification of study.

- a. Modelling reinforced concrete box-girder bridge type which in this experimental work, the effect of prestressing tendon is neglected due to the small size of bridge model.
- b. Measuring the bridge responses by using accelerometer, strain gauge and LVDT.
- c. Conducting the tests by using ANCO R51 hydraulic shaking table.
- d. Scaling the bridge becomes 3 meters length.
- e. Conducting the dynamic tests at transversal direction only.
- f. Producing the additional table by using steel plate and stiffener.

1.7 Methodology

The research design of this thesis is shown in Figures 1.9, in which, the symbols I, O, and P stand for input, output and process of the analysis respectively, while the arrows show the flows of input required by the process and the output as a result of the analysis.




Figure 1.9 Methodology of research.

1.7.1 Data Collection

From Figure 1.9, there are some data collection and information required for the analysis: the sample of structural bridge material, bridge structural drawing for finite element modelling and the soil data for site specific analysis and soil-pile interaction analysis.

The modelling parameter of bridge study involved the collection and testing of material properties of bridge structure from factories in Malaysia. The materials collected were tested in laboratory to produce mechanical material properties and nonlinear stress- strain relationship. The mechanical material properties of prestressed concrete box-girder bridge are discussed in detail in Chapter 4.

The structural drawing of integral prestressed concrete box-girder bridges is required to model the finite element bridge. The structural drawings are collected from Public Works Department of Malaysia (JKR) and C&S consultancy (a private Malaysian company). The soil data or N_{SPT} data is required for producing soil dynamic parameter and soil-pile interaction parameter using empirical correlations.

In this research, the following activities were performed in order to obtain the required data for finite element modelling:

1. Collecting structural drawings for integral prestressed concrete box-girder bridge.
2. Collecting soil data or N_{SPT} value at abutments and piers at the bridge location.

The data were used to model the elements of bridge using a computer program. This study is described in detail in Chapters 5 and 6.

For result validation purposes, the experimental work is carried out to verify the accuracy of finite element modelling under seismic loading. The information required to implement this study is as follows:

1. Material properties of bridge model
2. Shaking table setting and capability information.

1.7.2 Analysis and Experimental Work

Generally, there are seven main processes performed in this experimental work as shown in Figure 1.9. Mechanical material properties laboratory test, Soil-pile interaction analysis, bridge finite element modelling, nonlinear seismic study, capacity of bridge component, shaking table experimental work and numerical study.

1.7.2.1 Mechanical Material Properties Laboratory Test

In this study, bridge materials are obtained from a Malaysian precast concrete factory. The laboratory tests conducted are compressive strength, flexural strength, modulus of elasticity, Poisson's ratio and stress-strain curve relationship.

The laboratory work was carried out in Structural and Material Laboratory of Universiti Teknologi Malaysia. In the investigation, all testing of the specimens was performed in accordance to the relevant British Standards, namely BS1881part 102, 116, 118 and 121.

For dynamic soil properties, the correlations of N_{SPT} soil data were used in this study since no laboratory work was carried out for soil parameters.

1.7.2.2 Soil – Pile Interaction

The soil-pile interaction analysis requires soil data such as soil stratigraphy, ground water level and soil dynamic properties. In this study, empirical relationships were used to determine the soil dynamic properties. In the seismic analysis of the bridge structures, the foundation stiffness is a major element. Given the interplay between superstructure and substructure responses of the bridge, realistic evaluation of total bridge response dictates the need for a practical and realistic model for assessing the stiffness of the bridge foundations. The foundation stiffness can be modelled by a set of springs that represents the stiffness of the foundations.

In this research, the following activities were performed in order to obtain soil stiffness inputs for soil-pile interaction study:

1. Collecting the standard soil penetration investigations and seismic tests at the bridge location.
2. Conducting the analysis by using existing soil data to obtain soil stiffness (p-y curves at every certain pile depth).

The correlated N_{spt} soil properties were used in order to determine dynamic soil properties in bridge location. The procedure for soil structure interaction is described in detail in Chapter 6.

1.7.2.3 Bridge Modelling

The non-linear seismic analysis of bridges was done using finite element software for its three dimensional modelling.

1. Pier, abutment, and pile using 3D beam element.
2. Box-girder deck using Shell element.
3. Bearing using Link element.
4. Pilecap is represented by a stiff constraint with lumped mass in the centroid.
5. Soil-pile interaction using lumped springs along the pile.

1.7.2.4 Non-linear Seismic Analysis

Non-linear seismic analysis is performed in order to obtain the performance of bridge component under damaging level of earthquake. Nonlinear seismic analyses implemented are non-linear push-over analysis and non-linear time history analysis.

1.7.2.5 Shaking Table Experimental Work

This experimental study is performed in order to validate the result of numerical approach. Four steps involved in experimental work are as follows:

1. Scaling integral concrete box-girder bridge by implementing Buckingham PI theorem.
2. Setting the shaking table, shaker controller, strain gauge, Load Varied Displacement Transducer (LVDT) and accelerometer.
3. Analysing finite element modelling of scaled integral concrete box-girder bridge
4. Validating the results by comparing the acceleration, displacement of structure response from instrument and finite element modelling.

1.7.2.6 Numerical Study of Cast Bridge Model

This study is performed to obtain a good prediction and verify the result of the experimental work by using SAP 2000 computer program.

1.8 Organisation of Theses

The connection between the methodology and each chapter is shown in Figure 1.10. The body of this document begins with Chapter 1; Introduction. Following this introductory chapter is Chapter 2 which representing a Literature Review of the past and present body of knowledge pertaining to integral prestressed concrete Box-Girder bridges. Chapter 3 presents the theoretical background of linear and nonlinear seismic analysis. Chapter 4 presents the laboratory results and discussion of materials used in the experimental test. Chapter 5 presents the parametric study for continuous deck and monolithic pier deck system. Chapter 6 presents the case study for selected bridge in Malaysia. Chapter 7 presents the

validation result by conducting experimental method by using shaking table. The Conclusions and Recommendations are presented in Chapter 8.




Figure 1.10 The organisation of thesis

The content of each chapter can be described briefly as follows:

- **Chapter 1: Introduction.** This chapter describes the background of the research, the objectives to be achieved, the research scopes, the methodology, and the structure of the thesis.
- **Chapter 2: Literature Review.** This chapter reviews and evaluates the topics which are related to earthquake engineering. This chapter presents how the integral prestressed concrete box-girder bridge components are modelled using finite element software including the effect of boundary condition and soil pile interaction. Literature study regarding nonlinear seismic bridge analysis and the bridge response under seismic loading are also discussed in this chapter.
- **Chapter 3: Theoretical Background.** This chapter describes the theory of seismic analysis for bridge under linear and nonlinear behaviour.
- **Chapter 4: Bridge Material Investigation.** In this chapter, the concrete, rebar, and tendon material for box-girder deck are collected from the precast concrete factory in Malaysia and tested in the laboratory so as to obtain reliable mechanical material properties data for the bridge modelling in Chapter 5 and 6
- **Chapter 5: Bridge Seismic Parametric Study.** The two types of integral prestressed concrete box-girder bridge modelling is the most critical point in seismic risk assessment. Hence, the bridge nonlinear behaviour is implemented in this chapter and requires the detailed understanding to model and analysis the bridge.
- **Chapter 6: Bridge Seismic Case Study.** This chapter analyses the selected existing integral prestressed concrete box-girder bridge in Malaysia under seismic loading. The soil-pile interaction are analysed to obtain the soil stiffness which requires for modelling purposes. The seismic loadings at bridge location are defined using local site effect analyses. The material mechanical properties from the laboratory testing in chapter 3 are applied in this seismic risk analyses.
- **Chapter 7: Result Validation.** This chapter describes the application of dimensional analysis to model and simplify the bridge. The performance of bridge under shaking table test in term of acceleration, displacement

and strain is compared with the numerical approach which verifies the accuracy of seismic analysis using finite element software.

- ***Chapter 8: Conclusions and Recommendations.*** This chapter concludes and summarises the results on the previous chapters and give recommendations for further study.