



Some Numerical Methods for Solving Stochastic Impulse Control in Natural Gas Storage Facilities

Leyla Ranjbari*, Arifah Bahar and Zainal Abdul Aziz

Department of Mathematics; Faculty of Science, UTM, 81310 UTM Skudai, Johor, Malaysia

Received 11 November 2011, Revised 25 December 2012, Accepted 9 January 2012, Available online 26 January 2012

ABSTRACT

The valuation of gas storage facilities is characterized as a stochastic impulse control problem with finite horizon resulting in Hamilton-Jacobi-Bellman (HJB) equations for the value function. In this context the two categories of solving schemes for optimal switching are discussed in a stochastic control framework. We reviewed some numerical methods which include approaches related to partial differential equations (PDEs), Markov chain approximation, nonparametric regression, quantization method and some practitioners' methods. This paper considers optimal switching problem arising in valuation of gas storage contracts for leasing the storage facilities, and investigates the recent developments as well as their advantages and disadvantages of each scheme based on dynamic programming principle (DPP).

| Gas storage facility | Stochastic impulse control problems | Optimal switching | Optimal stopping time | Semi-Lagrangian scheme | HJB equation, Viscosity solution |

© 2012 Ibnu Sina Institute. All rights reserved.

1. INTRODUCTION

In the natural gas industry, the modelling and valuation of leases on natural gas storage have been major concerns in the last decade, especially since deregulation of U.S. and Europe energy markets. In this flourishing market, manager/renter of gas storage facilities has been taking advantages of the fluctuation in market prices by releasing natural gas from storage in seasons with high demand. Recently, several authors have focused on solving this operational flexibility problem to maximize the revenue, by exploiting storage operational strategies. These studies, such as [1 through 20], have led to the consideration of the optimal switching models with timing flexibility. In 1997, Pilipovic [16] in her book, which is the first book on energy risk, studied the natural gas price models and storage valuation problem as a price swing straddle, which is an operational method by using the strips of spark-spread options approach such as being used in 2003 by Bringedal [2], Eydeland and Wolyniec [6] and Thompson, Davison and Hassmussen [18]. Also, by using real options approach, for instance gas storage can be reduced to a collection of calendar call options. Option pricing methods are intuitive and have fast computational speed of convergence, but it ignores key operational constraints such as dynamic capacity limits [7, 18].

Moreover, with reference to studies in [1 through 20], the valuation of gas storage facilities is characterized as

a stochastic control problem resulting in Hamilton-Jacobi-Bellman (HJB) equations. As shown in [21, 22], the value of a stochastic control problem is identical to the viscosity solution of a HJB equation. As a result, the value of a gas storage contract can be computed by solving the corresponding HJB equation using partial differential equation (PDE)-based approaches such as typically finite difference (FD) methods. It is important to ensure that a numerical scheme converges to the viscosity solution of the corresponding HJB equation. In 2003, Thompson et al. [18] used a Tsitsiklis and Van Roy (TvR) scheme as an explicit time stepping. The TvR scheme suffers from time step restrictions due to stability conditions. To overcome this difficulty, Chen and Forsyth [4, 5 and 23] introduced semi-Lagrangian time-stepping scheme. This implicit finite difference scheme has the same difficulty as the simulation-based methods [3, 11] for HJB equation with no bang-bang control, i.e., it is computationally expensive. A control that only takes from a finite set is called bang-bang control. To construct a suitable PDE solver, Ware and Li [20, 24] developed a wavelet method coupled with a semi-Lagrangian approach to solve the gas storage HJB equation. Although the wavelet method resolves this difficulty, the convergence proof is problematic. Due to the presence of inventory, the HJB equation is a degenerate PDE and shows the path-dependency of the methods. Also, the PDE methods depend on price models and suffer from dimensionality.

In Ludkovski thesis [11], he introduced the optimal switching approach which reduced the storage facility

*Corresponding author at:

E-mail addresses: leili_utm@yahoo.com.my (Leyla Ranjbari)

problem to an iterated optimal stopping time over a finite horizon. He developed a robust numerical scheme based on Longstaff-Schwartz Monte Carlo regression (LS) which outperforms the PDE approaches in aspect of dimensionality problems. Besides the capability of easily handling multi-dimensional problems, this scheme considers the operational constraints in the model. This simulation based methods [3, 11] can be used directly to solve the stochastic control problem with bang-bang type control. But, for the control which is not of bang-bang type, these methods are computationally expensive. Furthermore, simulation-based schemes have difficulty in achieving high accuracy [5].

In addition to PDE solver and simulation-based approaches, another prevalent approach is lattice or tree models [12, 15] which can be considered as stochastic programming approaches. As an example of these approaches, in [15], Parsons presented a two-factor tree approach for valuing natural gas storage leases. His tree model has been tested successfully against historical data to quantify the optionality in storage leases. Meanwhile, lattice/tree methods such as trinomial and binomial tree approaches [7, 15 and 18], are resulted from Bellman's optimal principle and used in real options due to being flexible, relatively simple and readily implemented in a computer program. Thus it can be widely used to evaluate options. However, trees cannot handle optimal exercise strategy problems arisen in natural gas storage [18]. There are two reasons for this. First, such trees are just explicit finite difference methods for solving parabolic PDEs. In the case of natural gas storage the operating characteristics lead to equations of a parabolic and hyperbolic nature. Since there are too many state variables in the problem, including the storage level, spot price, and forward prices, it is very difficult to solve the hyperbolic equations by tree models or by solving a finite difference equation [10]. Then to solve the hyperbolic equations, we need another technique more sophisticated than tree methods. Secondly, trees cannot handle price spikes properly [18].

2. NATURAL GAS STORAGE FACILITY

2.1 Introduction

The gas storage facility problem discusses about determining the value of gas storage contracts for leasing the storage facilities. Owners of storage facilities lease out space within, and a leaseholder has the right to inject into or withdraw from the facility only for a pre-specified period of time, and within pre-specified volume constraints, which are described through a ratchet schedule [15]. A ratchet schedule is a schedule of all possible inventory levels (or ratchets) and their associated daily maximum injection and withdrawal rates. As the lease-holder injects or withdraws, she tends to maximize the revenue by only exploiting storage operational strategies and cover the dealing costs of operating the facility. Owners/operators of storage facilities

are not necessarily the owners of the gas held in storage. Indeed, most working gas held in storage facilities is held under lease with shippers, local distribution companies (LDCs), or end users who own the gas. On the other hand, the type of entity that owns/operates the facility will determine to some extent how that facility's storage capacity is utilized.

2.2 Why we choose the salt cavern storage?

Among the underground storage facilities, i.e., depleted reservoirs in oil and/or gas fields, aquifers, salt cavern formations and artificial cavern, salt cavern is a common concern among researchers due to providing very high withdrawal and injection rates relative to their working gas capacity. Since 1993, the natural gas storage industry has attempted to profit from the changes of the market conditions. The deregulation of energy market allows using the storage facility to inject or withdraw as changes in price levels or arbitrage opportunities presents in the market. Therefore, the facilities with more rapid cycle in their inventories, i.e., completely withdraw and refill working gas or vice versa, are more suitable to the flexible operational needs of today's storage users. On the other hand, the maximum profit obtains from high deliverability storage sites, which include salt cavern storage reservoirs as well as some depleted oil or gas reservoirs due to the largest daily withdrawal capability, [18, 19].

2.3 Storage facility problem

In this section, the corresponding continuous-time stochastic impulse control is introduced, with the notations following Ludkovski's work [11]. This operational flexibility problem is modelled as an optimal switching with timing flexibility to maximize the revenue by exploiting storage operational strategies [1 through 20]. Before going into the problem, we suppose some assumption on owner and gas market.

2.3.1 Assumption on manager/renter

1. She is rational. The manager/renter makes choices based on her rational outlook, available information and past experiences. And, government policy does not influence on her decisions. In this idea if the owner of storage facility believes that the price for gas will be higher in the future, it will stop or slow supply until the price rises. Consequently, the demand stays the same and gas prices will increase. In sum, the producer believes that the price will rise in the future, makes a rational decision to slow production and this decision partially affect what happens in the future. In conclusion, these rational expectations of the players will partially affect what happens to the economy in the future.
2. She is risk-neutral. Risk-neutral investor is only concerned with an investment's expected return and overlooks risk in her investments.

3. She is concerned to maximize the value function of her lease agreement over a finite time.
4. She is a price-taker. Her buying or selling transactions have no effect on the market in a form of monopoly. The owner can alter the injection and withdrawal rates without significantly affecting the market price of natural gas, [3].

2.3.2 Assumption on gas market

1. Market is liquid. In this market, due to high level of trading, trading does not affect the gas price. And, the gas can be easily sold or bought that reflects the ability to convert the gas to cash quickly or being marketability. Then, it is safer to invest in liquid assets than illiquid ones because it is easier for an investor to get his/her money out of the investment. We can say that the higher liquidity, the lower spread and volatility. Although there is no specific liquidity formula, liquidity ratios is used as a measure of liquidity.
2. Market is fairly liberal, i.e., all participants have the opportunity to rent a storage facility to speculate and take the advantages of the volatility in prices to maximize the profit.
3. Gas market shows a strong seasonality which leads to intrinsic value of storage. To buy in low price, the owner locks-in forward contracts and sell in high price in heating/cooling days.

2.3.3 Stochastic impulse control

We study the following optimal switching problem from Carmona and Ludkovski's work [3] as the storage facility model, with no changes or supplements. In advance, we label the three above operational strategies in the way that injection (-1), store or doing nothing (0) and withdrawal (1), i.e., we have three operational regimes $i \in \{-1,0,1\}$ by the payoff rate $\psi_i(t, G_t, C_t)$ in $\frac{\$}{year}$ from running the facility in regime i .

$$\left\{ \begin{array}{l} \text{Inject: } \psi_{-1}(t, G_t, C_t) = -G_t \cdot b_{in} - K_{-1}(C_t), \\ \quad \quad \quad dC_t = a_{in}(C_t)dt \quad (1) \\ \\ \text{Store: } \psi_0(t, G_t, C_t) = -K_0(C_t), \\ \quad \quad \quad dC_t = a_0(C_t)dt \quad (2) \\ \\ \text{Withdraw: } \psi_1(t, G_t, C_t) = G_t \cdot b_{out} - K_1(C_t), \\ \quad \quad \quad dC_t = -a_{out}(C_t)dt \quad (3) \end{array} \right.$$

where

- Time horizon T , the life time of leasing agreement of the facility,

- $(G_t), G_t \in \mathbb{R}^d$, Market gas prices given by a Markov continuous-time stochastic process quoted in dollars per million of British thermal units (MMBtu), with 1 (billion cubic feet) Bcf = 10^6 MMBtu.
- Level of inventory in storage denoted by C_t .
- Finite cave capacity represented by $C_{min} \leq C_t \leq C_{max}$.
- Constant discount (interest) rate r .
- Denote the injection rate by $a_{in}(C_t)$, quoted in Bcf per day. Injection of $a_{in}(C_t)$ Bcf of gas requires the purchase of $b_{in}(C_t) \geq a_{in}(C_t)$ Bcf on the open market.
- Similarly the withdrawal rate is labelled $a_{out}(C_t)$ and causes a market sale of $b_{out}(C_t) \leq a_{out}C_t$ Bcf.
- Capacity charges $K_i(t, C_t)$ in each regime.
- The case $b_i \neq a_i$ indicates gas loss during injection/withdrawal (typically on the scale of 0.25%–1% for salt dome storage). The transmission rates a_i, b_i are a function of C_t and are based on gas pressure laws.

The available strategies to the manager are specified via the set of admissible control U of possible storage policies u . For $t \in [0, T], u_t \in \{-1, 0, 1\}$ denotes the operating regime of the facility. The policy u is typically written $u = (\xi_1, \xi_2, \xi_3, \dots; \tau_1, \tau_2, \tau_3, \dots)$, where the variables $\xi_k \in \{-1, 0, 1\}$ denote the sequence of operating regimes taken by u , while $\tau_k \leq \tau_{k+1} \leq T$ denote the switching times. Thus, $u_t = \sum_k \mathbb{1}_{[\tau_k, \tau_{k+1})}(t)$, where by convention

$\tau_0 = 0, \xi_0 = i_0$ is the initial facility state.

Given the initial inventory $C_0 = c$ and the storage strategy u , the future inventory $\bar{C}_t(u)$ is completely determined. Namely, $\bar{C}_t(u)$ satisfies the ordinary differential equation

$$d\bar{C}_s(u) = a_{u_s}(\bar{C}_s(u))ds, \quad \bar{C}_0(u) = c \quad (4)$$

In addition, we also use the following notation.

$$\bar{C}_t(c, i) \triangleq c + \int_0^t a_i(\bar{C}_s(c, i))ds \quad (5)$$

Each change of the facility's regime incurs switching costs. In particular, moving the facility from regime i to regime j costs $K_{i,j} = K(i, j; t, G_t, C_t)$. We assume that the switching costs are discrete: $K_{i,j} \geq \varepsilon$ for all $i \neq j$ and some $\varepsilon > 0$, and $K_{i,i=0}$. In this research, among the storage facilities we only focus on salt dome facilities the switching costs are economically negligible; however, in other facilities, switching costs may be significant. Also, switching costs are assumed strictly positive so that it prohibits the owner would repeatedly change the regimes back-and-forth over a very short time. Since the ultimate computations are in discrete time, switching costs can be set to zero on implementation-level.

A necessary condition for u to belong to the set U of admissible strategies is to be \mathbb{F} -adapted, right-continuous and of \mathbb{P} -a.s. finite variation on $[0, T]$. \mathbb{F} -adaptiveness is a standard condition implying that the agent only has access to the observed price process and cannot use any other information. Finite variation means that the number of switching decisions must be finite almost surely. Thus, $\mathbb{P}(\tau_k < T \forall k \geq 0) = 0$. Besides, u must satisfy the model's restrictions; for example the finite storage constraint requires that $\bar{C}_t(u) \in [c_{min}, c_{max}]$ for all $t \leq T$. Further we assume that $U(t, c, i)$, representing the set of all admissible strategies on the time interval $[t, T]$ starting in regime i and with initial inventory c , is a closed subset of U .

Subject to those costs and the operational constraints, the facility manager maximizes the net expected profit. Given initial conditions at time t , $G_t = g, C_t = c$ and initial operating regime i , suppose the manager chooses a particular dispatching policy $u \in U(t, c, i)$. If we denote by $V(t, g, c, i; u)$ the corresponding expected profit until final date T , then

$$V(t, g, c, i; u) = E \left(\int_t^T e^{-r(s-t)} \psi_{u_s}(G_s, \bar{C}_s(u)) ds - \sum_{\tau_k < T} e^{-r\tau_k} K_{u_{\tau_k^-}, u_{\tau_k}} \middle| G_t = g, C_t = c \right) \tag{6}$$

where the first term above counts the total revenues from running the facility up to the horizon T and the second term counts the incurred switching costs. Thus the control problem is computing

$$V(t, g, c, i) \triangleq \sup_{u \in U(t, c, i)} V(t, g, c, i; u) \tag{7}$$

with $V(t, g, c, i; u)$ as defined in (6). Besides the value function V , an optimal policy u^* is characterized. If u^* exists, it achieves the supremum in (7).

To specify the terminal condition at T , one needs to enforce some conditions involved in contract. In typical contracts, the facility should be returned with the same inventory C_0 as initially held, and in certain state, e.g. store. A common condition, such as below (8), may make the penalty proportional to the difference with stipulated inventory C_0 , with multipliers \bar{K}_1 and \bar{K}_2 used for under-delivery and over-delivery respectively, and adding a second penalty of \bar{K}_3 if the final regime is not store.

$$V(T, g, c, i; C_0) = -\bar{K}_1 \cdot (C_0 - c)^+ - \bar{K}_2 \cdot (C_0 - c)^- - \bar{K}_3 \mathbb{1}_{i \neq 0} \tag{8}$$

Another common choice is $V(T, g, c, i; C_0) = -\bar{K}_1 \cdot g \cdot (C_0 - c)^+$, which penalizes for having less gas than originally and makes the penalty proportional to current price of gas.

Remark. Natural gas spot price process G_t represents the price at time t of the near-month forward contract, which is by far the most liquid contract on the market. It makes some

difficulty that the sale price in forward contract is locked-in in advance, while the inventory only changes at delivery time. Thus, we assume for simplicity that any purchase or sale is immediately reflected in the current inventory.

2.3.3 Assumption on gas spot price process

- (A) The process (G_t) is a d -dimensional, strong Markov, non-exploding process in \mathbb{R}^d .
- (B) The information filtration $\mathbb{F} = (\mathcal{F}_t)$ on the stochastic basis (Ω, \mathcal{F}, P) is the natural filtration of (G_t) .
- (C) The reward rate $\psi_i: [0, T] \times \mathbb{R}^d \times [c_{min}, c_{max}] \rightarrow \mathbb{R}$ is a jointly Lipschitz-continuous function of (t, g, c) and satisfies

$$E(\sup_{t \in [0, T]} |\psi_i(t, G_t, C_t)|^2 | G_0 = g, C_0 = c) < \infty \quad \forall g, c. \tag{9}$$

For notational clarity we suppress from now on the dependency of ψ_i and the coefficients of (9) on time t .

3. NUMERICAL SOLUTIONS

3.1 Introduction

To achieve numerical solutions of the corresponding optimal switching problem (6-7), we can consider one of the following strategies:

1. To directly tackle the quasi-variational (QV) formulation.
2. To replace the continuous-space process by some sort of discrete approximation.
3. To compute the conditional expectations appeared in value function with various methods.

These strategies lead to obtain the following numerical methods:

1. PDE approaches
2. Markov chain approximation
3. Nonparametric regressions
4. Quantization method

3.2 PDE approaches

Tsitsiklis and Van Roy (TvR) [18] introduced an explicit PDE approach and in [4, 23 and 25], they developed semi-Lagrangian time-stepping as an implicit FD scheme.

Since the optimal switching is a special case of impulse control, one can use the classical methods of solving stochastic impulse control problems which relates to studying the parabolic partial differential equations (PDEs)

resulted from applying Bellman’s optimal principle. In fact, a smooth solution of the quasi-variational Hamilton-Jacobi-Bellman (HJB) inequality is the value function of the impulse control problem. To prove the uniqueness of solutions, the notion of viscosity solutions is used as weak solutions. Indeed, the value function is always the unique viscosity solution of the system in verification theorem [11, 22 and 26]. The PDE solver relies on the quasi-variational formulation of verification theorem. Generally speaking, the PDE methods transform the stochastic control problem into a parabolic partial differential equation with a free boundary. To solve this parabolic PDE, there are a variety of tools such as the basic finite difference scheme (FD). By setting up a space-time grid, we solve the PDE by replacing derivatives with finite differences in the HJB equation and directly enforcing the barrier condition at each step. In spite of being the simplest setting, the approaches pose a multitude of challenges that prevent rigorous solutions. An FD method is easy to implement but suffers several major drawbacks. First, FD often needs a large number of time steps to be of numerical stability. Second, the method suffers from dimensionality problem: the size of the space grid is exponential in number of dimensions of price process d and generally speaking $d > 3$ is computationally infeasible. Finally, the switching boundary will inevitably be jagged due to the presence of a grid in the x -space. The last point can be alleviated with the use of an adaptive grid. The method’s accuracy depends on the order of the approximation used for the derivatives of u , which should be at least $O(\Delta t + \Delta x^2)$.

3.3 Markov chain approximation

The Markov chain approximation method, corresponding the second strategy, pioneered by Kushner [9] consists in replacing (X_t) by a continuous time Markov chain (\tilde{X}_t) with a finite state space \tilde{E} , such that its transition probabilities of (\tilde{X}_t) are consistent with the dynamics of (X_t) . Since the transition probabilities are computed through the infinitesimal generator of (X_t) , one needs to use the finite differences approximations of the HJB equation such as the PDE approaches. The formula (6) can also be re-written in probabilistic form as

$$\hat{V}(m\Delta t, x, c, i; u) = \sum_{y \in \tilde{E}} P_m(x, y) \cdot \hat{V}(m\Delta t, y, c, i; u) + P_m(x, x) \cdot V((m + 1)\Delta t, x, c, i; u) \tag{10}$$

where $P_m(x, y)$ indicates the transition probability of (\tilde{X}_t) , going from $(x, m\Delta t)$ to $(y, (m + 1)\Delta t)$ for any $x, y \in \tilde{E} = \{x_0 + n\Delta x\} \subset E$, and $\hat{V}(t_1, x, c, i; u) = \mathbb{E}(V(t_2, X_{t_2}, c, i; u) | X_{t_1} = x)$. Solving (10) only needs to invert the tri-diagonal matrix $\mathbb{P}_m = P_m(x, y)$. Like the PDE solver, this algorithm suffers from the curse of dimensionality and is not robust to extensions. Nevertheless, in low dimensions it provides a reliable benchmark.

3.4 Nonparametric regressions

This approach is related to the third strategy as we mentioned before to compute the conditional expectations. To compute the conditional expectation, there are several methods, including Malliavin calculus, Monte Carlo simulations and regression. In regression schemes we have a choice between regression against basis functions and fully non-parametric regression. Choosing a non-parametric regression relieves us of the concerns regarding selecting appropriate basis functions and may produce smoother conditional distributions [11]. The simplest version of this approach is k -nearest neighbours multivariate kernel regression. Thus, this regression is replaced by a local linear combination of the other paths’ values with the weights proportional to the distance. The use of nearest neighbours reduces the dimensionality difficulty. It is attractive due to its robustness and involving no additional error. However, the two major difficulties with the kernel method are selecting an appropriate bandwidth and the computations around the edges. The bandwidth h controls the peak of the weights around (x, y) . Thus, as the bandwidth increases, more distant points carry more weight and the estimate becomes more ‘global’. However, choosing h is heuristic and may require a lot of trial-and-error. The other difficulty is when the regressed *value* is extreme; the nearest neighbours have bias for the extreme values in contradiction to regression algorithm.

3.5 Quantization method

A powerful non-Markovian version of the second strategy, i.e., replacing the continuous-space process by a discrete approximation, with an adaptive approximating grid is the so-called Quantization Scheme (QS). The main motivation of quantization is to find a small and efficient approximating grid in exchange for giving up the Markov property and closed-form formulae for transition probability matrix $\mathbb{P}_m = P_m(x, y)$. This method instead of computing \mathbb{P}_m via PDE solver such as FD, uses Monte Carlo simulation. While this is likely to be slow, it can be done just once off-line and stored for later calculations. The gain will increase the robustness and results in much better dimensional scaling. The transition matrix is required to approximate closely the dynamics of between cells of the adjacent quantization grids. The quantization scheme can be summarized in these following stages:

1. Construct the quantization grid by Voronoi tessellations (cells) as a partition of state space E .
2. Simulate (\tilde{E}, \tilde{P}) with, for instance, Competitive Learning Vector Quantizer (CLVQ) algorithm.
3. Solve the optimal switching problem by computing the pseudo-Snell envelopes of the non-Markov (\tilde{X}_t) .

The advantageous of the quantization scheme can be mentioned as:

1. Since the entire algorithm for constructing (\tilde{X}_t) is Monte Carlo based, it is considered to be robust.
2. Simulation can be parallelized.

3. Once the grids and transition are computed, any control problem is solved because the approximation of (\tilde{X}_t) is independent from the optimization steps in contrast to regression algorithm.

However, there are some drawbacks to the method:

1. Estimation of the transition probability \tilde{P} is problematic.
2. To achieve an acceptable accuracy, the method needs to run in large number of simulations.

Ludkovski [3, 11] replaced the optimal switching problem with finite horizon by a recursive optimal stopping problems in finite time. Then, the exponential maturity randomization was used to construct the iterative sequence of infinite horizon stopping times. In stead of directly solving the obtained iterative problems, he used LS Monte Carlo regression scheme to compute the conditional expectation by exploiting the concept of Snell envelopes for revenue functions.

4. PRACTITIONER METHODS

Besides these methods, there are some practitioner methods to solve the operational flexibility problem of natural gas storage facility which are mentioned in the following:

4.1 Classical net present value (NPV) theory

In Dixit [27], he used discounted cash flow analysis to estimate the value of the asset based on projections of future prices and proper weighing and discounting of possible cases. Uncertainty was essentially eliminated, as static scenarios were used to forecast the future and select pre-determined optimal behaviour. The opportunity of dynamically responding to prices was ignored and as a result the contracts were consistently underpriced.

4.2 Markov decision process (MDP)

This is a stochastic programming approach implemented in Yushkevich [28]. In MDP, we have the tree-based versions of the stochastic control formulation, and there exist sequential decision problems under uncertainty. The problem is discretized in time and the path space of (X_t) is broken into a finite number of actions. Then the transition probabilities $P(x, y, \Delta t)$ are estimated for each current outcome x and possible transition action y . Finally, the problem is solved via dynamic programming that corresponds to a lattice discretization of the Quasi-Variational Inequality (QVI). Indeed, MDP or stochastic programming approach is a dynamic construction of the decision tree. The goals of using MDP are mentioned in below:

- (A) In finite horizon problem, the aim is to maximize the expected reward for the next n steps.
- (B) In infinite horizon, maximizing the expected discounted reward is considered.

The MDP tree is simple and intuitive to understand. However, if one must solve numerically then the computational complexity explodes for long horizons with much optionality.

4.3 Strips of spark-spread options approach

This approach is being carried out in Bringedal [2], Eydeland and Wolyniec [6] and Thompson, Davidson and Rassmussen [18]. The motivation is to reduce the problem to pricing standard financial options whose valuation is well understood. Accordingly, the payoff from the power plant is represented as a collection of European options that pay the maximum value to be obtained during each period. This method is intuitive and have fast computational speed of convergence, but it ignores key operational constraints such as dynamic capacity limits.

5. CONCLUSION

As a comparison for the numerical methods considered in this paper, one can mention that in small dimensions ($d < 3$) the best algorithm is the PDE approach such as semi-Lagrangian and TvR schemes. Otherwise, for $d > 2$, the LS and Quantization schemes should be used due to scalability to high dimensional problems. An industrial-strength implementation should be very fast and produce provable accurate results. And, to choose between LS and quantization schemes, if one is looking for a quick tool to solve optimal switching for a variety of (X_t) , the LS scheme is the best. On the other hand, if (X_t) is fixed, the quantization may be better.

ACKNOWLEDGEMENT

Leyla is thankful to SPS, UTM for financial support

REFERENCES

- [1] A. Boogert and C. De Jong, Gas storage valuation using a Monte Carlo method. Birkbeck Working Papers in Economics and Finance 0704, Birkbeck, School of Economics, Mathematics and Statistics. 2007.
- [2] A. Bringedal, Valuation of Gas Storage, a real options approach. NTNU. 2003.
- [3] R. Carmona and M. Ludkovski, Gas storage and supply guarantees: An optimal switching approach, Quantitative Finance, 10(4)(2010), 359-374.
- [4] Z. Chen and P. Forsyth, Implication of regime-switching model on natural gas storage valuation and optimal operation, Quantitative Finance, 10(2)(2010), 159-176.
- [5] Z. Chen and P. Forsyth, A semi-Lagrangian approach for natural gas storage valuation and optimal operation. To appear in SIAM Journal on Scientific Computing (2006).
- [6] A. Eydeland and K. Wolyniec, Energy and Power Risk Management, New Developments in Modelling Pricing and Hedging. Wiley. 2003.
- [7] Y. He, *Real options in the energy markets*. Ph.D. Thesis, University of Twente, 2007.

- [8] S. Hiksipoors and S. Jaimungal, Energy Spot Price Models and Spread Options Pricing. Commodities, Birkbeck College, University of London, 2007.
- [9] V. Kaminski, Y. Feng and Z.Pang, Value, Trading Strategies and Financial Investment of Natural Gas Storage Assets, Northern Finance Association Conference, Kananaskis, Canada. 2008.
- [10] Y. Li, Natural Gas Storage evaluation. Master's thesis, Georgia Tech, 2006.
- [11] M. Ludkovski, Optimal switching with application to energy tolling agreements. Ph.D. Thesis, Princeton University; 2005.
- [12] M. Manoliu, Storage Options Valuation Using Multilevel Trees and Calendar Spreads." International Journal of Theoretical and Applied Finance (2004), 425-464.
- [13] S. Nadarajah, F. Margot and N. Secomandi, Approximate dynamic programs for natural gas storage valuation based on approximate linear programming relaxations. Tepper working paper 2011-E5, 2011.
- [14] L.T. Ndounkeu, *Stochastic Control: With Applications to Financial Mathematics*. Ph.D. Thesis. African Institute for Mathematical Sciences (AIMS) South Africa, 2010.
- [15] C. Parsons, Quantifying natural gas storage optionality: A two-factor tree model, preprint, 2011.
- [16] D. Pilipovic, Energy Risk: Valuing and Managing Energy Derivatives. McGraw-Hill, 1997.
- [17] D. Pilipovic, Energy Risk: Valuing and Managing Energy derivatives. Second edition, McGraw-Hill, New York, 2007.
- [18] M. Thompson, M. Davison and H. Rasmussen, Natural gas storage valuation and optimization: a real options application. Working paper, University of Western Ontario, 2003.
- [19] A. Ware, Accurate semi-Lagrangian time stepping for gas storage problems. Fields Institute, University of Calgary, 2010.
- [20] A. Ware and H. Li, Natural gas storage and swing option pricing using adaptive wavelet collocation. Presented at the Oxford Centre for Industrial and Applied Mathematics Mathematical and Computational Finance Group Seminar, 2007.
- [21] W.H. Fleming and H.M. Soner, Controlled Markov processes and viscosity solutions. Springer, 2006.
- [22] H. Pham, On some recent aspects of stochastic control and their applications. *Probability Surveys*, 2(2005), 506–549.
- [23] Z. Chen, Numerical Methods for Optimal Stochastic Control in Finance. Ph.D. Thesis in Computer Science. University of Waterloo, Ontario, Canada, 2008.
- [24] H. Li, Adaptive wavelet collocation methods for option pricing PDEs. Ph.D. Thesis. University of Calgary, 2006.
- [25] R. Carmona and M. Ludkovski, Spot convenience yield models for the energy markets. In G. Yin and Y. Zhang, editors. AMS Mathematics of Finance, *Contemporary Mathematics*, 351(2004), 65-80.
- [26] H. Pham, Continuous-time stochastic control and optimization with financial applications, Springer-Verlag Berlin Heidelberg, 2009.
- [27] A. Dixit, Entry and exit decisions under uncertainty. *Journal of Political Economy*, 97(3)(1989), 620–638.
- [28] A. Yushkevich, Optimal switching problem for countable Markov chains: average reward criterion. *Math. Methods Oper. Res.*, 53(1)(2001), 1-24.