

SLOW PYROLYSIS OF *IMPERATA CYLINDRICA* IN A FIXED BED REACTOR

AZDUWIN BINTI KHASRI

A thesis submitted in fulfilment of the  
requirements for the award of the  
Master of Engineering (Chemical)

Faculty of Chemical Engineering  
Universiti Teknologi Malaysia

JULY 2012

To my beloved husband, mother and father

## **ACKNOWLEDGEMENT**

A million thanks goes to my supervisor Dr. Tuan Amran Tuan Abdullah for his guidance, and encouragement to complete my dissertation. He gave full cooperation and helps to ensure the progress of this dissertation run smoothly and successfully. I wish to express my appreciation to all the technician and lab assistant as well for helping me in doing the experiments.

I am also indebted to University Malaysia Perlis together with Ministry of Higher Education for funding my Master study. Without their fund, it is impossible for me to further study and complete my dissertation project. Other than that, special thanks to my beloved husband Mohd Ridzuan Mohd Jamir, my laboratory partner Redza Shah Azmeer Hasanudin, all my family members, colleagues, and friends for their advice, and support. Hopefully, this thesis will benefit all of us.

## ABSTRACT

Slow pyrolysis of *Imperata Cylindrica* has been conducted in a fixed bed reactor to determine the effect of temperature and particle sizes towards the product yield. The characterization of the *Imperata Cylindrica* has been analysed using several instruments such as Thermogravimetric Analysis (TGA), Carbon Hydrogen Nitrogen Sulfur and Oxygen (CHNS/O) analyzer, Bomb Calorimeter, and several analytical methods. Pyrolysis experiments were performed at temperature between 450- 600 °C, and particle sizes of 0.25-1.00 mm with constant nitrogen flow rate of 100 cm<sup>3</sup>min<sup>-1</sup> and heating rate of 22 °C . min<sup>-1</sup> (slow mode). The highest liquid oil yield obtained was 20.88 % at temperature 500 °C, with particle size of 0.5-1.0 mm, and heating rate of 22 °C . min<sup>-1</sup>. The obtained yield of liquid, solid and gas from pyrolysis were found in the range of 3.25-20.88 %, 22.63-30.50 % and 49.13-74.13 % respectively at different pyrolysis conditions. Liquid bio-oil produced from the pyrolysis of *Imperata Cylindrica* shows high water content in the range of 58.09-72.74 % which was checked using Karl Fisher Titration. From Gas Chromatography-Mass Spectrometry (GC-MS), the chemical components present in the liquid oil from pyrolysis of *Imperata cylindrica* include acids, phenols, ketones, aldehydes, ethers, and some species of aromatics.

## ABSTRAK

Pirolisis perlahan *Imperata cylindrica* telah dijalankan di dalam reaktor katil tetap untuk menentukan kesan suhu dan saiz zarah terhadap hasil produk. Pencirian *cylindrica* Imperata telah dianalisis dengan menggunakan beberapa instrumen seperti Termogravimetri Analisis (TGA), Penganalisa Sulfur Nitrogen Karbon Hidrogen dan Oksigen (CHNS/O), Bom Kalorimeter, dan beberapa kaedah analisis. Eksperimen pirolisis telah dijalankan pada suhu antara 450-600 ° C, dan saiz zarah 0.25-1.00 mm dengan kadar aliran nitrogen malar 100 cm<sup>3</sup>. min<sup>-1</sup> dan kadar pemanasan 22 ° C . min<sup>-1</sup> (mod perlahan). Hasil minyak cecair tertinggi yang diperolehi adalah 20.88 % pada suhu 500 °C, dengan saiz zarah 0.5-1.0 mm, dan kadar pemanasan 22 ° C . min<sup>-1</sup>. Hasil yang diperolehi cecair, pepejal dan gas daripada pirolisis ditemui dalam julat 3.25-20.88 %, 22.63-30.50 % dan 49.13-74.13 % masing-masing pada keadaan pirolisis yang berbeza. Cecair bio-minyak yang dihasilkan daripada pirolisis *Imperata cylindrica* menunjukkan kandungan air yang tinggi dalam julat 58.09-72.74 % yang telah diperiksa menggunakan Pentitratan Karl Fisher. Daripada Gas Kromatografi-Jisim Spektrometri (GC-MS), komponen kimia yang hadir dalam minyak cecair daripada pirolisis Imperata cylindrica termasuk asid, fenol, keton, aldehid, eter, dan beberapa spesies aromatik.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATIONS	xiii
	LIST OF SYMBOLS	xiv
	LIST OF APPENDICES	xv
 1	 INTRODUCTION	
	1.1 General Background	1
	1.2 Problem statement	2
	1.3 Objectives	3
	1.4 Scopes of research	4
	1.5 Hypothesis	4
	1.6 Significant of Research	5

1.7 Thesis Organisation	6
<b>2 LITERATURE REVIEW</b>	
2.1 <i>Imperata Cylindrica</i>	7
2.1.1 Introduction	7
2.1.2 Cultivation	8
2.1.3 Usage	8
2.2 Characterization of biomass	8
2.3 Pyrolysis	11
2.3.1 Type of Pyrolysis	12
2.3.1.1 Conventional(slow) Pyrolysis	13
2.3.1.2 Fast Pyrolysis	16
2.3.1.3 Flash Pyrolysis	17
2.3.2 Pyrolysis feed stock	18
2.3.3 Process features and requirements	19
2.3.3.1 Reactor configuration	19
2.3.3.2 Heat transfer	20
2.3.3.3 Char removal	20
2.3.3.4 Liquids collection	21
2.3.3.5 By-products	22
2.4 Pyrolysis liquid (bio-oil)	23
2.4.1 Physicochemical properties	23
2.4.1.1 Water content	24
2.4.1.2 Oxygen	25
2.4.1.3 Viscosity	26
2.4.1.4 Acidity	26
2.4.1.5 Heating Value	26
2.4.1.6 Ash	27
<b>3 RESEARCH METHODOLOGY</b>	
3.1 Feedstock sample and preparation	28
3.2 Apparatus	29
3.3 Chemicals	29

3.4	Characterization of Biomass	29
3.4.1	Proximate analysis	30
3.4.2	Ultimate Analysis	30
3.4.3	Component Analysis	31
3.4.3.1	Analysis of extractives	31
3.4.3.2	Analysis of hemicellulose	31
3.4.3.3	Analysis of lignin	33
3.4.3.4	Analysis of cellulose	33
3.4.4	Heating value Analysis	34
3.5	Pyrolysis Procedure	35
3.6	Bio-oil analysis	39
3.6.1	GC-MS	40
3.6.2	Water content	40
<b>4</b>	<b>RESULTS AND DISCUSSION</b>	
4.1	Characterization of <i>Imperata Cylindrica</i>	41
4.1.1	Proximate Analysis	41
4.1.2	Ultimate Analysis	44
4.1.3	Component Analysis	45
4.1.4	Heating value Analysis	47
4.2	Pyrolysis Experimental	49
4.3	Bio-oil Analysis	55
4.3.1	Water content	55
4.3.2	GC-MS	57
<b>5</b>	<b>CONCLUSIONS AND RECOMMENDATIONS</b>	62
5.1	Conclusions	62
5.2	Recommendations	63
	<b>REFERENCES</b>	65
	<b>Appendices A-C</b>	70-77



## LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	The main operating parameters for different type of pyrolysis	12
2.2	Characterization analysis of Rice husk	14
2.3	Various type of reactor used for pyrolysis and the heating method	19
2.4	Comparison of common properties of bio-oil (wood biomass) and Heavy fuel oil	24
4.1	Proximate analysis of <i>Imperata cylindrica</i>	43
4.2	Ultimate analysis of <i>Imperata Cylindrica</i>	46
4.3	Result data for component analysis calculation	47
4.4	Component analysis of <i>Imperata Cylindrica</i>	48
4.5	Heating value of <i>Imperata Cylindrica</i>	49
4.6	Characterization of <i>Imperata Cylindrica</i>	49
4.7	Product yield and conversion of <i>Imperata Cylindrica</i>	52
4.8	Functional group presents in <i>Imperata Cylindrica</i> liquid oil	59
4.9	Summary of component present in all samples analyzed by GC-MS	60

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Selective parameters of biomass characterization	9
2.2	Pyrolyser set-up of rice husk experiment	14
2.3	Effect of temperature on slow pyrolysis of Rice husk	15
2.4	Effect of Particle size on slow pyrolysis of Rice husk	16
3.1	Sample of <i>Imperata Cylindrica</i>	29
3.2	Flow chart of Characterization analysis	31
3.3	Residue of G <sub>1</sub>	34
3.4	Residue of G <sub>2</sub>	34
3.5	A bomb Calorimeter	36
3.6	Pyrolysis experimental set-up	37
3.7	Flow chart of pyrolysis experimental for first run	39
3.8	Flow chart of pyrolysis experimental for second run	40
3.9	Karl Fisher Titration	41
4.1	The proximate analysis	44
4.2	TGA and DTG curves for <i>Imperata Cylindrica</i>	44
4.3	Pyrolysis set-up	51
4.4	Liquid oil	51
4.5	Solid char	51
4.6	Effect of temperature on slow pyrolysis of <i>Imperata Cylindrica</i>	54
4.7	Effect of particle size on slow pyrolysis of <i>Imperata Cylindrica</i>	55
4.8	Water content of liquid oil for different pyrolysis	57

	temperature	
4.9	Water content of liquid oil for different particle size	57

## LIST OF ABBREVIATIONS

VM	-	Volatile Matter
FC	-	Fixed Carbon
Ad	-	Air dried
TGA	-	Thermogravimetric Analysis
GC-MS	-	Gas Chromatography Mass Spectrometry
CHNS/O	-	Carbon, Hydrogen, Nitrogen, Sulfur, Oxygen
HHV	-	High heating Value
LHV	-	Low Heating value
UTM	-	University Technology Malaysia

**LIST OF SYMBOLS**

°C	-	degree celcius
<i>wt. %</i>	-	weight percent
D	-	Diameter
T	-	Temperature
g	-	gram
min	-	min
mm	-	milimeter
t	-	time

**LIST OF APPENDICES**

<b>Appendix</b>	<b>TITLE</b>	<b>PAGE</b>
A	GC-MS Results Component Peak	71
B	Mole Fraction Of The Selected Components In Liquid Bio-Oil	75

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 General Background**

Nowadays, biomass has widely acknowledged as a source of alternative energies, which are more sustainable due to its great potential compared to fossil fuel in satisfying environmental aspects. And the most important, these kinds of alternative energy providing the only supply of renewable solid, liquid and gaseous fuels (Bridgwater, 2002).

Recently, there have been lots of studies in the field of thermo chemical conversion of biomass into liquid, gaseous or solid products. There are three types of thermal conversion technologies, which are combustion, gasification, and pyrolysis. Among all the process, pyrolysis is still at premature stage of improvement. Pyrolysis can be categorized in two modes process, which are slow pyrolysis and fast pyrolysis, which depends on the operational and also the main product where for fast pyrolysis the main product is bio-oil, and for slow pyrolysis the main product is char (Bridgwater, 1997).

In general, all types of biomass can be thermo chemically converted into bio-oil. In this work, *Imperata cylindrica* or also known as ‘*lalang*’ in Malaysia, were chosen as biomass feedstock since they are available in large quantity throughout the tropical and subtropical regions of the world. The bio-oil or liquid fuel produced from the pyrolysis process has wide application as a fuel and also for the production of various types of chemicals.

## 1.2 Problem Statement

Slow pyrolysis is often related to the production of charcoal while fast pyrolysis was related with production of bio-oil. Bridgwater (2003) have shown that slow pyrolysis of biomass will produce high content of charcoal. Researches in the world are more focusing on fast pyrolysis since it was the promising routes in producing bio-oil and this have cause neglecting of conventional (slow) pyrolysis process although slow pyrolysis also permits in producing solid, liquid, and gaseous yields in considerable portions (Demirbas, 2004).

The product from pyrolysis is highly dependent on the feedstock and the process conditions employed the pyrolysed liquid which known as bio-oil and it can yields up to 70–75 wt% from wood (Oasmaa et al., 2005). However, bio-oils are still considered as low quality liquid fuels compared to petroleum based fuel, due to its poor properties such as complex multiphase structures, low heating values, high contents of water, oxygen, solids and ash, high surface tension and viscosity, have instable chemical and thermal, pH values is low (acidic) , and also poor ignition and combustion properties. Although bio-oils are lacking in some properties compared to petroleum fuel, it does have some specialty in lubricate properties. Furthermore, bio-oils are more environmental friendly since they are biodegradable and less toxic as well. The challenge of research today is to develop bio-oils as commercialized liquid fuels to compete with existing petroleum fuels.



Some factors might affect the chemical composition of bio-oil such as biomass feedstock type, pyrolysis parameters (residence time, pressure, temperature, gaseous environment heating rate), pre-treatment process, and also condensation and vapour filtration (condensing method and medium, filter type, cooling rate). Hence, the different use of biomass feedstock and different reactor configuration will give different results among them. As a result, the fuel properties of different bio-oils usually vary in wide ranges.

### 1.3 Objectives

The objectives of this research are:

- i) To characterize physical and chemical properties of *Imperata cylindrica* as a biomass feedstock for pyrolysis.
- ii) To design and set up the rig for slow pyrolysis process.
- iii) To study the effect of pyrolysis parameters (temperature and particle size) towards product yield by applying slow mode pyrolysis.
- iv) To identify the chemical component presents in the liquid-oil produced with different pyrolysis condition.

## 1.4 Scopes of research

The scopes of this research are:

- i) The biomass samples undergo characterization analysis such as proximate, ultimate, and component analysis to check the properties of *Imperata cylindrica* by using Thermogravimetric analysis (TGA), CHNS/O analyzer, bomb calorimeter and several analytical procedures.
- ii) Running pyrolysis process in a batch reactor using slow mode pyrolysis with constant heating rate of  $22\text{ }^{\circ}\text{C} \cdot \text{min}^{-1}$  by varying two process parameter (process temperature between  $450\text{ }^{\circ}\text{C}$  to  $600\text{ }^{\circ}\text{C}$  and particles size of 0.25 to 1 mm).
- iii) Analyzing the chemical compound in the liquid oil obtained from the pyrolysis process by using GC-MS and the water content using Karl Fischer titration for each sample.

## 1.5 Hypothesis

The hypothesis for this research includes;

- i) Slow pyrolysis of *Imperata cylindrica* were expected to produce 40 %, 30 % and 30 % of solid, gas and liquid yield, respectively.
- ii) Employing larger particle size were expected to produce more amounts of liquid and solid yield and resulting less amount of gas yield compared to

lower particle size. The increases of temperature in pyrolysis are expected to produce more gases while solid and liquid yield will be decreased.

- iii) From the chemical characterization using mass spectrometry (GC–MS), the pyrolysis liquid products may contains substantial proportion of water, some solid particles and some organic compounds that belong to acids, alcohols, ketones, aldehydes, phenols, ethers, esters, sugars, furans, nitrogen derivatives and others possible compounds.

## 1.6 Significant of Research

The significant of this research is mainly to study the potential of *Imperata cylindrica* or cogon grass as a biomass feedstock for slow pyrolysis process. This biomass was chosen due to its abundant resources which can be found everywhere and easy to grow.

Today, research focuses more on fast pyrolysis process in producing more bio-oil but in this study, slow pyrolysis were run in a batch fixed bed reactor to analyses the product distribution yield by varying the biomass particle size and pyrolysis temperature. This would contribute to the new information and knowledge for this scope of research.

## 1.7 Thesis Organisation

Chapter 1 contains the introduction of the research and describe the objectives and the significance of this study. In Chapter 2, literature review and vigorous study about the biomass (*Imperata cylindrica*), type of pyrolysis, the characterization of biomass and properties of bio-oil were highlighted in this chapter. Research methodology in Chapter 3 were describe about the procedure of the characterization of the biomass, the instrument used, the rig set-up, the experimental procedure for the pyrolysis, and also the analysis of the product (bio-oil) using GC-MS. Chapter 4 presents the result and discussion of the characterization of the biomass in comparison with the previous study (slow pyrolysis of rice husk) together with the product distribution yield for slow pyrolysis process in a fixed bed reactor. The result of water content and component identification using GC-MS were also been discussed in this chapter. In the last Chapter which is Chapter 5, conclusion and recommendation were discussed to summarize and improving this research in future.

## REFERENCES

- Bakhshi, N.N. and Adjaye, J.D. (1994). Properties and characteristics of *Ensyn* bio-oil. *In: Biomass pyrolysis oil properties and combustion meeting*, Colorado, 54–66.
- Balat, M. (2009). Main routes for the thermo-conversion of biomass into fuels and chemicals. Part 1: Pyrolysis systems. *Energy Conversion and Management*. 50, 3147–3157.
- Beis, S.H., Onay, O., and Kockar, O.M. (2002). Fixed-bed pyrolysis of safflower seed: influence of pyrolysis parameters on product yields and compositions. *Renew Energy*. 26, 21–32.
- Boucher, M.E., Chaala, A., Pakdel, H., and Roy, C. (2000). Bio-oils obtained by vacuum pyrolysis of softwood bark as a liquid fuel for gas turbines. Part II: stability and ageing of bio-oil and its blends with methanol and a pyrolytic aqueous phase. *Biomass Bioenergy*. 19, 351–361.
- Bridgwater, A.V. (1997). Fast pyrolysis of Biomass in Europe. In: Kaltschmitt M, Bridgwater AV, editors. *Biomass gasification and pyrolysis state of the art and future prospects*. Newbury, UK: CPL Press, 53-67.
- Bridgwater, A.V. (2002). An introduction to fast pyrolysis of biomass for fuels and chemicals In *Fast pyrolysis of biomass: A handbook*, Newbury, UK : CPL Press, 67-75.

- Bridgwater A.V. (2003). Renewable fuels and chemicals by thermal processing of biomass. *Chem Eng J*.91, 87–102.
- Bridgwater, A.V. (2004). Biomass fast pyrolysis. *Biomass Energy*. 8(2), 21–49.
- Bridgwater, A.V. (2011), Review of fast pyrolysis and product upgrading. *Biomass and Bioenergy*. 1-27.
- Calabria, R., Chiariello, F., and Massoli, P. (2007). Combustion fundamentals of pyrolysis oil based fuels. *Exp Therm Fluid Sci*. 31, 413–20.
- Dai, W.S., Chen, L.H., and Lui, T.S. (2000). A study on SiO<sub>2</sub> particle erosion of flake graphite and spheroidal graphite cast irons. *Wear*. 239, 143-152.
- Demirbas, A. (2001). Biomass resource facilities and biomass conversion processing for fuels and chemicals. *Energy Convers Manage*. 42, 1357–78.
- Demirbas, A. (2004). Determination of calorific values of bio-chars and pyro-oils from pyrolysis of beech Trunkbarks. *J Anal Appl Pyrol*.72, 215–9.
- Elliott, D.C. (1994). Water, alkali and char in flash pyrolysis oils. *Biomass Bioenergy*. 7, 179–85.
- Gani, A., and Naruse, I. (2007). Effect of cellulose and lignin content on pyrolysis and combustion characteristics for several types of biomass. *Renewable Energy* Volume. 32(Issue 4), 649-661.
- Graboski, M., and Bain, R. (1981). Properties of Biomass Relevant to Gasification. *Biomass Gasification: Principles and Technology*. 56, 32-43.
- Klass, D.L. (1998). Biomass for renewable energy, fuels, and chemicals. San Diego, CA: *Academic Press*, 214-32.

- Kusum, L., and Sanjay P. M. (2000). Bio-energy resources. *Energy–Environment Technology Division*. 9, 44-52.
- Li, S., Xu, S., Liu, S., Chen, Y., and Lu, Q. (2004). Fast pyrolysis of biomass in free-fall reactor for hydrogen-rich gas. *Fuel Processing Technology*. 85, 1201–1211.
- Milne, T.A., Agblevor, F., Davis, M., Deutch, S., and Johnson, D. (1997). A review of chemical composition of fast pyrolysis oils. In: Bridgwater AV, editor. *Developments in thermochemical biomass conversion*. London: Blackie Academic & Professional. 409–24.
- Morris, K.W. (2001). Fast pyrolysis of bagasse to produce bio-oil fuel for power generation. *Int Sugar J*.103, 259–63.
- Natarajan, E. and Ganapathy S. E. (2009). Pyrolysis of Rice Husk in a Fixed Bed Reactor. *World Academy of Science, Engineering and Technology* .56, 504-508.
- Nowakowski, D.J., Bridgwater, A.V., Elliott, D.C., Meier, D., and Wild, P. (2010). Lignin fast pyrolysis: results from an international collaboration. *Journal of Analytical and Applied Pyrolysis*.88, 53–72.
- Oasmaa, A., Leppamäki, E., Koponen, P., Levander, J., and Tapola, E. (1997).Physical characterization of biomass-based pyrolysis liquids. *Application of standard fuel oil analyses*. Espoo 1997, Technical Research Centre of Finland.
- Oasmaa, A., and Czernik, S. (1999). Fuel oil quality of biomass pyrolysis oils – state of the art for the ender users. *Energy Fuel*.13, 914–21.
- Oasmaa, A., Peacocke, C., Gust, S., Meier, D., and McLellan, R. (2005). Norms and standards for pyrolysis liquids. Ender-user requirements and specifications. *Energy Fuel*.19, 2155–63.

- Oasmaa, A., Solantausta, Y., Arpiainen, V., Kuoppala, E., and Sipilai, K. (2009). Fast pyrolysis bio-oils from wood and agricultural residues. *Energy & Fuels*. 24, 1380–8.
- Ozcimen, D., and Karaosmanoglu, F. (2004). Production and characterization of bio-oil and biochar from rapeseed cake. *Renew Energy* .29, 779–87.
- Peacocke, G.V.C., and Bridgwater, A.V. (2004). Techno-economic assessment of power production from the Wellman Process Engineering and BTG fast pyrolysis processes. In: Bridgwater AV, Boocock DGB, editors. *Science in thermal and chemical conversion*. CPL Press, 1785-802.
- Putun, A.E., Ozcan, A., and Putun, E. (1999). Pyrolysis of hazelnut shells in a Fixed-bed tubular reactor: yields and structural analysis of bio-oil. *J. Anal. Appl. Pyrol.* 52, 33–49.
- Radlein, D. (2002). Study of levoglucosan production a review. *Fast pyrolysis of biomass: a hand book*, vol. 2. Newbury: CPL Press.
- Scahill, J.W., Diebold, J.P., and Feik, C.J. (1997). Removal of residual char fines from pyrolysis vapors by hot gas filtration. In: Bridgwater AV, editor. *Developments in thermochemical biomass conversion*. London: Blackie Academic & Professional, 253–66.
- Sensoz, S., Angin, D., Yorgun, S., and Kockar, O. M. (2000). Bio-oil production from an oilseed crop: Fixed-bed pyrolysis of rapeseed (*Brassica napus* L.). *Energy Sources*. 22(10), 891-899
- Sharma, H.C., Sharma, K.K. and Crouch, J.H. (2004). Genetic transformation of crops for insect resistance: Potential and limitations. *Critical Reviews in Plant Sciences*. 23, 47–72.



- Shen, D.K., Gu, S., and Bridgwater, A.V. (2010). The thermal performance of the polysaccharides extracted from hardwood: cellulose and hemicellulose. *Carbohydrate Polymers*. 82, 39–45.
- Shihadeh, A., and Hochgreb, S. (2000). Energy Fuels. *Fuels*. 14, 260-274.
- Sipila, K.E., Kuoppala, L., Fagernas, and Oasmaa A. (1998). Characterization of biomass-based flash pyrolysis oils. *Biomass and Bioenergy* .14(2), 103–113.
- Solantausta, Y., and Oasmaa, A., (2003). Fast pyrolysis of forestry residues and sawdust, production and fuel oil quality, *International nordic bioenergy conference*. 1 - 3.
- Thamburaj, R. (2000). Fast pyrolysis of biomass for green power generation. In: Proceedings of the first world conference and exhibition on biomass for energy and industry, Sevilla, June 5–9.
- Wildschut, J., Mahfud, F., Venderbosch, R., and Heeres, H. (2009). Hydrotreatment of fast pyrolysis oil using heterogeneous noble-metal catalysts. *Industrial and Engineering Chemistry Research*. 48, 10324–10334.