THERMAL EFFECT IN PRESSURE FLUCTUATION: INTERNAL FLOW

THAGIP TARIG MUBARAK HABIBALLAH

A project report submitted in partial fulfillment of the requirements for the award of the degree of Master of Engineering (Mechanical)

> Faculty of Mechanical Engineering Universiti Teknologi Malaysia

> > August 2012

"قل إن صلاتي ونسكي ومحياي ومماتي لله رب العلمين"

6:162 <mark>قر آن</mark>

6:162 Say: My contact prayer, and my rites, and my life, and my death, are all to Allah, Lord of the worlds.

ACKNOWLEDGEMENT

I am grateful and would like to express my sincere gratitude to my supervisor Assoc. Prof. Dr. Kahar Osman for his guidance, continuous encouragement and constant support during the project.

I would like to indicate the effort and help that I found from CFM lab members.

I acknowledge my sincere indebtedness and gratitude to my parents for their love, dream and sacrifice throughout my life. The words are not enough to properly describe my appreciation for their devotion, support and faith in my ability to attain my goals.

Thanks also extended to all the great minds in FKM that helped me to bring this study to this level.

ABSTRACT

In industrial processes, turbulent flows are known to sometimes generate significant levels of noise and consequent vibrations of the structures. As well the involvement of the heat in the most engineering processes; this study focus on the effect of temperature of the internal flow in the tube has been investigated numerically to study the vibration tendency on the tube structure. The Fluent software has been used with LES solution provided for more accurate results. The results show the direct relation of the temperature in the vibration tendency. The results also show that the diameter of the tube has inverse relationship to the vibration tendency of the structure.

ABSTRAK

Dalam kajian ini, kesan suhu aliran dalaman dalam tiub telah disiasat berangka untuk mengkaji kecenderungan getaran pada struktur tiub. Perisian Fasih telah digunakan dengan penyelesaian LES disediakan untuk hasil yang lebih tepat. Keputusan menunjukkan hubungan langsung suhu dalam kecenderungan getaran. Juga ia menunjukkan bahawa diameter tiub mempunyai hubungan yang songsang kepada kecenderungan getaran struktur.

Table of Contents

DECLARATION	ii
DEDICATION	iii
ACKNOWLEDGEMENTS	iv
ABSTRACT	V
ABSTRAK	vi
TABLE OF CONTENTS	vii
LIST OF TABLES	xii
LIST OF FIGURES	xiv
LIST OF ABBREVIATIONS	xiv

1 Introduction		6
1.1	1 Problem statement	7
1.2	.2 Objectives	7
1.3	.3 Scope of the study	7
1.4	.4 Significant of the study	8
2 Literature review		
2.1	1 Overview	9
2.2	.2 Fluid Structure Interaction	10
2.3	.3 Flow-Induced Vibration (FIV)	14
Vortex Induce Vibration (VIV) Large Eddy Simulation (LES)		20
		23
2.4	.4 Internal Flow	25
2.5	.5 Temperature Effect at Heat Exchanger	26

3	3 Research Methodology		31	
	3.1	CFI)	31
		3.1.1	Mass conservation in 3D	31
		3.1.2	Momentum equation in 3D	32
		3.1.3	Large Eddy Simulation	33
		3.1.4	Navier-Stokes Equation	33
3.1.5 Reynolds average Navier-Stokes (RANS)		3.1.5	Reynolds average Navier-Stokes (RANS)	35
		3.1.6	Pressure Implicit with Splitting of Operators	36
	3.2	The	Model	37
3.3 Fluent (CFD)		Flue	ent (CFD)	39
4	I	Results	and Discussion	42
4.1 Diameter and Temperature Effect on The Pressure Fluctuations		42		
	4.2	Free	quency Domain Results of the Pressure Fluctuation	48
5	(Conclusion 57		
6	Refrences 58			

Table of Figures

FIGURE 2-1: SCHEMATIC DIAGRAM FOR FLOW EFFECT ON THE STRUCTURE	
INSTABILITY.(BELVIN, R. 2002)	15
FIGURE 2-2: CLASSIFICATION OF FIV	19
FIGURE 3-1: 3D VIEW ILLUSTRATION OF FLOW	32
FIGURE 3-2: THE MESHED MODEL	38
FIGURE 3-3: CFD PROCESS	40
FIGURE 4-1 AVERAGE TOTAL PRESSURE (0.09 M DIAMETER, 298K)	43
FIGURE 4-2 TOTAL PRESSURE (0.09 M DIAMETER, 363K)	43
FIGURE 4-3 TOTAL PRESSURE (0.09 M DIAMETER, 463K)	43
FIGURE 4-4 TOTAL PRESSURE (0.09 M DIAMETER, 518K)	44
FIGURE 4-5 TOTAL PRESSURE (0.09 M DIAMETER, 600K)	44
FIGURE 4-6 TOTAL PRESSURE (0.06M DIAMETER, 298K)	44
FIGURE 4-7 TOTAL PRESSURE (0.06M DIAMETER, 363K)	45
FIGURE 4-8 TOTAL PRESSURE (0.06M DIAMETER,463K)	45
FIGURE 4-9 TOTAL PRESSURE (0.06M DIAMETER, 518K)	45
FIGURE 4-10 TOTAL PRESSURE (0.06M DIAMETER, 600K)	46
FIGURE 4-11 TOTAL PRESSURE (0.0254 M DIAMETER, 298K)	46
FIGURE 4-12 TOTAL PRESSURE (0.0254 M DIAMETER, 363K)	46
FIGURE 4-13 TOTAL PRESSURE (0.0254 M DIAMETER, 463K)	47
FIGURE 4-14 TOTAL PRESSURE (0.0254 M DIAMETER, 518K)	47
FIGURE 4-15 TOTAL PRESSURE (0.0254 M DIAMETER, 600K)	47
FIGURE 4-16 THE FFT FREQUENCY (0.09 M DIAMETER, 363K)	48
FIGURE 4-17 THE FFT FREQUENCY (0.09 M DIAMETER, 463K)	48
FIGURE 4-18 THE FFT FREQUENCY (0.09 M DIAMETER, 518K)	49
FIGURE 4-19 THE FFT FREQUENCY (0.09 M DIAMETER, 600K)	49

FIGURE 4-20 THE FFT FREQUENCY (0.06M DIAMETER, 298K)	49
FIGURE 4-21 THE FFT FREQUENCY (0.06M DIAMETER, 298K)	50
FIGURE 4-22 THE FFT FREQUENCY (0.06M DIAMETER, 363K)	50
FIGURE 4-23 THE FFT FREQUENCY (0.06M DIAMETER, 463K)	50
FIGURE 4-24 THE FFT FREQUENCY (0.06M DIAMETER, 518K)	51
FIGURE 4-25 THE FFT FREQUENCY (0.06M DIAMETER, 600K)	51
FIGURE 4-26 THE FFT FREQUENCY (0.0254 M DIAMETER, 298K)	51
FIGURE 4-27 THE FFT FREQUENCY (0.2546M DIAMETER, 363K)	52
FIGURE 4-28 THE FFT FREQUENCY (0.0254M DIAMETER, 463K)	52
FIGURE 4-29 THE FFT FREQUENCY (0.0254M DIAMETER, 518K)	52
FIGURE 4-30 THE FFT FREQUENCY (0.0254 M DIAMETER, 518K)	53
FIGURE 4-31 THE FFT FREQUENCY (0.0254M DIAMETER, 600K)	53
FIGURE 4-32 TOTAL PRESSURE COMPARISON AGAINST FLOW TIME (0.009 M)	54
FIGURE 4-33: TOTAL PRESSURE COMPARISON AGAINST FLOW TIME (0.006 M)	54
FIGURE 4-34: TOTAL PRESSURE COMPARISON AGAINST FLOW TIME (0.00254 M)	55
4-35: MAXIMUM PRESSURE VIBRATION AMPLITUDE	56

LIST OF ABBREVIATIONS

DNS	- Direct Numerical Simulations
LES	- Large Eddy Simulations
FSI	- Fluid–Structure Interaction
CFD	- Computational Fluid Dynamic
FIV	- Flow-Induced Vibration
VIV	- Vortex Induce Vibration
RANS	- Reynolds-averaged Navier-Stokes
GS	- Grid Scale
SGS	- Subgrid Scale
CL	- Coefficient of Lift
CD	- Coefficient of Drag

INTRODUCTION

Piping systems conveying liquids are subjected to severe transient loadings whenever changes in the momentum of the fluid or piping structure are abruptly induced due to planned or accidental actions. Typical sources of transients are (Rocher, R. 2012):

- 1. valve slam
- 2. startup and shutdown of pumps
- 3. loss of coolant in nuclear reactors
- 4. vibrations induced by operating equipment installed on the line
- 5. Earthquakes.

Fluid around a structure can significantly change the structure's vibration characteristics. The presence of a inactive fluid decreases the natural frequencies and increases the damping of the structure. A dense fluid couples the vibration of elastic structures which are adjacent to each other. Fluid flow can induce vibration. A turbulent fluid flow exerts random pressures on a structure, and these random pressures induce a random response. The structure can resonate with periodic components of the wake. (Blevins, R. 2000)

If a structure is sufficiently flexible, the structural deformation under the fluid loading will in turn change the fluid force. The response can be unstable with very large structural vibrations once the fluid velocity exceeds a critical threshold value. Vibration induced by fluid flow can be classified by the nature of the fluid structure interaction as effects which are largely independent of viscosity include added mass and inertial coupling. Unsteady pressure on the surface of a structure, due to either variations in the free stream flow or turbulent fluctuations, induces a forced vibration response. Strong fluid-structure interaction phenomena result when the fluid force on a structure induces a significant response which in turn changes the fluid force.

1.1 Problem statement

The volume flow rate of 0.024m³/s (Lee,H. et al,2009) is used to examine effect of the heated water flow on the circular tube. Cross bonding to different temperatures with values 298 K (Lee,H. et al,2009) 363K (Lee,H. et al,2009) 600K (Pironkov, P. 2010)

1.2 Objectives

To determine the effect of the temperature in internal flow related to FSI.

1.3 Scope of the study

- 1. Numerical solution will be used.
- 2. Include the pipe flow with and without temperature effect.
- 3. Investigate the effect of change of diameters of the pipe in constant flow rate.

1.4 Significant of the study

The heated tube has been widely used in the industrial application such as HVAC systems, heat exchangers, boilers, turbines, refineries reactors and most of the petro-chemical industry process.

REFRENCES

- Du and M. Schafer 2010, MECHANICAL AND THERMAL FLUID STRUCTURE INTERACTION OF NON-CONTACTING GAS SEALS IN JET ENGINES, Journal of Fluids and Structures, 2011. Retrieved from science direct April 2012
- P. MOUSSOU, PH. LAFON, S. POTAPOV, L. PAULHIAC1, A.S. TIJSSELING, 2006. Industrial cases of FSI due to internal flows eleronic version. Retrieved from science direct April 2012
- Yu Du , 2010. NUMERICAL SIMULATION OF MECHANICAL AND THERMAL FLUID– STRUCTURE INTERACTION IN LABYRINTH SEALS, (PhD thesis) 2010.
- Plamen Pironkov, 2010. NUMERICAL SIMULATION OF THERMAL FLUID–STRUCTURE INTERACTION, (PhD thesis), 2010.
- Jong Chull Jo , 2009. PRESSURE VESSELS AND PIPING SYSTEMS Fluid-Structure Interactions Journal of Fluids and Structures, 2091. Retrieved from science direct April 2012
- J. Pereira Gomes ,Ã, S. Yigit, H. Lienhart a, M. Schafer, 2011 Experimental and numerical study on a laminar fluid–structure interaction reference test case, Journal of Fluids and Structures, 2011. Retrieved from science direct April 2012
- PADMANABHAN SESHAIYER, 2009. A COMPUTATIONAL DOMAIN DECOMPOSITION APPROACH FOR SOLVING COUPLED FLOW-STRUCTURE-THERMAL INTERACTION PROBLEMS Journal of Fluids and Structures, 2009. Retrieved from science direct April 2012
- Rogerio Gomes da Rocha, Felipe Bastos de Freitas Rachid, 2012. Numerical solution of fluidstructure interaction in piping systems by Glimm's method. Journal of Fluids and Structures, 2012. Retrieved from science direct April 2012
- Iman Harimi, Mohsen Saghafian, 2012. Numerical simulation of fluid flow and forced convection heat transfer from tandem circular cylinders using overset grid method Journal of Fluids and

Structures, 2012. Retrieved from science direct April 2012

- Sylvain Bourdier , John R. Chaplin, 2012. Vortex-induced vibrations of a rigid cylinder on elastic supports with end-stops, Part 1: Experimental results Journal of Fluids and Structures, 2011. Retrieved from science direct April 2012
- Abdalla Al-Amiri, Khalil Khanafer, 2011. Fluid–structure interaction analysis of mixed convection heat transfer in a lid-driven cavity with a flexible bottom wall. Journal of Fluids and Structures, 2011. Retrieved from science direct April 2012
- R. D. Blevins 1999. VIBRATION OF STRUCTURES INDUCED BY FLUID FLOW, electronic version. Retrieved from science direct April 2012
- Dariusz P. Mikielewicz , A. Mohsen Shehata c, J. Derek Jackson , Donald M. McEligot, 2002. Temperature, velocity and mean turbulence structure strongly heated internal gas flows Comparison of numerical predictions with data, Journal of Fluids and Structures, 2011. Retrieved from science direct April 2012
- , P. Birken, K. J. Quint, S. Hartmann, A. Meister, 2008. On Coupling Schemes for Heat Transfer in FSI Applications, Journal of Heat and Mass Transfer, 2008. Retrieved from science direct April 2012.
- H AYM B ENAROYA, R ENE D. G ABBAI, 2007. Modelling vortex-induced fluid-structure interaction. Electronic version Retrieved from science direct April 2012.
- Gongmin Liu, Yanhua Li , 2011. Vibration analysis of liquid-filled pipelines with elastic constraints. Journal of Fluids and Structures, 2011. Retrieved from science direct April 2012
- S.Naga Sarada, A.V.Sita Rama Raju, K.Kalyani Radha,,2010. Experimental Numerical Analysis Enhancement of Heat Transfer in a Horizontal Circular Tube using Mesh Inserts in Turbulent Region, European Journal of Mechanical and Environmental Engineering, 2010. Retrieved from science direct April 2012
- J. HAMBURGERa, A. KUMARb, S. KRISHNAMURTHY, 2011. A General Partitioned Fluid-Structure Interaction Model for Non Matching Unstructured Mesh, 20ème Congrès Français de Mécanique 2011
- EUGENIO AULISA, SANDRO MANSERVISI, PADMANABHAN SESHAIYER ,2009. A COMPUTATIONAL DOMAIN DECOMPOSITION APPROACH FOR SOLVING

COUPLED FLOW-STRUCTURE-THERMAL INTERACTION PROBLEMS, Electronic Journal of Differential Equations 2009. Retrieved from science direct June 2012.

- L. Cheng , T. Luan, W. Du, M. Xu, 2009. Heat transfer enhancement by flow-induced vibration in heat exchangers, International Journal of Heat and Mass Transfer, 2009. Retrieved from science direct April 2012.
- Sylvain Bourdier 1, JohnR.Chaplin, 2012. Vortex-induced vibrations of arigid cylinder on elastic supports with end stops, Part1: Experimenta lresults, Journal of Fluids and Structures, 2012
- Xiao dong Wu, Fe iGe n, YoushiHong, 2012. A review of recent studieson vortex-induced vibrations of long slender cylinders, Journal of Fluids and Structures 2012. Retrieved from science direct April 2012.
- M.J. Pettigrew, C.E. Taylor , 2003. Vibration analysis of shell-and-tube heat exchangers: an overview—Part 1: flow, damping, fluidelastic instability, Journal of Fluids and Structures 2003. Retrieved from science direct April 2012.
- M.J. Pettigrew, C.E. Taylor,2003. Vibration analysis of shell-and-tube heat exchangers: an overview—Part 2: vibration response, fretting-wear, guidelines Journal of Fluids and Structures 2003. Retrieved from science direct April 2012.
- Abdalla Al-Amiri, Khalil Khanafer, 2010. Fluid–structure interaction analysis of mixed convection heat transfer in a lid-driven cavity with a flexible bottom wall, International Journal of Heat and Mass Transfer 2011. Retrieved from science direct FEB2012.