

**COST ANALYSIS FRAMEWORK FOR SEDIMENT
MANAGEMENT IN RESERVOIR INFRASTRUCTURE**

IMAM BUCHORI

UNIVERSITI TEKNOLOGI MALAYSIA

**COST ANALYSIS FRAMEWORK FOR SEDIMENT
MANAGEMENT IN RESERVOIR INFRASTRUCTURE**

IMAM BUCHORI

A Thesis submitted in fulfillment
of the requirements for the award of the degree of
Master of Science (Construction Contract Management)

Faculty of Built Environment
Universiti Teknologi Malaysia

DEDICATION

*“ To My Beloved Wife (Rizki Zahrotul Iza) and Son
(Rahmatusifa Annajwah), thank you for being wonderful
to me”*

“ To My Mother that I Love”

“To Abah and Umik that I Love”

ACKNOWLEDGMENT

Alhamdulillah I prayed to Allah SWT, because only upon His mercy and grace, this thesis can be completed. Greeting and Shalawat, I wish upon the Prophet Muhammad, may his shafa'at help us.

I am indebted to my project supervisor, Assoc. Prof Zakaria Mohd Yusof for his support, advice and encouragement from start until the completion of this project.

I am also indebted to Ministry of Public Works Indonesia for funding my master study. Management Perum Jasa Tirta I Malang that has give me permission for this master study. In particular, I would like to show my gratitude to Ir. Syamsul Bachri Dipl. Ph, Ir. Harianto Dipl. HE, Ir. Vonny C. Setiawati MT, Firman S. Efendi S.Si, Ir. Hermien Indraswari MT, Inni Dian Rohani, ST, Drs. Syaiful Hidayat and for everyone for supporting me during my study in UTM. Librarians at UTM and Geotechnical Division of Institute of Road Engineering also deserve special thanks for their assistance in supplying the relevant literatures.

My fellow postgraduate students should also be recognized for their support. My sincere appreciation also extends to all my colleagues and others who have provided assistance at various occasions. Their views and tips are useful indeed. Unfortunately, it is not possible to list all of them in this limited space. I am grateful to all my family members.

ABSTRACT

Water is importance element for the continuity of the life of human being. Generally, the human being was created and had settled down in orders to get basic needs in daily life. . In the present day, the scarcity of water due to human population increase, climate changes, drought, environment change, etc., causes need to store the freshwater is very importance and urgently and the build of dam reservoir is the one answer for that problem. The biggest problem that occurs in the dam reservoir is sedimentation. Sedimentation problem can make reduce gross storage of dam reservoir. Sedimentation management is one way of maintenance process for make sediment removal in dam reservoir. Maintenance cost for that dam reservoir can't direct separately, because that social function and business benefit working together. The cost analysis framework was undertaken to identifies and describe the estimated costs associated with the baseline , development and alternatives, and calculates comparative costs between them, also integration of risk factor management approaches into routine practice for the pilot teams. Because of that, is importance to know component cost and development of component cost that used for make cost analysis. In this research that to get guidance for make cost analysis base on component cost and also to developed, that type of research is develop theory and model, base on studies of published material and compare between theoretical. Research finding that almost eighty percent (80%) most of respondent that involved in cost analysis or cost estimate agree that practically to make framework for cost analysis is importance that the beginning, component cost base on theory and furthermore to make guidance is combine component cost in theory and practically, beside depend on the drawing, specification or other thing that needed for make cost analysis.

Keyword : Cost analysis framework, Sedimentation management, Cost estimate, and Maintenance cost

TABLE OF CONTENT

CHAPTER	TITLE	PAGE
	DECLARATION OF THESIS	ii
	DEDICATION	vi
	ACKNOWLEDGMENT	vii
	ABSTRACT	viii
	TABLE OF CONTENT	ix
	LIST OF FIGURE	xiii
	LIST OF TABLE	xiv
1	INTRODUCTION	1
	1.1 Background	1
	1.2 Problem Statement	6
	1.3 Objective of the Research	7
	1.4 Scope of the Research	8
	1.5 Importance of the Research	8
	1.6 Organization of the Chapters	9
2	LITERATURE REVIEW	10
	2.1 Introduction	10
	2.2 Reservoir	11

CHAPTER	TITLE	PAGE
	2.2.1 Reservoir Issues	13
	2.2.2 Reservoir Sedimentation	14
2.3	Sedimentation	15
	2.3.1 Sedimentation	17
	2.3.2 Environmental and Water Quality Issues	19
2.4	Sediment Management	23
	2.4.1 Flushing Method	24
	2.4.2 Dredging Method	25
	2.4.3 Excavation Method	26
	2.4.4 Environmental Issue in Sediment Management	27
2.5	Measurement and Quantification	28
	2.5.1 Measurement and Quantification under Malaysian Civil Engineering Standard Method Measurement 3 (CESMM 3)	29
	2.5.2 Measurement Quantification of Sediment Budget	30
2.6	Cost Analysis	32
	2.6.1 Cost Estimate	33
	2.6.2 Purpose of Cost Estimates	35
	2.6.3 Elements of Cost Estimate	36
	2.6.4 Detailed of Cost Estimates	42
	2.6.5 Development of Cost Estimates	46
2.7	Summary	47
3	RESEARCH METHODOLOGY	48
	3.1 Introduction	48
	3.2 Research Methodology	50

CHAPTER	TITLE	PAGE
3.3	Data Collection	52
3.4	Data Analysis	56
3.4.1	Specification for Object Data	56
3.4.2	Dredging Methods	56
	a) Existing Cost Analysis Data	56
	b) Identification Component Cost Analysis	57
	c) Development Component Cost Analysis	61
3.4.3	Flushing Methods	63
	a) Existing Cost Analysis Data	63
	b) Identification Component Cost Analysis	63
3.4.4	Methodological Consideration	63
4	DATA ANALYSIS AND DISCUSSION	65
4.1	Data Analysis	65
4.1.1	Specification for Object Data	65
4.1.2	Dredging Methods	66
	a) Existing Cost Analysis Data	66
	b) Identification Component Cost Analysis	67
	c) Development Component Cost Analysis	71
4.1.3	Flushing Methods	79
	a) Existing Cost Analysis Data	79
	b) Identification Component Cost Analysis	79
	c) Development Component Cost Analysis	82
4.1.4	Dredging and Flushing Methods	84
4.1.5	Combination of Flushing, Dredging and Dry Excavation Methods	87

CHAPTER	TITLE	PAGE
5	CONCLUSION AND RECOMENDATION	89
	5.1 Conclusion	89
	5.2 Limitation of the research	91
	5.3 Recomendation	91
	REFERENCES	94
	APPENDIX	98

LIST OF FIGURE

FIGURE NO.	TITLE	PAGE
1.1	Dam Reservoir Infrastructure in Brantas River basin	4
1.2	Measures to Reduce Sediment in Reservoir	5
2.1	Element of Cost	45
2.2	Example of Direct and Indirect Cost	45
3.1	Research Methodology	50
3.2	Data Collection Flow chart	52

LIST OF TABLE

TABLE NO.	TITLE	PAGE
2.1	Environmental Issue Related to Sediment Management	20
2.2	Measurement and Quantification Sediment Budget	32
2.3	Developing Element Cost Estimate of Capital Cost	37
2.4	Developing Element Cost Estimate of Operation & Maintenance	38
2.5	Component Cost Analysis Framework	39
3.1	Design of Research Process	49
3.2	Comparasion of Existing Component Cost Analysis	58
3.3	Average of Sample	59
3.4	Comparasion Component Cost Estimate between Temporary Result with Theory, Other Source and Own Interpretation	60
3.5	Final Component Cost Analysis Framework	61
3.6	Development Component Cost Analysis	62
4.1	Specification Data for Dam Reservoir	66
4.2	Table opinion completeness of cost component for dredging	70
4.3	Table opinion completeness of cost component for flushing	81
4.4	Table opinion completeness of cost component for combination of flushing, dredging and dry excavation	87

CHAPTER 1

INTRODUCTION

1.1 Background

Water is importance element for the continuity of the life of human being. Generally, the human being was created and had settled down in orders to get basic needs in daily life. In the present day, the scarcity of water due to human population increase, climate changes, drought, environment change, etc., causes need to store the freshwater is very importance and urgently. The impact from that happen caused to constructed dam reservoirs to store the fresh water's is importance. Another purpose of constructed dam reservoirs is used for flood prevention and used for power generation purposes for the last 50 - 100 years.

Today, dam reservoir problem that should be observed is decreasing of dam reservoir effective capacity and dam reservoir lifetime, that some of them getting older because of some environmental damages. One of problem is caused by sedimentation. Trapping of sedimentation on the upstream of the dam reservoir body is importance things, because it is a very serious problem for many countries for dam reservoir maintenance. Sedimentation has influence to life cycle of reservoir infrastructure as water reservoir. Increasing of sedimentation in the reservoir can make gross storage capacity less than gross storage capacity design. Additionally, performance operation from capacity decrease, significantly make the benefits

gained from hydroelectric power generation, irrigation, water supply and flood control decreases in a considerable amount because of the sedimentation. Sedimentation also give indirectly affected to the downstream and upstream of the dams reservoir. In the downstream sediment causes degradation in channel and changes in aquatic life or the environment condition. On the other hand, negative effects of sedimentation in upstream of a reservoir make increase of local ground water table, channel flood capacity reduction, decrease of bridge navigational clearance, and water diversions and withdrawals influence.

It happened also in Indonesia, especially in Brantas River in East java. In the report *On Engineering Studies For The Brantas Rives And The Bengawan Solo River Basins (2005)* by Nippon Koei CO, LTD said that since the basin development master plan for the Brantas River basin was formulated in 1962, eight dam reservoirs have been constructed for domestic and industrial water supply, power generation, flood control and irrigation (Sengguruh, Sutami, Lahor, Wlingi, Lodayo, Selorejo, Bening, and Wonorejo). Large amount of sediment inflow and sedimentation to be importance problem because of that the principal reservoirs of the Brantas River basin are rapidly losing their gross storage capacities (from 30 to 90 % of the original storage capacities). Sengguruh, Wlingi and Lodayo dam reservoirs (as smaller dams) for example, their effective storage capacities were reduced to around fourthy percent (40%) and the biggest Sutami dam reservoir had a large-scale storage loss in the past 31 years since its construction. Detailed sedimentation characteristics in each dam reservoir are presented below.

In Sengguruh dam, which has a catchment area of 1,659 km², is located on the upstream reach of the Brantas River and at just downstream reach of the confluence of the Brantas River and the Lesti River. The location is around 25 km south of Malang City, and approximately 14 km upstream reach of the Sutami dam. Since completion in 1988, sediment accumulation in the Sengguruh reservoir has rapidly reduced its effective storage capacity up to 41.5% of the design storage capacity. Especially, the rate of sedimentation was high immediately after completion and around 15 million m³ of sediment was deposited in the reservoir in the first nine years, which corresponded to 70 % of the designed gross storage.

In Sutami dam reservoir, has a large scale storage capacity, however, the storage capacity decreasing process of the early years after construction (1973 - 1977) had been very quickly, and decrease of gross storage capacity was about 82 million m³ for 4 years. After construction of the Sengguruh dam, the rate of the storage capacity decrease slowed down in comparison with that of before construction of the Sengguruh dam. The present gross storage capacity corresponds to 50.9% of that of designed condition, and the effective storage capacity is 57.4% of the designed condition.

In Lahor dam, which has a catchment area of 170 km², was constructed in 1977, and it was connected with the Sutami reservoir by a connection tunnel. The two reservoirs, therefore, are functioning as one reservoir. In 2002, 25 years after the dam completion, the gross storage capacity of the Lahor dam was 85% of that of designed. The sedimentation rate of the Lahor reservoir is less than other reservoirs in the Brantas River basin.

In Wlingi dam, which has a catchment area of 2,890 km², is located on the southern skirts of Mt. Kelud in the upstream reach of the Brantas River, and at around 25 km downstream reaches of the Sutami dam. The Wlingi dam was constructed in 1977 for the purpose of hydropower generation for peak demand and irrigation water supply, and it was also expected to take a role of temporary storage of the erupted material from Mt. Kelud. After construction of the Wlingi dam, the sedimentation rate has been very rapid, and annual average sediment deposit in the reservoir up to 1988 was around 1.3 million m³. In January 1990, just before the eruption of the Mt. Kelud, the gross storage capacity of the Wlingi reservoir was reduced to 19.2% of the designed gross storage capacity. As stated above, regardless of the eruption of Mt. Kelud, the Wlingi reservoir was suffered by high rate of the sediment inflow. Mt. Kelud erupted in February 1990. After this eruption, the Wlingi reservoir were filled up completely by the sediment and the removal works of deposited sediment in the Wlingi reservoir by dredging and sediment flushing were implemented to restore the storage capacity.

In Lodoyo Dam, that was constructed in 1983 for the purpose of after bay of

the Wlingi dam and power generation. The decreasing rate of storage capacity in the Lodoyo reservoir is high like the Wlingi reservoir. The gross storage capacity of the Lodoyo reservoir in 2003 was reduced to 2.03 million m³, which corresponds to 39% of the designed gross storage capacity of 5.20 million m³. There was not significant change in the decreasing rate of the storage capacity after the eruption of Mt. Kelud in 1990, owing to temporary storage effect of the Wlingi reservoir for the erupted material from Mt. Kelud.

In Selorejo dam, which has a catchment area of 236 km², is located at the upstream reach of the Konto River and there are many devastated areas in the mountain hill slope surrounding the reservoir. The Selorejo dam was constructed in 1972 as a multipurpose dam for irrigation water supply, power generation and flood control. The gross storage capacity of the Selorejo reservoir has been decreased to 44.01 million m³, which corresponds to 70.6% of the designed gross storage capacity of 62.30 million m³. The decreasing process of the storage capacity is moderate in comparison with those of the other dams on the Brantas River.



Figure 1.1 Dam Reservoir Infrastructure in Brantas River basin, East Java

Source: www.Jasatirta1.co.id

Sedimentation in dam reservoir infrastructure in the Brantas River basin to be seriously problem, because the position that closely with power plant infrastructure that use water for the turbine operation. All problem that appearance from the impact of sedimentation is reduction to gross storage capacity of dam reservoir function as collected water from rain water for flood management, electricity production and rice production / irrigation water supply ; build up new one for increasing supply of live human being (new gross capacity) needed of high investment ; for life cycle of dam reservoir function, still needed maintenance cost (for decommissioning, the maintenance cost is higher if that contain full sedimentation). In the report On Engineering Studies For The Brantas Rives And The Bengawan Solo River Basins (2005) by Nippon Koei CO, LTD said that element of reservoir sediment management can be categorized as follows : reduce of sediment inflow to reservoir, routing of sediment pass or through the reservoir, discard of deposited sediment, provide large storage volume and sediment placement, as shown in the following figure. 1.2.




Figure 1.2 Measures to Reduce Sediment in Reservoir

Source: Nippon Koei CO, LTD, 2005 - Engineering Studies for the Brantas Rives And The Bengawan Solo River Basins.

Sedimentation management that use in Wlingi and Lodoyo dam reservoir maintenance is removal sediment by flushing (use hydraulic principle methods), Dredging (use mechanical principle method) and variation of flushing and dredging, this is because that methods is sustainable. The cost and applicability of each

strategy have variation from one site to another and function of sediment accumulation.

Cost analysis is the act of developing, analyzing, and documenting cost estimates using analytical approaches and technique. A cost analysis was undertaken to describe the estimated costs associated with the development and integration of risk factor management approaches into routine practice for the pilot teams, and also used for produce cost estimates or budgeting. Cost analysis involved every compound that have influence for estimation, as material cost (direct and indirect); labor cost (direct and indirect); equipments and resources cost (direct and indirect); and overhead cost.

Perum Jasa Tirta I (PJT I) as public company that represented of government that have responsibilities for operation and maintenance for dam reservoir along Brantas River basin have social liability and business benefit. This research will be focused on the cost analysis framework that has effect to the financial income for PJT (business benefit side). The importance that should be know is the social function and business benefit is working together. No completely compound of cost analysis in estimated cost, caused analysis of financial benefit to be false. Financial analysis in sediment management not always use for calculate the project cost benefit, but also to know how far the influence of cost that been use to financial income for PJT I, beside that this purpose can use for cost budgeting in the future. Flushing for example, the water that been use not come from material that buying from supplier but they have influence directly to PJT I financial income and influence to the irrigation water policy.

1.2 Problem Statement

Large amount of sediment inflow and sedimentation to be importance problem because the reservoirs that constructed in the Brantas River basin is rapidly losing their gross storage capacities (from 30 to 90 % of the original storage capacities).

Sedimentation management is one choice for maintenance program. Dam reservoirs perform routine removal sediment by dredging every year. But the ability dredging of the reservoir is not sufficient, because the cost is relatively expensive, even that have good effectively for removal sediment. Other removal sediment that performs in dam reservoir is conducted to flushing. The applicability of each strategy have variation from one site to another and also sediment accumulation function. Maintenance cost for sediment management in dam reservoir can't direct separately between social function and business benefit, because that function working together. Incompletely component cost analysis for sedimentation management caused mistake for financial analysis (business benefit side) and cost benefit analysis (social function side).

With that circumstances, identification and development of component of cost is importance to analyze, so the cost analysis framework for sediment management in the reservoir infrastructure can be finding.

The question of problems that arises is whether component of cost analysis framework for sediment management that already applied is complete or not ?

1.3 Objective of the Research

The following objectives are proposed for this theses research that according with the problem statement (above) is:

- a) To identify the components of cost analysis.
- b) To develop cost analysis framework based on component of cost analysis.

1.4 Scope of the Research

The scope of this research is:

- a) Object specification is dam reservoir that located in Province of East Java, Indonesia and has function as water supply for power generation.
- b) For dredging methods dam reservoir that choice is Sengguruh; Sutami; Wlingi and Lodoyo; and for flushing methods dam reservoir that choice is Wlingi and Lodoyo.
- c) Number of data that will be used is two (2) – five (5) years (for dredging methods) and two (2) years (for flushing methods)
- d) Cost analysis framework will be focus on the dredging method, and flushing methods.
- e) Research will be doing from documentary study

1.5 Importance of the Research

Sedimentation velocity at each reservoir accumulating basin impacted on step-up sedimentary sediment volume at deep accumulating basin which directly impacted on that life cycle for that infrastructure it self. To settle that problem, two of alternative maintenance for removal sedimentation that was done is dredging methods and flushing methods (with some dredging and excavation process for make sediment comes out from water intake for power plant).

The aim of this study is to understand the problems associated with cost analysis framework for sediment management in reservoir infrastructure so that it can be used for get cost analysis framework guideline in next project for estimator in the same location or other location, because maintenance cost is importance matter for routine sediment removal. Beside that, completely of cost analysis framework has impact for true financial analysis and cost benefit analysis.

1.6 Organization of the Chapters

1.6.1 Chapter 1 – Introduction

Discuss the backgrounds of the study and clearly stated the problem statement, objective, scope of study, importance of the study, methodology and organization of the chapter. It frames the study effort and gives it specific focus to the research.

1.6.2. Chapter 2 – Literature Review

Discuss about the theoretical that will use in this research. Theory that will be explain as follow reservoir, Sedimentation, Sediment Management, Measurement and Quantification of Sediment Budget, and Cost Analysis.

1.6.3. Chapter 3 – Research Methodology

Discuss about research methodology phase and explanations for every phase.

1.6.4. Chapter 4 – Data Collection, Cost Analysis Framework Draft and Analysis Data

Discuss about data collection, cost analysis framework draft, and analysis data.

1.6.5. Chapter 5 - Conclusion and Recommendation

This chapter is the final chapter that summaries the finding of the research according to the research objectives. It also contains the problems encountered during the research as well as the recommendation for future research.

REFERENCES

- AMCP 706-132,(1975), *Engineering Design Handbook: Maintenance Engineering Techniques*, Department of the Army, Washington, D.C., June 1975.
- BSN (2000), *SNI 19-6471.(1-4) -2000, Tata Cara Pengerukan Sungai dan Pantai*, Jakarta, Indonesia.
- CIDB Malaysia (2007), *Malaysian Standard Methods of Measurement for Civil Works*, Kuala Lumpur, Malaysia.
- CIDB Malaysia (2008), *A Guide to Malaysian Standard Methods of Measurement for Civil Works*, Kuala Lumpur, Malaysia.
- Chakraborti, M., (1984). *Estimating, Costing and Specification In Civil Engineering*. Published by Author, Calcuta: Shree Hari Press.
- Dr. Phillip N. Owens (2008), *Sustainable Management of Sediment Resources Vol. 4*, Amsterdam, Netherlands.
- Departemen Pekerjaan Umum Dirjen Bina Marga (2008), *Panduan Analisis Harga Satuan No. 008/BM/2008*, Jakarta, Indonesia

- Gregory L. Morris & Jiahua Fan (1998), *Reservoir Sedimentation Handbook-Design and Management of Dams, Reservoirs and Watersheds for Sustainable Use*, United States of America.
- Hari Krisetyana (2008), *Tingkat Efisiensi Penggelontoran Endapan Sedimen di Waduk PLTA PB. Sudirman – UNDIP*, Semarang, Jawa Tengah, Indonesia.
- HR. Mulyanto (2008), *Efek Konservasi dari Sistem Sabo “ Untuk Pengendalian Sedimentasi Waduk”*, Yogyakarta, Indonesia.
- I Nyoman Pujawan (2009), *Ekonomi Teknik*, Surabaya, Jawa Timur, Indonesia.
- Leslie R. Odom & James R. Morrow, Jr (2006), *What’s this r? A Correlational Approach to Explaining Validity, Reliability and Objectivity Coefficients Paper*
- Perum Jasa Tirta I (2010), *Laporan Kegiatan Flushing Waduk Wlingi – Lodoyo*, Malang, East Java, Indonesia.
- Margareta b Jansson and Ulf Erlingsson (2000), *Measurement and Quantification of a Sedimentation Budget for a Reservoir with Regular Flushing*, AB Hydroconsult, Drottningatan 7, S-753 10 Uppsala, Sweden.
- M.A. Margolis (1996), *Cost Analysis : Concepts and Methods Outline*, California, United State of American.
- Nippon Koei CO, LTD (2005), *Report on Engineering Studies for The Brantas River and The Bengawan Solo River basin*, Malang, Indonesia.
- N. Talebbeydokhti and A. Naghshineh (2003), *Flushing Sediments Through Reservoir* in Iranian Journal of Science and Technology, Iran

- Niebel, B.W.,(1994). *Engineering Maintenance Management*, New York: Marcel Dekker.
- Omdahl, T.P., (1988). *Reliability, Availability, and Maintainability (RAM)Dictionary*, Milwaukee, Wisconsin: ASQC Quality Press.
- Prof. Dr. Damia Barcelo and Dr. Mira Petrovic (2007), *Sustainable Management of Sediment Resources Vol. I*, Amsterdam, Netherlands.
- Prof. Ahmad Rosdan Razak (2011), *Presentation Lecture of Management Accounting in Management Business*, UTM, Johor Bahru, Malaysia.
- Prof Robert I. Carr, Fellow, ASCE, *Cost – Estimating Principle Paper*
- Perum Jasa Tirta , *Rencana Anggaran Biaya Pekerjaan Swakelola (Dredging) Thn. 2004 – 2010*, Malang, East Java, Indonesia
- Philips F. Oswald (1992), *Engineering Cost Estimating third Edition* , University of Colorado Boulder, Colorado, United States of America.
- Rodney White (2001), *Evacuation of Sediment from Reservoirs*, London, England.
- Robert J. Kodoatie (2005), *Analisis Ekonomi Teknik*, Yogyakarta, Indonesia.
- Robert W. Young (2001), *Departement of The Army Cost Analysis Manual*, United States of America.
- S. Heise (2007), *Sustainable Management of Sediment Resources Vol. 3*, Amsterdam, Netherlands.
- Steward, Rodney D. (1991). *Cost Estimating (2nded.)*. Canada: John Wiley & sons, Inc.

T.L. Regulinski & Yash P. Gupta, *Reliability Cost Estimation : Managerial Perspectives Paper*

U.S. Environmental Protection Agency, *Great Lakes Contaminated Sediments* in
<http://www.epa.gov/glnpo/arcs/EPA-905-B94-003/B94-003.ch1.html>

UNESCO/WHO/UNEP (1996), *Water Quality Assessment, edited by Deborah Chapman*, E & FN, London-England

Walter Rast and Jeffrey Thornton (1999), *Water Resources : Health, Environment and Development, edited by Brian H. Kay*, E & FN Spon, London-England