APPLICATION OF LOW COST AIR DRYING MODEL IN TRADITIONAL SHIPBUILDING

BAYO-PHILIP PATRICK

A thesis submitted in partial fulfilment of the requirements for the award of the degree of Master of Engineering (Marine Technology)

> Faculty of Mechanical Engineering Universiti Teknologi Malaysia

> > JUNE 2013

Special dedication to my beloved WIFE, DAUGHTER and PARENTS.....

ACKNOWLEDGEMENT

Glory be to God almighty for his preservation, sustenance, mercy, and wisdom for the successful completion of this project. First, I would like to express my sincere gratitude to my supervisor and co-supervisor Dr. Eng Jaswar Koto and Prof. Dr. Ir.Ab Saman b. Abd Kader for providing timely academic guidance, useful comments, remarks, mentoring and engagement throughout the learning process of this master thesis. The execution and completion of this research would not have been smooth without their kind support.

I am also highly indebted to all my lecturers, Dr Pauzi, Prof Adi, Dr Faizul Amri Adnan and Dr Fuaad and to all other lecturers of the department of Marine Technology, Faculty of Mechanical Engineering, Universiti Teknologi Malaysia that I could not vividly recall their names; I say God in his mercy will reward you abundantly. My many thanks also go to their respective families.

Apart from my personal efforts, the success of this research work also depends largely on the encouragement and support of many others. I take this opportunity to express my profound gratitude to all the special people who have been instrumental in the successful completion of this thesis. I feel greatly honoured and privileged to come across great friends like you Ayo, Tope, Siow, Tamer, Sulaiman, Mustafa, Sohail, Mohammed, Saber, Mr Henry and Mr Adesina, my class mates and all the entire members of power palace branch of the redeemed Christian church of God Malaysia, your impacts will always be remembered. I would also like to show my greatest appreciation to my wife (funke) for her unconditional support without her encouragement, love, and support, I cannot say for sure if I would have stayed in school for a graduate degree and my beautiful princess (Teniola) who missed daddy's kisses at her tender moments. God bless you for your understanding, endurance and perseverance.

Furthermore, I would like to acknowledge with much appreciation the crucial role of my parents Mr and Mrs Bayo Philip, sincerely speaking I got a deeper understanding of what parenting is all about during the entire period of my study. I enjoyed a great deal of love, guidance, support, prayers and encouragement. Mummy and daddy I cannot thank you enough. I feel greatly motivated and I pray that God almighty will reward you and always keep you guys in good health and you will eat the fruits of your labour.

My heartfelt appreciation also go to all my siblings for their continued support through phone calls and social media, Mr and Mrs Adebowale Bayo-philip, Mr and Mrs Deji Philip, Bukola, Muyiwa, Busayo, Bolarinwa and Oladayo. I must not forget to extend my sincere appreciation to my in-laws, my mother in-law, Mrs Balogun, sister in-law Miss Lola Taiwo and to my wonderful mother Mrs mojisola Oguntibeju and children for their prayers and encouragement. God will bless you all.

Finally, my profound gratitude goes to the management and staff of Van Oord dredging and marine contractor for their patience and support.

ABSTRACT

Studies have revealed that delay in production process and delivery is one of the major issues in traditional ship building activities in Indonesia. Some other studies have also established unpredictability of the traditional air drying time as the major culprit responsible for the increase in the length of production time, increase in overall project cost and distasteful client/shipbuilder relationship. In the attempt to address the situation, this study proposes a low cost air drying model as an alternative to the traditional air drying method and adopted Indonesia as the study area. Meteorological data for Indonesia were accessed via the internet. A controlled experiment was performed. Two sets of lumber samples named A and C were dried over a period of seven (7) days. Set A was laid in the model (an improvised green house) set up at an open roof terrace at Block P 23, Faculty of Mechanical Engineering, Universiti Teknologi Malaysia. Set C was equally set up next to Set A but exposed and unprotected from the elements of weather. Lumber weight, relative humidity, temperature and time were taking at intervals for the two sets A and C simultaneously. The data collected were analyzed using Microsoft Excel. Graphs were plotted and interpreted. Lumber drying schedule for both traditional method and the proposed Low Cost Model were developed using meteorological data for a particular area in Indonesia noted for traditional ship building. A comparative analysis of the two schedules was done and the advantages of the Low cost Model over the traditional method were established.

ABSTRAK

Kajian telah mendedahkan bahawa kelewatan dalam proses pengeluaran dan penghantaran adalah salah satu isu utama dalam aktiviti pembinaan kapal tradisional di Indonesia. Beberapa kajian lain juga telah mewujudkan ketidaktentuan masa udara tradisional pengeringan sebagai punca utama yang bertanggungjawab bagi peningkatan dalam tempoh masa pengeluaran, peningkatan kos projek keseluruhan dan pelanggan / kapal hina hubungan pembina. Dalam usaha untuk menangani keadaan kajian ini mencadangkan kos model pengeringan udara yang rendah sebagai alternatif kepada kaedah tradisional udara pengeringan dan pakai Indonesia sebagai kawasan kajian. Data meteorologi untuk Indonesia telah diakses melalui internet. Satu eksperimen kawalan dilakukan. Dua set sampel kayu bernama A dan C telah kering dalam tempoh tujuh (7) hari. Set A diletakkan dalam model (rumah hijau spontan) yang ditubuhkan di teres bumbung terbuka di Blok P 23, Fakulti Kejuruteraan Mekanikal, Universiti Teknologi Malaysia. Set C telah dinubuhkan sebelah Set A tetapi terdedah dan tidak dilindungi dari unsur-unsur cuaca. Berat kayu, kelembapan, suhu dan masa telah mengambil pada jangka bagi kedua-dua set A dan C serentak. Data yang dikumpul dianalisis menggunakan Microsoft Excel. Graf telah diplot dan ditafsirkan. Jadual Kayu pengeringan untuk kedua-dua kaedah tradisional dan cadangan Model Kos Rendah telah dibangunkan menggunakan data meteorologi untuk kawasan tertentu di Indonesia terkenal dengan pembinaan kapal tradisional. Satu analisis perbandingan dua jadual yang telah dilakukan dan kelebihan Model kos rendah berbanding kaedah tradisional yang telah ditubuhkan.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	vi
	ABSTRAK	vii
	TABLE OF CONTENTS	viii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATIONS	xiv
	LIST OF APPENDICES	XV

1	INTR	INTRODUCTION		
	1.1	General		
	1.2	Background of Study		
	1.3	Problem Statement		

1

2

3

1.4	Objective of Study	5
1.5	Research Questions	6
1.6	Scope of Study	6
1.7	Significance of the Study	7
1.8	Expected Results	8
1.9	Research Arrangement	8

2

LITERATURE REVIEW

2.1	Introduction	9
2.2	Use of Lumber in Ship Building	10
	2.2.1 Equilibrium moisture content EQ	10
2.3	Wood Drying	12
2.4	Lumber Drying Methods	15
	2.4.1 Air Drying Methods	15
	2.4.1.1 Open Yard	15
	2.4.1.2 Shed	16
	2.4.1.3 Forced-Air Shed	16
	2.4.1.4Warehouse Pre-drying	17
	2.4.2 Kiln Drying	17
	2.4.2.1 Low Temperature Drying	17
	2.4.2.2 Conventional Steam-Heated Drying	18
	2.4.2.3 Vacuum Drying	18

2.5	Comparative Analysis of Timber Drying	
Meth	ods	18

RESEARCH METHODOLOGY

3

4

5

3.1	Introduction	20
3.2	Design of Operational Framework	20
3.3	Data Collection	23
	3.3.1 Data Collection Tools / Instrument	23
	3.3.2 Data Collection Procedure	23
	3.3.2.1 Apparatus	23
	3.3.2.2Experimental setup	24
3.4	Data Analysis	25
3.5	Apply the Obtained Data to Generate a Schedule	26

DATA COLLECTION

4.1	Introduction	27
4.2	Construction of the Air Drying Model	27
4.3	Experimental Setup and Procedure	28
4.3	Immersion of Samples in Water	29
4.4	Sample Arrangement	31
4.5	Data Collection	32

RESULT AND ANALYSIS

5.1 Experimental Results	36
--------------------------	----

	5.1.1	Required Drying Time of Lumber.	36
	5.1.2	Comparison between the Use of the Propose	ed
		Model and Traditional Method.	40
	5.1.3	Effect of Air Drying on the Size of the	
		Lumber	41
5.2	Apply	ing the Air Drying Time Data to Generate	
	Sched	ule	42
	5.2.1	Assumptions	42
5.3	Predic	tion of total drying cycles	44
5.4	Drying	g Scheduling and Delay Time	46
5.5	Summ	ary	56

CONCLUSION AND RECOMENDATION

6

7

6.1	Introduction	58
6.2	Research contribution	58
6.3	Conclusion	59
6.4	Recommendation and Future works	59

REFERENCES

APPENDICES A-I 64

xi

60

LIST OF TABLES

TABLE NO.	TITLE	PAGE
4.1	The time interval used for the first day	33
4.2	The time interval used for the day two and day three	33
4.3	The time interval used for day four today seven	34
5.1	The initial data for sample A after immersion	37
5.2	Series 60 – 4252 and Traditional Wooden Ship particulars	45
5.3	Comparison between both the drying methods	56

LIST OF FIGURES

FIGU	JRE NO. TITLE	PA	PAGE	
1.1	Drying lumber method in Kepulauan Riau, Indo	nesia	3	
3.1	Research flow of optimization of traditional ship	production.	22	
4.1	Construction of the Air Drying model		28	
4.2	Samples immersed in water		30	
4.3	Measuring initial weight of sample A after imme	rsion	30	
4.4	The arrangement of the samples		31	
4.5	Experiment under rain showers		32	
4.6	Sample A being weighted		34	
4.7	Sample C being weighted.		35	
5.1	Graphs showing the air drying time of lumber in	two specific conditions	39	
5.2	Rainfall for June, 2013 by Department of Irrigation	on and		
	Drainage Malaysia.		40	
5.3	Effect of rainfall on drying of lumber using the p	roposed technique and		
traditi	ional technique.		41	
5.4	Effect of air dry time on the size lumber using the	e proposed technique.	42	

5.5	The (2012) annual rainfall distribution for Kepulauan Riau, Indonesia	44
5.6	Rainfall distributions for the month of January, 2012	49
5.7	Rainfall distributions for the month of April 2012	50
5.8	Rainfall distributions for the month of June, 2012	50
5.9	Rainfall distributions for the month of December, 2012	51
5.10	Lumber Drying schedule for April 2012.	52
5.11	Lumber Drying schedule for June 2012	53
5.12	Lumber Drying schedule for December 2012.	54
5.13	Lumber Drying schedule for January, 2013	55

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
А	Moisture Decrease 1	64
В	Moisture Decrease 2	65
С	Moisture Decrease3	66
D	Moisture Decrease	67
E	Sample a Moisture decrease characteristics	68
F	Moisture decrease4	69
G	Moisture decrease5	70
Н	Moisture decrease6	71
I	Moisture decrease Characteristics	72

CHAPTER 1

INTRODUCTION

1.1 General

This study begins with a history of Indonesia maritime culture and highlights the evolution of traditional wooden ship. It also identifies some of the peculiar problems associated with traditional shipbuilding process in Indonesia particularly the issue of delivery. It then goes on to examine ways of proffering a solution to the identified problem. The study through the application of experimental techniques investigated the air drying time of lumber in two specific conditions. In addition, the data collected from the model test is analyzed and applied. The study proposes and advocates the adoption of low cost air drying technique of lumber. The study posits that the adoption of the air drying technique has the capacity to impact positively on the production process in traditional shipyards and ultimately lead to optimization of the production process. Lastly, it suggests areas of interest for future studies.

1.2 Background of Study

Indonesia traditional ship is a product of an indigenous technology developed long before the advent of western culture along the Coast of Sulawesi Island. The ships are built traditionally in both method and equipment without any sketches or calculations. The building expertise is passed down from generation to generation, a knowledge that is further honed through daily practice with the help of each builder's instincts and natural gift. Still built by hand in the traditional manner, these majestic sailing ships are a living spirit of the golden age of sail, which ended in the West in the early twentieth century, but still thrives in the waters of Indonesia.

The beauty and efficiency is not a product of technical science, they are a product of the spiritual nature of these people and their culture. They are at one with their environment and they follow a path of least resistance in their lives and in their work. This philosophy contributes to the beauty and efficiency of their ship designs, and it comes from a basic and simple understanding of the world in which they live. This philosophy based nature and balance allowed the peoples of the Indonesian islands to produce solutions to practical challenges long before the societies of Europe were able to.

In as much as one would like to appreciate the people and their philosophy, it is also good to mention that a mix of local craft and beliefs plus modern and scientific ways of doing things will go a long way in transforming the practice of ship building in Indonesia. Advances in science and technology, and abundant information available on the World Wide Web has caused unprecedented changes in many areas of human endeavor. However, Indonesian traditional ship builders have not taken full advantage of available technology and information particularly in the preparation of lumber which remains one of the critical and most unpredictable stages in construction. They have failed to explore outside the ancient method of wood preparation other possible ways of making lumber ready for use in shipyards. Nofrizal *et al*, 2012 has raised the drying lumber issue in traditional shipbuilding in Kepulauan Riau, Indonesia which is shown in Figure.1.1.



Figure1.1: Drying lumber issue in traditional ship production in Kepulauan Riau, Indonesia.

It is in the light of the above statement that this study will like to identify from literature different ways of preparing lumber for use in traditional shipyards and proposed a low cost model that may help in impacting the practice of traditional ship building in Indonesia positively.

1.3 Problem Statement

Literature reviewed revealed that several studies have identified some of the specific issues central to traditional ship construction in Indonesia. Mufti *et al*, 2012, lamented the lack of a blueprint or formal sketches as well as calculations on performance during the design stage. The study stated that the traditional ship

designs are derived from the replication of an existing ship that is serving its purpose well or from informal conversation between the shipbuilders and the client.

In another study, E. Prayetno *et al*, 2012, dwelt on quality control issues in traditional shipbuilding. The study mentioned that there is no standard quality control measure in the choice of materials. The master builders depend heavily on their senses specifically visual assessment and on the job experience acquired over the years. There is no scientific approach to quality control.

Moreover, A. Deah *et al* 2012, addressed safety issues from the perspectives of occupational safety and policies .The study observed that at the construction stage most of the builders failed to take necessary precautions to arrest issues that can expose workers to fatal injuries and jeopardize their health. For instance workers are not provided with the required safety wears such as helmet, boot, hand gloves that can protect them against injuries. Furthermore, the study highlighted non compliance to specified safety regulations at the point of ship building as laid down by government appointed regulatory agencies.

It is important to mention that some other studies have identified delivery as one of the critical issues in traditional ship building process. Surhan *et al* 2012, mentioned that the traditional shipbuilding process follows a certain unique procedure, a procedure which been handed down from one generation to another generation. The study posited that the unique procedure adopted by the builders was often fraught with flaws. These observed flaws make it almost impossible to give a definite start or completion date for a given project.

One of the major flaws cited by Surhan et al 2012, centred on the refusal of the builders to take advantage of available knowledge in modern day science and technology. The preparation and processing of wood for construction till date still take place in the open air. Consequently, wood air drying time remains dependent on prevailing weather conditions. Hence, it is difficult to estimate or project the time required to air dry a given quantity of wood needed to build a specific ship size.

Modern technology nowadays however, does allow wood drying to be carried out in diverse ways instead of just drying outside under the sun. This makes room for better and consistent results as the process can be partly or fully controlled. Not only that, it can also help in the projection of air drying time of wood and also encourage the application of scheduling tools at the construction stage. Application of scheduling tools in return may be an advantage in the optimization of the overall ship production process.

The focus of this study is to discuss and address lumber air drying time, and also develop a model that can be used in air drying time calculation. The ultimate goal is to propose a low cost air drying model which may be used to predict the time required to prepare a specific needed quantity of lumber for a given size of ship. This study believes that the proposed model with the ability to predict time for air drying of lumber will eliminate non standardization of time which has been a familial and perennial problem and hence the optimization of the overall production process through the application of scheduling tools.

1.4 Objective of Study

The objectives of this research are as follows:

i. To establish from literatures the different methods employed in drying of lumber.

- ii. To develop a low cost model that can be used to predict the air-drying time of lumber.
- iii. To conduct an experiment for estimating air-drying times of lumber in two specific conditions
- iv. To generate a comparable schedule of lumber air-drying time in specific conditions.

1.5 Research Questions

The research work has actually raised a few questions in order to have a clear understanding of the implications of the research prior to when the final results will be obtained. These questions are:

- i. What are the major building materials in traditional shipbuilding?
- ii. Where are the materials located?
- iii. How are the materials treated or prepared?
- iv. What are the likely challenges in material preparation?
- v. What are the likely consequences of the challenges in 4 above?
- vi. How can the challenges in 4 above be eliminated?

1.6 Scope of Study

The scope of this study includes the following:

- i. It is experimental in nature
- ii. It is a quantitative study
- iii. It is not a case study.

- iv. Limited to study of traditional ship in Indonesia.
- v. It is not a study of physical properties of lumber though it may involve a little of discussions on physical attributes of lumber

1.7 Significance of the Study

This study is significant because traditional wooden ship continues to be the vessel of choice for Indonesian fishermen. However, the unplanned work environment plus the exposure of both workmen and materials to the elements of weather make the production process especially lumber drying time highly unpredictable. Consequently, the builders often times find it difficult to prosecute contract jobs and deliver the finished product within the time specified in the contractual agreement.

Failure on the part of the builder to deliver has implications for builder-client business relationship as well as economic implications for both the builder and the client. The study of this nature has the potential to improve in a measurable manner the quality of the work environment as well the organisation of work within the shipyard. It can also help in the introduction of standardization of work breakdown which may encourage the use of scheduling tools. This study is of the opinion that the use of scheduling tools will ultimately lead to optimization of production processes within the sphere of traditional shipyards. In addition the optimization of the process may

- i. reduce project duration
- ii. reduce project costs
- iii. improve project efficiency
- iv. improve builder/client business relationship

1.8 Expected Results

Upon the completion of the experiment and analysis of data collected it is expected that:

- i. The proposed model should be able to predict the time required to air dry a specific quantity of wood.
- ii. The cumulative time required for air drying maybe translated into the overall production process and hence generate a practicable and an effective scheduling structure which may be put to test on real shipyard environment.

1.9 Research Arrangement

The arrangement of this research is shown below:

- i. The chapter one is the introduction to research problem which comprises of research background, problem statement, scope of study, and expected result.
- ii. Chapter two is conducting a literature review of existing research studies.
- iii. Chapter three is the research methodology
- iv. Chapter four is the data collection, analysis, and results.
- v. Chapter five is the discussion of the result obtained in Chapter 4.
- vi. Finally, chapter six is a conclusion, recommendation for future work.

REFERENCES

- A J; De Zeeuw, Carl Panshin, 1970, Structure, Identification, Uses, and Properties of the Commercial Woods of the United States and Canada. 0852-1697.
- Arfena. D et al 2012, Safety Issues in Production Traditional Ships in Kepulauan Riau-Indonesia, the 6th Asia-Pacific Workshop on Marine Hydrodynamics, Pp.496 - 500, Malaysia.
- Aulia Windyandari, 2008. Prospek Industri Galangan Kapal Dalam Negeri Guna Menghadapi Persaingan Global. Teknik – Vol. 29 No. 1 Tahun 2008, Issn
- Cochran, K. 2007. *Rule-Based Ship Design*, Rina International Conference on Computer Applications In Shipbuilding, Vol. 2, Pp 133-140.
- Eko.P et al 2012, Quality Issues in Traditional Ship Production in Kepulauan Riau-Indonesia, the 6th Asia-Pacific Workshop On Marine Hydrodynamics, Pp.491 - 495, Malaysia.
- Eyres David J. 2007. *Ship Construction*. Elsavier Ltd. Departement Oxford. Uk.
- Gaasbeek Richard M. Van. 1918. A Practical Course in Wooden Boat and Ship Building, the Fundamental Principles and Practical Methods Described in Detail. Frederick J. Drake & Co., Chicago.
- H. Saputra et al 2012, Critical Path Analysis of Traditional Ship Production in Kepulauan Riau-Indonesia, the 6th Asia-Pacific Workshop on Marine Hydrodynamics, Pp.577 - 581, Malaysia
- Karr, D. *et al*, 2009. Committee Iv.2: *Design Method*, 17th International Ship and Offshore Structures Congress, Seoul, Korea.
- Lars Hansson, 2007. *Microwave Treatment of Wood*, An Unpublished Phd Dissertation Submitted to Division of Wood Physicsluleå University of Technology Ltu Skellefteå.

- Lee, D. And Lee, K.-H. 1999. An Approach to Case-Based System for Conceptual Ship Design Assistant, Expert Systems with Applications, Vol. 16, Pp 97–104.
- Jennifer Hayes, *Home of the Bugis Boat Builders* Wera, Sumbawa, Http://Www.Seatrekbali.Com/Blog/Item/229-Bugis-Boat-Builders-Wera-Sumbawa.
- Maidin, P. (2003). *Tukang Timbal Fostering Boat: Tradition and Innovation*, Sari 21, Pp 39-56.
- Mufti F.M *et al* 2012, *Design Issue In Traditional Shipbuilding Process*, The 6th Asia-Pacific Workshop on Marine Hydrodynamics, Pp.571 576, Malaysia.
- Nofrizal et al 2012, Production Process of Traditional Ships in Kepulauan Riau-Indonesia, The 6th Asia-Pacific Workshop On Marine Hydrodynamics, Pp.110 - 117, Malaysia.
- Ramanathan, C et al. 2012. Construction delays causing risks on time and cost a critical review, Australasian Journal of Construction Economics and Building, 12 (1) 37-57
- Risandi.D.P et al 2012, Planning of Traditional Ship Production in Bintan-Indonesia, the 6th Asia-Pacific Workshop On Marine Hydrodynamics, Pp.592 - 595, Malaysia..
- Surhan Jamil Haron *et al* 2012, *Delivery Issues in Malaysian Traditional Ship Production Process*, the 6th Asia-Pacific Workshop on Marine Hydrodynamics, Pp.588 - 591, Malaysia.
- Marcia V.B *et al*, 2005, Evaluation of Wood Sorption Models for High Temperatures, University Laval,

Http://Theses.Ulaval.Ca/Archimede/Fichiers/23403/Ch04.Html#D0e4153

Mickeviciene Rima. 2011. *Global Competition in Shipbuilding: Trends and Challenges for Europe*. The Economic Geography Of Globalization. Isbn: 978-953-307-502-0.

Paul De Saint Front (*Boatbuilding In Indonesia*) Http://Yachtcreative.Com/Categories/Wahoob/21/Boatbuilding-Indonesia.Html

Putri, S. P. 2009. Risk Management for Traditional Boat Building - Phinisi Type, Degree Thesis, Civil Engineering, Faculty Of Engineering, University of Indonesia.

- S. Vongpradubchaia; P. Rattanadechoa, 2011. Microwave and Hot Air Drying of Wood Using a Rectangular Waveguide, Research Center of Microwave Utilization In Engineering (R.C.M.E.), Faculty Of Engineering, Department of Mechanical Engineering, Thammasat University (Rangsit Campus), Pathum Thani, Thailand.
- Salam, A. and Katsuya, O. 2008. Technological Adaptation in the Transformation of Traditional Boats in the Spermonde Archipelago, South Sulawesi, Southeast Asian Studies, Vol. 46, No. 2, Pp 200-227.
- Shin, S.-C, Lee, S.-S., Kang, D.-H., And Lee, K.-H. 2012. The Development Of Internet Based Ship Design Support System for Small and Medium Sized Shipyards, International Journal of Naval Architecture And Ocean Engineering, Vol. 4, Issue 1, Pp 33-43.
- Simpson, William T. 2004. Estimating Air Drying Times of Lumber with Multiple Regressions. Res. Note Fpl-Rn-0293. Madison, Wi: U.S. Department Of Agriculture, Forest Service, Forest Products Laboratory.6 P.
- Simpson, William; John Tschernitz 1979. *Importance of Thickness Variation in Kiln* Drying Red Oak Lumber. Corvallis, Oregon: Western Dry Kiln Clubs.
- Steinhagen, H.P. 1977. Thermal Conductive Properties of Wood, Green or Dry, from -40 to 100 °C: A Literature Review. Usda Forest Service General Technical Report Fpl-9, Forest Products Laboratory, Madison, Wi.
- Teesdale L. V., 1942, Air Drying of Lumber, Seasoning Wood for Ship Construction, United States Department of Agriculture Forest Service, Forest Products Laboratory Madison, Wisconsin in Cooperation With The University of Wisconsin.
- Turan, O., Aksu, S., and Cui, H. 2006. Case-Based Reasoning Approach to Ship Design, Journal of Harbin Engineering University, Vol. 27, Issue Supl. 2, Pp 122-132.
- Vincent Obiajulu Ogwuagwu, 2007. Numerical Simulation of Moisture Transfer in Wood Drying in Open-Wall Timber Shades, Mechanical Engineering
 Department, Federal University Of Technology, Minna, Nigeria, Leonardo
 Journal of Sciences Issn 1583-0233, P. 17-24

Wu, Y.-H. And Shaw, H.-J. 2011. Document Based Knowledge Base Engineering

Method for Ship Basic Design, Ocean Engineering, Vol. 38, Pp 1508–1521.

- Zbigniew J. Karaszewski. 1991. Infrastructure Study in Shipbuilding: A Systems Analysis of U.S. Commercial Shipbuilding Practices. 1991 Ship Production Symposiumproceedings: Paper No. Va.
- Zhuo Liu, David Kim Huat Chua and Ker-Wei Yeoh. 2011. Aggregate Production Planning for Shipbuilding with Variation - Inventory Trade - Off. International Journal of Production Research. Vol. 49, No. 20, 15 October. 6249-6272.