# SUPERVISORY CONTROL OF PARALLEL HYBRID ELECTRIC VEHICLES USING MATLAB/ SIMULINK

SAJJAD ABDOLLAHZADEH ANBARAN

UNIVERSITI TEKNOLOGI MALAYSIA

Replace this page with the Cooperation Declaration form, which can be obtained from SPS or your faculty.

# SUPERVISORY CONTROL OF PARALLEL HYBRID ELECTRIC VEHICLES USING MATLAB/ SIMULINK

### SAJJAD ABDOLLAHZADEH ANBARAN

A project report submitted in partial fulfilment of the requirements for the award of the degree of Master of engineering (Electrical-Power)

> Faculty of Electrical Engineering Universiti Teknologi Malaysia

> > JULY 2012

"To my parents, beloved brothers and sisters"

#### ACKNOWLEDGEMENT

Praise be to Allah, The Lord of universe. Only with His uncountable favors that I can finish this work. Wish He accept all of my faithful learning efforts as the way I sincerely express my gratefulness.

First and foremost, I would like to express my sincere gratitude toward my supervisor, Assoc.Prof. Nik Rumzi bin Nil Idris, for his advanced guidance, constant assistance, technical suggestions and encouragement in making this project a success.

Furthermore, I thank all the personnel at Universiti Teknologi Malaysia (UTM) for their effort to provide an interesting program and a nice working environment.

Last but not least, I dedicate my thesis to my family, especially my parents, who continuously provided me love and support in accomplishing my study.

Skudai, Johor - Malaysia Sajad A.Anbaran

#### ABSTRACT

Due to the limitation of fossil fuels and the high consumption rate of this energy for transportation, inclination of vehicle industry toward other sources of energy is inevitable. Electric vehicles and hybrid vehicles could be a good solution. Thanks to the state of art electric motors, power electronics, embedded power train controller, energy storage systems like batteries and ultra capacitors, the performance of the vehicle could become more and more energy efficient. Since the integrating of all these components in a drive train configuration could be a challenge for the manufacturer, computer simulation and modeling before prototyping could be really beneficial in terms of cost, safety and design performance.

The main objective of this study is to establish a systematic approach to parallel hybrid electric vehicle modeling and simulation as well as implementation of the supervisory control in order to improve system efficiency and reduce fuel consumption. This thesis offers an overview of the various applied control strategies in hybrid electric vehicles, specifically to the parallel hybrid electric vehicle. Several control strategies are described in literature as well as important of supervisory control strategy in hybrid electric vehicle and the difference in terms of energy management is discussed.

Different hybrid power-train configuration are presented and explained in this thesis. Hybrid electric vehicle driveline components including electric motor, vehicle dynamic, internal combustion engine and electric energy storage are illustrated. In addition, some of the principles of modeling and simulation are discussed and different methods of modeling are presented. A detailed parallel hybrid vehicle modeling and simulation in Matlab environment using Simscape toolbox is presented. A rule-based supervisory control strategy using Simulink/Stateflow is applied to control hybrid vehicle in order to operate parallel hybrid driveline component in their optimal region and consequently to achieve high-performance low-emission hybrid drive-train. Simulation results for the major components of hybrid driveline are presented to demonstrate the effectiveness of this supervisory control strategy.

#### ABSTRAK

Disebabkan oleh bahan api fosil yang terhad dan kadar penggunaan bahan api ini yang tinggi bagi kegunaan pengangkutan, kecenderungan industri automotif untuk berubah kepada sumber tenaga lain tidak dapat dielakkan. Kenderaan elektrik dan hibrid merupakan satu penyelesaian yang terbaik. Terima kasih kepada kemampuan motor elektrik, elektronik kuasa, pengawal pemacu, sistem penyimpan tenaga seperti bateri and kapasitor ultra, prestasi kenderaan ini mampu menjadi lebih baik lagi. Disebabkan oleh penggunaan komponen-komponen ini dalam sistem konfigurasi pemacu menjadi satu cabaran kepada industri pembuatan kenderaan, simulasi komputer dan pemodelan sebelum penghasilan prototaip mampu memberi manfaat dari segi kos, keselamatan dan rekabentuk.

Objektif utama kajian ini adalah untuk menghasilkan satu kaedah pendekatan sistematik untuk pemodelan dan penyelakuan kenderaan hibrid elektrik selari serta perlaksanaan kawalan penyeliaan bagi menambah baik kecekapan sistem dan mengurangkan penggunaan bahan api. Thesis ini membentangkan tinjauan tentang pelbagai strategi kawalan bagi kenderaan elektrik hibrid, khususnya kenderaan elektrik hibrid selari. Beberapa strategi kawalan yang telah dihasilkan beserta kepentingan strategi penyeliaan kawalan di dalam kenderaan elektrik hibrid serta perbezaan dari segi pengurusan tenaga juga dibincangkan.

Perbezaan konfigurasi pemacu hibrid akan dibentang dan dibincangkan dalam thesis ini. Komponen kenderaan elektrik pemacuan seperti motor elektrik, dinamik kenderaan, enjin pembakaran dalaman dan penyimpan tenaga elektrik juga disampaikan. Disamping itu, beberapa prinsip permodelan dan simulasi juga dibincangkan dan kepelbagaian teknik permodelan dibentangkan. Satu penerangan terperinci mengenai permodelan kenderaan hibrid selari dan simulasi di dalam persekitaran Matlab menggunakan Simscape dibentangkan. Strategi berasaskan syarat untuk strategi kawalan penyeliaan menggunakan Simulink/Stateflow telah digunakan dalam kawalan kenderaan hibrid untuk memastikan komponen pemacu beroperasi secara optima dan seterusnya mencapai kecekapan tinggi serta perlepasan pencemaran udara yang rendah. Keputusan simulasi untuk komponen utama dalam pemacuan hibrid dibentangkan bagi menunjukkan keberkesanan kaedah penyeliaan kawalan ini.

### TABLE OF CONTENTS

CHAPTER			]	TITLE	PAGE
	DECLARATION				ii
	DEDI	CATION			iii
	ACKN	OWLED	GEMENT		iv
	ABST	RACT			v
	ABST	RAK			vi
	TABL	E OF CO	NTENTS		vii
	LIST	OF TABL	ES		Х
	LIST	OF FIGUI	RES		xi
1	INTRO	ODUCTIO	DN		1
	1.1	Backgro	ound of the	e study	1
	1.2	Stateme	ent of the p	roblem	3
	1.3	Purpose	e of the stu	dy	3
	1.4	Objecti	ves of the s	study	4
	1.5	Signific	ant and sco	ope of the study	4
2	LITEI	RATURE	REVIEW		5
	2.1	Introdu	ction		5
	2.2	A breif	history of	HEVs	6
	2.3	Archite	cture of Hy	brid Electric Drive Train	7
		2.3.1	Series H	ybrid Electric Drive Train	7
		2.3.2	Parallel	Hybrid Electric Drive Train	9
		2.3.3	Drive tra	in components	11
			2.3.3.1	Internal Combustion Engine	11
			2.3.3.2	The ICE modelling	12
		2.3.4	The elec	tric machines	14
		2.3.5	The ener	gy storage System	17
			2.3.5.1	The battery	17
			2.3.5.2	Capacitors	19

		2.3.5.3	Power Electronics Converters	21
	2.3.6	Vehicle	Dynamics	21
		2.3.6.1	Rolling resistance	22
		2.3.6.2	Aerodynamic Drag	22
		2.3.6.3	Uphill Resistance	23
		2.3.6.4	Acceleration Force	23
2.4	Control	strategies	for hybrid vehicles	24
	2.4.1	Rule-bas	sed control strategies	25
		2.4.1.1	Deterministic rule-based strate-	
			gies	26
		2.4.1.2	Fuzzy rule-based methods	27
	2.4.2	Optimiz	ation based control strategy	27

# 3 METHODOLOGY

28

3.1	Introdu	ction	28
3.2	Sizing	of the driveline's component	28
	3.2.1	Engine Power Capacity	29
	3.2.2	Electric Motor Power Capacity	30
	3.2.3	Transmission design	31
	3.2.4	Energy storage system	32
3.3	Parallel	HEV Simulation	32
	3.3.1	Vehicle Dynamic Subsystem	33
	3.3.2	Electric Component Subsystem	34
		3.3.2.1 Electric Motor	35
		3.3.2.2 DC-DC Converter	36
		3.3.2.3 Energy storage/Battery	37
	3.3.3	Mechanical Component Subsystem	38
		3.3.3.1 Engine Simulation and Mod-	
		elling	38
		3.3.3.2 Mechanical Coupling devices	38
	3.3.4	Control Subsystem	40
	3.3.5	Parallel Hybrid Electric Vehicle Perfor-	
		mance Test	44
	3.3.6	Driver Model	44
	3.3.7	Fuel Economy Analysis	47

4	SIMULAT	49	
	4.1 In	troduction	49

	4.1.1	ECE 15 Cycle	49
	4.1.2	EUDC Cycle	56
	4.1.3	EUDC Cycle for low-powered vehicles	61
	4.1.4	FTP 72 Cycle	65
	4.1.5	Self-defined Drive Cycle	70
	4.1.6	Parallel HEV Fuel Economy	75
CON	CLUSION	AND RECOMMENDATIONS	77
5.1	Conclu	sion	77
5.2	Future	Works	78
DEFE	THOPS		
KEFF	<b><i>(ENCES</i></b>		80

REFRENCES				
-----------	--	--	--	--

5

іх

# LIST OF TABLES

TABLE NO.	TITLE	
3.1	Engine parameters	30
3.2	Battery specification	32
4.1	Parallel HEV fuel economy based on stuided driving	
	cycles	76

### LIST OF FIGURES

### FIGURE NO.

### TITLE PAGE

2.1	Functional block diagram of a series hybrid vehicle	8
2.2	Configuration of a series hybrid vehicle	8
2.3	Functional diagram of the parallel hybrid electric vehicle	10
2.4	Configuration of the parallel hybrid drive train	11
2.5	Schematic of typical 4S, gasoline engine	12
2.6	Power, Torque and SPC characteristics for ICE	13
2.7	SPC and efficiency of the typical ICE at different load	
	condition	13
2.8	Engine Static Model	13
2.9	A typical Electric Motor efficiency map	15
2.10	The Electric machine in generating mode	16
2.11	Motoring Mode	16
2.12	General Model of energy storage system[3]	18
2.13	Battery Circuit Model	19
2.14	Circuit model of super-capacitor pack	20
2.15	Acted Forces on vehicle	21
2.16	Classification of the hybrid power train control strategy	25
3.1	Motor torque-speed characteristics	31
3.2	Dynamic conceptual block diagram	33
3.3	Vehicle dynamic subsystem in Matlab/Simulink	34
3.4	Functional diagram of a typical electric propulsion	
	system	35
3.5	Electric motor Simulation in Simulink/Simscape	35
3.6	Motor torque-speed characteristics inserted in servomo-	
	tor block	36
3.7	DC/DC converter model in Simulink/Simscape	37
3.8	Battery Model in Simulik/Simscape	37
3.9	Engine simulation in Matlab/Simulink environment	38
3.10	Conceptual configuration of the speed coupling parallel	
	HEV	39

3.11	Planetary gear unit	40
3.12	Hybrid electric drive train with speed coupling of	
	planetary gear	40
3.13	Parallel HEV overall control scheme	41
3.14	Parallel HEV supervisory control strategy	42
3.16	Parallel HEV various operating mode	43
3.15	Parallel HEV supervisory control logic in stateflow	43
3.17	ECE 15 Cycle	44
3.18	EUDC Cycle	45
3.19	EUDC Cycle for low power Vehicles	45
3.20	FTP-72 Cycle	46
3.21	Self-defined Drive cycle	46
3.22	Driver Model block in Matlab/Simulink	47
3.23	Parallel HEV fuel economy	48
4.1	Vehicle output speed for ECE 15 drive cycle	50
4.2	EM gnerator torque for motion mode and regenerative	
	mode	51
4.3	Power generation for driving based on ECE 15	52
4.4	ICE generated torque	52
4.5	ICE throttle control signal	53
4.6	ICE output speed	54
4.7	Automative driver (Accelerator ) control signal	55
4.8	Electric characteristics of the dc bus	55
4.9	Battery SOC characteristics for ECE 15	56
4.10	Vehicle output speed for EUDC cycle	57
4.11	ICE power genratrion for EUDC	57
4.12	Engine speed under EUDC driving condition	58
4.16	Battery SOC characteristics based on EUDC	58
4.13	Engine throttle command	59
4.14	Accelerator command signal	59
4.15	Generated torque by EM	60
4.17	Vehicle dc bus characteristics	60
4.18	Vehicle output speed	61
4.19	Power generation by ICE	62
4.20	Produce torque by ICE	62
4.21	Throttle command to ICE	63
4.22	ICE speed (rpm)	63
4.23	Accelerator command signal based on EUDC	64
4.24	Generated torque by EM	64

4.25	Battery SOC characteristics	65
4.26	Vehicle output speed	66
4.27	ICE power generation on the basis of the FTP drive cycle	66
4.29	Engine Speed (rpm) based on FTP 72	67
4.28	ICE torque generation based on the FTP drive cycle	67
4.30	Automative driver command signal	68
4.31	Engine speed control throttle command signal	68
4.32	Motor Torque generation characteristics based on FTP	
	72	69
4.33	Battery State of Charge characteristics for FTP 72	69
4.34	DC bus electrical characteristics	70
4.35	vehicle output speed	71
4.36	Engine speed, rpm	71
4.37	Delivered torque to the load by ICE	72
4.38	Delivered power to the driveline by ICE	72
4.39	Throttle command to ICE	73
4.40	EM torqe baed on self-defined test driving cycle	73
4.41	Automative driver command to the control unit	74
4.42	DC/DC bus characteristics	74
4.43	Battery SOC characteristics	75

### LIST OF ABBREVIATIONS

EV	-	Electric Vehicle
HEV	-	Hybrid Electric Vehicle
ICE	-	Internal Combustion Engine
SOC	-	State Of Charge
EM	-	Electric Machine

### LIST OF SYMBOLS

$A_f$	-	Frontal Area
C	_	Capacitance
d	_	Piezoelectric Transmission Coefficient
E	_	Energy
F	_	Force
f	_	Frequency
$f_r$	_	Resistance Coefficient
$C_D$	_	Aerodynamic Drag Coefficient
$C_r$	_	Frictional Constant
J	_	Inertia of the vehicle
M,m	_	Mass
P	_	Power
$Q_{tot}$	_	Capacitor Total Charge
$R_{eq}$	_	Capacitor Equivalent Resistance
T	_	Period
V	_	Voltage
i(t)	_	Current
$i_t$	_	Transmission Efficiency
W	_	Weight
r	_	Tire Radius
α	_	Road Gradient
$\delta$	_	Mass Factor
$\eta$	_	efficiency
ρ	_	Air Density
τ	_	Torque
ω	_	Angular Velocity
	_	

#### **CHAPTER 1**

#### **INTRODUCTION**

### **1.1 Background of the study**

The sharp rise in petroleum consumption and fuel importing and consequently detrimental environmental effects of the fuel consuming tool cause serious concern on the economy and environment in the most countries. According to statistics, transportation is the one the most fuel consuming sectors. Two third of the imported petroleum in the developed countries are being consumed in transportation sector.

Since the dominant meant of the transportation has been in the form of the personal automobiles, this area has gained more attention. Limited domestic oil natural reserves and the extensive use of the personal cars have led to some economical concern and countries dependence to foreign oil markets. Half of consumed petroleum in the USA were imported. This shows the extend of the country's economy vulnerability to varying petroleum price and other related issues.

Owing to the fact that personal transportation has significant contribution to fuel consuming sector there still exist some hinder for automobile manufacturer production to meet related regulation regarding to vehicles performance, noise and harmful emission. Hence, Improvement of the fuel consumption and overall energy efficiency is one of the most important subjects for developing and designing new vehicles technologies. It is understandable that there exist a contrast between global concern on sustainable energy use and environmental protection. This contradictory clearly call for new technology to play fundamental role. The promising technology to overcome on these obstacles to meet regulations are exploitation of alternative energy sources in vehicle power-train, improving fuel economy and reducing the harmful emission. The new vehicle technology appeared in the forms of Electric Vehicle (EV), fuel cell vehicles, Hybrid Electric Vehicle (HEV). Among alternative power-train solution being investigated, HEVs due to their major advantages on other vehicles are more popular. In general, HEVs have two power sourcesto run the traction simultaneously or respectively in order to propel the vehicle wheels. Moreover, the HEVs are more efficient and performed better with compare to conventional engines. In some controlling circumstances HEVs can be run in zero emission vehicle (ZEV) state. So this fact made HEVs a important player in today's automobile market.

Since research and analyzing is a time consuming process, computer based simulation and modelling is an approach to deal with this limitation. Virtual prototyping, however, can be used to reduce the expenses and the length of the design cycle. Variety of the vehicle simulator such as SIMPLEV, HVEC, CarSim, ADVISOR and so on are available.

Many studies and researches have been carried out on hybrid electric vehicles. However, most of them used different simulation and modelling tools to perform their study. In the reference [10] a series hybrid and electric vehicle drive-train is modelled and simulated on PSCAD which is a transient simulation program. In addition in references [3], [14], [15], [16], [17], [18] various topologies of the hybrid electric vehicle have been investigated. In ref [1] PSAT is used to analyze performance of the HEV. Furthermore, researcher in ref[14] modeled and compared in both HEVSIM and ADVISOR then simulation results which is more accurate were compared. On the other hand, many technical control strategies have been proposed and at the same time investigated by references [8], [5], [1], [11] in which in ref [12] authors tried to introduce new vehicle controlling to fully meet driver desires. Past control methods were sensitive to different driving habits and vehicle parameters variation. Thus researcher in ref [12] has implemented neural network concept as control strategy to eliminate this flaw. Moreover, in ref [6], [19] several available types of batteries in the ADVISOR library are introduced. In addition, the temperature impact on the vehicle performance and life cycle of the battery is studied. Finally, a optimization study has been conducted to achieve low-weight and more fuel-economy HEV in ref [2].

#### **1.2** Statement of the problem

It is evident that the great amount of the fuel is being consumed by personal transportation and they have significant contribution on harmful emissions. Therefore, increasing concerns about environmental issues such as global warming and greenhouse emissions as well as natural oil sources depletion have made energy efficiency and being environmentally friendly as primary selling point for automobiles. In spite of the fact that HEVs offer some important advantages in comparison to conventional engines, their configuration comprise more component and greater complexity with higher initial price. Thus, implementation of the simulator software to predict the behaviour of the vehicular system under various circumstances are inevitable.

Compared to conventional vehicles, hybrid electric vehicles consist of more component (electrically and mechanically) and this increase the complexity of the vehicle system. In addition to these electrification component and subsystems, the dynamic analysis of the various component interaction becomes difficult. Modelling and simulation are absolutely necessary for concept evaluation, prototyping and analysis of the newly design HEV. Therefore, a modelling and simulation environment to model subsystems, embedded software and component is needed[2].

In the other word, in order to realize the benefits of HEVs, the designs must be extensively modelled and refined before improved emissions and fuel economy can be implemented on a large scale. This will require accurate, flexible simulation tools, which will expedite the design processes for HEVs. This will enable engineers to compare the relative performance of one design to another and concentrate on the best designs.

### **1.3** Purpose of the study

with an increasing growth of the concerns about environmental related issues which is partly contributed by the passengers cars in harmful emissions draws attention to this sector. Furthermore, the selection and analysis of the appropriate propulsion systems role in the reduction of the fuel consuming, long travelling range and efficiency are considerable. This increasing demand for more implementation of the fuel economy and efficient vehicles cause automobile designer to shift toward the design of new generation power-trains beyond the conventional (fuel-only) engines. Hence, the vehicles hybridization and enhanced design leads to fulfil the constraints and regulations on petroleum and environment. Simulation is one the efficient way in the design and analysis of different levels of the propulsion system before physical testing and construction begins. Furthermore, it provide this capability to examine various control strategy to have efficient running of the vehicle. The purpose of this study is to achieve greater understanding of the HEVs design and simulation, as well as, their impact on environment.

### 1.4 Objectives of the study

The objective of this study are:

- To simulate parallel configuration of the Hybrid Electric Vehicle using Matlab/Simulink
- To implement supervisory control of the HEV to optimal operation of the hybrid vehicle's component using stateflow toolbox of the MATLAB/Simulink.
- To investigate HEV's environmental impact
- To compare different topologies of the HEV in terms of their performance, fuel consumption and emission.
- To achieve more understanding of the Hybrid Electric Vehicles.

### **1.5** Significant and scope of the study

Currently many studies there are have been carried out to model and simulate of the different topologies of the HEVs. The result of this study can be used as part of the approach to new vehicle component selection. Therefore, the evaluation of the vehicle performance criteria including gradeability, acceleration, driving range, pollution, energy consumption will be the scope of this study[3].

#### REFERENCES

- 1. Zoroofi, S., *Modeling and Simulation of Vehicular Power Systems* in *Department of Energy and Environment*. 2008, CHALMERS UNIVERSITY OF TECHNOLOGY: Göteborg, Sweden.
- 2. Gao, D.W., C. Mi, and A. Emadi, *Modeling and Simulation of Electric and Hybrid Vehicles*. Proceedings of the IEEE, 2007. **95**(4): p. 729-745.
- 3. Ahmad A, P., *Battery thermal models for hybrid vehicle simulations*. Journal of Power Sources, 2002. **110**(2): p. 377-382.
- 4. *Hybrid Electric Vehicles*, in *Modern Electric*, *Hybrid Electric*, and *Fuel Cell Vehicles*. 2009, CRC Press. p. 123-150.
- 5. EMMA GRUNDITZ and E.J, *MODELING AND SIMULATION OF THE HYBRID ELECTRIC VEHICLE FOR SHELL ECO-MARATHON AND ELECTRIC GO-KART*, in *THE ENERGY AND ENVIRONMENT*. 2009, CHALMERS UNIVERSITY OF TECHNOLOGY CHALMERS.
- 6. Trzynadlowski and Andrzej, *INTRODUCTION TO MODERN POWER ELECTRONICS*. 2nd ed. 2010.
- 7. Environmental Impact and History of Modern Transportation, in Modern Electric, Hybrid Electric, and Fuel Cell Vehicles. 2009, CRC Press. p. 1-18.
- 8. James Larmine, J.L., *Electric Vehicle Technology Explained*. 2nd ed. 2003: John Wiley & Sons.
- 9. Momoh, O.D. and M.O. Omoigui. An overview of hybrid electric vehicle technology. in Vehicle Power and Propulsion Conference, 2009. VPPC '09. IEEE. 2009.
- 10. Parallel (Mechanically Coupled) Hybrid Electric Drive Train Design, in Modern Electric, Hybrid Electric, and Fuel Cell Vehicles. 2009, CRC Press. p. 281-308.
- 11. Sorrentino, M., G. Rizzo, and I. Arsie, *Analysis of a rule-based control strategy for on-board energy management of series hybrid vehicles*. Control Engineering Practice, 2011. **19**(12): p. 1433-1441.
- 12. Internal Combustion Engines, in Modern Electric, Hybrid Electric, and Fuel Cell Vehicles. 2009, CRC Press. p. 67-104.
- 13. Peaking Power Sources and Energy Storages, in Modern Electric, Hybrid Electric, and Fuel Cell Vehicles. 2009, CRC Press. p. 375-410.
- 14. Rodatz, P., et al., *Optimal power management of an experimental fuel cell/supercapacitor-powered hybrid vehicle*. Control Engineering Practice, 2005. **13**(1): p. 41-53.
- 15. Salmasi, F.R., *Control Strategies for Hybrid Electric Vehicles: Evolution, Classification, Comparison, and Future Trends.* Vehicular Technology, IEEE Transactions on, 2007. **56**(5): p. 2393-2404.
- 16. Çağatay Bayindir, K., M.A. Gözüküçük, and A. Teke, A comprehensive overview of hybrid electric vehicle: Powertrain configurations, powertrain control techniques and electronic control units. Energy Conversion and Management, 2011. **52**(2): p. 1305-1313.
- 17. Design and Control Principles of Plug-In Hybrid Electric Vehicles, in Modern Electric, Hybrid Electric, and Fuel Cell Vehicles. 2009, CRC Press. p. 333-352.

- 18. Technical Overview of Toyota Prius, in Modern Electric, Hybrid Electric, and Fuel Cell Vehicles. 2009, CRC Press. p. 499-518.
- 19. John, M.M., Propulsion Sysyem for Hybrid Vehicle 2010, IET.
- 20. Pisu, P. and G. Rizzoni, A Comparative Study Of Supervisory Control Strategies for Hybrid Electric Vehicles. Control Systems Technology, IEEE Transactions on, 2007. **15**(3): p. 506-518.
- 21. Pisu, P., K. Koprubasi, and G. Rizzoni. Energy Management and Drivability Control Problems for Hybrid Electric Vehicles. in Decision and Control, 2005 and 2005 European Control Conference. CDC-ECC '05. 44th IEEE Conference on. 2005.
- 22. Jinsong, Z., et al. A Simulation Method of Controlled Hybrid Petri Nets Based on Matlab Simulink/Stateflow. in Automation and Logistics, 2007 IEEE International Conference on. 2007.
- 23. Gou, J., et al. Acceleration Slip Regulation of Electric Vehicle. in Logistics Engineering and Intelligent Transportation Systems (LEITS), 2010 International Conference on. 2010.
- 24. Andong, Y., Z. Han, and Z. Bingzhan. Control of Hybrid Electric Bus based on hybrid system theory. in Electric Information and Control Engineering (ICEICE), 2011 International Conference on. 2011.
- 25. Vijay, E.V., et al. Electronic control unit for an adaptive cruise control system & amp; engine management system in a vehicle using electronic fuel injection. in Emerging Trends in Robotics and Communication Technologies (INTERACT), 2010 International Conference on. 2010.
- 26. Guoqiang, A., et al. Model-based energy management strategy development for hybrid electric vehicles. in Industrial Electronics, 2008. ISIE 2008. IEEE International Symposium on. 2008.
- 27. Salisa Abdul Rahman, N.A.a.J.Z., Modeling and simulation of an Energy Management System for Plug-in Hybrid Electric Vehicles, in Australian University Power engineering Conference (AUPEC'08). 2008. p. 274-280.
- 28. Ferreira, A.A., et al., *Energy Management Fuzzy Logic Supervisory for Electric Vehicle Power Supplies System.* Power Electronics, IEEE Transactions on, 2008. **23**(1): p. 107-115.
- Poursamad, A. and M. Montazeri, *Design of genetic-fuzzy control strategy for parallel hybrid electric vehicles*. Control Engineering Practice, 2008. 16(7): p. 861-873.
- 30. serrao, L., a comparative analysis energy management strategies for hybrid electric vehicles in Mechanical Engineering 2009, Ohio State university ohio
- 31. Butler, K.L., M. Ehsani, and P. Kamath, A Matlab-based modeling and simulation package for electric and hybrid electric vehicle design. Vehicular Technology, IEEE Transactions on, 1999. **48**(6): p. 1770-1778.
- 32. Cole, G., *Simple electric vehicle simulation (SIMPLEV)*, DOE Idaho National Eng. Lab.
- 33. Marr, W.W. and W.J. Walsh, *Life-cycle cost evaluations of elec-tric/hybrid vehicles*. Energy Conversion Management, 1992. vol. 33(no. 9): p. 849–853.
- 34. Bumby, J.R., *Computer modeling of the automotive energy re-quirements for internal combustion engine and battery electric-powered vehicles.* Proc. Inst. Elect. Eng, 1985. **132**(5): p. 256-279.
- 35. Markel, T., et al., *ADVISOR: a systems analysis tool for advanced vehicle modeling.* Journal of Power Sources, 2002. **110**(2): p. 255-266.

- 36. Jun, H. and G. Xuexun. *Modeling and simulation of hybrid electric vehicles* using HEVSIM and ADVISOR. in Vehicle Power and Propulsion Conference, 2008. VPPC '08. IEEE. 2008.
- Li, Y.-L., X.-S. Zhang, and L. Cai, A novel parallel-type hybrid-power gas engine-driven heat pump system. International Journal of Refrigeration, 2007. 30(7): p. 1134-1142.
- Fish, S. and T.B. Savoie, Simulation-Based OPtimal Sizing of Hybrid Electric Vehicle Components for Specific Combat Missions. IEEE Transaction on Magnetics 2001. 37(1): p. 485-488.
- 39. Delprat, S., et al., *Control of a parallel hybrid powertrain: optimal control.* Vehicular Technology, IEEE Transactions on, 2004. **53**(3): p. 872-881.
- 40. Jong-Seob, W., R. Langari, and M. Ehsani, *An energy management and charge sustaining strategy for a parallel hybrid vehicle with CVT*. Control Systems Technology, IEEE Transactions on, 2005. **13**(2): p. 313-320.
- 41. Doerffel, D.a.A.-S., Suleiman, System modeling and simulation as a tool for developing a vision for future hybrid electric vehicle drivetrain configurations, in IEEE Vehicle Power and Propulsion Conference (VPPC). 2006.
- 42. Hyeoun-Dong, L., et al., *Torque control strategy for a parallel-hybrid vehicle using fuzzy logic*. Industry Applications Magazine, IEEE, 2000. **6**(6): p. 33-38.
- 43. *Electric Propulsion Systems*, in *Modern Electric, Hybrid Electric, and Fuel Cell Vehicles*. 2009, CRC Press. p. 151-251.
- 44. A.Bouscayrol, S.A.Syed, and W.Lhomme, *Modelling Comparison of Planetary Gear using EMR and Simdriveline for Hybrid Electric Vehicles* in *IEEE*. 2009. p. 1835-1841.
- 45. Yimin, G. and M. Ehsani, *A torque and speed coupling hybrid drivetrainarchitecture, control, and simulation.* Power Electronics, IEEE Transactions on, 2006. **21**(3): p. 741-748.
- 46. Yimin, G., M. Ehsani, and J.M. Miller. *Hybrid Electric Vehicle: Overview* and State of the Art. in Industrial Electronics, 2005. ISIE 2005. Proceedings of the IEEE International Symposium on. 2005.