

THE EFFECT OF OVER DOSAGE OF CONCRETE RETARDER  
DARATARD 40 IN CONCRETE

JAYAKUMARAN A/L GOVINDASAMY

A project report submitted in partial fulfillment of the requirements for the award of the  
degree of Master of Engineering (Civil – Structure)

Faculty of Civil Engineering  
Universiti Teknologi Malaysia

NOVEMBER 2005

Especially dedicated  
to my beloved family

## ACKNOWLEDGEMENT

In preparation of this thesis, I was in contact with many peoples in the local market who engaged in ready mixed concrete productions, building constructions, as well as academicians and practitioners. They have contributed towards my understanding and thought. I wish to express my sincere appreciation to my main thesis supervisor Dr. Mohammad Ismail for his guidance, encouragement and put me in right direction while I am writing this thesis and the lab test. I am also expressed my thanks to Dr. Abd. Aziz Saim, Dr. Abd. Rahman Md. Sam and Dr. Jamaluddin Mohd.Yatim for theirs comment and advice during the presentation of master pre project.

I wish to express my sincere appreciation to Mr. Sivabalan, QA/QC Manager of Strong Mixed Concrete Sdn Bhd for the concrete materials and allows to conduct the testing in they concrete laboratory. I would like to record very grateful thanks to Mr. Suen, C. M. of Fosroc (M) Sdn Bhd and Mr. Deva of Sika Kimia Sdn Bhd for their comment and suggestion of the usage of concrete retarder admixtures in the concrete field.

I would like to thank the Universiti Teknologi Malaysia especially the Faculty of Civil Engineering lecturers in providing the knowledge and make the programme into reality. Thanks to my colleagues at work and during my studies for all valuable ideas and helpful advice. Lastly I wish my deeply appreciation and gratitude to all my family members.

## **ABSTRACT**

More than 70 % of insitu concrete is produced now by the ready mixed concrete industry in Malaysia. With the increases in economic growth and demand for highrise buildings as well as infrastructures make the industry to determine its own standards of the production by trial mixed design. The issues involves in the properties of fresh concrete during the casting stage. A high degree of workability is planned to speed up the construction. The suitable concrete retarder is being used in the fresh concrete to avoid the formation of cold joint due to time needed to place a large volume of concrete in a continuous operation. The chances to over dosage the concrete with retarder become so great and critical at the construction site. Sometimes it takes 2 to 3 days for the concrete to set and harden. It creates many doubt and disputes to engineers in the industries about the strength and durability of the concrete in long run. The study of behavior of the concrete with different dosage of retarder Daratard 40 has been conducted in the lab test prior to practical concrete practice. The investigation may help the industry to achieve the optimum dosage of concrete retarder without compromising the concrete strength. The relationships between slump test and optimum dosage of the Daratard 40 concrete retarder has been established from the study. Slump test a cheap, suitable and more reliable testing method use to detect the cause of over dosage in fresh concrete consent on consistency before placing and compaction works at the site.

## ABSTRAK

Pada masa kini sebanyak 70 % konkrit tuang disitu menggunakan konkrit siap bancur (ready mixed concrete) dalam industri konkrit di Malaysia. Dengan perkembangan ekonomi yang pesat dan bertambahnya keperluan bangunan pencakar langit serta infrastruktur/kemudahan asas membolehkan industri pengeluar konkrit siap bancur menyediakan rekabentuk bancuhan konkrit mereka tersendiri secara cubaan (trial mix). Kesan dan masalah yang dihadapi oleh konkrit yang baru siap bancur (fresh concrete) dari segi sifat (properties) semasa konkrit dalam proses penuangan di tapak bina adalah perlu dikaji. Bagi mempercepatkan dan memudahkan sesuatu proses kerja pembinaan, konkrit pada tahap darjah kebolehankerjaan (slump) yang tinggi dan praktikal sangat diperlukan supaya kerja pembinaan itu senang di bina. Bahan kimia seperti bahan campur kelambatan (concrete retarder) digunakan dalam industri konkrit siap bancur bagi tujuan mengelakkan pembentukan sambungan sejuk (cold joint) semasa proses pemejalan konkrit dan penuangan konkrit dalam isipadu dan keluasan yang besar dengan cara operasi yang berterusan. Kebarangkalian bagi menambahkan dos bahan campur kelambatan yang berpatutan adalah amat tinggi dan kritikal semasa menerima konkrit di tapak bina. Ini adalah kerana kecuaiian operator yang tidak sengaja dilakukan semasa membancur konkrit siap bancur di tapak lokasi yang lain dan berjauhan dari tapak bina yang sediada. Kadangkala 2 hingga 3 hari konkrit yang tuang dalam papan acuan tidak akan keras dan menjadi pejal. Ini menjadikan banyak tanda tanya dan bahan perbincangan dikalangan jurutera dalam industri pembinaan mengenai tahap kekuatan dan ketahanan ataupun tempoh perkhidmatan disepanjang hayat struktur konkrit tersebut. Satu kajian mengenai sifat konkrit akibat dos yang berbeza terutamanya berlebihan dos kepada bahan tambah kelambatan dalam konkrit telah dijalankan dalam makmal, ianya mirip dengan keadaan sebenar

yang berlaku di tapak bina. Hasil kajian ini akan membantu industri konkrit untuk menetapkan nilai optimum dos bahan tambah konkrit Daratard 40 dengan kekuatan izin konkrit yang maksimum. Hubungan diantara keboleherjaan (slump) dan nilai optimum dos bahan tambah konkrit dapat dijadikan sebagai pedoman. Satu alat pemantau/pengukuran seperti keboleherjaan (slump test equipments) yang murah serta sesuai dengan keadaan tapak bina dapat membantu mengesan dos bahan tambah konkrit yang berlebihan dalam konkrit sebelum dituangkan kedalam papan acuan serta pemadatan konkrit.

## TABLE OF CONTENTS

<b>CHAPTER</b>	<b>TITLE</b>	<b>PAGE</b>
	<b>TITLE PAGE</b>	<b>i</b>
	<b>DECLARATION OF ORIGINALITY AND EXCLUSIVENESS</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>TABLE OF CONTENTS</b>	<b>viii</b>
	<b>LIST OF TABLES</b>	<b>xiii</b>
	<b>LIST OF FIGURES</b>	<b>xv</b>
	<b>LIST OF SYMBOLS</b>	<b>xvi</b>
	<b>LIST OF APPENDIXES</b>	<b>xvii</b>

<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Introduction	1
	1.2 Problem Statement	5
	1.3 Objectives of the Study	5
	1.4 Scope of the Study	6
<b>CHAPTER 2</b>	<b>LITERATURE REVIEW</b>	<b>8</b>
	2.1 General	8
	2.2 Concrete Retarder	9
	2.3 Sugar	22
	2.4 Retarding water reducing admixture for concrete	22
	2.5 Durability of Concrete	25
	2.6 Common Defects and Repair to the Surface of Concrete	30
	2.6.1 Popouts	30
	2.6.2 Dusting	30
	2.6.3 Honey Combing	31
	2.6.4 Cavitation	32



2.6.5	Cold Joints	32
2.6.6	Efflorescence	33
2.6.7	Alkalis Silica Reaction	33
2.7	Deformation of Concrete	35
2.7.1	Early Shrinkage in Plastic Concrete	35
2.7.2	Drying Shrinkage	37
2.7.3	Creep	38
2.8	Cracking in Concrete	39
2.8.1	Structural Effects of Temperature	39
2.8.2	Heat Generation and Thermal Movement	40
2.8.3	Cracking	41
2.8.4	Cause of Cracking	46
<b>CHAPTER 3</b>	<b>METHODOLOGY/EXPERIMENTAL WORK</b>	<b>47</b>
3.1	Introduction	47
3.1.1	Ordinary Portland Cement	47
3.1.2	Retarder	48
3.1.2.1	Reaction of Retarder	49

3.1.3	Fine Aggregates	50
3.1.4	Coarse Aggregates	51
3.1.5	Water	51
3.2	Concrete Mix Design	52
3.3	Casting and Batching of the Specimens	55
3.4	Testing	57
3.4.1	Compressive Strength Test	57
3.4.2	Slump Test	58
3.4.3	Compaction Factor Test	64
3.4.4	Proctor Penetration Test	66
3.4.5	Water Penetration Test	68
3.4.6	Water Absorption Test	73
<b>CHAPTER 4</b>	<b>RESULTS</b>	<b>77</b>
4.1	Slump and Compaction Factor Test	77
4.2	Proctor Penetration Test	82
4.3	Compressive Strength Test	84
4.4	Water Penetration Test according to DIN 1048 Part 5	88
4.5	Water Absorption Test according to BS 1881: Part 122: 1983	90

<b>CHAPTER 5</b>	<b>DISCUSSIONS</b>	92
	5.1 Setting Time	92
	5.2 Loss of Workability/ Slump	93
	5.3 The Compaction Factor Ratio	93
	5.4 Compressive Strength	94
	5.5 Water Penetration	95
	5.6 Water Absorption	96
<b>CHAPTER 6</b>	<b>CONCLUSION AND RECOMMENDATION</b>	98
	6.1 Conclusion	98
	6.2 Recommendation	99
	<b>LIST OF REFERENCES</b>	101
	References	101 – 105

**APPENDIXES**

106

Appendixes

105 - 132

## LIST OF TABLES

TABLE NO.	TITLE	PAGE
Table 1.1	Sample of Specimens for Testing	7
Table 2.1	Addition Rate of Retarding Dispersing Components of Type A & D Admixtures	17
Table 2.2	Performance Requirements and Tests	20
Table 2.3	Typical Results of Compressive Strength For Dosage of Admixture	23
Table 2.4	Dosage of Admixture, Slump and Ambient Temperature	24
Table 2.5	Durability Requirements (BS 8110: Clause 3.3.3)	29
Table 3.1	Physical and Chemical Properties of OPC	48
Table 3.2	Properties of Retarder (Daratard 40)	49
Table 3.3	Detail of Mix Proportion of Daratard 40 (Concrete Retarder) to the Grade 30 Concrete	54

Table 3.4	Description of Workability and Magnitude of Slump	62
Table 3.5	Comparison of Workability Measurement	63
Table 4.1	Slump and Compaction Factor Test Results	78
Table 4.2	Setting Time of Concrete Results	82
Table 4.3	Compressive Strength Results	84
Table 4.4	Water Penetration Test Results	88
Table 4.5	Water Absorption Test Results	90

## LIST OF FIGURES

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 2.1	Effect of concentration of dispersant on The degree of cement particles surface coating	18
Figure 2.2	Permeability and Porosity	27
Figure 2.3	Present of water in capillary pores in concrete in equilibrium with a non saturated atmosphere	27
Figure 3.1	Concrete Cube Dimensions	56
Figure 3.2	Compressive strength testing machine	58
Figure 3.3	The slump test apparatus and type of downward movement of the fresh concrete	60
Figure 3.4	A true slump measurement	61
Figure 3.5	Comparison of slump, vebe and compaction factor test	64

Figure 3.6	The compacting factor test	66
Figure 3.7	Proctor penetration probe	67
Figure 3.8	Water penetration test apparatus in the laboratory	70
Figure 3.9	Indication of water penetration depth in Control Mix	71
Figure 3.10	Indication of water penetration depth in over dose with concrete retarder Daratard 40 (1000 ml and 1200 ml/ 100 kg of cement)	72
Figure 3.11	Specimen of water absorption test in the Control Mix and the recommended dosage 450 ml/ 100 kg of cement by manufacturers	75
Figure 3.12	Water absorption test in the over dose concrete retarder Daratard 40 1200 ml/ 100 kg of cement	76
Figure 4.1a	Slump loss behavior against time for the difference Dosage of concrete retarder Daratard 40	79
Figure 4.1b	Slump against difference dosage of concrete Retarder Daratard 40 in the fresh concrete	80
Figure 4.1c	Relationship between the results of slump and compaction factor test	81
Figure 4.2	Effect of concrete retarder Daratard 40 on setting time	83



Figure 4.3a	The compressive strength of concrete for the difference dosage of concrete retarder Daratard 40 against time (days)	86
Figure 4.3b	The early strength of concrete	86
Figure 4.3c	Compressive strength (N/mm <sup>2</sup> ) shown in bar chart	87
Figure 4.4a	Water penetration depth against difference dosage of concrete retarder Daratard 40	89
Figure 4.4b	Compressive strength at 28 days against water penetration in difference dosage of concrete retarder Daratard 40	89
Figure 4.5a	Water absorption (%) against difference dosage of concrete retarder Daratard 40	91
Figure 4.5b	Compressive strength at 28 days against water absorption (%)	91
Figure Appendix 2a	Simplified model of cement paste structure representing the gel particles and gel pores (c)	109
Figure Appendix 2b	Structure of hydrate silicas	110
Figure Appendix 2c	Types of water within calcium silicate hydrate (C-S-H)	116

## LIST OF SYMBOLS

<b>Ø</b>	=	Diameter of cylinder
<b>C</b>	=	Compressive strength
<b>P</b>	=	Applied load
<b>W</b>	=	Width of cube
<b>L</b>	=	Length of cube
<b>d</b>	=	Depth of penetration of water
<b>h</b>	=	Absorption of water
<b>M<sub>w</sub></b>	=	Mass increases in the specimen due to immersion of water
<b>M<sub>d</sub></b>	=	Mass of dry specimen

## LIST OF APPENDIXES

APPENDIXES	TITLE	PAGE
Appendix 1	Dosage Calculation for 1 m <sup>3</sup> of Concrete (340 kg of cement)	106
Appendix 2	Normal Concrete Mix	107
Appendix 3	Chemical Composition	119
Appendix 4	The four main compounds in Portland Cement	120
Appendix 5	Schematic Diagram of Formation and Hydration of Cement	121
Appendix 6	Hydration of Cements	122
Appendix 7	Classification of Admixtures in British and American Standards	123
Appendix 8	Recommended Slump for Various Type of Construction	124
Appendix 9a	Concrete Mix Design by Strong Mixed Concrete Sdn Bhd	125

Appendix 9b	Design of Normal Concrete Mixes	126
Appendix 10	Test Certificate of Ordinary Portland Cement	127
Appendix 11	W. R. Grace Manufactures Test Report on Concrete retarder Daratard 40	128
Appendix 12	Sieve Analysis Report for Mining Sand	129
Appendix 13	Sieve Analysis Report for 20 mm Granite Aggregates	130
Appendix 14	Water Test Report	131

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Introduction**

In this millennium a new challenge towards the construction industry not only in the process of producing consistent quality concrete but at the same time to be mindful as a responsible corporate citizen to preserve safety, health and environment. This has been manifested to be large extent in mega project such as Putra Jaya Development and more other project to be developed in our country. The ready mixed concrete industry in Malaysia experienced a dramatic consolidation of ready mix concrete players which saw multinationals company taking major position in the industry with potential for further growth. The industries enhance the knowledge in the IT to ensure competitiveness and technical skills matching world standards in concrete operations.

Concrete is a man made composite with major constituent of three materials namely cement, water and the aggregates and an additional material known as admixture, is sometimes added to modify certain of its properties. Cement is the chemically active constituent but its reactivity is only brought into effect on mixing with water. The aggregate plays not important roles in chemical reactions but its usefulness arises because of it is an economical filler material or hard composite material with good resistance to volume changes which take place within the concrete after mixing and it improves the durability of concrete. In hardened state, concrete is a rock like material with a high compressive strength. The fresh concrete in its plastic state may be mould into any form of shapes, it may be used to advantages architecturally or solely for decorative purposes. Normal concrete has low tensile strength and for structural applications it is normal practice to incorporate with steel bars to resist any tensile forces in the Reinforced Concrete. Concrete usually used in buildings for foundations, columns, beams and slabs, in shell structures, bridges, sewerage treatment plants, railway sleepers, roads, cooling towers, dams, chimneys, harbours or ports, offshore structures, coastal protection works and so on. In precast concrete product its widely used as concrete blocks, cladding panels, pipes and lamp posts ( Jackson & Dhir, 1996 ).

## **Ready Mixed Concrete**

More than 70% of in-situ concrete is produced now by the ready mixed concrete industry in Malaysia. This rapid development in output has caused the industry to determine its own standards of the production by trial mixed design. The use of large quantities of aggregates by the ready mixed concrete industry over along period ensures that the vast and expert knowledge of their properties is available for economic mix design. The coarse and fine aggregates availability varies according to geographical location and sources. Natural aggregates are obtained either as gravel or crushed rock from quarries and the mining sand. Sometimes due to shortage of supply the concrete mix do not comply exactly with the requirement of the relevant British Standard or Malaysia Standard but practical experience shows that with correct mix design, high quality concrete can still be produced. Aggregates should not be condemned solely on physical properties, but should be tested in trial mixes and their suitability assessed in terms of the properties of the concrete produced. It is most economical and cheapest to use locally available raw materials and the main choice of the ready mixed concrete producers. Ordinary Portland Cement (OPC) is easy available in Malaysia with high quality cement constituents and production also available some other types of cement such as sulphate resistance Portland cement also in the local market. **Admixtures** are normally used on request modifications and can not be made by varying the composition and proportion of the basic constituent materials or when the admixtures can produce the required effects

more economically (Stilwell, J.A The Concrete Society Journal 1984). Many type of admixtures found in the local market can used as accelerators, retarders, water-reducing and air entraining admixtures influence on hydration, liberation of heat, formation of pores and development of the cement gel. But in this study, the ready mixed concrete producers are using Daratard 40 as retarder admixture which is readily available from various sources of manufacturer's. The current practice usage of retarders by concrete industry at the site is about 300 ml to 550 ml per 100 kg of cement. The study showed about the effect of over dosage of concrete retarder Daratard 40 to the concrete mixed. In some cases at job site found that the concrete left unset for 2 to 3 days due to over dosage of the retarders admixture and become very common and serious in the concrete practice. It also creates many doubt and disputes about the strength and durability of concrete in the long run between concrete producers, project consultants and the contractor in the construction industry.



## **1.2 Problem Statement**

The current production of concrete by ready mixed concrete batching plant in Malaysia is about 120 cubic metre per hour of concrete or 2880 cubic metre capacity per number of batching plant. The chances of over dosage the admixture especially concrete retarder into the fresh concrete mix is very high. This may be due to human errors or negligence while adding the concrete admixture in specific quantities through automatic dispenser tank.

## **1.3 Objectives of the Study**

The main objectives of the study are:-

- (i) to determine the optimum over dosage of concrete retarders without compromising the concrete strength.
- (ii) to verify the slump test as a suitable technique to detect the over dosage in the fresh concrete before placing and compaction work at the job site.

The main significant of the project is to obtain the mean value of the compressive and tensile strength with optimum dosage of concrete retarder in the

fresh concrete at early age. This solution may help the contractors to remove their temporary works such props or scaffoldings which is supporting the permanent structures in the limited time frame with maximum mean value of the compressive strength of concrete.

#### **1.4 Scope of the study**

In this investigation, the concrete retarder Daratard 40 W.R.Grace is mixed with the proportion of 450 ml/100 kg of cement, 500 ml/100 kg, 600 kg/100 kg, 800 ml/100 kg, 1000 ml/100 kg and 1200 ml/100 kg of cement into the concrete mixed. The concrete retarder Daratard 40 is mixed with normal grade 30 concrete as per designed and supply in the local markets by the Concrete Producers. The Ordinary Portland Cement and the aggregates are 20 mm granite as coarse aggregate and mining sand as fine aggregate have been used in the batching. The specimens (cubes) shall be made and stored in the curing tank accordance with BS 1881 except that maximum temperature of  $27^{\circ} \pm 2^{\circ}\text{C}$  is permitted. At the age of 24 hours, 3, 7 and 28 days, the specimens were tested for the compressive strength. The water penetration and absorption test also been conducted for checking the durability of the concrete mixes. The slump, compaction factor and proctor penetration tests was carried out for every batch of concrete mixes this to look at the behavior of fresh concrete due to over dosage. The specimens detail which to be tested as shown in Table 1.1.

**Table 1.1: Sample of Specimens for Testing**

Mix (Dosage of Concrete Retarder Daratard 40)	Slump (mm)	Curing Condition	Cube Test (Days)			
			1	3	7	28
Plain Concrete( Control)	100	Cured into curing tank at 27° ± 2°C room temperature and kept 2 hours at atmospheric pressure before testing	3	3	3	7
450 ml/ 100 kg cement	75 ± 25		3	3	3	7
500 ml/ 100 kg cement			3	3	3	7
600 ml/ 100 kg cement			3	3	3	7
800 ml/ 100 kg cement			3	3	3	7
1000 ml/100 kg cement			3	3	3	7
1200 ml/ 100 kg cement			3	3	3	7

## LIST OF REFERENCES

- Allen, D. C. and Roper, H. (1991). "Concrete Structures." Essex, England.:  
Longman Scientific & Technical Group. pp. 40 – 53, 56 – 87.
- Bertolini, L., Elsener, B., Pedferri, P., Polder, R. (2004). "Corrosion of Steel in  
Concrete." Weinheim, Germany.: Wiley – VCH Verlag GmbH & Co., pp. 21 –  
34, 165 – 175.
- Building Research Established Report, (1976). "Design of Normal Concrete Mixes."  
Gartson, England.
- Bungey, J. H. and Millard, S.G. (1996). "Testing of Concrete in Structures."  
Glasgow, U.K.: Blackie Academic & Professional., pp. 245.
- BS 1881: Part 116: (1983). "Method for determination of compressive strength of  
concrete cubes." London, U.K.: British Standards Institution.
- BS 1881: Part 117: (1983). "Method for determination of tensile splitting strength."  
London, U.K.: British Standards Institution. pp. 1 – 3.

- BS 1881: Part 122: (1983). "Method for determination of water absorption."  
London, U.K.: British Standards Institution.
- BS 5075: Part 1: (1982). "Specification for accelerating admixtures, retarding admixtures and water reducing admixtures." London, U.K.: British Standards Institution., pp. 2 -3 / 16.
- Concrete Products Catalogue. "Product Information- Daratard-40 retarding type water reducing / plasticizing admixture for concrete." Kuala Lumpur, Malaysia.: W.R.Grace (M) Sdn Bhd.
- DIN 1048 Part 5: (1999). "Testing of Harden Concrete." Deutsche Norm.: German Standards. pp. 1, 5 – 8.
- Dodson, V. H. (1990). "Concrete Admixtures." New York, U.S.A.: Van Nostran Reinhold.
- Flatau, A. S. (1984). "Current Practice Sheets – Volume 1" The Concrete Society.: London, U.K. pp. 33 - 35.
- Gupta, B L. and Gupta, A. K. (1997). "Text Book of Concrete Technology." Delhi, India.: Standard Published Distribution., pp. 155, 156.

- Hansen, W. C. and Offutt, W. C. (1988). "Gypsum and Anhydrite in Portland Cement." Chicago, U.S.A.: U.S. Gypsum Company Ltd.
- Illston, J. M. and Domone, P. L. J. (2001). "Construction Materials." London.: U.K. pp. 110 – 116, 128 – 135, 192 – 215.
- Jackson, N. and Dhir, R. K. (1996). "Civil Engineering Materials." Hampshire, U.K.: Palgrave Publishers Ltd., pp. 162, 163, 172, 187, 188, 189, 190, 191, 192.
- Kong, F. K. and Evan, R. H. (1995). "Reinforced and Prestressed Concrete." London, U.K.: Chapman and Hall University and Professional Division., pp. 18 – 24, 38, 46.
- Lawrence, R. R. (2004). "Dealing with Cement – Admixture Interactions." GCP Course for Professional Development, Training Manual, Section 8.: W. R. Grace & Co.
- Neville, A. M. (1999). "Properties of Concrete." Essex, U.K.: Pearson Education Limited., pp. 189 - 196, 243 - 265.
- Neville, A. M. and Brooks, J. J. (1999). "Concrete Technology." Essex, U.K.: Pearson Education Limited., pp.18, 74, 83 - 90, 147 - 160, 389.

NRMCCAM, International Concrete Convention. (2000). “ Welcome Message and Keynote Address.” Pan Pacific Hotel, Kuala Lumpur, Malaysia. (3 & 4 May 2000).

Popovics, S. (2002). “Concrete Materials.” Delhi, India.: Standard Publishers Distributors., pp. 47, 63 – 70, 103 – 133, 246 – 254.

Ramachandran, V. S. (2002). “Concrete Admixture Handbook.” Delhi, India.: Standard Publishers Distributors., pp. 286 – 396.

Richardson, M. G. (2002). “Fundamentals of Durable Reinforced Concrete.” London, U.K.: Spon Press., pp. 38 – 49.

Ropke, J. C. (1982). “Concrete Problem.” New York, U.S.A.: McGraw – Hill Book Company., pp. 105 – 110.

Steven, H. K. and William, C. P. (1994). “Design and Control of Concrete Mixtures.” Illinois, U.S.A.: Portland Cement Association., pp. 63 – 67, 70, 77, 80, 82, 85,

Siddique, R. (2000). “Special Structural Concrete.” New Delhi, India.: Galgotia Publications Pvt. Ltd., pp. 286 – 289, 311 - 316.

Stillwell, J. A. (1984). "Current Practice Sheets – Volume 1." The Concrete Society.: London, U.K. pp. 21 - 23.