

MULTIELEMENTAL ANALYSIS OF AN INDUSTRIAL SOURCE  
EMISSION BY NEUTRON ACTIVATION ANALYSIS  
: A Case Study of A Palm-Oil Mill Plant

by

Mohd. Rashid Mohd. Yusoff  
Chemical Engineering Department  
Universiti Teknologi Malaysia  
54100 KUALA LUMPUR

Abdul Khalik Wood  
Nuclear Energy Unit  
Prime Ministers Department  
Kompleks PUSPATI  
43000 Kajang  
SELANGOR

Azman Firdaus Shafii  
Harrisons Malaysian Plantations Bhd.,  
Engineering Services Scheme  
42700 Banting  
SELANGOR

Presented at:

SEMINAR ON THE APPLICATION OF NUCLEAR  
TECHNIQUES IN INDUSTRY,  
KUALA LUMPUR.

17 - 19 November, 1987

MULTIELEMENTAL ANALYSIS OF AN INDUSTRIAL SOURCE  
EMISSION BY NEUTRON ACTIVATION ANALYSIS  
: A Case Study of A Palm-Oil Mill Plant

Mohd. Rashid Mohd. Yusoff  
Chemical Engineering Department  
Universiti Teknologi Malaysia  
54100 KUALA LUMPUR

Abdul Khalik Wood  
Nuclear Energy Unit  
Prime Ministers Department  
Kompleks PUSPATI, Bangi  
43000 Kajang  
SELANGOR

Azman Firdaus Shafii  
Harrisons Malaysian Plantations Bhd.  
Engineering Services Scheme  
42700 Banting  
SELANGOR

ABSTRACT

The concentrations of 29 elements in the palm-oil mill boiler flyash emitted from a mixed fiber and shell fired-fuel palm-oil mill plant were measured using a instrumental neutron activation analysis (INAA). Two separate samples of flyash 1) flyash retained by the particulate arrestor and 2) stack-ash emission collected downstream of the boiler were studied.

Results showed that potentially volatile elements (As, Ba, Br, Cl, Co, Cr, Cs, Sb, Rb and Zn) were enriched in the stack-ash emission as compared to retained-ash. Gallium, K and Na were intermediately enriched and Al, Ca, Ce, Eu, Fe, La, Lu, Mn, Sc, Sm, Th, Ti, V and Yb showed equally concentrated in both samples. Study suggests that the INAA can serve as an important analytical tool in elemental pollution studies from an industrial source emission.

## INTRODUCTION

Instrumental neutron activation analysis (INAA) has been extensively used in environmental trace element studies. It is an excellent method for the analysis of environmental samples because it is rapid, highly sensitive, does not require sample dissolution, and is relatively free of matrix interferences. Direct analysis with minimum sample handling is desirable not only for economic reasons, but also because it reduces the probability of sample contamination and loss of volatile elements.

The present study was conducted in order to demonstrate the application of this technique in a palm-oil mill industry. Particulate emission from a stationary source like a palm-oil mill operation plant can contribute significantly to the amount of anthropogenic origin especially trace elements.

It is estimated that there are more than 200 palm-oil mills present in this country and these give rise to about 400 boilers and 200 incinerators.<sup>1</sup> On average 20 tons or more of both fibres and shells are produced per 100 ton fresh-fruit bunches processed and these are usually consumed in the mill as boiler fuel. The situation will certainly create a great burden of flyash particulate emission if it is not properly controlled. Unfortunately, a significant portion of the flyash is in the respirable size range that can contribute the greatest potential hazard for human inhalation.<sup>2</sup> Thus, a study on the elemental composition presents in the palm-oil flyash collected downstream of the palm-oil mill boiler is warranted.

## METHODOLOGY

### Sample collection.

The flyash samples were obtained from a mixed fibre and shell fired-fuel palm-oil mill which has the capacity of processing 20 ton of fresh-fruit bunches per hour. The mill is equipped with 2 boilers (each rated to generate 15,000 kg/hr steam, one as standby) and one unit of multicyclones dust collector. Two samples at different locations downstream of the boilers were collected a) flyash retained in the multicyclones measured to be averaging about 2 kg per minute and b) stack flyash collected in the ducting before

leaving the stack exit. The retained sample was collected in bulk and dried in an oven for at least 24 hours. The sample was then sieved mechanically for 63 micron particle size and below before the elemental analysis. The stack flyash was collected isokinetically using portable Anderson universal stack sampler (D-1027). Further description of the equipment and methods of sampling are described in detail elsewhere.<sup>3</sup>

#### Elemental Analysis.

The elemental analysis was done by the INAA. The samples and standard were neutron irradiated in a Triga MKII reactor (average flux  $3 \times 10^{12} \text{ ncm}^{-2} \text{ s}^{-1}$  at 500 kw operating power) for two minutes. A decay time of about 20 minutes was required for the determination of Al, Ba, Ca, Cl, Eu, K, Mn, Na, Tl and V. The counting of active samples and standard were repeated after a decay period of 24 hours in order to analyze As, Na, K, Dy and Sm. The remaining elements were analyzed after 14 - 21 days decay of activated samples and standards irradiated for 6 hours. The Reference Material of NBS 1632a Coal ash was used as the standard.

The gamma ray spectra of the radioactive species were taken with a Hyperpure-germinium-semiconductor detector system including ND-66 multichannel analyzer (4096 channel). The FWHM of the system was 1.9 keV for the 1332 keV  $\gamma$ -ray peak of  $^{60}\text{Co}$ . The spectral data were analyzed on ND6680 with the Nuclear Data Peak Search Program which fit the peaks with Gaussian Function.<sup>4</sup>

## RESULTS

Results of the analysis of 29 elements in both stack and retained palm-oil flyash samples are listed in Table 1 and 2 respectively. A total of twenty analyses were done for the retained samples whereas only six analyses were possible for the stack samples due to insufficient amount of samples collected near the stack exit. As a result, both Ba and Tl were measured with some uncertainties and these are indicated by the 'less than' signs as in Table 2.

Both Dy and U peaks were not seen in the analysis of stack sample. The authors believed that these elements were below the detection limits due to insufficient amount of samples. No further effort was made to quantify this statement at this stage.

## DISCUSSION

Table 3 presents the elemental concentration ratio of stack to retained flyash samples. As can be seen from Table 3, several of the elements were found to be much higher concentration in the stack-ash sample. These include As, Ba, Br, Cl, Co, Cr, Cs, Sb, Rb and Zn. Arsenic is considered to be a toxic element even in trace amounts. Antimony (Sb) has a similar effect as As if heavily exposed. The concentrations of Br and Cl were high in several order of magnitudes in the stack-ash fraction. Their presence in the flyash is probably due to the application of herbicides and insecticides in the field which deposited or later absorbed by the plants.

The high concentrations of As, Ba, Br, Cl, Co, Cr, Cs, Sb, Rb and Zn in the stack-ash emission could infer that these elements were in the submicron sized particles. It also suggested that these elements had a lower degree of volatilization temperature and that they could easily evaporate in the combustion zone and condensed on the particles surface. The condensation phenomena may be aggravated during feeding the boiler manually with the solid-fuel (fibres and shells). A tremendous amount of fine flyash are produced in the combustion chamber during this process. It was also suggested that multicyclones are not efficient for submicron sized particles collection.

The other group of the elements mainly Al, Ca, Ce, Eu, Fe, La, Lu, Mn, Sc, Sm, Th, Ti, V and Yb were found equally concentrated in both of the samples. The elemental stack to retained concentration ratios showed no signs of enrichment for these elements. The elements were well retained in the dust collector and believed to be in supermicron sized particles. In fact many of these are not easily volatilised even during the combustion processes. Given the fact that there were no data on flyash size available, only rough inferences could be made to date based on these findings.

Gallium, K and Na were intermediately enriched in the stack-ash emission. Their elemental ratios were slightly higher than one but the enrichments were very minimal to allow any other judgement to be made on them.

## CONCLUSION

Based on the elemental ratios of stack to retained palm-oil mill flyash reveal that As, Ba, Br, Cl, Co, Cr, Cs, Sb, Rb and Zn are mainly concentrated in the stack-ash emission. Gallium, K and Na, are intermediately enriched and Al, Ca, Ce, Eu, Fe, La, Lu, Mn, Sc, Sm, Th, Ti, V and Yb show no significant enrichment in the stack sample. We conclude that certain elements in the palm-oil flyash are more concentrated on the finer-flyash particles that escape the emission control system and are emitted into the atmosphere. The environment is more likely to be exposed to these fine particles because of their longer atmospheric residence times (compared to larger particles). Also, the situation may affect mill workers especially with regard to possible eventual deep lung deposition. Consequently, further studies on this subject especially on size characterization of palm-oil flyash and potentially toxic elements are warranted. This study has also proved the usefulness of the NAA for multielement pollution source emission studies.

## Aknowledgements

The authors wish to thank Harissons Malaysian Plantations Berhad for giving the permission to publish this work.

#### REFERENCES

1. Azman, F.S. and Goyalupillay (1986). Atmospheric Emissions Control. A Decade of Environmental Management in HMPB.
2. Mohd. Rashid, M.Y. (1986). Size Distribution of Palm-Oil Mill Boiler Flyash from Stack Emission (Laboratory Report).
3. Hoaland, H.H. Methods for Determination of Velocity, Volume, Dust and Mist Content of Gases. Bulletin WP-50, 7th. Ed.
4. Thamson, K.R. and Meyers T. (1978). A Multiple User NAA System. Paper presented at American Nuclear Society Conference, Mayaguez, Puerto Rico, April 30 - May 4.

TABLE 1 : ELEMENTAL CONCENTRATIONS IN RETAINED FLYASH\*

Element	Mean	Std. dev.
Al (%)	1.79	0.32
As	17.9	3.25
Ba	79.1	45.2
Br	23.8	6.50
Ca (%)	1.94	0.07
Ce	22.7	3.06
Cl (%)	0.35	0.02
Co	2.03	0.68
Cr	34.2	4.53
Cs	2.13	0.54
Dy	1.74	0.49
Eu (ppb)	244	36
Fe (%)	1.46	0.11
Ga	3.64	1.89
K (%)	5.24	0.39
La	13.7	1.49
Lu (ppb)	211	18.0
Mn	790	61.5
Na (%)	0.07	0.004
Sb	0.75	0.26
Sc	3.02	0.22
Sm	1.78	0.25
Rb	311	57.3
Th	4.31	0.75
Ti (%)	0.13	0.03
U	1.37	0.42
V	22.6	8.08
Yb	0.87	0.16
Zn	122	18.9

\* Concentration in ppm or otherwise stated.



TABLE 2 : ELEMENTAL CONCENTRATIONS IN STACK FLYASH\*

Element	Mean	Std. dev.
Al (%)	1.44	0.27
As	100	42.5
Ba	<535	-
Br	373	45.6
Ca (%)	1.22	0.09
Ce	19.7	2.50
Cl (%)	4.78	0.98
Co	23.0	5.69
Cr	261	51.6
Cs	5.44	0.72
Dy	NS	-
Eu (ppb)	1.38	0.20
Fe (%)	1.27	0.28
Ga	7.26	2.65
K (%)	9.52	1.05
La	8.36	2.16
Lu (ppb)	162	20.0
Mn	741	78.4
Na (%)	0.09	0.01
Sb	2.60	0.57
Sc	1.96	0.21
Sm	0.99	0.15
Rb	753	20.5
Th	3.91	1.04
Ti (%)	<0.06	-
U	NS	-
V	4.68	1.30
Yb	0.40	0.05
Zn	356	49.4

\* Concentration in ppm or otherwise stated,  
NS = not seen.

TABLE 3 : FLYASH ELEMENTAL CONCENTRATION RATIOS\*

Elemental	Stack	Retained	Stack/Retained
Al (%)	1.44	1.79	0.8
As	100	17.9	5.6
Ba	<535	79.0	<6.8
Br	373	23.8	16
Ca (%)	1.22	1.94	0.6
Ce	19.7	22.7	0.9
Cl (%)	4.78	0.35	14
Co	23.0	2.03	11
Cr	261	34.2	7.6
Cs	5.44	2.13	2.5
Dy	NS	1.74	-
Eu (ppb)	1.38	244	0.01
Fe (%)	1.27	1.46	0.9
Ga	7.26	3.64	2.0
K (%)	9.52	5.24	1.8
La	8.36	13.7	0.6
Lu (ppb)	162	211	0.8
Mn	741	790	0.9
Na (%)	0.09	0.07	1.3
Sb	2.60	0.75	3.5
Sc	1.96	3.02	0.6
Sm	0.99	1.78	0.6
Rb	753	311	2.4
Th	3.91	4.31	0.9
Ti (%)	<0.06	0.13	<0.5
U	NS	1.37	-
V	4.68	22.6	0.2
Yb	0.40	0.87	0.5
Zn	356	122	2.9

\* Concentration in ppm or otherwise stated,  
NS = not seen