

RADIO PROPAGATION STUDIES AT 5.8GHZ WITHIN VEGETATED  
ENVIRONMENT FOR POINT-TO-MULTIPOINT APPLICATIONS

NOOR ZIELA BINTI ABD RAHMAN

UNIVERSITI TEKNOLOGI MALAYSIA

PROPAGATION STUDIES AT 5.8GHZ WITHIN VEGETATED ENVIRONMENT  
FOR POINT-TO-MULTIPOINT APPLICATIONS

NOOR ZIELA BINTI ABD RAHMAN

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Master of Engineering (Electrical)

Faculty of Electrical Engineering  
Universiti Teknologi Malaysia

SEPTEMBER 2013

To my family

## ACKNOWLEDGEMENT

It is my pleasure to convey my gratitude to people who involve in turning out this thesis possible in my humble acknowledgement. First of all, Alhamdulillah, I am so thankful to Allah SWT for His Most Merciful and Will that He granted me to finally complete the study. Without his Compassion, I might not be able to earn one.

Secondly, I would like to deliver my utmost gratitude to my supervisor, Prof. Dr. Tharek b Abd Rahman and co-supervisor Assoc. Prof. Dr. Tan Kim Geok for their endless supervision and guidance from the early stage of this research until the end of it.

Words fail me to express my appreciation to my husband, Mohd Rozaini b Mohd Zali whose dedication, love and persistent confidence in me, has taken the load off my shoulder. Special thanks to my parents, my grandmother, Kamariah bt M. Shuhud, my aunt, Rohana bt A. Jalal, my son Muhammad Afiq Hakeem b Mohd Rozaini and all of the family members for their devoted understanding, love and prayers. Also, I would like to thank AbduSamea for his knowledge sharing related to this research. In addition to that, collective acknowledgement goes to my colleagues at Multimedia University whose cooperation and understanding had been very helpful to me. Last but not least, I offer my regards to all of those who supported me in any aspect during the completion of the project as well as expressing my apology that I could not mention personally one by one.

## ABSTRACT

This thesis presents an empirical study for fixed wireless links based on IEEE802.16 standard in vegetated residential environment. Simulation and field measurements were conducted for suburban microcell channel by utilising 5.8 GHz of Unlicensed National Information Infrastructure (UNII). A set of comprehensive measurement that covered 13 point-to-multipoint links surrounding Universiti Teknologi Malaysia were selected to investigate the impact of vegetation on propagating radio waves. The aim of this study is to develop a path loss model that incorporates vegetation effect. Received Signal Strength (RSS), Signal-to-Noise Ratio (SNR) and factors influencing performance of the signal strength are highlighted here. Performance of RSS during daytime and night is also evaluated. The accuracy of proposed prediction model is analysed which quantifies that path loss is proportional to the distance of tree to the receiver, size, density and number of trees within the vicinity of transmitting and receiving antennas. Observation found that terrain and external effect, such as wind will significantly affect the signal performance too. Depending on the dynamic characteristics of trees presence between the communication links, the measurement results show that the path loss is increased from 5.69 dB to 33.67 dB. The results obtained are compared to Free Space Loss model, Weissberger model, and ITU-R model. Those established models are used to validate the applicability result obtained by means of Root Mean Square Error (RMSE). In view of this research work, a good agreement of the proposed excess loss model achieves the smallest RMSE for links obstructed by a single tree, row of trees, row of trees and road as well as row of trees, road and building.

## ABSTRAK

Tesis ini menerangkan kajian penyelidikan rangkaian talian tanpa wayar tetap berdasarkan piawaian IEEE802.16 di kawasan kediaman yang dikelilingi pokok. Kajian yang melibatkan simulasi dan eksperimen telah dijalankan di kawasan luar bandar pada frekuensi 5.8GHz '*Unlicensed National Information Infrastructure*.' Kajian menyeluruh telah dilakukan di 13 point-ke-multipoint *link* sekitar Universiti Teknologi Malaysia bagi mengkaji kesan pokok ke atas gelombang radio. Objektif kajian adalah untuk menghasilkan model empirik yang mengambil kira kesan pokok kepada isyarat radio. Kekuatan isyarat radio, nisbah *signal-to-noise* dan faktor yang mempengaruhi perubahan kekuatan isyarat radio turut dianalisa. Perbandingan kekuatan isyarat radio pada waktu siang dan malam turut dibentangkan. Dari analisis yang dijalankan, kekuatan isyarat radio bergantung kepada jarak antara pokok dan antena, saiz, kerimbunan pokok dan jumlah pokok di antara pemancar dan penerima. Cerun dan faktor luar seperti angin turut mempengaruhi kualiti gelombang radio. Analisa menunjukkan kehilangan isyarat meningkat dari 5.69dB kepada 33.67dB bergantung kepada ciri dinamik pokok di antara pemancar dan penerima. Model empirik ini dibandingkan dengan *Free Space* model, Weissberger model dan ITU-R model untuk tujuan pengesahan keputusan yang diperoleh. Berdasarkan perbandingan menggunakan *Root Mean Square Error* (RMSE), didapati model yang dihasilkan mempunyai nilai sisihan yang terkecil untuk semua *link* yang dikaji merangkumi *link* yang dihalang oleh sebatang pokok, beberapa pokok, beberapa pokok dan jalan, juga beberapa pokok, jalan dan bangunan.

## TABLE OF CONTENT

<b>CHAPTER</b>	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENT</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENT</b>	vii
	<b>LIST OF TABLES</b>	xii
	<b>LIST OF FIGURES</b>	xiv
	<b>LIST OF ABBREVIATIONS</b>	xviii
	<b>LIST OF SYMBOLS</b>	xix
	<b>LIST OF APPENDICES</b>	xxi
<b>1</b>	<b>INTRODUCTION</b>	
	1.1 Introduction	1
	1.2 Development of Broadband Wireless Access	2
	1.3 Application of Fixed Wireless Access	4

1.4	Problem Statement	5
1.5	Research Objectives	6
1.6	Scope of Research	6
1.7	Thesis Outline	10

## 2

### **RADIO WAVE PROPAGATION**

2.1	Introduction	11
2.2	Propagation Channel	12
2.3	Fresnel Zone	12
2.4	Radio Propagation Mechanism	16
2.4.1	Direct Wave	17
2.4.2	Reflection	17
2.4.3	Diffraction	18
2.4.4	Scattering	20
2.4.5	Absorption	20
2.4.6	Multipath Fading	21
2.5	Free Space Propagation	21
2.6	Received Signal Strength Indicator	22
2.7	Path Loss Model	23
2.8	Small Scale Fading	26
2.8.1	Gaussian Distribution	26
2.8.2	Rayleigh Distribution	27
2.8.2	Rician Distribution	28
2.8.3	Nakagami Distribution	28
2.8.4	Log-normal Distribution	29
2.9	Research Associated to Vegetation	30

2.10	Classification of Propagation Model	37
2.10.1	Empirical Model	38
2.10.1.1	Weissberger Model	38
2.10.1.2	ITU-R Model	39
2.10.1.3	ITU-R P.8337	39
2.10.2	Deterministic Model	40
2.10.3	Semi-deterministic Model	41
2.11	Summary	42

### **3 METHODOLOGY**

3.1	Introduction	42
3.2	Research Methodology	43
3.2.1	Investigation Phase	44
3.2.2	Implementation Phase	44
3.3	ATDI Simulation	47
3.4	Received Signal Strength Measurement Procedures	49
3.5	Measurement Procedures	51
3.5.1	Line-of-Sight (LOS) link	52
3.5.2	Near Line-of-Sight (NLOS) links	55
3.6	Measurement of received signal strength between daytime and night	63
3.7	Height of antennas, trees and buildings measurement	63
3.8	Summary	65

## 4

**RESULTS AND DISCUSSION**

4.1	Introduction	66
4.2	Received Signal Strength based on ATDI simulation	67
4.2.1	Single Tree	67
4.2.2	Row of trees	69
4.2.3	Row of Trees and Road	72
4.2.4	Row of Trees, Road and Building	74
4.2.5	Overall Performance	75
4.3	Received Signal Strength based on Field Measurement	76
4.3.1	Single Tree	76
4.3.2	Row of trees	78
4.3.3	Row of Trees and Road	83
4.3.4	Row of Trees, Road and Building	85
4.3.5	Overall Performance	87
4.4	Comparison of RSS between ATDI Simulation and Field Measurement	89
4.5	Comparison of RSS to Direct Wave	91
4.6	Path Loss	99
4.7	Fast Fading	105
4.8	RSS Performance during Daytime and Night	109
4.9	Signal-to-Noise Ratio	111
4.10	Summary	113

<b>5.1</b>	<b>CONCLUSION AND FUTURE WORK</b>	
5.1	Conclusion	115
5.2	Future Work	117
	<b>REFERENCES</b>	118
	<b>APPENDIX A</b>	127-131

**LIST OF TABLES**

<b>TABLE</b>	<b>TITLE</b>	<b>PAGE</b>
1.1	Guideline for short range communication device	4
2.1	Path loss exponent values for different types of wireless environment	25
3.1	Site information and antenna parameter for line-of-sight link	54
3.2	Site information and antenna parameter for links obstructed by row of trees	58
3.3	Site information and antenna parameter for links obstructed by row of trees and road	60
3.4	Site information and antenna parameter for links obstructed by row of trees, road and building	62
4.1	Simulation parameters and predicted results for LOS links	67
4.2	Simulation parameters and predicted results for NLOS links obstructed by row of trees	71
4.3	Simulation parameters and predicted results for NLOS links obstructed by row of trees and road	73
4.4	Simulation parameters and predicted results for NLOS links obstructed by row of trees, road and building	75

4.5	Received signal strength (RSS), path loss and excess loss for line-of-sight (LOS) links	77
4.6	Received signal strength (RSS), path loss and excess loss at links obstructed by row of trees	79
4.7	Received signal strength (RSS), path loss and excess loss at links obstructed by row of trees and road	84
4.8	Received signal strength (RSS), path loss and excess loss for links obstructed by row of trees, road and building	85
4.9	Average Received Signal Strength (RSS) recorded from December 2009 to April 2010	88
4.10	Comparison of RSS obtained from ATDI simulation and field measurement	90
4.11	Performance power received, path loss and excess loss relative to LOS link	92
4.12	Path loss and excess loss on 10 <sup>th</sup> April 2010	99
4.13	Data statistics for path loss, free space loss and excess loss	101
4.14	Error statistics of model prediction compared with excess loss for 13 links in UTM	104
4.15	Comparison of received power and path loss between daytime and night	109

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	K-Chart	8
2.1	Fresnel zone	13
2.2	Fresnel zone clearance	15
2.3	Radio wave mechanism	16
2.4	Plane Earth Propagation Model	17
2.5	Measurement geometries (a) line of trees, (b) into vegetation, (c) wedge vegetation, (d) edge vegetation	32
3.1	Overview of Research Work	43
3.2	Implementation Phase Design	46
3.3	Flow Chart of Field Strength Prediction Process by Using ATDI	48
3.4	Directional antenna with gain of 20dBi	50
3.5	Directional antenna with gain of 7dBi	50
3.6	Measurement area – Kolej Tun Dr Ismail and Kolej Tun Razak, UTM	51
3.7(a)	Measurement site - MA7_M10	53
3.7 (b)	Measurement site – K11_K28	53
3.8(a)	Measurement sites– K11_K23 and K11_K24	55
3.8(b)	Measurement site – L01_L34	56
3.8(c)	Measurement sites – K01_K16 and K01_K17	56

3.8(d)	Measurement site – M01_M19	57
3.9	Measurement sites – MA1_M23, MA1_M38 and MA1_M42	59
3.10	Measurement sites – K11_K22	61
3.11	Leica Disto A5	63
3.12	Dual Tilt Measurement	64
4.1	ATDI simulation for MA7_M10	67
4.2	ATDI simulation for K11_K28	68
4.3	ATDI simulation for K01_K16	69
4.4	ATDI simulation for K01_K17	69
4.5	ATDI simulation for K11_K23	69
4.6	ATDI simulation for K11_K24	70
4.7	ATDI simulation for M01_M19	70
4.8	ATDI simulation for L01_L34	70
4.9	ATDI simulation for MA1_M23	72
4.10	ATDI simulation for MA1_M27	72
4.11	ATDI simulation for MA1_M42	72
4.12	ATDI simulation for K11_K22	74
4.13	ATDI simulation for K11_K26	74
4.14	Received Power at MA7_M10 for one day (10 <sup>th</sup> April 2010)	77
4.15	Received Power at K11_K28 for one day (10 <sup>th</sup> April 2010)	77
4.16	Received Power at K01_K17 for one day (10 <sup>th</sup> April 2010)	81
4.17	Received Power at K01_K16 for one day (10 <sup>th</sup> April 2010)	81
4.18	Received Power at K11_K23 for one day (10 <sup>th</sup> April 2010)	81

4.19	Received Power at K11_K24 for one day (10 <sup>th</sup> April 2010)	82
4.20	Received Power at M01 to M19 for one day (10 <sup>th</sup> April 2010)	82
4.21	Received Power at L01_L34 for one day (10 <sup>th</sup> April 2010)	82
4.22	Received Power at MA1_M23 for one day (10 <sup>th</sup> April 2010)	84
4.23	Received Power at MA1_M38 for one day (10 <sup>th</sup> April 2010)	85
4.24	Received Power at MA1_M42 for one day (10 <sup>th</sup> April 2010)	85
4.25	Received Power at K11_K22 for one day (10 <sup>th</sup> April 2010)	86
4.26	Received Power at K11_K26 for one day (10 <sup>th</sup> April 2010)	86
4.27	RSS versus distance for 13 links in UTM	93
4.28	Excess loss versus number of trees for 13 links in UTM	95
4.29	Path loss versus distance for 13 links in UTM	100
4.30	Path loss versus distance for 13 links in UTM	101
4.31	Vegetation loss versus vegetation depth for 13 links in UTM	102
4.32	Comparison Excess Path Loss against Weissberger Model and ITU-R Model versus Vegetation Depth for 13 links in UTM	103
4.33	PDF comparison for links obstructed by single tree	105
4.34	PDF comparison for links obstructed by row of trees	106
4.35	PDF comparison for links obstructed by row of trees and road	106
4.36	PDF comparison for links obstructed by row of trees, road and building	107
4.37	PDF comparison for 13 links in UTM	107
4.38	Comparison of RSSI between daytime and night	110

4.39	Comparison of path loss between daytime and night	110
4.40	SNR versus RSS for 13 links in UTM	112
4.41	SNR versus distance for 13 links in UTM	113

**LIST OF ABBREVIATIONS**

EIRP	-	Effective Isotropic radiated Power
FWA	-	Fixed Wireless Access
IEEE	-	Institute of Electrical and Electronics Engineer
LAN	-	Local Area Network
LOS	-	Line-of-Sight
MAN	-	Metropolitan Area Network
NLOS	-	Non Line-of-Sight
RSSI	-	Received Signal Strength Indicator
SNR	-	Signal-to-Noise ratio
UNII	-	Unlicensed National Information Infrastructure
WiFi	-	Wireless Fidelity
WiMAX	-	Wireless Microwave Access
WLAN	-	Wireless Local Area Network

## LIST OF SYMBOLS

$F_N$	-	Fresnel zone radius
$\lambda$	-	Wavelength
$d_1$	-	Distance from one end terminal to point where $F_n$ is being determined
$d_2$	-	Distance from the other end terminal to point where $F_n$ is being determined
$c$	-	Speed of electromagnetic propagation
$f$	-	Frequency
$F_1$	-	First Fresnel zone
$d$	-	Length of the link in kilometers
$PL_{dB}$	-	Path loss
$P_T$	-	Transmitted power
$P_R$	-	Receiver power
$G_T$	-	Transmitter antenna gain
$G_R$	-	Receiver antenna gain
$L$	-	Total loss
$L_{FSL}$	-	Free space loss
$L_{EXCESS}$	-	Excess loss due to Vegetation
$PL_{(R_0)}$	-	Path loss at reference distance $R_0$
$R_0$	-	Reference distance
$R$	-	Distance between receiver and transmitter

$n$	-	Path loss exponent
$\mu$	-	Mean of random variable $r$
$\sigma$	-	Standard deviation of random variable $r$
$\sigma^2$	-	Time-average power of the received signal before envelope detection
$r$	-	Received signal envelope
$\mathcal{G}$	-	Variance of either real or imaginary terms of random multipath component
$I_0$	-	Modified Bessel function
$A$	-	Amplitude of dominant component
$m$	-	Shape parameter
$\Omega$	-	Scale parameter
$\Gamma$	-	Gamma function
$Am$	-	Maximum attenuation for one terminal within a specific type and depth of vegetation in dB
$\gamma$	-	Specific attenuation for every short vegetation paths in dB/m
$Erms$	-	Root mean square error

## **LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Steps to calculate RSSI by means of ATDI	125-129

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Introduction**

Emergence of interactive multimedia communication tools have led to a dramatic increase of interest on wireless communication technology during the last few years. Recent study conducted by Burson-Marsteller (2011) revealed that demand for wireless communication is constantly growing to provide network access which was previously dominated by wired communications. To cater large number of user and concurrently sustaining the scarcity of spectrum utilization, an accurate prediction model for reliable radio communication infrastructure is essential. This chapter briefly describes the development and application of fixed wireless access, as well as the research background, objective, scope and thesis outline. The subsequent chapters detailed out the research work conducted.

## 1.2 Development of Broadband Wireless Access

Fixed Wireless Access (FWA) refers to a range of radio system, used primarily to support various applications including data, voice and video services to multiple users within a radio coverage area. Instead of cables, radio link is used to convey fast broadband services between user and core networks. Rates for internet access will likely become cheaper due to lesser need to extend the cables for each subscriber and less number of access points. In fact, FWA has become a viable solution owing to its' convenience, flexibility and cost effectiveness.

Most of the FWA systems are deployed in millimeter-wave range as it offers large availability of bandwidth and high frequency reusability (Lacan & McBride, 2009). By leveraging the advanced of antenna innovation and smaller electronics components, large number of user can afford to use the technology in microcell systems.

The convergence of WiFi and WiMAX has contributed to an explosive growth of FWA systems. Integration of IEEE802.11 and IEEE802.16 for WiFi and WiMAX provided a complete suite of broadband services in large scale area (Finneran, 2004). WiMAX provides the ability to expand broadband services by offering coverage not in WiFi hotspots (Motorola & Intel, 2007). Synergy of both technologies also improved quality of signal received.

In terms of deployment perspective, both standards were designed for completely different applications. IEEE 802.11 was intended to add mobility to local area networks (LAN) while, IEEE 802.16 is designed to provide a basis for a carrier-provided to metropolitan access networks (MAN), wireless local area networks

(WLAN) and cellular mobile networks (Kowal, Kubal, Piotrowski, & Zielinski, 2010). However, some elementary technical characteristics are common such as spectrum shared between 802.16 and 802.11a at 5.8GHz as defined by Institute of Electrical and Electronics Engineers (2003).

Unlicensed National Information Infrastructure (UNII) is part of radio frequency spectrum used for WLAN based on IEEE 802.11 standards. WLAN operates in two frequency bands which are 2.4GHz and 5.8GHz. IEEE802.11b and IEEE802.11g standards govern for 2.4GHz whereas IEEE802.11a is specifically used for 5.8GHz (Dean, 2010). In Malaysia, upper UNII band which ranges from 5.75GHz to 5.875GHz is particularly used for FWA, mobile, radiolocation and amateur radio application (MCMC, 2009).

The evolution of broadband wireless specifically IEEE 802.16 standard was successfully initiated around year 2000. Several standards were revised through four phases. They are narrowband wireless local-loop systems, first generation line-of-sight (LOS) broadband systems, second generation non-line-of-sight (NLOS) broadband systems and standards-based broadband wireless systems to enable specific scenarios in both licensed and unlicensed frequencies (Andrews, Ghosh, & Muhamed, 2007).

Continued development of wireless technology based on IEEE802.16 and IEEE802.11 are likely to address connection challenges between suburban environment and wireless network. Therefore, to design a high performance FWA system, it is imperative that a detailed understanding of radio propagation mechanisms is achieved.

### 1.3 Application of Fixed Wireless Access

FWA is generally used for fast Internet access which provides businesses and residential user reliable and uninterrupted Internet access without the need to dial up each time a connection is required. It also offers potential for rapid development, backwards-compatibility with older laptop and desktop computer and low router operating power which are usually restricted to 1W, or 1/5000 of cellular telephone tower (Dobkin, 2005).

Application of FWA can be classified as point-to-point and point-to-multipoint. Point-to-point FWA applications enable communication from node to node comprising of a transmitter and a receiver. On the other hand, point-to-multipoint links provide multiple path of transmission from a single location to multiple locations.

A guideline for short range communications device was issued by (Malaysian Communications and Multimedia Commission, 2003) . This framework addressed the use of WLAN equipment for public wireless Internet access. The maximum Effective Isotropic Radiated Power (EIRP) should not exceed the values as specified in Table 1.1 below.

**Table 1.1:** Guideline for short range communication device

Frequency Band	Maximum EIRP (Watts)	Maximum EIRP (dBm)
2400 MHz to 2500 MHz	0.5	27
5250 MHz to 5350 MHz	1	30
2725 MHz to 5875 MHz	1	30

## 1.4 Problem Statement

Topographic features on natural elements such as vegetation and terrain has a higher effect as compared to man-made structures such as building and vehicular traffic. Trees which are varied in size, type, geometry, height and density are often planted between buildings. Some of the trees are higher than surrounding building, hence propagation is higher. Over the time, structure of trees might be changed due to growth and potentially block LOS of the communication links. Presence of trees within the first Fresnel zone will consequently degrades the signal strength to a few dB and limits the coverage area. As removing trees is not a practical solution, an accurate prediction model is required.

Numerous propagation studies in vegetated environment have been performed at UHF and VHF frequencies, which revealed that implication of vegetation cannot be neglected at frequency greater than 1GHz (Dias & Assis, 2011; Huang et al., 2006; Meng & Lee, 2010). Through extensive literature review, no satisfactory empirical model can accurately integrate the effect of vegetation in suburban areas, especially for tropical rainforest country. To date, only a few results for the NII band at 5.8GHz were presented, such as work presented by Muhammad, (2012), Pon, Rahman and Abu (2010) and (Karlsson, Schuh, Bergljung, Karlsson, & Lowendahl, 2001).

Therefore, to develop an accurate model which realistically suit Universiti Teknologi Malaysia (UTM) environment, the study is vital. Precise prediction model is imperative to determine link budget requirement, in order to achieve well-structured networks that able to cater large number of users and to optimize the scarcity of frequency in the most efficient manner.

## **1.5 Research Objectives**

The objectives of this research are:

- 1) To investigate the excess loss caused by vegetation that exists in the vicinity of FWA. Factors leading to degradation of received signal strength are analyzed accordingly.
- 2) To develop a radio prediction model which account the existence of vegetation between the communications links for suburban areas.
- 3) To investigate Received Signal Strength (RSS) performance during daytime and night.

## **1.6 Scope of Research**

This research investigates the propagation of radio wave under the same weather condition at 5.8GHz. The links represent typical point-to-multipoint links which incorporates a diversity of obstructions due to vegetation which includes single tree, row of trees, row of trees and roads as well as row of trees, buildings and roads. However, weather effects such as rain and fog are not considered in this research as the effect is insignificant at frequency of 5.8GHz as reported in various literature such as (Meng, Lee, & Ng, 2008), (ITU-R P.530-12, 2007) and (Pelet & Wells, 2004).

ATDI simulation and a series of field measurements will be carried out to determine excess loss for 13 WLAN access points in UTM. Terrain effect and Fresnel zone clearance are visualized by means of ATDI simulation. Received signal strength (RSS) and signal-to-noise ratio (SNR) with increasing vegetation depth as well as T-R separation distance are obtained from field measurement. Signal characteristic due to dynamic environmental factor such as day versus night is considered too.

In order to validate the path loss of proposed model, comparison to the established models, which are Free Space Loss model, Weissberger model and ITU-R model are performed with the aid of Root Mean Square Error (RMSE).

Scope, methodology and expected result are graphically presented as shown in Figure 1.1.



The scope of the research focuses on:

1) Simulation

ATDI simulation is used to predict first Fresnel zone and RSS of the individual communication link.

2) Field measurement

The measurement campaign is performed to investigate the average path loss of 13 links in UTM by considering LOS and NLOS links based on IEEE 802.11 WLAN standard at 5.8 GHz.

3) Collection of Data

Measurement data obtained will be filtered and screened using Textpad. These data are classified into RSS and SNR.

4) Data Analysis

After filtering the measurement data, RSS obtained from field measurement are illustrated with the aid of Matlab. The average path loss can be determined by using Microsoft Excel. Factors causing signal degradation are identified subsequently.

5) Model Development

A prediction model that agrees with campus environment based on parameters above will be developed.

6) Model Validation

The proposed model will be compared to existing vegetation model which are Weissberger model and ITU-R model.

## **1.7 Thesis Outline**

This thesis is structured in the following manner:

Chapter 2 investigates and describes fixed wireless access which provides mechanism on radio propagation and details out the effect of vegetation.

Chapter 3 concisely describes the experimental set-up in UTM. The experiment setup includes measurement procedures and equipments setup to perform the measurement.

Chapter 4 presents the ATDI simulation and empirical results of the measurement campaign. Detailed discussion on results obtained is enclosed.

Chapter 5 contains conclusion and suggestions for future work to be done based on findings presented in Chapter 4.

## REFERENCES

- Al-Nuaimi, M. O., & Stephens, R. B. L. (1998). Measurements and Prediction Model Optimisation for Signal Attenuation in Vegetation Media at Centimetre Wave Frequencies. *IEEE Proceedings of Microwaves, Antennas and Propagation*, 145(3), 201–206.
- Andrews, J. G., Ghosh, A., & Muhamed, R. (2007). *Fundamentals of WiMAX: Understanding Broadband Wireless Networking*. (T. S. Rappaport, Ed.) (pp. 4–16). New Jersey: Prentice Hall.
- Azevedo, J. A. R., & Santos, F. E. S. (2011). An Empirical Propagation Model for Forest Environments at Tree Trunk Level. *IEEE Transaction on Antennas and Propagation*, 59(6), 2357–2367.
- Bakshi, U. A., Bakshi, A. V., & Bakshi, K. A. (2009). *Electrical Measurements and Instrumentation*. India: Technical Publication Pune.
- Bello, J. C. R. D., Siqueira, G. L., & Bertoni, H. L. (2000). Theoretical Analysis and Measurement Results of Vegetation Effects on Path Loss for Mobile Cellular Communication Systems. *IEEE Transaction on Vehicular Technology*, 49(4), 1285–1293.
- Benzair, K. (1995). Measurements and Modelling of Propagation Losses through Vegetation at 1-4GHz. In *Ninth International Conference on Antennas and Propagation* (pp. 54–59).
- Blaunstein, N., Censor, D., Katz, D., Freedman, A., & Matityahu, I. (2003). Radio Propagation in Rural Residential Areas with Vegetation. *Progress In Electromagnetics Research*, 40, 131–153.
- Boban, M., Vinhoza, T. T. V., Ferreira, M., Barros, J., & Tonguz, O. K. (2011). Impact of Vehicles as Obstacles in Vehicular Ad Hoc Networks. *IEEE Journal on Selected Areas in Communications*, 29(1), 15–18.
- Bullington, K. (1947). Radio Propagation for Vehicular Communications. *IEEE Transaction on Vehicular Technology*, 26(4), 295–308.
- Burrows, C. R. (1966). Ultra-short-wave Propagation in the Jungle. *IEEE Transaction on Antennas Propagation*, 14(3), 386–388.
- Burson-Marsteller. (2011). Social Media Infographics H1 2011.
- Caldeirinha, R., & Al-Nuaimi, M. O. (2001). A novel FDTD based Model for Prediction of Bistatic RCS of Single Leaves and Trees. *Eleventh International Conference on Antennas and Propagation*. Manchester, UK.
- Camparetto, G., Schwartz, J., Schult, N., & Marshall, J. (2003). A Communications Analysis Tool Set That Accounts for The Attenuation due to Foliage, Buildings and Ground Effects. *IEEE Military Communications Conference*.

- Chua, T. H., Wassell, I. J., & Rahman, T. A. (2010). Combined Effects of Wind Speed and Wind Direction on Received Signal Strength in Foliated Broadband Fixed Wireless Links. *2010 Proceedings of the Fourth European Conference on Antennas and Propagation (EuCAP)*. Barcelona, Spain.
- Cuiñas, I., Antonio, J., Gay-Fernández, Alejos, A. V., & Sánchez, M. G. (2010). A Comparison of Radioelectric Propagation in Mature Forests at Wireless Network Frequency Bands. *2010 Proceedings of the Fourth European Conference on Antennas and Propagation*. Barcelona, Spain.
- Dapper, M., Wells, J. S., Scwallie, T., & Huon, L. (2003). RF Propagation in Short Range Sensor Communications. In E. M. Carapezza (Ed.), *Proceeding of the SPIE* (Vol. 5090, pp. 330–340). Orlando.
- De Bruyne, J., Joseph, W., Verlook, L., & Martens, L. (2008). Measurements and Evaluation of the Network Performance of a Fixed WiMAX System in Suburban Environment. *IEEE International Symposium on Wireless Communication System*. Reykjavik.
- Dean, T. (2010). *Network + Guide to Network* (5th ed., p. 865). Boston: Course Technology Cengage Learning.
- Deygout, J. (1966). Multiple Knife-edge Diffraction of Microwaves. *IEEE Transaction on Communications*, 14(4), 480–489.
- Dias, M. H. C., & Assis, M. S. de. (2011). An Empirical Model for Propagation Loss through Tropical Woodland in Urban Areas at UHF . *IEEE Transaction on Antennas and Propagation*, 59(1), 333–335.
- Didascalou, D., Younis, M., & Wiesbeck, W. (2000). Millimeter-Wave Scattering and Penetration in Isolated Vegetation Structures. *IEEE Transactions on Geoscience and Remote Sensing*, 38(5), 2106–2113.
- Dobkin, D. M. (2005). *RF Engineering for Wireless Networks : Hardware, Antennas and Propagation*. California, USA: Elsevier.
- Durgin, G., S.Rappaport, T., & Xu, H. (1998). Measurements and Models for Radio Path Loss and Penetration Loss In and Around Homes and Trees at 5.85GHz. *IEEE Transaction on Communications*, 46(11), 1484–1496.
- Egli, J. J. (1957). Radio Propagation Above 40 MC Over Irregular Terrain. *Proceedings of the IRE*, 45(10), 1383–1391.
- Epstein, J., & Peterson, D. W. (1953). An Experimental Study of Wave Propagation at 850 MC. *Proceedings of the IRE*, 41(5), 595–611.
- Ergen, M. (2009). *Mobile Broadband: Including WiMAX and LTE* (p. 513). Berkeley, USA: Springer.

- Finneran, M. F. (2004). *WiMAX versus WiFi: A Comparison of Technologies, Markets and Business Plan* (pp. 1–24).
- Giacomin, J. C., & Vasconcelos, F. H. (2006). Wireless Sensor Network as a Measurement Tool in Precision Agriculture. *28th IMEKO World Congress - Metrology for a Sustainable Development*. Rio de Janeiro, Brazil.
- Harn, G. K., Kiong, T. S., Koh, J., & Yap, D. (2008). WiMAX Channel Characteristic Analysis and Capacity Estimation. *2008 IEEE Region 10 Conference*. Hyderabad.
- Hashim, M. H., & Stavrou, S. (2006). Measurements and Modelling of Wind Influence on Radiowave Propagation Through Vegetation. *IEEE Transactions on Wireless Communications*, 5(5), 1055–1064.
- Haykin, S., & Moher, M. (2005). *Modern Wireless Communications*. New Jersey: Pearson Prentice Hall.
- Huang, X., Chen, B., Cui, H.-L., Jakob J. Stamnes, Pastore, R., Farwell, M., ... Ross, J. (2006). Radio-Propagation Model Based on the Combined Method Ray Tracing and Diffraction. *IEEE Transaction on Antennas and Propagation*, 54(4), 1284–1291.
- Husseini, A., Yaacoub, E., & Al-Kanj, L. (2010). A Wireless Communications Laboratory on Cellular Network Planning. *IEEE Transaction on Education*, 53(4), 653–661.
- ITU-R P.530-12, I. T. U. (ITU-R. (2007). *Propagation Data and Prediction Methods Required for the Design of Terrestrial Line-of-Sight Systems*.
- ITU-R P.833-7, I. T. U. (ITU-R. (2007). *Attenuation in Vegetation*.
- ITU-R P.833-7, I. T. U. (ITU-R. (2012). *Attenuation in Vegetation* (Vol. 7).
- James, K. R., Haritos, N., & Ades, P. K. (2006). Mechanical stability of trees under dynamic loads. *American Journal of Botany*, 93(10), 1522–1530.
- Joshi, G. G., Jr., C. B. D., Anderson, C. R., Newhall, W. G., Davis, W. A., Isaacs, J., & Barnett, G. (2005). Near-ground Channel Measurements over Line-of-Sight and Forested Paths. *IEEE Proceedings on Microwave, Antennas and Propagation*, 152(6), 589–596.
- Karlsson, A., Schuh, R. E., Bergljung, C., Karlsson, P., & Lowendahl, N. (2001). The influence of trees on radio channels at frequencies of 3GHz and 5GHz.  *Vehicular Technology Conference*.
- Kowal, M., Kubal, S., Piotrowski, P., & Zielinski, R. (2010). Operational Characteristic of Wireless WiMAX and IEEE802.11x Systems in Underground Mine Environments. *International Journal of Electronics and Telecommunications*, 56(1), 81–86.

- L. Willis, S., & Kikkert, C. J. (2005). Radio Propagation Model for Long-Range Ad-hoc Wireless Sensor Network. *2005 International Conference on Wireless Networks, Communications and Mobile Computing*. Maui.
- Lacan, I., & McBride, J. R. (2009). City Trees and Municipal Wi-Fi Networks: Compatibility or Conflict? *Abriculture and Urban Forestry*, 35(4), 203–210.
- LaGrone, A. H., & Chapman, C. W. (1961). Some Propagation Characteristics of High UHF Signals in the Immediate Vicinity of Trees. *IRE Transactions on Antennas and Propagations*, 9(5), 957–963.
- Lehpamer, H. (2004). *Microwave Transmission Networks: Planning, Design and Deployment* (p. 282). New York: McGraw-Hill.
- Liao, D. H., & Sarabandi, K. (2007). Modelling and Simulation of Near-Earth Propagation in Presence of a Truncated Vegetation Layer. *IEEE Transaction on Antennas and Propagation*, 55(3), 949–957.
- Lu, Y., Cheng, Y., Liu, W., Seah, H. W., Chan, H. L., & Tai, L. C. (2002). Low Frequency Radar Phenomenology Study in Equatorial Vegetation - Preliminary Results . *RADAR 2002*.
- Luca, D. De, Fiano, F., Mazzenga, F., Monti, C., Ridolfi, S., & Vallone, F. (2007). Outdoor Path Loss Models for IEEE 802.16 in Suburban and Campus-Like Environments. *IEEE International Conference on Communications* . Glasgow .
- Malaysian Communications and Multimedia Commission, M. (2003). Guideline on the Provision of Wireless LAN Service using Spread Spectrum Communications Equipment.
- Malhotra, R., Gupta, V., & Bansal, R. K. (2011). Simulation & Performance Analysis of Wired and Wireless Computer Networks. *International Journal of Computer Applications*, 14(7), 11–17.
- Mao, G., Anderson, B. D. O., & Fidan, B. (2006). Path Loss Exponent Estimation for Wireless Sensor. *Computer Network*, 51(10), 421–436.
- Masui, H., Kobayashi, T., & Akaike, M. (2002). Microwave Path-Loss Modeling in Urban Line-of-Sight Environments. *IEEE Journal on Selected Areas in Communications*, 20(6), 1151–1155.
- Maurer, J., Didascalous, D., Engelst, V., & Wiesbeck, W. (2010). Wideband Wave Propagation Measurements for Local Multipoint Distribution Services (LMDS) at 26GHz. *IEEE Conference on Vehicular Technology*.
- MCMC. (2009). Spectrum Allocations in Malaysia.
- Meireles, R., Boban, M., Tonguz, P. O., & Barros, J. (2010). Experimental Study on the Impact of Vehicular Obstructions in VANETs. *IEEE Vehicular Networking Conference*. Jersey City, NJ.

- Meng, Y. S., & Lee, Y. H. (2010). Investigations of Foliage Effect on Modern Wireless Communication Systems : A Review. *Progress In Electromagnetics Research, 105*, 313–332.
- Meng, Y. S., Lee, Y. H., & Ng, B. C. (2008). Investigation of Rainfall Effect on Forested Radio Wave Propagation. *IEEE Antennas Wireless Propagation Letter, 7*, 159–162.
- Meng, Y. S., Lee, Y. H., & Ng, B. C. (2009a). Empirical Near Ground Path Loss Modeling in a Forest at VHF and UHF Bands. *IEEE Transactions on Antennas and Propagation, 57*(5), 1461–1468.
- Meng, Y. S., Lee, Y. H., & Ng, B. C. (2009b). The Effects of Tropical Weather on Radio Wave Propagation over Foliage Channel. *IEEE Transaction on Vehicular Technology, 58*(8), 4023–4030.
- Motorola, & Intel. (2007). *WiMAX and WiFi Together: Deployment Models and User Scenarios* (pp. 1–11).
- Muhammad, N. A. (2012). *Influences of Wind and Rain on Radio Wave Propagation in Foliated Fixed Wireless at 5.8GHz*.
- Naz, N., & Falconer, D. D. (2000). Temporal Variations Characterization for Fixed Wireless at 29.5GHz. In *IEEE 51st Vehicular Technology Conference Proceedings*. Japan.
- Ndzi, D. L., Kamarudin, L. M., Mohammad, E. A. A., Zakaria, A., Ahmad, R. B., Fareq, M. M. A., ... Jaafar, M. N. (2012). Vegetation Attenuation Measurements and Modelling in Plantations for Wireless Sensor Network Planning. *Progress In Electromagnetics Research B, 36*, 283–301.
- Ndzi, D. L., Savage, N., & Stuart, K. (2005). Wideband Signal Propagation Through Vegetation. *XVII GA of URSI*. Delhi, India.
- P.526-8, I.-R. (2003). *Propagation by Diffraction* (pp. 1–23).
- Parsons, J. D. (2000). *The Mobile Radio Propagation Channel* (2nd ed.). West Sussex, England: John Wiley & Sons .
- Pelet, E. R., & Wells, J. E. S. G. (2004). Effect of Wind on Foliage Obstructed Line-of-Sight Channel at 2.5GHz. *IEEE Transaction on Broadcasting, 50*(3), 224–232.
- Phaiboon, S., & Phokharatkul, P. (2009). Path Loss Prediction for Low-Rise Buildings with Image Classification on 2-D Aerial Photographs. *Progress In Electromagnetics Research, 95*, 135–152.
- Pon, L. L., Rahman, T. A., & Abu, M. K. (2010). Investigation of Foliage Effects via Remote Data Logging at 5.8GHz. *WSEAS Transactions on Communication, 9*(4), 237–247.

- Rappaport, T. S. (2001). *Wireless Communications : Principles and Practice* (2nd ed.). New Jersey: Prentice Hall PTR.
- Reudink, D. O., & Wazowicz, M. F. (1973). Some Propagation Experiments Relating Foliage Loss and Diffraction Loss at X-band and UHF Frequencies. *IEEE Transaction on Communications*, 21(11), 1198–1206.
- Rogers, N. C., Seville, A., Ritcher, J., Ndzi, D., Savage, N., Caldeirinha, R. F. S., ... Austin, J. (2002). *A Generic Model of 1 - 60 GHz Radio Propagation through Vegetation*.
- Ryan, M. J., & Frater, M. R. (2002). *Communications and Information Systems* (p. 323). Canberra, Australia: Agros Press Series in Telecommunication Systems.
- Saunders, S., & Zaragon-Zavala, A. (2007). *Antennas and Propagation for Wireless Communication Systems*. New York: John Wiley and Sons Inc.
- Savage D Seville, A Vilar, E Austin, J, N. N. (2003). Radio Wave Propagation through Vegetation: Factors Influencing Signal Attenuation. *Radio Science*, 38(5), 1088.
- Savage, N., Ndzi, D. L., Austin, J., & Vilar, E. (2003). Signal Propagation through Vegetation: Consideration for Future Broadband Communication Systems . *Twelfth International Conference on Antenna and Propagation*.
- Schwengler, T., & Pendharkar, N. (2005). Propagation and Throughput Study for 802.16 Broadband Wireless Systems at 5.8GHz. *2005 IEEE Region 5 and IEEE Denver Section Technical, Professional and Student Development Workshop*.
- Seville, A. (1997). Vegetation Attenuation: Modelling and Measurements at Millimetric Frequencies. *Tenth International Conference on Antennas and Propagation*.
- Seybold, J. (2005). *Introduction to RF Propagation*. New Jersey: John Wiley & Sons.
- Swarup, S., & Tewari, R. K. (1979). Depolarization of Radio Waves in Jungle Environment. *IEEE Transaction on Antennas Propagation*, 27(1), 113–116.
- Tamir, T. (1967). On Radio-wave Propagation in Forest Environments. *IEEE Transaction on Antennas Propagation*, 15(6), 806–817.
- Tewari, R. K., Swarup, S., & Roy, M. N. (1984). An Empirical Result for The Height Gain in Forest Medium . *IEEE Transaction on Antennas and Propagation*, 32(11), 1265–1268.
- Thelen, J., Goense, D., & Langendoen, K. (2005). Radio Wave Propagation in Potato Fields. *First workshop on Wireless Network Measurements (co-located with WiOpt 2005)*. Riva del Garda, Italy.

- Vogel, W. J., & Goldhirsh, J. (1986). Tree Attenuation at 869MHz Derived from Remotely Piloted Aircraft Measurements. *IEEE Transactions on Antennas and Propagation*, 34(12), 1460–1464.
- Voldhaug, J. E., Braten, L. E., & Sander, J. (2010). Deployable WiMAX in a Forest Area; Channel Measurements and Modelling. *IEEE MILCOM 2010*. San Jose.
- Voldhaug, J. E., Braten, L. E., & Jostein Sander. (2010). Deployable WiMAX in a Forest Area; Channel Measurements and Modelling. In *The 2010 Military Communications Conference* (pp. 737–742).
- Weissberger, M. A. (1982). *An initial critical summary of models for predicting the attenuation of radio waves by trees*.
- Wiecek, D., & Wypior, D. (2011). New SEAMCAT Propagation Models : Irregular Terrain Model and ITU-R P.1546-4. *Journal of Telecommunications and Information Technology*, 3, 131–140.
- Xia, H. H., Bertoni, H. L., Leandro R. Maciel, Lindsay-Stewart, A., & Rowe, R. (1993). Radio Propagation Characteristics for Line-of-Sight Microcellular and Personal Communications. *IEEE Transaction on Vehicular Technology*, 41(10), 1439–1447.
- Yarong, L., Xiaofei, Y., Zhuojun, S., & Qiu, L. (2010). The Research of Path Loss Model Based on WiMAX Wireless Channel. *International Conference on Communication Systems, Networks and Applications*. Hong Kong.
- Yin, J., Yang, Q., & Ni, L. M. (2008). Learning Adaptive Temporal Radio Maps for Signal-Strength-Based Location Estimation. *IEEE Journal on Mobile Computing*, 7(7), 869–883.
- Zhang, W., He, Y., Liu, F., Miao, C., Sun, S., Liu, C., & Jin, J. (2011). Research on WSN Channel fading Model and Experimental Analysis In Orchard Environment. *5th IFIP TC 5/SIG 5.1 Conference, CCTA 2011*. Beijing, China.
- Zhou, T., Sharif, H., Hampel, M., Mahasukhon, P., Wang, W., & Ma, T. (2009). A Deterministic Approach to Evaluate Path Loss Exponents in Large-Scale Outdoor 802.11 WLANs. *Conference on Local Computer Networks*. Zurich, Switzerland.