A MULTI-FOCUS IMAGE FUSION TECHNIQUE FOR RGB COLOR IMAGES USING DISCRETE COSINE TRANSFORM (DCT).

SAFA RIYADH WAHEED

A dissertation submitted in partial fulfillment of the requirements for the award of the degree of Master of Science (Computer Science)

> Faculty of Computing Universiti Teknologi Malaysia

> > JAN 2014

This dissertation is dedicated to my family for their endless support and encouragement.

ACKNOWLEDGEMENTS

All praise is to Allah and my peace and blessing of Allah be upon our prophet, Muhammad and upon all his family and companions. In particular, I wish to express my sincere appreciation to my thesis supervisor, **PROF. DR.** <u>GHAZALI</u> <u>SULONG</u>, and to all my friends for encouragement, guidance, critics, advices and supports to complete this research. I really appreciate his ethics and great deal of respect with his students, which is similar to brothers in the same family.

In addition, I am extremely grateful to my father for unlimited support and encouragement during this research. I would like to thanks my beloved family: mother, fiancée, brother, and sisters who I am always beholden to them for their everlasting patience, support, encouragement, sacrifice, and love which have been devoted to me sincerely. I could endure for being away and eventually my master program came to fruition. For that, I ask Allah to bless all of them.

Besides, I would like to thank the authority of Universiti Teknologi Malaysia (UTM) and Faculty of Computing (FK) for providing me with a good environment and facilities such as computer laboratory to complete this project with software which I need during process.

Abstract

Image fusion is a process that combines information from multiple images of the same scene into a single image. In this study, a new image fusion technique is proposed using the Discrete Cosine Transform (DCT). Each of the source images may represent a partial view of the scene, and contains both 'relevant' and 'irrelevant' data. Since the target of image fusion technique is to combine the source images into a single composite image which contains a more accurate description of the scene than any of the individual sources. Moreover, the fused image has gotten the best possible quality without introduction of distortion or loss of information. DCT algorithm is considered efficient in image fusion. The proposed scheme is performed in five steps: (1) RGB colour image (input image) is split into three channels R, G, and B for both images.(2) DCT algorithm is applied to each channel (R, G and B) for image1 and image2 respectively. (3) The variance values are computed for the corresponding 8x8 blocks of each channel. (4) Each block of R (image 1) is compared with each block of R (image2) based on the variance value and then the block having maximum variance value is selected to be the block in the new image. This process is repeated for all channels of image1 and image 2. (5) Inverse discrete cosine transform (IDCT) is applied on each fused channel to convert it from coefficient values to pixel values, and then combined all the channels to generate the fused image. The proposed technique can potentially solve the problem of undesirable side effects like blurring or blocking artifacts from reducing the quality of the resultant image in image fusion. The proposed approach is evaluated using three measurement units: the average of Qabf, standard deviation and peak Signal Noise Rate (PSNR). The experimental results of this proposed technique achieved good results as compared to previous studies.

Abstrak

Gabunganimejadalahsatu proses yang menggabungkanmaklumatdaripadaberbilangimejdaritempatkejadian yang samakedalamsatuimej .Dalamkajianini, satuteknikbarugabunganimejadalahdicadangkanmenggunakanpiawaian MPEG (DCT).Setiapsatudaripadaimejsumberbolehmewakilipemandangansebahagiandaritem patkejadian, danmengandungikedua-dua data dan 'relevan' 'tidakrelevan' .Sejaksasaranalgoritmagabunganimejadalahuntukmenggabungkanimejimejsumberkedalamimejkomposittunggal yang mengandungipenerangan yang lebihtepattempatkejadiandaripadamana-manasumber-sumberindividu.Selainitu ,imej bersatutelahmendapatkualiti vang yang terbaiktanpapengenalanherotanataukehilanganmaklumat. Algoritma DCT dianggapcekapdalamgabunganimej. Skim yang dicadangkantelahdilaksanakan di lima langkah : (1) warnaimej RGB (imej input) terbahagikepadatigasaluran R, G, dan B bagikedua-duaimej. (2) algoritma DCT telahdigunakanuntuksetiapsaluran (R, G dan B) untuk image1 dan image2 masing-masing . (3) Nilaivariansdikirauntukblok 8x8 samasetiapsaluran Setiapblok image DCT. (4)R (1) telahdibandingkandengansetiapblok image2 R () berdasarkannilaivariansdankemudianblok yang mempunyainilaivariansmaksimumtelahdipilihuntukmenjadiblokdalamimejbaru. Proses inidiulangiuntuksemuasaluran image1 danimej 2. (5) Songsangpiawaian telahdigunakanpadasetiapsaluranpaduanuntukmenukarnilai-MPEG **IDCT** () nilaipekaliuntuk Pixel nilai-nilai, dankemudiandigabungkansemuasaluranuntukmenghasilkanimej yang bersatu. dicadangkanberpotensibolehmenyelesaikanmasalahkesansampingan Teknik vang yang tidakdiinginisepertikaburataumenyekatartifakdaripadamengurangkankualitiimej yang terhasildalamgabunganimej.Pendekatan yang disyorkandinilaimenggunakantiga unit pengukuran: purataQ^{abf}, sisihanpiawaidanpuncak Kadar BunyiIsyarat (PSNR). Keputusaneksperimenteknik yang dicadangkaninimencapaikeputusan yang baikberbandingdengankajiansebelumini.

TABLE OF CONTENT

CHAPTER

PAGE

| DECLARATION | ii |
|-------------------|-----|
| DEDICATION | iii |
| ACKNOWLEDGEMENT | iv |
| ABSTRACT | v |
| ABSTRAK | vi |
| TABLE OF CONTENTS | vii |
| LIST OF TABLES | Х |
| LIST OF FIGURES | xi |

1 INTRODUCTION

| 1.1 | Introduction | 1 |
|-----|-------------------------|---|
| 1.2 | Problem Background | 3 |
| 1.3 | Problem Statement | 5 |
| | 1.3.1 Research Question | 6 |
| 1.5 | Aim of The Study | 6 |
| 1.6 | Objectives of The Study | 7 |
| 1.7 | Scope of The Study | 7 |
| 1.8 | Thesis organization | 8 |

2 **LITERATURE REVIEW**

| 2.1 | Introdu | uction | 9 |
|-----|---------|-------------------------|----|
| 2.2 | RGB (| Color Images | 9 |
| | 2.2.1 | Color spaces | 10 |
| | 2.2.1.1 | RGB | 11 |
| | 2.2.1.2 | RGB to grey-scale image | |
| | | conversion | 14 |
| | 2.2.1.3 | YCbCr Color Space | 15 |

| 2.4 | Image fu | ision technologies overview | 20 |
|-----|---------------------------|--|----|
| 2.5 | Image fusion technologies | | 24 |
| | 2.5.1 | Fusion using Principle Component Analysis (PCA) | 24 |
| | 2.5.2 | Fusion using HIS color space | 25 |
| | 2.5.3 | Fusion using Laplacian pyramid method | 25 |
| | 2.5.4 | Fusion using gradient pyramid method | 25 |
| | 2.5.5 | Fusion using filter-subtract-decimate (FSD) pyramid method | 26 |
| | 2.5.6 | Fusion using discrete wavelet transforms (DWT) | 26 |
| | 2.5.7 | Multi-sensor and multi-resolution image fusion using the linear mixing model | 27 |
| | 2.5.8 | Image fusion schemes using ICA bases | 28 |
| | 2.5.9 | Statistical modeling for wavelet-domain image fusion | 29 |
| | 2.5.10 | Bayesian methods for image fusion | 29 |
| | 2.5.11 | Multidimensional fusion by image fusion | 30 |
| | 2.5.12 | Fusion of multispectral and images as an optimization problem | 31 |
| | 2.5.13 | Fusion of edge maps using statistical approaches | 32 |
| | 2.5.14 | Region-based multi-focus image fusion | 33 |
| | 2.5.15 | Concepts of image fusion in remote sensing applications | 34 |
| | 2.5.16 | Pixel-level image fusion metrics | 34 |
| | 2.5.17 | Objectively adaptive image fusion | 36 |
| | 2.5.18 | Performance evaluation of image fusion techniques | 36 |

| 2.6 | A wave | A wavelet-based image fusion | |
|-----|---|------------------------------|----|
| | 2.6.1 | Wavelet Theory | 37 |
| 2.7 | Quality indicators for assessing image fusion | | 45 |
| | 2.7.1 | Qualitative analysis | 45 |
| | 2.7.2 | Quantitative analysis | 46 |
| 2.8 | Summa | ry | 50 |

3 **RESEARCH METHODOLOGY**

| 3.1 | Introduction | 53 |
|-----|---------------------------------|----|
| 3.2 | General framework | 54 |
| 3.3 | Discrete Cosine Transform (DCT) | 58 |
| | 3.3.1 The One-Dimensional DCT | 58 |
| | 3.3.2 The Two Dimensional DCT | 59 |
| 3.4 | Material And Method | 60 |
| 3.5 | Performance measure | 61 |
| 3.6 | Comparing both fusion method | 64 |
| 3.7 | Robustness Testing | 65 |
| 3.8 | Summary | 65 |

4

INITIAL RESULT

| 4.1 | Introduction | 66 |
|-----|-----------------------|----|
| 4.2 | Dataset | 66 |
| 4.3 | Implementation Result | 70 |
| 4.4 | summary | 83 |

5 CONCLUSION

| 5.1 | summary | 84 |
|-----|--------------|----|
| 5.2 | Contribution | 85 |
| 5.3 | Future Work | 85 |

6 **REFERENCES** 86

LIST OF FIGURES

| FIGURE NO. | TITLE | PAGE |
|------------|--|------|
| 2.1 | The RGB color cube | 10 |
| 2.2 | The RGB channels | 12 |
| 2.3 | RGB color space as a 3-D cube | 13 |
| 2.4 | An example of RGB color image (left) to grey-scale image (right) conversion | 14 |
| 2.5 | The conversion formula between digital RGB data and YCbCr | 16 |
| 2.6 | Image fusion for an IKONOS scene for Cairo, Egypt: (a) multispectral low resolution input image, (b) panchromatic high resolution input image, and (c) fused image of IHS | 17 |
| 2.7 | CCD visual images with the (a) right and (b) left clocks out of focus, respectively; (c) the resulting fused image from (a) and (b) with the two clocks in focus | 18 |
| 2.8 | Images captured from the (a) visual sensor and (b) infrared sensor, respectively; (c) the resulting fused image from (a) and (b) with all interesting details in focus | 19 |
| 2.9 | (a) MRI and (b) PET images; (c) fused image from (a) and (b) | 20 |
| 2.10 | Image fusion block scheme of different abstraction levels | 21 |
| 2.11 | The image fusion classification level | 23 |
| 2.12 | The image fusion system using ICA/ Topographical ICA bases | 28 |
| 2.13 | Fusion of multispectral and panchromatic images as an optimization problem | 32 |

| 2.14 | The subjective and objective image fusion process evaluation | 35 |
|------|---|----|
| 2.15 | Block diagrams of generic fusion schemes where the input images have identical (a) | |

| | and different resolutions (b) | 42 |
|------|--|----|
| 2.16 | Objective method for image quality assessment | 46 |
| 2.17 | Methods for assessing image quality | 46 |
| 3.1 | Set 1. Image 1 (a) focus on left, Image 2 (b) focus on right | 54 |
| 3.2 | General framework of the proposed technique | 55 |
| 3.3 | DCT fusion process for selected channel | 60 |
| 4.1 | Qabf Evaluation using RGB and YCbCr | 78 |
| 4.2 | Qabf Evaluation levels using RGB and YCbCr | 78 |
| 4.3 | Standard Deviation Evaluation using RGB and YCbCr | 79 |
| 4.4 | Standard Deviation Evaluation levels using RGB and YCbCr | 79 |
| 4.5 | PSNR for fused images RGB and YCbCr | 81 |
| 4.6 | Mean Square Error for fused images by using RGB and YCbCr | 81 |
| 4.7 | Structural Content for fused images by using RGB and YCbCr | 82 |
| 4.8 | Normalized Cross-Correlation for fused images by using RGB and YCbCr | 82 |

LIST OF TABLES

| TABLE NO. | TITLE | PAGE |
|-----------|---|------|
| | | |
| 2.1 | comparison of different image fusion techniques | 43 |
| 4.1 | Data set Images | 67 |
| 4.2 | present the 19 dataset couple images and the results | |
| 4.3 | those applied by using RGB color space model present the 19 dataset couple images and the results | 71 |
| 4.4 | those applied by using YCbCr color space model showing values of PSNR, NCC, MSE, AD and | 74 |
| | Structural Content | 80 |

CHAPTER 1

INTRODUCTION

1.1 Introduction

Rapid development of the technique of sensors, micro-electronics, and communications requires more attention on information fusion. Several situations in image processing require high spatial and high spectral resolution in a single image. For example, the traffic monitoring system, satellite image system, and long range sensor fusion system are all used in the image processing. However, the majority of available equipment is not capable of providing this type of data convincing. The sensor in the surveillance system can only provide the scenery view in a narrow depth for a particular focus, yet the demand of the application of the system requires a clear view with a high depth of the field. Thus, the image fusion provides the possibility of combining different sources of information.

Besides, four applications motivate this thesis includes: (1) Multi-sensor image fusion, (2) Medical image fusion, (3) Surveillance System, and (4) Aerial and Satellite imaging. The particular applications discussed include medical diagnosis, remote sensing, surveillance systems, biometric systems, and image quality assessment.

In all sensor networks, every sensor can observe the environment, produce and transfer data. Visual sensor networks (VSN) is the term used in the literature to refer to a system with a large number of cameras geographically spread at monitoring

points (Patricio et al., 2006). In VSN, sensors are cameras which can record either still images or video sequences. Therefore, the processing of output information is related to image processing and machine vision subjects.

A distinguished feature of visual sensors or cameras is the great amount of generating data. This characteristic requires more local processing resources to deliver only the useful information represented in a conceptualized level (Castanedo et al., 2008). Image fusion is generally defined as the process of combining multiple source images into a smaller set of images, usually a single one that contain a more accurate description of the scene than any of the individual source images. The goal of image fusion, besides reducing the amount of data in network transmissions is to create new images that are more informative and suitable for both visual perception and further computer processing (Drajic et al., 2007). Due to the limited depth of focus on optical lenses, only the objects at a particular depth in the scene are in focus and those in front of or behind the focus plane will be blurred. In VSN we have the opportunity of extending the depth of focus using multiple cameras.

So far, several researches have been focused on image fusions which are performed on the images in the spatial domain (Lewis et al., 2007; Yang et al., 2008; Roux et al., 2008; Zaveri et al., 2009; Arif et al., 2012). The algorithms based on multi-scale decompositions are more popular. The basic idea is to perform a multi-scale transform on each source image and then integrate all of these decomposition coefficients to produce a composite representation. These methods combine the source images by monitoring a quantity that is called the activity level measure. The activity level determines the quality of each source image. The integration can be carried out either by choosing the coefficients with larger activity level or a weighted average of the coefficients. The fused image is finally reconstructed by performing the inverse multi-scale transforms. Examples of this approach include Laplacian, gradient, morphological pyramids, and discrete cosine transform (DCT).

In general, most of the spatial domain image fusion methods are complex and time-consuming, which made it not suitable for real-time applications. In VSN, especially the links between nodes, which are wireless consumed energy for data processing is much less than the consumed energy for communication. Therefore, in most of the sensor network systems, data are compressed before transmission to the other nodes. In VSN, images are compressed in camera nodes and then transmitted to the fusion agent, and afterwards the compressed fused image will be saved or transmitted to an upper node. Hence, when the source images are coded in Joint Photographic Experts Group (JPEG) standard, as a prevalent standard or when the fused image will be saved or transmitted in JPEG format, the fusion methods which are applied in DCT domain will be more efficient.

1.2 Problem Background

The success of fusion images acquired different modalities or an instrument is of great importance in many applications as medical imaging, microscopic imaging, remote sensing, computer vision and robotics. Image fusion can be defined as the process by which several image features are combined together to form a single image. Image fusion can be performed at different levels of the information representation. Four different levels can be distinguished according to (Abidi and Gonzalez,1992) i.e. signal, pixel, feature and symbolic levels. To date, the results of image fusion from remote sensing and medical imaging are primarily intended for presentation to a human observer for easier and enhanced interpretation. Therefore, the perception of the fused image is of paramount importance when evaluating different fusion schemes. Some generic requirements can be imposed on the fusion result:

- a) The fused image should preserve closely as possible for all relevant information contained in the input images.
- b) The fusion process should not introduce any artifacts or inconsistencies, which can distract or mislead the human observer or any subsequent image processing steps Rockinger.
- c) In the fused image, irrelevant features and noise should be suppressed to a maximum extent.

When fusion is done at pixel level, the input images are combined without any preprocessing. Pixel level fusion algorithms vary from very simple image averaging to very complex e.g. principal component analysis (PCA), pyramid based image fusion and wavelettransform fusion.

Several approaches to pixel level fusion can be distinguished based on whether the images are fused in the spatial domain or in a transform domain. After the fused image is generated it may be processed further to extract some features of interest. In image fusing, two or more images which are not more suitable for analysis are taken and these are converted into a single image in which noise is eliminated, but retaining the important features of each of the source images is more suitable for exploration. Fusion of colorimages can be carried in two ways:

- a) First convert color images into gray images and apply fusion for the gray images and then convert fused gray image back to color images.
- b) Decompose the color image into three components then apply fusion to red components of the input images individually and then fuse green components and then blue (or simultaneously). Afterward, the fusion combines all the three colors to form the final image.

But the problem involved in the process (a) is while converting image first from color to gray before fusion, gray to color after fusion the final image color characteristics may change because of the approximations involved in this process. So, a direct fusion of color images is preferred where the color of the images has the most importance.

1.3 Problem Statement

In recent years, many image fusion techniques and algorithms have been exploited and they have been successfully used in the fusion process. More recently, the development of DCT theory was implemented forDCT multi-scale decomposition to take the place of the pyramid decomposition for image fusion.

Image fusion is a process that combines information from multiple images of the same scene into a single image. In this study, a new image fusion technique is proposed using the Discrete Cosine Transform (DCT). Each of the source images may represent a partial view of the scene, and contain both 'relevant' and 'irrelevant' data. So the goal of an image fusion algorithm is to combine the source images into a single composite image which contains a more accurate description of the scene than any of the individual sources. Moreover, the fused image got the best possible quality without the introduction of distortion or loss of information.

The Discrete Cosine transform DCTfusionschemeoffer severaladvantages over similar pyramid based fusion schemes when it comes to image fusion:

(a) The DCT transform provides directional information while the pyramid representation doesn't introduce any spatial orientation in the decomposition process

- (b) In pyramid based image fusion, the fused images often contain blocking effects in the regions where the input images are significantly different. No such artifacts are observed in similar DCT based fusion results.
- (c) Images generated by DCT image fusion have better signaltonoise ratios PSNR than images generated by a pyramid image fusion when the same fusionrules are used.

1.3.1 Research Question

This Study will focus on the following questions:

- 1- How can multi-focus image fusion on color image at pixel level of the input images?
- 2- How can discrete cosine transform technique (DCT) beproposed as a new multi-focus fusion technique?
- 3- Is there any difference if a different color space modelwas used to get better technique for image fusion?
- 4- How can willevaluate the proposetechnique using standard dataset image?

1.4 Aim of the Study

The aim of this research is to implement an Image Fusion Technique for Color Images using Discrete CosineTransformby different color space model for improving the image fusion from the input images.

1.5 Objectives of theStudy

The objectives of this research are:

- 1. To propose new fusion techniqueusing discrete cosinetransform technique (DCT) based on RGB color space model.
- 2. To propose a new fusion technique using discrete cosinetransform technique (DCT) based on YCbCr color space model.
- 3. To compare and evaluate the proposed method using standard and referenced dataset.

1.6 Scope of theStudy

In order to achieve the objectives stated above, the scope of this study is limited to the following:

- The suggested technique applied by MATLAB language version on windows 7 milieus.
- 2. To focus on RGB input multi-focus images.
- 3. To focus on RGB and YCbCr color space model.
- 4. The database aimed to be used in this study is a standard RGB picture using in most popular search in the field of image fusion.

1.7 Thesis organization

The dissertation is organized as follows: In the first chapter provide the introduction, the problem background, problem statements, aim of the study, objective of this study and research question to the research. The chapter two also provides a simple overview introduction about the image fusion technique specifically themulti-focus images, basic principles of image fusion and image fusion techniques while the chapter three makesprovision for the proposed technique methodology explanation. The chapter four discussed a result of the methodology provided in chapter three. Finally, the overall conclusions of the thesis and recommendations for future works are in chapter five.

REFERENCES

- Abidi, M. A., & Gonzalez, R. C. 1992. Data fusion in robotics and machine intelligence. Academic Press Professional, Inc.
- Achim, A., Loza, A., Bull, D. and Canagarajah, N. 2006. Statistical modeling for waveletdomain image fusion. Department of Electrical and Electronic Engineering, University of Bristol, Bristol, UK.
- Ahmed, N., Natarajan, T. and Rao, K. R. 1974. Discrete Cosine Transform. IEEE Trans on Computers. 32. pp 90-93.
- Aiazzi, B., Alparone, L., Baronti, S. and Pippi, I. M. S. 2003. Generalisedlappacianpyramidbased fusion of MS+P image data with spectral distortion minimization. Institute of applied physics. Florence, Italy.
- Arif, M and Shah S. 2012. Block level multi-focus image fusion using wavelet transform. Proceedings of IEEE international conference on signal acquisition and processing (ICSAP). p. 213–6.
- Audícana, G. M. and Seco, A. 2003. Fusion of multispectral and panchromatic images using wavelet transform. Evaluation of crop classification accuracy. Proc. 22nd EARSeLAnnu.Symp.Geoinformation Eur. pp 265–272.
- Benes, T. E. 2002. Performance Comparison of various levels of Fusion of Multifocused Images using Wavelet Transform. pp 67-94.
- Beyerera, J., Heizmanna, M., Sanderb, J., and Ghetab, I. 2011.Bayesian methods for image fusion. Image Fusion: Algorithms and Applications, 157.
- Castanedo, F., García, J., Patricio, M. A., & Molina, J. M. (2008, June). Analysis of distributed fusion alternatives in coordinated vision agents. In Information Fusion, 2008 11th International Conference on (pp. 1-6). IEEE.
- Chan, Chan, L. and Nasrabadi, S. D. N. M. 2003 . Dualband FLIR fusion for automatic target recognition. Information Fusion. (4) pp 35-45.
- Chandana, M., Amutha, S. and Kumar, N. 2011. A Hybrid Multi-focus Medical Image Fusion Based on Wavelet Transform. International Journal of Research and Reviews in Computer Science (IJRRCS). 2 (4). pp 2079-2557.

- Chetan, K., Narendra, S. and Patel, M. 2011. Pixel based and Wavelet based Image fusion Methods with their Comparative Study. National Conference on Recent Trends in Engineering & Technology. pp. 13-14.
- Clevers, J.G.P.W., and Zurita-Milla, R. 2008. Multi-sensor and multi-resolution image fusion using the linear mixing model. Wageningen University, Centre of Geo-Information.
- Drajic, D., & Cvejic, N. 2007. Adaptive fusion of multimodal surveillance image sequences in visual sensor networks. Consumer Electronics, IEEE Transactions on, 53(4), 1456-1462.
- Garzelli, A., Capobianco, L. and Nencini, F. 2006. Fusion of multispectral and panchromatic images as an optimization problem. Department of Information Engineering. University of Siena, Siena, Italy.
- Giannarou, S. and Stathaki, T. 2003. Fusion of edge maps using statistical approaches. Communication and Signal Processing Group. Imperial College London, London, UK.
- Huang, W. and Jing, Zh.L. 2007. Multi-focus image fusion using pulse coupled neural network. Pattern Recognition Letters. 28 (9). pp 1123-1132.
- Ibrahim, S. and Wirth, M. 2009. Multiresolution region-based image fusion using the Contourlet Transform. IEEE TIC-STH.
- Lewis, J; Ocallaghan, R; Nikolov, B. S; and Canagarajah, N.2007. Pixel- and region-based image fusion with complex wavelets. Inform Fusion. 8 (2). p 30-119.
- Li, S. and Yang, B. 2005. Region-based multi-focus image fusion. College of Electrical and Information Engineering. Hunan University, China.
- Li, S., Kwok, J. T. and Wang, Y. 2001. Combination of images with diverse focuses using the spatial frequency. Information fusion. 2 (3). pp 167-176.
- Li, S; Yang B. 2008. Multifocus image fusion using region segmentation and spatial frequency. Image Vis Comput. 26 (7). 9-79.
- Malviya, A. and Bhirud, S. G. 2009. Image Fusion of Digital Images. International Journal of Recent Trends in Engineering. 2 (3). pp 95-132.
- Meng, M. and Liu, L. 2006. Sketching image morphing using moving least squares. Department of Mathematics. Zhejiang University, China.
- Mitianoudis, N. 2010. Image fusion: theory and application. International Hellenic University. Imperial college, London.

- Mitianoudis, N. Tania, Stathaki. 2007. Pixel-based and Region-based Image Fusion Schemes using ICA bases. Information Fusion. (8) 131-142.
- Naidu, V. 2010. Discrete Cosine Transform-based Image Fusion. Special Issue on Mobile Intelligent Autonomous System. Defence Science Journal. 60 (1). pp 48-54.
- Naidu, V.P.S. and Raol, J.R. 2008. Pixel-level Image Fusion using Wavelets and Principal Component Analysis. Defence Science Journal. 58 (3). pp. 338-352.
- Pajares, G. and Cruz, J. M. 2004. A wavelet-based image fusion tutorial. Pattern ecognit.37 (9). pp 1855–1872.
- Pajares, G. and Cruz, J. M. 2004. A wavelet-based image fusion tutorial. 2004 Pattern Recognition Society.
- Pennebaker, W. B. and Mitchell, J. L. 1993. JPEG Still Image Data Compression Standard. International Thomsan Publishing. Newyork.
- Pérez, Ó., Patricio, M. A., Garcia, J., Carbo, J., & Molina, J. M. (2006, July). Fusion of surveillance information for visual sensor networks. In Information Fusion, 2006 9th International Conference on (pp. 1-8). IEEE.
- Petrovic, V. and Cootes, T. 2007. Objectively adaptive image fusion. Imaging Science and Biomedical Engineering. University of Manchester, Oxford Road, Manchester, UK.
- Piella, G. 2003. A General Framework for Multiresolution Image Fusion: from Pixels to Regions. Information Fusion 4. pp 259-280.
- Piella, G., and Heijmans, H. 2002.Multiresolution image fusion guided by a multimodal segmentation. Proceedings of Advanced Concepts of Intelligent Systems. pp 175-182.
- Pohl et al., C.Pohl and J.L.VanGenderren. 1998. Multisensor image fusion in remote sensing: concepts, methods and applications. INT.J.REMOTE SENSING, 19 (5). pp 823-854.
- Pradham, P., Younan, N.H. and King, R.L. 2006. Concepts of image fusion in remote sensing applications. Department of Electrical and Computer Engineering. Mississippi State University. USA.
- Rajan, D. R. and Chaudhuri, S. 2002. Data fusion techniques forsuper-resolution imaging. Information Fusion (3) 25-38.

- Sadjadi, F. 2005. Comparative image fusion analysis. Proc. IEEE Conf. Comput. Vision Pattern Recogn. San Diego. USA.
- Schechner, Y. and Nayer, S. K. 2007. Multidimensional fusion by image fusion. Department of Computer Science. Columbia University, New York, USA.
- Scheunders, P., and De Backer, S. 2001. Fusion and merging of multispectral images with use of multiscale fundamental forms. JOSA A, 18(10). pp 2468-2477.
- Shapiro, L. G. 1982. Organization of relational models. International Conference Pattern Recognition. pp 360-365.
- Singh, S., Siddiqui, T. J., Singh, R. and Singh, H.V. 2011. DCT- domain robust data hiding using chaotic sequence. International Conference on Multimedia, Signal processing and communication technologies, IEEE. pp. 300-303.
- Smith, M. and Heather, J. 2005. Review of image fusion technology. <u>www.waterfallsolutions.co.uk</u>.
- Smith, M.I. and Heather, J.P. 2005. Review of image fusion technology. Proceedings on Defense and Security Symposium. Orlando.
- Stathaki, T. 2008. Image Fusion: Algorithms and Applications. New York: Academic.
- Toet, A. and Franken, E. M. 2003 . Perceptual evaluation of different image fusion schemes. 24 (1). pp 25–37.
- Vekkot, S., Huang, S. G. and Shukla, P. 2009. A Novel Architecture for Wavelet based Image Fusion. World Academy of Science, Engineering and Technology 57
- Vladimir, P. and Xydeas, C. 2005. Objective evaluation of signal-level image fusion performance. Optical Engineering. 44 (8) .Wageningen. Netherlands.
- Wang, H., Jing, Z. and Li, J. 2003. An image fusion approach based on discrete wavelet frame. Institute of Aerospace Information and Control. Shanghai Jiao Tong University.
- Wang, M., Dai, Y., Liu, Y., and Yanbing, T. 2010. Feature-level image sequence fusion based on histograms of Oriented Gradients. In Computer Science and Information Technology (ICCSIT), 2010 3rd IEEE International Conference on IEEE. pp 265-269.

- Wang, Q., Shen, Y. and Jin, J. 2005. Performance evaluation of image fusion techniques. Department of Control Science and Engineering. Harbin Institute of Technology, China.
- Xu, L; Roux, M; Mingyi, H, and Schmitt, F. 2008. A new method of image fusion based on redundant wavelet transform. Proceedings of the IEEE fifth international conference on visual information engineering. p 7-12.
- Xydeas, C. and Petrovic, V. 2006. Pixel-level image fusion metrics. Imaging Science and Biomedical Engineering. University of Manchester, Oxford Road, Manchester, UK.
- Zaveri T; Zaveri M; Shah V and Patel, N. 2009. A novel region based multifocus image fusion method. Proceedings of IEEE international conference on digital image processing (ICDIP). p. 4-50.
- Zeng, J. and Sayedelahl, A. 2006. Review of Image Fusion Algorithms for Unconstrained Outdoor Scenes. Department of Electrical and Computer Engineering, Howard University, Washington, ICSP.
- Zhang, Y. 2004. Understanding image fusion "Photogram". Eng. Remote Sens.70 (6) pp. 657–661.
- Zhang, Y. and Wang, R. 2004. Multi-resolution and multi-spectral image fusion for urban object extraction. International Society for Photogrammetry and Remote Sensing, XXth ISPRS Congress.
- Zhang, Z. and Blum, R.S. 1999. A Categorization of Multiscaledecompositionbased Image Fusion Schemes with a Performance Study for a Digital Camera Application. Proceedings of the IEEE . 87 (8). pp 1315-1326.
- Zhang, Z. and Blum, R.S. 1999. A Categorization of Multiscaledecompositionbased Image Fusion Schemes with a Performance Study for a Digital Camera Application. Proceedings of the IEEE. 87 (8). pp 1315-1326.
- Zheng, Y., Essock, E. A. and Hansen, B. C. 2004. An Advanced Image Fusion Algorithm Based on Wavelet Transform – Incorporation with PCA and Morphological Processing.