

**OFFLINE HANDWRITING RECOGNITION USING
ARTIFICIAL NEURAL NETWORK AND HIDDEN MARKOV MODEL**

TAY YONG HAUR

A thesis submitted in fulfillment of the requirements
for the joint award of the Degree of
Doctor of Philosophy

**Faculty of Electrical Engineering
Universiti Teknologi Malaysia**

And

**Ecole Doctorale Sciences et Technologies de l'Information et de Matériaux
Ecole Polytechnique de l'Université de Nantes
Université de Nantes**

November 2001

DEDICATION

To my family and my lovely girlfriend

ACKNOWLEDGEMENTS

I would like to express my deepest gratitude and appreciation to my supervisors, Prof. Dr. Marzuki bin Khalid and Prof. Dr. Dominique Barba, for their support and advice throughout the entire research process. Special thanks to Dr. Pierre-Michel Lallican, Dr. Stefan Knerr and Assoc Prof. Dr. Christian Viard-Gaudin, for their friendship, encouragement, enthusiastic guidance and support, which have made my Ph.D. research a fun and exciting journey of my life.

I must thank Universiti Teknologi Malaysia for funding this research. I am also grateful to the French Embassy in Kuala Lumpur and Vision Objects, for their support and assistance during my stays in Nantes, France, as well as participation in several international conferences.

Not forgetting, I would like to thank the staffs and colleagues in the following locations, for every enjoyable moment being with them:

- Center for Artificial Intelligence and Robotics (CAIRO), Universiti Teknologi Malaysia
- Laboratoire IVC, IRCCyN, Ecole Polytechnique de l'Université de Nantes
- Vision Objects

I would like to thank my parents and family members for their love and support. A special heart-felt thanks goes to my girlfriend, Ms. Lim Lee Hwa, for the sacrifices, patience and understanding. This research could not come to this point without her love and encouragement.

March 2002

TAY YONG HAUR

ABSTRACT

Cursive handwriting is the most natural way for humans to communicate and record information. The developments of automatic systems that are capable of recognizing human handwritings offer a new way of improving human-computer interface and of enabling computers to perform repetitive tasks of reading and processing handwritten documents more efficiently. The aim of this thesis is to design an offline handwritten word recognition system based on the hybrid of Artificial Neural Network (ANN) and Hidden Markov Model (HMM). The Input space segmentation (INSEG) approach proposes various ways to segment word into characters. This approach creates the problem of *junks* – character hypotheses that are not true characters. Two training approaches have been introduced, namely character level discriminant training and word-level discriminant training. The latter shows integration of the ANN and HMM by using the gradient descent algorithm. Different topologies of the ANN have been investigated for modeling of *junks*. Three isolated word databases, namely, IRONOFF, AWS and SRTP, have been used as the evaluation of the proposed system. Experimental results have shown that the ANN-HMM hybrid with word-level discriminant training consistently yield better recognition accuracy compared to character level discriminant training and discrete HMM-based recognition system. It achieves recognition accuracy of 97.3%, 88.4%, 90.5% and 95.8%, on IRONOFF-196, IRONOFF-1991, SRTP-Cheque, and AWS, respectively.

ABSTRAK

Tulisan sambung atau kursif merupakan satu cara yang paling mudah dan senang bagi manusia untuk berkomunikasi dan mencatatkan maklumat. Pembangunan satu sistem yang berkeupayaan untuk mengecam tulisan manusia membuka peluang baru untuk memperbaiki perantaramukaan di antara manusia dan komputer. Selain daripada itu, ia juga dapat membolehkan komputer melakukan kerja yang berulang untuk membaca dan memproses dokumen bertulis dengan berkesan. Tujuan tesis ini adalah untuk merekabentuk and membangunkan sebuah sistem pengecaman perkataan bertulis yang berasaskan hibrid antara Rangkaian Neural (ANN) dan Model Markov Tersembunyi (HMM). Pengsegmentasi INSEG mencadangkan pelbagai cara untuk mengsegmentkan perkataan kepada aksara-aksara. Process ini menyebabkan masalah *junk* – hipotesis aksara yang bukan aksara benar. Dua cara pembelajaran telah diperkenalkan iaitu pembelajaran diskriminasi peringkat aksara dan pembelajaran diskriminasi peringkat perkataan. Cara pembelajaran kedua itu menunjukkan persepaduan kedua-dua teknik ANN and HMM dengan menggunakan algoritma penurunan kecerunan (*gradient descent*). Pelbagai topologi ANN telah diperiksa untuk mengkaji kebolehan untuk pemodelan *junk*. Tiga pangkalan data perkataan bertulis, iaitu IRONOFF, AWS and SRTP telah digunakan untuk menilai keberkesanan sistem yang dicadangkan. Keputusan ujikaji-ujikaji yang telah dijalankan menunjukkan model hibrid ANN-HMM dengan cara pembelajaran diskriminasi berperingkat perkataan sentiasa menghasilkan keputusan yang lebih baik berbanding dengan pembelajaran diskriminasi berperingkat aksara serta sistem pengecaman berdasarkan HMM diskret. Ia mencapai ketepatan pengecaman 97.3%, 88.4%, 90.5% dan 95.8% pada IRONOFF-196, IRONOFF-1991, SRTP-Cheque dan AWS.

RESUME

L'écriture manuscrite, notamment cursive, permet aux Hommes de communiquer et de conserver l'information d'une manière très naturelle et spontanée. Le développement de systèmes automatiques capables de reconnaître l'écriture ouvre de nouvelles perspectives pour les interfaces Homme-machine ainsi que pour le traitement très rapide de masses de documents en automatisant les tâches de lecture de ceux-ci. L'objectif de cette thèse est de concevoir un système de reconnaissance hors-ligne de mots manuscrits basé sur un système hybride de type réseau de neurones artificiels (ANN) et modèles de Markov cachés (HMM). L'approche de segmentation proposée (INSEG) conduit à de multiples segmentations du mot en caractères. Cela induit un problème de représentation d'une classe « *poubelle* » (junks) pour représenter toutes les hypothèses de segmentation qui ne correspondent pas à de vrais caractères. Deux approches d'apprentissage sont introduites, un apprentissage discriminant au niveau caractère et un apprentissage discriminant au niveau mot. Cette dernière permet de coupler l'apprentissage du HMM et de l'ANN par un algorithme de descente de gradient. Plusieurs topologies ont été étudiées pour modéliser la classe « *poubelle* ». Trois bases de mots isolés, à savoir, IRONOFF, AWS et SRTP, ont été utilisées pour évaluer le système proposé. Les résultats expérimentaux obtenus montrent que le système hybride ANN-HMM, utilisé avec un apprentissage discriminant au niveau mot, surclasse à la fois le système hybride avec apprentissage discriminant au niveau lettre et un système HMMs discrets. Les performances de reconnaissances obtenues sont respectivement de 97.3%, 88.4%, 90.5% et 95.8%, sur les bases IRONOFF-196, IRONOFF-1991, SRTP-Cheque, et AWS.

TABLE OF CONTENTS

CHAPTER	TOPIC	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	RÉSUMÉ	vii
	TABLE OF CONTENTS	viii
	LIST OF TABLES	xiii
	LIST OF FIGURES	xv
	LIST OF SYMBOLS AND ABBREVIATIONS	xxi
CHAPTER 1	INTRODUCTION	1
	1.1 Background	1
	1.2 Problems	2
	1.2.1 Nature of the Handwriting Signals	3
	1.2.2 Handwriting Styles	4
	1.2.3 Writer Dependency	6
	1.2.4 Vocabulary Size	6

1.2.5	Language	7
1.3	Applications of Handwriting Recognition	8
1.3.1	Bank Cheque Processing	9
1.3.2	Form Processing	10
1.3.3	Handwritten Address Interpretation	10
1.3.4	Input Method for Electronic Appliances	11
1.4	Scope and Objectives	11
1.5	Thesis Layout	12
CHAPTER 2	HANDWRITING RECOGNITION	14
2.1	Introduction	14
2.2	Statistical Pattern Recognition	15
2.2.1	Bayes' Theorem	15
2.2.2	Pattern Classification Approaches	17
2.3	The State of the Art	19
2.4	Segmentation	22
2.4.1	Holistic Approach	24
2.4.2	Classical Analytical Approach	25
2.4.3	Recognition-based Segmentation Approach	27
2.5	Training and Recognition	27
2.5.1	Holistic Approach	27
2.5.2	Classical Analytical Approach	28
2.5.3	Segmentation by Recognition Approach	28
2.6	Summary	31

CHAPTER 3	OFFLINE CURSIVE HANDWRITTEN WORD RECOGNITION SYSTEM	33
3.1	Introduction	33
3.2	Recognition System Overview	33
3.3	Image Preprocessing	34
3.3.1	Binarization	34
3.3.2	Slant Estimation and Correction	35
3.3.3	Edge Smoothing	37
3.3.4	Reference Line Detection	38
3.4	Segmentation	39
3.4.1	Sliding Windows	40
3.4.2	Segmentation Graph	41
3.5	Feature Extraction	43
3.5.1	Handcrafted Features	44
3.5.2	Feature Vector Normalization	49
3.6	Recognition using ANN-HMM Hybrid	51
3.6.1	Basic Hidden Markov Models	55
3.6.2	Word-level Hidden Markov Models	58
3.6.3	Artificial Neural Network	59
3.6.4	Word Recognition	62
3.6.5	Forward-Backward	65
3.6.6	Viterbi	66
3.7	Summary	67
CHAPTER 4	SYSTEM PARAMETERS AND TRAINING	69
4.1	Introduction	69

4.2	Problems	70
4.2.1	Prior	70
4.2.2	Class Overlapping	72
4.2.3	Junk	73
4.3	Character-level Discriminant Training	74
4.3.1	Bootstrap	75
4.3.2	Refining	76
4.3.3	Junk Training	76
4.4	Word-level Discriminant Training	79
4.4.1	MMI Criterion	81
4.4.2	ML Criterion	86
4.4.3	Training	87
4.5	Summary	88
CHAPTER 5	EXPERIMENTS AND RESULTS	90
5.1	Introduction	90
5.2	Handwriting Databases	91
5.2.1	IRONOFF	92
5.2.2	SRTP	93
5.2.3	AWS	93
5.2.4	MNIST	94
5.3	Recognition Performance Measurement	94
5.4	Digit Recognition	95
5.5	Character-level Discriminant Training	100
5.5.1	Baseline Word Recognition System	102
5.5.2	Experimental Results	103

5.6	Word-level Discriminant Training	105
5.6.1	Training Convergence using MMI Criterion	106
5.6.2	Training Convergence using ML Criterion	107
5.6.3	Comparison of Different ANN Topology	109
5.6.4	Recognition Performance on Different Databases	112
5.7	Error Analysis	113
5.7.1	Correctly Recognized Examples	114
5.7.2	Preprocessing and Segmentation	118
5.7.3	Reference Lines Detection	120
5.7.4	Unmatched Label	121
5.7.5	Rare Handwriting Styles	122
5.7.6	Difficult	123
5.8	Size of Training Data	124
5.9	Combination of Multiple Recognizers	126
5.9.1	Different Initialization and Configurations	126
5.9.2	Offline and Online Features	129
5.10	Summary	131
CHAPTER 6	CONCLUSIONS	134
	BIBLIOGRAPHY	139
APPENDIX A	PUBLISHED PAPERS	156

LIST OF TABLES

Table 1-1.	Different categories of problems based on size of vocabulary	6
Table 2-1.	Reported recognition performance of offline handwritten word recognition systems.	22
Table 3-1.	Summary of the feature categories and number of features for each category.	49
Table 3-2.	Sixty-nine basic-HMMs used in the system	56
Table 5-1.	Summary of the handwriting databases used in this thesis	91
Table 5-2.	Digit recognition performance benchmark on MNIST as reported in [LeCun et al, 1998].	96
Table 5-3.	Number of stripes in feature extraction influences the number of input neurons of ANN.	97
Table 5-4.	Recognition performance for each training stage on IRONOFF-196	104
Table 5-5.	Recognition performance of the two recognizers on three data sets.	105
Table 5-6.	Reported recognition performances on AWS database.	105
Table 5-7.	Recognition performance of the two recognizers on three data sets.	113
Table 5-8.	Different types of errors	114

Table 5-9.	Training and test error rate on different number of training examples	124
Table 5-10.	Configuration and initialization of recognizers	127
Table 5-11.	Percentage of common errors and discrepancies between two recognizers with different configurations.	129
Table 5-12.	Percentage of common errors and discrepancies between online and offline recognizers with different configurations.	131

LIST OF FIGURES

Figure 1.1.	Various handwriting styles for the word “six”	2
Figure 1.2.	Different types of handwriting styles. (a) Box discrete characters.	4
Figure 1.3.	Various recognition processes to be performed to automate back cheque processing.	9
Figure 2.1.	Discriminant function formed by PDF, posterior probability and boundary forming classification for a two-class problem with one input feature.	17
Figure 2.2.	Training of a PDF classifier using data for two classes denoted C_1 and C_2 .	18
Figure 2.3.	Training of a posterior classifier using data for two classes denoted C_1 and C_2 .	19
Figure 2.4.	Example of an image of word ‘minimum’. It would be difficult to segment the word into letters without the knowledge of dictionary.	23
Figure 2.5.	(a) Word Image. (b) Word-shape divided in regions. (c) Global features extracted for each region.	24
Figure 2.6.	Schematic illustration of the two segmentation techniques. (a) OUTSEG associates likelihood of the sub-images to particular character classes (b) INSEG only chooses the relevant character hypotheses for the recognition.	28

Figure 3.1.	Process flow of the cursive handwritten word recognition system.	34
Figure 3.2.	Example of some results of the binarization process	35
Figure 3.3.	(a) 4 directions of a chain code. (b) Average slant of a chain code sequence.	36
Figure 3.4.	Example of results using the slant correction algorithm.	37
Figure 3.5.	3x3 convolution masks used in the smoothing algorithm. The middle pixel is toggled if any occurrence of the mask is found in the image. (a) Masks to eliminate orphan pixels. (b) Masks to fill in single pixel openings.	37
Figure 3.6.	Result of the edge smoothing algorithm.	38
Figure 3.7.	A word image is divided vertically in three zones, namely ascender, core and descender zone.	38
Figure 3.8.	Local minimas and maximas of an image.	39
Figure 3.9.	A variable size window sliding from left to right of an image.	40
Figure 3.10.	(a) Word 'cts' is segmented in 5 slices. (b) Segmentation graph that describes all possible ways to segment the word into letters. The bold lines indicate the true segmentation path for the word 'cts'.	42
Figure 3.11.	Vertical distances from the farthest ink pixel at the ascender zone (up), and descender zone (low), to the edge of the core zone.	46
Figure 3.12.	Line crossing for (a) horizontal and vertical directions and (b) +45° diagonal and -45° diagonal direction.	47
Figure 3.13.	Profiles for (a) left, right, top, down direction and (b) +45°, +135°, -45°, -135° diagonal direction.	47
Figure 3.14.	(Top) Distribution of the feature values of all the training examples. (Bottom) Linear transformation to	

- map values from f_{MIN} and f_{MAX} to $\overline{f_{MIN}}$ and $\overline{f_{MAX}}$, respectively. 51
- Figure 3.15. Each character hypothesis in the segmentation graph is fed into the ANN for likelihood computation. This in turn generates a recognition graph shown below the figure. 53
- Figure 3.16. Basic recognition lattice. Arcs linking the nodes show valid combinations of character hypotheses to form the word 'cts'. 54
- Figure 3.17. Topology of the (a) character-HMM and (b) ligature-HMM. 57
- Figure 3.18. Word-HMM "cts" is composed of character-HMMs 'c', 't' and 's', with ligature-HMMs inserted before and after each character-HMM. Lines in bold indicate the best path through the model for the example of Figure 3.10b. 59
- Figure 3.19. An example of a Multilayer Perceptron (MLP) with two layers of adaptive weights. 59
- Figure 3.20. Extended recognition lattice from Figure 3.16. White rhombuses represent the states that emit observation if given the observation formed by a specified number of slices. Gray rhombuses represent states that emit full observation (1.0), which correspond to the gray states in the basic-HMM in Figure 3.17. 63
- Figure 4.1. Character-level Discriminant Training versus Word-level Discriminant Training. 70
- Figure 4.2. (a) Typical image for class 'c'. (b) Typical image for class 'C'. (c) An image that gives ambiguity in deciding between classes 'C' and 'c'. 72
- Figure 4.3. Class overlapping between 'c' and 'C'. 73

Figure 4.4.	The junk class is covering all other area of the feature space that is not covered by the character classes.	74
Figure 4.5.	Three stages of character-level discriminant training.	75
Figure 4.6.	Pseudo-code for the character-level discriminant training	79
Figure 4.7.	For word-level discriminant training using MMI criterion, the ANN is trained by back-propagating the join gradients (position from the true model and negative from the best model) from the word models. Notice that no gradient is propagated for unrelated character classes.	85
Figure 4.8.	For word-level discriminant training using ML criterion, the ANN is trained by back-propagating the gradients from the true word models only.	87
Figure 4.9.	Flow chart of the word-level discriminant training process.	88
Figure 5.1.	Randomly selected examples from the IRONOFF Database.	92
Figure 5.2.	Randomly selected examples from the SRTP Database.	93
Figure 5.3.	Randomly selected examples from the AWS Database.	94
Figure 5.4.	The training (solid lines) and test (dotted lines) recognition results on different number of features and number of hidden neurons in the ANN. Chart (a) was obtained on training and testing with original 60,000 and 10,000 examples, respectively. Chart (b) was obtained on training with 240,000 examples, generated from the original 60,000 examples, and testing on 10,000 examples.	99
Figure 5.5.	Comparative digit recognition results for different ANN output activation functions.	100

Figure 5.6.	Overview of the recognition system. On the left is the discrete HMM recognizer, and on the right is the HMM/ANN Hybrid recognizer using separate training.	101
Figure 5.7.	Topology of a 5-state left-right character-HMM (left) and a 6-state ergodic ligature-HMM (right) for the discrete HMM recognizer.	103
Figure 5.8.	Concatenation of the word-HMM ‘million’	103
Figure 5.9.	Recognition performance (IRONOFF-1991) for each training epoch.	106
Figure 5.10.	Recognition performance on IRONOFF-1991 trained on ML criterion, for each training epoch.	108
Figure 5.11.	Six different configurations of the ANN used in the experiment.	111
Figure 5.12.	Recognition performance of recognizers with different configuration in the ANN on IRONOFF-1991 (* indicates the ANN is bootstrapped).	112
Figure 5.13.	Correctly Recognized Examples: True Class – ‘deux’	115
Figure 5.14.	Correctly Recognized Examples: True Class – ‘rugby’	115
Figure 5.15.	Correctly Recognized Examples: True Class – ‘gâchez’	116
Figure 5.16.	Correctly Recognized Examples: True Class – ‘voilà’	116
Figure 5.17.	Correctly Recognized Examples: True Class – ‘quinze’	117
Figure 5.18.	Correctly Recognized Examples: True Class – ‘Fréquence’	117
Figure 5.19.	Correctly Recognized Examples: True Class – ‘million’	118
Figure 5.20.	Preprocessing & Segmentation: True Class – ‘trente’	119
Figure 5.21.	Preprocessing & Segmentation: True Class – ‘seize’	120
Figure 5.22.	Preprocessing & Segmentation: True Class – ‘six’	120
Figure 5.23.	Preprocessing & Segmentation: True Class – ‘dix’	120

Figure 5.24.	Reference Lines Detection: True Class – ‘frs’	121
Figure 5.25.	Reference Lines Detection: True Class – ‘un’	121
Figure 5.26.	Reference Lines Detection: True Class – ‘l’élève’	121
Figure 5.27.	Unmatched Label: True Class – ‘Journal’	122
Figure 5.28.	Unmatched Label: True Class – ‘Hydrogen’	122
Figure 5.29.	Unmatched Label: True Class – ‘onze’	122
Figure 5.30.	Unmatched Label: True Class – ‘trente’	122
Figure 5.31.	Rare Handwriting Styles: True Class – ‘monétaires’	123
Figure 5.32.	Rare Handwriting Styles: True Class – ‘la’	123
Figure 5.33.	Rare Handwriting Styles: True Class – ‘celui’	123
Figure 5.34.	Tough: True Class – ‘frs’ (duplicate word)	123
Figure 5.35.	Tough: True Class – ‘centimes’	124
Figure 5.36.	Tough: True Class – ‘francs’	124
Figure 5.37.	Recognition Error versus Training Size on IRONOFF database.	125
Figure 5.38	(a)(b)and (c). The combined recognizer (open triangle) shows better recognition performance compared to its individual recognizers (solid diamond and rectangle indicators).	128
Figure 5.39.	The combined online and offline recognition performance on IRONOFF-1991 (plotted with triangle mark) exceed the individual online or offline recognizer’s performance.	130

LIST OF SYMBOLS AND ABBREVIATIONS

ϖ_{\min} and ϖ_{\max}	Minimum and maximum sliding window size.
h_{cz}	Core zone height.
Λ_{\max}	Maximum number of consecutive slice to form character hypotheses.
λ^r	True word model
λ^*	Best word model
L_{ML}	Maximum Likelihood Objective function
L_{MMI}	Maximum Mutual Information
O_t	Observation at time t
$P(O \lambda)$	Word likelihood
$p(x C)$	Character or class likelihood
$P(\lambda O)$	Word posterior probability
$P(C x)$	Character or class posterior probability
$p(x)$	Unconditional Probability
N^c	Maximum number of allowable combination of slices to form character c
Θ	Average word slant
α	Forward variable

β	Backward variable
a	Transition probability
b	Observation probability
ANN	Artificial Neural Networks
HMM	Hidden Markov Models
MLP	Multilayer Perceptrons
MLE	Maximum Likelihood Estimation
MMI	Maximum Mutual Information
DP	Dynamic Programming
SegRec	Segmentation by Recognition
SDNN	Space Displacement Neural Network
TDNN	Time Delay Neural Network
RNN	Recurrent Neural Network
INSEG	Input Space Segmentation
OUTSEG	Output Space Segmentation
IRONOFF	IRESTE Online/Offline Isolated Handwritten Word Database
AWS	Isolated Handwritten Word Database collected by Andrew W. Senior
S RTP	Isolated Handwritten Cheque-word Database collected by S RTP
MNIST	Isolated Handwritten Digit Database Modified from NIST database
PDA	Personal Digital Assistant

CHAPTER 1

INTRODUCTION

1.1 Background

One of the most common and natural medium of communication for human beings is through handwritings. Even with the introduction of new technologies, handwriting persists as an effective means of communication and information recording in our daily life.

On the other hand, the computer, which was created in the mid nineteenth century, with the initial intention to help performing complex mathematical calculations, has now emerged as a popular and important tool in most of the corporations and organizations. It has been used extensively to perform repetitive and routine tasks to increase productivity and efficiency of an organization. Although current computer technology has gone so far in terms of processing speed, it still offers an unnatural way of communication between human and computer. We still need to learn a set of input methods to adapt ourselves before we can use the computer efficiently. Therefore, having a computer with the ability to interact with human in a more natural way, such as the ability to recognize our speech and handwritings, might further increase the usage of the computers in the area where current computer technology are not accessible.

Although research in optical character recognition (OCR) has started quite some time, research in unconstrained handwriting recognition has only gain much

attention since the early 80 [Nagy, 2000]. Many of the successfully commercialized of handwriting recognition systems are still limited in application which can be applied to small and specific vocabularies, such as bank cheque reading and postal address interpretation [Augustin, et al, 1998] [Guillevic, et al, 1995] [Knerr, et al, 1997]. Usage in other applications especially those required large lexicons, such as recognizing handwritten notes, are, however, still not available.

1.2 Problems

Figure 1.1 shows various styles of handwriting for the word “*six*”. For word recognition purpose, all the examples shown belong to only one class out of all classes available in our known vocabulary. The examples shown in the figure only unveil very small portion of the handwriting styles for the word “*six*”. By only looking at the variability of each example of this particular class, we shall realize that to design a system that can recognize handwritings is indeed an extremely challenging task. From this example, we also realize the incredible recognition capability that humans have. Albeit its slow processing speed, our brain can still perform real-time handwriting recognition task that even the fastest computer can hardly achieve.




Figure 1.1. Various handwriting styles for the word “*six*”

The problems and difficulties of handwriting recognition task can be generally summarized into five categories:

- Nature of the handwriting signals
- Handwriting styles
- Writer dependency
- Size of vocabulary
- Language

The following subsections elaborate in detail each of the problems mentioned.

1.2.1 Nature of the Handwriting Signals

Depending on the nature of the applications, there are two different types of handwriting signals that can be retrieved from the input sources: offline handwriting signal and online handwriting signals.

Offline handwriting recognition deals with the problem of reading the handwritings at some point in time after they were written. The handwriting is typically captured and digitized from a paper by a scanner or camera. Thus, it is in the form of two-dimensional set of pixels with binary, gray-scale or color value.

On the other hand, an online system uses a graphic tablet to enter the handwriting. The data from the tablet is one-dimensional temporal signals $\{x(t), y(t)\}$, i.e. coordinates sampled at a constant interval in time, t . Information that can be retrieved by the system is the relative position of each point, velocity of the pen along its trajectory, and whether the pen is currently lifted or touching the tablet.

As the online signals record the temporal sequence of handwriting, we can easily transform the online signals into offline signals. However, it is quite difficult, if not impossible, to generate online signals from offline signals. In other words,

online handwriting signals contain more information, and thus, online handwriting recognition is regarded easier to solve in terms of recognition accuracy than its offline counterpart.

Nevertheless, handwriting recognition system for offline and online signals represent different perspective of challenges and applications. As online handwriting recognition is usually applied in direct interface with the user, it often requires real-time recognition response, immediately after the user finished writing a word. Apart from that, it also needs to handle recognition with very large vocabulary. This represents a challenge to the system especially when the recognition engine is built on a less powerful computational platform with stringent memory constraint.

Conversely, offline handwriting recognition systems normally perform the task at the back-end. Although the recognition speed is an important issue, it can be overcome by high-speed computers. Nonetheless, in most offline scenarios, there is no control on the type of writing medium and instrument used. The artifacts of the complex interactions between mediums, instruments and subsequent operations such as scanning and binarization present additional challenges to algorithms for offline handwriting recognition.

1.2.2 Handwriting Styles




Figure 1.2. Different types of handwriting styles. (a) Box discrete characters. (b) Spaced discrete characters. (c) Run-on discretely written characters. (d) Pure cursive handwriting. (e) Unconstraint handwriting.

Handwriting styles vary depending on the constraint applied on applications.

Figure 1.2 displays five main types of handwriting styles:

- **Boxed discrete characters.**
For applications like automatic form processing, normally users are requested to write each isolated capital letter in the pre-printed rectangles. These “boxed discrete characters” do not require character segmentation as the position of each isolated character is known. Handwritten characters can be extracted from the rectangles and can be recognized by a character recognizer.
- **Spaced discrete characters.**
The “spaced discrete characters” are separately written. Each character does not have ink traces to link with its neighboring characters. Only simple character segmentation algorithm is needed to retrieve each isolated character.
- **Run-on discretely written characters.**
For this type of handwriting, each character is written one after another. There may be ink traces that link between neighboring characters due to the writing speed.
- **Pure cursive handwriting.**
This is the handwriting style that is usually being taught in the school. Each character has to be nicely link with its neighboring characters. In the cursive handwriting, diacritic marks such as i-dots and t-bar are written after the main part of the word.
- **Unconstraint handwriting.**
This is the most frequently encountered handwriting style in our daily life. It is a mixture of spaced discrete, run-on discrete and cursive handwriting.

1.2.3 Writer Dependency

Handwriting styles are extremely diverse for individuals, depending on the geographical region, native handwriting and so on. It is much more difficult to design a system to recognize many people's handwritings than that of a single author. There are three levels of difficulties:

- **Mono-scriptor.**
For mono-scriptor system, the handwriting recognition system is trained and tested on the same scriptor. As the handwriting of the same writer is normally similar, the handwriting recognition accuracy is usually higher.
- **Multi-scriptor.**
Another tougher problem is the multi-scriptor system, where the handwriting recognition system has to deal with different person's handwriting. The training and testing data sets are from the same group of scriptors.
- **Omni-scriptor/Scriptor Independent.**
The toughest problem is the omni-scriptor system, where the handwriting recognition system has to deal with handwriting styles that it has never seen during the design or training stage. During design stage, the system is trained with onset of available database from one group of scriptors. However, it will be tested on a fresh database from an entirely different group of scriptors. This posed a great difficulty to the system. This is usually the problem for a real commercial handwriting recognition system.

1.2.4 Vocabulary Size

Table 1-1. Different categories of problems based on size of vocabulary

Category	Vocabulary Size	Applications
Small and specific	<100	Legal Amount Recognition
Limited but dynamic	<1000	Address Recognition
Large	>1000	General Applications

According to [Steinherz et al, 1999], one can classify the nature of the vocabulary or lexicon size into three main categories as shown in Table 1-1. The size of vocabulary has significant influence on the design of a handwriting recognition system. As the size of vocabulary grows, the chances to have more words that are similar increase, thus, more confusion occur. Therefore, as the vocabulary size increased, we would expect performance and speed of a particular recognizer to degrade.

1.2.5 Language

There are many different languages used in this world. Three most widely used handwritten languages are Latin-based languages, e.g. English or French, Chinese language and Arabic language. English alphabet has 52 letters (lower and upper case). French has all English alphabets plus 24 more alphabets with diacritical marks (lower and upper case). In English or French, the position and size of the letters is important. Upper case letters sit on the baseline and are full size. Lower case letters are smaller and most are about half the height of upper case letters. Handwritten English or French words are normally separated spatially. Letters within a word, however, are not usually separated spatially. For letters like “t”, “i”, “j”, etc., when written cursively, crosses (for “t”) and dots (for “i”, “j”, etc) tend to be delayed and thus they are not written exactly above of the main part of the characters.

Chinese has a much larger set of characters (alphabets). A complete vocabulary of Chinese characters is about 50,000. A more basic vocabulary that is sufficient for normal reading purpose is around 3,000 to 5,000 characters [Tappert et al, 1990]. A Chinese character has an average of 8-10 strokes: the simplest having one stroke and the most complicated contains more than 30 strokes. If written cursively, strokes are connected and shapes may deform from the basic style. Japanese language use Hiragana, Katakana, and Kanji. The first two groups are phonetic alphabets, and each has 46 full-size characters. The strokes of these characters are less than the one in Chinese character. Kanji are subset of Chinese characters. It has 6,349 characters as defined by Japanese Industry Standard but

daily usage limited to around 2,000. Chinese and Japanese characters are usually written in block; thus, there is less character segmentation problem.

Arabic alphabet consists of 29 letters. However, due to the dependency of the shape of a character on its position in a word, the number of character shapes increases from 29 to about 60. Arabic is written from right to left. Handwritten Arabic words usually include vertical combinations of characters called ligatures. This feature makes it difficult to determine the boundaries of the characters. [Amin, 1997]

Different languages of handwriting pose different kind of recognition problems. For this thesis, only the English and French language will be looked into detail.

1.3 Applications of Handwriting Recognition

There have been significant growth in the application of handwriting recognition systems in both online and offline domain during the past decade. The most important of these has been in bank cheque processing and handwritten address interpretation, whereas popularity of cellular phones and personal digital assistants (PDAs) lately has contributed to the online handwriting recognition on electronic appliances. The following sections describe the major applications in details.

1.3.1 Bank Cheque Processing




Figure 1.3. Various recognition processes to be performed to automate back cheque processing.

An automated bank cheque processing system is one that uses a computer system to replace the human operator for processing bank cheques automatically in an efficient way. The system is able to recognize the amount of cheques based on the courtesy amount, as well as the legal amount written on them. Apart from that, it is also able to recognize the date written on cheque. An automated bank cheque recognition system reduces laborious and repetitive human data entry, thus increase the productivity and efficiency of a bank.

Figure 1.3 illustrates an example of a cheque. In order to automate the cheque reading, various recognition processes are needed. The most important process is the courtesy amount recognition to recognize the amount of payment. To further verify the amount written, text written on the legal amount field is recognized. Date, signature, serial number and the payee name, are also need to be recognized or verified to make sure that it is a valid cheque.

There are substantial research challenges in the area of document image analysis and recognition for bank cheque processing. Due to the complex backgrounds and stamping noises, extraction of completely clean handwriting for

recognition is impossible. For this, we need to rely on the robustness of the handwriting recognition system to perform recognition with noisy inputs or to reject if it is too noisy. Due to limited vocabulary in legal amount, it has been getting rather promising in the development of commercial cheque-reading systems [Knerr, et al, 1998] [LeCun et al, 1998].

1.3.2 Form Processing

Numerous government agencies or private institutions use forms to collect data from the public. The design of the forms can be as simple as a few check boxes for the user to select the answers, to as complex as accepting unconstrained handwritings for particular questions. Much of this raw data must be stored structurally in the computer to be manipulated to produce useful pieces of information. Manual data entry is currently the bottleneck in the process, and it is exposed to human errors. Replacing human operators in manual data entry with reliable handwriting recognizers can indeed help produce higher and consistent productivity. Although forms must usually be hand printed to keep the writing as legible as possible, for human as well as for machine processing, cursive recognition systems are very much useful in many instances.

1.3.3 Handwritten Address Interpretation

The main objective of interpreting handwritten addresses is to automate the sorting of mail pieces. An address consists of country, state, city, street, primary number (street number or post-office box number), secondary number (apartment or house number) and finally the receiver's name. The interpretation result is represented in the form of a barcode and printed at the bottom of the envelope so that subsequent stages of sorting can be made by a barcode reader.

Handwritten Address Interpretation can be seen as an ideal application for scriptor-independent handwriting recognition, since it has a wide variety of difficulty, from postcode written at predetermined locations on an envelope, up to complete determination of an address without postcode, from discretely written postcode up to unconstrained multiple-lines address written by a foreigner.

1.3.4 Input Method for Electronic Appliances

With a widespread of various electronic handheld devices such as cellular phones, personal digital assistants (PDAs), electronic appliances have inevitably entered into our personal life and household. Current user interface of these electronic appliances are still very crude. The most popular input method used in today's computing environment – keyboard, is not suitable as a convenient user input method due to its size and cost of manufacturing. Handwriting input methods, such as the Graffiti[®] on PDA powered by PalmOS[®], only use uni-strokes handwritten character recognition. Pocket PCs that come with its default Transcriber cursive handwriting recognition software, is still yet to meet the normal user requirement. Thus, large vocabulary online handwriting recognition system is very much in demand in order to provide better user experience with the electronic appliances.

1.4 Scope and Objectives

The main objective of this thesis is to construct a system that is able to recognize isolated cursive handwritten English and French words. Although offline handwriting recognition is used through out the thesis, the classification model can also be applied to the online handwriting recognition.

This thesis describes a Segmentation-by-Recognition (SegRec) approach in handling handwriting recognition. As will be mentioned in the later chapters, that it is quite difficult, if not impossible, to develop an intelligent character segmentation process without the knowledge of characters. Therefore, our approach employs a simple segmentation process to segment a word into a left to right sequence of sub-characters, and then propose various hypotheses of merge sub-characters into characters. The main purpose of the segmentation process here is to preserve as much handwriting information as possible at this level. The recognition process then

try to spot the most probable segmentation based on the recognition results of each of the character hypothesis.

For SegRec approach, apart from performing classification between each character class, the recognizer also needs to model the character hypotheses that do not belong to any character class, which we term it as *junk*. A detailed experimental analysis in handling the junk problem will be described in this thesis.

Two fundamental training schemes for the hybrid ANN/HMM are presented in this thesis. First is the character-level discriminant training that optimizes the ANN at the character level and further optimizes the HMM at the word level. A method is introduced to carefully select junk examples from the training database to train the ANN explicitly. Another scheme is called word-level discriminant training where the ANN is optimized at the word-level using the stochastic gradient-descent (back-propagation) algorithm.

1.5 Thesis Layout

The thesis is divided into six chapters:

- **Chapter 1** describes some background information, the challenges and applications of the handwriting recognition as well as the objectives and contents of the thesis.
- **Chapter 2** provides literature review on handwriting recognition and summarizes the achievements of other works in the field of handwriting recognition. An introduction of the statistical pattern recognition system, which is the basis of this thesis, is also presented.
- **Chapter 3** describes in details the offline handwritten cursive word recognition system that has been designed. This chapter is separated into

four main parts, i.e. image preprocessing, segmentation, feature extraction and recognition, which corresponds to different processing stages in the handwriting recognition system. The last part of the chapter discusses the combination of ANN and HMM to perform the recognition.

- **Chapter 4** explains the training of the hybrid ANN/HMM recognition system. Two approaches, namely Character-level Discriminant Training and Word-level Discriminant Training are presented. Both approaches use popular gradient descent algorithm to optimize the parameters in the system.
- **Chapter 5** presents the experiments carried out to evaluate the performance of the system based on different training approaches and configurations. Detailed Error Analysis on the wrongly recognized examples is also presented.
- **Chapter 6** concludes about the handwriting recognition system and summarizes what has been achieved in this research. Further works that could be carried on from this thesis is also suggested.

between training and test recognition rate, we believe that the performance of the recognizer can be further improved when more training examples are available.

One interesting experiment that combines recognition results of an offline recognizer with an online recognizer can yield remarkable improvement on the recognition performance. This indicates that the feature extraction process of both systems is incomplete and tend to complement to each other. Further research should be done to understand those missing features that can help produce better recognition performance. This interesting finding shall be a motivating factor to the online handwriting recognition research community.

The handwritten word recognition system implemented in this thesis can be extended to recognize a phrase or sentence with minimum modifications. The only extra duty that the sentence recognizer needs to perform is to model the 'white space' between words. Although computational speed is an issue in this implementation as a sentence recognizer, trie structure or more compact data structure like Directed Acyclic Word Graph (DAWG) [Lifchitz et al, 2000] can be implemented to replace current linear structure. Of course, the sentence recognizer extended from this word recognition system is only a basic one. Further works in the area of Natural Language Processing (NLP) should be carried out for improvement on this sentence recognizer.

BIBLIOGRAPHY

- Amin, A (1997). "Offline Arabic Character Recognition: A Survey". International Conference on Document Analysis and Recognition, vol. 2, pp. 596-599.
- Augustin, E., Baret, O., Price, D. and Knerr, S. (1998). "Legal Amount Recognition on French Bank Checks Using a Neural Network-Hidden Markov Model Hybrid". International Workshop on Frontiers in Handwriting Recognition, pp. 45-54.
- Bahl, L.R., Brown, P.F., Souze, P.V.de, and Mercer, R.L. (1992). "Maximum Mutual Information Estimation of Hidden Markov Model Parameters for Speech Recognition". International Conference on Acoustic, Speech and Signal Processing, pp. 49-52.
- Bengio, Y., Mori, R.De, Flammia, G., Kompe, R. (1992). "Global Optimization of a Neural Network-Hidden Markov Model Hybrid", IEEE Transactions on Neural Networks, vol. 3, pp. 252-258.
- Bengio, Y., and LeCun, Y. (1994a). "Word Level Training of a Handwritten Word Recognizer Based on Convolutional Neural Networks". International Conference on Pattern Recognition, pp. 88-92.
- Bengio, Y., and LeCun, Y. (1994b). "Word Normalization for On-Line Handwritten Word Recognition". International Conference on Pattern Recognition, Jurusalem, vol. 2, pp. 409-413.

- Bengio, Y., LeCun, Y., and Henderson, D. (1994c). "Globally Trained Handwritten Word Recognizer Using Spatial Representation, Space Displacement Neural Networks and Hidden Markov Models". In *Advances in Neural Information Processing Systems 6*, San Mateo CA, pp. 937-944.
- Bengio, Y., and LeCun, Y. (1995a), "LeRec: A NN/HMM Hybrid for On-Line Handwriting Recognition". *Neural Computing*, vol. 7, no. 5.
- Bengio, Y. and Frasconi, P. (1995b). "Diffusion of Context and Credit Information in Markovian Models". *Journal of AI Research*, 3:249--270, 1995.
- Bengio, Y. and Frasconi, P. (1996a). "Input/Output HMMs for Sequence Processing". *IEEE Transactions on Neural Networks*, vol. 7, no. 5, pp. 1231-1249.
- Bengio, Y. (1996b). "Markovian Models for Sequential Data". Technical Report 1049, Dept. IRO, Université de Montréal.
- Bishop, C.M. (1995). *Neural Networks for Pattern Recognition*. Oxford Univ Press.
- Blumenstein, M., and Verma, B. (2001). "Analysis of Segmentation on the CEDAR Benchmark Database". *International Conference on Document Analysis and Recognition*, pp. 1142-1146.
- Bodenhause, U. , Manke, S. and Waibel, A. (1993). "Connectionist Architectural Learning for High Performance Character and Speech Recognition". *International Conference on Acoustic, Speech and Signal Processing*, vol. 1, pp. 625-628.
- Bourlard, H., and Wellekens, C.J. (1990). "Links between Markov Models and Multilayer Perceptrons". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 12, no 12, pp. 1167-1179.

- Bourlard, H., Konig, Y., and Morgan, N. (1995). "Remap: Recursive Estimation And Maximization Of A Posteriori Probabilities In Connectionist Speech Recognition". Proc. EUROSPEECH '95, Madrid.
- Bourlard, H., and Morgan, N. (1998). "Hybrid HMM/ANN Systems for Speech Recognition: Overview and New Research Directions". In C. L. Giles and M. Gori (Eds.), *Adaptive Processing of Sequences and Data Structures*, Volume 1387 of *Lecture Notes in Artificial Intelligence*, pp. 389-417.
- Bozinovic, R.M., and Srihari, S.N. (1989). "Off-line Cursive Script Word Recognition". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 11, no. 1, pp. 68-83.
- Breuel, T.M. (1994a). "A System for Off-Line Recognition of Handwritten Text". Technical Report #94-02, IDIAP, Switzerland.
- Breuel, T.M. (1994b). "Design and Implementation of a System for the Recognition of Handwritten Responses on US Census Forms". *International Workshop on Document Analysis Systems*, Oct 18-20.
- Bridle, J.S. (1990). "Probabilistic Interpretation of Feedforward Classification Network Outputs, with Relationships to Statistical Pattern Recognition". *Neurocomputing - Algorithms, Architectures and Applications*, vol. 6, pp. 227-236.
- Bunke, H., Roth, M., and Schukat-Talamazzini, E.G. (1995). "Off-line cursive Handwriting Recognition using Hidden Markov Models". *Pattern Recognition*, 28(9):1399-1413.
- Caesar, T., Gloger, J.M. and Mandler, E. (1993a). "Preprocessing and Feature Extraction for a Handwriting Recognition System". *International Conference on Document Analysis and Recognition*, pp. 408-411.

- Caesar, T., Gloger, J.M., and Mandler, E. (1993b). "Design of a System for Off-Line Recognition of Handwritten Word Images". JET POSTE.
- Caesar, T., Gloger, J.M., and Mandler, E. (1995). "Estimating the Baseline for Handwritten Material". International Conference on Document Analysis and Recognition, pp. 382-385.
- Casey, R.G., and Lecolinet, E. (1996). "A Survey of Methods and Strategies in Character Segmentation". IEEE Trans. On Pattern Analysis and Machine Intelligence, vol. 18, no. 17, pp. 690-706.
- Chen, M.Y., and Kundu, A. (1993). "An Alternative to Variable Duration HMM in Handwritten Word Recognition". International Workshop on Frontiers in Handwriting Recognition III, Buffalo.
- Chen, M.Y., Kundu, A., and Zhou, J. (1994). "Off-Line Handwritten Word Recognition Using Hidden Markov Model Type Stochastic Network". IEEE Trans on PAMI, vol. 16, no. 5, pp. 481-496.
- Chen, M.Y., Kundu, A., Srihari, and S.N. (1995). "Variable Duration Hidden Markov Mode and Morphological segmentation for Handwritten Word Recognition". IEEE Trans. Image Processing, vol.4 , no. 12, 1675-1687.
- Chen, W-T., and Gader, P. (2000). "Word Level Discriminative Training for Handwritten Word Recognition". International Workshop on Frontiers in Handwriting Recognition, pp. 393-402.
- Chiang, J-H. (1998). "A Hybrid Neural Network Model in Handwritten Word Recognition". Neural Network, vol. 11, pp. 337-346.
- Cho, W., Lee, S.W., and Kim, J.H. (1995). "Modeling and Recognition of Cursive Words with Hidden Markov Models". Pattern Recognition, vol. 28, no. 12, pp.1941-1953.

- Choisy, C., and Belaid A. (2000). "Analytic Word Recognition Without Segmentation Based on Markov Random Field", IWFHR'VII, Amsterdam, pp 487-492.
- Denker, J.S., and Burges, C.G.J. (1995). "Image Segmentation and Recognition". The Mathematics of Generalization, D. H. Wopert (ed.), Addison-Wesley, pp. 409-436.
- Dietterich, T. G. (2000). "Ensemble methods in machine learning". First International Workshop on Multiple Classifier Systems, pp. 1-15.
- Ding, Y., Kimura, F., Miyake, Y., and Sridhar, M. (2000). "Slant Estimation for Handwritten Words by Directionally Refined Chain Code". International Workshop on Frontiers in Handwriting Recognition, pp. 53-62.
- Duda, R.O., Hart, P.E., and Stork, D.G. (2001). "Pattern Classification". 2nd Edition, John Wiley & son.
- El-Yacoubi, A., Sabourin, R., Suen, C.Y., and Gilloux, M. (1998). "Amélioration de la Modélisation Markovienne dans un Système de Reconnaissance de Mots Manuscrits Hors-ligne". Colloque International Francophone sur l'Ecrit et le Document, Québec, p. 14-23.
- El-Yacoubi, A., Gilloux, M., Sabourin, R., and Suen, C.Y. (1999). "An HMM-Based Approach for Off-Line Unconstrained Handwritten Word Modeling and Recognition". IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 21, no. 8, p. 752-760.
- Farouz, C., Gilloux, M., and Bertille, J-M. (1998). "Handwritten Word Recognition with Contextual Hidden Markov Models". International Workshop on Frontiers in Handwriting Recognition, Taejon, pp. 133-142.

- Flake, G.W. (1998). "Square Unit Augmented, Radially Extended, Multilayer Perceptrons". In *Neural Networks: Tricks of the Trade*, pp. 145-163.
- Fu, K.S. (1982). *Syntactic Pattern Recognition and Applications*. N.J. Prentice-Hall.
- Gader, P., Mohamed, M., and Chiang, J.-H. (1992). "Segmentation-based Handwritten Word Recognition". USPS Advanced Technology Conference, Washington, D.C. pp. 215-226.
- Gader, P., Mohamed, M., and Chiang, J.-H. (1997). "Handwritten Word Recognition with Character and Inter-character Neural Networks". IEEE. *Transactions on System Man and Cybernetics*, 27(1), pp. 158-164.
- Gillies, A.M. (1992). "Cursive Word Recognition Using Hidden Markov Models". USPS Advanced Technology Conference, pp. 557-562.
- Gilloux, M., and Leroux, M. (1993). "Recognition of Cursive Script Amounts on Postal Checks". *Jet Poste*.
- Gilloux, M., Leroux, M., and Bertille, J.-M. (1995a). "Strategies for Cursive Script Recognition Using Hidden Markov Models". *Machine Vision and Application*, pp 197-205.
- Gilloux, M., Lemarié, B., and Leroux, M. (1995b). "A Hybrid Radial Basis Function/Hidden Markov Model Handwritten Word Recognition System". *International Conference on Document Analysis and Recognition*, Montreal, pp. 394-397.
- Gorski, N. (1997). "Optimizing Error-Reject Trade off in Recognition Systems". *Int. Conf. on Document Analysis and Recognition*, Ulm, pp. 1092-1096.
- Guillevic, D. and Suen, C.Y. (1995). "Cursive Script Recognition Applied to the Processing of Bank Cheques". *Proceedings of International Conference on Document Analysis and Recognition*, Montreal, pp. 11-14.

- Guyon, I., Bromley, J., Matic, N., Schenkel, M., and H. Weissman (1995a). "Penacee: A Neural Network System for Recognizing On-line Handwriting". In E. Domany, J. L. van Hemmen, and K. Schulten, editors, *Models of Neural Networks*, volume 3, pages 255-279, Springer.
- Guyon, I., and Warwick, C. (1995b). "Handwriting as Computer Interface". Survey of the State of the Art in Human Language Technology. NSF.
- Guyon, I., Schenkel, M., and Denker, J. (1996). "Overview and Synthesis of On-line Cursive Handwriting Recognition Techniques". In H. Bunke and Wang P.S.P., editors, *Handbook on Optical Character Recognition and Document Image Analysis*. World Scientific Publishing Company.
- Guyon, I., Makhoul, J., Schwartz, R., and Vapnik, V. (1998). "What size test set gives good error rate estimates?". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 20 (1), pp. 52-64.
- Jain, A.K., Duin, R.P.W., and Mao, J. (2000). "Statistical Pattern Recognition: A Review". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 22, no. 1, pp. 4-37.
- Kasyap, R.L., and Oommen, B.J. (1981). "An Effective Algorithm for String Correction using Generalized Edit Distances –I. Description of the algorithm and its Optimality ". *Inf. Science*, 23 (2), pp. 123-142.
- Knerr, S., Anisimov, V., Baret, O., Gorski, N., Price D., and Simon, J.C. (1997). "The A2iA Intercheque System: Courtesy Amount and Legal Amount Recognition for French Checks". *Automatic Bankcheck Processing*, pp. 43-86.

- Knerr, S., and Augustin, E. (1998a). "A Neural Network-Hidden Markov Model Hybrid for Cursive Word Recognition". International Conference on Pattern Recognition, Brisbane, vol 2, pp. 1518-1520.
- Knerr, S., Augustin, E., Baret, O., and Price, D. (1998b). "Hidden Markov Model Based Word Recognition and Its Application to Legal Amount Reading on French Checks". Computer Vision and Image Understanding, vol. 70, no. 3, pp. 404-419.
- Krogh, A., and Riis, S.K. (1999). "Hidden Neural Networks". Neural Computation, 11, pp. 541- 563.
- Lallican, P.M., and Viard-Gaudin, C. (1998). "Off-line Handwriting Modeling as a Trajectory Tracking Problem". International Workshop on Frontiers in Handwriting Recognition, IWFHR'6, Taejon, Korea, pp. 347-356.
- Lecolinet, E., and Baret, O. (1993). "Cursive Word Recognition: Methods and Strategies". NATO/ASI Series F: Fundamentals in Handwriting Recognition, pp. 235.
- LeCun, Y., Jackel, L.D., Bottou, L., Brunot, A., Cortes, C., Denker, J.S., Drucker, H., Guyon, I., Muller, U.A., Sackinger, E., Simard, P. and Vapnik, V. (1995a). "Comparison of Learning Algorithms for Handwritten Digit Recognition". International Conference on Artificial Neural Networks, Fogelman, F. and Gallinari, P. (Ed.), pp. 53-60.
- LeCun, Y., Botou, L., Jackel, L., Drucker, H., Cortes, C., Denker, J., Guyon, I., Müller, U., Säckinger, E., Simard, P. and Vapnik, V. (1995b). "Learning Algorithms for Classification: A Comparison on Handwritten Digit Recognition". Neural Networks, pp. 261-276.
- LeCun, Y., Bottou, L., Bengio, Y., and Haffner P. (1998a). "Gradient-Based Learning Applied to Document Recognition". Proceedings of IEEE, Vol. 86, No. 11, pp. 2278-2324.

- LeCun, Y., Bottou, L., Orr, G.B. and Muller, K.-R. (1998b). "Efficient Backprop". *Neural Networks -Tricks of the Trade*, Springer Lecture Notes in Computer Sciences 1524, pp. 5-50.
- Leroux, M., Salome, J.C., and Badard, J. (1991). "Recognition of Cursive Script Words in a Small Lexicon". *International Conference on Document Analysis and Recognition*, Saint Malo, pp. 774-782.
- Lifchitz, A., and Maire, F. (2000). "A Fast Lexically Constraint Viterbi Algorithm for On-line Handwriting Recognition". *International Workshop on Frontiers in Handwriting Recognition*, Amsterdam, pp. 313-322.
- Lindgren, N. (1965) "Cursive Script Recognition". *IEEE Spectrum*, pp. 104-116.
- Lippmann, R.P. (1987). "An Introduction to Computing with Neural Net". *International Conference on Acoustic, Speech and Signal Processing*, pp. 4-22.
- Lippmann, R.P. (1993). "Neural Networks, Bayesian a posteriori Probabilities, and Pattern Classification". *NATO ASI*, pp. 82-104.
- Lorette, G. (1998). "Handwriting Recognition or Reading? What is the situation at the dawn of the 3rd millennium". *International Workshop Frontiers in Handwriting Recognition*, pp. 1-13.
- Madhvanath, S., and Govindaraju, V. (2000). "The Role of Holistic Paradigms in Handwritten Word Recognition". *IEEE Transactions on PAMI*, Vol.23, No. 2, pp. 149-164.
- Malaviya, A., and Klette, R. (1996). "A Fuzzy Syntactic Method for On-line Handwriting Recognition". *Advances in Structural and Syntactical Pattern Recognition*, pp. 381-392.

- Manke, S. and Bodenhausen, U. (1994). "A Connectionist Recognizer for On-Line Cursive Handwriting Recognition". International Conference on Acoustics, Speech, and Signal Processing, vol. 2, pp. 633-636.
- Manke, S., Finke, M., and Waibel, A. (1995). "NPen++: A Writer Independent, Large Vocabulary On-line Cursive Handwriting Recognition System". Proceedings of the International Conference on Document Analysis and Recognition, Montreal, pp. 403-408.
- Manke, S., Finke, M., and Waibel, A. (1996). "A Fast Search Technique for Large Vocabulary On-line Handwriting Recognition". In International Workshop on Frontiers in Handwriting Recognition, Colchester, England.
- Marmelstein, P., and Eden, M. (1964). "A System for Automatic Recognition of Handwritten Word". Proc. FJCC (AFIPS), pp. 333-342.
- Marti, U., Kaufmann, G. and Bunke, H. (1997). "Cursive Script Recognition with Time Delay Neural Network using Learning Hints". In W. Gerstner, A. Germond, M. Hasler and J.-D. Nicoud, editors, Artificial Neural Networks - ICANN'97, pp. 973-979, Springer Verlag.
- Marti, U. and Bunke, H. (1998). "Towards General Cursive Script Recognition". In Proceedings IWFHR, Sixth International Workshop on Frontiers in Handwriting Recognition, pp. 379-388.
- Matan, O., Burges, C.J.C., LeCun, Y. and Denker, J.S. (1992). "Multi-digit Recognition Using a Space Displacement Neural Network". Proc. Neural Information Processing Systems Conference, pp. 488-495.
- Miller, D., Rao, A.V., Rose, K. and Gersho, A. (1996). "Global Optimization Technique for Statistical Classifier Design". IEEE Trans. on Signal Processing, vol. 44, pp. 3108-3122.

- Nagy, G. (2000). "Twenty Years of Document Image Analysis in PAMI". IEEE Trans. On PAMI, vol. 22, no. 1, pp. 38-61.
- Neukirchen, C., and Rigoll, G. (1997). "Advanced Training Methods and New Network Topologies for Hybrid MMI-Connectionist/HMM Speech Recognition Systems". International Conference on Acoustic, Speech and Signal Processing, pp. 3257-3260.
- Odell, J.J. (1995). "The Use of Context in Large Vocabulary Speech Recognition". Ph.D. thesis, University of Cambridge, England.
- Olivier, C., Paquet, T., Avila, M., and Lecourtier, Y. (1995). "Recognition of Handwritten Words Using Stochastic Models". International Conference on Document Analysis and Recognition, pp. 19-23.
- Otsu, N. (1979), "A Threshold Selection Method from Gray-Level Histograms". IEEE Trans. on Systems, Man and Cybernetics, vol. 9, no. 1, pp. 62-66.
- Parizeau, M., and Plamondon, R. (1995). "A Fuzzy Syntactical Approach to Allograph Modelling for Cursive Script Recognition". IEEE Transactions on PAMI, vol. 17, no. 7, pp. 702-712.
- Park, H-S, and Lee, S-W (1998). "A Truly 2-D Hidden Markov Model for Off-line Hand-written Character Recognition". Pattern Recognition, vol. 13, no 12, pp 1849-1864.
- Plamondon, R., and Srihari, S.N. (2000). "On-Line and Off-line Handwriting Recognition: A Comprehensive Survey". IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 22, no. 1, pp. 63-84.
- Procter, S., and Illingworth, J. (1998a). "Combining HMM Classifiers in a Handwritten Text Recognition System". International Conference on Image Processing, vol. 2, pp. 934-938.

- Procter, S., Elms, A.J., and Illingworth, J. (1998b). "A Method for Connected Hand-printed Numeral Recognition Hidden Markov Models". European Workshop on Handwriting Analysis and Recognition, pp. 11/1-11/6.
- Procter, S., Illingworth, J., and Elms, A.J. (1998c). "The Recognition of Handwritten Digit Strings of Unknown Length using Hidden Markov Models". ICPR, vol 2, pp. 1515-1517.
- Procter, S., Illingworth, J. (2000). "Cursive Handwriting Recognition using Hidden Markov Models and a Lexicon-driven Level Building Algorithm". IEEE Proc. On Vision, Image and Signal Processing, vol. 147, pp. 332-339.
- Rabiner, L.R., and Juang, B.H. (1986). "An Introduction to Hidden Markov Models". IEEE ASSP Magazine, pp. 4-16.
- Rabiner, L.R. (1989). "A Tutorial on Hidden Markov Models and Selected Applications in Speech Recognition". Proceedings of the IEEE, vol. 77, pp. 257-285.
- Renals, S., Morgan, N., Boulard, H., Cohen, M., and Franco H. (1994). "Connectionist Probability Estimators in HMM Speech Recognition". IEEE Transactions on Speech and Audio Processing 2(1), pp. 161-174.
- Richard M., and Lippmann, R. (1991). "Neural Network Classifiers Estimate Bayesian a Posteriori Probabilities". Neural Computation, 3:461-483.
- Rigoll, G. (1998). "Hybrid Speech Recognition Systems: A Real Alternative to Traditional Approaches?". International Workshop Speech and Computer, St. Petersburg, Russia, pp. 33-42.
- Rigoll, G. and Willett, D. (1998). "A NN/HMM Hybrid for Continuous Speech Recognition with a Discriminant Nonlinear Feature Extraction". Proc. IEEE-ICASSP, Seattle, pp. 9-12.

- Rigoll, G., Kosmala, A., and Willett, D. (1998). "A New Hybrid Approach to Large Vocabulary Cursive Handwriting Recognition". In International Conference on Pattern Recognition (ICPR), pages 1512-1514.
- Rigoll, G., Neukirchen, C., and Rottland, J. (1996). "A New Hybrid System Based on MMI-Neural Networks for the RM Speech Recognition Task". Proc. IEEE-ICASSP, pp. 865-868.
- Riis, S.K., and Krogh, A. (1997). "Hidden Neural Networks: A Framework for HMM/NN Hybrids". International Conference on Acoustics, Speech, and Signal Processing, vol. 4, pp. 3233-3236.
- Riis, S.K. (1998a). "Hidden Markov Models and Neural Networks for Speech Recognition". PhD Thesis.
- Riis, S.K. (1998b). "Hidden Neural Networks: Application to Speech Recognition". International Conference on Acoustics, Speech, and Signal Processing, vol. 2, pp. 1117-1120.
- Ris, C., Hennebert, J., Boulard, H., Renals, S., and Morgan, N. (1997). "Estimation of Global Posteriors and Forward-Backward Training of Hybrid HMM/ANN Systems". EuroSpeech, pp. 1951-1954.
- Rumelhart, D.E. (1992). "Theory to Practice; A Case Study – Recognizing Cursive Handwriting". In Third NEC Symposium Computational Learning and Cognition, Princeton, New Jersey.
- Saon, G, and Belaid, A. (1997a). "High Performance Unconstrained Word Recognition System Combining HMMs and Markov Random Fields". Automatic Bankcheck Processing, World Scientific Publication, Singapore, pp. 309-326.

- Saon, G, and Belaid, A (1997b). "Off-line Handwritten Word Recognition Using HMM-MRF Approach". International Conference on Document Analysis and Recognition, pp. 118-122.
- Schenkel, M., Weissman, H., Guyon, I., Nohl, C., and Henderson, D. (1993). "Recognition-based segmentation of on-line hand-printed words". Advances in Neural Information Processing Systems, pp. 723-730.
- Schenkel, M., Guyon, I., and Henderson, D. (1995). "On-line Cursive Script Recognition using Time Delay Neural Networks and Hidden Markov Models". Machine Vision and Applications, pp. 215-223.
- Schomaker, L., and Segers, E. (1999). "Finding Features used in the Human Reading of Cursive Handwriting". International Journal on Document Analysis and Recognition, vol. 2, pp. 13-18.
- Schuster, M. (1999). "On Supervised Learning from Sequential Data with Applications for Speech Recognition". PhD Thesis, Nara Institute of Science and Technology.
- Seiler, R., Schenkel, M. and Eggimann, F. (1996). "Off-Line Cursive Handwriting Recognition Compared with On-Line Recognition". International Conference on Pattern Recognition, vol. 4, pp. 505-509.
- Senior, A.W. (1994). "Off-line Cursive Handwriting Recognition using Recurrent Neural Networks". Ph.D. Thesis, Department of Engineering, University of Cambridge.
- Senior, A.W., and Robinson, T. (1996). "ForwardBackward Retraining of Recurrent Neural Networks", in Advances in Neural Information Processing Systems 8, MIT Press, pp. 743-749.

- Senior, A.W., and Robinson, A.J. (1998). "An Off-line Handwriting Recognition System". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, Vol. 20, No. 3, p. 309-321.
- Slavík, P., and Govindaraju, V. (2001). "Equivalence of Different Methods for Slant and Skew Corrections in Word Recognition Applications". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol 23, no. 3, pp. 323-326.
- Steinherz, T., Rivlin, E., and Intrator, N. (1999). "Off-Line Cursive Script Word Recognition - A Survey". *International Journal of Document Analysis and Recognition*, pp. 153-156.
- Tappert, C.C., Suen, C.Y., and Wakahara, T. (1990). "The State of the Art in On-Line Handwriting Recognition". *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 12, no.8, pp. 787-808.
- Tay, Y.H., Khalid, M., Knerr, S., Lallican, P.M., and Viard-Gaudin, C. (1999a). "An Off-line Cursive Hand-written Cheque-Word Recognition". *Malaysia Science and Technology Congress*.
- Tay, Y.H., Khalid, M., Knerr, S., Lallican, P.M., and Viard-Gaudin, C. (1999b). "Two-cost Stroke Segment Grouping Mechanism for Off-line Hand-written Check-Word Recognition". *Artificial Intelligence in Automation Industry*.
- Tay, Y.H., Lallican, P.M., Khalid, M., Viard-Gaudin, C., Knerr, S. (2001a). "Offline Handwritten Word Recognition Using A Hybrid Neural Network and Hidden Markov Model". *International Symposium on Signal Processing and its Applications*, vol. 2, pp. 382-385.
- Tay, Y.H., Lallican, P.M., Khalid, M., Viard-Gaudin, C. and Knerr, S. (2001b). "An Offline Cursive Handwritten Word Recognition System". *IEEE Region 10 Conference*.

- Tay, Y.H., Lallican, P.M., Khalid, M., Viard-Gaudin, C., and Knerr, S. (2001c). "An Analytical Handwritten Word Recognition System with Word-level Discriminant Training". International Conference of Document Analysis and Recognition, Seattle, 10-13 September 2001, pp. 726-730.
- Trier, O.D., and Jain, A.K. (1995a). "Goal-Directed Evaluation of Binarization Methods". IEEE Trans. on Pattern Analysis and Machine Intelligence, vol. 17, No 12, pp. 1191-1201.
- Trier, O.D., and Taxt, T. (1995b). "Evaluation of Binarization Methods for Document Images". IEEE Trans. on Pattern Analysis and Machine Intelligence, vol. 17, No 3, pp. 312-315.
- Tumer, K., and Ghosh, J. (1995), "Classifier Combining: Analytical Results and Implications", AAAI 96 - Workshop in Induction of Multiple Learning Models.
- Viard-Gaudin, C., Lallican, P.M., Knerr, S., and Binter, P. (1999). "The IRESTE On/Off (IRONOFF) Dual Handwriting Database". International Conference on Document Analysis and Recognition, pp. 455-458.
- Vinciarelli, A. and Luetttin, J. (1999). "Off-Line Cursive Script Recognition Based on Continuous Density HMM". IDIAP Research Report IDIAP-RR 99-25.
- Vinciarelli, A. (2000). "A Survey On Off-Line Cursive Script Recognition". IDIAP Research Report IDIAP-RR 00-43.
- Weibel, A., Hanazawa, T., Hinton, G., Shikano, K., and Lang, K. (1989). "Phoneme Recognition Using TimeDelay Neural Networks". IEEE Transactions on Acoustic, Speech and Signal Processing, Vol. 37, No. 3, pp. 328-339.

Weissman, H., Schenkel, M., Guyon, I., Nohl, C., and Henderson, D. (1994).
“Recognition-based Segmentation of Off-line Run-on Handprinted
Words: Input vs. output segmentation”. *Pattern Recognition*, 27 (3).