

ENHANCEMENT OF THE MACHINING SURFACE ROUGHNESS MODEL
WITH CUCKOO ALGORITHM

AZIZAH BINTI MOHAMAD

UNIVERSITI TEKNOLOGI MALAYSIA

ENHANCEMENT OF THE MACHINING SURFACE ROUGHNESS MODEL
WITH CUCKOO ALGORITHM

AZIZAH BINTI MOHAMAD

A thesis is submitted in fulfillment of the
requirements for the award of the degree of
Master of Science (Computer Science)

Faculty of Computing
Universiti Teknologi Malaysia

JUNE 2014

“This thesis is special dedicated to my lovely parents, Encik Mohamad bin Abu Bakar and Puan Karimah bt Awang, my lovely siblings Zanariah bt Mohamad and Liza bt Mohamad, my lovely nieces and nephews Fatin Munirah Najwa, Afiq Iskandar, Arif Shaifuddin, Adam Haikal and Fatin Nur Khalisha, and my dearly loved Mohamad Faizal bin Abdullah for their endless love, support and courage”

ACKNOWLEDGEMENTS

All praise to Allah, the Almighty, most Gracious and most Merciful. I would like to express a heartfelt gratitude to my supervisors, Dr. Azlan Mohd Zain, Dr. Nor Erne Nazira Bazin and Dr. Amirmudin bin Udin for their guidance, generous support, endless advice and enormous patience throughout my research work.

I would like to acknowledge with much appreciation to my family for giving me morale support and encouragement in completing my research. My sincere appreciation goes to Ministry of Higher Education and Universiti Teknologi Malaysia especially Zamalah Scholarship for providing me financial support during the period of my research work. I would also like to express my gratitude to all lab members of Soft Computing Research Group especially for Anis, Yana, Farah and Farhana in the Faculty of Computing for their help and support.

ABSTRACT

Quality of machining products is generally associated with the surface roughness (R_a) which is one of the important aspects that could affect machining performances. This study seeks to find the minimum value of R_a for a modern machining process, Abrasive Water Jet (AWJ). This study proposed Cuckoo algorithm to improve the surface roughness of the AWJ process because, since 2013, there has only been one study on the algorithm. R_a model in AWJ has five machining parameters comprising traverse speed (V), water jet pressure (P), standoff distance (h), abrasive grit size (D) and abrasive flow rate (m). These parameters in the R_a model have contributed to the best solution for machining performance by achieving the minimum values. In this study, to obtain better results, the parameters in the standard R_a model were enhanced in the modeling process where the number of parameters has been reduced. The enhanced parameters in the model are represented by “ Q ”. Computational techniques were used to evaluate the model whereas SPSS were used to validate the results. The result shows that minimum R_a value of the proposed model is 2.1709 μm . It was much lower than the results of three computational techniques which are Artificial Neural Network (ANN), Regression analysis and Support Vector Machine (SVM) by about 29.2 %, 23.8 % and 19.3% respectively.

ABSTRAK

Kualiti pemesinan biasanya dikaitkan dengan kekasaran permukaan (R_a), dan ia adalah salah satu daripada aspek penting yang mempengaruhi prestasi pemesinan. Kajian ini bertujuan untuk mencari nilai minimum R_a bagi proses pemesinan moden, pelepas jet air (AWJ). Kajian ini mencadangkan algoritma Cuckoo untuk meningkatkan kekasaran permukaan proses AWJ kerana, sejak 2013, hanya terdapat satu kajian ke atas algoritma Cuckoo. Model R_a dalam AWJ mempunyai lima parameter pemesinan yang terdiri daripada *traverse speed* (V), *water jet pressure* (P), *standoff distance* (h), *abrasive grit size* (D) dan *abrasive flow rate* (m). Parameter dalam model R_a ini menyumbang kepada penyelesaian yang terbaik untuk prestasi pemesinan dengan mencapai nilai minimum. Dalam kajian ini, untuk memberikan hasil ketetapan model yang lebih baik, parameter dalam model R_a yang piawai diubahsuai dalam proses pemodelan yang mana bilangan parameter tersebut telah dikurangkan. Parameter yang diubahsuai dalam model diwakili oleh ' Q '. Teknik-teknik pengiraan digunakan untuk menilai model manakala SPSS digunakan untuk mengesahkan keputusan. Keputusan menunjukkan bahawa nilai minimum R_a model yang dicadangkan ialah 2.1709 μm . Ianya lebih rendah berbanding keputusan tiga teknik pengiraan iaitu ANN, Analisis Regresi dan SVM sebanyak 29.2 %, 23.8 % dan 19.3% .

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xii
	LIST OF ABBREVIATIONS	xiii
	LIST OF SYMBOLS	xv
1	INTRODUCTION	1
	1.0 Introduction	1
	1.1 Background of the study	1
	1.2 Problem Statement	4
	1.3 Aim	5
	1.4 Objectives	5
	1.5 Scopes	6
	1.6 Significance of the research	6
	1.7 Summary	7

2	LITERATURE REVIEW	8
2.0	Introduction	8
2.1	Modeling theory in machining	8
2.2	Surface roughness, R_a	10
2.3	Mathematical model development for surface roughness	12
2.4	Abrasive Water Jet (AWJ) machining process	13
2.5	Cuckoo algorithm	14
2.6	Previous studies of surface roughness, R_a for modern machining	16
2.7	Previous studies on application of cuckoo search in various domain	21
2.8	Summary	32
3	RESEARCH METHODOLOGY	33
3.0	Introduction	33
3.1	Research flow	33
3.2	Assessment of real experimental data	34
3.3	Implementation of mathematical model	36
3.4	Implementation of standard surface roughness model using cuckoo	36
3.4.1	The step of the implementation of standard surface roughness model using cuckoo	39
3.5	Enhancement of surface roughness model with cuckoo algorithm	39
3.5.1	The step of the proposed model using cuckoo	42
3.6	Validation and evaluation of the results	43
3.7	Summary	43

4	STANDARD AND PROPOSED ENHANCED SURFACE ROUGHNESS MODEL USING CUCKOO ALGORITHM	45
4.0	Introduction	45
4.1	Standard model of surface roughness	45
4.2	Enhancing model of surface roughness	46
4.3	Best enhancement of surface roughness model	49
4.4	Summary	53
5	RESULTS VALIDATION AND EVALUATION	54
5.0	Introduction	54
5.1	Analysis of results	54
5.2	Validation of AWJ results	55
5.3	Evaluation of AWJ results	61
5.4	Summary	61
6	CONCLUSION	62
6.0	Introduction	62
6.1	Research Findings	62
6.2	Research Contribution	64
6.3	Recommendations for Future Work	64
6.4	Summary	65
	REFERENCES	66
	APPENDIX	72

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Previous studies of surface roughness, R_a for modern machining	18
2.2	Previous studies on application of cuckoo search in various domains	24
2.3	Experimental R_a values for AWJ (Caydas and Hascalik, 2008)	31
3.1	Chemical composition of Al 7075 alloy	35
3.2	Level process parameters and coding implementation	35
4.1	Experimental, Mathematical, Standard R_a and Enhanced R_a value	72
4.2	Correlation value for surface roughness model	49
4.3	The results of enhanced surface roughness prediction model for AWJ	50
4.4	Best point in Cuckoo	51
4.5	Error rate between Mathematical model with standard and enhanced surface roughness	52
4.6	Features of best prediction model for AWJ	53

5.1	Features of Standard R_a and proposed models of AWJ	58
5.2	Paired Samples Statistics of AWJ	59
5.3	Paired Samples Test	59
5.4	Summary result of AWJ	61

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Surface roughness profile (Yang and Chen, 2001)	10
2.2	Illustration of R_a in AWJ process (Engin, 2012)	11
2.3	Schematic of an abrasive water jet cutting process (Selvan and Raju, 2011)	14
3.1	Research Flow	34
3.2	A flowchart of the Cuckoo algorithm (Rajabioun, 2011)	38
4.1	Surface roughness values (Caydas and Hascalik, 2008 vs Standard R_a)	46
5.1	Surface roughness values (proposed model vs Caydas and Hascalik, 2008)	56
5.2	Surface roughness values (proposed model vs Standard R_a)	57

LIST OF ABBREVIATIONS

ACO	Ant Colony Optimization
AIS	Artificial Immune System
ANN	Artificial Neural Network
AWJ	Abrasive Water Jet
BBF	Bloom Filter
CBPA	Cuckoo Based Particle Approach
CHM	Chemical Machining
CS	Cuckoo Search
ECM	Electrochemical Machining
ECS	Enhanced Cuckoo Search
EDM	Electric Discharge Machining
ELR	Egg Laying Radius
FL	Fuzzy Logic
GA	Genetic Algorithm
GPMA	Generalized Particle Model Algorithm
GRA	Grey Relational Analysis
HS	Harmony Search
LHS	Latin Hyper-Cube Sampling
PCM	Photochemical Machining
PSCS	Hybrid Power Series And Cuckoo Search
PSO	Particle Swarm Optimization
PSRE	Hybrid Particle Swarm
RMSE	Root Mean Square Deviation
RSM	Response Surface Methodology
SA	Simulated Annealing
SVM	Support Vector Machine

TS

Tabu Search

USM

Ultrasonic Machining

 μ -WEDM

Micro Wire Electric Discharge Machining

LIST OF SYMBOLS

\hat{y}	Logarithmic value of the predictive
\hat{y}	Predicted value
b_0, b_1, b_3, b_4 and b_5	Model parameters to be estimated using the experimental data.
c, q, r, s, t and u	Model parameters to be estimated using the experimental data
d	Abrasive grit size
f_c	Cost
f_p	Profit
h	Standoff distance
L	Sampling length
m	Abrasive flow rate
N	Number of Sample Data
P	Water jet pressure
Q	Goal point
R	Surface Roughness
r	Correlation value
r	Positively correlated
V	Traverse speed
var_{hi}	Upper bound
var_{low}	Lower bound
x	Profile direction
x_0	Dummy variable
x_1, x_2, x_3, x_4 and x_5	Process parameter values (logarithmic transformations)
y	Profile curve

y	The actual i value
α	Integer
ε	Logarithmic transformation

CHAPTER 1

INTRODUCTION

1.0 Introduction

This chapter gives an overview of the research conducted in this study. The topics include background of the study, problem statement, aim, objectives, scopes and significance of the research.

1.1 Background of the study

Nowadays, the manufacturing industries are highly competitive. Manufacture's ultimate goal is to produce high quality products with reduced cost and production time. Machining is a part of the operation for almost all manufactures of metal products. Generally, the machining operations can be classified into two types which are traditional and non-traditional (modern). Traditional machining is the process of removing unwanted segment of metal work piece in the form of chips such as turning, drilling and milling. Modern machining or non-traditional machining uses technology such as abrasive water jet (AWJ), ultrasonic machining (USM), chemical machining (CHM), electrochemical machining (ECM) and photochemical machining (PCM).

The selection of machining process parameters is very crucial in order for the machine operations to be successful (Rao and Pawar, 2010a). The success of a machining process also depends on the proper selection of cutting condition based on cost and quality factors. The major issue arise in machining process is how to obtain accurate results of machining performance measurement such as surface roughness. Commonly, the selection of cutting conditions in machining process is left to the machine operator. Moreover, in machining cutting process, the process was done continuously in order to get the target value despite the cutting material can be used only once. Thus, this process will increase cost with a lot of wasted used material used. Machinist experience is important for the machining process and plays a major rule although sometimes it is difficult to maintain the optimum values for each experiment (Aggarwal, 2005).

Recently, machining technology has been improved significantly to meet the requirements of manufacturing in different fields. There are two fields that have been of interest to researches in machining, which are modeling and optimization. According to Zain *et al.* (2011a), modeling in machining refers to the process of estimating the potential minimum or maximum values of machining performance while optimization refers to the process of estimating optimal solution of cutting condition that leads to the minimum or maximum machining values of machining performances. Various techniques were considered and carried out to model and optimize the machining performances. This study only focuses on modeling of machining performance. The primary purpose of the machining modeling is to estimate the minimum values (such as surface roughness, operation time, operation cost etc.) or maximum values (such as material removal rate, tool wear etc.) of machining performance measurements.

Based on previous literature, surface roughness is one of the machining performance measurements mostly studied by researchers (Çaydaş and Ekici, 2012; Salgado *et al.*, 2009; Zain *et al.*, 2010a, 2010b, 2010c). Surface roughness is a measure of the technological quality of a product which greatly influences manufacturing cost. It describes the geometry of the machined surfaces and combined with the surface texture. Surface roughness is also a technological quality

measurement of a product and a factor that considerably affects the manufacturing cost (Caydas and Hascalik, 2008). Surface roughness plays an important role in wear resistance, tensile, ductility and fatigue strength for machine parts (Wang and Chang, 2004). Surface roughness is widely use as an index of product quality and in most cases a technical requirement for mechanical products (Yusup *et al.*, 2012; Benardos *et al.*, 2003). On the other hand, having a desired surface quality is a great importance for the functional behavior of the part. In order to find the desired value of surface roughness, several parameters need to be considered such as cutting tools properties, machining parameters, work piece properties and cutting phenomenon (Zain *et al.*, 2012a, 2012b). Various techniques have been considered by a number of researchers to model and optimize machining problems. This technique includes Artificial Neural Network, ANN (McCulloch and Pitts, 1943), Fuzzy set-theory (Zadeh *et al.*, 1988), Genetic Algorithm, GA (Holland *et al.*, 1970), Particle Swarm Optimization, PSO (Kennedy and Eberhart, 1995) and Ant Colony Optimization, ACO (Dorigo *et al.*, 1997).

Despite various techniques being applied in machining problem, only one machining research dealt with Cuckoo algorithm which was conducted by Yildiz *et al.* (2013) for optimization of machining parameters in end milling process labeled as one of the conventional machining processes. The author concluded that Cuckoo was a very effective and robust approach for the optimization of machining optimization problems. This study deals with modeling of surface roughness for abrasive water jet (AWJ) operation, classified as one of the modern machining processes. The results from this study contribute new knowledge to the machining field.

1.2 Problem Statement

The success of machining process depends on the proper selection of cutting condition based on cost and quality factors. The major issue in machining process is how to estimate and obtain accurate result of process parameters, such as surface roughness values using various machining factors of cutting operations. Conventionally, experimental trial was done repeatedly using different combination of cutting values to estimate the possible minimum value of machining performance. This is fully depended on mechanist experience who conducts the experiment. In such cases, machinist experience plays a major role but sometimes it is difficult to maintain the optimum values for each experiment (Aggawal and Singh, 2005).

With the help of computational approaches in estimating machining performances, minimum machinist expertise is required and the machining cost can be reduced. Hence, this study introduces the Cuckoo algorithm in producing and estimating minimum surface roughness value of machining process. In recent years, Cuckoo Search which is a combination with Levy Flight has become a new trend in current research especially in optimization of machining parameters. Cuckoo Search is capable to solve the problems of various fields such as engineering design (Yang and Deb *et al.*, 2010; Walton *et al.*, 2011; Noghrehabadi *et al.*, 2011; Kaveh *et al.*, 2011), software testing and data generation (Bacanin *et al.*, 2012; Kavita *et al.*, 2011; Perumal *et al.*, 2011) and pattern recognition problems (Vazquez *et al.*, 2011; Rani *et al.*, 2011; Ehsan *et al.*, 2011).

However, in some cases, the data in machining model may contain irrelevance and redundant features that is used as input features in development of surface roughness model using Cuckoo algorithm. This irrelevance and redundant data need to be eliminated from the input features in order to get a better prediction model. Standard surface roughness model approach does not have the ability to recognize this irrelevant element. So, there is a need for the model that is able to remove the unwanted data in order to improve the model performance. As a result, this study promotes the enhanced surface roughness mainly an extension of the idea

by Wang *et al.* (2007) where the current problem on the standard equation was reduced to produce a better result in modeling process.

In relation to the machining problem discussed above, three research question of this study are:

- i. How to estimate potential values of the machining process parameters to get possible values of minimum surface roughness?
- ii. How to modify the existing standard model in order to give better results of surface roughness?
- iii. How to identify the effectiveness of proposed enhancement model?

1.3 Aim

The aim of the study is to enhance the surface roughness model with Cuckoo algorithm to find the best minimum value of surface roughness, R_a for AWJ machining process.

1.4 Objectives

The objectives of the study are:

- i. To implement standard surface roughness model with Cuckoo algorithm in estimating the minimum value surface roughness of AWJ.
- ii. To enhance surface roughness model with Cuckoo algorithm for estimating the minimum surface roughness value of AWJ process.
- iii. To validate and evaluate the performance of the proposed enhancement model in estimating minimum surface roughness value.

1.5 Scopes

The scopes of the study are:

- i. Focus on abrasive water jet, AWJ classified as one of the modern machining processes.
- ii. Surface roughness, R_a is machining performance considered for AWJ process.
- iii. Five AWJ's process parameters such as traverse speed V , water jet pressure P , standoff distance h , abrasive grit size d and abrasive flow rate m will be considered.
- iv. Experimental data of AWJ are based on the experiment conducted by Caydas and Hascalik (2008).

1.6 Significance of the research

This study is to analyze the performance of proposed enhancement of surface roughness model for AWJ process with Cuckoo algorithm in prediction of machining surface roughness value. To indicate the effectiveness of the proposed enhancement model, the final results are compared with the experimental data (Caydas and Hascalik, 2008), SVM (Deris *et al.*, 2013), ANN (Caydas and Hascalik, 2008) and Regression (Caydas and Hascalik, 2008) in order to view the effectiveness of the proposed enhancement model in estimating the value of surface roughness, R_a . The proposed enhancement model is considered as a new research project in machining for estimating the machining surface roughness model.

1.7 Summary

This chapter discussed several topics related to the idea of research implementation. Background of the study, problem statement, aim, objectives, scopes and significance of the research were described in this chapter.

REFERENCES

- Aggarwal, A., and Singh, H. (2005). Optimization of machining techniques-a retrospective and literature review. *Sadhana*, 30(6), 699-711.
- Al-Zubaidi, S., Ghani, J. A., and Haron, C. H. C. (2013). Optimization of cutting conditions for end milling of Ti6Al4V Alloy by using a Gravitational Search Algorithm (GSA). *Meccanica*, 1-15.
- Bacanin, N. (2011). An object-oriented software implementation of a novel cuckoo search algorithm. *In Proc. of the 5th European Conference on European Computing Conference (ECC'11)* (pp. 245-250).
- Bacanin, N. (2012). Implementation and performance of an object-oriented software system for cuckoo search algorithm. *International Journal of Mathematics and Computers in Simulation*, 6(1), 185-193.
- Benardos, P. G., and Vosniakos, G. C. (2003) "Predicting surface roughness in machining: a review," *International Journal of Machine Tools and Manufacture*, 43(8), 833-844.
- Burnwal, S., and Deb, S. (2012). Scheduling optimization of flexible manufacturing system using cuckoo search-based approach. *The International Journal of Advanced Manufacturing Technology*, 1-9.
- Çaydaş, U., and Ekici, S. (2012) "Support vector machines models for surface roughness prediction in CNC turning of AISI 304 austenitic stainless steel," *Journal of Intelligent Manufacturing*, 23(3), 639-650.
- Çaydaş, U., and Hasçalık, A. (2008). A study on surface roughness in abrasive waterjet machining process using artificial neural networks and regression analysis method. *Journal of Materials Processing Technology*, 202(1), 574-582.
- Chandrasekaran, M., Muralidhar, M., Krishna, C. M., and Dixit, U. S. (2010). Application of soft computing techniques in machining performance

- prediction and optimization: a literature review. *The International Journal of Advanced Manufacturing Technology*, 46(5-8), 445-464.
- Chifu, V., Pop, C., Salomie, I., Suia, D., and Niculici, A. (2012). Optimizing the Semantic Web Service Composition Process Using Cuckoo Search. *Intelligent Distributed Computing V*, 93-102.
- Deris, A. M., Zain, A. M., and Sallehuddin, R. (2013). Hybrid GR-SVM for prediction of surface roughness in abrasive water jet machining. *Meccanica*, 1-9, 10.1007/s11012-013-9710-2.
- Dhivya, M., Sundarambal, M., and Anand, L. N. (2011a). Energy efficient computation of data fusion in wireless sensor networks using cuckoo based particle approach (CBPA). *Int. J. of Communications, Network and System Sciences*, 4(4), 249-255.
- Dhivya, M., Sundarambal, M., and Vincent, J. (2011b). Energy Efficient Cluster Formation in Wireless Sensor Networks Using Cuckoo Search. *Swarm, Evolutionary, and Memetic Computing*, 140-147.
- Dorigo, M., and Blum, C. (2005). Ant colony optimization theory: A survey. *Theoretical computer science*, 344(2), 243-278.
- Ehsan Valian, S. M. a. S. T. (2011). Improved Cuckoo Search Algorithm for Global Optimization. *International Journal of Communications and Information Technology, IJCIT 1*.
- Engin, I. C. (2012). A correlation for predicting the abrasive water jet cutting depth for natural stones. *South African Journal of Science*, 108(9-10), 1-11.
- Farshidianfar, A., Saghafi, A., Kalami, S. M., and Saghafi, I. (2012). Active vibration isolation of machinery and sensitive equipment using H_{∞} control criterion and particle swarm optimization method. *Meccanica*, 47(2), 437-453.
- <http://www.econ.iastate.edu/tesfatsi/holland.GAIntro.htm> [Accessed March 14, 2005].
- Jawahir, I.S., Balaji, A.K., Rouch, K.E. and Baker, J.R. (2003). Towards integration of hybrid models for optimized machining performance in intelligent manufacturing systems. *Journal of Material Processing Technology*. 139, 488-498.
- Kanagarajan, D., Karthikeyan, R., Palanikumar, K., and Davim, J. P. (2008). Optimization of electrical discharge machining characteristics of WC/Co composites using non-dominated sorting genetic algorithm (NSGA-II). *The*

International Journal of Advanced Manufacturing Technology, 36(11-12), 1124-1132.

- Kaveh, A., and Bakhshpoori, T. (2011). Optimum design of steel frames using Cuckoo Search algorithm with Lévy flights. *The Structural Design of Tall and Special Buildings*.
- Kavita C, G. N. P. (2011). A new Testing approach using Cuckoo Search to achieve Multi-Objective Genetic Algorithm. *Journal of computing* 3(4).
- Kennedy, J. Eberhart, R., (1995). Particle swarm optimization. *Proceedings., IEEE International Conference on*, vol.4, no., pp.1942, 1948 vol.4.
- Kolahan, F. (2010). A Statistical Approach for Predicting and Optimizing Depth of Cut in AWJ Machining for 6063-T6 Al Alloy. *International Journal of Mechanical Systems Science and Engineering*, 2.
- Kumar, A., and Chakarverty, S. (2011). Design optimization for reliable embedded system using Cuckoo Search. In *Electronics Computer Technology (ICECT), 2011 3rd International Conference on* (Vol. 1, pp. 264-268). IEEE.
- Markopoulos, A., Vaxevanidis, N. M., Petropoulos, G., and Manolakos, D. E. (2006,). Artificial Neural Networks Modeling of Surface Finish in Electro-Discharge Machining of Tool Steels. In *Proceedings of ESDA2006: 8th Biennial ASME Conference on Engineering Systems Design and Analysis*.
- McCulloch, W. S., and Pitts, W. (1943). A logical calculus of the ideas immanent in nervous activity. *The bulletin of mathematical biophysics*, 5(4), 115-133.
- Mohamad, A., Zain, A. M., Bazin, N. E. N., and Udin, A. (2013). Cuckoo Search Algorithm for Optimization Problems-A Literature Review. *Applied Mechanics and Materials*, 421, 502-506.
- Nalbant, M., Gökkaya, H., and Sur, G. (2007). Application of Taguchi method in the optimization of cutting parameters for surface roughness in turning. *Materials & design*, 28(4), 1379-1385.
- Natarajan, A., and Subramanian, P. K. (2012a). An Enhanced Cuckoo Search for Optimization of Bloom Filter in Spam Filtering. *Global Journal of Computer Science and Technology*, 12(1).
- Natarajan, A., and Subramanian, S. (2012b). Bloom filter optimization using Cuckoo Search. In *Computer Communication and Informatics (ICCCI), 2012 International Conference on* (pp. 1-5). IEEE.

- Nayak, K. C., Tripathy, R. K., Rani, S., Banakar, P., Shivananda, H. K., Bhosale, M. A., and Shinde, N. N. (2012). Taguchi integrated Least Square Support Vector Machine an alternative to Artificial Neural Network analysis of electrochemical machining process. *IOSR Journal of Mechanical and Civil Engineering (IOSRJMCE) ISSN*, 2278-1684.
- Noghrehabadi, A., Ghalambaz, M., Ghalambaz, M., and Vosough, A. (2011). A hybrid power series–Cuckoo Search optimization algorithm to electrostatic deflection of micro fixed-fixed actuators. *International Journal of Multidisciplinary Sciences and Engineering*, 2(4), 22-26.
- Ozcelik, B., Oktem, H. and Kurtaran, H. (2005). Optimum surface roughness in end milling Inconel 718 by coupling neural network model and genetic algorithm. 236.
- Perumal, K., Ungati, J. M., Kumar, G., Jain, N., Gaurav, R., and Srivastava, P. R. (2011). Test data generation: a hybrid approach using cuckoo and tabu search. In *Swarm, Evolutionary, and Memetic Computing* (pp. 46-54). Springer Berlin Heidelberg.
- Prakash, M., Saranya, R., Jothi, K. R., and Vigneshwaran, A. (2012). An Optimal Job Scheduling in Grid Using Cuckoo Algorithm.
- Raeisi, E., and Ziaei-Rad, S. (2012). The worst response of mistuned bladed disk system using neural network and genetic algorithm. *Meccanica*, 1-13.
- Rajabioun, R. (2011). Cuckoo optimization algorithm. *Applied Soft Computing*, 11(8), 5508-5518.
- Rani, K. A., and Malek, F. (2011a). Symmetric linear antenna array geometry synthesis using cuckoo search metaheuristic algorithm. In *Communications (APCC), 2011 17th Asia-Pacific Conference on* (pp. 374-379). IEEE.
- Rani, K. A., and Malek, F. (2011b). Preliminary study on cuckoo search parameters for symmetric linear array geometry synthesis. In *TENCON 2011-2011 IEEE Region 10 Conference* (pp. 568-572). IEEE.
- Rao, R. V., Pawar, P. J., and Davim, J. P. (2010b). Parameter optimization of ultrasonic machining process using nontraditional optimization algorithms. *Materials and Manufacturing Processes*, 25(10), 1120-1130.
- Rao, R., and Pawar, P. (2010a). Parameter optimization of a multi-pass milling process using non-traditional optimization algorithm. *Applied Soft Computing*, 10, 445-456.

- Sahoo, P., Routara, B. C., and Bandyopadhyay, A. (2009). Roughness modelling and optimisation in EDM using response surface method for different work piece materials. *International Journal of Machining and Machinability of Materials*, 5(2), 321-346.
- Salgado, D. R., Alonso, F. J., Cambero, I., and Marcelo, A. (2009) "In-process surface roughness prediction system using cutting vibrations in turning," *The International Journal of Advanced Manufacturing Technology*, 43(1), 40-51.
- Sardashti, A., Daniali, H. M., and Varedi, S. M. (2013). Optimal free-defect synthesis of four-bar linkage with joint clearance using PSO algorithm. *Meccanica*, 1- 13.
- Selvan, M. C. P., and Raju, D. N. M. S. "Selection of process parameters in abrasive waterjet cutting of copper, "*International Journal of Advanced Engineering Sciences and Technologies*, 7(2), 254-257, 2011.
- Senthilkumar, C., Ganesan, G., and Karthikeyan, R. (2010). Bi-performance optimization of electrochemical machining characteristics of Al/20% SiCp composites using NSGA-II. *Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture*, 224(9), 1399-1407.
- Seo, Y. W., Ramulu, M., and Kim, D. (2003). Machinability of titanium alloy (Ti'6Al'4V) by abrasive waterjets. *Proceedings of the Institution of Mechanical Engineers, Part B: Journal of Engineering Manufacture*, 217(12), 1709-1721.
- Somashekhar, K. P., Ramachandran, N., and Mathew, J. (2009). Modeling and optimization of process parameters in micro Wire EDM by Genetic Algorithm. *Advanced Materials Research*, 76, 566-570.
- Vazquez, R. A. (2011, June). Training spiking neural models using cuckoo search algorithm. In *Evolutionary Computation (CEC), 2011 IEEE Congress on* (pp. 679-686). IEEE.
- Walton, S., Hassan, O., Morgan, K., and Brown, M. R. (2011). Modified cuckoo search: A new gradient free optimisation algorithm. *Chaos, Solitons & Fractals*, 44(9), 710-718.
- Wang, M. Y., and Chang, H. Y. (2004). Experimental study of surface roughness in slot end milling AL2014-T6. *International Journal of Machine Tools and Manufacture*, 44(1), 51-57.

- Wang, Yi-Chi. (2007). "A note on 'optimization of multi-pass turning operations using ant colony system'." *International Journal of Machine Tools and Manufacture*, 47.12: 2057-2059.
- Yang, X. S., and Deb, S. (2009). Cuckoo search via Lévy flights. In *Nature & Biologically Inspired Computing, 2009. NaBIC 2009. World Congress on* (pp. 210-214). IEEE.
- Yang, X. S., and Deb, S. (2010). Engineering optimisation by cuckoo search. *International Journal of Mathematical Modelling and Numerical Optimisation*, 1(4), 330-343.
- Yang, X. S., and Deb, S. (2011). Multiobjective cuckoo search for design optimization. *Computers & Operations Research*.
- Yildiz, A. R. (2013). Cuckoo search algorithm for the selection of optimal machining parameters in milling operations. *The International Journal of Advanced Manufacturing Technology*, 64(1-4), 55-61.
- Zadeh, L. A. (1988). Fuzzy logic. *Computer*, 21(4), 83-93.
- Zain, A. M., Haron, H., and Sharif, S. (2012a). "Integrated ANN-GA for estimating the minimum value for machining performance," *International Journal of Production Research*, 50(1), 191–213.
- Zain, A. M., Haron, H., and Sharif, S. (2010a). Prediction of surface roughness in the end milling machining using Artificial Neural Network. *Expert Systems with Applications*, 37(2), 1755-1768.
- Zain, A. M., Haron, H., and Sharif, S. (2010b). Application of GA to optimize cutting conditions for minimizing surface roughness in end milling machining process. *Expert Systems with Applications*, 37(6), 4650-4659.
- Zain, A. M., Haron, H., and Sharif, S. (2010c). Genetic Algorithm and Simulated Annealing to estimate optimal process parameters of abrasive waterjet machining. *Engineering with Computer*.
- Zain, A. M., Haron, H., and Sharif, S. (2011). Estimation of the minimum machining performance in the abrasive waterjet machining using integrated ANN-SA. *Expert Systems with Applications*, 38(7), 8316-8326.
- Zain, A. M., Haron, H., Qasem, S. N., and Sharif, S. (2012b). "Regression and ANN models for estimating minimum value of machining performance," *Applied Mathematical Modelling*, 36(4), 1477-1492.