

BACKGROUND LOSSES REDUCTION BY EXCESSIVE PRESSURE CUT-OFF

ZAINUDIN BIN NGADIRAN

A thesis submitted in fulfilment of the requirements for the award of the degree of
Master of Engineering (Hydraulics)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

MARCH 2013

Bismillahirrahmanirrahim...

Tesis ini didedikasikan khas untuk insan-insan yang teristimewa:

Untuk isteri tercinta Zaharah Elias, dan
puteri-puteri yang dikasihi, Nur Zuhairah Afrina & Nur Zahirah Amani,

Teristimewa untuk insan yang sentiasa diingati arwah ayah dan ibu,

Penyelia, P.M Ir. Fatimah Mohd Noor,

Jabatan Kawalan NRW, rakan-rakan sepejabat dan keluarga tercinta.
Terima kasih di atas ilmu yang dicurahkan dan sokongan padu di sepanjang
menyempurnakan naskah tesis ini. Semoga insan-insan teristimewa ini dilimpahi
barakah di dalam kehidupan di dunia dan di akhirat kelak, InshaAllah.

ACKNOWLEDGEMENT

First and foremost, I would like to express my deepest appreciation to my supervisor Associate Professor Ir. Fatimah Mohd Noor, who has supported and guide me throughout the period of my research work. Furthermore, my gratitude also goes to my superior, Tn. Hj. Anuar Abd. Ghani, En. Yusof Halos, and En. Rosli Abidin for his invaluable encouragement and knowledge given to me throughout my research. I am very grateful that they had generously shared their knowledge and gave me strength to complete this research.

I also wish to express sincere appreciation to my fellow colleagues, especially members of NRW Control Department, SAJ Holdings Sdn Bhd, and Ranhill Water Services Sdn Bhd for their continuous support and encouragement. My sincere appreciation also extends to my entire dear friends for their kindness, encouragement and support.

Furthermore, I am forever thankful to my parents and family for their understanding, patience and encouragement throughout my life.

ABSTRACT

It is one of the greatest challenges water utilities are facing in striving to reduce and control Non Revenue Water (NRW) within an economic level. While supplying the population with sufficient water, the reduction of NRW has been a key issue in judging the performance of all water utilities. Background loss is one component of physical losses which is the most to contribute to NRW. This study aimed on pressure management method conducted at a site to reduce background loss. The pressure management method used is by the installation of a Pressure Reducing Valve (PRV) with timer-based pressure cut-off controller as an on-site verification. The BE59 - Kg. Melayu Pandan, one of the District Meter Area (DMA) in Johor Bahru has been selected as a case study. The Step Tests are carried out to analyse and identify the steps with high background leakage and to find suitable location for the purpose of PRV installation. The DMA meter and a data logger are used to measure and record pressure and flow profiles to determine leakage at each step and to establish leakage baselines, before and after the activation of the PRV. The results indicated a high reduction of background loss and given significant impact on the NRW level in Johor Bahru. In financial terms, volume of water saved and the monthly expenditure shows the return of investment (R.O.I) is in a period of 6 months. This research findings show a higher reduction on background loss can be achieved by optimising the cut-off controller, analysing further excess pressure cut-off based on pressure profiles in the existing or new DMA with a PRV and controller in a large scale. Comparisons with other methods of pipe replacement and Active Leakage Control (ALC), indicate that, the pressure management by excess pressure cut-off is the most feasible, economical and effective method in the NRW reduction.

ABSTRAK

Pihak pengurusan perkhidmatan bekalan air berhadapan dengan satu cabaran besar untuk mengurangkan dan mengawal kadar kehilangan air tidak berhasil (NRW) kepada paras yang ekonomik. Pengurangan kadar NRW merupakan petunjuk utama dalam menilai peningkatan prestasi sesebuah operator perkhidmatan bekalan air, selain memastikan air yang mencukupi dapat dibekalkan kepada penduduk. Kebocoran di bawah tanah yang di kategorikan sebagai kehilangan fizikal adalah merupakan komponen utama penyumbang kepada kadar NRW berbanding komponen-komponen NRW yang lain. Kajian ini menumpukan kepada kaedah pengawalan tekanan yang dijalankan ditapak untuk mengurangkan kebocoran di bawah tanah. Kaedah pengurusan tekanan digunakan melalui pemasangan Injap Pengurang Tekanan (*PRV*) dengan pemotongan tekanan terkawal berdasarkan penetapan masa sebagai pengesahan melalui kerja di tapak. Satu *District Meter Area* (*DMA*) dalam Johor Bahru, iaitu BE59 Kg. Melayu Pandan telah dipilih sebagai kajian kes dan Ujian Berlangkah dijalankan untuk menganalisis dan mengenalpasti kawasan dengan kebocoran di bawah tanah yang tinggi, disamping mencari lokasi pemasangan *PRV* yang sesuai. Meter kadar alir *DMA* dan alat merekod data digunakan untuk mengukur kadar aliran masuk dan taburan tekanan bagi mengira kebocoran pada setiap *step* dan penentuan garisan dasar nilai kebocoran sebelum dan selepas pengaktifan *PRV* pada *DMA* tersebut. Hasil kajian menunjukkan pengurangan kadar kebocoran di bawah tanah yang tinggi dan ini membantu mengawal dan menurunkan paras NRW di Johor Bahru. Dari sudut kewangan, nilai isipadu air yang dijimatkan dan perbelanjaan kos bulanan menunjukkan kadar bayaran balik *R.O.I* adalah dalam masa 6 bulan. Hasil kajian ini telah menunjukkan pengurangan kebocoran di bawah tanah yang tinggi juga boleh dicapai menerusi pengoptimuman penggunaan kawalan pemotongan tekanan berdasarkan penetapan masa melalui analisa taburan tekanan yang lebih terperinci yang dibuat pada *DMA* sedia ada atau yang baru dan juga perlaksanaan berskala besar pengurusan tekanan dengan penggunaan *PRV*. Berbanding dengan kaedah penukaran paip dan pengawalan kebocoran aktif (*ALC*), didapati kaedah pengurusan tekanan melalui pemotongan tekanan lebihan ini adalah lebih efektif dan ekonomik untuk pengurangan paras NRW.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATION AND SYMBOLS	xix
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Statement of Problem	2
	1.3 Objectives of Study	4
	1.4 Scope of Study	5
	1.5 Significance of Study	7
	1.6 Limitations of Study	9

2	LITERATURE REVIEW	11
2.1	Introduction	11
2.2	Non-Revenue Water and Leakages	15
2.2.1	Background Theory	18
2.2.2	Causes	19
2.2.3	Components	21
2.2.4	Monitoring and Control	23
2.3	NRW Components	24
2.3.1	Unbilled Authorised Consumption	24
2.3.2	Commercial Losses	25
2.3.3	Physical Losses	29
2.3.3.1	Leakage on Transmission and Distribution Mains	31
2.3.3.2	Leakage and Overflows from Utilities Storage Tanks	33
2.3.3.3	Leakage on Service Connections up to Customer Meter	34
2.4	Background Losses	37
2.4.1	Leakage Model	39
2.4.2	Measurement of Background Losses	40
2.5	Leakage Control Method	43
2.5.1	Active Leakage Control	46
2.5.1.1	Economic Level of Leakage	49
2.5.1.2	Step Testing	52
2.5.2	Speed and Quality of Repairs	56
2.5.3	Pipeline and Assets Management	57
2.5.4	Pressure Management	60
2.5.4.1	Pressure-Leakage Relationships	65
2.6	Pressure Reducing Valve	68
2.6.1	Fixed Outlet Controller	72
2.6.2	Time Modulated Controller	75
2.6.3	Flow Modulated Controller	78

3	METHODOLOGY	80
3.1	Introduction	80
3.2	Setting up of Site Works and Discussion	82
3.2.1	DMA Selection	84
3.2.1.1	Installation of Data Logger for Flow and Pressure	87
3.2.1.2	Background Losses Measurement	88
3.2.2	Step Test	91
3.2.2.1	Step Flow and Leakage Analysis	91
3.2.2.2	Pressure Survey	93
3.2.3	Installation of Pressure Reducing Valve (PRV)	94
3.2.4	Establishing Initial and Second Background Losses Baselines	95
3.3	Estimation of Saving	96
4	CASE STUDY	98
4.1	Introduction to Case Study Area	98
4.2	Site Works	109
4.2.1	Selection of DMA and Case Study Area	111
4.2.2	Step Test	120
4.2.3	Incorporation of Pressure Reducing Valve (PRV)	127
4.2.4	Establishing Background Loss Baselines	135
5	ANALYSIS OF RESULTS AND DISCUSSION	139
5.1	Introduction	139
5.2	Installation of Pressure Reducing Valve (PRV) with Timer Based – Pressure Cut Off Controller	140
5.3	Background Losses Baseline	142
5.4	Background Losses Reduction on Volume and Cost Saving	146
5.5	Alternative Leakage Control Method	149
5.5.1	Active Leakage Control	149
5.5.2	Pipe Replacement	151
5.6	Overall Findings and Discussion	152

6	CONCLUSIONS AND RECOMMENDATIONS	162
	6.1. Conclusions	162
	6.2. Recommendations	163
	6.3. Problems Encountered	165
	REFERENCES	167

LIST OF TABLES

TABLE NO.	TITLE	PAGE
1.1	District Meter Area in Johor, by district (Source: NRW Control, 2011)	9
2.1	Rate of NRW, by state (Source: The Malaysian Water Association, 2010)	12
2.2	Standard International Water Balance (Source: Farley <i>et al</i> , 2008).	17
2.3	References in National Reports regarding Pressure Management (Source: Lambert, 2002)	62
3.1	Net night flow (NNF in litres/second) ranges in October 2009 (Source: NRW Control, 2009)	85
4.1	Total connection and pipe length in DMA, by districts. (October 2009) (Source: NRW Control, 2009)	99
4.2	Volume and percentage of NRW, by district (2009 and 2010) (Source: NRW Control, 2010)	102
4.3	NNF for DMA under squatter area category in Johor Bahru (January – June 2009) (Source: NRW Control, 2009)	103
4.4	NNF for DMA under squatter area category in Johor Bahru (July - December 2009) (Source: NRW Control, 2009)	103
4.5	DMA distribution, by district (October 2009) (Source: NRW Control, 2009)	104
4.6	Distribution of problematic DMA, by problem, (October 2009) (Source: NRW Control, 2009)	106

4.7	Distribution of problematic DMA, by problem, (October 2009) (Source: NRW Control, 2009)	106
4.8	Background loses distribution by DMA for Johor Bahru (October 2009) (Source: NRW Control, 2009)	111
4.9	Rank of DMA with NNF from 20 to 40 l/s (October 2009) (Source: NRW Control, 2009)	112
4.10	The Step properties (Source: NRW Control, 2009)	121
4.11	The Step Test Results (Source: NRW Control, 2009)	123
4.12	The maximum and minimum pressure values	127
4.13	The maximum and minimum pressure ranges and the day and night pressure cut-off	134
5.1	The cost spent against background losses reduction.	150
5.2	The estimate cost to replace all the pipes and connections in Step 4.	151
5.3	The volume of NRW and background losses for the Johor state (Source: NRW Control, 2011).	153
5.4	The volume of NRW and background losses for the Johor Bahru (Source: NRW Control, 2011).	154
5.5	The total estimated cost spent for the leakage control methods	158
5.6	A comparison of the total estimated cost saving for three leakage control methods.	160

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Location of Johor state (red circle)	5
1.2	Location of DMA:BE59-Kg.Melayu Pandan in Google map	7
2.1	Johor NRW Level from January 2004 to December 2009 (Source: NRW Control, 2010)	13
2.2	Volume of treated water losses in Johor from 2006 to 2009 (Source: NRW Control, 2010)	14
2.3	Trend of NRW volume and background losses in Net Night Flow (NNF) in Johor from December 2006 to July 2009 (Source: NRW Control, 2010)	15
2.4	NRW components (Source: Frauendorfer and Liemberger, 2010)	22
2.5	Leakage control methods (Source: Technical Working Group on Waste Water, 1985).	23
2.6	Illegal tapping on meter stand (left) and air valve (right)	27
2.7	Tempered meter (left) and improper meter installation (right)	27
2.8	Sediment (left) and corrosion (right) inside the body of a water meter	28
2.9	Physical losses examples; air valve leaks and reservoir overflow	30
2.10	Leakages on distribution pipe	31
2.11	Catastrophic burst (left) and leakages on transmission	32

2.12	Background leakages; leakage on service connection and tapping ferrule	35
2.13	Major roads and properties damaged due to background leakages	35
2.14	Background losses diagram (Source: Farley <i>et al.</i> , 2008)	38
2.15	Invisible leakages or background losses	39
2.16	Leakage Model (Source: Farley <i>et al.</i> , 2008).	40
2.17	Relationship between leakage (Net Night Flow) and pressure (Source: Technical Working Group on Waste Water, 1985).	42
2.18	Leakage Management Strategy (Source: Technical Working Group on Waste Water, 1985).	44
2.19	Various type of leakage detection equipment	47
2.20	Leak Sounding	48
2.21	The leak run time components; awareness, location and repair	48
2.22	Economic Level of Leakage Model (Source: Farley and Trow, 2003)	50
2.23	Flow at closure and re-opening back the step valve in sequence (Source: Farley <i>et al.</i> , 2008).	54
2.24	Flow at closure of all the step valves and re-opening back in sequence (Source: Farley <i>et al.</i> , 2008).	54
2.25	Large flow drop in step 2 indicates presence of leaks (Source: Farley <i>et al.</i> , 2008).	55
2.26	Typical Step Test results showing the presence of leaks (Source: NRW Control, 2011).	56
2.27	Pipe failures due to aging	59
2.28	The relationships between pressure and (Source: Technical Working Group on Waste Water, 1985)	66
2.29	The relationships between pressure and leakage (Source: Farley <i>et al.</i> , 2008).	67

2.30	The cross section of a PRV	68
2.31	PRV Installation	69
2.32	Pressure profile in the distribution and reticulation during peak demand (Source: Mckenzie and Wegelin, 2005).	70
2.33	Pressure profile in the distribution and reticulation during low flow (consumption) demand (Source: Mckenzie and Wegelin, 2005).	71
2.34	Types of pressure control	72
2.35	Pilot or fixed outlet pressure controller sectional area (Source: NRW Control, 2012)	73
2.36	Schematic of PRV with fixed pressure controller (Source: NRW Control, 2012)	74
2.37	Pressure profile by using PRV with fixed outlet controller (Source: Thornton <i>et al.</i> , 2005).	74
2.38	PRV with time modulated controller	76
2.39	PRV with time modulated controller schematic (Source: NRW Control, 2012).	76
2.40	Pressure profile by using PRV with time-modulated controller (Source: Thornton <i>et al.</i> , 2005).	77
2.41	PRV with flow modulated controller	78
2.42	Pressure profile by using PRV with flow modulated controller (Source: NRW Control, 2012).	79
3.1	Works flowchart	81
3.2	The Setup Field Study process	83
3.3	Installation and Testing process	84
3.4	Typical DMA monitoring equipment	86
3.5	Typical data logger output showing typical flow and pressure in DMA (Source: NRW Control, 2010).	88
3.6	Typical flow profiles in DMA (Source: NRW Control, 2010).	90

3.7	The MNF components; LNF and NNF (Source: NRW Control, 2010)	90
3.8	Typical pressure profiles in DMA (Source: NRW Control, 2010)	94
4.1	Total reticulation pipe length percentage, by districts (October 2009) (Source: NRW Control, 2009)	100
4.2	Percentage of total connections, by districts (October 2009) (Source: NRW Control, 2009).	101
4.3	Percentage of DMA distribution, by district (October 2009) (Source: NRW Control, 2009).	105
4.4	Site study flow chart	110
4.5	BE 59 - Kg. Melayu Pandan in a Google map	114
4.6	BE 59 – DMA for Kg. Melayu Pandan	115
4.7	The schematic of BE 59 – DMA for Kg. Melayu Pandan	116
4.8	DMA panel for electromagnetic flow meter and data logger	117
4.9	A typical flow pattern for three days (Source: NRW Control, 2009).	118
4.10	A typical pressure pattern for three days (Source: NRW Control, 2009).	118
4.11	Monthly flows overlaid by daily (Source: NRW Control, 2012)	119
4.12	Monthly pressures overlaid by daily (Source: NRW Control, 2012)	119
4.13	Step Test Result (Source: NRW Control, 2009).	122
4.14	Step Test Analysis Form	123
4.15	Location of pressure point in the DMA	125
4.16	Pressure data logger installed in the DMA	125
4.17	The 24 hours pressure record for BE59–Kg. Melayu Pandan	126

4.18	Survey on location of the PRV installation at the DMA point (P1)	128
4.19	The arrows shows the selected location of the PRV installation at the DMA branches of the Step 4 (PV)	129
4.20	The PRV installation works	129
4.21	The daytime cut-off pressure reduction target, based on the pressure profile at the PRV installation point	130
4.22	Night-time cut-off pressure reduction target based on the pressure profile at the critical point	133
4.23	Typical pressure profiles at the upstream and downstream of PRV (PV) and at critical point (CP) (Source: NRW Control, 2009).	134
4.24	Typical background losses trend before and after the PRV installation (Source: NRW Control, 2009).	135
4.25	Background losses trend before and after the PRV installation	137
5.1	Pressure trend before and after PRV installation	141
5.2	The daytime (PV_{dt}) and night time (PV_{nt}) pressure cut-off targets	141
5.3	The pressure trend before and after PRV activation at critical point.	142
5.4	The MNF trends before (MNF_b) activation of PRV.	143
5.5	MNF_b and NNF_b trends before activation of PRV.	144
5.6	The MNF trend after (MNF_a) activation of PRV.	145
5.7	One month MNF_a and NNF_a trends after activation of PRV.	146
5.8	The MNF_b and MNF_a superimposed graphs of 4-days.	147
5.9	The NNF_b and NNF_a overlaid graph for 30 days periods.	148
5.10	The annual NRW and background loss volume for the Johor state (Source: NRW Control, 2011).	153
5.11	The annual NRW and background loss volume for Johor Bahru district (Source: NRW Control, 2011).	155

5.12	The annual background loss volume for the Johor state against Johor Bahru district (Source:NRW Control, 2011).	156
5.13	A comparison of the estimated cost per unit measurement (RM / m3) for the leakage control methods.	159
5.14	A comparison of the R.O.I for the three leakage control methods.	161
6.1	Background losses trend before and after activation the PRV with time-controller (Source: NRW Control, 2012).	165

LIST OF ABBREVIATION AND SYMBOLS

%	percentage
A.C	Asbestos Cement
ALC	Active Leakage Control
CP	Critical Point
CP _{cmin}	Estimated Elevation Difference between the CP and the Highest Customer Roof Tank Level
CP _{nmax}	Average Daily maximum Value for Night-time Periods at Critical Point
CV	Cut-off Value
CV _d	Cut-off Value for the Daytime Pressure
CV _n	Cut-off Values for Night-time Pressure
DMA	District Meter Area
BABE	Background and Burst Estimates
ELL	Economic Leakage Level
FAVAD	Fixed and Variables Area Discharges
HDPE	High Density Polyethylene
IWA	International Water Association
KPI	Key Performance Indices
LNF	Legitimate Night Flow
mH	Meter Head
MNF	Minimum Night Flow
MNF _a	Average MNF line after PRV installation
MNF _b	Average MNF line before PRV installation
NNF	Net Night Flow

NNF _a	Daily Average of the Background Losses Value After the PRV Installation
NNF _b	Daily Average of the Background Losses Value Before PRV Installation
NNF _d	Daily Volume of Background Losses Reduction
NNF _{da}	Average Daily Background Loss Volume After Activation of PRV
NNF _{db}	Average Daily Background Loss Volume Before Activation of PRV
NNF _r	Value of Background Losses Reduction
NRR	Natural Rate of Rise
NRW	Non-Revenue Water
P1	Inlet of the DMA inlet point
P2	Farthest point of the DMA
P3	Highest point of Step 3
PRV	Pressure Reducing Valve
PV	Point of PRV Installed
PV _{dmax}	Average maximum value of daytime pressure
PV _{dt}	Daytime Pressure Cut-off Target
PV _{nmax}	Average Maximum Value of Night-Time Pressure
PV _{nt}	Night-time Pressure Cut-off Target
PVC	Polyvinyl Chloride
R.O.I	Return of Investment
SAJ	SAJ Holdings Sdn Bhd
SPAN	Suruhanjaya Perkhidmatan Air Negara
UFW	Unaccounted for Water
VS	Average Daily Amount of Volume Saved
WLTF	Water Loss Task Force
WTP	Water Treatment Plan

CHAPTER I

INTRODUCTION

1.1 Introduction

Non-Revenue Water (NRW) is one of the greatest challenges to most water utilities. Since NRW level as an indicator of the water utility's operating efficiency, they need taken serious consideration on performing and establishing NRW policy and strategies to control, monitor, reduce and accurately quantify the NRW to ensure NRW reduction and control within the economic level. Physical Losses is the main component of NRW contributor and they come in the form of leakage on transmission and distribution main, leakage and overflows from storage tank, and leakage on service connections up to customer meters. Leakages from transmission and distribution mains are usually large events that can cause serious road infrastructure and public assets damages, bigger volume of water losses and severe injuries or death, especially when it happens in remote area such as, in private plantations and farms, private land, abandoned land, where leakage will run undetected for a few months or even years. In Johor the physical loss in 2006 was 23.8% (118.23 Mill. m³/year) and reduced to 23.3% (117.36Mill. m³/year) in 2007 (NRW Control, 2007). High frequency of pipe burst in remote areas that take longer

time to be localised, responded and repaired, made it the major contributor to physical losses.

Latest development on pressure management shows the conventional implementation of Pressure Reducing Valves (PRV) have improved and add a new function by using timer-based pressure cut-off and pressure modulation controller to minimise the excess pressure in the water reticulation, hence reduce the background loss. This timer-based pressure cut off controller is attached to the existing PRV and functions to cut-off excess pressure, where the higher current pressure switches to the lower user setting at a designated time, while pressure modulation will accommodate the pressure increase or decrease based on consumption demand or flow profile of the designated District Meter Area (DMA). This study will identify the impact on reduction of background losses by using the PRV with timer-based pressure cut-off at the DMA inlet and comparing the resulting cost of this equipment installation and operation with total length pipe replacement and Active Leakage Control (ALC) implementation.

1.2 Statement of Problem

Controlling and reducing NRW is the biggest challenge to the water operator since there are no very efficient tools and strategy to do so. In developing countries, physical loss, due to background leakage such as communication pipe leaks, burst and pipe breakages, pipe fractures due to pipe aging because of oldest infrastructure and worse assets condition, is a major and the biggest contributor to NRW.

According to the Asian Development Bank the estimated annual volume of NRW in urban water utilities in Asia is in the order of 29 billion cubic metres (m³). Assuming a value of water at USD 0.30 per cubic metre, Asia's water utilities are

losing nearly USD 9 billion per year. By cutting physical losses to half the present level (which is technically feasible), 150 million people could be supplied with already treated water (Frauendorfer and Liemberger, 2010).

Moreover, unmanageable pressure in water reticulation can cause high pressure, sudden changes and wide ranges of pressure transient to occur in the water supply system. This puts a high stress and load to the existing old water system. Pressure and leakage relationship shows a direct relation between these components. High pressures mean high leakage which is directly causing high NRW. This excessive pressure (or over pressure) to the water assets will directly create new leaks at the weak points on the existing assets, and increase the frequency and volume of leakage in the water supply system (Farley *et al.*, 2008).

Pressure Reducing Valve (PRV) is one of the most popular pressure management equipment widely implemented near to DMAs and branches. PRV is the basic pressure equipment which helps avoid the extreme pressures transient in a system. It works as a control by adjusting the maximum and cap the downstream pressure outlet at one fixed pressure line set by the user (Farley and Trow, 2003). In practice, the pressure set at the PRV outlet is the pressure demand on the daytime during peak flow demand. However, the pressure in the system will develop significant ranges more than the daytime (peak consumption demand), when there is less or no water consumed or with low head loss and no flows at the night time. To control and minimise this significant pressure increase in the system during night time, this study has proposed to attach a timer-based pressure cut-off tool to the existing PRV where it would function to provide the additional fix pressure line to control and cap the downstream pressure outlet across the day and night time.

Besides the pipe aging factor, there are no efficient tools to evaluate total pipe assets condition which is beneath the ground level where part of it is submerged under the ground water level. Pipe materials may chemically react with the surrounding nature compounds, for example pipe corrosion due acidic soils.

In developing countries, there are many cases of high NRW, although its level is shown to be reducing and under control. The background losses line shows an increased trend or upset than the NRW level reduction line, as expected. Once all the efforts to reduce background losses have been put in place, the soaring trends may become a major concern to those water operators to overcome in the coming years.

This study focuses on NRW against background losses trends in Johor. Data on volume of losses on monthly basis are collected and an approach used to reduce background losses by installing pressure management strategy using pressure reducing valve (PRV) is utilised. The PRV would cut down the excessive pressure resulted in the water reticulation system.

1.3 Objectives of Study

The objectives of the study has been identified as follows;

1. To determine the volume of background loss that contributes to non-revenue water (NRW) in Johor.
2. To analyse the volume saved due to reduce background loss by using the PRV to cut-off the excessive pressure.
3. To estimate and compare the return of investment and the cost for each cubic metre of active leakage control (ALC), pipe replacement and pressure management methods.

The outcome may contribute to the knowledge of better non-revenue water control and sustain by exposing the pressure management using PRV with excess pressure cut-off for better future selection.

1.4 Scope of Study

This study is focused on the implementation of NRW control methods in Johor state as shown in Figure 1.1, highlighting on progress performances, milestone, target, achievements and continued improvement efforts put up by the water authority.




Figure 1.1 Location of Johor state (red circle)

This study has selected Johor Bahru district as a case study is because of the following reasons;

- i. Johor Bahru is the biggest NRW and background losses contributor in the Johor state (NRW Control, 2012).
- ii. Johor Bahru has also recorded the highest population density, most DMAs and the longest pipe length in the Johor state (NRW Control, 2012).
- iii. Since Johor Bahru has the highest consumers, it has a variety of demographic and businesses such as shop house, light and heavy industry and etc.

A case study will be conducted on BE59 – Kg. Melayu Pandan. It is located along the Tebrau – Kota Tinggi main road and covers most of Kampung Melayu Pandan as shown in Figure 1.2. Out of 348 non-problematic DMAs in Johor Bahru district, BE59 – Kg. Melayu Pandan is selected as a case study due to the highest magnitude of background loss in the DMA rank in the Johor Bahru district. Selection of the district and DMA in this case study is discussed in details in Section 4.2.

Part of the pipe configuration will be installed with a PRV, identified as Step 4 pipe line. The PRV shall function as a control and to maintain pressure at a baseline of pressure during peak demand. Excess pressure is cut-off and background loss or Net Night Flow (NNF) reduction is expected in this DMA.



Figure 1.2 Location of DMA: BE59 - Kg. Melayu Pandan in Google map

1.5 Significance of Study

Reducing NRW means saving a lot of natural resources, energy, chemical usage, etc. The significance impact in reducing NRW is mentioned as follows;

- i. To cater for consumer growth and future demands, water utilities will need to look into large scale project on developing new water resources, water treated schemes and catchment area which involved a huge budget allocation to do so.
- ii. Low operational expenditure cost due to less consumption of electricity and chemical usage, and low water abstraction charges. Before it reaches its final destination, the water may have been pumped from the source to treatment plant, where further energy is used in the treatment process. It will then be pumped to a treated water reservoir and may require further pumping into the distribution

system. Since water is heavy, all of these processes require significant amounts of energy.

- iii. Increase cash revenue to water utility by channelling the volume losses to industrial consumers.
- iv. Increase water utilities efficiency and image or reputation especially on managing water losses.
- v. Provide sustainable water resources plan for future generations.

This study will look into the function of a PRV placed in the water supply line. The pressure and background loss or net night flow (NNF) baseline is determined and whatever excess pressure fluctuations that occur in that duration will be cut-off to maintain the baseline pressure. This excess pressure would reduce the volume of NNF, hence reducing the NRW for that particular district.

A District Meter Area (DMA) located in Johor Bahru district is chosen as a case study where a PRV with timer-based pressure cut-off controller is installed. This is done to reduce current background loss inside the DMA; i.e. by reducing the Net Night Flow (NNF). In Johor, the DMA is also called District Meter Zone (DMZ) and currently the water authority, SAJ Holdings Sdn. Bhd. (SAJ) has established 925 DMAs, as tabulated in Table 1.1. Eight hundred and forty six (846) of the DMAs are equipped with permanent electromagnetic flowmeter to monitor and measure background losses in daily basis, while another 79 new additional DMA are utilising portable insertion probe electromagnetic flowmeter for monitoring purposes done quarterly. This new additional DMA in this study is a new DMA, recently established by Active Leakage Control (ALC) team at a new mass development housing estate area, but with leakage level too low and uneconomical to for daily leakage measurement (NRW Control, 2011).

Table 1.1 District Meter Area in Johor, by district (Source: NRW Control, 2011)

DISTRICT / REGIONAL	DMA Established with Flowmeter	New DMA with Insertion Probe	TOTAL
JOHOR BAHRU	362	60	422
<i>i. Johor Bahru</i>	134	21	155
<i>ii. Pasir Gudang</i>	109	25	134
<i>iii. Kulai</i>	119	14	133
BATU PAHAT	120	5	125
MUAR	90	1	91
PONTIAN	58	0	58
KLUANG	77	13	90
KOTA TINGGI	59	0	59
MERSING	30	0	30
SEGAMAT	50	0	50
JOHOR	846	79	925

From economics point of view, large capital investment is always associated with the development of new water resources, water treatment plants, dams and water transfer schemes. However, it can be delayed or postponed for many years due to many unanticipated reasons. However, a postponement can create an opportunity to water providers to gain access in self-generated cash flow, increase in revenue, increase the water provider efficiency and reputation and meet the NRW percentage target as stated in contract between water provider and water authorities.

1.6 Limitations of Study

The limitations of study during carry out the site verification has identified and considered two criteria as follows;

- i. A collective DMA by magnitude of background loss or Net Night Flow (NNF) according to rank, and

- ii. The DMA under squatter areas.

These two criteria are considered due to;

- i. Collective DMA ranked by background loss magnitude is close to the objectives of this study. Furthermore almost all DMA have data loggers installed to gauge magnitude of daily background loss or Net Night Flow (NNF) in litre per second. Moreover, the historical data for the other options which involve many parameters or variables in their calculation lack specific formula to calculate monthly values. The database system to cater and record all the data for NRW and losses have not yet been develop, which at this moment is in the feasibility study phase for tendering.
- ii. The DMA under squatter area is considered in this study since the residents are staying in this area illegally, with the improper service facilities and physical infrastructures not provided sufficiently, and do not normally meet the local authority standard requirements. Furthermore, in most cases, the land acquisition taken by new land owner or developer can be complex as they are not allowed to do any physical works or any obvious improvement activities on the land. The consequences are; some of the major leakage management activities such as pipe replacement or rehabilitation, Active Leakage Control (ALC) and active leakage detection such as regular sounding are not allowed to be carried out.
- iii. Only the non-problematic DMA is considered in this study due to no current or actual data available for problematic DMA. The DMA monthly report for October 2009 is used as a reference for the purpose of this study.

REFERENCES

- American Water Works Association (2009). *Water Audits and Loss Control Programs - M36: Manual of Water Supply Practices*. United States, America: Glacier Publishing.
- Andrews, M., Berardo, P. and Foster, D. (2011). The Sustainable Industrial Water Cycle – A Review of the Economics and Approach. *Water Science and Technology: Water Supply*. 11(1), 67-77.
- Asset Replacement. (2010). *Asset Replacement Annual Report*. Malaysia: SAJ Holdings Sdn. Bhd.
- Bambos, C. (2008). Use of District Metered Areas Coupled with Pressure Optimisation to Reduce Leakage. *Water Science and Technology: Water Supply*. 8(1), 57-62.
- Carpenter, T., Lambert, A. O., and McKenzie, R. (2003). Applying the IWA Approach to Water Loss Performance Indicators in Australia. *Water Science and Technology: Water Supply*. 3(1), 153-161.
- Christodoulou, S. and Agathokleous, A. (2012). A Study on the Effects of Intermittent Water Supply on the Vulnerability of Urban Water Distribution Networks. *Water Science and Technology: Water Supply*. 12(4), 523-530.
- Fanner, P. and Thornton, J. (2005). The Importance of Real Loss Component for Determining the Correct Intervention Strategy. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 192 - 202.
- Farley, M. (2005). Technology and Equipment for Water Loss Management – ‘What’s New?’. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 432 - 441.

- Farley, M. and Liemberger, R. (2005). Developing a Non-Revenue Water Reduction Strategy: Planning and Implementing the Strategy. *Water Science and Technology: Water Supply*. 5(1), 41-50.
- Farley, M. and Trow, S. (2003). *Losses in Water Distribution Networks - A Practitioner's Guide to Assessment, Monitoring and Control*. London: IWA Publishing.
- Farley, M., Wyeth, G., Mohd Ghazali, Z., Istandar, A., and Singh, S. (2008). *The Manager's Non-Revenue Water Handbook: A Guide to Understanding Water Losses*. Malaysia: Ranhill Utilities Berhad and the United States Agency for International Development (USAID).
- Feldman, D. L. (2011). Integrated Water Management and Environmental Justice – Public Acceptability and Fairness in Adopting Water Innovations. *Water Science and Technology: Water Supply*. 11(2), 135-141.
- Frauentorfer, R. and Liemberger, R. (2010). *The Issues and Challenges of Reducing Non-Revenue Water*. Philippines: Asian Development Bank.
- Ishiwatari, Y., Mishima, I., Utsuno, N. and Fujita, M. (2013). Diagnosis of the Ageing of Water Pipe Systems by Water Quality and Structure of Iron Corrosion in Supplied Water. *Water Science and Technology: Water Supply*. 13(1), 178-183.
- JKR Design Criteria and Standards Committee (1989). *JKR Design Criteria and Standards for Water Supply System*. Kuala Lumpur: JKR Water Supplies.
- Kalanithy V. and Mohamed Mansoor, M. A. (2006). Demand Management in Developing Countries. In David, B. and Fayyaz, A. M. (Eds) *Water Demand Management*. (pp. 180-214). London: IWA Publishing.

- Klingel, P. (2012). Technical Causes and Impacts of Intermittent Water Distribution. *Water Science and Technology: Water Supply*. 12(4), 504-512.
- Kunkel, G. (2005). Developments in Water Loss Control Policy and Regulation in the United States. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 7 - 14.
- Lambert, A. O. (2002). International Report: Water Losses Management and Techniques. *Water Science and Technology: Water Supply*. 2(4), 1-20.
- Lambert, A. O. and Fantozzi, M. (2005). Recent Advances in Calculating Economic Intervention Frequency for Active Leakage Control, and Implications for Calculation of Economic Leakage Levels. *Water Science and Technology: Water Supply*. 5(6), 263-271.
- Lambert, A. O. and Lalonde, A. (2005). Using Practical Predictions of Economic Intervention Frequency to Calculate Short-run Economic Leakage Level, With or Without Pressure Management. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 310 - 321.
- Liemberger, R. (2002). Performance Target Based Non-Revenue Water Reduction Contracts: A New Concept Successfully Implemented in Southeast Asia. *Water Science and Technology: Water Supply*. 2(4), 21-28.
- Mckenzie, R. S. and Wegelin, W. (2005). Sebokeng/Evaton Pressure/Leakage Reduction: Public Private Partnership. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 382 - 391.
- Mukand, S. B., Md, S. I. and Das Gupta, A. (2009). Leakage Management in a Low-Pressure Water Distribution Network of Bangkok. *Water Science and Technology: Water Supply*. 9(2), 141-147.

- Nakazono, H., Dodo, O. and Kataishi, K. (2012). Effectiveness of Reconstruction of Water Supply System From the Economic Viewpoint and Affecting Factors – Case Study of a City. *Water Science and Technology: Water Supply*. 12(6), 937-942.
- Naveh, N., Ingham, M., Melamed, C., Enav, Y., Cohen, O. and Shalom, G. B. (2005). The Entrepreneurial Approach to Implementing a Leakage Control System in Municipal Networks – Case Studies. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 261 - 271.
- Network. (2012). *Annual Report – 2012: Network*. Malaysia: SAJ Holdings Sdn. Bhd.
- NRW Control. (2006). *Annual Report – 2006: NRW Control*. Malaysia: SAJ Holdings Sdn. Bhd.
- NRW Control. (2007). *Annual Report – 2007: NRW Control*. Malaysia: SAJ Holdings Sdn. Bhd.
- NRW Control. (2009). *Annual Report – 2009: NRW Control*. Malaysia: SAJ Holdings Sdn. Bhd.
- NRW Control. (2010). *Annual Report – 2010: NRW Control*. Malaysia: SAJ Holdings Sdn. Bhd.
- NRW Control. (2011). *Annual Report – 2011: NRW Control*. Malaysia: SAJ Holdings Sdn. Bhd.
- NRW Control. (2012). *Annual Report – 2012: NRW Control*. Malaysia: SAJ Holdings Sdn. Bhd.
- Pearson, D. and Trow, S. (2005). Calculating Economic Levels of Leakage. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 294 - 309.

- Pearson, D., Fantozzi, M., Debra, S. and Waldron, T. (2005). Searching for N2: How Does Pressure Reduction Reduce Burst Frequency?. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 368 - 381.
- Pilipovic, Z. and Taylor, R. (2003). Pressure Management in Waitakere City, New Zealand – A Case Study. *Water Science and Technology: Water Supply*. 3(1), 135-141.
- Project Planning. (2011). *Annual Report – 2011: Project Planning*. Malaysia: SAJ Holdings Sdn. Bhd.
- Rogers, D. (2005). Reducing Leakage in Jakarta, Indonesia. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 253 - 260.
- South African Water Research Commission (2002). *WRC Report TT 169/02*. Republic of South Africa: South African Water Research Commission.
- Standards and Practice Committee (1994). *MWA Design Guidelines for Water Supply System*. Kuala Lumpur: Malaysian Water Association.
- Tanyimboh, T. T., Marika, T. T. and Saleh, S. (2011). Reliability Assessment of Water Distribution Systems with Statistical Entropy and Other Surrogate Measures. *Water Science and Technology: Water Supply*. 11(4), 437-443.
- Technical Working Group on Waste Water (1985). *Leakage Control Policy and Practice*. London: Water Authorities Association.
- The Malaysian Water Association. (2006). *Malaysia Water Industry Guide 2006: Water Supply Statistics & Performance Indicators*. Kuala Lumpur: The Malaysian Water Association.

- The Malaysian Water Association. (2012). *Malaysia Water Industry Guide 2012: Water Supply Statistics & Performance Indicators*. Kuala Lumpur: The Malaysian Water Association.
- Thornton, J. and Lambert, A. O. (2005). Progress in Practical Prediction of Pressure: Leakage Pressure: Burst Frequency and Pressure: Consumption Relationships. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 347 - 357.
- Thornton, J., Shaw, M., Aguiar, M. and Liemberger, R. (2005). How Low Can You Go? A Practical Approach to Pressure Control in Low Pressure Systems. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 392 - 402.
- Tooms, S. and Morrison, J.A.E. (2005). DMA Management Manual by the Water Losses Task Force: Progress. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 427 - 431.
- Trow, S., and Farley, M. (2004). Developing a Strategy for Leakage Management in Water Distribution System. *Water Science and Technology: Water Supply*. 4(3), 149-168.
- Tuhovcak, L, Svoboda, M., Svitak, Z. and Tothova, K. (2005). The Technical Audit of Water Distribution Network Using the Different Leakage Indicators. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 495 - 503.
- Vanham, D. (2011). How Much Water Do We Really Use? A Case Study of The City State of Singapore. *Water Science and Technology: Water Supply*. 11(2), 219-228.
- Warren, R. P. (2005). The Service Pipe – A Forgotten Asset in Leak Detection. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 203 - 211.

Woodward, C. A., Rogers, C. D. F. and Chapman, D. (2005). The Effect of Soil Properties on Leakage Economics. *Conference Proceedings of the Leakage 2005*. 12-14 September. Halifax, Canada, 339 - 346.

Wyatt, A. and Alshafey, M. (2012). Non-Revenue Water: Financial Model for Optimal Management in Developing Countries – Application in Aqaba, Jordan. *Water Science and Technology: Water Supply*. 12(4), 451-462.