

OPTIMIZATION PARAMETER FOR MPEG-4 DATA OVER WIRELESS
SENSOR NETWORK

NORLEZAH BINTI HASHIM

UNIVERSITI TEKNOLOGI MALAYSIA

OPTIMIZATION PARAMETER FOR MPEG-4 DATA
OVER WIRELESS SENSOR NETWORK

NORLEZAH BINTI HASHIM

A project report submitted in partial fulfilment of the
requirement for the award of the degree of
Master of Engineering (Electrical – Electronics & Telecommunications)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

JANUARY 2014

To my beloved parents, husband and my adorable son

ACKNOWLEDGEMENT

I would like to take this opportunity to express my sincere appreciation to my supervisor of this project, Dr. Sharifah Hafizah bte Syed Ariffin who has relentlessly and tirelessly assisted me in completing this project. She has given me the opportunity to do this project under her supervision and guide me to complete the project. My utmost thanks also goes to my family who has given me support throughout my academic years.

It is to my advantage that I have received help and support from my fellow graduate and senior students. Thus I would like to express my heartfelt appreciation to Farizah Yunus, Abdul Hadi Fikri, Mohd Rozaini Abd Rahim and Telematic Research Group (TRG) for suggestions and supports towards the successful completion of this project. It is of my greatest thanks and joy that I have met with these great people.

ABSTRACT

Conventional Wireless Sensor Network (WSN) always deals with scalar data such as temperature, humidity, pressure and lights. These types of data are very suitable for low rate and low power networking technology such as IEEE802.15.4. Transmitting a video for IEEE 802.15.4 standard is an interest due to the capability of providing low complexity with low cost but still maintaining the good quality of video in term of Peak Signal to Noise Ratio (PSNR). However transferring video posed new challenges for bandwidth constrained sensor networks like WSN. Furthermore, processing power put a serious limitation on it for any sophisticated processing. Therefore a method needed for reliable video transfer and one way is to compress the video format. A simulation testing has been done to determine the optimal threshold for quantization scale, group of picture and frame per second in order to tailor with the environment of WSN 802.15.4. When these three parameters are changed, the video quality and bandwidth requirement will be affected. Therefore this project aims to create an embedded code in TelG mote according to this concept. Experiment testbeds are conducted for indoor and outdoor to investigate the network performance in term of packet delivery ratio and total packet loss. Results show the packet delivery ratio of optimized MPEG-4 data for Akiyo *cif* file is 36% better than the non-optimized MPEG-4 data, Foreman *cif* file is 12% and Mobile *cif* file is 8%. Thus this project have proved that optimized parameter of MPEG-4 data has successfully increase the network performance of WSN.

ABSTRAK

Aplikasi Rangkaian Sensor tanpa Wayar (*WSN*) konvensional secara umumnya mengendalikan data yang bersifat skala seperti suhu, kelembapan, tekanan dan cahaya. Data seperti ini amat sesuai untuk teknologi perhubungan rangkaian yang mempunyai kadar data dan penggunaan kuasa yang rendah seperti piawaian IEEE 802.15.4. Penghantaran video untuk standard IEEE 802.15.4 menarik minat kerana kebolehannya menyediakan kerumitan yang rendah dengan kos yang rendah tetapi masih mengekalkan kualiti video yang baik dalam terma nisbah isyarat puncak kepada hingar. Walaubagaimanapun, penghantaran video memberi cabaran baru kepada rangkaian sensor berjalur lebar yang sempit seperti *WSN*. Tambahan pula, kuasa pemproses meletakkan had yang serius untuk pemprosesan yang canggih. Oleh itu satu cara diperlukan bagi pemindahan video yang boleh dipercayai dan satu cara adalah dengan memadatkan format video. Oleh itu ujian simulasi telah diadakan untuk menentukan ambang yang optimum bagi skala pengkuantuman, *group of picture* dan *frame per second* yang sesuai dengan persekitaran *WSN* 802.15.4. Apabila parameter ini berubah, kualiti video dan keperluan jalur lebar akan terjejas. Oleh itu matlamat projek ini adalah untuk membina kod terbenam di dalam TelG berpandukan konsep ini. Eksperimen telah dijalankan di dalam bangunan dan di luar bangunan bagi menyiasat prestasi rangkaian dalam bentuk nisbah penghantaran paket dan jumlah kehilangan paket. Keputusan menunjukkan nisbah penghantaran paket untuk format video MPEG-4 yang dioptimumkan adalah lebih baik berbanding format video MPEG-4 yang tidak dioptimumkan sebanyak 36% untuk fail Akiyo *cif*, 12% untuk fail Foreman *cif*, dan 8% untuk fail Mobile *cif*. Projek ini telah membuktikan bahawa format video MPEG-4 yang dioptimumkan telah Berjaya meningkatkan prestasi rangkaian dalam *WSN*.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	TITLE	i
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATIONS	xiii
	LIST OF SYMBOLS	xvi
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Problem Statements	2
	1.3 Research Objectives	3
	1.4 Scope of Project	3
	1.5 Thesis Outline	4
2	LITERATURE REVIEW	5
	2.1 Overview of WSN	5
	2.1.1 WSN architecture	6
	2.1.2 WSN general description	7
	2.1.3 WSN application	8
	2.1.4 WSN network topology	8

2.1.5	WSN communication protocols & routing	10
2.2	The MPEG-4 format	14
2.2.1	Optimized parameter of MPEG-4	15
2.3	TelG system Architecture	20
2.3.1	Power unit	20
2.3.2	Processing unit	21
2.3.3	Communication unit	22
2.3.4	Sensing unit	23
2.4	TelG Design	23
2.5	WiseOS operating system	24
2.5.1	WiseOS Software Architecture	24
2.5.2	NesC Programming Language	25
2.6	Previous Related Researches	25
2.7	Summary	29
3	METHODOLOGY	30
3.1	Software Component	30
3.1.1	WiseOS	30
3.1.2	NesC Programming Language	31
3.2	Hardware Component	31
3.2.1	TelG Mote	31
3.2.2	Hardware Limitation	32
3.3	Types of samples used in research	32
3.4	State Diagram of the Algorithm	34
3.5	Flowchart of the Algorithm	36
3.6	Experiment Testbed Setup	37
3.7	Summary	40

4	RESULTS AND DISCUSSION	43
4.1	Optimized versus non-optimized data (indoor)	43
4.1.1	1 hop experiments	44
4.1.2	2 hop experiments	48
4.2	Indoor versus outdoor data for two hops experiments	51
4.3	Outdoor versus simulation data for two hops experiments	54
4.5	Summary	57
5	CONCLUSION AND FUTURE WORK	58
5.1	Conclusion	55
5.2	Proposed Future Work	59
	REFERENCES	60
	APPENDIX	64

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Power consumption of ATmega644PV	21
3.1	Types of video sample used in research	33
3.2	Types of data used in research	38
3.3	Packet Configuration	41

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Accessing WSN through internets	6
2.2	WSN Architecture	7
2.3	WSN Network Topology	9
2.4	MPEG-4 encoding structure and component	14
2.5	Flow of encoding and decoding video process	16
2.6	The prediction Dependencies between Frames in MPEG-4 for Group of Picture	17
2.7	Flow chart to choose the optimal value for quantization scale, roup of picture and frame per second	18
2.8	Trace file	19
2.9	TelG system architecture	20
2.10	XBee Module	23
2.11	WiseOS Design	24
2.12	Superframe Diagram	25
2.13	State transition diagram for capturing and transmitting JPEG images	28
3.1	TelG mote	31
3.2	Akiyo video sequence	33
3.3	Foreman video sequence	33
3.4	Mobile video sequence	33
3.5	State diagram of the algorithm	34
3.6	Flowchart of the algorithm	36

3.7	Experimental testbed setup	39
3.8	Experiment setup for one hop (indoor)	40
3.9	Experiment setup for two hops indoor (3m – 8m)	41
3.10	Experiment setup for two hops indoor (9m – 15m)	41
3.11	Experiment setup for two hops outdoor (3m – 15m)	42
4.1	Packet Delivery Ratio for 1 hop <i>cif</i> MPEG-4 file	45
4.2	Packet Delivery Ratio for 1 hop <i>qcif</i> MPEG-4 file	45
4.3	Packet Loss for 1 hop <i>cif</i> MPEG-4 file	47
4.4	Packet Loss for 1 hop <i>qcif</i> MPEG-4 file	47
4.5	Packet Delivery Ratio for 2 hops <i>cif</i> MPEG-4 file	48
4.6	Packet Delivery Ratio for 2 hops <i>qcif</i> MPEG-4 file	49
4.7	Packet Loss for 2 hops <i>cif</i> MPEG-4 file	50
4.8	Packet Loss for 2 hops <i>qcif</i> MPEG-4 file	50
4.9	Packet Delivery Ratio for 2 hops <i>cif</i> (outdoor vs indoor)	51
4.10	Packet Delivery Ratio for 2 hops <i>qcif</i> (outdoor vs indoor)	52
4.11	Packet Loss for 2 hops <i>cif</i> (outdoor vs indoor)	53
4.12	Packet Loss for 2 hops <i>qcif</i> (outdoor vs indoor)	53
4.13	Packet Delivery Ratio for 2 hops <i>cif</i> (outdoor vs simulation)	54
4.14	Packet Delivery Ratio for 2 hops <i>qcif</i> (outdoor vs simulation)	55
4.15	Packet Loss for 2 hops <i>cif</i> (outdoor vs simulation)	56
4.16	Packet Loss for 2 hops <i>qcif</i> (outdoor vs simulation)	57

LIST OF ABBREVIATIONS

API	-	Application Programming Interface
BO	-	Beacon Order
CAP	-	Contention Access Period
CSMA-CA	-	Carrier Sense Multiple Access with collision avoidance
CDMA	-	Code Division Multiple Access
CIF	-	Common Intermediate Format
EEPROM	-	Erasable Programmable Read Only Memory
FDMA	-	Frequency Division Multiple Access
FPS	-	Frame per Second
GOP	-	Group of Picture
GTS	-	Guaranteed time slots
HL	-	Hardware Layer
HAL	-	Hardware Abstraction Layer
HPL	-	Hardware Presentation Layer
ISP	-	Internet Protocol
LLC	-	Logical Link Control
LQI	-	Link Quality Indication
MAC	-	Media Access Control
MPEG-4	-	Motion Picture Expert Group
MTU	-	Maximum Transmission Unit
NL	-	Network Layer
OSI	-	Open System Interconnections
PHY	-	Physical Layer of OSI model

PSNR	-	Peak Signal to Noise Ratio
QCIF	-	Quarter Common Intermediate Format
QS	-	Quantization Scale
QoS	-	Quality of Service
SO	-	Superframe Order
SSCS	-	Convergence sub layer
SHR	-	Self Healing Ring Network
TDMA	-	Time Division Multiple Access
UART	-	Universal Asynchronous Receiver/Transmitter
USART	-	Universal Synchronous Asynchronous Receiver/Transmitter
XBee	-	Zigbee
WSN	-	Wireless Sensor Network

LIST OF SYMBOLS

P_r	-	Received power
P_t	-	Transmitted power
G_t	-	Gain of transmitting antenna
G_r	-	Gain of receiving antenna
h_t	-	Height of transmitter
h_r	-	Height of receiver
d	-	Distance from transmitter
L	-	System loss

LIST OF APPENDIX

APPENDIX	TITLE	PAGE
A	TRACE FILE	64

CHAPTER 1

INTRODUCTION

This chapter gives the overall idea of this research. It discusses the background of research, the problem statements, research objectives and the scope of work.

1.1 Introduction

Nowadays, we can see wireless sensor network is used in many applications such as disaster prevention and relief and environmental monitoring. The importance of wireless sensor networks arises from their capability for detailed monitoring in remote and inaccessible locations where it is not feasible to install conventional wired infrastructure. More interest is given to the wireless sensor network (WSN) for IEEE 802.15.4 standard due to its advantages in providing low data rate transmission, low energy consumption, ease to deploy in the network and low cost with the small size of the sensor. However, the transmission of data especially video

for IEEE 802.15.4 standard is more challenging due to large amount of bandwidth is required. Furthermore, WSN IEEE 802.15.4 standard only allowed the maximum of 250 kbps data rate.

One way to overcome the issue of bandwidth is by compressing the video format, for example MPEG-4 video. The Researcher in [1] has developed the benchmark for the settings of video encoding which can provide better video quality suitable for WSN application. The researcher mentioned three parameters namely quantization scale, group of picture, and frame per second that are important in determining the quality of a received video. Therefore this project aims to conduct an experiment to investigate the network performance of optimized MPEG-4 video format proposed by [1] over WSN for IEEE 802.15.4 standard using TelG sensor node.

1.2 Problem Statement

Conventional WSN always deals with scalar data such as temperature, humidity, pressure and lights. These types of data are suitable for low rate and low power networking technology such as IEEE802.15.4. However, transferring video data posed new challenges for bandwidth constrained sensor networks like WSN. Furthermore, processing power puts a serious limitation on it for any sophisticated processing. Therefore a method is needed for reliable video data transfer.

Transmitting a video for IEEE 802.15.4 standard is an interest due to the capability of providing low complexity with low cost but still maintaining the good quality of video in term of Peak Signal to Noise Ratio (PSNR). The MPEG-4 video is already proven suitable to be transmitted over IEEE 802.15.4 standard. Therefore this project aims to conduct an experiment to investigate the network performance of MPEG-4 video data over WSN for IEEE 802.15.4 standard using TelG sensor node. However, due to limitation of power and memory in WSN; the encoding and decoding process is done outside TelG. This also can reduce the hardware complexity. Encoding and decoding process consumes a lot of power huge memory so the complexity will increase.

1.3 Research Objectives

The research objectives are stated as follows:

- i. To develop an algorithm to transfer MPEG-4 data in WSN using TelG devices.
- ii. To perform experiments based on the algorithm and analyze the network performance.

1.4 Scope of Work

This research is limited to several scopes. First, the development of optimized parameter for MPEG-4 is done using TinyOS operating system and network embedded systems C (nesC) programming language. Then the developed code is uploaded into TelG mote before the testbed is deployed. The testbed network used 2 sensor nodes and the XTerminal¹ software will be used to view the result obtained from testbed. Performance of test bed and simulation will be compared.

Second, the encoding and decoding process is done manually outside TelG. The reason for this is due to the limitation of TelG and WSN where the processor inside TelG puts a serious limitation for any sophisticated processing and WSN only allowed a maximum data rate of 250 Kbps. Decoding and encoding process needs a huge memory. Thus, in order to save the internal memory of TelG, the encoding and decoding process is done outside TelG devices.

¹ It is a window terminal emulator for displaying client applications.

1.5 Thesis Outline

There are five chapters included in this thesis. Chapter I is the Introduction which covers the project overview, problem statement, objectives and scope of work.

Chapter II presents the Literature Review on related theories and previous related work to this project. The theories part discusses on the overview of the WSN, the MPEG-4 format, the optimized MPEG-4 data, and TelG software and hardware architecture.

Chapter III is the Methodology which includes planning and implementation process of the project. Under planning, the state diagram and the flow chart are elaborated in detail. Implementation includes the discussion on the testing methodology used in this project.

Chapter IV consists of result and discussions. It covered the experimental results from the project. This chapter will also discuss the findings observed from the results.

Chapter V is the conclusion and future work. This chapter concludes the thesis and suggestions of future development.

REFERENCES

1. F. Yunus, S. H. S. Ariffin, S.K. Syed-Yusof, N.N. Ismail, A. H. F. A. Hamid, N. Fisal, "Optimum Parameters for MPEG-4 Data over Wireless Sensor Network", International Journal of Engineering & Technology (0975-4024), Vol. 5 Issue 5, p4501-4513. 13p, 2013.
2. A. Alkhatib, G. S. Baicher, "Wireless Sensor Network Architecture", International Conference on Computer Networks and Communication Systems (CNCS 2012) IPCSIT vol.35(2012) IACSIT Press, Singapore, 2012.
3. Part 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks (LR-WPANs), IEEE Standard 802.15.4-2006, 2006.
4. Information Technology - Coding of Moving Pictures and Associated Audio for Digital Storage Media up to about 1.5 Mbit/s: Part 2 - Video, International Standard ISO/IEC 13818-3:1994(E), 1994.
5. Information Technology - Generic Coding of Moving Pictures and Associated Audio: Part 2 - Video, International Standard ISO/IEC 13818-2: 1995 (E), 1995.

6. L. Chariglione, "MPEG and Multimedia Communications", IEEE Transactions on Circuits and Systems for Video Technology, Vol. 7, No. 1, pp. 5-18, Feb. 1997.
7. S.Prasanna, R. Srinivasa, "An Overview of Wireless Sensor Networks Applications and Security", International Journal of Soft Computing and Engineering (IJSCE) ISSN: 2231-2307, Volume-2, Issue-2, May 2012.
8. T.Ebrahimi, C. Horne, "MPEG-4 natural video coding: An overview", Signal Processing: Image Communication, Elsevier Science, Vol. 15, pp. 365-385, (2000)
9. I. E. G. Richardson, "H.264 & MPEG-4 Video Compression: Video Coding for Next Generation Multimedia", Wiley, 2003.
10. R.A. Rashid, N. Fisal, A.H.F.A. Hamid, "Wireless Multimedia Sensor Network Platform for Low Rate Image/Video Streaming", Jurnal Teknologi. Special Edition (Instrumentation and Sensor Technology), pp.54:1-12, 2011.
11. Atmel Corp. 2009. 8-bit Microcontroller with 16/32/64K Bytes in-System Programmable Flash. San Jose California: Datasheet.
12. MaxStream Inc. 2005. XBee™/XBee-PRO™ OEM RF Modules. Lindon UT. Product Manual.
13. M. Smart and B. Keepence, " Understanding MPEG-4", White paper IC-COD-REP012, *Indigo Vision*, 2008.
14. A. Huszak and S. Imre, "Analysing GOP Structure and Packet Loss Effects on Error Propagation in MPEG-4 Video Streams," Proceedings of the 4th International Symposium on Communications, Control and Signal Processing, ISCCSP, 2010.

15. A.Garcia-Sanchez, F.Garcia-Sanchez, J.Garcia-Haro, "Feasibility Study of MPEG-4 Transmission on IEEE 802.15.4 Networks", International Conference on Wireless and Mobile Computing, Networking and Communication, 2008.

16. A.Garcia-Sanchez, F.Garcia-Sanchez, J.Garcia-Haro, "A Cross-Layer Solution for Enabling Real-Time Video Transmission over IEEE 802.15.4 Networks", *Multimedia Tools and Application*, 2010.

17. P. Shin and K. Chung, "A Cross-Layer Based Rate Control Scheme for MPEG-4 Video Transmission by Using Efficient Bandwidth Estimation in IEEE 802.11e", International conference Information Networking ICOIN, 2008.

18. Z. Ma, J. Zhou, and T. Wu, "A cross-layer QoS scheme for MPEG-4 streams", Wireless Communications, Networking and Information Security (WCNIS), 2010 IEEE International Conference, pp. 392-396, 2010.

19. Abdul Hadi Fikri Bin Abdul Hamid, Rozeha A. Rashid, Norsheila Fisal, S. K. S. Yusof, S. H. S. Ariffin Liza Latiff. "Development of IEEE802.15.4 based Wireless Sensor Network Platform for Image Transmission." *International Journal of Engineering & Technology IJET*. 9(10):112-118, 2009.

20. Y. Xiao, X. Du, F. Hu, and J. Zhang, "A Cross-layer Approach for Frame Transmissions of MPEG-4 over the IEEE 802.11e Wireless Local Area Networks", Wireless Communication and Networking Conference, pp. 1728-1733, 2008.

21. M.R. Garey, and D.S. Johnson, *Computers and Intractability: a Guide to the Theory of NP-completeness*, Freeman, San Francisco, CA, 1979.

22. J. Duato, "A necessary and sufficient condition for deadlock-free routing in cut-through and store-and-forward networks," *IEEE Trans Parallel and Distrib. Systems*, vol. 7, no. 8, pp. 841-854, 1996.
23. C. Smythe, "ISO 8802/5 token ring local area networks," *Elect. & Communic. Eng. J.*, vol. 11, no. 4, pp. 195-207, 1999.
24. R. Bronson and G. Naadimuthu, *Operations Research*, 2 ed., Schaum's Outlines, McGraw Hill, New York, 1997.
25. F.L. Lewis and V.L. Syrmos, *Optimal Control*, 2nd ed., Wiley, New York, 1995.
26. P.R. Kumar, "New technological vistas for systems and control: the example of wireless networks," *IEEE Control Systems Magazine*, pp. 24-37, Feb. 2001.
27. E. Altman, T. Basar, T. Jimenez, and N. Shimkin, "Competitive routing in networks with polynomial costs," *IEEE Trans. Automat. Control*, vol. 47, no. 1, pp. 92-96, 2002.