IMAGE-BASED OBJECT DETECTION AND IDENTIFICATION

SALIM MOHAMMED HUMAID ALWAILI

A thesis submitted in fulfillment of the requirements for the award of the degree of Master of Science (Remote Sensing)

Faculty of Geoinformation and Science Engineering Universiti Teknologi Malaysia

May 2007

To the spirit of my beloved father, To my mother, To my wife Ziyana, And to my kids Bader, Ahmed, and Mohammed

ACKNOWLEDGEMENT

I wish to express my sincere appreciation to the Head of Remote Sensing section Professor Dr. Mazlan Bin Hashim, for his encouragement, guidance, patience, and support. I will always be indebted to him for her persistence in ensuring that this thesis is up to the academic world standards. I am also very thankful to my supervisor En. Samsudin Bin Ahmad for his guidance.

I am also thankful to the staff in the Faculty of Geoinformation and Science Engineering for their assistance during the past three semesters.

Last, but not least, I am extremely grateful and indebted to my sponsors, the National Survey Authority. In particular, I would like to thank the Head of the NSA Brigadier Mohammed Said Al-Kharousi and the Director of Support Services.

ABSTRACT

Object detection is a process of identifying and locating objects in image scene. It is a process of combining digital image processing and computer vision. There are two main approaches for object detection, namely contour-based and region-based detection for both approaches. Segmentation plays an important role in object-detection. Detection and extraction of the spatial and spectral responses of different targets of interest could only be carried out with different approaches. In this study, object-based detection is carried out to identify and recognize typical military targets (Plane1, Plane2, Tank) located on natural background using spectral and spatial approaches. This is useful in military intelligence or strategic planning where it assists in identifying the aforementioned targets. In the spectral-based object detection, the spectroradiometer readings of the targets are individually observed on different backgrounds (white platform used as calibration plane, sand and camouflage). These spectroradiometer observations are reduced and examined for forming the unique spectral signatures of the targets. Spatial-characteristics of the targets are also examined using object-based detection where multi-resolution segmentation were employed for this purpose. Results of the study obtained that all the three targets can be extracted with more than 20% differentiation, while the spectral characteristics of the targets are also good indications for object detection with overall accuracy of RMSE = ± 0.6 .

ABSTRAK

Pengesanan objek daripada imej adalah satu proses di mana objek sasaran dikenalpasti dan ditentukan. Proses ini menggabungkan pemprosesan imej digital dengan ' computer vision'. Terdapat dua pendekatam utama dalam proses pengesanan objek iaitu Berdasarkan Kontur dan Berdasarkan Bahagian. Teknik Segmentasi merupakan teknik utama bagi kedua-dua pendekatan ini. Pengesanan penentuan elemen spatial dan spektral objek sasaran adalah fokus utama dalam kajian ini, di mana sasaran utama yang digunakan mempunyai kepentingan ketenteraan, iaitu Kapal Terbang Pejuang 1, Kapal Terbang Pejuang 2 dan Kereta Kebal. Bagi Pendekatan Spektral, cerapan alat spektroradiometer dijalankan bagi semua objek sasaran dengan pelbagai variasi latarbelakang. Terdiri daripada permukaan putih yang digunakan sebagai rujukan kalibrasi, latarbelakang pasir dan bahan penyamaran. Cerapan spektroradiometer ini kemudiannya dilaraskan sebelum pencarian ciri-ciri 'spectral signatures' sasaran dibuat. Penentuan ciri-ciri spatial objek dijalankan dengan menggunakan 'multi-resolution segmentation'. Hasil daripada kajian ini mendapati kaedah spektral boleh digunakan untuk mengenalpasti sasaran yang diuji dengan ketepatan RMSE = ± 0.6 .

TABLE OF CONTENTS

CHAPTER		TITLE	PAGE		
	TITLE				
	DECLEARATION				
	DEI	DICATION	iii		
	AK	NOWLEDGMENT	iv		
	ABSTRACT ABSTRAK				
	TABLE OF CONTENTS				
	LISTS OF TABLES				
	LIS	T OF FIGURES	X		
	LIS	T OF APPENDIX	xi		
1	INT	1			
	1.1	The Importance of Object Detection	1		
	1.2	Problem Statement	4		
	1.3	Objectives	4		
	1.4	Scope of the Study	5		
	1.5	Significance of the Research	6		
	1.6	Chapter Organization	6		
2	OB.	IECT DETECTION APPROACHES AND			
	API	7			
	2.1	Introduction	7		
	2.2	Approaches to Object Detection and Recognition	7		
	2.3	Image Segmentation	11		
		2.3.1 Contour Segmentation	11		
		2.3.2 Region Segmentation	12		
		2.3.3 Object Oriented Approach	14		
	2.4	Reflectance and Object Detection	14		

	2.5	Auton	natic Obj	ect Detection	15
	2.6	Summ	nary		17
3	ME'	THOD	OLOGY		18
	3.1	Introd	uction		18
	3.2	Mater	ials		20
		3.2.1	Target S	Sets	20
		3.2.2	The Da	ta Capture	20
			3.2.2.1	Digital Camera Nikon Coolpix 7900	21
			3.2.2.2	Spectro-radiometer	21
			3.2.2.3	Images of Target Sets	21
			3.2.2.4	Reflectance Measurement	24
	3.3	Data I	Pre-proce	ssing	25
		3.3.1	Radiom	eter Correction	25
		3.3.2	Geomet	ric Rectification	27
		3.3.3	Image S	Segmentation	28
		3.3.4	Multire	solution Segmentation	29
			3.3.4.1	Classification of Segmented Image	30
			3.3.4.2	Classification Based Segmentation	33
			3.3.4.3	Feature Space Optimization	34
4	RES	SULTS	AND AN	JALYSIS	35
	4.1	Introd	uction		35
	4.2	Objec	t Detectio	on Based on Reflectance	36
	4.3	Spect	ral Assess	sment	41
	4.4	Segme	entation I	Results	43
	4.5	Asses	sment of	Object Detection Based on Spatial Entities	46
	4.6	Discu	ssion		48
5	COI	NCLUS	SIONS A	ND RECOMMENDATIONS	50
	5.1	Concl	usions		50
	5.2	Recor	nmendati	ons	51

LIST OF TABLES

TABLE No.	TITLE	PAGE
3.1	Descriptive statistics and the amount shift applied to the	26
	red and blue bands to normalize radiometric effects	
3.2	The result of rectification process	27
3.3	Signatures of the class of interest of the target set	32
4.1	Separation of spectral reflectance curve at RGB bands of	37
	the targets for the white board set	
4.2	Separation of spectral reflectance curve at RGB bands of	39
	the targets for the sand background set	
4.3	Separation of spectral reflectance curve at RGB bands of	41
	the targets for the camouflage set	
4.4	Assessment for the spectral reflectance curves for the 3	42
	target sets for the RGB bands	
4.5	Overall assessment for the spectral reflectance curves for	42
	the 3 target sets for the RGB bands	
4.6	Accuracy assessment for the segmentation process	45
4.7	Results of feature space optimization	45
4.8	A matrix for feature space optimization	46
4.9	Results of spatial assessment	48

TABLE OF FIGURES

FIGURE No.	TITLE	PAGE
2.1	Block diagram of object detection	10
2.2	Region-based segmentation diagram	13
2.3	Automatic Target Detection Process	16
3.1	Flow chart for the methodology carried out in the study	19
3.2	The target set	22
3.3	Configuration of spectro-radiometer with respect with	25
	respect target platform for calibration purpose	
3.4	The histograms for the RGB bands of the calibration	26
	board	
3.5	The image segmentation process in the eCognition	29
	system adopted in the study	
3.6	Image classification	32
4.1	Reflectance curve for the white board target set	36
4.2	Reflectance curve for the sand target set	38
4.3	Reflectance curve for the camouflage target set	40
4.4	Results of the object detection using image segmentation	43
4.5	Assessment of spatial entities based on generated	47
	template	

LIST OF APPENDIXES

APPENDIX No.	TITLE	PAGE
APPENDIX I	Description of Generic Shape Features	57

CHAPTER 1

INTRODUCTION

1.1 The Importance of Object Detection

Object detection is a process of identifying and locating objects in a scene. It is a process of combining digital image processing and computer vision (Gonzalez *et al*, 2001). The main goal of an object detection process is to detect and identify objects in a scene. Selected parameters, which are commonly used for object detection such as the interpretation parameters aimed to recognizes and identify objects, will be described in the following sections. The commonly used parameters in object detection for remote sensing images are elaborated in the following section.

Image-based object detection has been widely used in the remote sensing field. Skilled interpreter and computer-assisted interpretation are two essential factors in digital-recognition objects. In the manual-interpretation approach, seven interpretation elements are usually used to interpret images; namely size, shape, shadow, tone, color, texture and pattern. The size of an object is defined by the most commonly parameters such as length, area, perimeter, area and volume. The shape of an object is determined by its geometric characteristics such as linear, curvilinear, circular, elliptical, radial, square, etc. The shadow is a silhouette caused by side-illuminated objects, often. The image tone of an object refers to the gray scale of the image, typically ranging from bright to total dark. It is used in extracting the scene of the height or relief of the object of interest. The color tone is also used in the interpretation of color images. Texture is a group of small patterns often used in extracting groups of objects. Pattern is usually used in the spatial arrangement of

2

objects on the ground (systematic, unsystematic, etc.). Apart from the above seven interpretation elements, other elements are used in manual interpretation such as the associated relationships as the combination of the elements, geographic characteristics and configuration of the objects. A well-trained interpreter can interpret the image using the above elements easily as a dichotomous key (Jensen 2000).

The use of digital interpretation approach is widely used in various applications. In this approach, the computer systems (including appropriate software) are used to extract object features using basic interpretation elements. The most common elements used for digital recognition are tone, color and texture. Tone and color of individuals in the scene are the two dominant interpretation elements used in the computer-based object detection based on statistical pattern recognition techniques (Hardin and Thomson, 1992). At present, both the manual and computer-based interpretation are used hand-in-hand, where each of these approaches compliment each other as fully computer-based interpretation is rather limited due to each of the dedicated systems being built for specific purposes.

The image-based object detection has formed wide applications, which includes military and biomedical imaging. In military applications, recognizing and detecting of targets within specific areas has been the main focus. Such targets are crucial inputs into intelligence planning and monitoring. In the biomedical applications, object-detection has been carried out for assisting medical practitioners in diagnosis of diseases/sickness (Yuan-Hui Yu and Chin-Chen Chang, 2006). These include also recognition of fingerprints and eye pupil as biometric identification, apart from the study of human perception to vision and recognition ability.

Image-based object detection and recognition is important, particularly for intelligence where it is widely used in the planning of military operations. It is also very important for assisting pilots, tanker operators, and shooters to detect and identify targets of interest. Using this technique the operator could identify the target of interest faster and more precisely. Computer-assisted object detection could be used for automatic detection of any object or target of interest. This is referred to as automatic target recognition (ATR), which generally refers to the self-directed or aided target detection and recognition by computer processing of images from a variety of sensors such as forward looking infrared (FLIR), synthetic aperture radar (SAR), inverse synthetic aperture radar (ISAR), laser radar (LADAR), millimeter wave (MMW) radar, multispectral/ hyperspectral sensors, low-light television (LLTV), video, etc. ATR is an extremely important approach that is useful for targeting and surveillance missions of defense weapon systems operating from a variety of platforms (BHANU et al, 1997).

Automatic target recognition aims to reduce the workload of human operators such as image analysts, pilots, and tankers, who are tasked with a large scope of activities ranging from assessing the battlefield/battlespace situation over large areas and volumes to targeting individual targets on land, sea, or air. It is also used to reacquire targets when used on unmanned lethal weapon systems such as missiles. The effectiveness and efficiency of locating and detecting targets is greatly increased with this application (Clark et al, 1997).

In the context of medical imaging, object detection is widely used in detecting symptoms peculiar to disease or related to malfunction or strange organs. It uses the concept of detecting foreign bodies inside the human body. Yfantis et al. (2000) proposed an algorithm for detecting cancer using ultrasound image. The algorithm is based on calculating a number of attributes in the section of interest in the image and finding the distance in the multivariate space of the vector of attributes in the section from 2 predetermined centroids (cancerous and non-cancerous). If the distance from the non-cancerous centroid is smaller than the distance from the cancerous centroid the region is classified as non-cancerous, otherwise it is cancerous. Gender classification could be also done with the help of object detection using face detection and principal component analysis technique (Zehang et al, 2002).

In this study, artificial steel objects on a sand background will be detected using the object-oriented approach and spectral reflectance characteristics. The image sets in this study are captured using digital optical camera in a controlled laboratory environment where a spectroradiometer device is used for acquiring reflectance measurements from the object targets.

1.2 Problem Statement

Remotely sensed images are formed as the resultant of the interaction of electromagnetic radiation (EMR) with the earth surface. The magnitudes of these interactions are dependent on the wavelength of the EMR and the characteristics of the earth's surface. Extraction of any feature from these images can therefore be made based on the spectral and spatial entities of the EMR interactions. Two typical algorithms established for object detection in remote sensing were based on both these the spatial and spectral interactions. In this study, the region-based algorithm is used for detecting and identifying spatial entities (shape and area), while the spectral reflectance characteristics of the objects are used for recognizing the target of interest.

1.3 Objectives

The objectives of this study are:

- To detect and extract selected targets from remotely sensed images based on the spectral and spatial characteristics;
- (2) To perform accuracy assessment of the objects extracted in objective (1).

1.4 Scope of the Study

The scopes of the study are as follows:

- (i) The images used are captured in the laboratory using a digital camera, of a set of known miniature military targets with sand background. The targets comprised two steel model air fighters (Plane1, Plane2) and one steel model tank.
- (ii) The images of the targets are captured within the visible spectrum of EMR at different sets:
 - (a) The white board, captured as a control;
 - (b) Targets on the white board (capturing reflectance for individual target);
 - (c) Sand reflectance;
 - (d) Camouflage reflectance;
 - (e) Targets on sand (capturing reflectance for individual target); and
 - (f) Reflectance for the targets covered with camouflage.
- (iii)The corresponding spectral responses of the targets with the background were also observed using spectroradiometer in the range of 400-700nm, equivalent to the wavelength of the camera used to capture the digital image.
- (iv)The spectral responses of the targets are reduced and analyzed for the absolute responses within the given wavelength range for determining the best differentiation among the targets.
- (v) The detection and extraction of objects using spectral entities is performed based on region growing and region merging algorithm where it has to satisfy the condition (Hsiao et al, 2005).

1.5 Significance of the Research

Detection and extracting the spatial and spectral responses of different targets are usually done through different approaches. This research helps users to identify and recognize different kinds of targets (Plane1, Plane2, Tank), which are sited on natural background using spectral and spatial approaches. It is useful for military purposes and could be utilized in different applications.

1.6 Chapter Organization

This report consists of five chapters. Chapter 1 is an introduction and background of the project. Chapter 2 reviews some previous similar works for animage-based object detection/recognition. This includes segmentation approaches, the importance of reflectance in object detection and automatic target detection.

The methodology of the study is described in Chapter 3, where the materials and method used in this study is elaborated. The results of the study are presented, analyzed and discussed in Chapter 4. Finally, Chapter 5 concludes the findings of this study, apart from highlighting the future recommendations for improving this study.