

EVALUATION OF WATERFLOODING USING CARBONATED WATER FOR
OIL RECOVERY

MOHAMAD FAIZUL BIN MAT ALI

A thesis submitted in fulfilment of the
requirements for the award for the degree of
Master of Engineering (Petroleum)

Faculty of Petroleum and Renewable Energy Engineering
Universiti Teknologi Malaysia

MAY 2015

This thesis is dedicated to:

My wife Noraini binti Ibrahim

My family especially for my late mother Adima binti Lin

And last but not least for my future kids

ACKNOWLEDGEMNT

In the name of Allah the Most Gracious and the Most Merciful, I would like to express my sincere gratitude to my thesis supervisor Prof. Dr. Radzuan bin Junin for the continuous support of my master study and research, for his patience, motivation, enthusiasm, and immense knowledge. His guidance helped me in all completing this work.

Besides my advisor, my sincere thanks also go to Universiti Teknologi Malaysia (UTM) and Research Management Center (RMC) for supporting this study, researchers and academicians for their contribution towards my research including the understanding and thoughts. Last but not least, I would like to thank my family especially my parents and my wife for supporting me spiritually throughout my life.

ABSTRACT

Malaysian oilfields especially in Malay basin are showing the signs of maturity phase that involves high water-cut and pressure declining, after more than 30 years of extensive exploration and production. In recent development, Malaysia underwent Water Alternating Gas (WAG) process in the Tapis field to improve oil recovery. However, WAG, which utilises carbon dioxide in the Enhanced Oil Recovery (EOR) process has a few flaws that includes poor sweep efficiency due to high mobility ratio of gas and oil, which promotes an early breakthrough. Therefore, a concept of carbonated water injection (CWI) to utilise carbon dioxide was applied. The aim of this study was to measure the suitability of carbonated water to be implemented in oil recovery at high pressure condition, simulating reservoir condition. The simulated reservoir condition was made using a coiled sand pack filled with rounded grain glass beads and pressurised to 2000 psi with 60 °C as a controlled condition. A series of displacement test to investigate the range of recovery improvement at different carbon dioxide concentrations were carried out using different recovery mode stages. Wettability analysis has also been done to analyse the wettability of sandpack treated with carbonated water. The result from this study has shown a positive improvement in oil recovery with 50% concentration of carbon dioxide showed the highest recovery where it recovered additional 28% oil in secondary recovery and 16% recovery in tertiary recovery. Carbonated water also has the ability to alter the wettability of sandpack and sandstone rock to become more water-wet condition. Moreover, carbonated water was more suitable to be in the secondary recovery process, replacing the plain waterflood process, which is a common practice in every field. As a conclusion, carbonated water has a high potential in oil recovery processes, in both secondary and tertiary stages.

ABSTRAK

Lapangan minyak di Malaysia terutama sekali di Lembangan Melayu telah menunjukkan fasa kematangan, misalnya nisbah air yang tinggi dan juga pengurangan tekanan. Dalam perkembangan terbaharu, Malaysia telah mula menjalankan projek Perolehan Minyak Tertingkat di lapangan minyak Tapis yang menggunakan cara suntikan selangan air dan gas. Namun begitu, aplikasi ini mempunyai beberapa kelemahan, antaranya perolehan yang rendah disebabkan oleh nisbah mobiliti gas dan minyak yang tinggi menyebabkan perlepasan gas pramatang. Oleh itu, konsep suntikan air berkarbonat digunakan untuk mengatasi masalah ini. Kajian ini dilakukan bertujuan untuk menilai kesesuaian cara suntikan air berkarbonat untuk diaplikasikan pada keadaan tekanan tinggi sesuai dengan keadaan reservoir minyak. Model reservoir minyak telah dibina dengan menggunakan padatan pasir pada tekanan 2000 psi dan suhu 60 °C. Beberapa siri ujian sesaran pada kepekatan karbon dioksida yang berbeza telah dilaksanakan bagi menyiasat julat keupayaan perolehan minyak pada peringkat perolehan yang berbeza. Analisis kebolehasan suntikan air berkarbonat juga telah dijalankan bagi mengenal pasti keterbasahan padatan pasir dan batu pasir yang digunakan dalam kajian. Hasil kajian menunjukkan bahawa air berkarbonat dengan ketepuan 50% telah menghasilkan perolehan minyak yang tertinggi dengan tambahan perolehan sebanyak 28% menerusi perolehan Sekunder dan 16% menerusi perolehan Tertier. Kajian ini juga mendapati bahawa air berkarbonat mempunyai kebolehan untuk meningkatkan lagi keterbasahan mampatan pasir dan batu pasir. Selain itu air berkarbonat adalah lebih sesuai digunakan pada proses perolehan Sekunder bagi menggantikan proses banjir air yang digunakan selama ini. Sebagai rumusan, suntikan air berkarbonat didapati mempunyai potensi yang baik dalam proses perolehan minyak yang mencakupi kedua-dua perolehan Sekunder dan perolehan Tertier.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xii
	LIST OF EQUATIONS	xiii
	LIST OF ABBREVIATION	xiv
	NOMENCLATURES	xv
	LIST OF APPENDICES	xvii
1	INTRODUCTION	
	1.1 Introduction	1
	1.2 Problem Statement	2
	1.3 Objective	3
	1.4 Scope and Limitation of Research	4
	1.5 Significance of Study	5
2	LITERATURE REVIEW	
	2.1 Enhanced Oil Recovery	6
	2.1.1 EOR by Lithology	6
	2.1.2 EOR by Technology	7

2.2	Carbon Dioxide Enhance Oil Recovery Technology	9
2.3	Carbonated Waterflood Technology	10
2.4	Factor Controlling Carbonated Water Displacement Efficiency	12
2.4.1	Miscibility	12
2.4.2	Sweep Efficiency	13
2.4.3	Wettability concepts	14
2.4.4	Water Salinity	15
2.4.5	Mobility Ratio	17
2.5	Carbon Dioxide Fluid Properties	18
2.6	Relative Permeability	20
2.7	Summary	21
3	METHODOLOGY	
3.1	Introduction	22
3.2	Research Activity Workflow	22
3.3	Materials	24
3.4	Apparatus	24
3.5	Fluid Preparation Procedures	25
3.5.1	Carbonated Water.	25
3.5.2	Crude Oil	26
3.5.3	Saline Solution	26
3.6	Displacement Study Equipment	27
3.6.1	Sandpack	27
3.6.2	Displacement Pump	28
3.6.3	Oil Bath	30
3.6.4	Transfer Bottle	31
3.7	Experimental Setup and Procedures	31
3.7.1	Experimental Procedure for Displacement Tests	32
3.7.2	Experimental Procedure for Cleaning Process	34
3.7.3	Experimental Procedure for Porosity Measurement	35

3.7.4	Permeability Measurement	36
3.7.5	Minimum Miscibility Pressure (MMP) Estimation	36
3.7.6	Experimental Procedure for Density Measurement	37
3.8	Injection Carbonated Water Schedule	38
3.9	Wettability Test Procedure	39
3.9.1	Wettability Phase at Different Carbon Dioxide Concentrations	39
3.9.2	Wettability Alteration at Room Temperature	40
4	RESULTS AND DISCUSSION	
4.1	Introduction	41
4.2	Sandpack properties	42
4.3	Oil properties	42
4.4	Displacement Test Results	43
4.4.1	15% CO ₂ Carbonated water Displacement Result	46
4.4.2	30% CO ₂ Carbonated Water Displacement Result	47
4.4.3	40% CO ₂ Carbonated Water Displacement Result	48
4.4.4	50% CO ₂ Carbonated Water Displacement Result	49
4.4.5	Water Breakthrough Analysis	50
4.5	Comparison between Highest and Lowest Carbonated Water Recovery	51
4.6	Minimum Miscibility Pressure	52
4.7	Wettability Inference from Oil-Water Relative Permeability	53
4.7.1	Multiple Carbon Dioxide Concentrations	54
4.8	Sessile Drop Wettability Determination	61
4.9	Recovery Mode Analysis	64
5	CONCLUSIONS AND RECOMMENDATIONS	
5.1	Conclusions	65
5.2	Recommendations	66

REFERENCES	68
APPENDICES	75

LIST OF TABLES

NO. OF TABLE	TITLE	PAGE
2.1	Method for Estimating Miscibility Pressure	13
2.2	Type of Wettability	14
2.3	Solubility of Carbon Dioxide in water at High Temperature and Pressure	16
2.4	Properties of Carbon Dioxide	19
3.1	Flow rate of displacement pump (cc/hour)	30
3.2	Carbonated water injection series	38
4.1	Properties of coiled beadpack	42
4.2	Properties of Crude Oil	43
4.3	Test results of carbonated water recovery process for secondary and tertiary mode	45
4.4	Comparison between Highest and Lowest Oil Recovery	52
4.5	Summary of Estimating MMP	53
4.6	Wettability Phase Inference from Two Phases Relative Permeability	54
4.7	Oil Recovered During Wettability Study under Reservoir Conditions	55
4.8	Summary of Relative Permeability Analysis	61
4.9	Contact Angle-Wettability Relationship	61
4.10	Sessile Drop Contact Angle Result	62

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Phase Diagram of Pure Carbon Dioxide	19
3.1	Research Activity Workflow	23
3.2	A 60ft Coiled Sandpack	27
3.3	(a) Plain View of Displacement Pump (b) Displacement Pump Used as Injector (c) Lever of Displacement Pump	29
3.4	Oil Bath with Temperature Controller	30
3.5	Stainless Steel Transfer Bottle	31
3.6	Schematic Diagram for Displacement Study	32
3.7	Flow Diagram for Displacement Test Study	34
4.1	Test Result Of Oil Recovery Improvement	44
4.2	Oil Recovery at 15% CO ₂ Concentration	46
4.3	Oil Recovery at 30% CO ₂ Concentration	47
4.4	Oil Recovery at 40% CO ₂ Concentration	48
4.5	Oil Recovery at 50% CO ₂ Concentration	49
4.6	Water Breakthroughs during Recovery Process	50
4.7	Relative Permeability of Waterflooding Process	56
4.8	Relative Permeability of 15% CO ₂ Concentration	57
4.9	Relative Permeability of 30% CO ₂ Concentration	58
4.10	Relative Permeability of 40% CO ₂ Concentration	59
4.11	Relative Permeability of 50% CO ₂ Concentration	60
4.12	Contact Angle Behaviour at Various pH Values	63

LIST OF EQUATIONS

EQUATIONS	TITLE	PAGE
2.1	Carbon Dioxide Equilibrium State in High Pressure	17
2.2	Carbon Dioxide Solubility Reaction	17
2.3	Mobility of Oil	17
2.4	Mobility of Water	17
2.5	Mobility of Gas	17
2.6	Mobility Ratio	18
2.7	Darcy Equation of Linear Viscous Flow of Oil	20
2.8	Darcy Equation of Gravity Flow of Oil	20
3.1	Bulk Volume Calculation	35
3.2	Porosity Calculation	35
3.3	Darcy Equation for Permeability	36
3.4	Crude Oil Specific Gravity Determination	37
3.5	Degree API Determination	37
3.6	Molecular Weight Determinations	37
3.7	MMP Determinations	37
3.8	Density Equation	38
3.9	Volume Oil Saturation	40
4.1	Honopour's Correlation for Water Relative Permeability of Sand Water-Wet	54
4.2	Honopour's Correlation for Water Relative Permeability of Sand Oil-Wet	54
4.3	Ionic Equations of Carbonic acid	63

LIST OF ABBREVIATIONS

ASP	-	Alkali Surfactant Polymer
BPD	-	Barrel Per Day
BSTB	-	Billion Stock Tank Barrels
BT	-	Water Breakthrough
CWI	-	Carbonated Water Injection
EOR	-	Enhanced Oil Recovery
IFT	-	Interfacial Tension
MEOR	-	Microbial Enhanced Oil Recovery
MMP	-	Minimum Miscibility Pressure
OOIP	-	Original Oil In Place
PGAW	-	Polymer Gas Alternate Water
PV	-	Pore Volume
SAGD	-	Steam Assisted Gravity Drainage
STOIP	-	Stock Tank Oil Initially in Place
SWACO ₂	-	Simultaneous Water-Carbon Dioxide
WACO ₂	-	Water Alternating Carbon Dioxide
WAG	-	Water Alternating Gas
WF	-	Waterflooding

NOMENCLATURE

$^{\circ}\text{API}$	-	Degree API of Oil
$^{\circ}\text{C}$	-	Degree Celsius
ϕ	-	Porosity
$\Delta P/L$	-	Pressure Gradient
μ_0	-	Oil Viscosity, cp
λ_g	-	Gas Mobility, md/cp
λ_o	-	Oil Mobility, md/cp
λ_w	-	Water Mobility, md/cp
ρ_o	-	Oil Density, g/cc
ρ_w	-	Water Density, g/cc
γ	-	Specific Gravity
A	-	Cross sectional Area, ft ²
cc	-	Cubic Centimeter
cp	-	Centipoise
ft	-	feet
g	-	Gravity Acceleration, m/s ²
ID	-	Internal Diameter, in
K	-	Permeability, md
K_{abs}	-	Absolute Permeability, md
K_g	-	Effective Gas Permeability, md
K_o	-	Effective Oil Permeability, md
K_w	-	Effective Water Permeability, md
K_{rg}	-	Relative Gas Permeability
K_{ro}	-	Relative Oil Permeability

K_{rw}	-	Relative Water Permeability
L	-	Length, ft
M	-	Mobility Ratio
MW	-	Molecular Weight, lb/mol
OD	-	Outer Diameter, in
psi	-	Pressure, pound per square inch
T	-	Reservoir Temperature, °C
V_b	-	Bulk Volume, cc
V_p	-	Pore Volume, cc

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Production Data for Secondary mode and tertiary modes	75-83
B	MMP Estimation	84
C	Relative Permeability Data	85-89

CHAPTER 1

INTRODUCTION

1.1 Research Background

Recent trend in Malaysia has shown a promising future for Enhanced Oil Recovery (EOR) technology with the latest occurrence of Tapis EOR project. Tapis EOR project, which started in 2014, will become the first EOR project that will be done in Malaysia. Tapis field will be implementing Water Alternating Gas - Enhanced Oil Recovery(WAG-EOR) method for recovering unexpended oil, which uses Carbon Dioxide (CO₂) as the alternating gas. Generally, CO₂ gas was being used in this process since CO₂ gas is highly soluble in oil (Nasehi and Asghari, 2010). Furthermore, CO₂ gas is readily accessible in excess amount, thus, this will reduces the cost for obtaining CO₂.

However, the utilisation of CO₂ gas in EOR as injection technology has a shortcoming. It has been widely known that the implementation of CO₂ gas in EOR technology will face one major dilemma, which is premature breach of gas (Riazi *et al.*, 2009). Thus, maintaining a small early breakthrough will become the number one task when applying gases into EOR process. This will also become the problem that will be tackled when Tapis WAG-EOR process begins.

In recent years, CO₂ gas has become an increasingly popular research area in EOR technology. The application of CO₂ gas in EOR technology has been utilised all around the world. Research in improving CO₂ technology has been showing much

improvements toward the application of CO₂ gas in EOR project (Dong *et al.*, 2011a). One of the improvements that have been arising from CO₂ technology problem was the application of carbonated water (Dong *et al.*, 2011b). This technology has been manipulating the ability of CO₂ to miscible with oil and water to enhance oil production especially in the EOR process.

This recent development should be taken into account in dealing with CO₂ project. Studies should be carried out to investigate the suitability of carbonated water as a new option in EOR especially for the future Malaysia EOR project. Laboratory scale research should be designed and carried out in order to evaluate carbonated water for future application. This will enables us to further understand the effect of carbonated water towards oil recovery improvement.

1.2 Problem Statement

One of the major problems in gas especially CO₂-EOR project is the early CO₂ breakthrough due to channelling of CO₂ via reservoir fluids. The channelling of CO₂ in reservoir fluid was due to the properties of gas that travels in the easy path of reservoir structure. This behaviour will caused fingering effects that eventually produce poor sweep efficiency. Several strategies have been introduced including Carbonated Water Injection (CWI) in improving injection performance compared to other conventional CO₂ injection (Sohrabi *et al.*, 2011). CWI method had gained respect as an economically convenient way of augmenting hydrocarbon production. Hence, it is essential to understand the property changes during CWI to optimise the efficiency of the process as well as maximising oil production.

Improvement in sweep efficiency of gas injection process has become one of the objectives in EOR study. It was known that gas injection has major problems associated with it such as the early breakthrough due to fingering. Fingering effect has caused

shorter contact time with targeted crude oil in the reservoirs. This was also common when using CO₂ injection process, which resulted in poor areal sweeps efficiency that leads to an early breakthrough.

The next improvement that should be highlighted is the wettability changes in CWI. Wettability of reservoir rock is one of the parameters that control the remaining oil-in-place. Thus, the understanding of wettability changes during displacement process is an important subject in the displacement study for recovering oil efficiently. Hence, a study focusing on the wettability change of carbonated water towards reservoir rock will be carried out.

Last but not least, a suitable stage in introducing carbonated water into reservoir also plays an important role in EOR. Some researchers have suggested an application of carbonated water in secondary recovery (Asghari *et al.*, 2009) while others have proposed carbonated water as a method in tertiary recovery stage (Kechut *et al.*, 2010). Since carbonated water will be applying the same concept of waterflooding process, thus, a clear line on implementation stages should be addressed so the recovery of residual oil can be improved.

1.3 Objectives

Based on this research, the objectives of this study are:

1. To investigate the effect of CO₂ concentration in carbonated water towards oil recovery.
2. To evaluate the wettability behaviour of sandstone rock by measuring water-advancing contact angle in different rock-water-oil systems using sessile drop method at different CO₂ concentrations of carbonated water.

3. To compare oil recovery obtained by injecting the carbonated water to sandpack with that obtained by implementing secondary stage recovery and tertiary stage recovery.

1.4 Scope and Limitation of Research

This research concentrates on investigating the potential of carbonated water as an EOR method that could be used in Malaysian oilfields. Throughout the study, the temperature and pressure are constantly at 60 °C and 1000-2000 psi, respectively. The temperature was chosen as to assimilate the condition of the Malay Basin, which has a geothermal gradient of 5 °C /328 ft (Tjia and Liew, 1996). The pressure was chosen to simulate oilfield pressure, which has a depth of 4000-6300 ft. All results in this research are only applicable on the condition that has been set during the study.

For the purpose of this study, a salinity of simulated connate water of 10,000 ppm has been chosen throughout this study. Simulated reservoir was made using 60ft coiled sandpaks with 1.86×10^{-3} ft in outer diameter (OD) and 1.54×10^{-3} ft in inner diameter (ID). The cross-sectional area is 0.00027 ft^2 and the bulk volume of sand pack is 458.8 cc. Meanwhile, the pore volume is about 160.58 cc with porosity of sand pack approximately 35 percent. The absolute permeability of the sand pack is approximately 7.789 Darcy. The tube was packed with 80-100 mesh rounded grains glass beads to represent fine grained sandstone reservoir rock porous media. Crude oil used was obtained from kemaman crude oil terminal with oil viscosity of 3.67 cp and density of about 0.8264 g/cc (41°API). The injection rate for all runs was set constant throughout the study, which is 560 cc/hr.

Wettability analysis was done in room condition since there was no suitable equipment that can be used to determine the contact angle in reservoir conditions. A set of carbonated water was prepared in high pressure condition and then the pressure was

gradually decreased until it reached room conditions. The test was conducted using a sessile drop method, which is a direct contact angle measurement to determine the contact angle of oil and water, consequently determining the wetting phase of reservoir sandstone rock model. The experiment was repeated several times to improve reproducibility.

1.5 Significance of Study

The accomplishment of this research would greatly contribute in the research community. The outcome of this research will provides a further insight into the carbonated water process. Good comprehension on carbonated water was needed so that we can improve our approach on carbonated water and enable us to add more information in improving oil recovery using carbonated water. Extensive research on carbonated water will improved the probability on carbonated water into a full scale real field application in a near future.

Based on this research, carbonated water has its additional values in improving residual oil recovery. Carbonated water injection (CWI) can become an alternative injection strategy that eliminates many of the shortcomings of direct CO₂ injection. Carbonated water has a much better sweep efficiency, as its viscosity is higher than that of water and much higher than that of CO₂. In terms of CO₂ storage, CWI provides one of the safest mechanisms for CO₂ storage, since the injected CO₂ is in solution rather than free phase. CW has higher density compared to water and hence it sinks in the reservoir as opposed to bulk CO₂ injection where CO₂ floats under the caprock representing significant leakage risks.

REFERENCES

- Ahmed T., (2001). *Reservoir Engineering Handbook*. (fourth edition). Gulf Professional Publishing . 933.
- Ahmed T and Meehan D.N., (2012). *Advance Reservoir Management and Engineering*. (Second Edition). Elsevier Inc. 568
- Al adasani, A. and Bai, B. (2011). Analysis of EOR Projects and Updated Screening Criteria. *Journal of Petroleum science and Engineering*. 79, 10-24.
- Al-otaibi F. M., Al-Mutairi S. M., Kokal S. L., Funk J. J. and Al-Qahtani J. F. (2012). Best Practices for Conducting CO₂-EOR Lab Study. *SPE EOR Conference at Oil and Gas West Asia*. Muscat, Oman.
- Al-otaibi, M.B., Azmy, R.M., and Nasr-El-Din, H.A. (2010). A Comprehensive EOR Study Using Low Salinity Water in Sandstone Reservoirs. *Improve Oil Recovery Symposium*. 24-28 April. Tulsa, Oklahoma USA. SPE129976.
- Al-otaibi, M.B., and Nasr-El-Din, H.A. (2009). Chemistry of Injection Water and its Impact on Oil Recovery in Carbonate and Clastic Formations. *SPE International Symposium on Oilfield Chemistry*. 20-22 April. The Woodlands, Texas USA. SPE 121565.
- Alvarador, V. and Manrique, E. (2010). Enhance Oil Recovery: An Update Review, *Energies*. **3**, 1529-1575.
- Al-quraini, A., Sohrabi, M., and Jamiolahmady, M (2007). Heavy Oil Recovery by Liquid CO₂/Water Injection. *SPE Europe/EAEG Annual Conference and Exhibition*. 11-14 June. London, United Kingdom, SPE107163.
- American Society for Testing and Material (2014). *A213/A213M-14*. West Conshohocken, United States. PA 19428-2959.
- Anderson, W. G. (1986). Wettability Literature Survey – Part 6: The Effects of Wettability on Waterflooding. *JPT*. 38(12), 1246-1262.
- Asghari, K., Araghi, M.N., Ahmadloo, F. and Nakutnyy, P. (2009). Utilization of CO₂ for Improving the Performance of Waterflooding in Heavy Oil

- Recovery. *Canadian International Petroleum Conference (CIPC)*. 16-18 June. Calgary, Alberta. Paper 2009-130.
- Baranenko, V.I., Fal'kovskii, L.N., Kirov, V.S., Kurnyk, L.N., Musienko, A.N., and Piontkovskii, A.I. (1988). Solubility of Oxygen and Carbon Dioxide in Water. *AtomnayaEnergiya*. Vol. 68 (No. 4), 291-294.
- Beeson, D. M., and Ortloff, G.D. (1959). Laboratory Investigation of the Water-Driven Carbon Dioxide Process for Oil Recovery. *Journal of Petroleum Technology*. SPE 1100-G.
- Christensen, R. J. (1961). Carbonated Waterflood Result-Texas and Oklahoma. *Seventh Annual Meeting of Rocky Mountain Petroleum Section of AIME*. 25-26 May. Farmington, SPE 66.
- Crawford, H. R., Neill, G. H., Bucy, B.J., and Crawford, P.B. (1963). Carbon Dioxide- A Multipurpose Additive for Effective Well Stimulation. *Journal of Petroleum Technology*. SPE 571, 237-242.
- Craig, F.F., (1971). The Reservoir Engineering Aspects of Waterflooding: *SPE Monograph 3*. Society of Petroleum Engineers (SPE), 134 p
- Donaldson E. C. (1985). *Enhanced Oil Recovery; Fundamentals and Analysis*. New York:
- Donaldson, E.C. and Thomas R.D., (1971). Microscopic Observations of Oil Displacement in Water-Wet and Oil-Wet Systems. *Society of Petroleum Engineers of AIME*. SPE 3555.
- Donaldson, E.C., Lorenz, P. B and Thomas, R. D., (1969). Wettability determination and Its effect on recovery efficiency. *Journal Society of Petroleum Engineer*. Vol. 9, No. 1, pp. 13-20.
- Dong, Y., Ishizawa, C., Lewis, E., and Dindoruk, B (2011a). Carbonated Water Flood: What We Observed in Sand Pack Experiments. *International Symposium of the Society of Core Analysts*. 18-21 September. Texas, SCA2011-34.
- Dong, Y., Dindoruk, B., Ishizawa, C., Lewis, E., and Kubicek, T. (2011b). An Experimental Investigation of Carbonated Waterflooding. *SPE Annual Technical Conference and Exhibition*. 30 October–2 November. Denver, Colorado. SPE 145380, 1-16.
- Farouq Ali S. M. (2013). All You Need is Darcy's Equation to Determine EOR Success or Failure. *SPE Western Regional & AAPG Pacific Section Meeting*.

- Hangx, S.J.T., (2005). Behaviour of the CO₂-H₂O System and Preliminary Mineralisation Model and Experiments. *CATO WP 4.1.Vol 3*
- Hickok, C. W., Christensen, R. J. and Ramsay, JR, H. J. (1960). Progress Review of K&S Carbonated Waterflood Project. *Journal of Petroleum Technology*. SPE 1474-G, 20-24.
- Holm L.W. (1982). CO₂ Flooding: Its Time Has Come. *Journal of Petroleum Technology*.
- Holm L.W. (1987). Evolution of the Carbon Dioxide Flooding Processes. *Journal of Petroleum Technology*.
- Holm L.W and Josendal V.A (1980). Effect of Oil Composition on Miscible-type Displacement by Carbon Dioxide. *SPE/DOE Enhanced Oil Recovery Symposium*.
- Honarpour, M., Koederitz, L., and Harvey, A.H. (1986). *Relative Permeability of Petroleum Reservoirs*, 16-41. Boca Raton, Florida: CRC Press
- Igalauer, S., Wu, Y., Shuler, P., Tang, Y. and Goddard III, W.A. (2010). New Surfactant Classes for Enhanced Oil Recovery and Their Tertiary Oil Recovery Potential. *Journal of Petroleum Science and Engineering*. 71, 23-29.
- Kechut, N.I., Riazi, M., Sohrabi, M. and Jamiolahmady, M. (2010). Tertiary Oil Recovery and CO₂ Sequestration by Carbonated Water Injection (CWI). *SPE International Conference on CO₂ Capture, Storage and Utilization*. 10-12 November. New Orleans, Louisiana. SPE 139667, 1-12.
- Knoche. W (1980). *Chemical Reaction of CO₂ in Water*. Biophysics and Physiology of Carbon Dioxide. (3-11). Springer Link.
- Krumrine, P.H., Falcone, J.S., Campbell, T.C., (1982). Surfactant flooding 2: the effect of alkaline additives on permeability and sweep efficiency. *SPE Journal*. 22 (6), 983–992.
- Lasater J.A and Petroleum Co. Magnolia (1958). Bubble Point Pressure Correlation. *Fall Meeting of Southern California Petroleum Section*.
- Martin, J. W. (1951). Additional Oil Production Through Flooding with Carbonated Water. *Producer Monthly*. July, 18-22.
- Manrique, E., Thomas, C., Ravikiran, R., Izadi, M., Lantz, M., Romero, J., and Alvarado, V. (2010). EOR: Current Status and Opportunities. *2010 SPE*

- Improved Oil Recovery Symposium*. 24-28 April. Tulsa, Oklahoma. SPE130113, 1-21.
- Mungan, N. (1966). Certain Wettability Effect in laboratory Waterfloods. *SPE Annual Fall Meeting*. 3-6 Oct. Denver, USA. SPE 1203.
- Nasehi, M. and Asghari, K. (2010). Use of CO₂ in Heavy-oil Waterflooding. *SPE International Conference on CO₂ Capture, Storage and Utilization*. 10-12 November. Louisiana, SPE 139672.
- Neumann, A.W and Good, R.J (1979). *Technique of Measuring Contact Angle*. (11). Surface and Colloid Science. New York: Platinum Press. 31-91.
- Owen, W.W. and Archer, D.L (1971). The Effect of Rock Wettability on Oil-Water Relative Permeability Relationships. *Journal of Petroleum Technology*. SPE 3034, 873-878.
- Picha, M.S., (2007). Enhance Oil Recovery by Hot CO₂ Flooding. *15th SPE Middle East Oil and Gas Show and Conference*. 11-14 March. Bahrain. SPE 105425, 1-5.
- Pistone, S., Stacey, R., and Horne, R. (2011). The Significance of Co₂ Solubility In Geothermal Reservoirs. *Proceedings Thirty-Sixth Workshop on Geothermal Reservoir Engineering*. January 31 - February 2. Stanford, California: SGP-TR-191.
- Properties of Carbon Dioxide, Union Engineering, Denmark. www.UNION.dk
- Ramsay, JR, H. J. and Small, F. R., (1964). Use of Carbon Dioxide for Water Injectivity Improvement. *Journal of Petroleum Technology*. SPE 595, 25-31.
- Rathmel, J.J., Stalkup, F.I. and Hassinger, R.C (1971). A Laboratory Investigation of Miscible Displacement by Carbon Dioxide. *Society of Petroleum Engineer Journal*. SPE 3483.
- Riazi, M., Sohrabi, M., jamiolahmadi, M., Ireland, S and Brown, C. (2009). Oil Recovery Improvement Using CO₂-Enriched Water Injection. *SPE EUROPEC/EAGE*. 8-11 June. Amsterdam, The Netherlands, SPE 121170, 1-10.
- Rosenqvist, J., Kilpatrick, A. and Yardley, B.W.D. (2012). Solubility of Carbon Dioxide in Aqueous Fluids and Mineral Suspensions at 294 K and Subcritical Pressures. *Applied Geochemistry*. 27, 1610-1614.

- Ruska Instrument Corporation (1982). *General Description and Operating Procedure of Ruska Positive Displacement Pump*. (Manual No 31506). Houston, Texas: Ruska Instrument Corporation. 69.
- Sen. R. (2008). Biotechnology in Petroleum Recovery: The Microbial EOR. *Progress in Energy and Combustion Science*. 34. 714-724.
- Siregar, S., Mardisewojo, P., Kristanto, D. and Tjahyadi, R. (1999). Dynamic interaction between CO₂ Gas and Crude Oil in Porous Medium. *1999 SPE Asia Pacific Improved Oil Recovery Conference*. 25-26 October. Kuala Lumpur, Malaysia. SPE 57300, 1-7.
- Smith, A. S., Sorensen, A. J., Steadman, N. E., and John A. Harju, A. J., and Ryan. D. (2011). Zama Acid Gas EOR, CO₂ Sequestration and Monitoring Project. *Energy Procedia* . 4, 3957–3964.
- Sohrabi, M., Kechut, N. I., Riazi, M., Jamiolahmady, M., Ireland, S and Robertson, G. (2011). Safe storage of CO₂ together with improved oil recovery by CO₂-enriched water injection, *Chemical Engineering Research And Design*. 89, 1865-1872.
- Sohrabi, M., Kechut, N. I., Riazi, M., Jamiolahmady, M., Ireland, S and Robertson, G. (2012). Coreflooding Studies to Investigate the Potential of Carbonated Water Injection as an Injection Strategy for Improved Oil Recovery and CO₂ Storage. *Transp Porous Med*. 91,101–121.
- Stalkup F. I. (1978). Carbon Dioxide Miscible Flooding; Past, Present, And Outlook for the Future. *SPE-AIME Fifth Symposium on Improved Methods for Oil Recovery*. Tulsa.
- Torrey, P.D. (1951). Oil Recovery by Fluid Injection. *Proceedings Third World Petroleum Congress*. section II, 565-607.
- Tjia, H.D and Liew, K.K. (1996). Change in Tectonic Stress Field in Northern Sunda Shelf Basins. *Geological Society* (London). Special Publication No. 106, 291-306.
- Vialle, S., Vanorio, T. and Mavko, S. (2010). Monitoring the changes of rock properties in a micritic limestone upon injection of a CO₂-rich fluid. *SEG Denver 2010 Annual Meeting*. Denver, USA. 2692-2696.
- Yun, N and Franklin, M.O.Jr. (1998). Calculation of Minimum Miscible Pressure. *SPE/DOE Improved Oil Recovery Symposium*. 19-22 April. Tulsa, Oklahoma. SPE 39683.

Zhang, Y., Huang, S., and Luo, P. (2010). Coupling Immiscible CO₂ Technology and Polymer Injection to Maximize EOR Performance for Heavy Oil. *Journal of Canadian Petroleum Technology*. 49(5), 27-33.