

ARTIFICIAL IMMUNE SYSTEM AND PARTICLE SWARM OPTIMIZATION
FOR ELECTROENCEPHALOGRAM BASED EPILEPTIC SEIZURE
CLASSIFICATION

NASSER OMER SAHEL BA-KARAIT

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Computer Science)

Faculty of Computing
Universiti Teknologi Malaysia

NOVEMBER 2015

To my beloved family

ACKNOWLEDGEMENT

All praise and thanks are due to Allah, and peace and blessings of Allah be upon our prophet, Muhammad and upon all his family and companions. Thanks to Allah who give me good health in my life and thanks to Allah for everything. Without help of Allah, I was not able to achieve anything in this research.

In preparing this thesis, I was in contact with many people, researchers, academicians, and practitioners. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main supervisor, Prof. Dr. Siti Mariyam Shamsuddin, for encouragement, guidance, critics, advices and supports to complete this research. I really appreciate her ethics and great deal of respect with her students, which is similar to dealing between the mother, and her sons and daughters in the same family. I am also grateful to my cosupervisor Assoc. Prof. Dr. Rubita Sudirman for her precious advices and comments.

I am grateful to all my colleagues, friends, staff, and lecturers in Faculty of Computing, Universiti Teknologi Malaysia and Hadhramout University of Science and Technology for their help and support at every step during this course of studies. My sincere thank goes to Hadhramout University of Science and Technology for the generous financial support.

ABSTRACT

Automated analysis of brain activity from electroencephalogram (EEG) has indispensable applications in many fields such as epilepsy research. This research has studied the abilities of negative selection and clonal selection in artificial immune system (AIS) and particle swarm optimization (PSO) to produce different reliable and efficient methods for EEG-based epileptic seizure recognition which have not yet been explored. Initially, an optimization-based classification model was proposed to describe an individual use of clonal selection and PSO to build nearest centroid classifier for EEG signals. Next, two hybrid optimization-based negative selection models were developed to investigate the integration of the AIS-based techniques and negative selection with PSO from the perspective of classification and detection. In these models, a set of detectors was created by negative selection as self-tolerant and their quality was improved towards non-self using clonal selection or PSO. The models included a mechanism to maintain the diversity and generality among the detectors. The detectors were produced in the classification model for each class, while the detection model generated the detectors only for the abnormal class. These hybrid models differ from each other in hybridization configuration, solution representation and objective function. The three proposed models were abstracted into innovative methods by applying clonal selection and PSO for optimization, namely clonal selection classification algorithm (CSCA), particle swarm classification algorithm (PSCA), clonal negative selection classification algorithm (CNSCA), swarm negative selection classification algorithm (SNSCA), clonal negative selection detection algorithm (CNSDA) and swarm negative selection detection algorithm (SNSDA). These methods were evaluated on EEG data using common measures in medical diagnosis. The findings demonstrated that the methods can efficiently achieve a reliable recognition of epileptic activity in EEG signals. Although CNSCA gave the best performance, CNSDA and SNSDA are preferred due to their efficiency in time and space. A comparison with other methods in the literature showed the competitiveness of the proposed methods.

ABSTRAK

Analisis automatik aktiviti otak daripada elektroensefalogram (EEG) mempunyai aplikasi yang ketara dalam pelbagai bidang seperti penyelidikan epilepsi. Kajian ini telah mengkaji keupayaan pilihan negatif dan pilihan klonal dalam sistem imun tiruan (AIS) dan pengoptimuman kumpulan zarah (PSO) untuk menghasilkan pelbagai kaedah yang boleh dipercayai dan cekap untuk pengecaman serangan epilepsi berdasarkan EEG dimana ia masih belum diterokai. Pada awalnya, model pengelasan berasaskan pengoptimuman telah dicadangkan untuk menggambarkan penggunaan secara tunggal bagi pilihan klonal dan PSO untuk membina pengelas terpusat terhampir bagi isyarat EEG. Setelah itu, dua model hibrid bersandarkan pengoptimuman pilihan negatif telah dibangunkan untuk mengkaji gabungan teknik berdasarkan AIS dan pilihan negatif dengan PSO dari perspektif pengelasan dan pengesanan. Dalam model ini, satu set pengesanan telah dicipta menggunakan pilihan negatif sebagai toleran-kendiri dan kualiti kedua-duanya bertambah baik terhadap tak kendiri menggunakan pilihan klonal atau PSO. Model-model ini mengandungi mekanisme untuk mengekalkan kepelbagaian dan pengitlakan dalam kalangan pengesanan. Pengesanan telah dihasilkan dalam model pengelasan bagi setiap kelas, manakala model pengesanan menjana pengesanan hanya untuk kelas tidak normal. Model-model hibrid ini berbeza antara satu sama lain dalam konfigurasi penghibridan, perwakilan penyelesaian dan fungsi objektif. Ketiga-tiga model cadangan disarikan kepada beberapa kaedah inovatif dengan mengaplikasikan pilihan klonal dan PSO untuk pengoptimuman, iaitu algoritma pengelasan pilihan klonal (CSCA), algoritma pengelasan zarah kumpulan (PSCA), algoritma pengelasan pilihan klonal negatif (CNSCA), algoritma pengelasan pilihan kumpulan negatif (SNSCA), algoritma pengesanan pilihan klonal negatif (CNSDA) dan algoritma pengesanan pilihan kumpulan negatif (SNSDA). Kaedah-kaedah ini telah dinilai ke atas data EEG menggunakan pengukuran lazim dalam diagnosis perubatan. Hasil kajian menunjukkan bahawa kaedah cadangan telah mencapai pengecaman yang cekap dan boleh dipercayai bagi aktiviti epileptik dalam isyarat EEG. Walaupun CNSCA memberikan pencapaian yang terbaik, namun CNSDA dan SNSDA menjadi pilihan kerana kecekapan mereka dari aspek masa dan ruang. Perbandingan dengan kaedah-kaedah lain dalam literatur menunjukkan kebolehsaingan pada kaedah yang dicadangkan.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENT	vii
	LIST OF TABLES	xiii
	LIST OF FIGURES	xv
	LIST OF ABBREVIATION	xix
	LIST OF APPENDICES	xx
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Problem Background	3
	1.3 Problem Statement	9
	1.4 Objectives of Study	10
	1.5 Scope of Study	11
	1.6 Significance of Study	11
	1.7 Thesis Organization	12
2	LITERATURE REVIEW	14
	2.1 Introduction	14
	2.2 Human Brain Activity	14
	2.3 Brain Activity Recording Techniques	16

2.4	Electroencephalogram	17
2.5	Epileptic Activity in Brain	20
2.6	EEG Pattern Recognition	21
2.7	Wavelet Transform	24
2.8	Natural Immune System	29
2.9	Artificial Immune System	33
2.9.1	Negative Selection Algorithm	35
2.9.2	Clonal Selection Algorithms	37
2.9.2.1	Clonal Selection Algorithm (CLONALG)	38
2.9.2.2	B-Cell Algorithm	40
2.9.3	Immune Network Models	42
2.9.3.1	Resource limited Artificial Immune System (RLAIS)	42
2.10	Swarm Intelligence	44
2.10.1	Self-organization	45
2.10.2	Division of labor	46
2.11	Particle Swarm Optimization	47
2.11.1	PSO Technique	47
2.11.2	Necessity of V_{max}	50
2.11.3	Inertia Weight	50
2.11.4	Clerc's Constriction Factor	51
2.11.5	Acceleration Coefficients	52
2.11.6	Neighborhood Topology	53
2.11.7	PSO Algorithm Models	54
2.11.8	Binary PSO	54
2.12	Automated EEG-Based Epileptic Seizure Recognition	57
2.12.1	Related Works	57
2.12.2	Discussion	65
2.12.3	Artificial Immune System in EEG-Based Applications	68

2.12.4	Particle Swarm Optimization in EEG- Based Applications	71
2.13	Summary	72
3	METHODOLOGY	74
3.1	Introduction	74
3.2	Operational Framework	74
3.2.1	Phase 1: Preparation Phase	76
3.2.1.1	EEG Data Collection	76
3.2.1.2	EEG Data Preprocessing	78
3.2.1.3	Feature Extraction	80
3.2.2	Phase 2: Development of Classification Methods	84
3.2.2.1	Optimization based Classification (OBC) Model: Individual Classification Methods	85
3.2.2.2	Optimization based Negative Selection Classification (OBNSC) Model: Hybrid Classification Methods	86
3.2.2.3	Optimization based Negative Selection Detection (OBNSD) Model: Enhanced Hybrid Classification Methods	86
3.2.3	Phase 3: Performance Evaluation	87
3.2.3.1	Hold-Out Validation	87
3.2.3.2	K-Fold Cross Validation	88
3.2.3.3	Performance Measures	89
3.3	Summary	91

4	INDIVIDUAL CLASSIFICATION METHODS BASED ON CLONAL SELECTION AND PARTICLE SWARM OPTIMIZATION	92
4.1	Introduction	92
4.2	Optimization-Based Classification (OBC) Model	92
4.2.1	Nearest Centroid Classifier	93
4.2.2	Individual Encoding	95
4.2.3	Fitness Function	96
4.2.4	Optimization Process	97
4.3	Clonal Selection Classification Algorithm	97
4.4	Particle Swarm Classification Algorithm	99
4.5	Experimental Results	101
4.5.1	Experimental Setup	101
4.5.2	Results and Discussion	102
4.5.2.1	Performance Measures Analysis	103
4.5.2.2	Comparison between CSCA and PSCA	107
4.5.2.3	Computational Time Analysis	109
4.6	Summary	113
5	HYBRID CLASSIFICATION METHODS BASED ON ARTIFICIAL IMMUNE SYSTEM AND PARTICLE SWARM OPTIMIZATION	114
5.1	Introduction	114
5.2	Optimization-Based Negative Selection Classification (OBNSC) Model	114
5.3	Negative selection algorithm	116
5.4	Detector Optimization	117
5.4.1	Individual Encoding	118
5.4.2	Evaluating Fitness of Individual	118
5.5	Detector Status Function	119
5.6	Diversity Maintenance	120

5.7	Clonal Negative Selection Classification Algorithm	120
5.8	Swarm Negative Selection Classification Algorithm	122
5.9	Testing Procedure	124
5.10	Results and Discussion	124
	5.10.1 Performance Measures Analysis	125
	5.10.2 Comparing the Different Methods of OBC Model and OBNSC Model	127
	5.10.3 Computational Time Analysis	131
5.11	Summary	135
6	ENHANCED HYBRID CLASSIFICATION METHODS BASED ON ARTIFICIAL IMMUNE SYSTEM AND PARTICLE SWARM OPTIMIZATION	136
6.1	Introduction	136
6.2	Optimization-Based Negative Selection Detection (OBNSD) Model	136
6.3	Individual Encoding	137
6.4	Individual Fitness Evaluation	138
6.5	Detector Generator	139
6.6	Optimization-Based Negative Selection Detection Methods	141
6.7	Results and Discussion	143
	6.7.1 Performance Measures Analysis	144
	6.7.2 The Different Models-based Methods Comparison	147
	6.7.3 Computational Time Analysis	151
6.8	Comparison with Related Works	155
6.9	Summary	160

7	CONCLUSION AND FUTURE WORK	161
7.1	Introduction	161
7.2	Summary of Thesis	161
7.3	Contributions of the Research	163
7.4	Future work	165
	REFERENCES	167
	Appendices A – F	186-215

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Components of PSO algorithm	52
2.2	Formula for the four PSO models	54
3.1	A summary of EEG data annotation	77
3.2	Decomposition levels Frequencies of db2 wavelet for the EEG dataset	84
3.3	Samples of extracted features from five different sets of the EEG dataset	84
4.1	Class distribution of the patterns in the training and testing EEG datasets	103
4.2	Results of CSCA and PSCA for different groups of EEG dataset	104
4.3	Results of CSCA for different partitions of EEG data groups	111
4.4	Results of PSCA for different partitions of EEG data groups	112
5.1	Results of CNSCA and SNSCA for different groups of EEG dataset	125
5.2	Results of CNSCA for different partitions of EEG data groups	132
5.3	Results of SNSCA for different partitions of EEG data groups	133
6.1	Results of CNSDA and SNSDA for different groups of EEG dataset	144

6.2	Results of all proposed methods for different groups of EEG dataset	147
6.3	Results of CNSDA for different partitions of EEG data groups	152
6.4	Results of SNSDA for different partitions of EEG data groups	153
6.5	Comparison of the proposed methods with other methods in the literature using EEGs1	156
6.6	Comparison of the proposed methods with other methods in the literature using EEGs2	157
6.7	Comparison of the proposed methods with other methods in the literature using EEGs3	158
6.8	Comparison of the proposed methods with other methods in the literature using EEGs4	159

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	A drawing of a typical neuron	15
2.2	The international 10-20 system	18
2.3	Implanted strip electrodes	18
2.4	The different epilepsy-related states in EEG recordings	21
2.5	Typical steps for the design of EEG-based epilepsy diagnosis system	22
2.6	Sub-band decomposition of DWT	28
2.7	Wavelet and scaling functions of Daubechies wavelets family	29
2.8	Antibody-antigen complex	30
2.9	Lymphocyte life cycle	30
2.10	The clonal selection principle	32
2.11	Positive and negative responses of immune network	33
2.12	The negative selection algorithm	36
2.13	r -continuous matching rule	37
2.14	CLONALG algorithm	39
2.15	Multiple-points and contiguous mutation	40
2.16	B-cell algorithm	41
2.17	RLAIS algorithm	43
2.18	Swarm intelligence in nature	46
2.19	Concept of modification of searching point in PSO	48
2.20	PSO algorithm	49

2.21	Neighborhood topology in PSO, (a): Global neighborhood, (b): Von Neumann neighborhood, (c): Ring neighborhood	53
2.22	The sigmoid function over a domain of $[-v_{max}, v_{max}]$	56
3.1	Operational framework of the research	75
3.2	Samples of five different sets of the EEG dataset	78
3.3	Preprocessing and feature extraction steps	82
3.4	Wavelet decomposition of a sample EEG segment taken from set A	83
3.5	Wavelet decomposition of a sample EEG segment taken from set E	83
4.1	Proposed optimization based classification (OBC) model	93
4.2	Centroid structure	94
4.3	Proposed clonal selection classification algorithm (CSCA)	99
4.4	Proposed particle swarm classification algorithm (PSCA)	100
4.5	Accuracy and stability analysis for CSCA using different performance measures	105
4.6	Accuracy and stability analysis for PSCA using different performance measures	106
4.7	Comparison of CSCA and PSCA: accuracy and stability using CCR	107
4.8	Comparison of CSCA and PSCA: accuracy and stability using TPR	108
4.9	Comparison of CSCA and PSCA: accuracy and stability using TNR	109
4.10	The computational time for training CSCA and PSCA on different sizes of EEG data	113
5.1	Proposed optimization based negative selection classification (OBNSC) model	115
5.2	Proposed negative selection algorithm	117

5.3	Proposed clonal negative selection classification algorithm (CNSCA)	121
5.4	Proposed swarm negative selection classification algorithm (SNSCA)	123
5.5	Accuracy and stability analysis for CNSCA using performance measures	126
5.6	Accuracy and stability analysis for SNSCA using performance measures	127
5.7	Comparison of CSCA, PSCA, CNSCA, and SNSCA: accuracy and stability using CCR	128
5.8	Comparison of CSCA, PSCA, CNSCA, and SNSCA: accuracy and stability using TPR	129
5.9	Comparison of CSCA, PSCA, CNSCA, and SNSCA: accuracy and stability using TNR	130
5.10	The computational time for training CSCA, PSCA, CNSCA, and SNSCA on different sizes of EEG data	134
5.11	The number of memory detectors generated by CNSCA, and SNSCA for the different EEGs groups using different training sets	135
6.1	Proposed optimization based negative selection detection (OBNSD) model	138
6.2	Detector generation steps using clonal selection	140
6.3	Detector generation steps using PSO	141
6.4	Proposed clonal negative selection detection algorithm (CNSDA)	142
6.5	Proposed swarm negative selection detection algorithm (SNSDA)	143
6.6	Accuracy and stability analysis for CNSDA using performance measures	145
6.7	Accuracy and stability analysis for SNSDA using performance measures	146
6.8	Comparison of CSCA, PSCA, CNSCA, SNSCA, CNSDA and SNSDA: accuracy and stability using CCR	148

6.9	Comparison of CSCA, PSCA, CNSCA, SNSCA, CNSDA and SNSDA: accuracy and stability using TPR	149
6.10	Comparison of CSCA, PSCA, CNSCA, SNSCA, CNSDA and SNSDA: accuracy and stability using TNR	150
6.11	The computational time for training CSCA, PSCA, CNSCA, SNSCA, CNSDA, and SNSDA on different sizes of EEG data	154
6.12	The number of memory detectors generated by CNSCA, SNSCA, CNSDA and SNSDA for the different EEGs groups using different training sets	155

LIST OF ABBREVIATIONS

AIS	-	Artificial Immune System
ALC	-	Artificial Lymphocyte
BCA	-	B-Cell Algorithm
CCR	-	Correct Classification Rate
CNSCA	-	Clonal Negative Selection Classification Algorithm
CNSDA	-	Clonal Negative Selection Detection Algorithm
CSAs	-	Clonal Selection Algorithms
CSCA	-	Clonal Selection Classification Algorithm
CV	-	Cross Validation
DWT	-	Discrete Wavelet Transform
EEG	-	Electroencephalogram
EEGs	-	EEG Signals
HOV	-	Hold-Out Validation
NCC	-	Nearest Centroid Classifier
NIS	-	Natural Immune System
NSA	-	Negative Selection Algorithm
PSCA	-	Particle Swarm Classification Algorithm
PSO	-	Particle Swarm Optimization
SNSCA	-	Swarm Negative Selection Classification Algorithm
SNSDA	-	Swarm Negative Selection Detection Algorithm
TNR	-	True Negative Rate
TPR	-	True Positive Rate
WT	-	Wavelet Transform

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Complete Results of Clonal Selection Classification Algorithm (CSCA)	186
B	Complete Results of Particle Swarm Classification Algorithm (PSCA)	191
C	Complete Results of Clonal Negative Selection Classification Algorithm (CNSCA)	196
D	Complete Results of Swarm Negative Selection Classification Algorithm (SNSCA)	201
E	Complete Results of Clonal Negative Selection Detection Algorithm (CNSDA)	206
F	Complete Results of Swarm Negative Selection Detection Algorithm (SNSDA)	211

CHAPTER 1

INTRODUCTION

1.1 Introduction

The human brain is a highly complex organ representing the center of the nervous system. It contains about 100 billion of interconnected neurons. A neuron is a cell that uses biochemical reactions to receive, process, and transmit information and commands (Aziz, 2007; Rabbi, 2013).

Activity of brain describes a wide range of different states which are normal and abnormal. Normal states consist of physical states such as sleep, wakefulness, and exertion; as well as mental states such as calmness, happiness, and anger. Abnormal states are primarily noted in neurological disorders such as schizophrenia, insomnia, and epilepsy (Ghosh Dastidar, 2007; Polat and Güneş, 2008). However, there is significant overlap in the activation patterns of brain states. Therefore, it is very difficult to use these patterns to conclusively identify the state.

The techniques that are used to measure the activities of the brain can be broadly classified into two categories: hemodynamic/metabolic and electromagnetic (Scanziani and Häusser, 2009). The functional neuroimaging techniques based on principles of hemodynamic such as Functional Magnetic Resonance Imaging (fMRI) or metabolic such as Positron Emission Tomography (PET) infer functional activity through measuring local changes in blood oxygenation levels or glucose metabolism respectively (Ermer, 2001). Conversely, electromagnetic techniques describe

electrical properties of biological cells and tissues. Magnetoencephalogram (MEG) and electroencephalogram (EEG) are the electromagnetic techniques widely employed to measure the electrical activities of neurons from the magnetic fields and the fluctuations in potential respectively (Ermer, 2001; Rabbi, 2013).

Among these techniques, EEG is favorable due to several advantages: the electrical activity of the brain is recorded directly, it is less cumbersome and very inexpensive, and its high temporal resolutions (milliseconds, mS) which allow direct observation of the dynamic brain activity. With EEG, it is possible to follow the rapid changes in cortical activity that reflect neural processing functions, where the electrical events of single neurons typically last from one to several tens of mS (Ermer, 2001; Majumdar, 2011; Stam *et al.*, 1999; Wong, 2004).

The EEG records electric potentials that are generated by neurons in the brain. The brain activity in different areas over a time period is measured, using many electrodes in order to characterize the spatio-temporal dynamics of neuronal activity in the brain. This result in multi-channel EEG signals, each represents an EEG signal at different positions (Ghosh Dastidar, 2007; Madan, 2005). The EEG can be a non-invasive or invasive with respect to electrode location. In non-invasive technique, the EEG signals are recorded from the surface of the head based on the International 10-20 system (Homan *et al.*, 1987; Jasper, 1958; Shibasaki, 2008). The EEG in this case is referred to as the scalp EEG. The invasive electrodes consist of three types: electrocorticogram (ECoG), intracranial EEG (IEEG), and depth EEG. The ECoG is measured from the cortex directly using subdural electrodes strip/grid; whereas the IEEG is measured from inside the skull; and finally the depth EEG is measured from inside the brain (Gardner, 2004).

The EEG signals (EEGs) conveys valuable information about the states of the brain. Therefore, EEGs analysis has important applications in brain computer interface (BCI), psychotropic drug research, monitoring patients in critical condition in the ICUs, sleep studies, and epilepsy research (Majumdar, 2011).

Epilepsy is characterized by recurrent seizures due to temporary electrical disturbance of the brain (Acharya *et al.*, 2012b). The occurrence of a seizure seems unpredictable and its course of action is still largely unknown to date. Research is therefore needed to gain a better understanding of the mechanisms generating epileptic seizures. Careful analysis of EEGs could provide valuable insight into this widespread brain disorder (Adeli *et al.*, 2003; Subasi, 2007).

Monitoring of epilepsy requires a continuous EEG recording for durations extending usually days. The recorded data is intensively used to study the epileptic seizures for pre-surgical evaluation. It provides essential information for locating the brain regions that generate epileptic activity (Jordan, 1993; Ocak, 2008). In some cases, epilepsy patients have seizures that are uncontrollable. Recently, methods have started being developed to treat medically resistant epilepsy. In those methods, implantable medical devices monitor the electrical activities of the brain and deliver a local therapy; such as chemical infusions or electrical stimulation; to the affected regions of the brain in order to reduce the frequency of seizures (Alam and Bhuiyan, 2013; Patnaik and Manyam, 2008; Tang and Durand, 2012).

1.2 Problem Background

Epileptic activity is typically studied using continuous long-term EEG monitoring systems. As a result, large amounts of EEGs are recorded (Madan, 2005). Nature of the signals is dynamic with high temporal resolutions (Majumdar, 2011). Visual analysis of the EEG recordings by a reviewer is clearly a very time consuming and costly task. Moreover, the analysis depends on expertise and experience of the reviewer, and therefore it is subjective (Alam and Bhuiyan, 2013). These challenges are further augmented in cases of the scalp EEGs where the number of channels is increased to more than 300 channels (Liu *et al.*, 2012; Oostenveld and Praamstra, 2001) and overlapping symptomatology epileptic seizures with other neurological disorders (Song and Zhang, 2013). Hence, automating the process of epileptic seizures recognition in EEGs is of great importance. The development in studies of signal processing and data mining has provided a great possibility to

manipulate this problem through identifying associations or hidden patterns in EEGs (Song and Zhang, 2013).

Although there are a large amount of information in EEGs, but some contents of EEG are not useful. Lower frequency oscillations are characterized as artifacts, and include electrocardiograms, eye blinks, and muscle movements, to name a few. On the other hand, very high frequency oscillations may be recorded due to electromagnetic interference. All these contents of EEGs can be categorized as noises and need to be removed (Ghosh Dastidar, 2007; Song and Zhang, 2013). Therefore, various techniques of signal processing theory have been employed to extract the features of relevant information in EEGs. These techniques include the Fast Fourier transform (FFT) (Polat and Güneş, 2007; Polat and Güneş, 2008; Tezel and özbay, 2009), autoregressive (AR) (Alkan *et al.*, 2005; Übeyli, 2010), and wavelet transform (WT) (Orhan *et al.*, 2011; Song and Zhang, 2013; Subasi, 2007; Übeyli, 2009c).

Signal processing based on FFT retains only the frequencies information whereas the information of the time is lost (Amirmazlaghani and Amindavar, 2009). Furthermore, the FFT suffers from large noise sensitivity (Subasi, 2005b). The short-time Fourier transform can localise information of frequency and time using a uniform time window. Therefore, it has limited precision where all frequencies have constant resolution (Xu *et al.*, 2009). AR method reduces the problem of spectral loss and provides better resolution of frequency, but it is good only for stationary signals. Since the EEGs are non-stationary, the AR is not suitable to analyze frequency of such signals (Subasi, 2005a). In contrast, the WT has ability for localizing frequency and time components of signal with a variable window size that is adapted based on the frequency. Hence, the WT has become an efficient method for feature extraction of non-stationary signals (Ocak, 2009). In this work, EEG dataset used in the current study has been analyzed using WT for feature extraction.

Feature extraction is the preliminary stage in which highly informative measures are produced as representative features for EEGs. The main stage of an automated system for epileptic seizures recognition in EEGs is EEG patterns

classification. In this stage, the machine learns to mine the EEGs to differentiate between EEG patterns in epileptic state and other brain states in order to make rational decisions on the classes of the patterns (Li, 2010; Majumdar, 2011). Thus, applications of machine learning techniques in analyzing EEGs have an increasing interest in recent years. In biomedical research, it is essential to understand and develop advanced signal classification techniques for the recognition of EEG changes (Siuly *et al.*, 2011). In this regard, soft computing is the most promising approaches among many techniques of machine learning. The soft computing strives to achieve robust and practical solutions at reasonable cost by tolerating uncertainty, imprecision and approximation to be part of the computational model (Goel *et al.*, 2013; Majumdar, 2011).

In this context, tremendous efforts have long been made by researchers trying to solve the problem of automatic diagnosis of epilepsy from EEGs, and thus several methods have been presented in the literature. Many of these approaches include techniques that belong to the area of soft computing such as different types of artificial neural networks (ANN) (Kumar *et al.*, 2010; Orhan *et al.*, 2011; Song and Zhang, 2013; Subasi, 2007; Übeyli, 2008b; Übeyli, 2009c), adaptive neuro-fuzzy inference system (ANFIS) (Güler and Übeyli, 2005; Kannathal *et al.*, 2005; Übeyli, 2009b), support vector machine (SVM) (Chandaka *et al.*, 2009; Joshi *et al.*, 2014; Nicolaou and Georgiou, 2012; Subasi and Gursoy, 2010; Übeyli, 2008a), and artificial immune system (AIS) (Polat and Güneş, 2008).

Artificial immune system (AIS) emerged in the 1990s as a flourishing field of soft computing (de Castro and Timmis, 2002b; de Castro and Timmis, 2003; Gao *et al.*, 2009b). The AIS can exhibit robust and powerful capabilities in information processing to solve complex problems. From the perspective of computational, it has important characteristics such as maintenance, diversity, learning, and memory. Moreover, the AIS shows fast convergence speed with ability to avoid the immaturity and degeneration of the searching (Aydin *et al.*, 2010; Guo, Lei *et al.*, 2011; Leung *et al.*, 2007). To date, research primarily has focused on three main components within AIS which include the theories of negative selection, clonal selection and immune network (Smith and Timmis, 2008).

The algorithms of AIS have not been widely explored in the field of EEG-based diagnosis. Actually, there are very few studies in which AIS models have been employed to recognize epileptic seizures in EEGs. Polat and Güneş (2008) used an algorithm belongs to immune network theory called artificial immune recognition system (AIRS) to propose a system with three stages: feature extraction using FFT, dimensionality reduction based on PCA, and EEG classification using AIRS with fuzzy resource allocation. However, there are also a few studies that have applied AIS methods in other fields related to EEG. Guo, Lei *et al.* (2011) introduced immune algorithm for feature weights and parameters selection of SVM which was used to classify different mental tasks for EEG-based BCI. Artificial immune network (cob-aiNet) was used by Coelho *et al.* (2012) to optimize the feature of EEGs based on Davies-Bouldin index and extreme learning machine ANN classifier for BCI system in motor imagery paradigms.

The negative selection algorithm (NSA) is more appropriate for application in anomaly and fault detection compared to other AIS theories (Amaral, 2011; Aydin *et al.*, 2010). It has been proven to be an efficient algorithm for solving such problems (Garrett, 2005; Ji and Dasgupta, 2007). The NSA was firstly proposed for the real-time detection of computer virus (Forrest *et al.*, 1994). Since then, it has been used widely in such domains as diagnosis of motor fault (Aydin *et al.*, 2008; Gao *et al.*, 2009a; Laurentys *et al.*, 2010; Xinmin *et al.*, 2007), detection of aircraft fault (Dasgupta *et al.*, 2004), and security of communication network (Dasgupta and Gonzalez, 2002; Hoffmeyr and Forrest, 1999). Nevertheless, the NSA has not been investigated in the area of EEGs applications so far.

On the other hand, the random search of the traditional NSA cannot be guaranteed to generate detectors in the most efficient way. That is to say, distribution of the detectors is unbalanced in the problem space. As a result, some regions of abnormal (non-self) space are uncovered, whereas other regions are re-covered by redundant detectors (Aydin *et al.*, 2010; Gao *et al.*, 2007; Wen *et al.*, 2014). Many methods have been introduced in the literature to overcome this drawback (Amaral *et al.*, 2007; Aydin *et al.*, 2008; Aydin *et al.*, 2010; Dasgupta and Gonzalez, 2002; Gao *et al.*, 2006; Gao *et al.*, 2007; Gao *et al.*, 2008; Gao *et al.*,

2009a; Graaff and Engelbrecht, 2006; Igawa and Ohashi, 2009). Most of these methods use optimization techniques, i.e., particle swarm optimization (PSO), genetic algorithm (GA), and clonal selection algorithms (CSAs), to guide the search in NSA and generate detectors with optimal distribution.

Gao *et al.* (2007) used a multi-phase PSO to optimize NSA detectors. It was integrated with anti-collision technique to increase diversity of detectors. However, fixed radius for the detectors is used. A classification algorithm based on NSA has been proposed by Igawa and Ohashi (2009). They applied a clonal selection algorithm named CLONALG in order to generate efficient detectors. In testing stage when a pattern cannot be detected, the radius of each detector is enlarged. However, many detectors in this case may overlap the others and normal (self) space. Aydin *et al.* (2010) proposed a negative selection method using chaotic maps and a CSA. In their algorithm, the chaotic maps are used to initialize the detectors and in mutation operator, whereas the CSA is employed to optimize the coverage and diversity of the detectors. The quality of each detector is evaluated based on the number of data samples recognized by (1) only current detector, (2) current detector and other detectors. The downside is that some parts of problem space may be searched many times. Furthermore, domination of second factor can result in poor coverage and redundant detectors.

Principles of clonal selection have been used to introduce various algorithms that are employed for tasks such as data mining, clustering and optimization. However, clonal selection algorithms (CSAs) are more suitable to deal with optimization problems and have found widespread use in such applications (Aydin *et al.*, 2010; Shojaie and Moradi, 2008). Clonal selection has excellent search abilities with an important mechanism to guarantee diversity of individuals in new generations. Hence, CSAs can avoid the local convergent effectively (Trojanowski and Wierchoń, 2009; Wang *et al.*, 2008).

In literature, a few studies applied CSAs to solve some optimization or clustering problems in applications of EEGs. Shojaie and Moradi (2008) presented a clonal selection algorithm for features selection and parameters optimization of

SVM. The SVM was used to assess event-related potentials (ERP) in EEGs of guilty knowledge test (GKT) based on the P300 waves. Dursun *et al.* (2012) proposed artificial immune clustering based on clonal selection for data reduction in order to solve class imbalance problem in training data. It was applied for sleep stage classification in EEG, Electrooculogram (EOG), and Electromyogram (EMG) signals using ANN. Their results confirmed superiority of artificial immune method compared to fuzzy C-means clustering. Feature selection also considered using immune clonal algorithm (ICA) to improve detecting epileptic EEGs (Peng and Lu, 2012). It was compared with PSO using four classifiers. The finding showed in general that the ICA slightly outperformed the PSO in classification accuracies.

The clonal selection-inspired algorithms have not been applied previously for EEGs classification. However, the optimization techniques can be employed for classification by representing each class with a centroid (class center) (De Falco *et al.*, 2007; Mohemmed and Zhang, 2008; Omran *et al.*, 2005). The goal is to optimize the positions of all centroids to build nearest centroid classifier (NCC). It is clear that CSAs and PSO can be effectively faced such problem. The PSO is a global optimization algorithm, simple in concept, easy to implement, robust to control parameters and computationally efficient (Eberhart and Shi, 1998; Wang *et al.*, 2007).

To the best of our knowledge, the PSO has not been used for classification of EEGs. However in many works, the classifier of EEGs is trained and/or its parameters are optimized by PSO (Chai *et al.*, 2013 In Press; Cinar and Sahin, 2013; Firpi *et al.*, 2007; Hema *et al.*, 2008; Lin and Hsieh, 2009; Nguyen *et al.*, 2012). Also, it was employed to estimate the locations of sources of electrical activity, e.g. epileptic, in the brain based on the scalp EEGs (Escalona-Vargas *et al.*, 2013; Qiu *et al.*, 2005; Shirvany *et al.*, 2012; Shirvany *et al.*, 2013; Shirvany *et al.*, 2014; Xu *et al.*, 2010). Other EEGs issues have been addressed by PSO such as feature selection (Nakamura *et al.*, 2009; Zhiping *et al.*, 2010) and optimal selection of Electrode Channels (Jin *et al.*, 2008; Kim *et al.*, 2012; Meng *et al.*, 2011). In this context, it was used by Atyabi *et al.* (2013) for dimensions reduction of both electrode and feature. Furthermore, Xu *et al.* (2014) considered simultaneously finding of the

optimal frequency band and time interval of EEG signals using PSO. Finally, the adaptive noise canceller (ANC) was implemented with the PSO to detect hand movement based ERP from the EEGs by Ahirwal *et al.* (2014).

1.3 Problem Statement

Brain activities analysis from EEGs is indispensable in the study of epilepsy. An automatic computational model which is able to recognize epileptic EEGs is valuable for assisting the experts to analyze information of patients in the EEG recordings and for diagnosing and treatment epilepsy (Adeli *et al.*, 2003). Also, such methods form an integral part of closed-loop therapeutic systems that depend on implantable devices.

Automatic diagnosis of epilepsy is generally modeled as an abnormal EEGs recognition problem (Majumdar, 2011; Song and Zhang, 2013). As discussed in previous section, the AIS and PSO seem very promising fields for dealing with such problem. Therefore, these computational techniques have been considered to be widely studied in the area of EEG-based epileptic seizure recognition. Accordingly, the main question which must be answered is as follows:

How can the techniques of AIS and PSO produce different methods that perform efficiently and provide reliable recognition for epileptic activity in EEGs?

To study the main question of this research stated above, the following sub-research questions need to be addressed:

- *What are the abilities of individual algorithms of AIS and PSO in classifying EEGs?*

- *Can hybridization of AIS-based techniques with each other or with PSO improve the EEGs-based epileptic seizures recognition?*
- *Can modification of hybridization configuration enhance the performance of the proposed methods in recognizing epileptic EEGs?*

1.4 Objectives of Study

The main goal of this study is to investigate the capabilities of AIS and PSO in classifying EEGs to recognize the epileptic seizure in brain activities for purposes of epilepsy diagnosis. Therefore, the following specific objectives of the study have been stated:

- 1) To propose classification methods based on clonal selection and PSO for building nearest centroid classifier for EEGs.
- 2) To develop hybrid negative selection classification methods using the techniques of clonal selection and PSO for recognition of epileptic EEGs.
- 3) To further improve the efficiency of the hybrid methods proposed by configuring the hybridization on the basis of detection.
- 4) To evaluate the performance of the different proposed methods in diagnosing the epilepsy using EEG signals.

1.5 Scope of Study

This research studies the recognition of epileptic activity in human brain from EEGs by soft computing techniques. Hence, its scope limits to the following points.

- 1) The current work focuses on AIS and PSO to introduce hybrid and individual algorithms for automatic recognition of epileptic EEGs. In AIS, the theories of negative selection and clonal selection are studied.
- 2) In the preliminary stage, discrete wavelet transform (DWT) is applied for feature extraction of EEGs. The focus is on classification stage due to its importance in forming model discriminates between EEGs patterns.
- 3) The epilepsy diagnosis application using EEGs is considered in this study. Therefore, the publicly-available EEG data described in Andrzejak *et al.* (2001) is used to test the proposed methods. This dataset describes different cases for epilepsy diagnosis.
- 4) The performance of the proposed methods is evaluated using correct classification rate (CCR), true positive rate (TPR) or sensitivity, and true negative rate (TNR) or specificity which are the common measures in medical diagnosis tasks. Also, the algorithms are compared to one another and with other studies in literature.

1.6 Significance of Study

In this study, the abilities of the AIS and PSO techniques are widely explored in the field of EEG-based epileptic seizure recognition for diagnosis and treatment of epilepsy. More significantly, different methods are proposed which have not been

introduced yet for classification of EEGs in order to test the individual and hybrid capabilities of AIS and PSO.

In this regard, the performance of clonal selection and PSO for classifying EEGs is studied individually through building NCC. Also, two hybrid negative selection models are developed in which clonal selection or PSO can be used to optimize the coverage of problem space. The first model is designed on the basis of classification where a set of detectors are produced for each class, while the second one takes into account the concept of detection and therefore the detectors are generated for only the abnormal class. The hybridization configuration and the solution structure of clonal selection (antibody) and PSO (particle) are different of each other for these two models.

Obviously, six algorithms are proposed in this research based on AIS and PSO for recognizing epileptic activities from EEGs: clonal selection classification algorithm (CSCA), particle swarm classification algorithm (PSCA), clonal negative selection classification algorithm (CNSCA), swarm negative selection classification algorithm (SNSCA), clonal negative selection detection algorithm (CNSDA), and swarm negative selection detection algorithm (SNSDA).

1.7 Thesis Organization

This thesis is organized into six major chapters and an introductory chapter. The second Chapter shows a review covering explanation of human brain activity and its recording techniques such as electroencephalogram (EEG). The EEG pattern recognition methodology and its applications in automated diagnosis of epilepsy are detailed in the chapter. Broad overviews on the fundamental methods which are used in this study are given. The use of these methods in EEG-based applications is also presented.

Chapter 3 describes the overall methodology followed to achieve the research objectives. It is introduced in a general operational framework that contains all phases and steps needed to be conducted in this work.

Chapter 4 presents an optimization based classification model to build nearest centroid classifier (NCC) for EEGs. The solution encoding and fitness function in this model are explained. The chapter describes in details two methods abstracted from the model by employing the clonal selection and particle swarm optimization (PSO) for optimization process. The experimental results of these algorithms are presented and their performances are discussed.

Chapter 5 introduces a classification model based on negative selection and optimization. The hybridization schema of the model to represent each class of the problem by a set of detectors is presented. The two versions of this model based on the use of clonal selection and PSO for optimization are developed and their performance for epileptic seizures recognition in EEGs is studied.

Chapter 6 illustrates an optimization based negative selection detection model for epilepsy diagnosis in EEGs. The chapter explains the schematic representation of the model and broadly discusses how a set of detectors is generated using negative selection algorithm (NSA) and optimized by clonal selection and PSO to recognize the epileptic activity in brain. At the end of the chapter, the results of all experiments conducted on different methods of this model are described accompanied with overall discussion.

Finally, Chapter 7 draws overall conclusions of the thesis, and highlights the contributions of this research. Recommendations and suggestions for possible future work are also discussed in the chapter.

REFERENCES

- Aarabi, A., Wallois, F. and Grebe, R. (2008). Does spatiotemporal synchronization of EEG change prior to absence seizures?. *Brain Research*. 1188 (0), 207-221.
- Abe, S. (2005). *Support vector machines for pattern classification*. London, UK: Springer.
- Acharya, U. R., Molinari, F., Sree, S. V., Chattopadhyay, S., Ng, K.-H. and Suri, J. S. (2012a). Automated diagnosis of epileptic EEG using entropies. *Biomedical Signal Processing and Control*. 7 (4), 401-408.
- Acharya, U. R., Vinitha Sree, S., Alvin, A. P. C. and Suri, J. S. (2012b). Use of principal component analysis for automatic classification of epileptic EEG activities in wavelet framework. *Expert Systems with Applications*. 39 (10), 9072-9078.
- Acır, N. and Güzeliş, C. (2004). Automatic spike detection in EEG by a two-stage procedure based on support vector machines. *Computers in Biology and Medicine*. 34 (7), 561-575.
- Acır, N. (2005). Automated system for detection of epileptiform patterns in EEG by using a modified RBFN classifier. *Expert Systems with Applications*. 29 (2), 455-462.
- Adeli, H., Zhou, Z. and Dadmehr, N. (2003). Analysis of EEG records in an epileptic patient using wavelet transform. *Journal of Neuroscience Methods*. 123 (1), 69-87.
- Ahirwal, M. K., Kumar, A. and Singh, G. K. (2014). Adaptive filtering of EEG/ERP through noise cancellers using an improved PSO algorithm. *Swarm and Evolutionary Computation*. 14 (0), 76-91.
- Ahmed, T. (2004). *Adaptive particle swarm optimizer for dynamic environments*. M.S. Thesis. The University of Texas at Arlington, Arlington, Texas, United States.

- Alam, S. M. S. and Bhuiyan, M. I. H. (2013). Detection of Seizure and Epilepsy Using Higher Order Statistics in the EMD Domain. *IEEE Journal of Biomedical and Health Informatics*. 17 (2), 312-318.
- Alkan, A., Koklukaya, E. and Subasi, A. (2005). Automatic seizure detection in EEG using logistic regression and artificial neural network. *Journal of Neuroscience Methods*. 148 (2), 167-176.
- Altunay, S., Telatar, Z. and Erogul, O. (2010). Epileptic EEG detection using the linear prediction error energy. *Expert Systems with Applications*. 37 (8), 5661-5665.
- Amaral, J. L. M., Amaral, J. F. M. and Tanscheit, R. (2007). Real-Valued Negative Selection Algorithm with a Quasi-Monte Carlo Genetic Detector Generation. In de Castro, L. N., *et al.* (Eds.). *Artificial Immune Systems*, Lecture Notes in Computer Science: LNCS 4628. (pp. 156-167). Berlin Heidelberg: Springer-Verlag.
- Amaral, J. M. (2011). Fault Detection in Analog Circuits Using a Fuzzy Dendritic Cell Algorithm. In Liò, P., *et al.* (Eds.). *Artificial Immune Systems*, Lecture Notes in Computer Science: LNCS 6825. (pp. 294-307). Berlin Heidelberg: Springer-Verlag.
- Amirmazlaghani, M. and Amindavar, H. (2009). *EMG signal denoising via Bayesian wavelet shrinkage based on GARCH modeling*. Proceedings of the IEEE International Conference on Acoustics, Speech and Signal Processing. 19-24 April. Taipei, Taiwan, 469-472.
- Andrzejak, R. G., Lehnertz, K., Mormann, F., Rieke, C., David, P. and Elger, C. E. (2001). Indications of nonlinear deterministic and finite-dimensional structures in time series of brain electrical activity: Dependence on recording region and brain state. *Physical Review E*. 64 (6), 061907.
- Atyabi, A., Luerssen, M. H. and Powers, D. M. W. (2013). PSO-based dimension reduction of EEG recordings: Implications for subject transfer in BCI. *Neurocomputing*. 119 (0), 319-331.
- Ayaz, E., Öztürk, A., Seker, S. and Upadhyaya, B. R. (2009). Fault detection based on continuous wavelet transform and sensor fusion in electric motors. *Compel - The International Journal for Computation and Mathematics in Electrical and Electronic Engineering*. 28 (2), 454-470.

- Aydin, I., Karakose, M. and Akin, E. (2008). *Artificial immune inspired fault detection algorithm based on fuzzy clustering and genetic algorithm methods*. The IEEE International Conference on Computational Intelligence for Measurement Systems and Applications. 14-16 July. Istanbul, Turkey, 93-98.
- Aydin, I., Karakose, M. and Akin, E. (2010). Chaotic-based hybrid negative selection algorithm and its applications in fault and anomaly detection. *Expert Systems with Applications*. 37 (7), 5285-5294.
- Aziz, J. N. Y. (2007). *Multi-channel signal-processing integrated neural interfaces*. M.A.Sc. Thesis. University of Toronto, Canada.
- Bao, F. S., Lie, D. Y. C. and Yuanlin, Z. (2008). *A New Approach to Automated Epileptic Diagnosis Using EEG and Probabilistic Neural Network*. 20th IEEE International Conference on Tools with Artificial Intelligence. 3-5 Nov. Dayton, Ohio, 482-486.
- Bonabeau, E., Dorigo, M. and Theraulaz, G. (1999). *Swarm intelligence: from natural to artificial systems*: Oxford university press.
- Brownlee, J. (2007). Clonal selection algorithms. *Complex Intelligent Systems Laboratory, Swinburne University of Technology, Australia*.
- Burrus, C. S., Gopinath, R. A., Guo, H., Odegard, J. E. and Selesnick, I. W. (1998). *Introduction to wavelets and wavelet transforms: a primer*. Upper Saddle River, New Jersey: Prentice hall.
- Chai, R., Ling, S., Hunter, G., Tran, Y. and Nguyen, H. (2013 In Press). Brain Computer Interface Classifier for Wheelchair Commands using Neural Network with Fuzzy Particle Swarm Optimization. *IEEE Journal of Biomedical and Health Informatics*. VV (99), PP.
- Chai, R., Ling, S. H., Hunter, G. P., Tran, Y. and Nguyen, H. T. (2014). Brain-Computer Interface Classifier for Wheelchair Commands Using Neural Network With Fuzzy Particle Swarm Optimization. *IEEE Journal of Biomedical and Health Informatics*. 18 (5), 1614-1624.
- Chandaka, S., Chatterjee, A. and Munshi, S. (2009). Cross-correlation aided support vector machine classifier for classification of EEG signals. *Expert Systems with Applications*. 36 (2, Part 1), 1329-1336.
- Cinar, E. and Sahin, F. (2013). New classification techniques for electroencephalogram (EEG) signals and a real-time EEG control of a robot. *Neural Computing and Applications*. 22 (1), 29-39.

- Clerc, M. (1999). *The swarm and the queen: towards a deterministic and adaptive particle swarm optimization*. Proceedings of the 1999 Congress on Evolutionary Computation. 6 - 9 July. Washington, D.C., USA, 1951 -1957.
- Coelho, G. P., Barbante, C. C., Boccato, L., Attux, R. R. F., Oliveira, J. R. and Von Zuben, F. J. (2012). *Automatic feature selection for BCI: An analysis using the davies-bouldin index and extreme learning machines*. The 2012 International Joint Conference on Neural Networks (IJCNN). 10-15 June. Brisbane, Australia, 1-8.
- Cvetkovic, D., Übeyli, E. D. and Cosic, I. (2008). Wavelet Transform Feature Extraction from Human PPG, ECG, and EEG Signal Responses to ELF PEMF Exposures: A Pilot Study. *Digital Signal Processing*. 18 (5), 861-874.
- Dasgupta, D. and Gonzalez, F. (2002). An immunity-based technique to characterize intrusions in computer networks. *IEEE Transactions on Evolutionary Computation*. 6 (3), 281-291.
- Dasgupta, D., KrishnaKumar, K., Wong, D. and Berry, M. (2004). Negative Selection Algorithm for Aircraft Fault Detection. In Nicosia, G., *et al.* (Eds.). *Artificial Immune Systems*, Lecture Notes in Computer Science: LNCS 3239. (pp. 1-13). Berlin Heidelberg: Springer-Verlag.
- Daubechies, I. (1988). Orthonormal bases of compactly supported wavelets. *Communications on pure and applied mathematics*. 41 (7), 909-996.
- Daubechies, I. (1990). The Wavelet Transform, Time-Frequency Localization and Signal Analysis. *IEEE Transactions on Information Theory*. 36 (5), 961-1005.
- De Castro, L. N. and Von Zuben, F. J. (2000). *The clonal selection algorithm with engineering applications*. In Proceedings of GECCO, Workshop on Artificial Immune Systems and Their Applications. July. Las Vegas, USA, 36-39.
- de Castro, L. N. and Timmis, J. (2002a). *An artificial immune network for multimodal function optimization*. Proceedings of IEEE Congress on Evolutionary Computation. May 12-17. Honolulu, Hawaii, 699-704.
- de Castro, L. N. and Timmis, J. (2002b). *Artificial immune systems: a new computational intelligence approach*. London, UK: Springer.
- de Castro, L. N. and Von Zuben, F. J. (2002). Learning and optimization using the clonal selection principle. *IEEE Transactions on Evolutionary Computation*. 6 (3), 239-251.

- de Castro, L. N. and Timmis, J. I. (2003). Artificial immune systems as a novel soft computing paradigm. *Soft Computing*. 7 (8), 526-544.
- De Falco, I., Cioppa, A. D. and Tarantino, E. (2007). Facing classification problems with Particle Swarm Optimization. *Applied Soft Computing*. 7 (3), 652-658.
- Dhiman, R., Saini, J. S. and Priyanka. (2014). Genetic algorithms tuned expert model for detection of epileptic seizures from EEG signatures. *Applied Soft Computing*. 19 (0), 8-17.
- Dorai, A. (2009). *Automated epileptic seizure onset detection*. M.A.Sc. Thesis. University of Waterloo, Waterloo, Ontario, Canada.
- Dursun, M., Ozsen, S., Gunes, S. and Yosunkaya, S. (2012). *Comparison of Artificial Immune Clustering with Fuzzy C-means Clustering in the sleep stage classification problem*. The 2012 International Symposium on Innovations in Intelligent Systems and Applications. 2-4 July. Trabzon, Turkey: IEEE, 1-4.
- Eberhart, R. and Shi, Y. (1998). Comparison between genetic algorithms and particle swarm optimization. In Porto, V. W., *et al.* (Eds.). *Evolutionary Programming VII*, Lecture Notes in Computer Science: LNCS 1447. (pp. 611-616). Berlin Heidelberg: Springer-Verlag.
- Eberhart, R. C. and Shi, Y. (2000). *Comparing inertia weights and constriction factors in particle swarm optimization*. In Proceedings of the 2000 Congress on Evolutionary Computation. 16 -19 July. La Jolla, California, USA, 84-88.
- Eberhart, R. C. and Shi, Y. (2001). *Particle swarm optimization: developments, applications and resources*. Proceedings of the 2001 Congress on Evolutionary Computation. May 27-30. Seoul, Korea, 81-86.
- Engelbrecht, A. P. (2007). *Computational intelligence: an introduction*. (2nd ed.). England: John Wiley & Sons.
- Ermer, J. J. (2001). *Realistic forward modeling and source complexity reduction methods for EEG and MEG*. Ph.D. Thesis. University of Southern California, Los Angeles, California.
- Escalona-Vargas, D. I., Gutiérrez, D. and Lopez-Arevalo, I. (2013). Performance of different metaheuristics in EEG source localization compared to the Cramér–Rao bound. *Neurocomputing*. 120 (0), 597-609.
- Estrada, E. F. (2010). *Computer-aided detection of sleep apnea and sleep stage classification using HRV and EEG signals*. Ph.D. Thesis. The University of Texas at El Paso, El Paso, Texas, United States.

- Firpi, H., Smart, O., Worrell, G., Marsh, E., Dlugos, D. and Litt, B. (2007). High-Frequency Oscillations Detected in Epileptic Networks Using Swarmed Neural-Network Features. *Annals of Biomedical Engineering*. 35 (9), 1573-1584.
- Forrest, S., Perelson, A. S., Allen, L. and Cherukuri, R. (1994). *Self-nonsel self discrimination in a computer*. Proceedings of the 1994 IEEE Computer Society Symposium on Research in Security and Privacy. 16-18 May. Oakland, California, 202-212.
- Fu, K., Qu, J., Chai, Y. and Dong, Y. (2014). Classification of seizure based on the time-frequency image of EEG signals using HHT and SVM. *Biomedical Signal Processing and Control*. 13 (0), 15-22.
- Gandhi, T., Panigrahi, B. K., Bhatia, M. and Anand, S. (2010). Expert model for detection of epileptic activity in EEG signature. *Expert Systems with Applications*. 37 (4), 3513-3520.
- Gandhi, T. K., Chakraborty, P., Roy, G. G. and Panigrahi, B. K. (2012). Discrete harmony search based expert model for epileptic seizure detection in electroencephalography. *Expert Systems with Applications*. 39 (4), 4055-4062.
- Gao, X. Z., Ovaska, S. J. and Wang, X. (2006). *Genetic Algorithms-based Detector Generation in Negative Selection Algorithm*. Proceedings of the 2006 IEEE Mountain Workshop on Adaptive and Learning Systems. 24-26 July. Logan, Utah, 133-137.
- Gao, X. Z., Ovaska, S. J. and Wang, X. (2007). *Particle Swarm Optimization of detectors in Negative Selection Algorithm*. In Proceedings of the IEEE International Conference on Systems, Man and Cybernetics. 7-10 Oct. Montreal, Quebec, Canada, 1236-1242.
- Gao, X. Z., Ovaska, S. J., Wang, X. and Chow, M. Y. (2008). A neural networks-based negative selection algorithm in fault diagnosis. *Neural Computing and Applications*. 17 (1), 91-98.
- Gao, X. Z., Ovaska, S. J., Wang, X. and Chow, M. Y. (2009a). Clonal optimization-based negative selection algorithm with applications in motor fault detection. *Neural Computing and Applications*. 18 (7), 719-729.

- Gao, X. Z., Wang, X. and Ovaska, S. J. (2009b). Fusion of clonal selection algorithm and differential evolution method in training cascade-correlation neural network. *Neurocomputing*. 72 (10–12), 2483-2490.
- Gardner, A. B. (2004). *A novelty detection approach to seizure analysis from intracranial EEG*. Ph.D. Thesis. Georgia Institute of Technology, Georgia, United States.
- Garrett, S. M. (2005). How Do We Evaluate Artificial Immune Systems?. *Evolutionary Computation*. 13 (2), 145-177.
- Ghosh-Dastidar, S. (2007). *Models of EEG data mining and classification in temporal lobe epilepsy: Wavelet-chaos-neural network methodology and spiking neural networks*. Ph.D. Thesis. The Ohio State University, Columbus, Ohio, United States.
- Ghosh Dastidar, S. (2007). *Models of EEG data mining and classification in temporal lobe epilepsy: Wavelet-chaos-neural network methodology and spiking neural networks*. Ph.D. Thesis. The Ohio State University.
- Goel, N., Singh, S. and Aseri, T. C. (2013). A Review of Soft Computing Techniques for Gene Prediction. *ISRN Genomics*. 2013 (Article ID 191206), 8 pages.
- Gonzalez, F. A. (2003). *A study of artificial immune systems applied to anomaly detection*. Ph.D. Thesis. The University of Memphis, Memphis, Tennessee, United States.
- Gotman, J. (1982). Automatic recognition of epileptic seizures in the EEG. *Electroencephalography and clinical neurophysiology*. 54 (5), 530-540.
- Gotman, J. (1999). Automatic detection of seizures and spikes. *Journal of Clinical Neurophysiology*. 16 (2), 130-140.
- Graaff, A. J. and Engelbrecht, A. P. (2006). Optimized coverage of non-self with evolved lymphocytes in an artificial immune system. *International Journal of Computational Intelligence Research*. 2 (2), 127-150.
- Graham, J. K. (2005). *Combining particle swarm optimization and genetic programming utilizing LISP*. M.S. Thesis. Utah State University, Logan, Utah, United States.
- Grewal, S. and Gotman, J. (2005). An automatic warning system for epileptic seizures recorded on intracerebral EEGs. *Clinical neurophysiology*. 116 (10), 2460-2472.

- Güler, İ. and Übeyli, E. D. (2005). Adaptive neuro-fuzzy inference system for classification of EEG signals using wavelet coefficients. *Journal of Neuroscience Methods*. 148 (2), 113-121.
- Güler, N. F., Übeyli, E. D. and Güler, İ. (2005). Recurrent neural networks employing Lyapunov exponents for EEG signals classification. *Expert Systems with Applications*. 29 (3), 506-514.
- Guo, L., Rivero, D., Dorado, J., Munteanu, C. R. and Pazos, A. (2011). Automatic feature extraction using genetic programming: An application to epileptic EEG classification. *Expert Systems with Applications*. 38 (8), 10425-10436.
- Guo, L., Wu, Y., Zhao, L., Cao, T., Yan, W. and Shen, X. (2011). Classification of Mental Task From EEG Signals Using Immune Feature Weighted Support Vector Machines. *IEEE Transactions on Magnetics*. 47 (5), 866-869.
- Hapuarachchi, P. (2006). *Feature selection and artifact removal in sleep stage classification*. M.A.Sc. Thesis. University of Waterloo, Waterloo, Ontario, Canada.
- Hema, C. R., Paulraj, M. P., Nagarajan, R., Yaacob, S. and Adom, A. H. (2008). Application of particle swarm optimization for EEG signal classification. *Biomedical Soft Computing and Human Sciences*. 13 (1), 79-84.
- Hoffmeyr, S. and Forrest, S. (1999). *Immunity by design: An artificial immune system*. Proceedings of the Genetic and Evolutionary Computation Conference. 13-17 July. Orlando, Florida, USA, 1289--1296.
- Homan, R. W., Herman, J. and Purdy, P. (1987). Cerebral location of international 10–20 system electrode placement. *Electroencephalography and Clinical Neurophysiology*. 66 (4), 376-382.
- Hsu, K.-C. and Yu, S.-N. (2010). Detection of seizures in EEG using subband nonlinear parameters and genetic algorithm. *Computers in Biology and Medicine*. 40 (10), 823-830.
- Huang, C.-L. and Dun, J.-F. (2008). A distributed PSO–SVM hybrid system with feature selection and parameter optimization. *Applied Soft Computing*. 8 (4), 1381-1391.
- Hur, J. (2007). *Multi-robot system control using Artificial Immune System*. Ph.D. Thesis. The University of Texas at Austin, Texas, United States.
- Igawa, K. and Ohashi, H. (2009). A negative selection algorithm for classification and reduction of the noise effect. *Applied Soft Computing*. 9 (1), 431-438.

- Iscan, Z., Dokur, Z. and Demiralp, T. (2011). Classification of electroencephalogram signals with combined time and frequency features. *Expert Systems with Applications*. 38 (8), 10499-10505.
- Ives, J., Thompson, C. and Woods, J. (1973). Acquisition by telemetry and computer analysis of 4-channel long-term EEG recordings from patients subject to "petit-mal" absence attacks. *Electroencephalography and clinical neurophysiology*. 34 (6), 665-668.
- Ives, J. R., Thompson, C. J., Gloor, P., Oliver, A. and Woods, J. F. (1974). The on-line computer detection and recording of spontaneous temporal lobe epileptic seizures from patients with implanted depth electrodes via a radio telemetry link. *Electroencephalography Clinical Neurophysiology*. 37, 205-974.
- Jasper, H. H. (1958). The ten twenty electrode system of the international federation. *Electroencephalography and Clinical Neurophysiology*. 10, 371-375.
- Jerne, N. K. (1974). Towards a network theory of the immune system. *In Annals of Immunology*. 125 (1-2), 373-389.
- Ji, Z. and Dasgupta, D. (2007). Revisiting Negative Selection Algorithms. *Evolutionary Computation*. 15 (2), 223-251.
- Jin, J., Wang, X. and Zhang, J. (2008). *Optimal selection of EEG electrodes via DPSO algorithm*. Proceedings of the 7th World Congress on Intelligent Control and Automation. 25-27 June. Chongqing, China: IEEE, 5095-5099.
- Jin, N. (2008). *Particle swarm optimization in engineering electromagnetics*. Ph.D. Thesis. University of California, Los Angeles, California, United States.
- Jordan, K. G. (1993). Continuous EEG and Evoked Potential Monitoring in the Neuroscience Intensive Care Unit. *Journal of Clinical Neurophysiology*. 10 (4), 445-475.
- Joshi, V., Pachori, R. B. and Vijesh, A. (2014). Classification of ictal and seizure-free EEG signals using fractional linear prediction. *Biomedical Signal Processing and Control*. 9 (0), 1-5.
- Kannathal, N., Choo, M. L., Acharya, U. R. and Sadasivan, P. K. (2005). Entropies for detection of epilepsy in EEG. *Computer Methods and Programs in Biomedicine*. 80 (3), 187-194.
- Karim, A. and Adeli, H. (2002). Incident detection algorithm using wavelet energy representation of traffic patterns. *Journal of Transportation Engineering*. 128 (3), 232-242.

- Kaya, Y., Uyar, M., Tekin, R. and Yıldırım, S. (2014). 1D-local binary pattern based feature extraction for classification of epileptic EEG signals. *Applied Mathematics and Computation*. 243 (0), 209-219.
- Kelsey, J. and Timmis, J. (2003). Immune Inspired Somatic Contiguous Hypermutation for Function Optimisation. In Cantú-Paz, E., *et al.* (Eds.). *Genetic and Evolutionary Computation*, Lecture Notes in Computer Science: LNCS 2723. (pp. 207-218). Berlin Heidelberg: Springer-Verlag.
- Kennedy, J. and Eberhart, R. (1995). *Particle swarm optimization*. In Proceedings of the IEEE International Conference on Neural Networks. 27 Nov - 1 Dec. Perth, Australia, 1942-1948.
- Kennedy, J. (1997). *The particle swarm: social adaptation of knowledge*. In IEEE International Conference on Evolutionary Computation. 13-16 April. Indianapolis, USA, 303-308.
- Kennedy, J. and Eberhart, R. C. (1997). *A discrete binary version of the particle swarm algorithm*. Proceedings of the 1997 IEEE International Conference on Systems, Man, and Cybernetics: Computational Cybernetics and Simulation. 12-15 Oct. Orlando, Florida, USA, 4104-4108.
- Kennedy, J. (1999). *Small worlds and mega-minds: effects of neighborhood topology on particle swarm performance*. Proceedings of the 1999 Congress on Evolutionary Computation. July 6-9. Washington D.C., USA, 1931-1938.
- Kennedy, J. and Mendes, R. (2002). *Population structure and particle swarm performance*. Proceedings of the 2002 Congress on Evolutionary Computation. May 12-17. Honolulu, Hawaii, 1671-1676.
- Kim, J.-Y., Park, S.-M., Ko, K.-E. and Sim, K.-B. (2012). A Binary PSO-Based Optimal EEG Channel Selection Method for a Motor Imagery Based BCI System. In Lee, G., *et al.* (Eds.). *Convergence and Hybrid Information Technology*, Communications in Computer and Information Science: CCIS 310. (pp. 245-252). Berlin Heidelberg: Springer-Verlag.
- Kordylewski, H., Graupe, D. and Kai, L. (2001). A novel large-memory neural network as an aid in medical diagnosis applications. *IEEE Transactions on Information Technology in Biomedicine*. 5 (3), 202-209.
- Kumar, S. P., Sriraam, N., Benakop, P. G. and Jinaga, B. C. (2010). Entropies based detection of epileptic seizures with artificial neural network classifiers. *Expert Systems with Applications*. 37 (4), 3284-3291.

- Kumar, T. S., Kanhangad, V. and Pachori, R. B. (2015). Classification of seizure and seizure-free EEG signals using local binary patterns. *Biomedical Signal Processing and Control*. 15 (0), 33-40.
- Kumar, Y., Dewal, M. L. and Anand, R. S. (2014). Epileptic seizure detection using DWT based fuzzy approximate entropy and support vector machine. *Neurocomputing*. 133 (0), 271-279.
- Laurent, F. (2008). *Predicting epileptic seizures from intracranial EEG*. M.Eng. Thesis. McGill University, Montreal, Canada.
- Laurentys, C. A., Ronacher, G., Palhares, R. M. and Caminhas, W. M. (2010). Design of an Artificial Immune System for fault detection: A Negative Selection Approach. *Expert Systems with Applications*. 37 (7), 5507-5513.
- Lee, S.-H., Lim, J. S., Kim, J.-K., Yang, J. and Lee, Y. (2014). Classification of normal and epileptic seizure EEG signals using wavelet transform, phase-space reconstruction, and Euclidean distance. *Computer Methods and Programs in Biomedicine*. 116 (1), 10-25.
- Leung, K., Cheong, F. and Cheong, C. (2007). Generating Compact Classifier Systems Using a Simple Artificial Immune System. *IEEE Transactions on Systems, Man, and Cybernetics, Part B: Cybernetics*. 37 (5), 1344-1356.
- Li, S., Zhou, W., Yuan, Q., Geng, S. and Cai, D. (2013). Feature extraction and recognition of ictal EEG using EMD and SVM. *Computers in Biology and Medicine*. 43 (7), 807-816.
- Li, Y. (2010). *Multichannel EEG signal classification - A geometric approach*. Ph.D. Thesis. McMaster University, Canada.
- Liang, S.-F., Wang, H.-C. and Chang, W.-L. (2010). Combination of EEG Complexity and Spectral Analysis for Epilepsy Diagnosis and Seizure Detection. *EURASIP Journal on Advances in Signal Processing*. 2010 (Article ID 853434), 15 pages.
- Lin, C.-J. and Hsieh, M.-H. (2009). Classification of mental task from EEG data using neural networks based on particle swarm optimization. *Neurocomputing*. 72 (4-6), 1121-1130.
- Lin, I. L. (2005). *Particle swarm optimization for solving constraint satisfaction problems*. M.Sc. Thesis. Simon Fraser University, Burnaby, British Columbia, Canada.

- Liu, Y., Zhou, W., Yuan, Q. and Chen, S. (2012). Automatic Seizure Detection Using Wavelet Transform and SVM in Long-Term Intracranial EEG. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*. 20 (6), 749-755.
- Madan, T. (2005). *Compression of long-term EEG using power spectral density*. M.A.Sc. Thesis. Concordia University, Montreal, Quebec, Canada.
- Majumdar, K. (2011). Human scalp EEG processing: Various soft computing approaches. *Applied Soft Computing*. 11 (8), 4433-4447.
- Mallat, S. G. (1989). A theory for multiresolution signal decomposition: the wavelet representation. *IEEE Transactions on Pattern Analysis and Machine Intelligence*. 11 (7), 674-693.
- Meng, L., Jin, J. and Wang, X. (2011). *A comparison of three electrode channels selection methods applied to SSVEP BCI*. Proceedings of the 4th International Conference on Biomedical Engineering and Informatics. 15-17 Oct. Shanghai, China: IEEE, 584-587.
- Meyer, Y. and Ryan, R. D. (1993). *Wavelets: Algorithms and Applications*. Philadelphia, PA: Society for Industrial and Applied Mathematics.
- Mihandoost, S., Amirani, M., Mazlaghani, M. and Mihandoost, A. (2012). Automatic feature extraction using generalised autoregressive conditional heteroscedasticity model: an application to electroencephalogram classification. *Signal Processing, IET*. 6 (9), 829-838.
- Mohammed, A. W. and Zhang, M. (2008). *Evaluation of particle swarm optimization based centroid classifier with different distance metrics*. Proceedings of the IEEE Congress on Evolutionary Computation: the IEEE World Congress on Computational Intelligence. 1-6 June. Hong Kong, China, 2929-2932.
- Nakamura, T., Ito, S., Mitsukura, Y. and Setokawa, H. (2009). *A Method for Evaluating the Degree of Human's Preference Based on EEG Analysis*. In Proceedings of the Fifth International Conference on Intelligent Information Hiding and Multimedia Signal Processing. 12-14 Sept. Kyoto, Japan, 732-735.
- Neal, M. (2002). *An Artificial Immune System for Continuous Analysis of Time-varying Data*. In Proceedings of the First International Conference on Artificial Immune Systems, 76-85.

- Nguyen, L. B., Nguyen, A. V., Sai Ho, L. and Nguyen, H. T. (2012). *A particle swarm optimization-based neural network for detecting nocturnal hypoglycemia using electroencephalography signals*. In Proceedings of the 2012 International Joint Conference on Neural Networks. 10-15 June. Brisbane, Australia: IEEE, 1-6.
- Nicolaou, N. and Georgiou, J. (2012). Detection of epileptic electroencephalogram based on Permutation Entropy and Support Vector Machines. *Expert Systems with Applications*. 39 (1), 202-209.
- Niknazar, M., Mousavi, S. R., Vosoughi Vahdat, B. and Sayyah, M. (2013). A New Framework Based on Recurrence Quantification Analysis for Epileptic Seizure Detection. *IEEE Journal of Biomedical and Health Informatics*. 17 (3), 572-578.
- Nunes, T. M., Coelho, A. L. V., Lima, C. A. M., Papa, J. P. and de Albuquerque, V. H. C. (2014). EEG signal classification for epilepsy diagnosis via optimum path forest – A systematic assessment. *Neurocomputing*. 136 (0), 103-123.
- Ocak, H. (2008). Optimal classification of epileptic seizures in EEG using wavelet analysis and genetic algorithm. *Signal Processing*. 88 (7), 1858-1867.
- Ocak, H. (2009). Automatic detection of epileptic seizures in EEG using discrete wavelet transform and approximate entropy. *Expert Systems with Applications*. 36 (2, Part 1), 2027-2036.
- Omran, M. G. H., Engelbrecht, A. P. and Salman, A. (2005). *Dynamic clustering using particle swarm optimization with application in unsupervised image classification*. The Fifth World Enformatika Conference (ICCI 2005). November. Prague, Czech Republic, 199-204.
- Omran, M. H., Engelbrecht, A. & Salman, A. (2006). Particle Swarm Optimization for Pattern Recognition and Image Processing. In Abraham, A., *et al.* (Eds.). *Swarm Intelligence in Data Mining*, Studies in Computational Intelligence: SCI 34. (pp. 125-151). Berlin Heidelberg: Springer-Verlag.
- Oostenveld, R. and Praamstra, P. (2001). The five percent electrode system for high-resolution EEG and ERP measurements. *Clinical Neurophysiology*. 112 (4), 713-719.
- Orhan, U., Hekim, M. and Ozer, M. (2011). EEG signals classification using the K-means clustering and a multilayer perceptron neural network model. *Expert Systems with Applications*. 38 (10), 13475-13481.

- Pachori, R. B. and Patidar, S. (2014). Epileptic seizure classification in EEG signals using second-order difference plot of intrinsic mode functions. *Computer Methods and Programs in Biomedicine*. 113 (2), 494-502.
- Patnaik, L. M. and Manyam, O. K. (2008). Epileptic EEG detection using neural networks and post-classification. *Computer Methods and Programs in Biomedicine*. 91 (2), 100-109.
- Peng, Y. and Lu, B.-L. (2012). *Immune clonal algorithm based feature selection for epileptic EEG signal classification*. Proceedings of the 11th International Conference on Information Science, Signal Processing and their Applications. 2-5 July. Montreal, Quebec, Canada: IEEE, 848-853.
- Polat, K. and Güneş, S. (2007). Classification of epileptiform EEG using a hybrid system based on decision tree classifier and fast Fourier transform. *Applied Mathematics and Computation*. 187 (2), 1017-1026.
- Polat, K. and Güneş, S. (2008). Artificial immune recognition system with fuzzy resource allocation mechanism classifier, principal component analysis and FFT method based new hybrid automated identification system for classification of EEG signals. *Expert Systems with Applications*. 34 (3), 2039-2048.
- Qiu, L., Li, Y. and Yao, D. (2005). *A feasibility study of EEG dipole source localization using particle swarm optimization*. The 2005 IEEE Congress on Evolutionary Computation. 2-5 Sept. Edinburgh, Scotland, UK, 720-726 Vol.1.
- Qu, H. and Gotman, J. (1995). A seizure warning system for long-term epilepsy monitoring. *Neurology*. 45 (12), 2250-2254.
- Rabbi, A. F. (2013). *Epileptic seizure detection and prediction from electroencephalogram using neuro-fuzzy algorithms*. Ph.D. Thesis. The University of North Dakota, Grand Forks, North Dakota.
- Samant, A. and Adeli, H. (2000). Feature Extraction for Traffic Incident Detection Using Wavelet Transform and Linear Discriminant Analysis. *Computer-Aided Civil and Infrastructure Engineering*. 15 (4), 241-250.
- Scanziani, M. and Häusser, M. (2009). Electrophysiology in the age of light. *Nature*. 461 (7266), 930-939.

- Sharma, R. and Pachori, R. B. (2015). Classification of epileptic seizures in EEG signals based on phase space representation of intrinsic mode functions. *Expert Systems with Applications*. 42 (3), 1106-1117.
- Shi, Y. and Eberhart, R. (1998). *A modified particle swarm optimizer*. Proceedings of the 1998 IEEE International Conference on Evolutionary Computation: IEEE World Congress on Computational Intelligence. 4-9 May. Anchorage, Alaska, 69-73.
- Shibasaki, H. (2008). Human brain mapping: Hemodynamic response and electrophysiology. *Clinical Neurophysiology*. 119 (4), 731-743.
- Shirvany, Y., Edelvik, F., Jakobsson, S., Hedstrom, A., Mahmood, Q., Chodorowski, A. and Persson, M. (2012). *Non-invasive EEG source localization using particle swarm optimization: A clinical experiment*. The 34th Annual International Conference of the IEEE Engineering in Medicine and Biology Society. 28 Aug. - 1 Sept. San Diego, California, USA, 6232-6235.
- Shirvany, Y., Edelvik, F., Jakobsson, S., Hedström, A. and Persson, M. (2013). Application of particle swarm optimization in epileptic spike EEG source localization. *Applied Soft Computing*. 13 (5), 2515-2525.
- Shirvany, Y., Mahmood, Q., Edelvik, F., Jakobsson, S., Hedstrom, A. and Persson, M. (2014). Particle Swarm Optimization Applied to EEG Source Localization of Somatosensory Evoked Potentials. *IEEE Transactions on Neural Systems and Rehabilitation Engineering*. 22 (1), 11-20.
- Shojaie, S. and Moradi, M. H. (2008). *An Evolutionary Artificial Immune System for feature selection and parameters optimization of support vector machines for ERP assessment in a P300-based GKT*. Proceedings of the 2008 Cairo International Biomedical Engineering Conference. 18-20 Dec. Cairo, Egypt: IEEE, 1-5.
- Siuly, Li, Y. and Wen, P. (2011). Clustering technique-based least square support vector machine for EEG signal classification. *Computer Methods and Programs in Biomedicine*. 104 (3), 358-372.
- Smith, S. L. and Timmis, J. (2008). An immune network inspired evolutionary algorithm for the diagnosis of Parkinson's disease. *Biosystems*. 94 (1-2), 34-46.

- Song, Y. and Zhang, J. (2013). Automatic recognition of epileptic EEG patterns via Extreme Learning Machine and multiresolution feature extraction. *Expert Systems with Applications*. 40 (14), 5477-5489.
- Stam, C. J., Pijn, J. P. M., Suffczynski, P. and Lopes da Silva, F. H. (1999). Dynamics of the human alpha rhythm: evidence for non-linearity. *Clinical Neurophysiology*. 110 (10), 1801-1813.
- Stewart, A. X., Nuthmann, A. & Sanguinetti, G. (2014). Single-trial classification of EEG in a visual object task using ICA and machine learning. *Journal of Neuroscience Methods*, 228: 1-14.
- Subasi, A. (2005a). Automatic recognition of alertness level from EEG by using neural network and wavelet coefficients. *Expert Systems with Applications*. 28 (4), 701-711.
- Subasi, A. (2005b). Epileptic seizure detection using dynamic wavelet network. *Expert Systems with Applications*. 29 (2), 343-355.
- Subasi, A. and Erçelebi, E. (2005). Classification of EEG signals using neural network and logistic regression. *Computer Methods and Programs in Biomedicine*. 78 (2), 87-99.
- Subasi, A. (2006). Automatic detection of epileptic seizure using dynamic fuzzy neural networks. *Expert Systems with Applications*. 31 (2), 320-328.
- Subasi, A. (2007). EEG signal classification using wavelet feature extraction and a mixture of expert model. *Expert Systems with Applications*. 32 (4), 1084-1093.
- Subasi, A. and GURSOY, M. I. (2010). EEG signal classification using PCA, ICA, LDA and support vector machines. *Expert Systems with Applications*. 37 (12), 8659-8666.
- Tang, Y. and Durand, D. M. (2012). A tunable support vector machine assembly classifier for epileptic seizure detection. *Expert Systems with Applications*. 39 (4), 3925-3938.
- Tezel, G. and özbay, Y. (2009). A new approach for epileptic seizure detection using adaptive neural network. *Expert Systems with Applications*. 36 (1), 172-180.
- Timmis, J., Neal, M. and Hunt, J. (2000). An artificial immune system for data analysis. *Biosystems*. 55 (1-3), 143-150.
- Timmis, J. and Neal, M. (2001). A resource limited artificial immune system for data analysis. *Knowledge-Based Systems*. 14 (3-4), 121-130.

- Timmis, J., Edmonds, C. and Kelsey, J. (2004). *Assessing the performance of two immune inspired algorithms and a hybrid genetic algorithm for function optimisation*. Proceedings of the Congress on Evolutionary Computation. June 19-23. Portland, Oregon, USA, 1044-1051.
- Timmis, J., Hone, A., Stibor, T. and Clark, E. (2008). Theoretical advances in artificial immune systems. *Theoretical Computer Science*. 403 (1), 11-32.
- Trojanowski, K. and Wierzchoń, S. T. (2009). Immune-based algorithms for dynamic optimization. *Information Sciences*. 179 (10), 1495-1515.
- Übeyli, E. D. (2008a). Analysis of EEG signals by combining eigenvector methods and multiclass support vector machines. *Computers in Biology and Medicine*. 38 (1), 14-22.
- Übeyli, E. D. (2008b). Wavelet/mixture of experts network structure for EEG signals classification. *Expert Systems with Applications*. 34 (3), 1954-1962.
- Übeyli, E. D. (2009a). Analysis of EEG signals by implementing eigenvector methods/recurrent neural networks. *Digital Signal Processing*. 19 (1), 134-143.
- Übeyli, E. D. (2009b). Automatic detection of electroencephalographic changes using adaptive neuro-fuzzy inference system employing Lyapunov exponents. *Expert Systems with Applications*. 36 (5), 9031-9038.
- Übeyli, E. D. (2009c). Combined neural network model employing wavelet coefficients for EEG signals classification. *Digital Signal Processing*. 19 (2), 297-308.
- Übeyli, E. D. (2009d). Decision support systems for time-varying biomedical signals: EEG signals classification. *Expert Systems with Applications*. 36 (2, Part 1), 2275-2284.
- Übeyli, E. D. (2009e). Measuring saliency of features representing EEG signals using signal-to-noise ratios. *Expert Systems with Applications*. 36 (1), 501-509.
- Übeyli, E. D. (2009f). Statistics over features: EEG signals analysis. *Computers in Biology and Medicine*. 39 (8), 733-741.
- Übeyli, E. D. (2010). Least squares support vector machine employing model-based methods coefficients for analysis of EEG signals. *Expert Systems with Applications*. 37 (1), 233-239.

- Uy, E. T. (2005). *A quantitative evaluation of dry-sensor electroencephalography*. Ph.D. Thesis. Stanford University, California, United States.
- Wang, C.-M., Kuo, C.-T., Lin, C.-Y. and Chang, G.-H. (2008). Application of artificial immune system approach in MRI classification. *EURASIP Journal on Advances in Signal Processing*. 2008 (Article ID 547684), 8 pages.
- Wang, D., Miao, D. and Xie, C. (2011). Best basis-based wavelet packet entropy feature extraction and hierarchical EEG classification for epileptic detection. *Expert Systems with Applications*. 38 (11), 14314-14320.
- Wang, Z., Zhang, Q. and Zhang, D. (2007). *A PSO-Based Web Document Classification Algorithm*. In Proceedings of the Eighth IEEE ACIS International Conference on Software Engineering, Artificial Intelligence, Networking, and Parallel/Distributed Computing. 30 July - 1 August. Qingdao, China, 659-664.
- Wen, C., Xiaoming, D., Tao, L. and Tao, Y. (2014). Negative selection algorithm based on grid file of the feature space. *Knowledge-Based Systems*. 56 (0), 26-35.
- Wong, D. K. (2004). *Multichannel classification of brain-wave representations of language by perceptron-based models and independent component analysis*. Ph.D. Thesis. Stanford University, California, United States.
- Wongsawat, Y. (2007). *On the study of multi-channel EEG: Lossless compression, signal modeling and classification*. Ph.D. Thesis. The University of Texas at Arlington, Arlington, Texas, United States.
- Xiao, H. (2006). *A new multiobjective optimization algorithm based on artificial immune systems and its engineering application*. Ph.D. Thesis. University of Toronto, Toronto, Canada.
- Xinmin, T., Baoxiang, D. and Yong, X. (2007). *One-class Bearing Fault Detection using Negative Clone Selection Algorithm*. The 33rd Annual Conference of the IEEE Industrial Electronics Society. 5-8 Nov. Taipei, Taiwan, 2672-2677.
- Xu, P., Tian, Y., Lei, X. and Yao, D. (2010). Neuroelectric source imaging using 3SCO: A space coding algorithm based on particle swarm optimization and l_0 norm constraint. *NeuroImage*. 51 (1), 183-205.
- Xu, P., Liu, T., Zhang, R., Zhang, Y. and Yao, D. (2014). Using particle swarm to select frequency band and time interval for feature extraction of EEG based BCI. *Biomedical Signal Processing and Control*. 10 (0), 289-295.

- Xu, Q., Zhou, H., Wang, Y. and Huang, J. (2009). Fuzzy support vector machine for classification of EEG signals using wavelet-based features. *Medical Engineering & Physics*. 31 (7), 858-865.
- Zainuddin, Z., Huong, L. K. and Pauline, O. (2012). On the Use of Wavelet Neural Networks in the Task of Epileptic Seizure Detection from Electroencephalography Signals. *Procedia Computer Science*. 11 (0), 149-159.
- Zhiping, H., Guangming, C., Cheng, C., He, X. and Jiakai, Z. (2010). *A new EEG feature selection method for self-paced brain-computer interface*. The 10th IEEE International Conference on Intelligent Systems Design and Applications. 29 Nov. - 1 Dec. Cairo, Egypt, 845-849.