

MICRO HYDRAULIC TURBINE FOR POWER GENERATION IN MICRO
SCALE CHANNELS

ALY HASSAN ABDALLA ABDELBAKY

UNIVERSITI TEKNOLOGI MALAYSIA

MICRO HYDRAULIC TURBINE FOR POWER GENERATION IN MICRO
SCALE CHANNELS

ALY HASSAN ABDALLA ABDELBAKY

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Mechanical Engineering)

Faculty of Mechanical Engineering
Universiti Teknologi Malaysia

JANUARY 2016

Dedicated to my beloved family and to soul of my brother Abdalla
for their toleration and sincere help during my life.

ACKNOWLEDGEMENT

In the Name of Allah, Most Gracious, Most Merciful

At the beginning, I would like to thank "Allah Taala" for his innumerable blessings and guidance that enabled me to complete this work successfully.

I am indebted to my main supervisor **Prof. Dr Omar Yaakob**, for his helpful guidance, patience and support during the progress of this investigation and for his comments on the draft of the thesis. From the inception of this study until its completion.

I wish to express my deepest gratitude and sincerest appreciation to my co supervisor **Dr. Yasser Ahmed**, he has generously provided me with continuous guidance and encouragement which contributed measurably to complete this work.

I wish to express my gratitude to **my parents, my wife and my brother Abdalla (God bless his soul)** who have gracefully shared and endured my ups and downs during this endeavour.

I would like to thank the **Universiti Teknologi Malaysia (UTM)** for giving me the opportunity to accomplish this work through the laboratory facilities and library.

Finally, I wish to express my deepest gratitude and sincerest appreciation to all those who offered me advices and suggestions.

ABSTRACT

Micro hydrokinetic energy scheme presents an attractive, environmentally friendly and efficient electric generation in rural, remote and hilly areas. However, this scheme is yet to be fully discovered, as researchers are still searching for solution for the main problems of low velocity of current in the open flow channels and low efficiency of hydrokinetic turbines. This research proposes a novel system configuration to capture as much as kinetic energy from stream water current. Deploying acceleration nozzle in channels is a unique solution for increasing the efficiency of channels' current flow systems while the use of micro hydraulic cross flow turbine (CFT)/ Banki turbine is the most proper and practical solution. This system, known as bidirectional diffuser augmented (BDA) channel, functions by utilizing dual directed nozzles in the flow, and surrounded by dual cross flow/ Banki turbines. In this study, numerical and experimental investigations were carried out to study the flow field characteristics of the new system approach with and without turbines. A numerical investigation was carried out in this research work using finite volume Reynolds-Averaged Navier-Stokes Equations (RANSE) code ANSYS CFX and Fluent. Validation was carried out by using experiments, with and without turbines. The flow characteristics through channel and the performance of the twin (lower and upper) cross flow turbines were studied, and it was found that the water flow speed had been significantly enhanced due to the current BDA system in which the speed of the flow was increased by 400%. The maximum efficiency of the overall system with two turbines was nearly 55.7%. The efficiency was relatively low compared to hydraulic turbine efficiency, however, this can be considered very good in view that head available to the present system was very low. The use of this system will contribute towards a more efficient utilization of flows in rivers and channels for electrical generation in rural areas.

ABSTRAK

Sistem tenaga mikro hidrokinetik merupakan sumber janaan tenaga yang mesra alam dan cekap di luar bandar, pedalaman dan kawasan berbukit. Walau bagaimanapun, sistem ini masih belum dikaji sepenuhnya dan para pengkaji masih mencari penyelesaian kepada masalah halaju yang perlahan dalam saluran air terbuka dan rendahnya kecekapan turbin hidrokinetik. Kajian ini mencadangkan konfigurasi sistem baru untuk menjana seberapa banyak tenaga kinetik daripada arus aliran air. Pemasangan nozel pemecut di saluran merupakan penyelesaian unik untuk meningkatkan kecekapan sistem arus saluran manakala penggunaan turbin aliran lintang hidraulik mikro (CFT)/turbin Banki merupakan penyelesaian terbaik dan praktikal. Sistem ini yang dikenali sebagai saluran penambah serapan dua hala (BDA) berfungsi dengan menggunakan nozel dwi tuju di dalam aliran, dikelilingi aliran dan lintang/ turbin Banki. Kajian berangka dan eksperimen telah dijalankan untuk mengkaji kaedah baru sistem ciri-ciri medan aliran ini dengan dan tanpa turbin. Simulasi berangka telah dilakukan menggunakan kod ANSYS CFX dan Fluent *finite volume Reynolds-Averaged Navier-Stokes Equations* (RANSE). Pengesahan telah dijalankan melalui eksperimen, dengan turbin dan tanpa turbin. Ciri-ciri aliran melalui sistem saluran dan prestasi dwi (bawah dan atas) turbin aliran lintang telah dikaji dan didapati bahawa aliran air telah dipertingkatkan dengan ketara disebabkan oleh sistem BDA di mana kelajuan aliran telah meningkat sebanyak 400%. Kecekapan tertinggi keseluruhan sistem dengan dua turbin adalah hampir 55.7%. Kecekapannya didapati lebih rendah daripada kecekapan turbin hidraulik. Namun, kecekapan ini boleh dianggap sangat baik memandangkan tekanan sedia ada untuk sistem kajian ini adalah sangat rendah. Penggunaan sistem ini akan menyumbang ke arah penggunaan aliran yang lebih cekap di sungai-sungai dan saluran bagi penjanaan elektrik di kawasan luar bandar.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiv
	LIST OF ABBREVIATIONS	xxiii
	LIST OF SYMBOLS	xxiv
	LIST OF APPENDICES	xxvii
1	INTRODUCTION	1
	1.1 Background	1
	1.2 Problem Statement	3
	1.3 Objectives of the Study	3
	1.4 Scope of the Study	3
	1.5 Significance of the Study	5
	1.6 Organization of the Thesis	5
2	LITERATURE REVIEW	7
	2.1 Overview	7
	2.2 Open Channel Flow	7
	2.2.1 Harnessed Power from Channels	8

2.2.2	Helical Channels Acceleration	11
2.2.3	Accelerated Nozzle in Channels	16
2.3	Tidal Current Power (Hydrokinetic Power) Turbines	19
2.3.1	Operation and Performance of Hydrokinetic Turbines	22
2.3.1.1	Horizontal Axis Current Turbines (HAT)	23
2.3.1.2	Vertical Axis Turbines (VAT)	35
2.4	Low Head Micro Hydropower Turbines	59
2.5	Cross Flow Turbines/ Banki Turbines	63
2.5.1	Velocity Diagram	65
2.5.2	Performance and Operation of CFT	66
2.6	Summary of Literature Review	80
3	RESEARCH METHODOLOGY	81
3.1	Introduction	81
3.2	Methodology	83
3.3	Numerical Approach	83
3.3.1	Grid Generation	83
3.3.2	Computational Method	84
3.3.3	Governing Equation	84
3.3.4	Basic Steps of the CFD simulation	86
3.4	Experimental Apparatus	88
3.5	Analysis and Validation	88
3.6	Stages Detailed Methods and Objectives	89
3.6.1	Stage (1): Micro Water Channels Flow Acceleration	89
3.6.1.1	Water Flow Field in Helical Channels	89
3.6.1.2	Parametric Study of the Use of Different Nozzles in Micro Channel	93
3.6.2	Stage (2): Novel Approach of Bidirectional Diffuser Augmented Channel (BDA)	98
3.6.2.1	Scope and objective	98
3.6.2.2	BDA Model	98
3.6.2.3	Experimental Set up	99
3.6.2.4	Test cases	100
3.6.2.5	Numerical Method	102

3.6.3	Stage (3): BDA System Including Cross Flow or Banki Turbines	104
3.6.3.1	Scope and Objective	104
3.6.3.2	Diffuser- Augmented Channel and CF Turbines Models	104
3.6.3.3	Numerical Methodology	106
3.6.4	Stage (4): Finding the Optimized Runner Design of CFT	108
3.6.4.1	Introduction	109
3.6.4.2	Scope and objectives of the stage	109
3.6.4.3	Test Cases	109
3.6.4.4	Numerical Approach	111
3.6.5	Stage (5): BDA Channel Provided with Optimized Turbines	111
3.6.5.1	Scope and Objectives	111
3.6.5.2	Final Prototype Model	112
3.6.5.3	Experimental Set up	113
3.6.5.4	Numerical Approach	113
4	RESULTS	115
4.1	General	115
4.2	Numerical Results of Water Flow Field in Helical Channels	115
4.3	Numerical Results of the Use of Different Nozzles in Micro Channel	121
4.3.1	Diameter Ratio Effects	122
4.3.2	Convergence and Convergence – Divergence Systems	125
4.3.3	Nozzle Edge Shapes Effects	126
4.4	Novel Approach of Bidirectional Diffuser- Augmented Channel (BDA)	128
4.4.1	Experimental Results	128
4.4.2	Numerical Results	132
4.5	Numerical Results of BDA System Including Cross Flow /Banki Turbines	136

	4.5.1	Flow Field Characteristics through System	137
	4.5.2	Performance Characteristics of CFT	140
4.6		The Numerical Finding of the Optimized Runner Design of the CFT	142
	4.6.1	Analytical Approach of Flow Characteristics	142
	4.6.2	Velocity Diagrams	143
	4.6.3	Numerical Results	144
4.7		Novel Channel Provided with Optimized Turbines Prototyping	151
	4.7.1	Experimental Results	151
	4.7.2	Numerical Results	155
5		DISCUSSIONS	158
	5.1	General	158
	5.2	Discussions on Water Flow Field in Helical Channels	158
	5.3	Discussions on the Numerical Findings of the Nozzle - Channel	160
	5.3.1	Diameter Ratio Effects	160
	5.3.2	Convergence and Convergence – Divergence Systems	161
	5.3.3	Nozzle Edge Shapes Effects	162
	5.3.4	NACA0025	162
	5.4	Concluding Remarks for Helical and Nozzle Channel Systems	164
	5.5	Novel Approach of Bidirectional Diffuser- Augmented Channel (BDA)	165
	5.5.1	Discussions of the Experimental Work	165
	5.5.2	Discussions of the Numerical Results	166
	5.6	BDA System Including Cross Flow or Banki Turbines	170
	5.6.1	Numerical Flow Field Characteristics through System	170
	5.6.2	Discussions on Performance of CFT in Third Stage	172
	5.7	Finding the Optimized Runner Design of CFT	173

5.7.1	Analytical Discussions of Flow Characteristics of the Current CFT	173
5.7.2	Discussions on Numerical Results	174
5.8	Novel System Channel Provided with Optimized Turbines Prototyping	178
5.8.1	Discussions on Experimental Findings	178
5.8.2	Validation with Experiment	180
5.8.3	Discussions on CFD Velocity Vectors and Pressure Contours	184
6	CONCLUSION AND FUTURE WORK	186
6.1	Conclusion	186
6.2	Recommendations for Future Work:	187
	REFERENCES	189
	Appendices A-C	206-232

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Advantages and disadvantages of horizontal and vertical turbines	22
2.2	Measured values between approach flow velocity, rotational speed and efficiency of Turbine (Dong <i>et al.</i> , 2012)	38
2.3	Maximum power coefficient and corresponding TSR for different angle of attack (Zhao <i>et al.</i> , 2013).	41
2.4	Performance parameters of the Evopod and Gorlov turbines (the electrical energy output is given for the whole spring-neap tidal cycle, 14.8 days) (Ramos and Iglesias, 2013)	52
2.5	Efficiency, advantages and disadvantages of micro hydropower turbines	60
2.6	The optimum and recommended dimensional and performance parameters of CFT can be drawn from the literature review (Referring to Figure 2.49).	79
3.1	Helical channels main geometrical specifications for group (A) of fixed pitch, $2\pi p = 0.5 \text{ m}$ (Bereaux <i>et al.</i> , 2004; Morales and Rosa, 2012; Xia and Liu, 2014)	91
3.2	Helical channels main geometrical specifications for group (B) of fixed curvature radius, $R = 1 \text{ m}$ (Bereaux <i>et al.</i> , 2004; Morales and Rosa, 2007)	91
3.3	Numbers of total mesh elements that had been used in each case in this study	93
3.4	Nozzle main geometrical parameters were tested in the current stage	95
3.5	Grid dependence study was conducted for case of diameter ratio $(d_2/d_1) = 2/3$.	97

3.6	Comparison between various turbulence models and analytical calculations for detecting average velocity at the nozzle plan of the channel bbb for case of diameter ratio $(d_2/d_1) = 2/3$.	98
3.7	The effect of grid size on the inlet runner velocity for lower turbine TSR 0.46.	108
3.8	Four tested cases of inlet and outlet angles	111
4.1	Helical channels flow characteristics for group (A) in case of constant pitch (P).	117
4.2	Helical channels flow characteristics for group (B) in case of constant curvature radius (R).	117
4.3	Nozzle channel flow characteristics and captured power for nozzle diameter ratio variations.	124
B.1	The turbulence models descriptions (André Bakker, 2005)	223
B.2	The turbulence models Usages (André Bakker, 2005)	224

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Typical in-stream plant using existing facilities (Kumar <i>et al.</i> , 2011)	8
2.2	Experimentally derived cross-stream velocity fields for open-channel flow (Ransome <i>et al.</i> , 2006)	12
2.3	Interface position: $Re = 602$ & $Fr = 2.20$, numerical and experimental mean interface (Morales and Rosa, 2007)	14
2.4	Vector plots of the secondary flow for helical square channel at different values of torsion λ with curvature of $\delta = 0.1$ and $Dn = 50$ (Alam <i>et al.</i> , 2007).	15
2.5	Distributions of axial velocities in curved micro channels with different aspect ratios: (a) 1, (b) 0.667, (c) 0.5 (Chu <i>et al.</i> , 2012)	16
2.6	Velocity contours for channel with 25° converged nozzle (Khan <i>et al.</i> , 2013)	18
2.7	Relationship between flow speed and maximum extracted power defined by Equation 2.2.	19
2.8	Horizontal axis turbines (a) Inclined axis, (b) Rigid Mooring, (c) Nonsubmerged Generator, (d) Submerged Generator (Herman <i>et al.</i> , 2014)	20
2.9	Cross-flow turbines (a) in-plane (b) squirrel cage Darrieus (c) H-Darrieus (d) Darrieus (e) Gorlov (f) Savonious (Herman <i>et al.</i> , 2014)	21
2.10	Test rig and the efficiency curve of the study of Bahaj <i>et al.</i> 2007	24
2.11	C_p Vs. TSR curves for various current speeds (Jo <i>et al.</i> , 2014)	25
2.12	(a) River turbine operation. (b) Turbine components: (1) protecting grid (2) stator, (3) propeller, (4) suction tube, (5) center cone, and (6) transmission box (Anyi and Kirke, 2010)	26

2.13	The performance characteristics of HF-Sx hydrofoil developed by Goundar <i>et al.</i> 2012.	28
2.14	Coefficient of power for the designed hydrofoil HF10XX at different current velocities and tip speed ratios (Goundar and Rafiuddin, 2013)	28
2.15	(a) The contra rotating arrangement and (b) power coefficient (C_p) for the CFD cases and experiments are compared (Lee <i>et al.</i> , 2015)	30
2.16	Shrouded or ducted models (Gadden, 2007)	31
2.17	Towing tank tests: comparison between the bare turbine, the 23°shrouded turbine and 26° shrouded turbine (Scherillo <i>et al.</i> , 2011)	32
2.18	Effect of diffuser angle on power output (Gaden and Bibeau, 2010)	33
2.19	Towing tank tests: comparison between the bare turbine, the 23° diffuser exit and 26° diffuser exit (Scherillo <i>et al.</i> , 2011)	33
2.20	Performance curves of the model turbine with and without shrouds at flow speeds of (a) 0.7 m/s, (b) 0.9 m/s, and (c) 1.1 m/s (Shahsavarifard <i>et al.</i> , 2015)	34
2.21	Maximum power coefficient as a function of solidity and flow velocity for straight-blade Darrieus turbine (Dai and Lam, 2009)	36
2.22	The Hunter Turbine (Yang and Lawn, 2011)	37
2.23	Comparison between numerical and experimental values of power coefficient of the Hunter turbine (Yang and Lawn, 2011)	37
2.24	Torque coefficient C_Q and power coefficient C_p with TSR for different pitch angle (Lazauskas and Kirke, 2012)	39
2.25	Power coefficient against TSR at different angle of attack (Zhao <i>et al.</i> , 2013)	40
2.26	Three blades in present study (a) full blade; (b) slotted blade with fixed flap; (c) slotted blade oscillating flap (Xiao <i>et al.</i> ,2013)	41
2.27	Power coefficient against TSR at different flap angle (Xiao <i>et al.</i> , 2013)	42
2.28	Three Savonius rotors (Khan <i>et al.</i> , 2009b)	43
2.29	Power coefficient against TSR for three cases (Khan <i>et al.</i> , 2009b)	44
2.30	Torque against overlap ratio (Yaakob <i>et al.</i> , 2010)	45

2.31	Different positioning of deflector plate with respect to modified Savonius rotor tested in the study of Golecha <i>et al.</i> (2011)	46
2.32	Comparison of power coefficient versus TSR for modified Savonius turbine with and without deflector plate (Golecha <i>et al.</i> , 2011)	47
2.33	Blade shapes of helical and straight Darrieus turbines (Shiono <i>et al.</i> , 2002)	49
2.34	Straight and helical turbine efficiency versus tip speed ratio (Shiono <i>et al.</i> , 2002)	49
2.35	The optimized hydrofoil and two blades tested turbine (Yang and Shu, 2012)	50
2.36	Helical turbine efficiency versus tip speed ratio at different Re for (a) optimized (b) Gottingen 623 (c) NACA0012 (Yang and Shu, 2012)	51
2.37	Models of GHT and LST (Bachant and Wosnik, 2015)	52
2.38	GHT and LST coefficients of power versus tip speed ratio (Bachant and Wosnik, 2015)	53
2.39	Ducted straight blade VAT (Kirke, 2006)	54
2.40	Performance of a straight blade Darrieus turbine with and without duct (Kirke, 2006)	55
2.41	Performance coefficient of a helical blade Darrieus turbine with and without diffuser (Kirke, 2011)	55
2.42	Power coefficient of Darrieus turbine with and without duct (Alidadi and Calisal, 2014)	56
2.43	Irrigation channel and combined turbine arrangement (Sahim <i>et al.</i> , 2013)	57
2.44	Power coefficient against TSR for single and combined turbines arrangement (Sahim <i>et al.</i> , 2013)	58
2.45	Low head micro hydropower turbines classification	59
2.46	Efficiency variation over different head ranges from 0.5 to 3.5 m (Williamson <i>et al.</i> , 2014)	62
2.47	Part flow efficiencies (Fraenkel <i>et al.</i> , 1999)	63
2.48	Inflow in horizontal and vertical orientations (Ossberger GmbH Co. 2011)	64
2.49	Main geometrical parameters of CFT	64

2.50	Velocity triangle	66
2.51	CFT efficiency versus TSR at different parameters (Desai and Aziz, 1994)	69
2.52	Variations of maximum efficiency with exit angle (Hara <i>et al.</i> , 1994)	69
2.53	Guide vane with plate showing the different guide opening (GO) (Kokubu <i>et al.</i> , 2013)	70
2.54	Hydraulic efficiency variations between guide vane with plate and without plate (Kokubu <i>et al.</i> , 2013)	71
2.55	Turbine performance at 5m head for different nozzle opening (Kaunda <i>et al.</i> , 2014a)	71
2.56	Torque transfer characterization at 5m head and 350 rpm rotational speed (Kaunda <i>et al.</i> , 2014a)	72
2.57	The first and second stage for the design runner speed (Andrade <i>et al.</i> , 2011)	73
2.58	Comparison between numerical hydraulic efficiency and experimental global efficiency against runner speed (Andrade <i>et al.</i> , 2011).	74
2.59	Numerical output results for CFT (Sammartano <i>et al.</i> , 2013)	76
2.60	Schematic of the CFT nozzle model used in the studies of Choi <i>et al.</i> 2009; Choi <i>et al.</i> 2010; Kim <i>et al.</i> 2012; Prasad <i>et al.</i> (2014); Kim <i>et al.</i> 2015 showing various parts	77
2.61	Performance curves (a) Choi <i>et al.</i> (2009) (b) Prasad <i>et al.</i> (2014) (c) Kim <i>et al.</i> (2015) (d) Kim <i>et al.</i> (2012)	79
3.1	Methodology Design	82
3.2	Modelling of Simulation steps in the current CFD Analysis	87
3.3	Helical Channel Physical Model.	90
3.4	Cross section of a rectangular channel showing the coordinate system	90
3.5	Micro Scale Channel physical model	95
3.6	NACA0025 nozzle	96
3.7	The meshed nozzle – channel configuration.	97
3.8	Schematic diagram of test bi-directed augmented diffuser (BDA) model	99

3.9	Schematic diagram of the present section experimental apparatus	100
3.10	Schematic diagram showing the velocity distribution of water flow in open channel in a directions of Y and Z.	101
3.11	Cross section of the configuration inlet showing the coordinate system	101
3.12	The inlet velocity profiles of BDA in a directions of Y and Z for three cases.	102
3.13	Meshing for (a) front and rear channel, and (b) bidirectional augmented diffuser	103
3.14	Schematic diagrams of diffuser - augmentation channel surrounding the runners.	105
3.15	The cross flow turbine runner	105
3.16	Schematic of the test model showing different parts	106
3.17	Meshing for (a) model channel, (b) bidirectional diffuser augmented channel and (c) the turbine runner.	107
3.18	The cross flow turbine runner main parameters and four test cases with different blade inlet angles, outlet angles and diameter ratio	110
3.19	Optimized lower and upper CFT runners surrounded by model diffuser - augmented channel.	112
3.20	Meshing for front, rear channel, BDA and the turbines runner	114
4.1	Cross sectional free surface positions variations at different curvature for group A of constant pitch.	116
4.2	Cross sectional free surface positions variations with different torsion for group B of constant curvature radius.	116
4.3	Variations of helical channel average flow velocity with curvature (δ) for group A.	118
4.4	Helical channel average velocity variations with torsion (λ) for group B.	118
4.5	Relation between curvature, dean, Reynolds and Froude numbers for group A of constant pitch.	119
4.6	Relation between torsion, Dean, Reynolds and Froude numbers for group B of constant curvature radius.	119
4.7	Velocity contours in plane ($x=1m$ from the inlet) normal to main flow at different curvature for group A of constant pitch.	120

4.8	Velocity contours in plane ($x=1\text{m}$ from the inlet) normal to main flow at different torsion for group B of constant curvature radius	121
4.9	Free surface positions, velocity and pressure variations along central plane of the channel for different nozzle diameter ratio (d_2/d_1)	122
4.10	Water velocity contours showing the flow of water along nozzle-channel for various nozzle diameter ratio (d_2/d_1).	123
4.11	Turbulence Intensity (TI) variations along the central of channel for different nozzle diameter ratio (d_2/d_1).	125
4.12	Velocity contours showing the flow of water along nozzle channel for cases of (a) convergence and (b) convergence- divergence.	125
4.13	Free surface positions and pressure variations along the channel for convergence and convergence- divergence systems.	126
4.14	Water turbulence kinetic energy contours for cases of (a) convergence and (b) convergence- divergence.	126
4.15	Velocity contours showing the flow of water through nozzle plan for curved and straight nozzle edges.	127
4.16	Velocity contours showing the flow patterns of water along channel for NACA 0025.	127
4.17	Schematic view showing the positions of velocities and maximum power measurements.	128
4.18	Lower and upper velocity variations along BDA system for three cases	130
4.19	The potential of harnessed hydrokinetic power along BDA system for three cases.	131
4.20	Velocity distribution at BDA system inlet for (a) case 1 (b) case 2 (c) case 3.	132
4.21	Velocity vectors showing the flow of water along the proposed BDA system for three cases.	133
4.22	Velocity vectors showing the flow of water through the proposed BDA system in Z- plan for three cases.	134
4.23	Pressure contours of the flow of water through the BDA system for the three cases.	135

4.24	The potential velocity vectors of BDA system with and without separation.	136
4.25	Velocity vectors in two plan of the channel with turbines at TSR= 0.42.	137
4.26	Turbines inlet velocity variations at TSR for lower and upper regions.	138
4.27	Velocity vectors showing the water flow through the two rotors at TSR = 0.478 for lower turbine and TSR= 0.534 for upper.	139
4.28	Velocity vectors showing the water flow through the lower runner blades in the first stage at TSR = 0.478.	139
4.29	Pressure contours of the water flow through the two turbines at TSR = 0.478 for lower turbine and 0.534 for upper turbine	140
4.30	The variations of output power of the lower and upper turbines at different TSR	141
4.31	Efficiency variations of the lower and upper turbines at different TSR.	142
4.32	Flow distribution through the cross-flow turbine runner.	143
4.33	Velocity triangles of four tested cases.	144
4.34	Runner inlet velocity variations with peripheral velocity for lower and upper turbines in four cases.	145
4.35	Water velocity vectors through the runner for all cases from simulated runner RPM= 45 and time $t = 5s$.	146
4.36	Water velocity vectors variations with changing of TSR for case 3	147
4.37	Power variations of the tested turbines cases at different TSR	148
4.38	Efficiency variations of the tested turbines cases at different TSR	149
4.39	Lower and upper turbines efficiency variations with various flow rate.	150
4.40	Velocity variations along the BDA channel and through CFT rotors measured experimentally at optimum TSR	151
4.41	Runner inlet velocity variations at different peripheral velocity for lower and upper runners.	152
4.42	Runner inlet velocity and peripheral velocity variations at different TSR for (a) lower turbine and (b) upper turbine.	153

4.43	Output torque and power variations with various (a) TSR and (b) flow rate.	154
4.44	Efficiency variations with different (a) TSR and (b) flow rate.	155
4.45	Velocity vectors through turbines in two plan.	156
4.46	Pressure contours through two turbines in two plan.	157
5.1	Velocity values differences along the central plane of channel between NACA 0025, curved and straight nozzle edges.	163
5.2	The potential of harnessed power at different current speed approaching determined numerically.	164
5.3	Experimental and numerical of lower and upper velocity regions variations along BDA system for (a) case 1 (b) case 2 (c) case 3	168
5.4	Numerical and experimental results of the maximum harnessed power for BDA system with and without separation .	170
5.5	Experimental and numerical of lower and upper velocity regions variations for optimum TSR.	181
5.6	Performance comparison of two CFT between CFD and Exp. results	183
A.1	Schematic diagram of the present experimental apparatus.	211
A.2	Schematic diagram of the channel system showing the level of the water.	212
A.3	High speed camera	213
A.4	High speed camera location and facilities	213
A.5	V710 high speed camera and Images showing the visualization of the water flow through BDA with and without turbines.	214
A.6	Phantom tracking software to capture the velocities through BDA model	215
A.7	Futek TRS 605 torque meter	216
A.8	IBT 100 Evaluation Instrument	217
A.9	Measurement loop	218
A.10	NAHRIM flow meter propeller	218
B.1	Fluid region of pipe flow discretized into finite set of control volumes (mesh) (Versteeg and Malalasekera, 2007).	220
B.2	The grid mesh types that used in 2-D and 3-D domain (Versteeg and Malalasekera, 2007).	220

B.3	Different available turbulence models (André Bakker, 2005)	223
B.4	Residuals monitors (André Bakker, 2005)	229

LIST OF ABBREVIATIONS

BDA	_	Bidirectional Diffuser Augmented Channel
CFD	_	Computational Fluid Dynamics
CF	_	Cross Flow
CFT	_	Cross Flow Turbine
HAT	_	Horizontal Axis Turbine
NACA	_	National Advisory Committee for Aeronautics
PAT	_	Pump as Turbine
RANSE	_	Reynolds Averged Navier - Stokes Equation
RPM	_	Revolution Per Minutes
SIMPLE	_	Semi-Implicit Methods for Pressure- Linked Equation
SST	_	Shear Stress Transport
TI	_	Turbulence Intensity
TSR	_	Tip Speed Ratio
UNDP	_	United Nations Development Program
UTM	_	Universiti Teknologi Malaysia
VAT	_	Vertical Axis Turbine

LIST OF SYMBOLS

A	–	Cross sectional area of turbine (turbine’s flow) (m^2)
A_c	–	Cross sectional area of channel (m^2)
A_f	–	Cross sectional area of helical channel (m^2)
C_p	–	Power Coefficient “Hydrokinetic” ($C_p = \frac{T \times \omega}{0.5\rho AU_0^3}$); “Hydropower” ($C_p = \frac{T \times \omega}{\rho gQH}$)
d_1	–	Channel diameter (m)
d_2	–	Contraction Nozzle diameter (m)
D_o	–	Outer diameter of the turbine runner (m)
D_i	–	Inner diameter of the turbine runner (m)
D_i/D_o	–	Runner diameter ratio
DE	–	Dean Number ($DE = Re \times \sqrt{\delta}$)
Dh	–	Hydraulic depth (m) ($D_h = \frac{4A}{p_w}$)
D_ω	–	The cross-diffusion term
Fr	–	Froude Number ($Fr = \frac{U_o^2}{gh_n}$)
g	–	Gravitational acceleration ($m. s^{-2}$)
G_ω	–	Generation of turbulence kinetic energy
G_k	–	The generation of ω .
h	–	Depth of the channel (m)
H	–	Head (m)
h_h	–	Hydraulic depth (m)
K	–	Turbulence kinetic energy
K_h	–	Head ratio of Pump as turbine (PAT).
K_Q	–	Flow rate ratio of PAT.
L	–	CFT runner length (m)
L_C	–	Channel length (m)

L_n	–	Nozzle length (m)
\dot{m}	–	Water channel mass flow rate ($kg.s^{-1}$)
n	–	Manning's resistance coefficient
p	–	Pitch (m)
P_C	–	Maximum extracted power (W) ($P_C = 0.5\rho AU_o^3$)
P_{opt}	–	Optimum power (W)
p_w	–	Wetted perimeter (m)
Q	–	Runner inlet flow rate ($m^3.s^{-1}$)
r	–	CFT runner radius (m)
R	–	Curvature radius (m)
Re	–	Reynolds number ($Re = \frac{\rho*U_o*D_h}{\mu}$)
R_r	–	Hydraulic radius (m)
S	–	Channel bed slope (m)
t	–	Thickness of turbine blade (m)
T	–	Channel water draft (m)
U_o	–	Water flow velocity (m/s)
U	–	Peripheral velocity
$u_i = (u \ v \ w)$	–	Velocity components in the directions of $x_i=(x \ y \ z)$
v	–	Absolute velocity/Mean runner inlet velocity (m/s)
v_r	–	Relative velocity (m/s)
W	–	Width of channel (m)
Y_k	–	The dissipation of k
Y_ω	–	The dissipation of ω
Z	–	No. of Blades

Greek Symbols

α	–	Blade angle of attack
β_1	–	Blade inlet angle
β_2	–	Blade outlet angle
Γ_k	–	The effective diffusivity for k .
Γ_ω	–	The effective diffusivity for ω

δ	–	Helical channel curvature ($\delta = \frac{0.5w \times R}{p^2+R^2}$)
ε	–	Block ratio
η	–	Turbine Efficiency ($\eta = \frac{T * \omega}{0.5\rho AU_0^3}$)
μ	–	Water Dynamic viscosity ($N.s.m^{-2}$)
λ	–	Angle of CFT entry arc
λ_t	–	Helical channel torsion ($\lambda_t = \frac{0.5w \times p}{p^2+R^2}$)
ρ	–	Water density (kg/m^3)
τ	–	CFT blade thickness (m)
τ_{max}	–	Maximum thickness of aerofoil thickness (m)
ω	–	Angular velocity of the turbine (rad/s)

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Experimental methodology	206
B	Numerical methodology	219
C	List of publications related to current research	232

CHAPTER 1

INTRODUCTION

1.1 Background

From 7 billion population of the world, 1.3 billion people still remain without access to electricity, especially those in the rural and poor areas. From this number, 22% are those living in developing countries; mostly living in the sub-Saharan Africa and developing countries in Asia (International Energy Agency's World Energy Outlook 2014). Nevertheless, it is expected that in the beginning of year 2040, at least one billion people gain access to electricity while nearly 500 million still remain without access. Renewable energy is also expected to represent 50% of the total power generation in these areas (International Energy Agency). This is because renewable resources provide efficient solution to achieve a perfect connection between renewable energies and sustainable development in the future. Tidal- current energy is one of the most prominent, clean and predictable renewable power resource from water in the world, especially regarding micro stations which can be deployed in isolated and hilly areas for electrification process (Kai *et al.*, 2013; Hammar. *et al.*, 2012; Liu, *et al.*, 2011).

Micro hydropower scheme is the most suitable and efficient option for generating renewable energies. This is due to its low environmental harmful effect and lower operation and maintenance costs (Paish, 2002). Most rural and hilly areas use micro hydropower plants in order to generate cheap, available and effective electricity supply (Vermaak *et al.*, 2014). Moreover, the micro hydropower schemes present an effective solution which has been recommended by many international organizations

such as The United Nations Industrial Development Organization and The World Bank. Hydrokinetic technology is a new type of micro hydro-power that functions by utilizing hydrokinetic turbines in flow of river or channels to produce power (Vermaak *et al.*, 2014; Chamorro *et al.*, 2013; Kumar *et al.*, 2011). Harnessing kinetic energy from the flow of water in open channels is closely similar to tidal current power generation, so that existing facilities like weirs, barrages and falls can be optimized.

Many countries such as Malaysia that are surrounded by irrigation or rainy channels, have a great potential for exploiting this feature of nature. Adhau *et al.* (2012) carried out extensive study for potential sites, on the hydrological data for feasible development of mini/micro hydro power plant. They concluded that irrigation projects are viably economical and technical for micro power generation. Current or hydrokinetic energy that can be captured from the water flow in the irrigation and rainy channels is a new type of micro hydro-power system. This might be a promising technology in the countries with vast tidal current energy.

The open helical channels has wide range of application in nuclear, chemical, polymer processing, heat and mass transfer fields. These various applications can be developed for expanding the range of their applications, especially in the renewable energy field. The flow in helical channels is able to create centrifugal force from the curved wall to the channel center by which the highest velocity at the outside wall caused (Williams *et al.*, 1902). This accelerates the flowing water through the channels. It is certainly useful in case of energy extraction from the water channels.

On the other hand, accelerated nozzle in channels, a subject in the renewable energy fields that little attention is paid to, is the most efficient choice to accelerate the flow and increase the harnessed power of the flowing water.

In the last four years, researches were focused on studying the stream of water in channel technology in both flow pattern and turbine system viewpoint. They have discussed the developments on the open channel flow and the most appropriate turbine system which can be utilized in these channels. There are various conventional current

energy turbines which can be used to capture the hydrokinetic energy from the flowing of water, horizontal axial flow turbines and vertical axis flow turbines.

Besides, one of the most attractive turbines is cross flow turbine (CFT) which is known as Banki and Ossberger turbine. This type of turbine is more practical than the other types of existing micro hydropower turbines. It is easy to construct and cost effective (Olgun 1998). These turbines are also suitable for high and medium flow rates and low head (Ghosh *et al.*,2011) capable of generating average efficiency of 80% for small and micro power outputs (Ossberger GmbH Co. 2011). This value is, however, lower than those of other most popular hydro turbines such as Pelton, Turgo, Francis and Kaplan (Okot 2013). In comparison, the main advantage of this turbine is its ability to keep maximum efficiency with different ranges of flow (Walseth 2009). Hence, the CFT is more appropriate for run-of-river applications due to its lower requirement for large head, and it is depending on the flow rate than other types of hydro turbines (Olgun 1998).

1.2 Problem Statement

Nowadays, irrigation or rainy channels have a great potential for developing renewable energy sector in the developing countries. Though potential, this scheme is yet to be fully discovered to the considerable extent, as researchers are still searching for solution for the main problem of low velocity and low depth of current in the open flow micro channels. This low current characteristic is the main consideration of this study. This is become important when it is known that conventional tidal current turbines are highly dependent upon the current speed and water depth. Moreover, another drawback of the conventional tidal current turbines is its low efficiency.

1.3 Objectives of the Study

Due to the shortcomings explained in the problem statement, the flow in the channel system needs to be accelerated in order to increase the harnessed power.

Deployment of a novel turbine configuration in the channel is a solution to overcome the low efficiency of conventional hydrokinetic turbines. Therefore, the main goal of this research is to improve the flow characteristics and enhance overall efficiency of the system for better extracting tidal current energy from flow in a channel, stream or river.

The objectives are to:

- i. Develop a new configuration system with bidirectional nozzles in two directions of the micro channel.
- ii. Develop a new type of hydraulic cross flow turbine system suitable for the micro scale water channels.
- iii. Evaluate turbine operation and performance in the new channel arrangement in order to analyze the whole system.

1.4 Scope of the Study

In this study, a novel system configuration has been proposed in order to capture as much as kinetic energy from the water flow in micro scale channels. This idea is fairly a new approach in the hydrokinetic energy generation fields. The system, known as bidirectional diffuser augmented channel (BDA), is totally dependent upon utilizing bidirectional nozzle in two different flow directions, surrounded by dual cross flow/Banki turbines.

The optimum parameters of the bidirectional nozzle and CFT runners utilizing in micro channels were analyzed and determined using CFD. Then, prototype of the BDA channel with optimized CFT rotors had been fabricated for using in experiment.

1.5 Significance of the Study

Micro hydropower stations are significantly cost effective in socio-economic development, particularly for isolated hilly and rural areas. Moreover, hydrokinetic is a novel type of micro hydropower energy by which the energy can be extracted from rivers, irrigation/rainy channels and shallow waters. Development of hydrokinetic or current schemes involves with a main problem which is the appearance of low velocities. Installing nozzles in channels is the most efficient solution to overcome this issue. The current study proposed a new system of nozzles to be deployed in micro rainy and irrigation channels.

Implementation of cross flow turbine (CFT) or Banki turbine also is the most proper solution to overcome the low efficiency of conventional tidal current turbines. It is observed that this solution is more practical; efficient, simple and cost effective. The use of CFT with current configuration is a new concept of hydrokinetic power generation.

Numerical and experimental investigations were carried out in this research in order to evaluate the novel approach system. Moreover, CFD is becoming an important tool to investigate and design the cross flow turbines and it is supported by validated results.

1.6 Organization of the Thesis

Structure of this thesis is organized in six chapters. First chapter presents an overview of the current study. It also provides the objectives, scope and the significance of the present research with respect to the literature review findings.

In chapter two a detailed review of the previous researches which are related to the current work are provided. For the clarity of presentation, the literature review has been grouped under different headings namely, open channel flow, tidal current

power (hydrokinetic power) turbines, operation and performance of low head micro hydropower turbines and cross flow turbines/ Banki turbines.

Chapter three presents objectives, scopes and numerical and experimental research methods of different stages. Mathematical model, grid generation, computational method, and its assumptions are explained in this chapter. Experimental methodology which gives the detailed description of facilities, experimental set up and apparatus and the test procedure are also included.

Chapter four proposes the numerical results for the usage of helical channel and different nozzle shapes in micro scale open channels. It also presents the experimental and numerical results and findings of a new configuration system known as bidirectional diffuser-augmented channel which utilizes bidirectional nozzles in two directions of channels with and without turbines.

Chapter five discusses the numerical results of flow characteristics of helical and nozzle channel. Furthermore, special configuration of ducted channel and dual cross flow turbines performance are discussed experimentally and numerically in four sections.

Finally, chapter six presents the conclusions drawn from the numerical simulation and experimental test of the special configuration of nozzle system and cross flow turbines. In addition, recommendations for future studies in this field have also been presented.

REFERENCES

- Adhau S.P, .Moharil R.M, Adhau P.G. (2012). Mini-hydro power generation on existing irrigation projects: Case study of Indian sites. *Renewable and Sustainable Energy Reviews*. 16, 4785–4795.
- Alam, M.M., Begum, D., Yamamoto, K. (2007). Flow through a helical pipe with rectangular cross-section. *Journal of Naval Architecture and Marine Engineering*. 4(2), 99-110.
- Anders Goude, Olov Ågren. (2014). Simulations of a vertical axis turbine in a channel. *Renewable Energy*. 63, 477-485.
- Andrade D, Jesús, Christian Curiel, Frank Kenyery, Orlando Aguillón, Auristela Vásquez, and Miguel Asuaje. (2011). Numerical investigation of the internal flow in a Banki turbine. *International Journal of Rotating Machinery*. Article ID 841214, 1-12.
- André Bakker. (2005). *CFD lectures. Fluent Inc.*
- Agarwal T. (2012). Review of Pump as Turbine (PAT) for Micro-Hydropower. *International Journal of Emerging Technology and Advanced Engineering*. 2 (11), 159– 163.
- Akhot, V., Orszag, S.A., Thangam, S., Gatski, T.B. & Speziale, C.G. (1992). Development of turbulence models for shear flows by a double expansion technique. *Physics of Fluids A*. 4 (7), 1510-1520.
- Alexander K.V. , Giddens E.P. , Fuller A.M. (2009). Radial- and mixed-flow turbines for low head micro hydro systems. *Renewable Energy*. 34, 1885–1894.
- Alidadi M, Calisal S. (2014). A numerical method for calculation of power output from ducted vertical axis hydro-current turbines. *Computers & Fluids*. 105,76–81.
- Anagnostopoulos J S., Papantonis Dimitris E. (2012). A fast lagrangian simulation method for flow analysis and runner design in pelton turbines. *Journal of Hydrodynamic*. 24(6), 930-941.
- Anyi M, Kirke B. (2010). Evaluation of small axial flow hydrokinetic turbines for

- remote communities. *Energy for Sustainable Development*. 14, 110–116.
- Araquistain T M. (2010). *Tidal Power: Economic and Technological assessment*. Master thesis. Department of Thermal Engineering, Tsinghua University. page (43).
- Arkel V R, Owen J, Allison S, Tryfonas T, Winter A, Entwistle R. (2011). Design and preliminary testing of a novel concept low depth hydropower device. *Oceans*. 11, 19–22.
- Bachant P, Wosnik M. (2015). Performance measurements of cylindrical and spherical-helical cross-flow marine hydrokinetic turbines with estimates of exergy Efficiency. *Renewable Energy*. 74, 318-325.
- Bahaj A.S., Batten W.M.J., McCann G. (2007). Experimental verifications of numerical predictions for the hydrodynamic performance of horizontal axis marine current turbines. *Renewable Energy*. 32, 2479–2490.
- Bai X , Avital E. J, Munjiza. A, Williams J.J.R. (2014). Numerical simulation of a marine current turbine in free surface flow. *Renewable Energy*. 63, 715-723.
- Balje, O. E. (1981). *Turbomachines*. New York: John Wiley & Sons Inc.
- Banos R, Mazano F., Gugliaro A, Montoya F.G, Cgil, Alcayde A. (2011). Gomez J., Optimization applied to renewable and sustainable energy: A review. *Renewable and Sustainable Energy Reviews*. 15, 1753-1766.
- Batten W.M.J., Bahaj A.S., Molland A.F., Chaplin J.R. (2008). The prediction of the hydrodynamic performance of marine current turbines. *Renewable Energy*. 33, 1085–1096.
- Bereaux, Y., Moguedet, M., Raoul, X., Charmeau, J.Y., Balcaen, J. and Graebbling, D. (2004). Series solutions for viscous and viscoelastic fluids flow in the helical rectangular channel of an extruder screw. *Journal of non-newtonian fluid mechanics*. 123(2), 237-257.
- Berger, S.A.; and Talbot, L. (1983). Flow in curved pipes. *Annual Review of Fluid Mechanics*. 15, 461-512.
- Bozorgi. A, Javidpour. E, Riasi. A. Nourbakhsh. A. (2013). Numerical and experimental study of using axial pump as turbine in Pico hydropower plants. *Renewable Energy*. 53, 258-264.
- Brookshier P. (2004). *Encyclopedia of Energy, Hydropower Technology*. New York: Elsevier, pages (333-341).
- Bryan R. Cobb, Kendra V. Sharp. (2013). Impulse (Turgo and Pelton) turbine

- performance characteristics and their impact on pico-hydro installations. *Renewable Energy*. 50, 959-964.
- Bryden I, Melville G. (2004). Choosing and evaluating sites for tidal current development. In: Proceedings of the institution of mechanical engineers, Part A. *Journal of Power and Energy*. 218, 567–78.
- Bryden I , Scott J.Couch. (2007). How much energy can be extracted from moving water with a free surface: A question of importance in the field of tidal current energy?. *Renewable Energy*. 32, 1961–1966.
- Burton J.D. and Muluget A.G. (1992). Running centrifugal pumps as micro-hydro turbines performance prediction using the area ratio method. *Renewable Energy. Technology and the Environment*. 2839-2847.
- Chamorro L. P., Hill C., Morton S., Ellis .C, Arndt R. E. A., Sotiropoulos. F. (2013). On the interaction between a turbulent open channel flow and an axial flow turbine. *J.Fluid Mech*. 716, 658-670.
- Choi, Young-Do, Jae-Ik Lim, You-Taek Kim, and Young-Ho Lee. (2008). Performance and internal flow characteristics of a cross-flow hydro turbine by the shapes of nozzle and runner blade. *Journal of Fluid Science and Technology*. 3 (3), 398-409.
- Choi, Young-Do, Chang-Goo Kim, Young-Ho Lee. (2009). Effect of wave conditions on the performance and internal flow of a direct drive turbine. *Journal of mechanical science and technology*. 23(6), 1693-1701.
- Choi, Young-Do, Chang-Goo Kim, You-Taek Kim, Jung-Il Song, Young-Ho Lee. (2010). A performance study on a direct drive hydro turbine for wave energy converter. *Journal of mechanical science and technology*. 24, 2197-2206.
- Chu, J.C., Teng, J.T., Xu, T.T., Huang, S., Jin, S., Yu, X.F., Dang, T., Zhang, C.P. and Greif, R. (2012). Characterization of frictional pressure drop of liquid flow through curved rectangular microchannels. *Experimental Thermal and Fluid Science*. 38, 171-183.
- Dai, Y., and Lam, W. (2009). Numerical study of straight-bladed Darrieus-type tidal turbine. *ICE-Energy*, 162(2), 67-76.
- Dai, Y., Gardiner, N., Sutton, R., and Dyson, P. (2011). Hydrodynamic analysis models for the design of Darrieus-type vertical-axis marine current turbines. Proceedings of the Institution of Mechanical Engineers, Part M. *Journal of Engineering for the Maritime Environment*. 225(3), 295-307.

- Das, S.K. (1993). Water flow through helical coils in turbulent condition. *The Canadian Journal of Chemical Engineering*. 71(6), 971-973.
- Davis S. (2005). *Micro Clean power from water*. (2nd edition). Gabriola island, Canda: New society publisher.
- Dean, W.R. (1927). Note on the motion of fluid in a curved pipe. *The London, Edinburgh and Dublin Philosophical Magazine and Journal of Science*. 4(20), 208-223.
- Dean, W.R. (1928). Fluid motion in a curved channel. *Proceedings of the Royal Society of London, Series A*. 121(787), 402-420.
- Derakhshan S and Nourbakhs A. (2008). Experimental study of characteristic curves of centrifugal pumps working as turbines in different specific speeds. *Experimental Thermal and Fluid Science*. 32, 800–807.
- Derakhshan, S., Mohammadi B, Nourbakhs A. (2009). Efficiency improvement of centrifugal reverse pumps. *Journal of fluids engineering*. 131(2), 021103.
- Derakhshan S and Kasaeian N. (2012). Optimal design of axial hydro turbine for micro hydropower plants. *26th IAHR Symposium on Hydraulic Machinery and Systems, IOP Conf. Series, Earth and Environmental Science*. 19–23 August. 15; 042029.
- Desai V.R, Aziz N.M. (1994). An experimental investigation of cross-flow turbine efficiency. *Journal of Fluids Engineering*. 116(3), 545-550.
- Development Program (UNDP) report available from: <http://www.undp.org/content/undp/en/home/presscenter/pressreleases/12/01/19/t-o-cut-poverty-in-asia-and-the-pacific-energy-plus-package-a-must-says-un-report.html>. Accessed on 14/11/2013
- Dong, Z. Y., Zhang, X., Wang, L., Han, W., Yu, X. W., Yan, X. F., Li, X. P.(2012). A Comparison of Rotational Speed of Marine Current Power-Generation Turbine with and without a Speeding-up Inlet. *Advanced Materials Research*. 383, 4516-4520.
- Draper S, Thomas A.A. Adcock, Alistair G.L. Borthwick , Guy T. Houlsby. (2014). Estimate of the tidal stream power resource of the Pentland Firth. *Renewable Energy*. 63, 650-657.
- Durgin W., Fay W (1984), Some Fluid Flow Characteristics of a Crossflow Type Hydraulic Turbine. *In proceedings of American Society of Mechanical Engineers (ASME) Winter Annual Meeting on small hydropower fluid machinery*, New Orleans, USA.

- Elbatran A.H ,Yaakob O.B ,Yasser M. Ahmed ,Shabara H.M. (2015). Operation, performance and economic analysis of low head micro-hydropower turbines for rural and remote areas: A review. *Renewable and Sustainable Energy Reviews*. 43, 40–50.
- Energy Systems & Design Ltd, <http://www.microhydropower.com/our-products/stream-engine/> (accessed on 21 /8/ 2013.)
- entec Consulting & Engineering, the entec cross flow turbine T 15 available from http://www.entec.ch/entecweb/media/T15_Brochure.pdf, (accessed on 12/5/2014).
- Eustice, J. (1910). Flow of water in curved pipes. *Proceedings of the Royal Society of London, Series A*. 84(568), 107-118.
- Fatemeh, G. and Mahmud T.H.M. (2013). CFD Simulation of nanosulfur crystallization incorporating population balance modeling. *Iranica Journal of Energy & Environment Special Issue on Nanotechnology*. 4(1), 36-42.
- Fiuzat, Abbas A., and Bhushan P. Akerkar. (1991). Power outputs of two stages of cross-flow turbine. *Journal of energy engineering*. 117(2), 57-70.
- Fraenkel, P., Paish, O., Bokalders, V., Harvey, A., Brown, A. and Edwards, R. (1999). *Micro-Hydro Power: A Guide for Development Workers*. London: IT Publications.
- Fu, J., Song, W. and Wang, H. (2012). Optimization design of bucket roots type linefor Pelton turbines. *Nongye Jixie Xuebao/Transactions of the Chinese Society of Agricultural Machinery*. 43(9), 62-65.
- Furukawa A, Satoshi Watanabe, Daisuke Matsushita and Kusuo Okuma. (2010). Development of ducted Darrieus turbine for low head hydropower utilization. *Current Applied Physics*. 10; 128–132.
- Gaden, D.L.F. (2007). *An Investigation of River Kinetic Turbines : Performance Enhancements, Turbine Modelling Techniques ,and an Assessment of Turbulence Models*. Doctoral dissertation. University of Manitoba.
- Gaden, D.L.F. and Bibeau, E.L. (2010). A numerical investigation in to the effect of diffusers on the performance of hydrokinetic turbines using a validated momentum source turbine model. *Renewable Energy*. 35, 1152–1158.
- Garrett, C and Cummins, P. (2007). The efficiency of a turbine in a tidal channel. *J Fluid Mech*. 588, 243-51.
- Germano, M. (1982). On the effect of torsion on a helical pipe flow. *Journal of Fluid*

- Mechanics*. 125, 1-8.
- Germano, M. (1989). The Dean equations extended to a helical pipe flow. *Journal of Fluid Mechanics*. 203, 289-305.
- Golecha, K., Eldho, T., and Prabhu, S. (2011). Influence of the deflector plate on the performance of modified Savonius water turbine. *Applied Energy*. 88(9), 3207-3217.
- Golecha, K. Eldho, T.I. and Prabhu S.V. (2012). Performance study of modified Savonius water turbine with two deflector plates. *International Journal of Rotating Machinery*. 2012, 1-12 .
- Goude, A. and Agren, O. (2014). Simulations of a vertical axis turbine in a channel. *Renewable Energy*. 63, 477-485.
- Goundar, Jai N., Rafiuddin M. Ahmed and Young-Ho Lee. (2012). Numerical and experimental studies on hydrofoils for marine current turbines. *Renewable Energy*. 42, 173-179.
- Goundar, Jai N. and Rafiuddin M. Ahmed. (2013). Design of a horizontal axis tidal current turbine. *Applied* .111, 161–174.
- Guney M.S and Kaygusuz. (2010). Hydrokinetic energy conversion systems: A technology status review. *Renewable and Sustainable Energy Reviews*. 14, 2996–3004.
- Hamma. L, Ehnberg.J , Mavume.A , Francisco. F , Molander. S. (2012). Simplified Site-screening method for micro tidal current turbines applied in Mozambique. *Renewable Energy*. 44, 414-422.
- Hammar L, Jimmy Ehnberg , Alberto Mavume , Francisco Francisco and Sverker Molander. (2012). Simplified site-screening method for micro tidal current turbines applied in Mozambique. *Renewable Energy*. 44, 414 - 422.
- Hashim, N.B., Huddleston D H, Ibrahim Z, Chong N B. (2006). *Perfomance of High-velocity Channels in Flood-prone Areas*. research project. Department of Hydraulics & Hydrology, Faculty of Civil Engineering, Universiti Teknologi Malaysia. research vote no: 71840.
- Hassan. H.F, El-Shafie and Othman A. Karim. (2012). Tidal current turbines glance at the past and look into future prospects in Malaysia. *Renewable and Sustainable Energy Reviews*. 16, 5707–5717.
- Hothersall, R. (1985). *A review of the cross-flow turbine*. New York :In Proceedings of American Society of Civil Engineers (ASCE) on Waterpower. vol. 2. page 914.

- Ira h. Abbott, Albert E. Von Doenhoff, Louis S. and Stivers, Jr. (1945). *report no. 824 summary of airfoil data*. Washington DC, USA: National Advisory Committee for Aeronautics.
- International Energy Agency, Energy access database, available from: <http://www.worldenergyoutlook.org/resources/energydevelopment/energyaccessdatabase/>, accessed on 17/4/2015
- International Energy Agency's World Energy Outlook 2014 Executive summary, available from: <https://www.iea.org/Textbase/npsum/WEO2014SUM.pdf>, accessed on 17/4/2015.
- Jiang, F.; Drese, K.S.; Hardt, S.; Küpper, M.; and Schönfeld, F. (2004). Helical flows and chaotic mixing in curved micro channels. *American Journal of American Institute of Chemical Engineers*. 50(9), 2297-2305.
- Jiménez E.E. (2009). *Final study report of Achievable Renewable Energy Targets for Puerto Rico's Renewable Energy Portfolio Standard, Chapter 8*. University of Puerto Rico, Puerto Rico. Available at <http://www.uprm.edu/aret/>.
- Jing F, Sheng Q and Zhang, L. (2014). Experimental research on tidal current vertical axis turbine with variable-pitch blades. *Ocean Engineering*. 88, 228–241.
- Jo Chul hee, Jin young Yim, Kang hee Lee and Yu ho Rho. (2012). Performance of horizontal axis tidal current turbine by blade configuration. *Renewable Energy*. 42, 195-206.
- Jo Chul-Hee, Jun-Ho Lee, Yu-Ho Rho and Kang-Hee Lee. (2014). Performance analysis of a HAT tidal current turbine and wake flow characteristics. *Renewable Energy* 65; 175-182.
- Kai-Wern Ng, Wei-Haur Lam and Saravanan Pichiah. (2013). A review on potential applications of carbon nanotubes in marine current turbines. *Renewable and Sustainable Energy Reviews*. 28, 331–339.
- Kai-Yo, H.; Chih-Yang, Wu.; and Yi-Tun, Huang. (2014). Fluid mixing in a microchannel wit longitudinal vortex generators. *Chemical Engineering Journal* 235(1), 27-36.
- Kari Sornes. (2010). *Small-scale water current turbines for river applications*. Zero Emission Resource Organization,. Available from: <http://www.zero.no/publikasjoner/small-scale-water-current-turbines-for-river-applications.pdf> [accessed 05.06.2014].
- Kaunda, Chiyembekezo S., Cuthbert Z. Kimambo and Torbjorn K. Nielsen. (2014a).

- Experimental study on a simplified crossflow turbine. *International Journal of Energy and Environment*. 155-182.
- Kaunda, Chiyembekezo S., Cuthbert Z. Kimambo and Torbjorn K. Nielsen. (2014b). A numerical investigation of flow profile and performance of a low cost Crossflow turbine. *International Journal of Energy and Environment*. 275-296.
- Kaunda Chiyembekezo S, Kimambo Cuthbert Z, Nielsen and Torbjorn, K.A. (2014c). technical discussion on micro hydro power technology and its turbines. *Renewable and Sustainable Energy Reviews*. 35, 445–459.
- Keawsuntia, Y. (2011). Electricity generation from micro hydro turbine: A case study of crossflow turbine, *International Conference and Utility Exhibition on Power and Energy Systems: Issues and Prospects for Asia*. 28-30 Sept. 2011. Pattaya City, Thailand, 1-4.
- Khan, A. A., Abdul M. Khan, Zahid, M. and Rizwan, R. (2013). Flow acceleration by converging nozzles for power generation in existing canal system. *Renewable Energy*. 60 , 548 - 552.
- Khan M.J., Iqbal M.T. and Quaicoe, J.E. (2008). River current energy conversion systems: Progress, prospects and challenges. *Renewable and Sustainable Energy Reviews*. 12, 2177–2193.
- Khan, M. J., Bhuyan, G., Iqbal, M. T. and Quaicoe, J. E. (2009). Hydrokinetic energy conversion systems and assessment of horizontal and vertical axis turbines for river and tidal applications: a technology status review. *Appl. Energy*. 86, 1823–1835.
- Khan, N. I., Iqbal, T., Hinchey, M., and Masek, V. (2009b). Performance of savonius rotor as a water current turbine. *The Journal of Ocean technology*. 4(2), 71-83.
- Khosrowpanah, S., Fiuzat, A., and Albertson, M. (1988). Experimental Study of Cross Flow Turbine. *J. Hydraulic Eng*. 114(3), 299–314.
- Khurana, S., Kumar, V. and Kumar, A. (2013). The effect of nozzle angle on erosion and the performance of turgo impulse turbines. *International Journal on Hydropower and Dams*. P. 97-101.
- Kiely, G. K., and E. J. McKeogh. (1991). Experimental comparison of velocity and turbulence in compound channels of varying sinuosity. *Channel Flow Resistance: Centennial of Manning's Formula*. 393-408.
- Kim, J.; Parviz, M.; and Robert, M. (1987). Turbulence statistics in fully developed channel flow at low Reynolds number. *Journal of Fluid Mechanics*. 177(1), 133-

166.

- Kim K P, Rafiuddin Ahmed and Young-Ho Lee. (2012). Efficiency improvement of a tidal current turbine utilizing a larger area of channel. *Renewable Energy*. 48, 557 - 564.
- Kim, Byung-Ha, Joji Wata, Mohammed Asid Zullah, M. Rafiuddin Ahmed and Young-Ho Lee. (2015). Numerical and experimental studies on the PTO system of a novel floating wave energy converter. *Renewable Energy*. 79, 111-121.
- Kirke, B. (2006). *Developments in Ducted Current Turbine Sustainable Energy Centre*, University of South Australia, Mawson Lakes, Australia.
- Kirke, B. (2011). Tests on ducted and bare Helical and straight blade Darrieus hydrokinetic turbines. *Renewable Energy*. 36(11), 3013–22.
- Kirke, B. K., and Lazauskas, L. (2011). Limitations of fixed pitch Darrieus hydrokinetic turbines and the challenge of variable pitch. *Renewable Energy*. 36(3), 893-897.
- Kokubu, Kiyoshi, Toshiaki Kanemoto and Keisuke Yamasaki. (2013). Guide Vane with Current Plate to Improve Efficiency of Cross Flow Turbine. *Open Journal of Fluid Dynamics*. 3(2), 28.
- Kothandaraman C.P and Rudramoorthy R. (2007). *Fluid Mechanics and Machinery*. (2nd Edition). New Delhi, India: Age International Publishers. pages (383-393).
- Koukouvinis, P.K., Anagnostopoulos, J.S. and Papantonis, D.E. (2011). SPH method used for flow predictions at a Turgo impulse turbine: Comparison with Fluent. *World Academy of Science, Engineering and Technology*. 79, 659-666.
- Kumar A, Tschei, Ahenkorah, A., Caceves, R. Devernay, J.M, Freitas, M., Hall, A., Killingtveiet, A. and Liu, Z. (2011). *Hydropower in IPCC Special Report In Renewable Energy Sources And Climate Change*. UK and USA: Cambridge University press.
- Kusakana K, Munda JL, Jimoh A.A. (2008). Economic and environmental analysis of micro hydropower system for rural power supply. *Proceedings of the IEEE 2nd International Power and Energy Conference*. 1-3 Dec. Johor Bahru. pp. 441–444.
- Lain, S., and Osorio, C. (2010). Simulation and evaluation of a straight-bladed Darrieus-type cross flow marine turbine. *Journal of scientific & industrial research*. 69(12), 906-912.
- Launder, B. E., Reece, G. J. and Rodi, W. (1975). Progress in the Development of a Reynolds-Stress Turbulent Closure. *Journal of Fluid Mechanics*. 68(3), 537-

566.

- Lawn, C.J. (2003). Optimization of the power output from ducted turbines. *Proc. Inst. Mech. Eng. Part A, J. Power Energy*. 217, 107–117.
- Lazauskas, L. and Kirke, B. K. (2012). Modeling passive variable pitch cross flow hydrokinetic turbines to maximize performance and smooth operation. *Renewable Energy*. 45(0), 41-50.
- Lee N J, In Chul Kim, Chang Goo Kim, Beom Soo Hyun and Young Ho Lee. (2015). Performance study on a counter-rotating tidal current turbine by CFD and model experimentation. *Renewable Energy*. 79, 122-126.
- Liu H, Shun Ma, Wei Li, Hai-gang Gu, Yong-gang Lin and Xiao-jing Sun. (2011). A review on the development of tidal current energy in China. *Renewable and Sustainable Energy Reviews*. 15, 1141–1146.
- Lokocz, T.A. (2012). *Testing of a Ducted Axial Flow Tidal Turbine, University of Maine, Wind Energy Explained: Theory Design and Application*. (2nd edition). UK: Wiley.
- Matthews, B.W.; Fletcher, C.A.J.; Partridge, A.C.; and Jancar, A. (1996). Computational Simulation of Spiral Concentrator Flows in the Mineral Processing Industry. *Chemeca*. 96, 17.
- Matthews, B.W.; Fletcher, C.A.J.; and Partridge, A.C. (1997). Computational simulation of fluid and dilute particulate flows on spiral concentrators. *International Conference on CFD in Mineral & Metal Processing and Power Generation*. 3-4 July. Melbourne, Australia, 101-109.
- Miller G, Corren D, Peter Armstrong, Joseph Franceschi (1987), a study of an axial-flow turbine for kinetic hydro power generation. *Energy*. 12(2), 155-162.
- Mockmore, C.A. and Merryfield, F. (1949). The Banki Water Turbine. In Bulletin Series, Engineering Experiment Station; Oregon State System of Higher Education, Oregon State College: Corvallis, OR, USA.
- Morales, R.E.M. and Rosa E.S (2007). Modeling of free surface flow in a helical channel with finite pitch. *Journal of the Brazilian Society of Mechanical Sciences and Engineering*. 29(4), 345-353.
- Morales, R.E.M and Rosa E.S. (2012). Modeling fully developed laminar flow in a helical duct with rectangular cross section and finite pitch. *Applied Mathematical Modelling*. 36(10), 5059-5067.
- Motohashi, H., Goto, M. and Sato, Y. (2010). Development and field test of

- open cross flow type micro water turbines. *Nihon Kikai Gakkai Ronbunshu, B Hen/Transactions of the Japan Society of Mechanical Engineers*. Part B, 76 (763), 371-373.
- Motwani K H, Jain S V and Patel R N (2013). Cost analysis of pump as turbine for pico hydropower plants – a case Study. *Procedia Engineering*. 51, 721–726.
- Munson B. R., Young. D F. and Theodore H. Okishi. (2006). *Fundamentals of fluid mechanics*. (5th edition). China: John Wiley and Sons (Asia), Pte Ltd, page (576).
- Nakase, Y., J. Fukutomi, T. Watanabe, T. Suetsugu, T. Kubota, and S. Kushimoto. (1982). A study of Cross-Flow turbine (Effects of nozzle shape on its performance), *In Small Hydro Power Fluid Machinery (Proc. the Winter Annual Meeting of the American Society of Mechanical Engineers)*, Phoenix, Arizona,USA, pp.13-18.
- Nobari, M.R.H.; and Malvandi, A. (2013). Torsion and curvature effects on fluid flow in a helical annulus. *International Journal of Non-Linear Mechanics*. 57, 90-101
- Olgun, H. (1998), Investigation of the performance of a cross flow turbine. *International Journal of Energy Research*. 22, 953-64.
- OKA CORPORATION BHD,
<http://www.oka.com.my/index.asp?LanguagesID=1&TitleReferenceID=1212&CompanyID=29>. Accessed on 12 /12/ 2013.
- Okot, D. (2013). Review of small hydropower technology. *Renewable and Sustainable Energy Reviews*. 26, 515–520.
- Orengine international Ltd, <http://www.orengine.com/en/orengine-international-hydro-turbines-crossflow.php>. Accessed on 16 /7/ 2015.
- Ossberger GmbH Co. (2011) The Ossberger turbine. Bayern, Germany.
<http://www.ossberger.de/cms/en/hydro/the-ossberger-turbine-for-asynchronous-and-synchronous-water-plants/>. Accessed on 15 /8/ 2013.
- Ott, R. and Chappel J. (1989), Design and efficiency testing of a cross-flow turbine. *In Proceedings of American Society of Civil Engineers (ASCE) on Waterpower 89*, August 23-25. New York, N.Y. 1534-1539.
- Paish, O. (2002a). Micro-hydropower: Status and prospects, *Proceedings of the Institution of Mechanical Engineers, Part A: Journal of Power and Energy*. 2002, 216-231.
- Paish, O. (2002b). Small hydro power: technology and current Status. *Renewable and Sustainable Energy Reviews*. 6, 537–556.

- Patankar, S.V. (1980). *Numerical heat transfer and fluid flow*. (1st edition). USA: Taylor & Francis.
- Parker, G. J. (1996). A Theoretical Study of the Performance of an Axial Flow Turbine for a Micro hydro Installation, Proceedings of the Institution of Mechanical Engineers, Part A: *Journal of Power and Energy*; 210; 121.
- Peerhossaini, H. and Le Guer, Y. (1992). Effect of curvature plane orientation on vortex distortion in curved channel flow. *Ordered and Turbulent Patterns in Taylor-Couette Flow*. USA: Springer, 263-272.
- Poskas, P., Simonis, V. and Ragaisis, V. (2011). Heat transfer in helical channels with two-sided heating in gas flow. *International Journal of Heat and Mass Transfer*, 54(4), 847-853.
- Prasad D. D , Rafiuddin. M Ahmed and Young-HoLee. (2014). Flow and performance characteristics of a direct drive turbine for wave power generation, *Ocean Engineering*. 81, 39–49.
- Ramos. H, Borga. A (1999), Pumps as turbines: an unconventional solution to energy production, *Urban Water 1* ; 261-263.
- Ramos, H. M. and Simão M, Borga A. (2013). Experiments and CFD Analyses for a New Reaction Micro hydro Propeller with Five Blades. *J. Energy Eng.* 139, 109-117.
- Ramos, V. and Iglesias, G. (2013). Performance assessment of Tidal Stream Turbines: A parametric approach. *Energy Conversion and Management*. 69, 49-57.
- Ranjitkar, G., Jinxing, H. and Tung, T. (2006). Application of micro-hydropower technology for remote regions. *IEEE EIC Climate Change Technology*. 10 May, 1–10.
- Renewables FIRST company,
<https://www.renewablesfirst.co.uk/hydropower/hydropower-learning-centre/crossflow-turbines/> Accessed in 18/6/2015.
- Resiga, R.S., Thi, C., Sebastian Muntean, Gabriel Dan Ciocan and Bernd Nennemann. (2006). Jet Control of the Draft Tube Vortex Rope in Francis Turbines at Partial Discharge. *23rd IAHR Symposium*. October. Yokohama, 17-21.
- Resiga, R.S, Muntean, S., Stein, P. and Avellan, F. (2009). Axisymmetric swirling flow simulation of the draft tube vortex in Francis turbines at partial discharge. *International Journal of Fluid Machinery and Systems*. 2(4), 295-302.
- Rojanamon, P. and Taweep, C. (2009). Thawilwadee Bureekul Application of

- geographical information system to site selection of small run-of-river hydropower project by considering engineering/economic/ environmental criteria and social impact. *Renewable and Sustainable Energy Reviews*. 13, 2336–2348.
- Round and George, F. (2004). *Incompressible Flow Turbomachines*. chapter 3 (turbines). Burlington: Butterworth-Heinemann.
- Ruprecht, A., Helmrich, T., Aschenbrenner, T. and Scherer, T. (2002). Simulation of vortex rope in a turbine draft tube, *Proceedings of the Hydraulic Machinery and Systems, 22nd IAHR Symposium*. 9-12 September. Lausanne, 9-12 .
- Sahim, K., Santoso, D., and Radentan, A. (2013). Performance of Combined Water Turbine with Semielliptic Section of the Savonius Rotor, *International Journal of Rotating Machinery*. 2013, 5.
- Sammartano, Vincenzo, Costanza Aricò, Armando Carravetta, Oreste Fecarotta, and Tullio Tucciarelli. (2013). Banki-michell optimal design by computational fluid dynamics testing and hydrodynamic analysis. *Energies*. 6(5), 2362-2385.
- Scherillo, F., Maisto, U ., Troise, G ., Coiro, D.P., and Miranda, S . (2011). Numerical and experimental analysis of a shrouded hydro turbine. *International Conference on Clean Electrical Power (ICCEP)*. 14-16 June. Ischia, Italy, 216–222.
- Schönfeld, F. and Hardt, S. (2004). Simulation of helical flows in micro channels. *Journal of American Institute of Chemical Engineers*. 50(4), 771-778.
- Shahsavari, M., Bibeau, E. L. and Chatoorgoon, V. (2015). Effect of shroud on the performance of horizontal axis hydrokinetic turbines, *Ocean Engineering*. 96, 215–225.
- Shimokawa K, Furukawa A, Kusuo Okuma, Daisuke Matsushita and Satoshi Watanabe. (2012). Experimental study on simplification of Darrieus-type hydro turbine with inlet nozzle for extra-low head hydropower utilization. *Renewable Energy*. 41, 376-382.
- Shiono Mitsuhiro, Kdsuyuki Suzuki and Sezji Kiho. (2002). Output Characteristics of Darrieus Water Turbine with Helical Blades for Tidal Current Generations. *Proceedings of The Twelfth International Offshore and Polar Engineering Conference Kitakyushu*. 26-31 May . Japan.
- Simonis, V., Poskas, P.; and Ragaisis, V. (2012). Enhancement of heat transfer and hydraulic drag in gas-cooled helical channels with artificial roughness on convex wall. *Nuclear Engineering and Design*. 245, 153-160.
- Singh, P. and Nestmann, F. (2009). Experimental optimization of a free vortex

- propeller runner for micro hydro application. *Experimental Thermal and Fluid Science*. 33, 991–1002.
- Singh, P. and Nestmann, F. (2011). Experimental investigation of the influence of blade height and blade number on the performance of low head axial flow turbines. *Renewable Energy*. 36 , 272-281.
- Small Hydropower Technology and Market Assessment 2009, <http://www.oregon.gov/energy/renew/hydro/docs/SmallHydropowerTechnology-and-Market-Assessment.pdf?ga=t> accessed on 5/09/2013.
- Sproles Darrell W. (1996). *Computer Program To Obtain Ordinates for NACA Airfoils*, NASA Technical Memorandum 4741,1996, National Aeronautics and Space Administration, Langley Research Center, Hampton, Virginia.
- Solemslie, B. W. and Dahlhaug, O. G. (2012). A reference Pelton turbine design. *26th IAHR Symposium on Hydraulic Machinery and Systems, IOP Conf. Series: Earth and Environmental Science*. 19-23 August. Beijing, China, 15, 032005.
- Stamatelos, F. G., Anagnostopoulos, J. S. and Papantonis, D. E. (2011). Performance measurements on a Pelton turbine model, *Proceedings of the Institution of Mechanical Engineers, Part A: Journal of Power and Energy*. 225- 351.
- Stokes, Y.M. (2001). Flow in spiral channels of small curvature and torsion. *IUTAM Symposium on Free Surface Flows*. 289-296.
- Stokes, Y.M. (2001). Computing flow in a spiral particle separator. *14th Australasian Fluid Mechanics Conference*. 10-14 December. Adelaide University, Adelaide, Australia, 1-4.
- Stokes, Y.M., Wilson, S.K. and Duffy, B.R. (2004). Thin-film flow in open helically-wound channels. *15th Australasian Fluid Mechanics Conference*. 13-17 December. The University of Sydney, Sydney, Australia, 1-4.
- Stokes, Y.M., Duffy, B.R., Wilson, S.K. and Tronnolone, H. (2013). Thin-film flow in helically wound rectangular channels with small torsion. *Physics of Fluids*. 25(8), 083-103.
- Tide tables Malaysia. (2010). *National Hydrographic Centre*. Malaysia: Royal Malaysian Navy.
- Thomson and James. (1876). On the origin of windings of rivers in alluvial plains with remarks on the flow of water round bends in pipes. *Proceedings of the Royal Society of London*. 25 (171-178), 5-8.
- Thomson and James. (1877). On the origin of windings of rivers in alluvial plains,

with remarks on the flow of water round bends in pipes. *Proceedings of the Royal Society of London*. 26(3), 56-57.

Toshipaproducts

http://www.tic.toshiba.com.au/product_brochures_and_reference_lists/ekids.pdf.
(Accessed on 29/08/2013).

Tushar K. Ghosh and Mark A. Prelas. (2011). *Energy Resources and Systems, Renewable Resources*. Volume 2, chapter 3. Netherlands: Springer.

U.S. Department of Energy (2001), Energy Efficiency and Renewable Energy, Small hydropower systems, FS217July 2001, U.S Department of Energy, USA.

Vennell, R. (2011). Estimating the power potential of tidal currents and the impact of power extraction on flow speeds. *Renewable Energy*. 36, 3558-3565.

Vennell, R. (2012a). Realizing the potential of tidal currents and the efficiency of turbine farms in a channel. *Renewable Energy*. 47, 95-102.

Vennell, R. (2012b). The energetics of large tidal turbine arrays. *Renewable Energy*. 48, 210-219.

Vennell, R. (2013). Exceeding the Betz limit with tidal turbines. *Renewable Energy*. 55, 277-285.

Vermaak, H. J., Kanzumba Kusakana and Sandile Philip Koko. (2014). Status of micro-hydrokinetic river technology in rural applications: A review of literature. *Renewable and Sustainable Energy Reviews*. 29, 625–633.

Versteeg H.K. and Malalasekera W. (1995). *An introduction to Computational Fluid Dynamics: The Finite Volume Method* . (2nd edition). USA: Pearson Education Limited, ISBN 978-0-13-127498-3.

Voith Hydro Pelton turbines <http://voith.com/en/products-services/hydropower/turbines/pelton-turbines-563.html>. Accessed on 10 /8/ 2013).

Voith-Siemens. (2013). Francis turbines, Hydropower generation, Voith, http://voith.com/en/Voith_Francis_turbines.pdf. Accessed 15 /8/ 2013.

Wallace, A.R. and Whittington, H.W. (2008). *Performance prediction of standardized impulse turbines for micro hydro*. Water Power & Dam Construction. U.K: Elsevier, B.V Sutton., Int..

Walseth, E. C. (2009). *Investigation of the Flow through the Runner of a Cross-Flow Turbine*. Master of Science in Product Design and Manufacturing, Norwegian University of Science and Technology, Department of Energy and Process

- Engineering, Norway.
- Wachter, S. J. (2009). *Pint-Size Dams Harness Streams*. New York Times, 16 March.
- Williams, A. A. (1994). The Turbine Performance of Centrifugal Pumps: A Comparison of Prediction Methods, *Proceedings of the Institution of Mechanical Engineers, Part A: Journal of Power and Energy*. 208, 59.
- Williams, A. A. (1996). Pumps as turbines for low cost micro hydro power. *World Renewable Energy Congress Renewable Energy (WREC), Energy Efficiency and the Environment*. 15–21 June. Colorado, U.S.A , 1227–1234.
- Williams, G.S., Clarence, W.H. and George, H.F. (1902). Experiments at Detroit, Michigan, on the effect of curvature upon the flow of water in pipes. *Transactions of the American Society of Civil Engineers*. 47(1), 1-196.
- Williamson, S.J. , Stark, B.H. (2012). Experimental optimisation of a low-head pico hydro turgo turbine , *3rd IEEE International Conference on Sustainable Energy Technologies (ICSET)*. 24 - 27 September. Kathmandu, Nepal, 322-327.
- Williamson, S.J., Stark B.H. and Booker J.D. (2013). Performance of a low-head pico-hydro Turgo turbine. *Applied Energy*. 102, 1114–1126.
- Williamson, S. J., Stark, B. H., and Booker, J. D. (2014). Low head pico hydro turbine selection using a multi-criteria analysis. *Renewable Energy*, 61; 43-50.
- Wilcox, D. C. (2008). Formulation of the $k-\omega$ Turbulence Model Revisited. *AIAA Journal*. 46 (11), 2823–2838
- Xia, G.D. and Liu, X.F. (2014). An investigation of two-phase flow pressure drop in helical rectangular channel. *International Communications in Heat and Mass Transfer*. 54, 33-41.
- Xiao, Q., Liu, W., and Incecik, A. (2013). Flow control for VATT by fixed and oscillating flap. *Renewable Energy*. 51, 141-152.
- Xiao Y.X, Han Feng-qin and Zhou Jing-lin. (2007). Kubota Takashi, numerical prediction of dynamic performance of pelton turbine. *Journal of Hydrodynamic, Ser.B*. 19(3), 356-364.
- Xiao Y. X, Cui T, Wang Z. W and Yan. (2012). Numerical simulation of unsteady free surface flow and dynamic performance for a Pelton turbine. *26th IAHR Symposium on Hydraulic Machinery and Systems, IOP Conf. Series: Earth and Environmental Science*. 19–23 August. Beijing, China, 15; 052033.
- Yaakob, O. B., Tawi, K., and Sunanto, D. S. (2010). Computer simulation studies on the effect overlap ratio for savonius type vertical axis marine current turbine. *Int.*

J. Eng. Trans. 23, 79-88.

- Yaakob, O. B. (2012). Marine renewable energy initiatives in Malaysia and South East Asia. *13th meeting of the United Nations Open-ended Informal Consultative Process on Oceans and the Law of the Sea*. 29 May to 1 June (2012). New York.
- Yang, B., and Lawn, C. (2011). Fluid dynamic performance of a vertical axis turbine for tidal currents. *Renewable Energy*. 36(12), 3355-3366.
- Yang, B., and Shu, X. W. (2012). Hydrofoil optimization and experimental validation in helical vertical axis turbine for power generation from marine current. *Ocean Engineering*. 42(0), 35-46.
- Yang, S.S., Fan-Yu Kong, Hao Chen and Xiang-Hui Su. (2012). Effects of Blade Wrap Angle Influencing a Pump as Turbine. *Journal of fluids engineering*. 134(6), 061102.
- Yousef Yassi and Hashemloo. (2010). Improvement of the efficiency of the Agnew micro hydro turbine at part loads due to installing guide vanes mechanism. *Energy Conversion and Management*. 51, 1970–1975.
- Zhao, G., Yang, R.S., Liu, Y., and Zhao, P.F. (2013). Hydrodynamic performance of a vertical-axis tidal-current turbine with different preset angles of attack. *Journal of Hydrodynamics, Ser. B*. 25(2), 280-287.