

THREE DIMENSIONS POSITIONING BASED LOCATION TRACKING
TEHCNIQUE FOR INDOOR ENVIRONMENT

NORHIDAYU SHAHILA BINTI ABU HASSAN

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Master of Engineering (Electrical)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

MAY 2014

This thesis is dedicated to

Dad, Abu Hassan Bin Haji Mat Saman,

Mum, Sharifah Binti Jalil

Also my siblings and my fiancé Habib Sandriawan

For my supervisors Assoc. Prof. Dr. Sharifah Hafizah Binti Syed Ariffin, Assoc.
Prof. Dr. Liza Binti Abdul Latiff and also to all my friends who have always been
very supportive and guide me throughout my academic career.

ACKNOWLEDGEMENT

Alhamdulillah, thanks to Allah S.W.T the most merciful and the most compassionate for the guidance and knowledge bestowed upon me, for without it I would not have been able to come this far. Peace is upon him, Muhammad the messenger of God.

I would like to express my sincere gratitude to my supervisor, Assoc. Prof. Dr. Sharifah Hafizah Binti Syed Ariffin for guiding me throughout my research, contributing ideas, providing information and also advice to make the report more complete. Her valuable and constructive suggestions have enabled this project to run smoothly.

My appreciation also to my co-supervisor, Assoc. Prof. Dr Liza Binti Abdul Latiff for her cooperation, guidance and assistance in this project. I am also indebted to all fellow students and staffs of UTM-mimos Centre of Excellence, Faculty of Electrical Engineering, UTM for giving the relevant trainings, guidance and equipments.

A special thank to my family, my fiancé and all my friends for their advice, patience and consistent encouragement. Lastly my heartfelt appreciation goes to all who have directly or indirectly helped me to make this project a success.

ABSTRACT

Traditional tracking system with Two Dimensions-image (2D-image) standard presents only few and dull information to users. In addition, 2D localization only supports one level platform (i.e. horizontally). Thus, the Three Dimensions (3D) location tracking system has been developed to support multilevel building. The aim of this research is to develop a positioning based indoor tracking system with 3D locations which are able to provide more useful location tracking information to users using radio signals. In this research, a Wireless Fidelity (Wi-Fi) based indoor location tracking approach is introduced. We used the existing Wireless Local Area Network (WLANs) attached devices called the Access Point (AP) to the edge of the wired network. Mobile Node (MN) communicates with the three APs to receive signals. The Receive Signal Strength Indicator (RSSI) is used to calculate the distance between MN and APs. To determine the location of the MN the trilateration method is used. Finally, the database file is developed to store all the results calculated by the location server. The location tracking system is able to detect positions of MN without using Global Positioning System.

ABSTRAK

Sistem penjejak tradisional dengan imej piawai Dua Dimensi (2D) hanya mempersembahkan maklumat yang sedikit dan pudar kepada para pengguna. Tambahan pula penyetempatan 2D hanya menyokong satu aras pelantar (contohnya melintang). Maka, sistem penjejak kedudukan Tiga Dimensi (3D) telah dibangunkan untuk menyokong bangunan yang mempunyai pelbagai aras. Sasaran kajian ini adalah untuk membangunkan kedudukan berdasarkan sistem penjejak dalaman dengan kedudukan 3D yang berupaya menyediakan maklumat penjejakan kedudukan yang lebih berguna kepada pengguna menggunakan isyarat radio. Dalam kajian ini, pendekatan penjejak kedudukan dalaman berdasarkan Sistem Rangkaian Pautan tanpa Wayar (Wifi) diperkenalkan. Kami menggunakan alat Rangkaian Kawasan Tempatan tanpa Wayar (WLAN) yang sedia ada yang dipanggil Titik Capaian (AP) pada rangkaian berwayar. Titik Mobil (MN) berkomunikasi dengan tiga titik capaian untuk menerima isyarat. Penunjuk Kekuatan Isyarat Menerima (RSSI) digunakan untuk mengira jarak antara titik mobil dan titik capaian. Untuk menentukan kedudukan titik mobil kaedah *trilateration* digunakan. Akhirnya, fail pangkalan data dibangunkan bagi menyimpan semua keputusan yang dikira oleh pemberi kedudukan. Sistem penjejak kedudukan berupaya mengesan kedudukan-kedudukan MN tanpa menggunakan Sistem Kedudukan Sejagat.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATIONS	xiii
1	INTRODUCTION	
	1.1 Overview	1
	1.2 Problem Statement	4
	1.3 Research Objectives	5
	1.4 Scope of work	5
	1.5 Significant Contributions of Research	7
	1.6 Organization of the Thesis	7
2	LOCATION TRACKING TECHNOLOGIES	
	2.1 Overview	9
	2.2 Indoor Location Tracking Systems	10
	2.2.1 Proximity Estimation	12

2.2.2	Angulation Estimation	13
2.2.3	Triangulation	14
	2.2.3.1 Different Case of Triangulation Estimation	19
2.2.4	Trilateration Estimation	21
2.2.5	Fingerprinting Estimation	24
2.3	Another Ranging Approach	27
2.3.1	Kalman Filter	27
2.3.2	MoteTrack	28
2.4	Indoor Location Tracking System Applications	29
2.4.1	Active Badge	29
2.4.2	Cricket	30
2.4.3	RADAR	30
2.5	IEEE 802.11 Standard	31
2.6	Internet Protocol version 6 (IPv6)	32
2.6.1	The Advantages of IPv6	33
2.6.2	Comparison between IPv6 and IPv4	35
2.6.3	Quagga Software	37
2.7	Operating System	38
2.7.1	Ubuntu	39
2.8	Summary	40
3	DESIGN AND IMPLEMENTATION OF THREE DIMENSION TRILATERATION SYSTEM	
3.1	Introduction	41
3.2	Equipments Features	41
3.3	System Architecture	43
3.4	Receive Signal Strength Indicator (RSSI) Approach	46
3.5	3D Trilateration Approach	48
3.6	Path Loss Equations	51
3.7	System Process Flow	42
3.8	Summary	58
4	DESIGN AND IMPLEMENTATION OF THREE DIMENSION FINGERPRINTING SYSTEM	

4.1 Overview	59
4.2 System Architecture	59
4.3 Fingerprinting Technique	62
5 RESULTS AND DISCUSSIONS	
5.1 Overview	64
5.2 Trilateration Systems Results	64
5.2.1 2D Trilateration System	64
5.2.2 3D Trilateration System in One Level	68
5.2.3 3D Trilateration System in Multilevel	75
5.3 3D Fingerprinting System Results	78
6 CONCLUSIONS	
6.1 Overview	81
REFERENCES	83-87
Appendices A-G	

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Comparison between the IPv6 and IPv4	35
3.1	Cisco Aironet 1200 Series AP physical interface connection	43
5.1	Comparison between Real and Measured 2D Coordinates of Mobile Node	67
5.2	Comparison between a Real and Measured 3D Coordinate of Mobile Node	69
5.3	Comparison between a Real and Measured 3D Coordinate of Mobile Node	70
5.4	Comparison between a Real and Measured 3D Coordinate of Mobile Node	71
5.5	Comparison between Real and Measured 3D Coordinates of Mobile Node	76

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Concept of the GPS satellite constellation	4
2.1	Classification of Location Tracking System	11
2.2	Proximity Estimation	12
2.3	Triangulation Estimation	15
2.4	Estimation in Centralized System	20
2.5	Estimation in Target Node	20
2.6	Trilateration Estimation	22
2.7	Fingerprinting Implementation	25
3.1	3D View of Trilateration Architecture	44
3.2	Top View of Trilateration Architecture	45
3.3	Side View of Trilateration Architecture	48
3.4	Flow of the System	53
3.5	Flowchart at Location Server	54
3.6	IPv6 address for the Location Server	55
3.7	IPv6 address for the Mobile Node	56
3.8	Input and Output Compiling at Location Server	57
3.9	Output Compiling at Mobile Node	57
3.10	Hub (DLINK WIRELESS) Connection	58
4.1	Front View of Fingerprinting Architecture	60
4.2	Top View of Fingerprinting Architecture	61
5.1	Real and Measured 2D Coordinate of Mobile Node	65
5.2	Real and Measured 2D Coordinate of Mobile Node	66
5.3	Real and Measured 2D Coordinate of Mobile Node	66

5.4	Real and Measured 2D Coordinate of Mobile Node	67
5.5	Real and Measured 3D Coordinate of Mobile Node	72
5.6	Real and Measured 3D Coordinate of Mobile Node	73
5.7	Real and Measured 3D Coordinate of Mobile Node	74
5.8 (a), (b), (c)	Real and Measured 3D Coordinates of Mobile Node	77
5.9	Real and Measured 3D Coordinate of Mobile Node using Fingerprinting System	79
5.10	Real and Measured 2D Coordinate of Mobile Node using Fingerprinting System	80

LIST OF ABBREVIATIONS

<i>AOA</i>	-	Angle of Arrival
<i>AP</i>	-	Access Point
<i>GPS</i>	-	Global Positioning System
<i>IEEE</i>	-	Institute of Electrical and Electronics Engineers
<i>IETF</i>	-	Internet Engineering Task Force
<i>IP</i>	-	Internet Protocol
<i>IPng</i>	-	IP next generation
<i>IPv4</i>	-	Internet Protocol version 4
<i>IPv6</i>	-	Internet Protocol version 6
<i>MN</i>	-	Mobile Node
<i>NAT</i>	-	Network Address Translation
<i>NIC</i>	-	Network Interface Card
<i>RSSI</i>	-	Received Signal Strength Indicator
<i>SIP</i>	-	Session Initiation Protocol
<i>TOA</i>	-	Time of Arrival
<i>VoIP</i>	-	Voice over Internet Protocol
<i>WLAN</i>	-	Wireless Local Area Network

CHAPTER 1

INTRODUCTION

1.1 Overview

Nowadays, wireless technology becomes very important in life which enables humans to communicate around the world either in short distance or long distance without having to plug in any cable. All sectors including universities, companies, stations as well as airports and cafeteria provide wireless communication facilities. The networks are developed using a devices called access point that provide total connectivity surround the area and connection to internet. Some devices are necessary to cover a big area including outside a building and small area like an office, a lab or an airport. The signal strength of the access point influence the number of users supported. If the signal strength is high, large number of users can be supported and vice versa. However, the numbers of access point is not influenced the signal strength. Even single wireless internet access point can support a large number of users simultaneously.

Besides internet access, wireless communication supports the world community with variety of applications in the military, consumer, government and

business such as radio and television broadcasting, HF radio and satellite communication, home accessories, GPS service, television and many more. These advantages bring the idea to implement user location tracking on the premises using this network. Localization is the process of determining an object's location in space. Location tracking can be categorized as indoor and outdoor localization. Location tracking and positioning systems can be classified by the measurement techniques applied to determine mobile device location. The approaches differ in terms of the technique used to sense and measure the position of the mobile device in the target environment.

Real Time Location System (RTLS) that determine position of the mobile device can be classified as below[1]:

- (i) Cell of origin (nearest cell)
- (ii) Distance (lateration)
- (iii) Angle (angulation)
- (iv) Location patterning (pattern recognition)

The implementation of location tracking system can be used one or more of this techniques. Some of the methods are able to optimize performance in two or more environments with very different propagation characteristics. The techniques give an advantage where at least two of this methods can be combined to sense and measured the position of mobile device. Regardless of the underlying positioning technology, the real time nature of an RTLS is only as real-time as its most current timestamps, signal strength readings, or angle-of-incidence measurements. The timing of probe responses, tag transmissions, and location server polling intervals can introduce discrepancies between the actual and reported device position observed during each reporting interval.

Nowadays, many technologies are being used to create location-tracking and location-based systems. The technologies including [2]:

(i) Geographic Information Systems (GIS)

For large-scale location-tracking systems, it is necessary to capture and store geographic information. Geographic information systems can capture, store, analyze and report geographic information.

(ii) Global Positioning System (GPS)

A constellation of 27 Earth-orbiting satellites (24 in operation and three extras in case one fails) as shown in Figure 1.1. A GPS receiver, like the one in user mobile phone, can locate four or more of these satellites, figure out the distance to each and deduce user location through trilateration. For trilateration, it must have a clear line of sight to these four or more satellites. GPS is suitable for outdoor positioning, such as surveying, farming, transportation or military used.

(iii) Radio Frequency Identification (RFID)

RFID is small and less battery microchips that can be attached to consumer goods, cattle, vehicles and other objects to track their movements. RFID tags are passive and only transmit data if prompted by a reader. Then, the reader transmits radio waves that can activate the RFID tag. The tag transmits information via a pre-determined radio frequency. This information is captured and transmitted to a central database. RFID tags are replacement for traditional UPC bar codes.

(iv) Wireless Local Area Network (WLAN)

WLAN is a network of devices that connect via radio frequency, such as 802.11b. These devices pass data over radio waves and provide users with a network with a range of 70 to 300 feet (21.3 to 91.4 meters).



Figure 1.1 Concept of the GPS satellite constellation

1.2 Problem Statement

Location tracking in an indoor environment is possible with various techniques based on mechanical, acoustical, ultrasonic, optical, infrared, inertial or radio signal measurements. Nowadays, location tracking information and visualization of 3D graphics either in outdoor or indoor environment had been presented as one of research issues. Traditional tracking system with 2D image standard presents only few and dull information to users. In addition, 2D localization only supports one level platform. Thus, the 3D location tracking system had been developed to support multilevel building.

There are many approaches to measure the location of the nodes in a network. However the methods need high cost and require specific and complex hardware. In this research, the RSSI method was preferred due to its low cost and simple in

implementation. The focus area in this research which is location tracking at the server side.

1.3 Research Objectives

The objectives of this research are to develop a 3D location tracking system to support multilevel building. The development apply an indoor tracking system with 3D locations which are able to provide more useful location tracking information to user using radio signals. The development including:

- (i) To develop an indoor location tracking system in three dimension provisioning based.
- (ii) To determine location of a mobile node at several service level using RSSI.
- (iii) To implement trilateration method and fingerprint method of tracking system.

1.4 Scope of Work

The scope of this research is to design the location tracking system to determine a mobile unit position in 3 Dimension network. The system presents in IEEE 802.11 infrastructure networks. The system operates in the IPv6 network to provide more reliable network supporting by Ubuntu. Location determination of a mobile unit is based on the RSSI from several access points varies with position of mobile. This system uses a SNMP framework to collect RSSI in the mobile unit and

communicate it to a server where the location of mobile is determined and available via http.

The designs of location tracking system in this work are using trilateration method and fingerprint method. These methods usually work in two phases:

(i) First phase (offline phase)

A database of the RSSI in each location is built. The existing Wireless Local Area Network (WLANs) attached devices work as the access point (AP) to the edge of wired network. Nodes communicate with the AP using a wireless network adapter similar in function to a traditional Ethernet adapter. The location server and the mobile node is setup. The mobile node is collected the signals from the APs and send to location server to create a database.

(ii) Second phase (online phase)

Given a sample of RSSI and a classification system which uses database information, the location server calculated the mobile node position in terms of coordinate (x, y, z) .

Most of works differ in latter phase. The design and implementation of 3D indoor location tracking has been demonstrated in a testbed to determine the position of mobile node in termed of coordinate (x, y, z) displayed at location server.

1.5 Thesis Contribution

The achievement of the research is the design and development of three dimension indoor locations tracking for mobile user. The proposed indoor location tracking consists of the software components which include the OS and the testbed network. The software component has been designed in the Ubuntu by program the system network and the testbed network has been developed by applying office environment using WLANs as a access points, desktop as a location server, laptop as a mobile node and wireless adapter as a hub between location server and mobile node. In general the contribution of the work can be highlighted as follows;

- (i) Development and implementation of indoor location tracking for three dimension (3D) that support multilevel building.
- (ii) Development and implementation of IPv6 network that supports the system in IEEE 802.11 infrastructure networks.
- (iii) Implementation of the trilateration method and fingerprint method for location tracking.
- (iv) Development and implementation of location determination of a mobile node based on the RSSI from several access points.
- (v) Development and implementation of indoor location tracking system testbed for mobile node in the office environment using the RSSI.

1.6 Organization of the Thesis

This thesis has been written in six chapters to highlight the design, development and the implementation of the 3D indoor location tracking. It begins with chapter 1 as the introduction to the thesis. It consists of overview of the

research, problem statement, objectives of the research, scope of the work and significant contribution of the project.

Chapter 2 provides the relevant background for understanding the location tracking systems for indoor environment. Besides that, this chapter presents the other important components including indoor location tracking system application, VoIP, IEEE 802.11 Standard and Internet Protocol version 6 (IPv6). The final part of chapter 2 discusses on the operating system used in the location tracking system.

Chapter 3 describes the designing and implementation of the 3 Dimension of Trilateration system. The system architecture and design is further explained in detailed in Chapter 3.

Chapter 4 elaborates the designing and implementation of the 3 Dimension of fingerprinting system. The system architecture and design is also further explained in detailed in Chapter 4.

Chapter 5 discusses the experimental results on both Trilateration system and Fingerprint system. The final chapter 6 concludes the outcomes of the research.

REFERENCES

1. Cisco Systems, Inc. Wi-Fi Location-Based Services 4.1 Design Guide. 20 May, 2008.
2. Wikipedia Foundation, “Positioning System”, http://en.wikipedia.org/wiki/positioning_system, Wikipedia, 2012.
3. Chuan-Chin Pu, Chuan-Hsian Pu, and Hoon-Jae Lee. Indoor Location Tracking using Received Signal Strength Indicator. Emerging Communications for Wireless Sensor Networks. ISBN: 978-953-307-082-7.
4. Chakkaphong Suthaputchakun; Anuchit Rueangroong. An Application of Indoor Location Tracking in Museum using IEEE802.11. *Electrical/ Electronics, Computer, Telecommunications and Information Technology - Conference on Application Research and Development (ECTI-CARD) 2010*, May 10, pp. 123-126.
5. M. Sakata; Y. Yasumuro; M. Imura; Y. Manabe; K. Chihara. ALTAIR:Automatic Location Tracking system using Active IR-Tag. *Proceeding in IEEE Conference on Multisensor Fusion and Integration for Intelligent Systems, (MFI) 2003*, Tokyo, Japan.
6. Pu, C.-C. Development of a New Collaborative Ranging Algorithm for RSSI Indoor Location Tracking in WSN. PhD Thesis, 2009, Dongseon University, South Korea.
7. Greg Welch and Gary Bishop, “An introduction to the Kalman Filter”, Department of Computer Science, University of North Carolina at Chapel Hill, Chapel Hill, July 2006.
8. Ingvar Strid and Karl Watentin, “Block Kalman Filtering for large-scale DSGE models”, *Sveriges Riksbank Working Paper Series*, June 2008.

9. Konrad Lorincz and Matt Welsh, "MoteTrack: A Robust, Decentralized Approach to RF-Based Location Tracking", *In Proceedings of the International Workshop on Location and Context-Awareness (LoCA 2005)* at Pervasive 2005, May 2005.
10. R. Want, A. Hopper, V. Falcao, and J. Gibbons, "The Active Badge Location System," *ACM Trans. Inf. Syst.*, vol.10, no. 1, pp. 91-102, 1992.
11. A. Smith, H. Balakrishnan, M. G oraczko, and N. Priyantha, "Tracking Moving Devices with the Cricket Location System," in *MobiSYS 04: Proceedings of the 2nd international conference on Mobile systems, applications, and services*, 2004, pp. 190-202.
12. P. Bahl and V. N. Padmanabhan, "RADAR: An In-building RF-based User Location and Tracking System," in *INFOCOM (2)*, 2000, pp. 775-784.
13. Machtelt Garrels, "*Introduction To Linux*", Second Edition, 2007.
14. A.Ali, L.A.Latiff,N.Fisal, " Integrating Mobile IPv6 into Wireless Mobile Ad Hoc Network, " *ICT 2004*, August 1-6, 2004, Fortaleza, Brazil.
15. Luis Mengual, Oscar Marban, Santiago Eibe. Clustering-based Location in Wireless Networks. *The International Journal of Expert Systems with Applications*. 2010. Vol. 37, pp. 6165 – 6175.
16. Nur Haliza Abdul Wahab, and Sharifah H.S.Ariffin, "Development of IPv6 Network with Location Assisted Transfer for Real Time Applications", APAN Research Paper.
17. L.A.L atiff, A.Ali, Ooi Chia-Ching, and N.Fisal, "Development of an Indoor GPS-free Self-Positioning System for Mobile Ad Hoc Network (Manet)", *International Conference on Communication*, 16-18 Nov., 2005.
18. L.A.Latiff, N. Fisal, and Sharifah H. S. Ariffin, "Simulation of Position-based Routing Protocol in Wireless Mobile Ad Hoc Network", *Third Asia International Conference on Modelling & Simulation*, 25 – 29 May, 2009.
19. N.Fisal, A.Ali, L.A.L atiff, and Ooi Chia-Ching, "Location-based Geocasting and Forwarding (LGF) strategy in Mobile Ad Hoc Network", *Proceeding (527) Networks and Communication Systems*, 2006.
20. Rudolf Pailer, Florian Wegscheider, and Joachim Fabini, "Terminal-Centric Location Services in the IP Multimedia Subsystem", *Vehicular Technology Conference*, 2006.

21. Hechmi Khelifi, and Jean-Charles Gregoire, "IMS Application Servers (Roles, Requirements, and Implementation Technologies)", IEEE Computer Society, 2008.
22. Peter Weik, "IMS Adoption and Communities Fueled by the Open IMS Core Project, Using MySQL for the Home Subscriber Server", Fraunhofer Institute FOKUS.
23. Bosco Eduardo Fernandes, "IPv6 the Catalyst for Convergence", Workshop on IPv6, Geneva, 22-23 June, 2005.
24. A.Ali, L.A.Latiff, N.Fisal, "An indoor 3D GPS-free Position Location for Mobile Ad Hoc Network", MMU International Symposium on Information and Communication Technologies 2004, Oct. 2004.
25. Wikipedia Foundation, "Session Initiation Protocol", <http://en.wikipedia.org/wiki/SIP>, 12 August 2009.
26. Faruk Bagci, Florian Kluge, Theo Ungerer, and Nader Bagherzadeh, "LocSens – An Indoor Location Tracking System using Wireless Sensors," Computer Communications and Networks, ICCCN '08: Proceedings of 17th International Conference, 2008, pp. 1-5.
27. Rashmi Bajaj; Samantha Lalinda Ranaweera; Dharma P.Agrawal. GPS: Location-Tracking Technology. *Computer in Science & Engineering* 2002, 92-94.
28. Howstuffworks, "Tracking Technolog," <http://electronics.howstuffworks.com/gadgets/high-tech-gadgets/location-tracking1.htm>.
29. Howstuffworks, "Types of Tracking," <http://electronics.howstuffworks.com/gadgets/high-tech-gadgets/location-tracking2.htm>.
30. Wikipedia, "Wireless LAN," http://en.wikipedia.org/wiki/Wireless_LAN.
31. Yanick Pouffary. IPv6 Advantages. *All IP Workshop* 2000, Feb, 2-26.
32. P. Bahl; V. N. Padmanabhan. Enhancements to the RADAR user location and tracking system. *Technical report, Microsoft Research* 2000, Feb.
33. A. Smith; H. Balakrishnan; M. Goraczko; N. Priyantha. Tracking Moving Devices with the Cricket Location System. *Proceeding in 2nd USENIX/ACM MOBISYS Conference* 2004, Boston, MA.

34. A. Harter; A. Hopper; P. Steggles; A. Ward; P. Webste. The Anatomy of a Context Aware Application. *Proceeding in 5 th Annual ACM/IEEE International Conference on Mobile Computing and Networking (MOBICOM) 1999*, Seattle, Washington, USA.
35. P. Enge; P. Misra. Special Issue on GPS: The Global positioning System. *Proceeding of the IEEE 1999*.
36. Mert Bal; Henry Xue; Weiming Shen; Hamada Ghenniwa. A 3D Indoor Location Tracking and Visualization System Based on Wireless Sensor Networks. *IEEE International Conference on Systems, Man, and Cybernetics (IEEE SMC 2010)*, Istanbul, Turkey, October 10-13,2010, pp. 1-7.
37. Simon Takens. Indoor Location Tracking using Signal Strength Pinpoints. *Master of Science Thesis*, University of Groningen, July 2010.
38. Yuri Alvarez; Maria Elena de Cos; Jose Lorenzo; Fernando Las-Heras. Novel Received Signal Strength-Based Indoor Location System: Development and Testing. *EURASIP Journal on Wireless Communications and Networking*, Campus Universitario de Gijon, Spain, Volume 2010.
39. Mike Ng Ah Ngan; Behrang Parhizkar; Mohammed Abdul Karim; Arash Habibi Lashkari. Mobile WiFi-Based Indoor Positioning System. *International Journal of Computer Science and Information Security*, LIMKOKWING University Cyberjaya, Selangor, Malaysia, Vol. 10, No. 3, March 2012.
40. Salim Outemzabet; Chahe Nerguizian. Accuracy Enhancement of an Indoor ANN-based Fingerprinting Location System Using Kalman Filtering. *IEEE 2008*, Ecole Polytechnique de Montreal, Canada.
41. F. Viani, L.Lizzi, P. Rocca, M. Benedetti, M. Donelli, A. Massa. Object Tracking Through RSSI measurements in wireless sensor networks. 8th May, 2008.
42. N. B. Privantha; A. Chakraborty; H. Balakrishnan. The Cricket Location-support system. *Proceedings of the 6th Annual International Conference on Mobile Computing and Networking (Mobi-Com'00)*, New York, NY, USA: ACM Press, 2000,pp32-43.
43. J. Hightower; R. Want; G. Borriello. Spoton: An indoor 3D Location Sensing Technology based on RF Signal Strength. University of Washington, Seattle, WA, USA, Tech. Rep. UW CSE 00-02-02, 2000.

44. D. Kanon. Using Calibration Pinpoints as a means of Indoor Location of Smart Devices. University of Groningen, 2010.
45. Nishkam Ravi; Pravin Shankar; Andrew Frankel; Ahmed Elgammal; Liviu Iftode. Indoor Localization Using Camera Phones. Rutgers University, Piscataway.
46. Ahmad Hatami. Application of Channel Modeling for Indoor Localization Using TOA and RSS, May 2006.
47. Cong; T.-X; Kim; E & Koo; I. An Efficient RSS-Based Localization Scheme with Calibration in Wireless Sensor Networks, *IEICE Trans. Communications*, vol. E91B, no. 12, pp. 4013-4016.
48. Favre-Bulle; B. Prenninger; J. & Eitzinger, C. Efficient Tracking of 3D-Robot Positions by Dynamic Triangulation, *MTC*, St. Paul, Minnesota, May 1998, pp. 446-449.
49. He; J. Optimizing 2-D Triangulations by the Steepest Descent Method, *PACIA*, Wuhan, China, December 2008, pp. 939-943.
50. Kamath; S. Meisner; E. & Isler; V. Triangulations Based Multi Target Tracking with Mobile SENSOR Networks, *ICRA*, Roma, Italy, April 2007, pp. 3283-3288.
51. Li, X.-Y.; Calinescu, G.; Wan, P.-J. & Wang, Y. Localized Delaunay Triangulation with Application in Ad Hoc Wireless Networks, *IEEE Trans. Parallel and Distributed Systems*, 2003, vol. 14, no. 10, pp 1035-1047.