APPLICATION INDEPENDENT IN LOCATION TRACKING FRAMEWORK

SAZZAD HOSSAIN

A thesis submitted in fulfilment of the requirements for the award of the degree of

Master of Engineering (Electrical)

Faculty of Electrical Engineering

Universiti Teknologi Malaysia

MARCH 2013

To beloved my Mother who always performs dowa for my success...

ACKNOWLEDGEMENT

I would like to thank my supervisor and my Alma mater, Dr. Sharifah Hafizah Syed Ariffin for her willingness and kindness to guide and teach me until this research has been completed successfully. I would like to take this opportunity to deliver and extend my heartfelt gratitude to whom have made possible to complete my thesis.

I would also like to thank the Head of the MIMOS-CoE lab Prof. Norsheila Fisal for granting me to work on MIMOS-CoE Lab. I would also thank my co-supervisors Dr. Choong Neng and Dr. Liza Abdul Latif for their help to review my paper and giving me innovative ideas. I would also like to thank MIMOS for providing the equipments and fund for this research. I would also like to appreciate ministry of Higher Education for providing grants for this research

Last but not least, I thank my family: my parents Abed Hossain and Jahanara Begum, for giving me life in the first place, for educating me in respect to both arts and science, for unconditional support and encouragement to pursue my interests. My siblings; Ezaz Hossain, Asmia Hossain and Asif Hossain, always encourage me to be confident. My thank goes to all of my colleagues and friends for their encouragement. They were always beside me and accompanying me. And to Almighty Allah, who made all things possible.

I am very much appreciative and proud to be able to have this opportunity to finish my Master by Research at Universiti Teknologi Malaysia.

ABSTRACT

Due to significant popularity of location-based services and multimedia communication over mobile devices, many researches have been conducted to extend the features of location tracking and make it cost effective to users. This research focuses on the performance of an indoor location tracking system on IPv6 network island with multiple real time applications that has location assisted session transfer feature for mobile users. Received signal strength Indicator mechanism has been used to locate the moving nodes. This research involved the development of location tracking server that monitors the dynamic and centralised MySQL database management system. Session initial protocols user agent has been used to deploy intercommunicating of multimedia data such as video and audio conference, text messaging among the moving nodes and users are able to transfer the multimedia sessions seamlessly to their nearest mobile nodes which will be determined by the location server. This study, thus, presents the variation of location tracking accuracy of triangulation system and fingerprint system on different indoor surroundings to compare the performance of their location tracking accuracy. Two indoor positioning systems, triangulation method (TM) and fingerprint method (FPM) were implemented and experiments were successfully conducted in different large area and small area scenarios of indoor environment. FPM experiments were examined into two sections: FPM database with data redundancy and FPM database without data redundancy. FPM database without data redundancy achieved 94.287% tracking accuracy which is the highest comparing to the FPM database with data redundancy and TM.

ABSTRAK

Disebabkan keperluan perkhidmatan yang berasakan lokasi dan komunikasi media untuk peranti mudah alih, banyak penyelidikan telah dijalankan untuk meluaskan penggunaan penjejakan lokasi dan membuat ianya lebih kos efektif kepada pengguna. Kajian ini memberi tumpuan kepada prestasi sistem penjejakan lokasi dalam bangunan (persekitaran tertutup) di rangkaian IPv6 dengan pelbagai aplikasi masa sebenar yang mempunyai ciri-ciri lokasi sesi perpindahan untuk membantu pengguna yang bergerak. Mekanisma petunjuk kekuatan isyarat yang diterima telah digunakan untuk mencari nod yang bergerak. Penyelidikan ini melibatkan pembangunan pelayan penjejakan lokasi akan memantau sistem pengurusan pangkalan data MySQL berpusat yang berada didalam rangkaian yang protokol permulaan sesi telah digunakan untuk sama. Ejen pengguna untuk menempatkan komunikasi data multimedia seperti video dan persidangan audio, mesej teks untuk nod yang bergerak dan pengguna dapat memindahkan sesi multimedia kepada nod terdekat yang ditentukan oleh pelayan lokasi. Dengan itu projek ini membincangkan beberapa variasi ketepatan oleh sistem triangulasi dan kaedah cap jari dalam beberapa persekitaran tertutup. Dua sistem lokasi persekitaran tertutup iaitu triangulasi (TM) dan kaedah cap jari (FPM) telah dijalankan dan experimentasi telah berjaya dilakukan dibeberapa kawasan besar dan kecil yang berbeza dalam persekitaran tertutup. Ujian FPM telah dibuat dalam dua bahagian: FPM pangkalan data dengan data pertindihan dan FPM pangkalan data tanpa data pertindihan. FPM pangkalan data tanpa pertindihan telah memberi kelebihan data mencapai 94.287% penjejakan lebih tepat berbanding dengan FPM pangkalan data dengan pertindihan data dan TM.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	V
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xii
	LIST OF ABBREVIATION	xvii
	LIST OF SYMBOLS	xviii
	LIST OF PUBLICATIONS	xix

1 INTRODUCTION

1.1	Overview	1
1.2	Problem Statement	4
1.3	Objectives	5
1.4	Scope	5
1.5	Significant Contribution of Research	6
1.6	Thesis Organization	7

2 LITERATURE REVIEW

2.1	Overv	view	8
2.2	Locat	ion Tracking Technology	9
2.3	Sessio	on Initial Protocol Overview	11
2.4	SIP U	ser Agent	13
2.5	Seam	less Connectivity	15
2.6	Relate	ed Works	17
	2.6.1	SIP Based Location Services	17
		2.6.1.1 RFID Location Tracking System	17
		Based on SIP (SIP-RLTS)	
		2.6.1.2 SIP-based Seamless-handoff (S-	19
		SIP)	
		2.6.1.3 An Indoor Tracking-based	21
		Handoff Mechanism for VoIP	
		Applications in IEEE 802.11 WLANs	
	2.6.2	Location Tracking Mechanism	23
		2.6.2.1 Cricket Location Tracking	23
		2.6.2.2 LANDMARC Tracking	24
		Algorithm	
		2.6.2.3 Fingerprint Position Error	25
		Estimation	
2.7	IEEE	802.11 Standard	28
2.8	Intern	et Protocol version 6 (IPv6) Network	29
2.9	MySq	l Database Management Systems	30
2.10) Sumn	nary	32

TRIANGULATION TRACKING SYSTEM AND 3 SIP SESSION TESTBED

3.1	Overview	33
3.2	Triangulation Tracking System Architectural	34

Design

3.3	Flow of Overall System	35
	3.3.1 Location Server Work Flow	35
	3.3.2 SIP Session Connectivity	38
3.4	Triangulation Method Algorithm	38
3.5	Work flow of SIP Session Handover	41
	3.5.1 SIP Peer to Peer Activity	41
	3.5.2 SIP Session Handover Flow	42
3.6	Setup and Configuration	43
	3.6.1 Location Server Setup	44
	3.6.2 Mobile Node Setup	49
3.7	Hardware Requirements	56
3.8	Summary	57

4

TRIANGULATION AND SIP SESSION

RESULTS

4.1	Introduction		58
4.2	Triangulation Location Tracking Analysis		59
	4.2.1	Experiment without Wall Interference:	61
	Small	Area	
	4.2.2	Experiments without Wall Interference:	64
	Large	Area	
	4.2.3	Experiment with X-Axis Wall	67
	Interference: Small Area		
	4.2.4	Experiment with X-Axis Wall	70
	Interfe	erence: Large Area	
	4.2.5	Experiment with Y-Axis Wall	72
	Interfe	erence: Small Area	
	4.2.6	Experiment with Y-Axis Wall	75
	Interfe	erence: Large Area	
4.3	SIP S	ession Implementation	77
4.4	SIP S	eamless Session Handover	78

	4.4.1	Audio SIP Session	79
	4.4.2	Video SIP Session	81
	4.4.3	Text Message SIP Session	83
4.5	Summar	ry	85

5 FINGERPRINT METHOD IMPLEMENTATION AND RESULTS

5.1	Introduction	86
5.2	Fingerprint Method	87
5.3	Fingerprint Algorithm Design and Deployment	89
5.4	Fingerprint Testbed Setup	92
5.5	Fingerprint Experiments	95
	5.5.1 FPM Experiments with RSSI Data	95
	Redundancy	
	5.5.1.1 FPM Experiment with RSSI Data	97
	Redundancy: Small Area	
	5.5.1.2 FPM Experiment with RSSI Data	92
	Redundancy: Large Area	
	5.5.2 FPM Experiments without RSSI Data	101
	Redundancy	
	5.5.2.1 FPM Experiment without RSSI	101
	Data Redundancy: Small Area	
	5.5.2.2 FPM Experiment Without RSSI	103
	Data Redundancy: Large Area	
5.6	Summary	105
CO	NCLUSION	
6.1	Introduction	106
6.2	Recommendations and Future Works	109

REFERENCES

6

Appendices A-B	
----------------	--

111

118-128

LIST OF TABLES

TITLE

TABLE NO.

2.1	Recent location tracking technologies	9
3.1	List of required hardware and software	56
4.1	Small area experiment without wall interference	62
4.2	Large area experiment without wall interference	64
4.3	X-Axis wall barrier on small area	68
4.4	X-Axis wall barrier on large area	70
4.5	Y-Axis with wall barrier on small area	73
4.6	Y-Axis wall barrier on large area	75
5.1	FPM small area experiment with RSSI data redundancy	97
	results	
5.2	FPM large area experiment with RSSI data redundancy	99
	results	
5.3	FPM small area experiment without RSSI data	102
	redundancy results	
5.4	FPM large area experiment without RSSI data	103
	redundancy results	
6.1	Average error of triangulation and fingerprint	108
	experiments on different scenarios	

PAGE

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Session Initial Protocol flow of work	12
2.2	Kphone SIP user agent	14
2.3	Greenpacket's Intouch connection manager for android	16
2.4	RFID location tracking system based on SIP architecture	18
2.5	SIP-based seamless-handoff (S-SIP) network	20
	architecture	
2.6	Indoor tracking-based handoff mechanism for VoIP	22
	applications in IEEE 802.11 WLANs architectural	
	design	
2.7	Cricket location tracking experimental setup	24
2.8	LANDMARC testbed environment	25
2.9	Fingerprint position error estimation	27
2.10	Wi-Fi networks	28
3.1	Overall testbed design of the system	34
3.2	a) Flow of location server on IPv6 network b) Flow of	36-37
	SIP session connectivity	
3.3	Triangulation method	39
3.4	SIP activity diagram	42
3.5	Sequence diagram of SIP session transference	44
3.6	Start up SIP server	44
3.7	Location sever program	45
3.8	Results on MySQL database	46
3.9	Quagga application on Ubuntu	47
3.10	Zebra configuration file	48

3.11	Mysql database configuration file	48
3.12	Kphone SIP user agent	49
3.13	Client program	50
3.14	SIP user agent Kphone call invitation	50
3.15	Kphone text messaging	51
3.16	Video conference	52
3.17	SIP session transfer	53
3.18	Kphone audio session configurations	54
3.19	Kphone external application tools	55
4.1	The indoor experiment layout	59
4.2	Small area experiments without wall interference	62
4.3	Small area experiment for fixed position without wall	63
	interference	
4.4	Large area experiments without wall interference	65
4.5	Large area experiment for fixed position without wall	66
	interference	
4.6	Triangulation scenario on X-Axis wall interference	67
4.7	X-axis with wall interference experiment in small area	69
4.8	X-Axis with wall interference experiment on large area	71
4.9	Triangulation scenario on Y-Axis wall interference	72
4.10	Y-Axis interference experiment on small area	74
4.11	Y-Axis interference experiment on large area	76
4.12	Bob handover session to Sally	78
4.13	Bob audio sessions	79
4.14	Marry audio session	80
4.15	Bob video sessions	81
4.16	Marry video session	82
4.17	Bob text message session	83
4.18	Marry text message session	84
5.1	Fingerprint coordinate structure	88
5.2	Flow of fingerprint method program	90
5.3	Pseudo code to find the closest match	92
5.4	Fingerprint location tracking testbed	93

5.5	FPM location tracking program			
5.6	FPM database with redundant RSSI data			
5.7	FPM small area experiments with RSSI data redundancy			
5.8	FPM Large area experiments with RSSI data redundancy			
5.9	FPM small area experiments without RSSI data			
	redundancy			
5.10	FPM large area experiments without RSSI data	104		
	redundancy			
6.1	Accuracy comparison of location tracking	108		

LIST OF ABBREVIATIONS

ACK	-	Acknowledgment
ALSA	-	Advanced Linux Sound Architecture
AP	-	Access Point
API	-	Application Programming Interface
B2BUA	-	Back-to-back user agent
BS	-	Base Station
DHCPv6	-	Dynamic Host Configuration Protocol for IPv6
FPM	-	Fingerprint Method
GIS	-	Geographic information system
GNU	-	Free Unix style operating system
GPS	-	Global Positioning System
GSM	-	Global System for Mobile Communications
HTTP	-	Hypertext Transfer Protocol
IEEE	-	Institute of Electrical and Electronics Engineers
IETF	-	Internet Engineering Task Force
IM	-	Instant Messaging
IPng	-	Internet Protocol Next Generation
IPSec	-	Internet Protocol Security
IPv4	-	Internet Protocol version 4
IPv6	-	Internet Protocol version 6
LAMP	-	Linux, Apache, MySQL and PHP stack
LAN	-	Local Area Networ
LANDMARC	-	Indoor Location Sensing Using Active RFID
LBS	-	Location-Based Service
LS	-	Location Server
LTE	-	Long term Evolution

MAN	-	Metropolitan Area Network
MBONE	-	Multicast Backbone
MICE	-	Multimedia Application Tool
MN	-	Mobile Node
NAT	-	Network Address Translation
NNTP	-	Network News Transfer Protocol
OSS	-	Open Sound System
PDA	-	Personal digital assistant
QoS	-	Quality of Service
RadioMAP	-	RSS mapping with the location of Access Points's
		coverage
RFC	-	Request for Comments
RFID	-	Radio Frequency Identification
RITS	-	RSS-based Indoor Tracking System
RSS	-	Real Simple Syndication
RSSI	-	Received signal strength indication
RTP	-	Real-time Transport Protocol
SA	-	Service Agent
SDP	-	Session Description Protocol
SIP	-	Session Initiation Protocol
SIP-RTLS	-	RFID Location Tracking System Based on SIP
SMTP	-	Simple Mail Transfer Protocol
SRTP	-	Secure Real-time Transport Protocol
S-SIP	-	SIP-based Seamless-handoff
STP	-	Signaling Transfer Point
STUN	-	Session Traversal Utilities for NAT
UA	-	User Agent
UDP	-	User Datagram Protocol
URI	-	Uniform Resource Identifier
URL	-	Uniform Resource Locator
V2I	-	Vehicle-to-Infrastructure
V2V	-	Vehicle to Vehicle
VIC	-	Video Conference Tool

VoIP	-	Voice over IP
WBD	-	eBeam Whiteboard software
WiFi	-	Mechanism for Wirelessly Connecting Electronic
		Devices
WiMax	-	Worldwide Interoperability for Microwave Access
WLAN	-	Wireless Local Area Network
WSN	-	Wireless Sensor Network
WWW	-	World Wide Web

LIST OF SYMBOLS

α	-	The Angle between a and d
X _{mn}	-	X-coordinates distance of P1
Y _{mn}	-	Y-coordinates distance of P1
d_0	-	Reference distance
$P_{r}(d)$	-	Received power
$\Pr(d_0)$	-	Received power at the reference distance d_0
Xσ	-	Gaussian random
WAF	-	Wall Attenuation Factor
Т	-	Number of walls between transmitter and receiver.

LIST OF PUBLICATIONS

Journals:

- Nurhaliza Abd Wahab, S.H.S. Syed Ariffin, Sazzad Hossain, Norhidayu S. Abu Hassan, N. Fisal, S.K. Syed-Yusof, Rozeha Rashid, K. N. Choong, Indoor Seamless Roaming for VoIP Using IPv6 Location Assisted Network. Cyber Journal: Journal of Selected Area in Telecommunications, April 2011, pp. 23-30, 2011.
- Sazzad Hossain, Sharifah H. S. Ariffin, N. Fisal, Choong K. N., Norhidayu S. A. H. and Liza A. L, "Seamless Multimedia Communication Applications using Location Tracking Platform on IPv6 Network", Cyber Journal: Journal of Selected Area in Telecommunications, April 2011, pp. 42-50, 2011.

Conferences:

- Sazzad Hossain, Sharifah H.S. Ariffin, Norsheila Fisal, Choong Khong Neng, N.S. Abu Hassan, L.A. Latiff, "Accuracy Enhancement of Fingerprint Indoor Positioning System", isms, pp.600-605, 2012 Third International Conference on Intelligent Systems Modelling and Simulation, 2012
- Sazzad Hossain, Sharifah H. S. Ariffin, Norsheila Fisal, Norhidayu Shahila Abu Hassan, Liza Abdul Latiff, Choong Khong Neng "Performance Analysis Indoor Location Tracking Framework with SIP on IPv6 Island", International Conference on Modeling, Simulation and Applied Optimization (ICMSAO-2011), pp. 1-7 Kuala Lumpur, Malaysia on April 19-21, 2011.
- 3. Sazzad Hossain, Sharifah H. S. Ariffin, Norsheila Fisal, Norhidayu Shahila Abu Hassan, Liza Abdul Latiff, Choong Khong Neng, "Seamless SIP Multimedia Session Transfer on IPv6 Network Via Device Switching", International

Conference on Modeling, Simulation and Applied Optimization (ICMSAO-2011), pp. 1-7 Kuala Lumpur, Malaysia, April 19-21, 2011.

CHAPTER 1

INTRODUCTION

1.1 Overview

Modern researches on the location tracking are not only focusing on the calculating distance but also seeking to developed communications between the moving nodes [1] [2]. Nowadays, indoor location tracking in wireless networks is a leading area of research. The ability to determine and track the physical location of mobile wireless nodes in the wireless local area networks (WLANs) leads to many interesting applications, particularly with regard to the tracking of people, vehicles, and robots [3-8]. There are several softwares and methods have been used to enhance the performance and usability of indoor location tracking system. The location tracking of wireless multimedia application for users is an important feature, considered as remarkable progress in location base service.

Locating objects is becoming prominent by using technologies such as global positioning system (GPS) [9], but due to indoor channel characteristics, estimating location indoors accuracy remains a difficult problem. GPS system appears with scalable, efficient and cost effective location services that are available to the large public. However, the satellite emitted signals cannot be oppressed indoor to effectively determine the location. Due to different environmental characteristics and high price of technology, widespread availability of indoor location tracking system remains in doubt. There are actually various ways for determining and tracking position indoors, but to do so accurately remain very expensive. Sometimes it is quite

difficult to measure the accurate positions of the moving nodes. However, due to the maturity in the wireless technology, location-tracking of objects and people in indoor or outdoor environments has received ample attention from researchers lately. There are various methods for identifying and tracking user position such as Cricket [10], Active Badge [11], LANDMARC [12] and Mote Track [13]. Hence, accurate estimation of location in both environments remains a longstanding difficult task.

Different indoor location tracking have their own ways to determine the position or the location of moving objects [14] [15] [16] [17]. Using location tracking mechanism, it is possible to calculate the current location of a user or an indoor object. For some applications it is sufficient to estimate the user's location in a room. Providing more accuracy opens up an opportunity for more specific services, such as real time application. Nowadays, location tracking services provide many other application for instance; audio alarm, location images, instant messaging among the moving nodes within the same range. In this research, Session Initiation Protocol (SIP) is integrated with the triangulation method to provide different multimedia communication between the mobile nodes within the range. SIP protocol is a signaling protocol which is widely used in the transport layer for controlling multimedia communication sessions such as voice and video calls over Internet Protocol (IP) [18]. The Session Initiation Protocol is a protocol to establish, maintain, and tear down multimedia sessions. Most operational experience with SIP to date has been over the IPv4 network; however, SIP implementations that support IPv6 are starting to emerge. In SIP, IPv6 support needs to be provided not only by the host on which a SIP element is executing on, but support is also expected from the application itself [19].

IPv6 is the next generation protocol for the Internet. It's designed to provide several advantages over current Internet Protocol Version 4 (IPv4). Both IPv6 and IPv4 define network layer protocol that sends from one computer to another computer over packet-switched networks such as the Internet. IPv6 deals with the main problem of IPv4, that is, the exhaustion of addresses to connect computers or host in a packet-switched network. IPv6 has a very large address space and consists of 128 bits as compared to 32 bits in IPv4 [20]. IPv6 brings quality of service that is required for several new applications such as IP telephony, video/audio, interactive games or ecommerce. Whereas IPv4 is a best effort service, IPv6 ensures Quality of Service (QoS), a set of service requirements to deliver performance guarantee while transporting traffic over the network.

A Wireless Local Area Network (WLAN) typically extends an existing wired local area network. WLANs are built by attaching a device called the Access Point (AP) to the edge of the wired network. Nodes communicate with the AP using a wireless network adapter with same in function as a traditional Ethernet adapter. The signal from the nodes or the APs that use WLAN can be read or calculated using Received Signal Strength Indication (RSSI) method. RSSI is a measurement of the present power in a received radio signal. RSSI is generic radio receiver technology metric, which is usually invisible to the user of device containing the receiver, but is directly known to users of wireless networking of IEEE 802.11 protocol family [21] [22]. Most of the previous researches on RSSI are done by utilizing existing WLAN infrastructure. This approach is no doubt a cost effective solution, however, the uses for this WLAN suffers from the elimination of rays. Some signals are too weak to contribute in the calculation of distance and therefore, they must be eliminated from the system.

The research focuses on two indoor positioning methods and their performance on a specific architecture of indoor environment. The positioning methods are; Triangulation and Fingerprinting location tracking method. The developed location tracking server has a dynamic database system which saves each data retrieved by the positioning methods and its further uses. SIP session protocol has been applied to create communication between the mobile nodes. Developed location sever has the extended feature to let the mobile node know its nearest neighbor, so that the mobile nodes can transfer their session to their nearest neighboring nodes. Entire system has been developed on Ubuntu (Linux) platform and IPv6 network has been used in the WLAN.

1.2 Problem Statement

By using RSSI, it is possible to calculate the current location or position of an indoor object. For some applications, it is even sufficient to estimate user's location in a room. Providing more accuracy opens up an opportunity for more specific services. Usually, indoor location tracking has been used to establish an ubiquitous environment to track the motion of the moving nodes or objects. These objects are such as artificial robots, tiny devices, mobiles, laptops, or monitoring children activity. It is important to calculate the proximity position of the mobile objects and store them for future records. However, several multimedia applications can be used to enhance the usability of location tracking system during tracking the devices. Some of the problems have been identified on existing systems which are given below;

- Different methods have been used, but accuracy of indoor positioning remains a hitch.
- Installations difficulties and lack of user-friendliness of the system is considered as a big issue.
- Most of the recent technologies in Location Tracking System are very expensive and less effective when it comes to use of dynamic applications which has been discussed in chapter 2.
- Applications of current location tracking system can be enhanced by adding different other software with the location tracking system.

1.3 Objectives

The objectives of the research are mentioned as follows:

- To develop a framework that can support the existing Triangulation Location Tracking System with compatible centralized database system.
- To implement Seamless Multimedia Sessions between the moving nodes over IPv6 network on the top of existing Triangulation Location Tracking System.
- To implement Fingerprint Location Tracking System and compare the tracking result with the Triangulation Location Tracking System.

1.4 Scope

The scope of this research is to develop seamless multimedia communication between the moving nodes. SER (SIP Express Router) is used as the SIP Server. SIP protocol has been used to create communication between the moving nodes over IPv6 network. Kphone SIP open source user agent is modified to create seamless SIP session. IPv6 Island Network using Ubuntu (Linux) operating system or platform which had been previously setup in UTM MIMOS CoE. All the experiments and the entire setup of this research have been implemented inside UTM MIMOS CoE laboratory. Ubuntu 9.04 is used as operating system for the Location Server and Mobile Nodes. The software called as Quagga which comes up with Ubuntu is used to set up this IPv6 network. To further enhance the operation of the Location Server, MySql database server 2005 have been deployed. The location tracking mechanism using RSSI methods has been exercised to implement Triangulation and Fingerprinting Method.

1.5 Significant Contribution of Research

This research has been conducted to improve the accuracy of the location tracking mechanism concentration in a particular indoor environment and to increase the efficiency of overall system. Extended literature review has assisted to generate new concepts in the applications on location tracking system. The contributions are being listed below;

- Seamless multimedia communication has been successfully deployed on the moving nodes over IPv6 network. SIP protocol has been applied to reduce the high traffic data during video or audio session.
- Existing Triangulation Tracking System has been improved by add centralized database and SIP session (for example; audio session, video session and text messaging session) between the moving nodes.
- Fingerprint Tracking System is developed to improve the accuracy to improve the accuracy of the tracking system. Fingerprint Tracking System has been divided into two phases; With Data Redundancy and Without Data Redundancy. Fingerprint Without Data Redundancy experiment has achieved 94.287% tracking accuracy which the highest comparing to other experiments.
- Triangulation and Fingerprint tracking program's source code has been developed from the scratch. The codes are well documented for its further uses.
- Triangulation and Fingerprint experiments have been conducted on different scenarios of an indoor environment to observe the variation error of their tracking results.
- In this research, Ubuntu is used as a platform and MySql is used as Database which provides to users a cost effective solutions.
- This kind of system can be fruitful to child-care services or health-care industries. The management can monitor their patient and patient can communicate with nearest doctor or nurse available within the same network.

1.6 Thesis Organization

This thesis is organized as follows;

Chapter 2 presents the literature review of the research, the IPv6 Network, the features of IPv6 introduction in a brief, overview of SIP protocol, Database Management System, IEEE 802.11 network and Location Tracking mechanism using RSSI. Some of the similar recent works to this research has been discussed as well.

Chapter 3 and Chapter 4 present the methodology and implementation of Triangulation method and the multimedia Seamless Session transference mechanism on moving over IPv6 network. The flow of the overall system and the implementation of database system have also discussed in this chapter. The experimented results of Triangulation method on different scenarios and Seamless connectivity of SIP sessions over IPv6 network have been briefed in Chapter 4.

Chapter 5 presents the implementation of Fingerprint method and analyzes the experimental results which have achieved on indoor environment.

The Conclusion and some new ideas proposed as future work have been discussed in the Chapter 6.

REFERENCES

- R. R. Mohamed, K. N. Choong, N. Hamzah, C. S. Lee, N. H. Wahab and S. H. Ariffin. RSSI-based Location Tracking Method for Device Switching of Real-time Application. *Wireless Communication Cluster*, Kuala Lumpur, Malaysia, 29 June 2010.
- Z. Shah, R. A. Malaney and N. T. Dao. An Architecture for Location Tracking Using SIP. *Global Telecommunications Conference*, 2007. GLOBECOM '07. IEEE, 26-30 Nov. 2007, 124.
- 3. N. Swangmuang and P. Krishnamurthy. Location Fingerprint Analyses Toward Efficient Indoor Positioning. *Sixth Annual IEEE International Conference on Pervasive Computing and Communications*, 2008, 101–109.
- H. Godrich, V. M. Chiriac, A. M. Haimovich, and R. S. Blum, Target tracking in MIMO radar systems: Techniques and performance analysis. *Proc. IEEE Radar Conf*, Washington, DC, May 2010, 1111–1116.
- M. Caceres, F. Sottile, and M. A. Spirito. Adaptive location tracking by kalman filter in wireless sensor networks. *In IEEE International Conference* on Wireless and Mobile Computing, Networking and Communications (WiMob 2009), Marrakech, Morocco, Oct. 2009.
- 6. M. Caceres, F. Sottile, and M. Spirito. WLAN-based real time vehicle locating system. *In Proc. IEEE Vehicular Technology Conference*, April 2009.
- F. Gustafsson and F. Gunnarsson. Mobile Positioning Using Wireless Networks, *IEEE Signal Processing Magazine*, July 2005, 41-53.
- Y. Gu, A. Lo, N. Ignas. A Survey of Indoor Positioning Systems for Wireless Personal Networks. *IEEE Communications Surveys & Tutorials*, 2009, 13-32.

- R. Filjar, T. Kos and V. Cicin. GPS positioning performance in the wake of the Halloween 2003 geomagnetic storm. *50th International Symposium*. 10-12 September 2008.
- S. Zhou, H. Feng, and R. Yuan. Error compensation for cricket indoor location system. *Parallel and Distributed Computing, Applications and Technologies*, 2009 International Conference pp. 390–395, 2009.
- R. Want and A. Hopper. Active badges and personal interactive computing objects. *IEEE Transactions on Consumer Electronics*. Vol. 38, Issue 1, 10 20.
- X. Yinggang, W. Zhiliang and Z. Shanshan. On RFID positioning base on LANDMARC and improved algorithm. *Control Conference (CCC)*, 2010 29th Chinese. 29-31 July 2010. Beijing, China, 4831 – 4836.
- K. Lorincz and M. Welsh. MoteTrack: A Robust, Decentralized Approach to RF-Based Location Tracking. *Springer Personal and Ubiquitous Computing*. Special Issue on Location and Context-Awareness, October 2006. ISSN: 1617-4909, 1617-4917.
- Z. Li, C. Chu, and Wen Yao. SIP-RLTS: An RFID Location Tracking System Based on SIP. 2008 IEEE International Conference on RFID, Las Vegas, Nevada, USA, April 16-17, 2008, pp.172-182.
- B. K. Kim, H. M. Jung, J-B. Yoo, W. Y. Lee, C. Y. Park and Y. W. Ko. Design and implementation of cricket-based location tracking system. *Proc.* of World Academy of Science, Engineering and Technology Vol. 28, pp. 96-100, 2008.
- Sadeh, N., Hong, J., Cranor, L., Fete, I., Kelley, P., Prabaker, M., and Rao, J. Understanding and capturing peoples privacy policies in a mobile social networking application. *Journal of Personal and Ubiquitous Computing* 13, 6 (August 2009).
- Miklas, A. G., Gollu, K. K., Chan, K. K. W., Saroiu, S., Gummadi, K. P., and De lara, E. Exploiting social interactions in mobile systems. *UbiComp'07: Proceedings of the 9th international conference on Ubiquitous computing* (Berlin, Heidelberg, 2007), Springer-Verlag, pp. 409–428.
- IETF Datatracker, Session Initiation Protocol Core (sipcore). http://datatracker.ietf.org/wg/sipcore/charter/, 10 September 2010.

- B. E. Fernandes. IPv6 the Catalyst for Convergence. Workshop on IPv6, Geneva, 22-23 June, 2005.
- Ed. H. Soliman. Mobile IPv6 Support for Dual Stack Hosts and Routers. RFC 5555, June 2009.
- 21. The New York Times Company, Bradley Mitchell, Wireless Standards -802.11b 802.11a 802.11g and 802.11n. http://compnetworking.about.com/cs/wireless80211/a/aa80211standard.htm Accessed on 1 February 2011.
- 22. The New York Times Company, Bradley Mitchell, WLAN. http://compnetworking.about.com/cs/wirelessproducts/g/bldef_wlan.htm Accessed on 22 February 2011.
- J. Keisler, R. Blake and J. Wagner. Implementing Geographic Information Systems (GIS) in Spreadsheet Models: What, Why, and How. *International Conference on System Sciences*, 2009. HICSS '09. 42nd Hawai . 5-8 Jan. 2009. Big Island, HI, 1 10.
- 24. G.B. Al-Suwaidi, M.J. Zemerly. Locating friends and family using mobile phones with global positioning system (GPS). *Computer Systems and Applications*, 2009. AICCSA 2009. Sharjah, 555 558.
- R. Bajaj, S.L. Ranaweera, D.P. Agrawal. GPS: Location-Tracking Technology. *IEEE Computer Society*. 35(4), 92 – 94.
- 26.Packetizer,UnderstandingSIP-BasedVoIP.http://www.packetizer.com/ipmc/sip/papers/understanding_sip_voip/,Accessed on 21 December 2010.
- T. Robles, R. Ortiz, J. Salvachja. Porting the session initiation protocol to ipv6. *IEEE Internet Computing* Vol.7. (2002) 43–50.
- IETF (Internet Engineering Task Force), User agent. https://tools.ietf.org/html/rfc5536#section-3.2.13, Accessed on 16 October 2010.
- Geeknet, Inc., KPhone. http://sourceforge.net/projects/kphone/, Accessed on
 22 September 2010.
- Kphone VoIP, Homepage, http://ss7.ca/kphone/, Accessed on 22 December 2010.
- IPTEL, VoIP portal, KPhone IPv6. http://old.iptel.org/products/kphone/ , Accessed on 21 April 2010.

- Lawrence Berkeley National Laboratory, Video Conferencing Tool". http://ee.lbl.gov/vic/, Accessed on 25 May 2010.
- A. M. Vegni, T. Inzerilli and R. Cusani. Seamless Connectivity Techniques in Vehicular Ad-hoc Networks. *Advances in Vehicular Networking Technologies*, Miguel Almeida (Ed.), ISBN: 978-953-307-241-8.
- 34. S. Annese, C. C.-F. Casetti, Chiasserini, N. Di Maio, A. Ghittino and M. Reineri. Seamless Connectivity and Routing in Vehicular Networks with Infrastructure. *IEEE Journal on Selected Areas in Communications*. 29 (3), 501 514.
- Technology Review, V. Lelitha Devi. Seamless Connectivity. http://www.technologyreview.in/computing/37659/, Accessed on 22 July 2010.
- 36. J. Zhang, H. Chan and V. Leung. A SIP-based Seamless-handoff (S-SIP) Scheme for Heterogeneous Mobile Networks. *IEEE Communications Society* subject matter experts for publication in the WCNC 2007 proceedings, 3949-3953.
- 37. C. Lee, S. Seo, and J. Song. An Indoor Tracking-based Handoff Mechanism for VoIP Applications in IEEE 802.11 WLANs. 4th International Conference on Information and Automation for Sustainability, Pages: 324-329, December, 2008.
- B.Amutha, M.Ponnavaikko, Location Update Accuracy in Human Tracking system using Zigbee modules, *International Journal of Computer Science* and Information Security, Vol. 6, No. 2, 2009.
- 39. H. Song, S. Lee, J. Yoon and V. Shin. Localization performance enhancement using IMM fusion in cricket sensor network. *IEEE International Conference on Information and Automation (ICIA)*, Gwangju, South Korea, 20-23 June 2010, 1526 – 1531.
- 40. M. N. Lionel, Y. Liu, Y. C. Lau and A. P. Patil. LANDMARC: Indoor Location Sensing Using Active RFID. Springer Netherlands, *Wireless Networks* 2005.
- X. Yinggang, K. JiaoLi, W. ZhiLiang and Z. Shanshan. Indoor location technology and its applications base on improved LANDMARC algorithm. *Control and Decision Conference (CCDC)*, 2011, Beijing, China, 23-25 May 2011, 2453 – 2458.

- T. Wei and S. Bell. Indoor localization method comparison: Fingerprinting and Trilateration algorithm. *Spatial Knowledge and Information SKI-Canada*, 2011, 3rd March 2011, Qubec, Canada.
- 43. R. Zhou. Wireless indoor tracking system (WITS). DoIT Conference on Software Research. 2006, 163-177.
- H. Lemelson, M. B. Kjærgaard, R. Hansen and T. King. Error Estimation for Indoor 802.11 Location Fingerprinting. *LoCA '09 Proceedings of the 4th International Symposium on Location and Context Awareness*, 2009. Berlin, Germany, 138 – 155.
- 45. D. Dearman, A. Varshavsky, E. Lara, K.N. Truong. An exploration of location error estimation. *In Proceedings of the Ninth International Conference on Ubiquitous Computing*, 2007.
- P. Crow. Fujitsu Network Commutations. University of Arizona Prescott T. Sakai, Cypress Semiconductor 1997. IEEE Communications Magazine, September 1997.
- 47. University of California Berkeley, Mustafa Ergen, "IEEE802.11", www.eecs.berkeley.edu/ergen/docs/ieee.pdf, 2002 Accessed on 22 January 2011.
- 48. Cisco Systems, Cisco Aironet 1200 Series, http://www.cisco.com/en/US/products/hw/wireless/ps430/index.html, Accessed on 15 January, 2010.
- R. Hinden, S. Deering R. Hinden and S. Deering. IP Version 6 Addressing Architecture. RFC 1884, February 2006.
- 50. Network World. Internet Protocol version 6. http://www.networkworld.com/news/2010/012110-ipv6-warning.html, 10
 September 2010.
- Claburn, Thomas (2007). Google Releases Improved MySQL Code. Information Week. Retrieved 2008-11-30.
- 52. Nur Haliza Abdul Wahab, and Sharifah H.S.Ariffin. Development of IPv6 Network with Location Assisted Transfer for Real Time Applications. 28th APAN (Asia Pacific Advanced Network) Kuala Lumpur, Malaysia, 20 July, 2009.
- A. Ali Ahmed, Indoor Location Tracking In Integrated MAnet Mobile IPv6 Network. Master Thesis. Universiti Teknologi Malaysia, 2005.

- IPTEL, VoIP portal, "About SIP Express Router", http://www.iptel.org/ser/, Accessed on 21 May 2010.
- Canonical Ltd. Ubuntu. http://www.ubuntu.com/project/about-ubuntu, Accessed on 21 January 2010.
- 56. Sveasoft Inc. Quagga. http://www.dd-wrt.com/index.php/Quagga, Accessed on 27 January 2010.
- Openmaniak Co. Zebra protocol. http://openmaniak.com/quagga_tutorial.php, Accessed on 2 February 2010.
- 58.OracleCorporation.MySQLCAPI,http://dev.mysql.com/doc/refman/5.0/en/c.html, Accessed on 17 June 2010.
- 59. D-Link Systems, Inc. Wireless Routers. http://www.dlink.com/category/productcategories/?cid=1, Accessed on 7 May 2010.
- HowStuffWorks Inc. How Location Tracking Works. http://electronics.howstuffworks.com/everyday-tech/location-tracking.htm, Accessed on 20 February 2010.
- Pyung Soo Kim, Myung Eui Lee, Soohong Park, Young Keun Kim. A New Mechanism for SIP over Mobile IPv6. *In Proceedings of ICCSA* (3)'2007. 975-984.
- I. Horrocks, P. F. Patel-Schneider, H. Boley, S. Tabet, B. Grosof, and M. Dean. SWRL: A semantic web rule language combining owl and ruleml, http://www.daml.org/2003/11/swrl/, November2003.
- J. M. Polk, and B. Rosen. Location conveyance for the session initiation protocol. Draft-ietf-sip-location-conveyance-09.txt, Internet Draft, Nov 2007, work in progress (2007).
- A. Coronato, G. De Pietro, and M. Esposito. A semantic context service for pervasive grids. *Proc. of the International Conference on Hybrid Information Technology*, ICHIT 2006, IEEE CS.
- K.L. Sue, C.H. Tsai, and M.H. Lin. FLEXOR: A Flexible Localization Scheme Based on RFID. In I. Chong, and K. Kawahara (Eds.), *International Conference on Information Networking* (ICOIN 2006), LNCS 3961, pp. 306-316, 2006.

- X. Liu, M.D. Corner, and P. Shenoy. Ferret: RFID Localization for Pervasive Multimedia. In P. Dourish, and A. Friday (Eds.), *International Conference of Ubiquitous Computing* (Ubicomp 2006). LNCS 4206, pp. 422-440, 2006.
- 67. C. Floerkemeier, M. Lampe, C. Roduner. Facilitating RFID development with the Accada prototyping platform. *Proceedings of PerWare Workshop* 2007 at IEEE International Conference on Pervasive Computing and Communications. New York, USA, March 2007.
- G. Mao, B. D. O. Anderson, and B. Fidan. Path loss exponent estimation for wireless sensor network localization. *Computer Networks*, vol.51, no. 10, 2006, pp. 421-436.