

STRUCTURAL BEHAVIOUR OF PRE-FABRICATED COMPOSITE PAD
FOOTING FOUNDATION USING COLD-FORMED STEEL OF LIPPED
CHANNEL SECTIONS

KOO TING CHOONG

UNIVERSITI TEKNOLOGI MALAYSIA

STRUCTURAL BEHAVIOUR OF PRE-FABRICATED COMPOSITE PAD
FOOTING FOUNDATION USING COLD-FORMED STEEL OF LIPPED
CHANNEL SECTIONS

KOO TING CHOONG

A project report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering (Structure)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

MAY 2017

To my late grandmother whom I deeply respect,

You will be fondly remembered and will be sorely missed by us.

ACKNOWLEDGEMENT

First of all, I would like to thank the Professor Mahmood Md Tahir and Dr. Shek Poi Ngian for giving me the opportunity to be involved in this project, and for the guidance that they have given to me throughout the time during Masters Project 1 and Masters Project 2. They had also made the course of the project easier through their meticulous management of the resources required for the project.

There are also many people who had helped me in making the implementation of the project possible. Mr. Misdianto who had helped me in fabricating the cold-formed steel section formworks for both pad footing and stump, and also for bending of the reinforcement bars for stumps. UTM Structure and Material Lab technicians had also helped during the casting of the pad footings and during the testing of the specimens. Without them, this project would have been impossible to be completed, and thusly, I thank them for their whole-hearted effort and cooperation.

Last but not least, I would like to thank my friends and family who had given me encouragement and support during my hardship in the mid of my Masters' studies. Their encouragement had given me strength to endure and overcome my problems to complete this project.

ABSTRACT

Pad footing foundations are traditionally made of concrete reinforced by high tensile steel bars moulded by timber formwork. This type of fabrication has three main disadvantages, which are large deviation of intended geometry due to weak structural integrity of used timber formworks, wastage of timber material as temporary timber formwork does not contribute to the strength of pad footing and as to be disposed after a certain number of usage, and longer construction time due to the need to remove the timber formwork after the concrete has hardened. Due to these disadvantages, the traditional method of constructing pad footing can cause an increase in construction cost and time, uncertainty in the quality of the final product and also environmental issues from the disposal of used timber formwork. To overcome the existing flaws of pad footing construction, the concept of pre-fabrication construction of pad footing foundation has been introduced using cold-formed steel lipped channel sections to replace timber as permanent formwork, and to replace high tensile steel bars as reinforcement in the pad footing foundation. However, such practice of using cold-formed steels in pre-fabricated pad footing foundation is still uncommon and no design guide has been established yet. This thesis investigates the moment and shear resistances and the failure modes of such pre-fabricated pad footing foundation designed to BS EN 1992-1. A total of 9 specimens were tested, which consisted of six 1000 mm x 1000 mm x 150 mm footings, and three 1000 mm x 1750 mm x 150 mm footings. The experimental result and theoretical calculation was on good agreement and the use of cold-formed steel increased the structural resistance of the footing due to composite effects. As a result, the proposed pre-fabricated pad footing foundation using cold-formed steel lipped channel sections is proved to be feasible in actual construction practice and can be reliably designed by using the existing code in BS EN 1992-1.

ABSTRAK

Penapak tunggal yang tradisional diperbuat daripada konkrit bertetulang dengan bar keluli tegangan tinggi dan dibentuk oleh acuan kayu. Jenis pembinaan tersebut mempunyai tiga kelemahan utama, iaitu sisihan besar dari geometri bertujuan disebabkan oleh integriti struktur lemah kayu terpakai, pembaziran bahan kayu sebagai acuan kayu kerana tidak menyumbang kepada kekuatan penapak tunggal dan perlu dilupuskan selepas sebilangan penggunaan, dan masa pembinaan lebih panjang kerana acuan kayu perlu ditanggalkan selepas konkrit telah keras. Oleh kerana kelemahan ini, kaedah tradisional membina penapak tunggal boleh menyebabkan peningkatan dalam kos pembinaan dan masa, kualiti produk akhir rendah dan juga isu-isu alam sekitar daripada pelupusan acuan kayu yang digunakan. Untuk mengatasi masalah pembinaan penapak tunggal, konsep pembinaan pra-fabrikasi telah diperkenalkan dengan menggunakan keluli terguling sejuk dengan keratan berbibir untuk menggantikan kayu sebagai acuan kekal, dan untuk menggantikan bar keluli tegangan tinggi sebagai tetulang dalam penapak tunggal. Walau bagaimanapun, amalan menggunakan keluli terguling sejuk dalam penapak tunggal yang dibina secara pra-fabrikasi masih lagi luar biasa dan tiada panduan reka bentuk lagi yang telah ditubuhkan. Tesis ini mengkaji rintangan momen dan ricih, dan juga mod kegagalan penapak tunggal pra-fabrikasi tersebut direkakan dengan menggunakan BS EN 1992-1. Sebanyak 9 spesimen yang terdiri daripada enam 1000 mm x 1000 mm x 150 mm penapak tunggal dan tiga 1000 mm x 1750 mm x 150 mm penapak tunggal telah diujikan. Keputusan eksperimen dan pengiraan teori menunjukkan kesamaan yang baik dan penggunaan keluli terguling sejuk meningkat rintangan struktur penapak tunggal disebabkan oleh kesan komposit. Oleh itu, boleh disimpulkan bahawa penapak tunggal yang dicadangkan menggunakan keluli terguling sejuk dengan keratan berbibir dibuktikan dapat dilaksanakan dalam pembinaan sebenar dan direka dengan menggunakan kod yang sedia ada di BS EN 1992-1

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENT	vii
	LIST OF TABLES	ix
	LIST OF FIGURES	x
	LIST OF SYMBOLS	xii
	LIST OF NOTATIONS	xiv
	LIST OF ABBREVIATIONS	xv
	LIST OF APPENDICES	xvi
1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement	2
	1.3 Research Objective	3
	1.4 Research Significance	3
	1.5 Research Scope	4
	1.6 Organisation of the Writing and Terminologies	4
2	LITERATURE REVIEW	6
	2.1 Background on Industrialized Building System (IBS)	6
	2.2 Background on Composite Construction	9
	2.3 One-way Local Buckling Due to Intimacy Contact with	9

	Concrete	
2.4	Previous Research On One-Way Local Buckling Phenomena	12
2.5	Types of Foundation	14
2.6	Design of Pad Footing	16
2.7	Development of Pre-Fabricated Cold-formed Steel Composite Pad Footing	17
2.8	Concluding Remarks	19
3	RESEARCH METHODOLOGY	20
3.1	Specimens and Materials Details	20
3.2	Design of the Pre-Fabricated CFS Composite Pad Footing	28
3.3	Preparation of Specimens	31
3.4	Experimental Tests Setup and Procedures	33
3.5	Data Acquisition	35
3.6	Concluding Remarks	36
4	RESULTS AND DISCUSSION	37
4.1	Experimental Results and Failure Modes of Specimens	37
4.2	Experimental Results of Case 1	38
4.3	Experimental Results of Case 2	42
4.4	Experimental Results of Case 3	47
4.7	Summary of Results	52
5	CONCLUSIONS	53
5.1	Summary of Research Work	53
5.2	Recommendation for Future Research	54
5.3	Conclusions	55
	REFERENCES	57
	APPENDIX A & B	61-69

LIST OF TABLES

TABLE NO.	TITLE	PAGE
3.1	Actual materials facts sheet used for design of specimens.	24
3.2	Summarized details of the specimens.	24
3.3	Theoretical failure loads of the specimens for all 3 cases.	31
4.1	Test results of Case 1	38
4.2	Test results of Case 2	42
4.3	Test results of Case 3	47

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Badir-Razali building system classification.	8
2.2	Assumed buckling shapes for outstanding flanges subject to uniform compression formulated by Wright (1995).	11
2.3	Types of shallow foundation.	15
2.4	Distribution of pressure for different soil type.	16
3.1	The cubes, size 150 mm, prepared for the cube tests.	21
3.2	The cubes casted for the cube tests.	22
3.3	The TONIPAC 300 Testing Machine used for cube tests.	22
3.4	The samples for tensile and coupon tests.	23
3.5	Typical graph generated from one of the tensile tests.	23
3.6	Plan view of Case 1 and Case 2 specimens.	25
3.7	A-A Section view of Case 1 and Case 2 specimens ('Strong section')	26
3.8	B-B Section view of Case 1 and Case 2 specimens ('Weak section')	26
3.9	Plan view of Case 3 specimens.	27
3.10	The specimens before casting work.	32
3.11	The specimens after casting work.	33
3.12	DARTEC test rig used for the experimental tests.	34

3.13	A typical test setup for all 3 cases. Specimens were simply supported at two ends.	35
3.14	Illustration of setup of the test	35
3.15	Flow of data acquisition.	36
4.1	Bottom cracks parallel to the support and internal CFS reinforcements, indicating flexural failure.	39
4.2	Steel brackets were torn out of position and tek screws were sheared off due to high deflection and deformation of the footing.	39
4.3	Large deflection and deformation seen from the side of Case 1 specimens after test.	40
4.4	Illustration of the cracks of Case 1 specimens after test.	41
4.5	Bottom of Case 2 specimen after being tested to failure. Radial symmetrical yield lines cracks from the centre to the edge of the pad were observed.	43
4.6	Top of the samples showed cracks near the edge of stump in a line parallel and next to the edge of internal CFS reinforcements.	44
4.7	Steel bracket and tek screws connections were intact and in good shape, indicating minimal deflection of footing had occurred, further suggested shear failure had occurred.	45
4.8	Illustration of the cracks of Case 2 specimens after test.	47
4.9	Bottom of Case 3 specimen after being tested to failure. Radial symmetrical yield lines cracks from the centre to the edge of the pad were observed.	48
4.10	Top of the samples showed cracks near the edge of stump in a line parallel to the edge of internal CFS reinforcements.	49
4.11	Minimal deflection and deformation is observed after test. Steel bracket and tek screws connections were found to be intact and in good shape after test.	50
4.12	Steel bracket and tek screws connections were found to be intact and in good shape after test.	51
4.13	Illustration of the cracks of Case 3 specimens after test.	52

LIST OF SYMBOLS

A_c	-	Cross section area of concrete
A_s	-	Area of steel reinforcement required
A_{sl}	-	Area of steel reinforcement provided
b_w	-	Breadth of the pad
c	-	Thickness of concrete cover
d	-	Effective depth of the pad
D	-	Height of CFS
F	-	Flange measurement of CFS
L	-	Lip measurement of CFS
f_{cu}	-	Characteristic strength of concrete
f_y	-	Characteristic strength of steel
f_{yc}	-	Characteristic strength of CFS
K	-	Factor based on simplified stress block
M	-	Moment
t	-	Thickness of CFS
U	-	Critical perimeter, $1.5d$ away from the stump/column
U_o	-	Stump/Column perimeter
V	-	Design shear force due to ultimate loads
$V_{Rd,c}$	-	Concrete shear resistance
V_{min}	-	Minimum concrete shear resistance
z	-	Lever arm of section
%	-	Percent
=	-	Equals
+	-	Plus, or Mathematical operator: plus
-	-	Dash, or Mathematical operator: minus
×	-	Mathematical operator: multiply
÷ or /	-	Mathematical operator: divide

- \wedge - Mathematical operator: to the power of
- $\sqrt{\quad}$ - Mathematical operator: square root of

LIST OF NOTATIONS

- F1010 - Case 1 specimen label. F indicating expected failure mode in flexure; first two and second two digits reflect width and length of pad respectively, 10 = 1000 mm
- S1010 - Case 2 specimen label. S indicating expected failure mode in shear; first two and second two digits reflect width and length of pad respectively, 10 = 1000 mm
- F1017 - Case 3 specimen label. F indicating expected failure mode in shear; first two and second two digits reflect width and length of pad respectively, 10 = 1000 mm, 17 = 1750 mm.
- C35 - Grade of concrete: 35 N/mm² characteristic strength at 28 days.
- KS15016C - Name of CFS section, refer to Table 3.1
- R6 - Stump/Column link bars with 6 mm diameter.
- T10 - Stump/Column reinforcement bar with 10 mm diameter.

LIST OF ABBREVIATIONS

BS	-	British Standard
BSI	-	British Standard Institution
CFS	-	Cold-formed Steel
CIDB	-	Construction Industry Development Board Malaysia
IBS	-	Industrialised Building System
kN	-	Unit of measurement: kilo Newton
<i>max</i>	-	maximum
<i>min</i>	-	minimum
mm	-	Unit of measurement: millimeter
mm ²	-	Unit of measurement: millimeter square
MPa	-	Unit of measurement: Mega Pascal, equivalent to N/mm ²
N	-	Unit of measurement: Newton
N/mm ²	-	Unit of measurement: Newton per millimeter
<i>vs</i>	-	Versus

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Force vs displacement graphs	61
B	Theoretical calculation spreadsheet & Bill of Quantities	67

CHAPTER 1

INTRODUCTION

1.1 Research Background

Waste generated from construction can cause many problems in terms of waste of materials, loss of profit, waste management and environmental pollutions. In construction industry, one of the most prominent wastage is the use of timber formwork for containment of freshly poured concrete. These temporary timber formworks contribute no structural strength to the structure as they have to be removed after the concrete has hardened and gained sufficient strength to support itself and other loadings. Different structural members may have different sizes, thus many of these formworks may only be used once and have to be modified to be used again in other areas of the building. Modification and stripping of the formworks can be time consuming and have no real value to the building itself. After being used multiple times, timber formwork could deteriorate and loses its geometrical and structural strength integrity, thus need to be replaced by new formworks. Replacements can increase the construction cost and there is also wastage from the old formworks that needed to be properly managed. Many irresponsible contractors discard the old formworks through open air burning, which contributed to air pollution.

As construction industry is booming, there are more demand for faster and better quality construction methods, which should also generate less wastage. One of the method for fast and quality construction is through prefabrication in the controlled environment of a plant. Precast concrete production eliminates the use of temporary timber formwork, as they are produced by using steel or aluminum formworks in the

plant. Steel or aluminum formworks do not deteriorate like timber after being used multiple times and they can be recycled, thus resulting in no wastage. Although there is no wastage, construction time is still similar to the conventional method as the metal formworks needed to be stripped off after the concrete has hardened. To further shorten the construction time in concrete buildings, permanent formworks are therefore more advantageous to be used compared to temporary formworks.

1.2 Problem Statement

Conventional cast in-situ pad footings require timber formwork. This method of construction generate waste as timber formwork could deteriorate after a certain amount of usage. When timber formwork loses its geometry and strength integrity, the resulting pad footing also could have undesired geometry and size. Conventional cast in-situ pad footings also require longer construction time as the timber formwork need to be stripped off after the concrete has hardened. A new method of construction is needed to eliminate the use of timber formwork for time, cost and environmental benefits.

Although it is widely acknowledged that composite construction can speed up construction time and have better structural performance compared to traditional reinforced concrete and steel, there are still comparably very few construction projects that utilize composite construction that consists of thin-walled steel skin with infilled concrete. One of the main reasons is that these type of structures have not been researched extensively and there are no well-established design codes dedicated to designing concrete infilled thin-walled steel structural elements for current practicing engineers as a guide. Most of the research done on concrete infilled thin-walled steel have been focused on application in column, beam and slab construction. As a result, some infilled thin-walled steel construction can be found applied to column, beam and slab construction in certain countries, where high structural performance and fast construction time are highly valued.

Application of infilled thin-walled steel in foundation structure construction

has not been reported before the research of Wong (2009), which focused on the structural behaviour of the composite pad footing with cold-formed lipped steel section (CFS) as both permanent formwork and reinforcement. After the research shows promising results in this type of construction, where the composite footing performed better than the theoretical calculations based on BS8110, a prototype building was constructed in the compound of Universiti Teknologi Malaysia (UTM), Skudai with this novel type of composite pad footing as its foundation structure. However, Wong's study did not include the stumps using CFS as permanent formwork and reinforcements. Also, the study was done in accordance to the requirements of BS 8110-1:1997, which is now superseded by the BS EN 1992-1. Thus, a new study of pre-fabricated pad footing using cold-formed lipped steel section designed to the requirements of BS EN 1992-1 is required.

1.3 Research Objectives

The objectives of this research are:

1. To study the structural behaviour of the square and rectangular pad footings together with its stump, using CFS as permanent formwork and reinforcement through experimental tests.
2. To validate the behaviour of the proposed construction method through comparison of the experiments results and the design requirements of BS EN 1992-1.

1.4 Research Significance

The importance of this research are:

1. Validation of the suitability of a well-established design code such as BS EN 1992-1 in predicting the most relevant structural resistances, such as moment and shear resistances of CFS pad footing.
2. Allow practicing engineers to design CFS pad footing conventionally as a reinforced concrete in accordance to BS EN 1992-1 confidently.

3. Improve construction cost and time through the usage of CFS composite pad footing in the building industry.
4. Reduce material wastage and contribute to environmental friendly construction through the application of CFS composite pad footing by eliminating timber formwork.

1.5 Research Scope

The main focus of this research is on the two structural resistances of pad footing most relevant to structural design for industrial application, which are the moment and shear resistance. Thus, the scope of this research is:

1. Analyze the bending and shear resistances of CFS composite square 1m x 1m x 0.15m square pad footing and 1m x 1.75m x 0.15m rectangular pad footing through experiment which tests the footings to failure.
2. Compare experimental results to theoretical calculations based on the requirements of BS EN 1992-1, and establish the relationships between the two.

1.6 Organisation of the Writing and Terminologies

This section provides the general overview on how the research work has been carried out and also the presentation of the obtained result in this writing. Chapter 1 and Chapter 2 consist of the available information regarding composite construction background and information which lead to the idea of proposing a prefabricated pad footing. Chapter 3 covers on the experimental and theoretical aspects of pad footing, and related methodology to conduct the research work. Chapter 4 extended the works and presented results and discussion on the data acquired and analysed from the experimental works, and standardized table is prepared. Chapter 5 concludes the writing and the research work. While efforts have been made to present the research work and the results as clearly as possible, it is the writer's concern that undefined

terms might cause confusion. Therefore, all symbols, abbreviations, and notations used in this writing can be referred as listed in the front of this thesis.

REFERENCES

- Abdul Kadir, M.R., Lee, W.P., Jaafar, M.S., Sapuan, S.M., Ali, A.A.A. (2006). Construction performance comparison between conventional and industrialised building systems in Malaysia. *Structural Survey*. Volume 24 No 5. Emerald Insight. Page 412-424.
- Arumugasaamy, P. (2006). *Structural design of foundation*. In Gunaratne, M. (Ed.). *The foundation engineering handbook* (Page 179-234). Boca Raton: Taylor & Francis Group, LLC.
- Badir, Y.F., Kadir, M.R.A. and Ali, A.A.A. (1998). Theory of classification on Badir-Razali building system classification. *Bulletin of Institution of Engineers, Malaysia*.
- Badir, Y.F., Abdul Kadir, M.R., and Hashim, A.H. (2002). Industrialized Building Systems Construction in Malaysia. *Journal of Architectural Engineering*, March 2002. Page 19-23.
- British Standards Institution (1992). *BS EN 1992-1. Design concrete structures*. London: British Standards Institution.
- British Standards Institution (1998). *BS 5950 Part 5. Structural use of steelwork in building - Code of practice for design of cold formed thin gauge sections*. London: British Standards Institution.
- British Standards Institution (1986). *BS 8004. Code of practice for foundations*. London: British Standards Institution.
- British Standards Institution (2002). *BS EN 1990. Eurocode - Basis of structural design*. London: British Standards Institution.
- British Standards Institution (2001). *BS EN 10002 Part 1. Metallic materials - Tensile testing - Method of test at ambient temperature*. London: British Standards Institution.

- British Standards Institution (2000). *BS EN 12350 Part 1. Testing fresh concrete - Sampling*. London: British Standards Institution.
- British Standards Institution (2000). *BS EN 12350 Part 2. Testing fresh concrete - Slump test*. London: British Standards Institution.
- British Standards Institution (2000). *BS EN 12390 Part 1. Testing hardened concrete - Shape, dimensions and other requirements for specimens and moulds*. London: British Standards Institution.
- British Standards Institution (2000). *BS EN 12390 Part 2. Testing hardened concrete - Making and curing specimens for strength tests*. London: British Standards Institution.
- British Standards Institution (2000). *BS EN 12390 Part 3. Testing hardened concrete – Compressive strength of test specimens*. London: British Standards Institution.
- British Standards Institution (2007). *BS EN 14991. Precast concrete products - Foundation elements*. London: British Standards Institution.
- Chai, J. (2003). Shallow Foundation. In Chen, W.F. and Lian, D. (Eds.). *Bridge engineering handbook*. (Chapter 31.1-31.8). Boca Raton: CRC Press LLC.
- Construction Industry Development Board Malaysia (2003). *Industrialised building systems (IBS) Road Map 2003-2010*.
- Das, B. M. (1999). *Shallow foundations: Bearing capacity and settlement*. Boca Raton: CRC Press LLC.
- De Andrade, S.A.L., da S. Vellasco, P.C.G., Mergulhao, A.J.R. (2002). Structural assessment of cold-formed composite structures. *Steel and Composite Structures*, Vol. 2 No. 5. Page 397-410.
- Hanna, A.S. (1999). *Concrete Formwork Systems*. New York: Marcel Dekker, Inc.
- Haron, N.A., Hassim, S., Abd. Kadir, M.R., and Jaafar, M.S. (2005), Building cost comparison between conventional and formwork system. *Jurnal Teknologi*. Volume 43(B). Universiti Teknologi Malaysia. Page 1-11.
- Helena, H.J. and Knight G.M.S. (2005). Behaviour of cold-formed steel hollow and concrete-filled members. *Steel and Composite Structures*, Vol. 5 No. 1. Page 35-47.
- Hossain, K.M.A (2005) Designing thin-walled composite-filled beams. *Structures & Buildings*. Volume 158 Issue SB4 August 2005. Proceedings of the Institution of Civil Engineers. Page 267-278

- Mosley, W.H., Bungey, J.H., and Hulse, R. (1999). *Reinforced concrete design*. (5th ed.) Bristol: Palgrave.
- Nethercot, D.A. (2003). *Fundamentals*. In Nethercot, D.A. (Ed). *Composite construction*. (1.1-1.11). London: Spon Press.
- Oehlers, D.J. (1993). Composite Profiled Beams. *Journal of Structural Engineering*. Vol 119 No 4. Page 1085-1100
- Oehlers, D.J., Wright, H.D., and Burnet, M.J. (1994). Flexural strength of profiled beams. *Journal of Structural Engineering*. Vol 120 No 2. Page 378-393
- Prabhavathy, R.A. and Knight G.M.S. (2006). Behaviour of cold-formed steel concrete infilled RHS connections and frames. *Steel and Composite Structures*. Vol. 6, No. 1. Page 71-85
- Uy, B. and Bradford, M.A. (1994). Inelastic local buckling behaviour of thin steel plates in profiled composite beams. *Journal of Structural Engineering*. Vol. 72 No 16. Page 259-267
- Uy, B. and Bradford, M.A. (1996). Local buckling of thin steel plates in composite construction: experimental and theoretical study. *Proc. Instn Civ Engrs Structs & Bldgs*. Vol 110. Page 426-440.
- Wong, Kah Leong and Mahmood, Md Tahir and Mohd Yassin, Airil Yasreen and Shek , Poi Ngian and Tan , Cher Siang (2008) *Analytical study on pad footing foundation design using cold-formed steel lipped channel section*. In: International Graduate on Engineering and Science (IGCES'08), 23-24 December, 2008, Universiti Teknologi Malaysia, Skudai, Johor.
- Wright, H.D. (1993). Buckling of plates in contact with a rigid medium. *Journal of Structural Engineering*. Vol 71 No 12, Page 209-215
- Wright, H.D. (1995). Local stability of filled and encased steel sections. *Journal of Structural Engineering*. Vol 121 No 10, Page 1382-1388
- Wright, H.D. (2004). *Composite beams*. In Nethercot, D.A. (Ed). *Composite construction*. (2.1-2.10). London: Spon Press.