

HEAT LOAD CALCULATION AND ANALYSIS FOR COMMERCIAL  
BUILDING AIR CONDITIONING SYSTEM

TAN FOO CHUAN

A project report submitted in partial fulfilment of the  
requirements for the award of the degree of  
Masters of Science (Mechanical Engineering)

Faculty of Mechanical Engineering  
Universiti Teknologi Malaysia

JULY 2017

*Parents who raised me up*  
*Brothers and sister who were raised with me*  
*Friends who shared the shoulders with me*  
*Humanity*

## ACKNOWLEDGEMENT

I would first like to thank my thesis advisor Prof. Dr. Mazlan Abdul Wahid of the Faculty of Mechanical Engineering at University Teknologi Malaysia. The door to Prof. Dr. Mazlan office was always open whenever I ran into a trouble spot or had a question about my research or writing. He consistently allowed this paper to be my own work, but steered me in the right the direction whenever he thought I needed it.

I would also like to thank the experts who were involved in the validation survey for this research project: Ir.Yuen Cheng Piou and Ar.Lim See Heing. Without their passionate participation and input into the air conditioning system and building envelope design and specification, the validation survey could not have been successfully conducted.

My Hourly Analysis Program (HAP) advisor Mr.Douglas Wong of the Design and Sale Manager at Carrier Malaysia Sdn Bhd and Second reader Ir.Ng Yong Kong the Deputy Green Building Index (GBI) Facilitator Course of this thesis should also be recognized, and I am gratefully indebted to their very valuable comments on this thesis.

Finally, I must express my very profound gratitude to my parents and to my best friend for providing me with unfailing support and continuous encouragement throughout my years of study and through the process of researching and writing this thesis. This accomplishment would not have been possible without them. Thank you.

## ABSTRACT

Air conditioning system consume more than 50% of total commercial building energy consumption such as hotel, office, shopping mall and hospital in Malaysia. Solar heat through fenestration particularly on vertical surfaces play as major role in determining the thermal performance of a building. Maximum solar heat gain factors (SHGFs) has been used to estimate the peak heat load. This project describes the procedure of peak heat load calculation by using overall thermal transfer value (OTTV) and hourly analysis program (HAP) to obtain the heat load profile. A 33 story hotel building layout and envelope is being used and further optimization on the building envelope configuration has been done to observe the result. This research have showed how building envelop configuration affect the building cooling load requirement and apply in decision making base on the return of investment (ROI). The hourly analysis program result have showed that hotel air conditioning system operated at 80% or higher cooling capacity (Peak load) only during 1pm to 3pm and most of the time plant room is operate at Part Load condition. Plant room energy consumption and return of investment (ROI) analysis help in decision making on the particular building envelope configuration. The result showed that ROI period increase with the quantity of double glazed with low-E glass applied in hotel envelope and it is more cost effective if this type of glass is being apply at non shaded external surface. This study also carry out ROI evaluation and comparison for the plant room that with and without variable speed drive (VSD), the result showed that VSD plant room only take around 2 years to get the return of the initial investment cost.

## ABSTRAK

Di Malaysia, kegunaan tenaga sistem penghawa dingin bangunan komersial seperti hotel, pejabat, pusat membeli-belah dan hospital adalah lebih daripada 50% tenaga daripada jumlah kegunaan tenaga seluruh bangunan. Haba solar yang melalui perbukakan cermin tingkap terutamanya permukaan menegak memainkan peranan yang penting untuk menentukan prestasi haba sebuah bangunan. Faktor maksimum peruntukan haba solar telah diguna untuk menganggarkan kuasa haba maksimum yang diperolehi oleh bangunan. Projek ini menerangkan prosedur penganggaran peruntukan kuasa haba maksimum sebuah bangunan dengan cara megunakan nilai keseluruhan pemindahan haba (OTTV) dan jugak megunakan program simulasi yang mengira peruntukan haba setiap jam (HAP) untuk mendapatkan profil peruntukan haba bangunan. Pelan sebuah bangunan hotel sedia ada dan sampul bangunan telah di gunakan dan pengoptimuman terhadap konfigurasi sampul bangunan dijalankan untuk memerhati pengubahan peruntukan kuasa haba bangunan tersebut. Kajian ini menunjukkan bagaimana konfigurasi sampul bangunan menjejaskan kuasa penyejukan yang diperlukan dan jugak keputusan yang dibuat berdasarkan pulangan pelaburan. Program simulasi yang mengira peruntukan haba setiap jam (HAP) telah menunjukkan bahawa sistem penyaman udara hotel tersebut hanya beada di 80% atau lebih daripada kapasiti penyejukannya pada jam 1pm hingga 3pm sahaja dan kebanyakan masa bangunan hanya ada pada keadaan separa daripada kapasiti penyejukannya. Analisis penggunaan tenaga bilik penyejuk dan pulangan pelaburan bantu membuat keputusan terhadap konfigurasi sampul bangunan. Keputusan menunjukkan tempoh pulangan pelaburan menigkat dengan kegunaan kuantiti kaca double glazed dengan low-E di sampul hotel dan ia lebih kos efektif jika digunakan di permukaan dinding yang tidak berlorek. Kajian ini jugak menjalankan penilaian dan penerangan tempoh pulangan pelaburan bagi bilik penyejuk dengan dan tanpa variable speed drive (VSD), keputusan menunjukkan bilik penyejuk dengan VSD hanya ambil hampir 2 tahun untuk mendapatkan balik kos pelaburan permulaan.

## TABLE OF CONTENTS

<b>CHAPTER</b>	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENTS</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF TABLES</b>	x
	<b>LIST OF FIGURES</b>	xii
	<b>LIST OF ABBREVIATION</b>	xv
	<b>LIST OF SYMBOL</b>	xvi
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Project Background	1
	1.2 Problem Statement	3
	1.3 Objectives	3
	1.4 Chapter Organisation	4
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>5</b>
	2.1 Heat Transfer Mechanism	5
	2.1.1 Conduction	5
	2.1.2 Convection	6
	2.1.3 Radiation	7
	2.2 Heat Load Components in Building Heat Load Calculation	7

2.2.1	Internal Load	8
2.2.2	External Load	8
2.3	Basic Concept of Overall Thermal Transfer Value (OTTV) and Hourly Analysis Program (HAP)	9
2.3.1	Overall Thermal Transfer Value (OTTV)	9
2.3.2	Hourly Analysis Program (HAP)	10
2.4	Commercial Building Air Conditioning System	11
2.4.1	Variable Refrigerant Flow (VRF/VRV) System	11
2.4.2	Chilled Water System	12
2.4.3	Air Distribution System	13
2.4.4	Applied of Variable Speed Drive (VSD) in Air Conditioning System	15
2.4.5	Air Cooled Split Unit	16
2.4.6	Comparison for Chilled water, VRF and ACSU system	17
2.5	Building Envelope Configuration and Design	19
<b>3</b>	<b>METHODOLOGY</b>	<b>23</b>
3.1	Introduction	23
3.2	Concept Applied and Procedure in OTTV Calculation	23
3.3	Procedure of OTTV Calculation Base on Building Envelop Analysis	25
3.4	Heat Load Calculation Using Hourly Analysis Program (HAP)	33
3.5	Changing of Building Envelope Specification	41

<b>4</b>	<b>RESULTS AND DISCUSSION</b>	<b>43</b>
4.1	OTTV Result and Discussion	43
4.2	HAP Result and Discussion	45
4.3	Plant Room Power Consumption	52
4.4	Discussion on Return of Investment for VSD Plant Room Proposer	53
4.5	Discussion on Return of Investment for Various Type of Building Envelop Proposer	54
<b>5</b>	<b>CONCLUSION</b>	<b>58</b>
5.1	Conclusion	58
	<b>REFERENCES</b>	<b>60</b>
	<b>APPENDICES</b>	



## LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	OTTV and RTTV in Thailand Building Code	10
2.2	Comparison of Part Load Efficiency for VSD and NON-VSD Water Cooled Chiller	16
2.3	Cooling Energy Reduction by Applying Five Improved Envelop Design Measure Compare With Baseline Building	20
2.4	Comparison of Solar Absorptivity ( $\alpha$ ) for Various Type of Finishing Surface and Colour	21
2.5	Comparison of U-Value $U_w$ for Various Type of Walls Construction Method	21
2.6	Comparison of U-Value of Windows ( $U_f$ ) and Shading Coefficient (SC) for Various Type of Glass	22
3.1	Summary of Wall Information and Specification for Hotel Room South-West Wall-1-a in Table Format	29
3.2	Summary of Wall Type for Hotel Room from South-West View	29
3.3	Summary of Typical Wall Type for Hotel Room from North-East View	30
3.4	Summary of Total Quantity and Wall Type for Hotel Floor (Level 10~29)	30
3.5	Calculation of Heat Conducted Through Wall	31
3.6	Calculation of Heat Conducted Through Window	32
3.7	Calculation of Solar Heat Gain though Wall	32
3.8	Change of Building Envelop Configuration	42

4.1	Summary of OTTV Result for All Configurations	44
4.2	HAP Air System Sizing Summary for Level-1 Lift Lobby	45
4.3	HAP Hourly Zone Load for Level-1 Lift Lobby	46
4.4	HAP Plant Sizing Summary for Configuration-2	49
4.5	HAP Plant Load Profile on July and August for Configuration-2	50
4.6	Comparison of Total Space Peak Load with Plant Peak Load for Configuration 1 to 6	52
4.7	Efficiency for Plant Room Equipment With and Without VSD	52
4.8	Calculation of Yearly Plant Room Power Consumption with and without VSD for Configuration-1 (OTTV=111)	53
4.9	Calculation of VSD Plant Room Energy Cost Saving for 6 Types of Building Envelop Configuration	54
4.10	Calculation of VSD Plant Room Return of Investment (ROI) for 6 Types of Building Envelop Configuration	54
4.11	Calculation of additional cost for of Building Envelop Configuration 1, 2 and 3	55
4.12	Calculation of additional cost for of Building Envelop Configuration 4, 5 and 6	56
4.13	Calculation of Return of Investment (ROI) for 6 Types of Building Envelop Configuration	57

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Heat Transfer in Conduction Mode	6
2.2	Heat Transfer in Convection Mode	6
2.3	Heat Transfer in Radiation Mode	7
2.4	Typical VRF System Schematic Diagram	12
2.5	Typical Chilled Water System Schematic Diagram	13
2.6	Typical Variable Air volume Box (VAV Box) Control Schematic Diagram	14
2.7	Typical Ducting Layout for Air Distribution System With Variable Air volume Box (VAV Box)	14
2.8	Typical Outlook of Wall Mounted Type Air Cooled Split Unit	17
3.1	Top View of The Entire Building Project Development (“The Shore”)	25
3.2	Hotel North-West Elevation (External wall)	26
3.3	Hotel North-East Elevation (External wall)	27
3.4	Typical Floor Plan for Hotel Room Level 10 and 11	28
3.5	Section View B-B Show in The Figure 3.4 for Hotel Room	28
3.6	Create Wall Properties for Reinforce Concreate Wall With White Surface	34
3.7	Create Wall Properties for Brick Wall With ACP Cladding	34

3.8	Create Wall Properties for Brick Wall With Insulated ACP Cladding	34
3.9	Create Window Properties for Double Glazed Clear With Low-E and Air Gap Window	35
3.10	Create Window Properties for Using Single Glazed With Dark Grey Tinted Glass Window	35
3.11	Define Shading Geometry Properties for Hotel Room	36
3.12	Create Roof Properties for Insulated Steel Deck Roof	36
3.13	Create Roof Properties for Reinforce Concrete Roof	36
3.14	Create People Density Profile for Banquet Hall and Sky Bar	37
3.15	Create Lighting and Machines Load Profile for Office Area and Hotel Room	37
3.16	Define Space General Information for Sky Bar	38
3.17	Define Space Internal Load Information for Sky Bar	38
3.18	Define Space External Wall, Window and Door Information for Sky Bar	39
3.19	Define Space Roof for Sky Bar	39
3.20	Define Space Floor Properties for Sky Bar	40
3.21	Define Space Partition Properties for Sky Bar	41
4.1	The Plot of HAP Hourly Zone Load Profile for Level-1 Lift Lobby	46
4.2	The Plot of HAP Hourly Zone Load Profile for Level-3A Banquet Hall	47
4.3	The Plot of HAP Hourly Zone Load Profile for Level-3A Coffee House	48
4.4	The Plot of HAP Hourly Zone Load Profile for Level-4 Office Area	48

4.5	The Plot of HAP Plant Load Profile on July and August for Configuration-2	51
-----	---	----

## LIST OF ABBREVIATION

OTTV	-	Overall Thermal Transfer Value
TD	-	Difference Between Interior and Exterior (K)
$TD_{eq}$	-	Equivalent Temperature Difference (K)
WWR	-	Window-to-Wall Ratio
SF	-	Solar Factor of Fenestration
SC	-	Shading Coefficient of Fenestration (Dimensionless)
$U_w$	-	U-Value of Opaque Wall (W/m <sup>2</sup> .K)
$U_f$	-	U-Value of Fenestration (W/m <sup>2</sup> .K)
COP	-	Coefficient of Performance
RPM	-	Revolution Per Minuets
$FAN_{EFF}$	-	Fan efficiency
$PUMP_{EFF}$	-	Pump efficiency
SHGFs-	-	Solar Heat Gain Factors
ROI	-	Return of Investment
HAP	-	Hourly Analysis Program
AHU	-	Air Handling Unit
FCU	-	Fan Coil Unit
VAV	-	Variable Air Volume
DX	-	Direct Expansion
ACMV	-	Air Conditioning and Mechanical Ventilation
PID	-	Proportional–Integral–Derivative
BAS	-	Building Automated System
RT	-	Refrigerant Tonnage (12,000 btu)

## LIST OF SYMBOLS

$Q$	-	Heat flow rate
$k$	-	Thermal conductivity of the material
$A$	-	Cross-sectional area
$dT/dx$	-	Temperature gradient
$h$	-	Coefficient of convection
$T_{\infty}$	-	Outside temperature
$T_s$	-	Surface temperature
$T$	-	Absolute temperature of surface
$\sigma$	-	Stefan-Boltzmann constant
$\alpha$	-	Solar absorption(dimensionless)
$\dot{V}$	-	Flow rate in CFM (for fan) and usgpm (for pump)
$\omega$	-	Angular speed (in RPM)
$P$	-	Pressure for fan (inch of water gauge) or pump head for pump ( in feet of water)
$R$	-	Thermal resistance ( $K/W$ )

## CHAPTER 1

### INTRODUCTION

#### 1.1 Project Background

Over the past decade, construction industries at tropical countries have given much more attention on energy saving concepts. To ensure energy savings, the main key is to reduce air conditioner capacity in a building. This is achievable with a proper heat load calculation to be carried out to ensure energy saving without sacrificing the comfort level of the air conditioning system. In a tropical country, solar heat gain by the building through vertical and horizontal wall created much more impact than internal load such as heat rejected by human body, machine, equipment and lighting. The overall thermal transfer value (OTTV) on building envelopes has become the base reference that determine the building envelopes thermal performance. Xiaoxia Sang [1] has examined energy-efficient building envelop design decision making in Hong Kong and found out that there is a large potential of reducing building cooling energy during building envelop material selection and design.

In 2005, Lam et al. published a paper in which they described that building cooling load can be expresses in term of simple two-parameter linear regression equation involving OTTV and with the further long term data collection such as ambient temperature, global solar radiation on vertical and horizontal surface, a simulation technique can be carry out to obtain not only the maximum load but also the load profile of the building [2].



In Malaysia standard (MS: 1525), OTTV calculation is using the fix maximum solar heat gain factor that apply into OTTV calculation for standardize purpose so that OTTV value obtain is indicate the maximum amount of heat gain through the building envelop. In fact, OTTV value is varied time to time and the maximum heat gain through different walls orientation will not happen at the same time. ChutinanSinghpoo et al [3] conducted a study to predict value of overall thermal transfer value (OTTV) of building at different time in one day. A case study of sixth floor of Pienvichitr Building KhonKaen University, Thailand; the result show that OTTV varied time to time on the maximum happen at 02.00 pm. If the single value of OTTV obtained from MS: 1525 has been applied to estimate the building load, it may cause overdesign on total capacity in the air conditioning system.

On the other hand, Li and Lam [4] have carried out the research to develop a simple approach for estimation of solar heat gain where the maximum solar heat gain and average solar heat gain for OTTV are computed and compared. The research shows that surface which facing different directions have different maximum and average solar heat gain. This is meant that OTTV of the building is overestimated if by using a single value of solar heat gain.

Heat load calculations need consideration on the entire external and internal load. The load will change hourly due to variation of external temperature, solar heat gain, internal load and etc. The equation can be inserted in a programme such as M.S.Excel. However, the processes are tedious which involved many weather and internal load data that need to be inserted into the calculation. Hourly analysis programme (HAP) has been used for heat load calculation in the air conditioning system because will help to speed up the process. The build-in feature in HAP allows the user to obtain the entire building heat load and its profile in various type of buildings and applications.

## 1.2 Problem Statement

There are a lot of commercial building in Malaysia do not carry out a proper building heat load calculation. Most of the air conditioning system design capacity is only base on rules of thumbs (watt of cooling power require per unit area). Without a proper heat load calculation to determine the building envelope thermal performance and heat load profile, designer do not have enough information for decision making during the building design stage as a result mechanical and electrical consultant overdesign on the building system. Moreover, architect do not allocated enough design effort on the building envelop thermal performance. As a result, the construction and operation cost increase. Overall thermal transfer value (OTTV) calculation need to be done during building envelope design and materials selection. Such information need to be considered while designing the air conditioning system. In order to obtained heat load profile, energy consumption and cost analysis has to be carried out properly to achieved final decision.

## 1.3 Objective

The objectives of this study are as follows:

1. To obtain overall thermal transfer value (OTTV) for a commercial building with various sets of building envelop configuration and design.
2. To obtain building heat load profile and peak load of building space and plant room for a commercial building with various sets of building envelop configuration using hourly analysis programme (HAP).
3. To calculate and compare the energy consumption and return of investment (ROI) for various sets of building envelop configuration and air conditioning system. Heat load profile obtained from HAP is applied. ROI obtained will help to select most suitable building envelop configuration and air conditioning system design.

## **1.4 Chapter Organisation**

This thesis is divided into 5 chapters. Chapter 1 introduce the background and objectives of the study. Chapter 2 is about the literature review on the previous research which related to the project in various areas. This will help to give a better understanding about project contents before dealing with the calculation and simulation. Chapter 3 describes the methodology needed for the project which include; how to extract the information from the floor plan and others specification. Format of OTTV calculation and summary of data need to define in to the hourly analysis programme. Chapter 4 gives the results and discussion of the OTTV, heat load profile. There are also discussion on difference building envelop configuration and air conditioning design that suitable base on the energy consumption and Return of Investment (ROI) obtained. Last but not least, Chapter 5 is the overall conclusion of the project. Furthermore, there are recommendations of future works is given as well.

## REFERENCES

1. Sang, X., Pan, W., & Kumaraswamy, M. M. (2014). Informing Energy-efficient Building Envelope Design Decisions for Hong Kong. *Energy Procedia*, 62, 123-131.
2. Li, D. H., & Lam, J. C. (2000). Solar heat gain factors and the implications to building designs in subtropical regions. *Energy and Buildings*, 32(1), 47-55.
3. Singhpoo, C., Punnuchaoenwong, N., & Benjapiyaporn, C. (2015). Study of the Effect of Temperature Differences on the Overall Thermal Transfer Value of buildings. *Energy Procedia*, 79, 348-353.
4. Lam, J. C., Tsang, C. L., Li, D. H., & Cheung, S. O. (2005). Residential building envelope heat gain and cooling energy requirements. *Energy*, 30(7), 933-951
5. Hui, S. C. M., 1997. Overall thermal transfer value (OTTV): how to improve its control in Hong Kong, *In Proc. of the One-day Symposium on Building, Energy and Environment, 16 October 1997, Shangrila Hotel, Kowloon, Hong Kong, HKIE BS Division/CIBSE/ASHRAE/PolyU, pp. 12-1 to 12-11.*
6. Rattanongphisat, W., & Rordprapat, W. (2014). Strategy for Energy Efficient Buildings in Tropical Climate. *Energy Procedia*, 52, 10-17.
7. Malaysia Standard MS 1525:2007, Code Of Practice On Energy Efficiency And Use Of Renewable Energy For Non-Residential Buildings (First Revision).
8. Malaysia Green Building Confederation. (2015). Green Building Index Facilitator Course Book I.
9. Food and Agriculture Organization of the United Nations, [www.fao.org](http://www.fao.org)

10. Mitsubishi Heavy Industries VRF Inverter Multi-System Air Conditioners Catalogue
11. CARRIER MALAYSIA SDN BHD-Chiller technical data sheet