

A STRUCTURAL MODEL FOR COST EFFECTIVE BUILDING MAINTENANCE  
THROUGH DESIGN FOR MAINTAINABILITY

SHUBASHINI A/P GANISEN

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Doctor of Philosophy (Facilities Management)

Faculty of Geoinformation and Real Estate  
Universiti Teknologi Malaysia

JUNE 2016

## DEDICATION

“To My Beloved Appa and Amma  
Mr. Ganisen and Mrs. Shashikala Devi  
for your ever ending love and supports throughout my life.”

“To My Dearest Husband Nantha Kumar  
for your unconditional love, encouragements and supports.”

“Not forgotten my three siblings  
Jayshini, Thulashini and Mitrashini.”  
“Hopefully my hard work for the past 4 years will be  
your inspiration to work even harder.”

“To My Juniors Rinitah & Prabha,  
“My Friends Vaani and Gunavathy  
for your help and supports”

“And my Almighty  
Nothing possible without Him”

“Couldn’t complete this research without all of you”  
...Thank you for always being there for me....

## ACKNOWLEDGEMENT

First of all, my deep appreciation and gratitude dedicate to The Department of Property Management, Faculty of Geoinformation and Real Estate, Universiti Teknologi Malaysia for giving me this opportunity to experience preparing research project. A special thanks to all my lecturers who help me to go through my four years studies of PhD in Facilities Management. I extend my deepest appreciation for your knowledge, advices and support to help me complete my studies successfully.

I owe an immense debt of gratitude to my supervisors, Prof. Sr. Dr. Hakim Bin Mohammed, Dr. Izran Sarrazin and my former main supervisor Dr. Lenin Jawahar Nesan (currently external supervisor). Their sound advice, fruitful discussions and careful guidance were invaluable during the preparation of this research and gave me the motivation to perform to my maximum ability.

I would also like to thank those practitioners and experts who agreed to fill the questionnaires survey form, without your time and cooperation; this research would not have been possible. Lastly, I would like to thank my fellow friends for always supporting each other to go through all the obstacles to finish this research.

## **ABSTRACT**

Building maintainability is renowned in the lack of integration with building design. This has been seen as one of the major factors contributing to various problems facing the building industry, precisely the increasing building maintenance costs. Initial study and critical reviews on literatures reveals that there is a need to identify a comprehensive building design for maintainability criteria and indicators to reduce the overwhelming cost of building maintenance through mitigation of defects. To address the above issues, this research was carried to establish an exhaustive building design for maintainability criteria and indicators to achieve cost effective building maintenance. Total of nine design for maintainability criteria, thirty-eight indicators and eighteen cost effective building maintenance indicators were identified and validated in two phases of survey and analysis. In the first phase, Delphi survey was conducted and in the second phase Structural Equation Modeling (SEM) technique was used to validate, develop and determine the structural model of building design for maintainability for cost effective building maintenance. This research aims to address the long pending quest of incorporating maintainability during the building design phase and form as basis to promote facility management practices in the building design phase. The results of this research firmly established the structural relationship model among building design maintainability criteria and indicators to achieve cost effective building maintenance. The structural model developed through this research can greatly benefits and being a useful reference in the construction industry particularly for the architects and designers to incorporate maintainability during the building design phase to achieve cost effective building maintenance.

## ABSTRAK

Keboleh penyelenggaraan bangunan terkenal dengan kekurangan integrasi reka bentuk bangunan. Ini dilihat sebagai salah satu faktor utama yang menyumbang kepada pelbagai masalah yang dihadapi oleh industri bangunan atau lebih tepat lagi, kos penyelenggaraan bangunan semakin meningkat. Kajian awal dan kajian kritikal literatur menunjukkan bahawa terdapat keperluan untuk mengenal reka bentuk lengkap bagi kriteria keboleh penyelenggaraan bangunan dan petunjuk-petunjuk untuk mengurangkan kos yang kian meningkat. Bagi menangani isu-isu di atas, kajian ini telah dijalankan untuk mewujudkan kriteria reka bentuk bangunan bagi keboleh penyelenggaraan yang menyeluruh dan petunjuknya untuk mencapai kos penyelenggaraan bangunan yang efektif. Sembilan petunjuk-petunjuk reka bentuk bagi kriteria keboleh penyelenggaraan bangunan, tiga puluh lapan petunjuknya serta lapan belas petunjuk kos pembinaan berkesan telah dikenal pasti dan diuji dalam dua fasa kajian dan analisis. Dalam fasa pertama kaji selidik Delphi telah digunakan dan dalam fasa kedua, analisis permodelan persamaan berstruktur (SEM) telah digunakan untuk mengesah, membangun dan menentukan model berstruktur keboleh penyelenggaraan bangunan bagi kos penyelenggaraan bangunan yang efektif. Kajian ini bertujuan untuk mengemukakan persoalan yang telah kian lama tertangguh dalam menggabungkan keboleh penyelenggaraan semasa fasa reka bentuk bangunan dan membentuk asas bagi menggalakkan amalan pengurusan fasiliti pada peringkat reka bentuk bangunan. Hasil kajian ini dengan jelas membentuk model hubungan struktur diantara kriteria keboleh penyelenggaraan bangunan dan petunjuk-petunjuk bagi mencapai kos penyelenggaraan yang efektif. Model struktur yang dibangunkan dari hasil kajian ini boleh memberi manfaat yang besar dan menjadi rujukan yang berguna dalam industri pembinaan terutamanya kepada arkitek dan pereka bentuk bangunan untuk memasukkan unsur keboleh penyelenggaraan pada fasa reka bentuk bangunan untuk mencapai kos penyelenggaraan bangunan yang efektif.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xv
	LIST OF FIGURES	xix
	LIST OF ABBREVIATIONS	xx
	LIST OF APPENDICES	xxii
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Introduction	1
	1.2 Research Background	3
	1.3 Problem Statement	7
	1.4 Research Questions	16
	1.5 Research Objectives	17
	1.6 Scope of the Research	17
	1.7 Significance of the Research	19
	1.8 Research Methodology	21
	1.9 Structure of the Thesis	24

<b>2</b>	<b>INTEGRATED MAINTENANCE IN BUILDING DESIGN</b>	<b>25</b>
2.1	Introduction	25
2.2	Building Maintenance an Overview	27
2.3	Building Maintenance Practice in Malaysia	28
2.4	The Factors Causing Building Maintenance Problems or Defects	29
	2.4.1 Design Deficiencies	30
	2.4.2 Poor Construction Quality and Knowledge	31
	2.4.3 Inadequate Maintenance Planning and Practice	32
	2.4.4 Material Limitations	32
	2.4.5 External Factors	33
	2.4.6 Communication Gap	34
2.5	The Effect of Design Deficiency on Building Maintenance	35
	2.5.1 Increasing Building Maintenance Cost	35
	2.5.2 Impact on Building Performance	36
	2.5.3 Increase in Social Consequences	37
	2.5.4 Increase in Environmental Consequences	37
2.6	Design Deficiency related Building Maintenance Defects or Problems	38
2.7	The Effect of Design Deficiency on Building Maintenance Cost	43
2.8	Building Maintenance Cost	45
2.9	The Role of Facility Management (Facility Manager) in Design	46
2.10	Incorporation of Building Maintenance during Building Design	51
2.11	Summary of Chapter	53

<b>3</b>	<b>BUILDING DESIGN FOR MAINTAINABILITY AND COST</b>	
	<b>EFFECTIVE MAINTENANCE</b>	<b>54</b>
3.1	Introduction	54
3.2	Maintainability in Building Research	55
3.3	The Definition of Building Maintainability	56
3.4	The Aim and Objective of Building Maintenance	58
3.5	Building Maintenance Practice in Malaysia	59
3.6	Building Design for Maintainability Practice	60
3.7	Cost Effective Building Maintenance	63
	3.7.1 Cost Effective Building Maintenance Indicators	63
	3.7.1.1 Direct Maintenance Cost	65
	3.7.1.2 Indirect Maintenance Cost	74
3.8	Building Design for Maintainability Criteria and Indicators to achieve Cost Effective Building Maintenance	83
	3.8.1 Accessibility	84
	3.8.2 Durability	88
	3.8.3 Cleanability	90
	3.8.4 Availability	92
	3.8.5 Standardization	94
	3.8.6 Simplicity and Flexibility	97
	3.8.7 Modularization	99
	3.8.8 Identification	102
	3.8.9 Sustainability	105
3.9	The Linkage between Building Design for Maintainability (BDM) and Cost Effective Building Maintenance (CEBM)	111
3.10	Building Design for Maintainability Criteria associated with particular Building Element	113
	3.10.1 Basement	114
	3.10.2 Façade	114
	3.10.3 Floor	115
	3.10.4 Roof	116
	3.10.5 Electrical System	117



		x
	3.10.6 HVAC System	118
	3.10.7 Lift	119
	3.10.8 Sanitary Plumbing	121
	3.10.9 Fire Protection	121
	3.11 Summary of Chapter	124
<b>4</b>	<b>RESEARCH METHODOLOGY</b>	<b>125</b>
	4.1 Introduction	125
	4.2 Research Paradigms	125
	4.3 Research Methodology	127
	4.4 Research Design	129
	4.5 Phase 1: The Identification of Building for Design Maintainability Criteria and Indicators to achieve Cost Effective Building Maintenance	129
	4.5.1 Step 1: Literature Review	130
	4.5.2 Step 2: Initial Study	131
	4.5.3 Step 3: Extensive Literature Review	134
	4.5.4 Validation of Content	136
	4.5.4.1 Overview of Delphi Study	138
	4.5.4.2 The Delphi Method Selection	139
	4.5.5 Step 4: Delphi Study Questionnaire Preparation	141
	4.5.6 Step 5: Delphi Study Selection of Expert Panel	144
	4.5.7 Step 6: Delphi Study Content Validation	147
	4.5.8 Step 7: Delphi Study Data Analysis	149
	4.5.8.1 Certain Level Agreement	151
	4.6 Phase 2: To Identify Structural Relationship among BDM Criteria and Indicators with Cost Effective Building Maintenance	152
	4.6.1 Step 8: Questionnaire Preparation	152
	4.6.2 Step 9: Reliability Test	153
	4.6.2.1 Selection of Respondents for Pilot Survey	153
	4.6.2.2 Pilot Survey	154
	4.6.2.3 Questionnaire Reliability Test	154

4.6.3	Step 10: Selection of Respondents for Main Survey	155
4.6.4	Step 11: Questionnaire Survey	159
4.6.4.1	Questionnaire Design	159
4.6.4.2	Self-administered Questionnaire	160
4.6.4.3	Questionnaire Distribution and Collection	161
4.6.5	Step 12: Data Analysis	162
4.6.5.1	Structural Equation Modeling (SEM)	162
4.6.5.2	Partial Least Square Approach	164
4.6.5.3	The Choice of PLS as A Method of Analysis	166
4.6.5.4	Measurement Model	167
4.6.5.5	Model Validation (Two Stage Structural Equation Modelling)	168
4.6.5.6	Stage One: Assessment of Measurement Model	170
4.6.5.7	Stage Two: Assessment Structural Model	174
4.7	Summary of Chapter	178
<b>5</b>	<b>DATA ANALYSIS PHASE I</b>	<b>179</b>
5.1	Introduction	179
5.2	Respondent Profile of Delphi Survey	179
5.3	Analysis Result of First and Second Objective: Delphi Study	181
5.3.1	Stage 1: Delphi Survey	181
5.3.1.1	1 <sup>st</sup> Round of 1 <sup>st</sup> Stage Delphi Survey	182
5.3.1.2	2 <sup>nd</sup> Round of 1 <sup>st</sup> Stage Delphi Survey	186
5.3.2	Stage 2: Delphi Survey	191
5.3.2.1	1 <sup>st</sup> Round of 2 <sup>nd</sup> Stage Delphi Survey	191
5.3.2.2	2 <sup>nd</sup> Round of 2 <sup>nd</sup> Stage Delphi Survey	194
5.4	Findings from Delphi Study	196
5.5	Summary of Chapter	198

<b>6</b>	<b>DATA ANALYSIS PHASE II</b>	<b>199</b>
	6.1 Introduction	199
	6.2 Survey Response Rate	199
	6.2.1 Demographic of the Respondents	201
	6.3 Preliminary Analysis	203
	6.3.1 Non-response Bias	203
	6.3.2 Kruskal Wallis Test	206
	6.3.3 Data Screening	208
	6.3.3.1 Missing Data	208
	6.3.3.2 Outliers	210
	6.3.3.3 Normality of the Data	211
	6.3.3.4 Common Method Variance	212
	6.4 Analyse Results and Findings for Objective 3: PLS-SEM Approach	214
	6.4.1 Research Model	214
	6.4.2 Stage One: Assessing the Measurement Model	217
	6.4.2.1 Indicator Reliability	218
	6.4.2.2 Convergent Validity	220
	6.4.2.3 Discriminant Validity	222
	6.4.3 Stage 2: Assessing the Structural Model	226
	6.4.3.1 Coefficient of Determination	227
	6.4.3.2 Path Coefficient	229
	6.4.3.3 Result of Relationship Testing	230
	6.4.3.4 Effect size ( $f^2$ value)	235
	6.4.3.5 Predictive relevance	236
	6.6 Summary of Chapter	239
<b>7</b>	<b>RESULTS AND DISCUSSION</b>	<b>240</b>
	7.1 Introduction	240
	7.2 Discussion of Findings	241
	7.2.1 Findings and Achievement of the First Objective of the Research	241
	7.2.2 Findings and Achievement of the Second Objective of the Research	242

7.2.3	Findings and Achievement of the Third Objective of the Research	246
7.2.3.1	Accessibility (Acc ---> CEBM)	251
7.2.3.2	Durability (Dur ---> CEBM)	251
7.2.3.3	Cleanability (Cle ---> CEBM)	252
7.2.3.4	Availability (Ava ---> CEBM)	253
7.2.3.5	Standardization (Sta ---> CEBM)	253
7.2.3.6	Simplicity (Sim ---> CEBM)	254
7.2.3.7	Modularization (Mod ---> CEBM)	255
7.2.3.8	Identification (Ide ---> CEBM)	255
7.2.3.9	Sustainability (Sus ---> CEBM)	256
7.3	Summary of Chapter	257
<b>8</b>	<b>CONCLUSION AND RECOMMENDATION</b>	<b>258</b>
8.1	Introduction	258
8.2	Overview of the Research	258
8.3	Contribution and Implication of the Research	260
8.3.1	Contribution to Knowledge	261
8.3.2	Practical Implications	262
8.4	Recommendation for Future Research	263
8.5	Limitation of the Research	264
8.6	Summary of Chapter	266
	<b>REFERENCES</b>	<b>267</b>
	Appendices A-D	295 - 335

## LIST OF TABLES

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
1.1	Significant of Integrating Building Maintainability	1
1.2	The Awareness of Malaysia Building Practitioners on Building Maintainability Knowledge	9
1.3	The BDM criteria identified by previous researches in different Maintainability Studies	11
1.4	A Review of Previous Studies on Building Design for Maintainability Issues	14
2.1	Building Defects identified by Previous Researches due to the Six Main Area of Design Deficiency	40
2.2	Factors attributed to the Gap between FM and Design	47
3.1	Difference between Civil & Architectural and Mechanical & Electrical Systems	62
3.2	Key indicators of Labour Cost to achieve CEBM	69
3.3	Key indicators of Material and Spare Parts Cost to achieve CEBM.	71
3.4	Key indicators of Equipment and tools Cost to achieve CEBM	74
3.5	Key indicators of Administration and management cost to achieve CEBM	76
3.6	Key indicators of Penalties and loss of revenue cost to achieve CEBM	79
3.7	Overall Cost Effective Building Maintenance (CEBM) Indicators	80
3.8	Key indicators of Accessibility Criteria	87

3.9	Key indicators of Durability Criteria	90
3.10	Key indicators of Cleanability Criteria	92
3.11	Key indicators of Availability Criteria	94
3.12	Key indicators of Standardization Criteria	97
3.13	Key indicators of Simplicity and Flexibility Criteria	99
3.14	Key indicators of Modularization Criteria	102
3.15	Key indicators of Identification or Diagnoseability Criteria	104
3.16	Key indicators of Sustainability Criteria	107
3.17	Building Design for Maintainability (BDM) Criteria and Indicators	109
3.18	Building elements with the associated design for Maintainability Criteria	123
4.1	The need for an extensive Literature Reviews	135
4.2	The Delphi Technique versus the Content validity survey	137
4.3	Sample Size based on Power Analysis	156
4.4	Total Population of Registered Professionals in the Board	157
4.5	Comparison of Variance based Partial Least Square (PLS) and Covariance based Structural Equation Modelling (CB- SEM)	165
5.1	The number of experts involved in each round of the Delphi Survey	180
5.2	Demographics of the Expert Panels	181
5.3	The Result of Section 2 of 1st Round Delphi Survey (CLA 67% Analysis)	182
5.4	The Result of Section 3 of First Round Delphi Survey (CLA 67% Analysis)	184
5.5	The Result of Section 2 of Second Round Delphi Survey (CLA 67% Analysis)	187
5.6	The Result of Section 3 of Second Round Delphi Survey (CLA 67% Analysis)	189
5.7	The Result of First Round Delphi Survey (CLA 67% Analysis)	192

5.8	The Result of Second Round Delphi Survey (CLA 67% Analysis)	194
5.9	Final CEBM Indicators (validated)	196
5.10	Final BDM Criteria and Indicators (validated)	197
6.1	Response rate by category of the method	200
6.2	Overall response rate	201
6.3	Demographics of the Respondents	202
6.4	Independent Sample T-test	204
6.5	Dependent Sample T-test	206
6.6	Kruskal Wallis non-parametric test result (Type of Specialisation)	207
6.7	Kruskal Wallis non-parametric test result (Data Collection Method)	207
6.8	Missing Data Statistics	209
6.9	Outliers Cases using Standardized Z Value	211
6.10	Variance Extracted by the Factor Solution	212
6.11	The Relationship of Exogenous with Endogenous Latent Variables	215
6.12	Assessing Reflective Measurement Model	217
6.13	The initial loadings and outer loadings of all the indicators of each construct from the measurement model	218
6.14	The Convergent Validity - The Standardized Item loadings, Composite Reliability (CR) and Average Variance Extracted (AVE) of the Measurement Model	220
6.15	The Correlation Matrix for the Constructs (Fornell and Larcker Criterion)	223
6.16	The Results of Cross Loadings	224
6.17	Assessing Structural Model	227
6.18	The Significance level ( $p$ -Value) with the $t$ -Value	229
6.19	The Results of Path Coefficient and Relationship Testing	230
6.20	The Effect Size ( $f^2$ ) of the Latent Variable	235

6.21	The $q^2$ Value of the Latent Variables	238
7.1	The Validated CEBM Indicators List	242
7.2	The Validated BDM Construct and Indicators List	243
7.3	The Final list of BDM Criteria associated with each of the Building Elements	245
7.4	The Result of Measurement Model	247
7.5	The Results of Relationship Testing	249



## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Research Methodology Diagram	23
2.1	Building Life Cycle Costing Profile	44
2.2	Building Whole Life Cycle cost and Life Cycle Cost Structure	46
2.3	Current Role of Facility Manager in Design	48
2.4	Proposed Role of Facility Manager in Design	49
2.5	Proposed design/construction maintenance feedback	50
3.1	Balance in Cost effectiveness and System Effectiveness	61
3.2	The Elements of a Building from Maintainability point of View	62
3.3	The Cost of Building Maintenance Task	65
3.4	Influence of Design for Maintainability on Maintenance Cost	83
3.5	Proposed Structural Model of Design for Maintainability Criteria and Cost Effective Building Maintenance	112
4.1	Research Methodology Diagram	128
4.2	Initial Study Diagram	133
6.1	The Research Model	216
6.2	The $R^2$ Value of Endogenous Latent Variables	228
6.3	The Results of Path Coefficient	234
6.4	Results for Redundancy Model	237
7.1	Results for Redundancy Model	250

## LIST OF ABBREVIATIONS

AVE	-	Average Variance Extracted
BCA	-	Building Construction Authority
BCA	-	Building Construction Authority
BDM	-	Building Design for Maintainability
BM	-	Building Maintenance
BMI	-	Building Maintenance Information
BRE	-	Building Research Establishment
BRE	-	Building Research Establishment
BS	-	British Standard
CB-SEM	-	Covariance based Structural Equation Modelling
CEBM	-	Cost Effective Building Maintenance
CFA	-	Confirmatory Factor Analysis
CIDM	-	The Construction Industry Development Board
CLA	-	Certain Level Agreement
CMV	-	Common Method Variances
CR	-	Composite Reliability
EFA	-	Exploratory Factor Analysis
FA	-	Factor Analysis
FM	-	Facility Management
FYMP	-	Five Year Malaysia Plan
HVAC	-	Heat, Ventilation and Air Condition
LAM	-	The Board of Architects Malaysia
LCC	-	Life Cycle Cost
LV	-	Latent Variables
MAFM	-	Malaysia Association of Facility Management

MPJBT	-	Majlis Perbandaran Johor Bahru Tengah	xxi
MRA	-	Multiple Regression Analysis	
MV	-	Manifest Variables	
NPP	-	National Physical Plan	
PA	-	Path Analysis	
PAM	-	Malaysian Institute of Architects	
PLS	-	Partial Least Square	
SEM	-	Structural Equation Modelling	
SPSS	-	Statistical Package for Social Science	
UTM	-	Universiti Teknologi Malaysia	
WBDG	-	Whole Building Design Guide	

**LIST OF APPENDICES**

<b>APPENDIX NO.</b>	<b>TITLE</b>	<b>PAGE</b>
A	Delphi Panels List	302
B	Survey Questionnaires of the Research	308
C	Cronbach's Alpha Reliability Test Results	333
D	The Results of Normality Test	338

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Introduction**

Facility management (FM) defined as “combines skills from design disciplines, such as architecture, engineering and interiors, from business fields like, management, marketing and real estate, and from behavioral sciences as an umbrella of professions”, that responsible for "coordinating all efforts related to planning, designing and managing buildings and their systems, equipment and furniture to enhance the organization's ability to compete successfully in a rapidly changing world" (Becker, 1990). Professional bodies such as; British Institute of Facilities Management (2012), International Facilities Management Association (2004) and The Facilities Management Association of Australia (2012), define FM as a profession that encompasses multiple disciplinary activities that integrating people, place and technology within the context of built environment. The scope of FM discipline covers a broader range of services such as, building/ ground management and maintenance, asset management, construction management, environmental management, catering, cleaning, security, IT management, postal, secretarial, health and safety and human resource. Therefore, FM often viewed as a field of operational process that lies beyond design, construction, installation and need to be in the delivery of the buildings.

Building maintenance considered huge activity in the context of emerging discipline of FM. Maintenance crucial for overall life cycle process (planning, design, construction, occupancy) of a building. However, maintenance and few other FM input such as sustainability, landscape and space are renowned in the lack of integration with building design. Based on the studies conducted by Mohammed and Hassanain (2010); Ramly (2006); Wilson (2002); Chanter and Swallow (1996), the inconsideration of maintainability during the building design has been seen as one of the major factors contributing to various problems facing the building industry. Among those problems are namely, building services related defects, early deterioration of building components, inadequate structural design (foundation), inadequate waterproofing and drainage, inadequate accessibility for repair, replacement and cleaning process, improper material selection and so on (Al-Shiha *et al.*, 1993; Al- Hammad *et al.*, 1997; Silva *et al.*, 2004; Ishak *et al.*, 2007; Das, 2010). These increasing numbers of design deficiencies can be reflected through the lofty maintenance costs (Silva and Ranasinghe, 2010; Ballast, 2010; Al- Hammad *et al.*, 1997), high rate of environmental and biological defects (Chew and Tan, 2003) as well as social consequences (Chew *et al.*, 2005 and 2004).

The integration of maintainability during the building design is of essence since able to pursue a balance among economic, social and functional, as well as environmental performance of a construction project. Various building scholars and literature have evidenced the significant of integrating maintainability during the building design, as shown in **Table 1.1**.

**Table 1.1:** Significant of integrating building maintainability

<b>Authors</b>	<b>Significant of integrating maintainability</b>
Blanchard <i>et al.</i> (1995)	Increases the life of infrastructure assets, reduces the costs & increases benefits of the final delivered project.
Dunston & Williamson (1999)	Reduced costs for the contractors and the facility owners.
Nayanthara <i>et al.</i> (2004)	Minimize building life-cycle cost (LCC) & increase efficient use of asset.
Chong and Low (2006)	Prevent nearly 66% of building defects.
Felten <i>et al.</i> (2009)	Save approximately 20% of the annual operating cost.

<b>Authors</b>	<b>Significant of integrating maintainability</b>
Das & Chew (2011)	Able to mitigate defects to balance decreasing maintenance budgets and increasing building standards.
Saghatforoush <i>et al.</i> (2012)	Making Project Life-cycle longer by eliminating the failures during the maintenance phase.
Wood (2012)	Able to maintain a building economically & effectively through its life.
Ismail and Mohammad (2014)	Building adaptable to future needs and maintain a stable usage cost throughout the building's design life.
Nicolella (2014)	Lead to minimization of difficult and costly operation to users.

## 1.2 Research Background

In recent years, the developed world increasingly facing the overwhelming total costs of operating and managing buildings due to huge maintenance workloads during the post occupancy phase (Wood, 2012; Das et al., 2010 and Building Maintenance Information (BMI), 2000). Studies indicate that American industry spends more or less \$200 billion each year on maintenance (Fogel and Petersen, 1997). Additionally, it is estimated that in the UK, up to 50% of the construction budget was spent for repair and maintenance works in buildings (Boussabaine and Kirkham, 2004). While BMI (Wood, 2005) reported in the last 10 years, building maintenance are increased about 66% and between 1989 and 2000, it's take about 43.6% increasing (El-Haram, Marenjak and Horner, 2002). A recent research in US, reported the increase of maintenance costs over the last ten years (1997-2007) is 3.3% for residential, non-residential and military facilities buildings (Whitestone Research, 2007). Meanwhile Hong Kong recorded an increase in the cost of maintenance work over the past 5 years. In Singapore, the average annual maintenance expenditure for residential buildings is claimed to be S\$37.99 per square meter, which is significant, when compared to the average turnover in construction (Building Construction Authority (BCA) Singapore, 2000). These numbers of studies are enough to demonstrate that, there is indeed high maintenance cost burdens facing by the building industry globally.

In the context of Malaysia, every year billions of ringgits were losing by the government due to the increasing building maintenance cost (Ali, 2009; Lateed, 2008). Malaysia is developed by the National Physical Plan (NPP), under which the Five Year Malaysia Plan (FYMP) is carried out. In this Malaysia Plan, focus will be given to the investigation on the preparation of annual budget for the maintenance of government-own building. In order to attain clearer picture on increasing maintenance cost of building in Malaysia, it is necessary to highlight the budget allocation for maintenance and repair works of public buildings. Under the 9th Malaysian Plan (2006 – 2010), the government has allocated the sum of US\$ 330m for upgrading, renovating, and maintaining various facilities as part of the development budget (Government of Malaysia, 2006; Mohd Sidek, 2007). Under the 6th (1990-1995), 7th (1996 -2000) and 8th Plans (2001-2005), allocation for maintenance and upgrading as a percentage of the development allocation was 0.2% under each of the Plans, while under the 9th Plan (2000-2010), the allocation increased substantially to 0.5%. This marked an increment of 150%.

In financial terms, the allocations increased from RM 101 million under the 6th Plan to RM 203.2 million under the 7th Plan. This is an expansion of about 100%. Further, there was some 6% expansion under the 8th Plan compared to that of the 7th Plan. However, under the 9th Plan, it further increased from the RM 214.5 million to RM 1,079 million, an expansion of some 403%. Additionally, in 2006, the Malaysian Government allocated about 1 trillion ringgits towards repairing and maintaining public building facilities (Government of Malaysia, 2006). Adding to this, in year 2005, 2007 and 2009 the Government allocates a special allocation of RM 2.5 billion, RM 1.0 billion and RM 615 million respectively for maintenance works (Mohd-Noor *et al.*, 2011). These allocations proves that the maintenance cost of public building in Malaysia is now clearly increasing and directed to ineffective building maintenance cost.



In addition, Eizzatul et al., (2012) highlighted in her research that buildings in Malaysia are suffering from ineffective building maintenance cost. Analysis by Lateef (2008) illustrates that the expenditure on maintenance in Malaysia is on the increase due to a huge backlog of building maintenance. He further stated that, buildings in Malaysia require effective maintenance; otherwise they will become liabilities. Also, it has been established that there is a gross inadequacy in the way of schools' buildings is managed (Zainal Abidin and Roslan, 2006). Even, Mohd Zulakhmar (2006) stressed that the procedures of maintaining buildings in Malaysia are not effective. As refer to numerous building maintenance related researchers namely; Sani et al. (2012); Mohd-Noor et al., (2011); Ali et al. (2009), (2010); Lateef, Khamidi and Idrus, (2010) and Zuhairuse et al., n.d.; asserted that, the ineffective building maintenance cost issues are known among the biggest obstacle facing by the building industry in Malaysia.

Consequent from the alarming building maintenance cost (Chew and Silva, 2004), the building maintenance and management issues has arisen in mounting significance. Hence, many countries are increasingly realized the importance of understanding, recognizing and assessing the overwhelming total costs of building maintenance (Arditi and Nawakorawit, 1999(a), (b) and Wood, 2009). Along with it, one of the more impending tasks which has been increasingly become a matter of growing importance in many countries is reducing the amount of significant building defects and thus minimize the rising cost of building maintenance. Building defects were defined as results of failures or shortcomings in the function, performance, statutory, or user requirements of the structure, fabric, services, or other facilities of buildings (Low and Wee, 2001). Defects arising in a building often exhibit a chain effect, hinder performance, increase maintenance workloads and contribute to increasing building maintenance cost (Josephson and Hammarlund 1999; Ilozor *et al.*, 2004).

To date many research had been conducted in the face of identifying the factors causing increasing building defects. As refers to researches, design limitations (Building Research Establishment, (BRE), 1983; Adejimi, 2005; Ishak *et al.*, 2007; Alhaji and

Hassain, 2010; Sivanathan *et al.*, 2012), poor construction quality and knowledge (Al-Hammad *et al.*, 1997; Dunston, 1999; Mills *et al.*, 2009), inadequate maintenance planning and practice (Bleanchor *et al.*, 1995; Horner *et al.*, 1997; Shabha, 2003), material limitations (Peacock, 1986; Olubodun, 1996; Chew *et al.*, 1999; 2000), as well as external factors such as climate; environment, soil condition, and chemical attack (Gambardella and Moroni, 1990; Honstede, 1990; Richardson, 1991) are among the factors causing inherent maintenance problems and induce high maintenance cost. However, vast amount of researches has highlighted that, increasing cost of building maintenance is highly attributed to design limitations. Design limitations known as the defects or problems causes due to faults in building design.

Survey of Assaf *et al.* (1996) on 11 major groups of defects through a literature review and interviews showed that building defects were mostly generated by design, specifications. The survey by Josephson and Hammarlund (1999), on seven buildings through observations and surveys showed that 32% of all defect costs originated from the client and design. Additionally, in Hong Kong Lam (2000) broadly stressed that, the causes of building maintenance problems and defects under design were accountable up to 40% of the overall cause. On the other hand, in Singapore, building defects due to poor design specifications led to 60% of the overall cause of building maintenance related problems (Chong and Low, 2006). Meanwhile in Malaysia, studies by Abdul Mohsen and Sadi (1997) and Nor Haniza *et al.* (2007) affirmed that building failures and defects in buildings are resulted due to design faults. In a research carried out by Mohammed Alhaji *et al.* (2010), they stated that most of maintenance problems existing in the facilities are not caused by construction failure but from building design failure. On the other hand, Sophia (2011) had carried out a pilot study to identify the causes of ineffective maintenance cost in Malaysia buildings. The results show that increasing building maintenance costs is attributed to the failure of building design. For an instance, The Majlis Perbandaran Johor Bahru Tengah (MPJBT) administration building's external walls were made from glass and needed to be maintained every 6 months. The maintenance costs for this work have reached about RM25,000 every six months. Another issue

identified by Sophia was in relation to the Taman Impian Emas public market, which has an aesthetic roof design. However, due to design faults, the roof of the market need undergo repair at the cost of RM300, 000. Further, Ramly et al. (2006) reviewed 4,389 records from 36 public housing areas in Kuala Lumpur, and found that 47% of the building defects were caused due to design faults.

Recognizing the increasing building maintenance cost due to inherent maintenance problems, building industry is moving forward on identifying the solution for this situation (Chew *et al.*, 2004 and Wood, 2009). It is apparent that, ineffective building maintenance cost has forced the industry to recognize the immediacy to rectify and to reduce such incidences and consequently reduce the increasing building maintenance cost.

### **1.3 Problem Statement**

Recognising the importance of achieving cost effective building maintenance (CEBM), it is vital to decrease the mounting numbers of building defects generated due to design faults. Design decision and substitution made during the initial phase of building construction have major impact on the overall performance of a building. Hence, maintenance workloads plus increasing maintenance cost can effectively resolve if building design takes into account the need for careful and methodical planning, monitoring and execution of future maintenance. For this statement, previous researchers; Silva, Ranasinghe, and De Silva, (2012); Wood (2012); Das and Chew (2011); Chew *et al.* (2010); Banaitiene (2008), have supported and stated that ‘the incorporation of building maintenance into the building design phase denotes ease of maintenance through mitigation of defects and consequently contribute to reduce maintenance cost and time. The integration of maintenance activities during the building design phase is a concept refers as ‘building design for maintainability’ (BDM).

Predominant amount of reports and studies signifies that, BDM is a significant issue to be considered during a building development process (Silva and Ranasinghe, 2010; Che-Ani *et al.*, 2009; Liu, 2006). Lack of BDM consideration, has been seen as one of the major factors contributing to various problems facing by the building industry (Wilson, 2002; Chanter and Swallow, 1996; Ramly, 2006). It is substantiate that, the consideration of BDM able to reduce the building defects decrease the increasing building maintenance cost and consequently achieve cost effectiveness. This statement is supported by a case study conducted by Chong and Low (2006), which found that design integrated maintenance able to prevent nearly 66% of building defects. In addition, investigation of Dunston and Williamson (1999) revealed evidence that, few projects in the building construction industry that have focused on the maintenance concerns during the design have typically realized reduced maintenance costs. Even Ismail and Mohammad (2014) highlighted that, incorporating maintainability consideration into building design lead to cost effectiveness throughout the building life. Further, Emirates Business (2009) declared, 10% of investment cost and 30% of operating cost can be saved if maintenance incorporated during the design phase. Thus, one prospective solution to address the issue of higher maintenance cost is to make certain the marriage of maintainability with the building design.

Unfortunately, architects and designers often overlook this most important factor, which has the potential to carry out future maintenance tasks easefully (Koo, 2000). As a result, building industries are still suffering with mounting numbers of maintenance problems and increasing maintenance cost. In Malaysia, maintainability has higher significance due to its tropical climate. This is because, in tropics building components need additional maintenance as alternate dry and wet seasons shorten the lifespan of materials to a great extent (Chew *et al.*, 2004). Further, Malaysia also needs to outwit the standard of building and its facilities in order to attract and retain global investors as well as increase and strengthen the economic profile of the country. Hence, the incorporation of BDM is considered as necessary for buildings in Malaysia. However, the integration of BDM seems to be lack in Malaysia

(Ramly, 2006; Razak and Jafar, 2012), although in the 2009 manual of asset management, the Government of Malaysia has published that, requirements such as maintenance, space, landscape and energy should be considered in the design stage.

The statement by Ramly (2006); Razak and Jafar (2012) is also supported by Rozita (2006). In her study, that involved 38 designer firms (architectural, civil and structural) and 30 maintenance firms in Malaysia, Rozita (2006) concluded that maintainability is rarely considered during the building design phase by architects in Malaysia. In the effort to validate the relevance of Rozita's findings after an 8 year gap the author of this research conducted a preliminary survey (refer section 4.5.2, Chapter 4) that involved architects, engineers (mechanical, electrical and civil) and facility managers/ maintenance managers to study the awareness on maintainability and its consideration during the design phase. The result of the survey reveals that building practitioners in Malaysia are still oblivious in considering BDM strategies. The summary of the preliminary survey is shown in Table 1.2.

**Table 1.2:** The Awareness of Malaysia Building Practitioners on Building Maintainability Knowledge.

Questions Asked	Architects		Engineers (Mechanical; Electrical; Civil)		Facility Managers/ Maintenance Managers	
	YES	NO	YES	NO	YES	NO
1) Awareness on Maintainability	80%	20%	85%	15%	30%	70%
2) Awareness on Building Design for Maintainability	70%	30%	60%	40%	30%	70%
3) Consideration of Maintainability during the design phase.	42%	58%	35%	65%	25%	75%

Source: Preliminary Study (2013)

The percentage figures shown in the Table 1.2 demonstrates the level of awareness of Malaysia's building practitioners on the knowledge of maintainability. The questions were divided into 4 main categories namely;

- i) Awareness of building practitioners on building maintainability
- ii) Building practitioners awareness on building design for maintainability.
- iii) Consideration of maintainability aspects during the design phase of a building by the building practitioners.
- iv) Reasons for considering and not considering BDM practice.

Category (i) included to identify whether the practitioners are aware on maintainability concept applied to a building and its facilities. Category (ii) is to identify the awareness of practitioners on the BDM concept. It is important to focus on BDM concept as the research focuses on maintainability considered during the design phase although maintainability can be implemented throughout the entire life-cycle of a project. Category (iii) is to identify the consideration of maintainability aspects during the building design phase by the building practitioners. This is to know whether the practitioners consider the maintainability characteristics during the project design phase. Category (iv) is to identify the reason behind considering or not considering BDM practice by the building practitioners. This is to know what would be the reason for considering and not considering the BDM practice. The result of pilot survey shows that a large majority of the practitioners aware on maintainability and BDM. However, most of them less consider the maintainability and BDM aspects. The result of this preliminary study also supported by the study conducted by Rozita (2006) as both demonstrating the similar result.

The practitioners (48% architects, 35% engineers and 25% facility managers) that agreed for considering maintainability during the building design phase notified that they mainly stress 'easy access' (maintainability characteristic) during the building design phase. It is important to highlight that, the respondents agreed and assumed that a building would be 'maintainable' if the easy access feature is considered. Thus, in the previous project they consider easy access features solely during the design of a building. Further, the respondents that never experience taking maintainability into consideration during the design phase they not familiar with BDM characteristics. From their responses, respondents highlighted that

unavailability of maintainability guideline, limited amount of construction cost, plus with the presence of several demand; especially complex design, higher level of building system and services from the building stakeholders, occupants and owners, are the reasons for not considering BDM. Thus, it is so obvious that, the unclear understanding of BDM criteria are the main reason for not considering maintainability during the building design phase by the Malaysia's construction industry (Preliminary Survey, 2013).

Although many maintainability related studied had been carried out by the academic research and comprehensively discussed the issue of maintainability in journals and conferences, yet, in the practical world, most organizations have no comprehensive and established criteria to induce towards the aim to achieve maintainable as well as CEBM. It is undeniable, that various scholars and professionals in the construction industry have brought forward some maintainability criteria to be considered. Adding to this, the emergence of recent maintainability studies has brought similar and some particularly related maintainability criteria into view (see Table 1.3). These limited maintainability criteria may lead to the inadequate maintainability decision to be considered during the design phase. Therefore, it is apparent to impose a comprehensive list of BDM criteria and indicators to be considered during the building design. The Table 1.3 lists down the BDM criteria identified by previous researches in different maintainability studies.

**Table 1.3:** The BDM criteria identified by previous researches in different maintainability studies.

Criteria	Indicators	Authors
1) Accessibility	-	Her & Russell (2002)
2) Commercial Availability of Spare Parts		
3) Cost for Replacement Parts		
4) Standard Tools		
5) Clear instructions for Maintenance tasks		
1) Accessibility	-	Chew <i>et al.</i> (2004)
2) Downtime		
3) Material Performance		
4) Environment		

Criteria	Indicators	Authors
1) Construction Quality 2) Environment 3) Material Durability, Sustainability & Maintainability 6) Maintenance Quality	-	Chew <i>et al.</i> (2006)
1) Efficient Access 2) Adequate Safety 3) Maintenance needs 4) Plan for Easy maintenance 5) Environment Consideration	-	Silva & Ranasinghe (2010)
1) Accessibility 2) Clean ability 3) Functionality 4) Compatibility 5) Complexity	-	Saghatforoush <i>et al.</i> (2012)
1) Accessibility 2) Material Selection 3) Communication 4) Environment 5) Standardization 6) Maintenance Cost 7) Easy Assembly 8) Diagnose ability	3- 4 Indicators for each criteria	Sivanathan (2014)

As can be seen in Table 1.3, there are only limited and comparatively similar maintainability criteria had been identified. Yet, if we think more broadly about enabling the whole building, it will be realized that, to make the whole building ‘maintainable’, it is vital to include many more dimensions associated with appropriate supports from the built environment professionals (Duggan and Blayden, 2001). The availability of inadequate maintainability criteria blur the clarity on what the factors need to be considered in order to achieve better maintenance. Additionally there are only countable research was conducted to identify more specifically the indicators of each maintainability criteria and thus it leads to the inability of comprehensive information to be applied during the building design phase. The unavailability of indicators for each maintainability criteria had result the identification of maintainability criteria to be incomplete. This is because, having maintainability criteria independently had vague the ability of maintainability decision to be considered during the design phase. Therefore, the identification of indicators for each of the BDM criteria is apparent to form more comprehensive and clearly delineated decisive maintainability criteria.



As the main objective of identifying comprehensive BDM criteria and indicators are to reduce the overwhelming cost of maintenance through mitigation of defects, it is vital to discover the relationship among both of it. This aspect is vital in providing the building practitioners a clear picture of structured way or commonly described as “structural relationship” of BDM criteria and CEBM. The term CEBM is defined as a building which deemed design to be lowest maintenance costs and with greatest return on investment (Whole Building Design Guide (WBDG), 2012; Krstic and Marenjak, 2012; File, 1991). Further, the word “structural” is defined as relating to the arrangement of and relations between the parts or elements of a complex whole (Pearsall & Hanks, 1998). Structural relationship or “what factor lead to what factor” will eventually help the building professionals determine the relevant BDM criteria and indicators to achieve CEBM. Hence, it is strongly assumed that providing the structural relationship among BDM criteria and indicators with CEBM will help the findings be more comprehensive and clear.

Despite of all these facts, the question is, did the previous researches on maintainability consider the BDM criteria and indicators to reduce the spiralling building maintenance cost burdens? Unfortunately, the identification of comprehensive BDM criteria to be applied during the design phase of building in particular to achieve CEBM is still known as unsolved riddle. This is based upon a review of former researches that focus on the BDM issues. The Table 1.4 below shows the summarize version of researches carried out by various researchers related to maintainability issues from the year of 1970’s till lately. Although the consideration of maintainability has been studied by various research since 70’s, the tables shows that, the studies carried out by the previous research can easily explain as twofold; On the one hand, much attention have been given to the temporal aspects of building maintenance; maintenance workloads (common maintenance defects) encountered result of neglecting maintainability aspects (Gibson, 1979; Ransom, 1981; Ikpo, 1983; Seeley, 1987; Al-Hammad *et al.*, 1997; Dunston *et al.*, 1999, Ishak *et al.*, 2007 and Das *et al.*, 2010) and barriers to implement maintainability during the design phase (Che-Ani, 2009; Lin *et al.*, 2003). On the other hand, few have taken

initiatives to develop drivers such as organizational success factors, best practices and guidelines to be followed by built environment professionals to implement maintainability input during the design, construction and maintenance (Ismail and Mohammad, 2014; Silva *et al.*, 2004; Duggan and Blayden, 2001; Meier and Russell, 2000 and Mills, 1994), some studied on significant design, construction and maintenance risk factors for better maintainability (Das and Chew, 2011; Chew and Das, 2007 and Silva and Ranasinghe, 2010). Few more researches seems to extreme and possible to develop maintainability framework, index, scoring device and even assessment model to evaluate the maintainability level of building (Das and Chew, 2010; Chew *et al.*, 2008(a), (b); Chew and Tan, 2004 and Nicolella, 2014).

**Table 1.4:** A Review of Previous Studies on Building Design for maintainability Issues

Year	Author	Maintainability Issues
1979	Gibson	The <b>effect of faulty design on building maintenance</b> . The
1981	Ransom	importance of implementing maintainability during design.
1983	Ikpo	
1987	Seeley	
1997	Al-Hammad <i>et al.</i>	
1999	Dunston <i>et al.</i>	
2000	Meier & Russell	<b>Maintainability best practices</b> into a model implementation process as starting point for implement maintainability.
2001	Duggan & Blayden	<b>Organizational collaboration</b> to implement design stage maintainability to ensure productivity, cash flow & profitability.
2002	Her & Russell	<b>Milestones</b> of the Construction Industry Institute model process for maintainability implementation.
2003	Chew <i>et al.</i>	A <b>model was developed to assess the maintainability of façade</b> using neural network techniques.
2003	Lin <i>et al.</i>	<b>Develop a computer based decision support system</b> for improving the communication between building design and maintenance through Building Automation Systems.
2004	Chew <i>et al.</i>	Offers 2 approaches to integrate with the maintainability concept to augment building <b>performance</b> throughout its <b>economic life</b> .
2004	Bamisile	Explained how the <b>maintainability analysis</b> could be carried out before construction.
2004	Silva <i>et al.</i>	Identification of <b>key factors</b> (knowledge & benchmark) to enhance the level of maintainability in buildings.
2007	Ishak <i>et al.</i>	<b>The effects of design on the maintenance bring awareness and approaches</b> for better maintenance works.

	<b>Author</b>	<b>Maintainability Issues</b>
<b>2009</b>	Che-Ani <i>et al.</i>	<b>Identification of design for maintainability factors</b> that contributing to stabilize the sustainability and maintenance.
<b>2010</b>	Silva & Ranasinghe	<b>Maintainability Problems and strategies</b> to solve those problems.
<b>2010</b>	Alhaji & Hassanain	Investigate the <b>role of the facility manager</b> in the architectural design process.
<b>2010</b>	Das <i>et al.</i>	<b>Decision-analysis framework</b> for building maintainability management.
<b>2011</b>	Das & Chew	Developed <b>defect grading tool</b> to improve building maintainability by preventing defects.
<b>2012</b>	Wood	A Mind mapping developed as a framework for buildings that are <b>economical and efficient to build and to run.</b>
<b>2012</b>	Sivananthan <i>et al.</i>	<b>Overview Design Deficiencies on Ease of Maintenance.</b>
<b>2014</b>	Ismail and Mohamad	<b>Incorporate building maintainability factors</b> in building design <b>to improve the building design life.</b>
<b>2014</b>	Nicolella	<b>A methodology</b> for evaluating maintainability as a tool <b>for durable and sustainable buildings.</b>

Thus, it is obvious that there is a still a gap of what are the inclusive BDM criteria and indicators that need to be considered during the building design in order to achieve CEBM (Duggan and Blayden, 2001). The unavailability of comprehensive as well as clearly delineate BDM criteria and indicators result in uncountable building defects and impose high maintenance cost. In short, there is a need to identify the comprehensive (or important) building BDM criteria and indicators that provide maintainable building and subsequently influence CEBM. Consequently, this will lead to an improved future building designs, construction quality, maintenance management, and etc. Hence the author find, it is necessary to study more broadly on the term ‘maintainability’ and its associated criteria to open up a possible path for the practitioners, particularly Malaysia’s construction industry to apply those criteria during the building design phase.

In summary, the issues that are addressed in this research are:

- i) The comprehensive design for maintainability criteria and indicators to be applied during the design phase of a building to achieve cost effective building maintenance need to be identified and clearly explained.
- ii) The structural relationship of the design for maintainability criteria and indicators to achieve cost effective building maintenance need to be identified.

#### **1.4 Research Questions**

This research attempts to answer the following questions;

- 1) What are the cost effective building maintenance indicators?
- 2) What are the building design for maintainability criteria and indicators to be considered during the building design phase to achieve cost effective building maintenance?
- 3) How are the structural relationship among the design for maintainability criteria and indicators to achieve cost effective building maintenance?

## **1.5 Research Objectives**

Addressing the issues mentioned in Section 1.3, this research aims to study the influence of building design for maintainability on achieving cost effective building maintenance. Subsequently, a structural model for establishing the relationship between building design for maintainability and cost effective building maintenance will be developed. In pursuance to achieve the aforesaid aim, the research will focus on the following objectives.

- i) To identify the cost effective building maintenance indicators.
- ii) To identify the building design for maintainability criteria and indicators to be considered during the design phase to achieve cost effective building maintenance.
- iii) To determine the structural relationship among the building design for maintainability criteria and among the indicators to achieve cost effective building maintenance.

## **1.6 Scope of the Research**

The first scope of this research involves a panel composed of experts closely related in building design, maintenance and its related field (Architecture, Civil Engineering, Structural Engineer, Building Service Engineer, Building maintenance or management, Facilities maintenance or management and Quantity Surveying etc) in the Klang Valley, Penang, Ipoh and Johor. In the absence of much literature on the comprehensive building BDM criteria and indicators, it is imperative to validate the identified criteria and indicators through the expertise who possess substantial experience in building design and maintenance practices. This expertise does not

have to be academic; it could be the knowledge of an experienced practitioner (Valerdi, 2013). The panel of experts will be selected based on a number of criteria including their research interest (knowledge) and experience with the issues under investigation (Jeffery *et al.*, 2000; Hardy *et al.*, 2000; Skulmoski *et al.*, 2007; Valerdi, 2013), hierarchy or position (Mead and Moseley, 2001; Valerdi, 2013), publications (academicians) (Duncan *et al.*, 2004; Valerdi, 2013) or involvement in projects (practitioners) (Powell, 2003; Cantrill *et al.*, 1996; Haughey, 2010), and their willingness to participate (Powell, 2003; Skulmoski *et al.*, 2007). Delbecq *et al.* (1975) further stated that the professional staff members together with their support team are well qualified to be subjects of a Delphi study.

A number of experts in the area closely related with building design, maintenance and its related field have been identified by the researcher using judgemental sampling as the potential population (see Appendix A, Table 1) of Delphi panel. The panels of experts who showed their willingness and interest to participate in the research from the potential population had been listed (see Appendix A, Table 2). Around 16 experts' panels in the area of study have confirmed to participate in this research. They are all experienced and well performed in building design and maintenance topics. The panel of experts served to validate the CEBM indicators and building BDM criteria and indicators identified from the literature. In addition, the panels of experts also will determine the BDM criteria and indicators that associated with particular building elements (basement, facade, floor, roof, lighting system, HVAC, lift, sanitary plumbing and fire-protection).

Second, for the purpose of main survey the people closely related to the design and maintenance of buildings was involves. This consists of architects, civil engineers, building maintenance personnel (facilities and property maintenance personnel), building engineers and building surveyor that operate in Klang Valley, Penang, Ipoh and Johor. Their opinion on the building performance criteria and indicators to be identified in this research is the backbone to the achievement of the research objectives.

Third, as the research focuses on integrating maintainability during the building design and certain elements of a building from maintainability point of view, the structural model that was developed have been limited neither by complexity, size or type of building.

## **1.7 Significance of the Research**

This research contributes to;

### **1.7.1 Filling in the gap that exists in the delineation of the building design for maintainability criteria and indicators and contribute to the knowledge.**

Though numerous literatures and studies has been conducted on building maintainability, yet there is still a gap of what are the actual and significant building maintainability criteria and indicators that need to be considered during the building design, construction and maintenance phase. As for the time constraints and several other limitations, this research intended fill the gap of identifying building design related maintainability criteria and indicators to achieve CEBM especially in the context of Malaysia. Thus, by studying and identifying the BDM criteria and indicators, this research expands knowledge on the influence of BDM towards achieving CEBM.

### **1.7.2 Provide beneficial reference for local architects, design engineers, facility managers, engineers, construction manager and building owners.**

The research will solve the long pending quest of inadequate awareness of building professionals on maintainability and the consideration of maintainability

during the design phase. In general, this research believed to be beneficial reference for local architects, design engineers, facility managers, engineers, construction manager and building owners to incorporate maintainability in the design stage to ensure a successful cost reduction during the building maintenance phase particularly for future projects in Malaysia. This is because the result of this research will assist the professionals in the building design phase to put extra care to attain better maintenance during the building maintenance phase. As a result, the maintainability related problems occur during occupancy stage that relatively increase cost burdens could be reduced.

**1.7.3 Seeks to obtain useful knowledge and an in depth understanding as well as introduce new courses for postgraduate and undergraduate of built environment students on incorporating maintainability aspects during the design stage.**

This study also seeks to obtain useful knowledge as well as an in depth understanding on integrated BDM issues. This study will also enhance the research potential of the investigators to explore all other issues related to the subject area in the future. Additionally, the educational aspect of the research has been designed to provide an excellent opportunity to both the postgraduate and undergraduate of Facility Management and Construction Engineering students to improve their understanding on incorporating maintainability aspects in the design stage. Incorporating maintainability during the design stage is still relatively new concept and yet to be investigated and taught in construction programs. To meet this new challenge, this paper plans to introduce new courses in our graduate level facility management program and the emerging results of the study will be integrated into the coursework, senior design project and thesis work. The findings of the paper will be disseminated through major international journals and magazines.



## 1.8 Research Methodology


The research work is executed in two main phases as discussed below. The research methodology is illustrated in the flow chart shown in the Figure 1.1.

The first phase in the research methodology is aimed to obtain a holistic idea of the research problem and recognized the knowledge gap. A thorough review on various literatures was conducted to obtain the issues and problem associated with the study area. In order to investigate and verify the issues obtained through reviews with the Malaysia's situation, a simple pilot survey was conducted in the early phase of the research. Three groups of respondents were selected for the pilot study, consisting of architect, maintenance personnel and engineer (civil, electrical and mechanical). The main aim of the research in the first phase is to identify, from the available literatures, the BDM criteria and indicators to achieve CEBM. Through critical review of the available literatures the indicators of CEBM were first identified. The CEBM indicators were used as a needle to form the theoretical BDM criteria and indicators.

Following the critical review on literature, next step is aimed to verify the CEBM indicators and BDM criteria and indicators obtained through literature review. Delphi Method (expert's opinion) is the method that will be used to conduct the verification. In first phase of Delphi survey the CEBM indicators and the BDM criteria and indicators will be verified. In the second phase of Delphi survey experts will be required to determine the BDM criteria that applied for the associated building elements (basement, facade, floor, roof, lighting system, HVAC, lift, sanitary plumbing and fire-protection). Respondents used for this Delphi study will be expert from building design, maintenance and its related field (Architecture, Civil Engineering, Building Maintenance, Quantity Surveying, etc).

In the second phase of the research methodology, the verified theoretical design for maintainability criteria and indicators were converted into questionnaire form and distributed to the respondents of the survey in order to examine and validate the proposed relationship between the constructs. Therefore, first questionnaire will be developed based on the output received from expert's survey, to collect empirical data to test the proposed theoretical model. As BDM deals with design and maintenance, the designers, architects, property or facility managers were considered the best respondent. Respondents will be selected from the membership list of professional bodies in Malaysia namely, The Board of Valuers, Appraisers and Estate Agent, Malaysia Association of Facility Management (MAFM), The Board of Architects Malaysia (LAM), Malaysian Institute of Architects (PAM) and The Construction Industry Development Board (CIDB). Before the main survey distribution is conducted, a pilot study will be conducted in order to test the reliability of the main questionnaire. Finally the questionnaire distribution will be conducted.

The last phase (second process of phase two) of the research methodology, aims to analyse the obtained data from the main survey to develop a structural model to reveal the causal relationship of the proposed model. The data obtained from the main survey will be analysing using the partial least square (PLS) approach of SEM.



**Figure 1.1:** Research Methodology Diagram

## 1.9 Structure of the Research

This dissertation has been organised into 8 chapters according to the logical development that has taken place over the entire period of research. The overall 8 chapters are as organized as following;

**Chapter 1. Introduction:** In this chapter a general introduction, background and the justification of the research has been provided. A brief overview on the concepts of BDM and its importance were also explained. It further addressed the aim and objectives, scope and purpose, the significance, the methodology applied to conduct this research and a brief summary on the structure of this thesis.

**Chapter 2. Integrated Maintenance in Building Design:** To obtain a holistic idea of the research problem, and the rationale and concept of integrated maintenance during the building design phase. Therefore, the relevant topics reviewed are: the practice of maintenance in Malaysia, factors causing building maintenance problems, the effect of design deficiencies on building maintenance, design deficiencies related building maintenance cost, the role of Facility Management in building design and finally the rationale and concept on integration of maintenance during the building design phase. This helped to recognize the knowledge gap, issues and rationale of the study.

**Chapter 3. Building Design for maintainability and Cost Effective Maintenance:** It provides an argument for the importance of incorporating BDM principles during the building design phase to achieve CEBM. The CEBM definition and indicators were identified. Subsequently, the CEBM indicators will be the needle to identify the BDM criteria and indicators. The influence of the BDM criteria and indicators on achieving CEBM will be discussed in detail.

**Chapter 4. Research Methodology:** Discusses the methodology employed in this research. The chapter explains the design of the questionnaire developed to identify and verify the CEBM indicators and the BDM criteria and indicators established in Chapter 3 of the research. This chapter subsequently discusses the selection of respondents, data collection and analysis methods employed in this research. The final part of this chapter explicates about the validation process of structural relationship model of the building BDM criteria and CEBM.

**Chapter 5. Data Analysis Phase I:** It will explain the analyses that will be undertaken for achieving the first and second objectives of this research.

**Chapter 6. Data Analysis Phase II:** This chapter will discuss the analysis that carried out in order to achieve the third objective of the research. In the final part of this chapter the structural relationship model of building BDM criteria and CEBM will be verified.

**Chapter 7. Results and Discussion:** This chapter discusses the results obtained and the extent to which the results fulfil the objectives of this research.

**Chapter 8. Conclusion and Recommendations:** After summarizing the whole research and the key findings, the conclusions are made. The contribution and implications of the findings towards the construction industry in general and CEBM in particular are explained. After the knowledge contribution and practical implications of this study are highlighted, finally the limitations are discussed, followed by improvements and identification of the scope of future research.

## REFERENCES

- Abdulmohsen Al-Hammad and Sadi Assaf (1997). The Effect of Faulty Design on Building Maintenance. *Journal of Quality in Maintenance*. Vol. 3, pp. 29-39.
- Action Energy, (2001). New ways of cooling — Information for building designers General Information Leaflet GIL 85. Available From: [www.actionenergy.org.uk](http://www.actionenergy.org.uk). [Accessed: 6 April 2013].
- Adejimi, A. (2005), “Poor building maintenance in Nigeria: are architects free from blames?”, in *ENHR International Conference on Housing: New Challenges and Innovations in Tomorrow’s Cities, Iceland, 29 June-3 July*, Department of Architecture, College of Engineering and Technology, Olabisi Onabanjo University, Ibojun Campus. Ogun State, Nigeria, pp. 1-15.
- Addelson, L. (1996). *Building Failure*. Butterworth Architecture, UK.
- Adler, M., et al (1996). *Gazing into the Oracle: The Delphy Method and its Application to Social Policy and Public Health*. London: Jessica Kigsley Publications.
- Afranie, S and Osei Tutu, E. (1999). Analyzing of Problems, Practices and Policy.
- Afshari, A.R., Yusuff, R.M., & Derayatifar, A.R., (2012). An application of Delphi method for eliciting criteria in personnel selection problem. *Scientific Research and Essays*. 7(33), pp. 2927-2935.
- Ahmad R. H. (2006), Maintenance Management and Services (Case Study: PERKESO Building in Peninsular Malaysia. *A project report submitted as a partial fulfillment of the requirements for the award of the degree of Master in Construction Management*. Faculty of Civil Engineering, University Technology Malaysia.

- Ahmad, R, Nur Azhahani, A and Nur Haniza, I. (2006). The Effects Design on The Maintenance Of Public Housing Buildings In Malaysia-Part One. *Journal of Buildings Engineer.*
- Aibinu A. A. and Al-Lawati A. M. (2010).Using PLS-SEM technique to model construction organizations' willingness to participate in e-bidding. *Automation in Construction.* Vol. 19, p. 714–724.
- Alexander, K. (2009). *Facilities management futures.* Manchester, UK: A Euro FM Publication, Centre for Facilities Management.
- Ali, A. S., Kamaruzzaman, S. N., Sulaiman, R. and Peng, Y. C. (2010). Factors Affecting Housing Maintenance cost in Malaysia. *Journal of Facilities Management,* Vol. 8 No. 4, pp. 285-298.
- Ali, A.S. (2009). Cost decision making in building maintenance practice in Malaysia. *Journal of Facilities Management.* 7(4) p. 298-306.
- Alexander, K. (1996). *Facilities Management: Theory and Practice.* London, UK: E & FN Spon.
- Alexandrov, A. V., Pullicino, P. M., Meslin, E. M., & Norris, J. W. (1996). Agreement on disease-specific criteria for do-not-resuscitate orders in acute stroke. *Stroke,* 27, p. 232-237.
- Alhaji, M. and Hassanain, M.A. (2010), “Towards Improvement in Facilities Operation and Maintenance through Feedback to the Design Team”, *The Built & Human Environment Review,* Vol. 3 No. 1, pp. 72-87.
- Al-Hammad, A., Assaf, S. and Al-Shihah, M. (1997), “The Effect of Faulty Design on Building Maintenance”, *Journal of Quality Maintenance Engineering,* Vol. 3 No. 1, pp. 29–39.
- Al-Khatam, J.A (2003). Buildings Maintenance Cost. Master of Engineering Report (CEM-600). College of Environmental Design. Construction Engineering and Management, King Fahd University of Petroleum & Minerals.
- Al- Shiha, Mansoor Mohammad, M.S (1993), “The Effects of Faulty design and Construction on Maintenance”, Saudi Arabia, Master Dissertation.
- AMCP 706-134 (1972). *Engineering Design Handbook: Maintainability Guide for Design.* Department of Defense, Washington, D.C.

- Ammenwerth, E., Mansmann, U., Iller, C. and Eichstadter, R. (2003) Factors affecting and affected by user acceptance of computer-based nursing documentation: results of a two-year study. *Journal of the American Medical Informatics Association*;10:69-84.
- Anderson J. C. and Gerbing D. W. (1988). Structural Equation Modeling in Practice: A Review and Recommended Two-Step Approach. *Psychological Bulletin*. Vol. 103, p. 411- 423.
- Ankenbrandt, F.L., Lapole, R.E. and Margulies, G. (1963), *Maintainability Design*, Engineering Publishers, Elizabeth, New Jersey.
- Arditi, D. and Nawakorawit, M. (1999a), “Designing Buildings for Maintenance: Designers’ Perspective”, *Journal of Architecture Engineering*, Vol. 5 No.4, pp. 107–116.
- Arditi, D. and Nawakorawit, M. (1999b), “Issues in Building Maintenance Property Managers Perspective”, *Journal of Archit Engineering*, Vol. 5 No. 4, pp. 117-132.
- Arditi, D. and Messiha, H. (1996). Life-cycle costing in Municipal Projects. *Journal of Infrastructure System*. 2(1) p.5–14.
- Assaf, S., Al-Hammad, A. and Al-Shihah, M. (1996), “Effects of faulty design and construction on building maintenance”, *Journal of Perform Constr Facilities*, No. 10 Vol. 4, pp. 171–174.
- Assaf, A.H. and Al-Shihah, M. (1995). The Effect of Faulty Construction on Building Maintenance. *Journal of Building Research and Information*. 23(1) p.175–81.
- Assaf, S., Al-Hammad, A. and Al-Shihah, M. (1995). The Effect of Faulty Construction on Building Maintenance. *Journal of Building Research and Information*. 23(3) p.175–181.
- Ballast, D.K. (2010), *Interior Design Reference Manual: Everything You Need to Know to Pass the NCIDQ Exam*, 5th edition, Professional Publications Inc, United States of America, USA.
- Barabadi, A. Barabady, J. and Markeset, T. (2011). Maintainability analysis considering time-dependent and time independent covariates. *Reliability Engineering and System Safety* 96. pp.210–217.



- Barone, C., Pinto C., Normann, N., Capussotti, L., Cognetti, F., Falcone, A. and Mantovani, L. (2014). KRAS Early Testing: Consensus Initiative and Cost Effectiveness Evaluation for Metastatic Colorectal Patients in an Italian Setting. PLoS ONE 9(1): e85897, 1 Vol (9), p. 1-13.
- Barrett, P. S. and Stanley, C. A. (1999). *Better Construction Briefing*. Oxford, U.K: Blackwell.
- BCA (2000). Enhancing Maintainability of Buildings – Pilot Study Report. Building Construction Authority, Singapore.
- Becker, F. (1990). *The Total Workplace*. New York, USA: Van Nostrand Reinhold.
- Berg, Sven. (2006). "Snowball Sampling–I," pp.7817–7821 in *Encyclopedia of Statistical Sciences*, edited by Samuel Kotz, Campbell Read, N. Balakrishnan, and Brani Vidakovic. Hoboken, NJ: John Wiley and Sons, Inc.
- Bernama (2009). Government Identifies Initiatives For National Asset Management Concept. Available from: <http://www.kettha.gov.my/en/printpdf/node/882>. [Accessed on 14<sup>th</sup> September 2013].
- Biggs, S., et al (2011). Safety leaders' perceptions of safety culture in a large Australian construction organisation. Queensland University of Technology. Vol. NA, pp. 01-13.
- Blanchard, B.S (1999). *System Engineering Management*. New York: John Wiley and Sons. pp.7.
- Blanchard, B.S., Verma, D. and Peterson, E.L. (1995), *Maintainability: A Key to Effective Serviceability and Maintenance Management*, John Wiley & Sons, Inc, Canada.
- Blanchard, B. S. and Lowery, E. E. (1969). *Maintainability: Principles and Practices*. New York: McGraw-Hill.
- Boje, D. M., & Murnighan, J. K. (1982). Group confidence pressures in iterative decisions. *Management Science*. Vol. 28, pp.1187-1196.
- Boothroyd and Dewhurst (1983). *Design for Assembly Handbook*. pp. 109–114, Boothroyd and Dewhurst, Inc.

- Bourke, K. and Davies, H. (1997). *Factors Affecting the Service Life Predictions of Buildings: A Discussion Paper*. Laboratory Report, Prepared for Building Research Establishment. Garston, U.K.
- Boussabaine, A.H. and Kirkham, R.J. (2004). Simulation of Maintenance Costs in UK Local Authority Sport Centres. *Journal of Construction Management and Economics*. Vol. 22 pp.1011-20.
- Briffett, C. (1990). *Balancing Design and Maintenance Issues : Building maintenance and Modernization Worldwide*. Vol. 2, Singapore: Longman.
- British Standards, BS3811:1984 (1984), “*Glossary of Maintenance Management terms in Terotechnology*”, London: BSI.
- British Standards, EN 13306:2010 (2010), “Maintenance. Maintenance terminology” British adopted European Standard.
- Brochner, J. (2003). Integrated Development of Facilities Design and Services. *Journal of Performance of Constructed Facilities*. Vol.17 (1), p. 19-23.
- Brooks, K. W. (1979). Delphi technique: Expanding applications. *North Central Association Quarterly*. Vol. 53, 377-385.
- Brockhoff, K. (1975). *The performance of forecasting groups in computer dialogue and face to face discussions*. In: Linstone, H., & Turoff, M. (Eds.), *The Delphi method: techniques and applications*, Addison-Wesley, London.
- Buck, et al., (1993). Using the Delphi process to analyze social policy implementation: a post hoc case from vocational rehabilitation. *Policy Sci*. Vol. 26, p.271–288.
- Building Construction Authority, Singapore (2000) CONQUAS 21, 2000.
- Building Research Establishment (BRE) (1983). Design and Site Procedures – Defects and Repairs. *Building Research Establishment Digests*. Vol. 4, Her Majesty's Stationery Office, London.
- Building Research Establishment (BRE) (1991). Housing defects reference manual, The building research establishment defect action sheets. E&FN Spon, London.
- Burrell, G. and Morgan, G. (1979). *Sociological Paradigms and Organizational Analysis, Elements of the Sociology of Corporate Life*. London, Heinemann. Educational Books Ltd.
- Buzan, T. (1988). *Make the Most of your Mind*. London: Pan Books.

- Building Owners and Managers Association (BOMA) (2006), “The Green Issue Spring 2006”, *Kingsley Quarterly*, Practical Industry Intelligence for Commercial Real Estate, BOMA International and Kingsley Associates, New York.
- Boote, D.N. & Beile, P. (2005). Purpose of Literature Review. Scholars before researchers: On the centrality of the dissertation literature review in research preparation. *Educational Researcher*. 34(6) p. 3-15.
- Cane, D., Morrison, A. and Ireland, C. J. (1998). Maintenance and Service Costs of Commercial Buildings Ground-Source Heat Pump Systems. *ASHRAE Trans*. 104(2) p.699–706.
- Cantrill J.A et al. (1996). The Delphi and Nominal Group Techniques in Health Services Research. *International Journal of Pharmacy Practice*. 4(1) p.67-74.
- Carpenter, T. and Ollmann, A. (2008). Sustainable Design and Development: An Integrated Team. *Journal of Construction Account and Taxation*. 18(4).
- Carson, D., Gilmore, A., Perry, C. and Gronhaug, K., (2001). *Qualitative Marketing Research*, Sage Publications, London
- Cash, C. G. (1997a). *The Relative Durability of Low-slope Roofing*. Proceeding 4th International Symposium on Roofing Technology. Rosemont. 1(2) p.17–19.
- Cash, C. G. (1997b). *Comparative Testing and Rating of Thirteen Thermoplastic Single ply Roofing Membranes*. Proceeding 8th International Conference on Durability of Building Materials and Components. M. Lacasse and D.Vanier, eds. Toronto: National Research Council. p.1083–1092.
- Cavana, R.Y, Delahaye, B.L. and Sekaran, U. (2001). *Qualitative and Quantitative Methods*. John Wiley & Sons Australia, Milton, Queensland.
- CEN/TC319, EN13306:2010 (2010), *Maintenance—Maintenance Terminology*. Bruxelles: European Standard.
- Central Bank of Malaysia (2006). *Central Bank of Malaysia Annual Report*. Central Bank of Malaysia, Kuala Lumpur.
- Chan, Y. (2007). A Delphi study of knowledge management systems: scope and requirements. *Journal of Information and Management*. Vol 44(6), pp. 583-597.

- Chakravarti, A.K., *et al* (1998). Modified Delphi methodology for technology forecasting case study of electronics and information technology in India, *Technol. Forecast. Soc. Chang.* Vol 58 p. 155–165.
- Chanter, B., and Swallow, P. (2007). *Building Maintenance Management*, 2nd Ed. Oxford, UK: Blackwell Publishing.
- Che-Ani, A.I., Chohan, A.H., Goh, N.A., Tahir, M.M., Surat, M. and Usman, I.M.S. (2009), Sustainability design formulation in achieving best practice of building maintenance. *World Academy of Science, Engineering and Technology*, pp. 1156-1160.
- Chew, M.Y.L., Silva, N.D. and Tan, S.S. (2010). A neural network approach to assessing building façade maintainability in the tropics. *Construction Management and Economics*, Vol. 22 No. 1, pp. 581–594.
- Chew, M.L., Das, S. and Sulaiman, N.H.B. (2008a). Quantifying Maintainability Parameters for Vertical Transport System. in *11th International Conference on Durability of Building Materials & Components, Istanbul, Turkey, Istanbul Technical University, 2008*, pp. 11-14.
- Chew, M.Y.L., Das, S., De Silva, N. and Foon, F.Y. (2008b). Grading Maintainability Parameters for Sanitary-plumbing System for High-rise Residential Buildings. in *CIB International Conference in Building Education & Research, Sri Lanka, 11<sup>th</sup> -15<sup>th</sup> February, 2008*, pp. 887-900.
- Chew, M.Y.L. and Das, S. (2007). Maintainability Aspects of Central Chilled Water HVAC System. in *4th. International Conference on Construction in the 21st Century. Miami, Florida, Florida International University, 2007*, pp. 86.
- Chew, Silva, Tan and Das (2006). Grading of Risk Parameters for Facade Maintainability. *International Journal on Architectural Science.* 7 (3) pp.77-87.
- Chew, M.Y.L., Tan, S.S. and Kang, K. H. (2005). Contribution Analysis of Maintainability Factors. *Architectural Science Review*, Vol. 48 No. 3, pp. 215-228.
- Chew, M. Y. L. (2005). Defect Analysis in Wet Areas of Buildings. *Journal of Construction and Building Material.* 19(3) pp.165–173.
- Chew, M.Y.L., De Silva, N. and Tan, S.S. (2004) c. Maintainability of wet areas of non-residential buildings. *Struct. Survey*, Vol. 22 No.1, pp. 39–52.

- Chew, M.Y.L. and De Silva, N. (2004). Factorial Method for Performance Assessment of Building Façades. *Journal of Construction Engineering and Management*. 130(4), pp.525–33.
- Chew, M. Y. L., and Tan, S. S. (2004). A Multivariate Approach to Maintenance Prediction of Wet Areas. *Journal of Construction Management and Economics*. 22(4) pp. 395–407.
- Chew, M.Y.L., Tan, S.S. and Kang, K H. (2004)a. Building Maintainability—Review of State of the Art. *Journal of Architectural Engineering*, Vol. 10 No. 3, pp. 80-87.
- Chew, M. Y. L., De Silva, N., and Tan, S. S. (2004)b. Maintainability of wet areas of non-residential buildings. *Struct. Survey* 22(1) p.39–52.
- Chew, M.Y.L. and Tan, S.S. (2003). Neural Network Approach for Grading of Maintainability of Wet Areas in High-Rise Buildings. *International Journals on Architectural Science*, No. 4 Vol. 4, pp. 150-167.
- Chew, M.Y.L. and De Silva, N. (2003a). Benchmarks to minimize water leakages in basements. *Structural Survey*. 21(4) pp. 131-45.
- Chew, M.Y.L. (2000). Joint sealant for Wall Cladding. *Polymer Testing*. 19(6) pp. 643–653.
- Chew, M.Y.L., Wong, C.W. and Kang, L.H. (1999). *Building Facades—A Guide to Common Defects in Tropical Climates*. Singapore: World Scientific Publishing.
- Chew, M.Y.L. (1994). Efficient Maintenance: Overcoming Building Defects and Ensuring Durability. Conference on Building Safety. The Asia Business Forum, Kuala Lumpur.
- Chin W. W., Marcolin B. L., and Newsted P. R. (2003). A partial least squares latent variable modeling approach for measuring interaction effects: Results from a monte carlo simulation study and voice mail emotion/adoption study. *Information Systems Research*. Vol. 14, pp.189–217.
- Chin W. W., (2010). *Handbook of Partial Least Squares*. pp. 655–690. Springer-Verlag.
- Chong, W.K. and Low, S.P. (2006), “Latent Building Defects: Causes and Design Strategies to Prevent Them”, *Journal of Performance of Constructed Facilities*, Vol. 20 No. 3, pp. 213-221.
- Christian, J. and Pandeya, A. (1997). Cost predictions of facilities. *Journal of Management and Engineering*. 13(1) pp.52–61.

- Chohan, Hyder, A., Ani, Irfan, A., Che, Memon, Waheed, A., Ishak, Nor Haniza, Zubair (2010). Design Liability towards Building Maintenance at Post Occupational Stage. Available from: AllBusiness.com. [Accessed on: 10 December 2014].
- Chuan, O. K. (The Minister of Housing and Local Government) (2008, May 9 pN13). *Call for Check on Buildings: architects push for inspection every five years*. The Star pN33.
- Construction Industry Development Board (CIDB) (2011). Number and Value of Projects Awarded as of December 2010. Kuala Lumpur: *Construction Industry Development Board*.
- Collinson Grant (2010). *Managing Indirect Costs*. Manchester: Collinson Grant.
- Construction Industry Development Board (CIDB) (2003). *Malaysia (CIDB) Directory*, 3rd edn, Builder's InforNet (M) Sdn Bhd, Selangor.
- Cornik, T. (1991). *Quality Management for Building Design*. Essex, UK: Butterworth Heinemann Ltd.
- Cook (1992). The Effect of Building on Wind. A Thesis Submitted in partial fulfillment of the Requirements of University of Aston for the Bachelor of Degree. University of Aston.
- Cooper D. R. and Schindler P. S., (2008). *Business Research Methods*. McGraw-Hill.
- Cousins, J., Butler, T. and Shah, S (2005). What designers need from facilities managers. *British Institute of Facilities Management Conference, March 2005*.
- Creswell, J.W. (2005). *Educational research: Planning, Conducting and evaluating quantitative and qualitative research* (Second ed.). Upper Saddle River, N.J.: Pearson Merrill Prentice Hall.
- Cuhls, K. (2004). *Delphi method, Foresight Methodologies*. United Nations Industrial Development Organization.
- Custer, R. L., Scarcella, J. A., & Stewart, B. R. (1999). The modified Delphi technique: A rotational modification. *Journal of Vocational and Technical Education*. Vol. 15 (2), pp.1-10.
- Dajani, J., Sincoff, M., Talley, W., (1979). Stability and agreement criteria for the termination of Delphi studies. *Technol. Forecast. Soc.* Vol. 13, pp. 83-90.

- Dalkey N., and Helmer O., (1963). An experimental application of the Delphi method to the use of experts. *Manage Science*. Vol.9, pp.458–67.
- Das, S., and Chew, M.Y.L. (2011). Generic Method of Grading Building Defects Using FMECA to Improve Maintainability Decisions. *Journal of Performance of Constructed Facilities*, Vol. 25 No. 6, pp. 522-533.
- Das, S., and Chew, M.Y.L. (2010a), “Multi-criteria decision analysis in building maintainability using analytical hierarchy process”, *Construction Management and Economics*, Vol. 28 No.10, pp. 1043–1056.
- Das, S., Chew, M.Y.L and Poh, K.L. (2010b). Multi Criteria Decision Analysis in Building Maintainability using Analytical Hierarchy Process. *Journal of Construction Management and Economic*, Vol 28 (1), pp. 1043-1056.
- Dalkey, N.C., (1969). The Delphi Method: An Experimental Study of Group Opinion. Available from: [http://www.rand.org/pubs/research\\_memoranda/RM5888/](http://www.rand.org/pubs/research_memoranda/RM5888/). [Accessed on: 10 April 2014].
- Davey, C., McDonald, J., Lowe, D., Duff, R., Powell, J. A., and Powell, J. E. (2006). Defects Liability Management by Design. *Build. Res. Inf.* 34(2) pp.145–153.
- Dawes, J.(2008). Do data characteristics change according to the number of scale points used? : An experiment using 5-point, 7-point and 10-point scales. *International Journal of Market Research*, Vol. 50, p.61–77.
- Delbecq, A.L., Van de Ven, A.H., Gustavson, D.H., (1975). *Group Techniques for Program Planning: a Guide to Nominal Group and Delphi Processes*. Scott Foresman and Company, Glenview, Illinois.
- Deming, W. E., (1990). *Sample Design in business research*. John Wiley and Sons. pp. 31.
- Department of the Environment (1972). *Research and Development Bulletin: Building Maintenance*. The Report of the Committee, London, HMSO.
- Dewhurst, P. and Abbatiello, N. (1996), *Design for Service – Ability*, In: Huang, G.Q. (ed.), *Design for X – Concurrent Engineering Imperatives*, Chapman & Hall, London, pp. 298-317.
- Dhillon, B.S. (2010). *Life Cycle Costing for Engineers*. United States of America: Tylor and Francis Group.

- Dhillon, B.S. (2008), *Mining Equipment Reliability, Maintainability and Safety*, Springer-Verlag London, London.
- Dhillon, B.S. (2006), *Maintainability, Maintenance and Reliability for Engineers*, Tylors and Francis Group, London.
- Dhillon, B.S (1999a), *Design Reliability: Fundamentals and Applications*. CRC, Boca Raton, FL.
- Dhillon, B.S (1999b), *Engineering Maintainability: How to Design for Reliability and Easy Maintenance*. Gulf, Houston, Texas.
- Downs, W.R. (1976). *Maintainability analysis versus maintenance analysis*. Proceedings of the Annual Reliability and Maintainability Symposium. pp. 476–481.
- Duggan, M. and Blyden, R. (2001). Venture Maintainability: A Path towards Project Success –Why are some projects less successful than others and what can we do to improve? *Journal of Quality in Maintenance Engineering*. 7(4) p.241-251.
- Duncan, E., Nicol, M and Ager, A., (2004). Factors that constitute a good cognitive behavioural treatment manual: a Delphi study. *Behav. Cogn. Psychother*. Vol. (32) pp. 199-213.
- Dunston, P.S. and Williamson, C.E. (1999). Incorporating maintainability in constructability review process. *Journal of Management in Engineering*. 15(5) p.56–60.
- Edum-Fotwe, F. T. and Gibb, A. G. F. (2001). *Standardisation in NHS PFI hospital schemes. Final Report Project B*. August, (99) 19/SP-T2000.
- Egan, J. (1998). Rethinking Construction: Report of The Construction Task Force to The Deputy Prime Minister. *Dept. of the Environment, Transport and the Regions*. London.
- ‘Eizzatul ‘Ain S., Hishamuddin., M.A. and Suwaibatul I.S., (2012). A Review of the Effect of Building Design on maintenance Mangement. *3rd International Conference on Business and Economic Research (3<sup>rd</sup> ICBER) Proceesing, 12-13 March 2012. Golden Flower Hotel, Bandung, Indonesia*.
- Erdener, E. (2003) Linking Programming and Design with Facilities Management. *Journal of Performance of Constructed Facilities* 17(1) pp.4-8.



- Edum-Fotwe, F. T., Egbu. C. and Gibb, A. G. F. (2003). Designing Facilities Management Needs into Infrastructure Projects: Case from a Major Hospital. *Journal of Performance of Constructed Facilities*. 17(1) pp.43-50.
- El-Haram, M. A., and Horner, M. W. (2002). Factors affecting housing maintenance cost. *Journal of Quality in Maintenance Engineering*. 8(2) pp. 115-123.
- El-Haram, M.A., Horner, R.M and Munns, A.K. (1996). Applications of RCM to building maintenance strategies. *Proceeding of 6<sup>th</sup> International Logistics Symposium, Exter*. pp.133-143.
- Encyclopædia Britannica (1911). *Basement – Architectural Elements*. Volume 3. Available from: [http://en.wikisource.org/wiki/1911\\_Encyclop%C3%A6dia\\_Britannica/Basement](http://en.wikisource.org/wiki/1911_Encyclop%C3%A6dia_Britannica/Basement). [Accessed on 3 April 2014].
- English, G.M and Keran, G.L (1976). The prediction of air travel and aircraft technology to the year 2000 using the Delphi method, *Transp. Res.* Vol.10 pp. 1–8.
- Feldman, E.B. (1975), *Building Design for Maintainability*, McGraw-Hill, United State of America, USA.
- File, W. T., (1991). *Cost Effective Maintenance- Design and Implementation*. Butterworth-Heinemann Ltd.
- Fink, A., and Kosecoff, J.B. (1985). *Social surveys; Educational surveys*. Sage Publications (Beverly Hills).
- Foo (1988). *Total Building Maintenance Concept*. Master of Science Thesis, in Singapore: National University of Singapore.
- Fornell C. and Bookstein F. L. (1982). Two Structural Equation Models: LISREL and PLS Applied to Consumer Exit-Voice Theory. *Journal of Marketing Research*. Vol. 19, pp. 440–452.
- Foxcroft, C., Paterson, H., le Roux, N., & Herbst, D. Human Sciences Research Council, (2004). *'Psychological assessment in South Africa: A needs analysis: The test use patterns and needs of psychological assessment practitioners: Final Report: July*. Available from: [http://www.hsrc.ac.za/research/output/outputDocuments/1716\\_Foxcroft\\_Psychologicalassessmentin%20SA.pdf](http://www.hsrc.ac.za/research/output/outputDocuments/1716_Foxcroft_Psychologicalassessmentin%20SA.pdf). [Accessed on 15 April 2014].

- Fuller, Sielinde K, and Stephen R Petersen. 1997. *Life-Cycle Costing Manual for the Federal Energy Management Program*. 135. 1995 ed
- Gabrielli, J. (2010). Architecture. *Whole Building Design Guide*. Washington, DC., USA: National Institute of Building Science.
- Gambardella, L. M., and Moroni, M. (1990). *Expert systems application to building pathology diagnosis: Methodology*. Proceeding 2nd European Conference on Application of Artificial Intelligence and Robotics to Building, Architecture and Civil Engineering, Liege, Belgium, pp.252–258.
- Gefen D., Straub D., and Boudreau M. C. (2000). Structural Equation Modeling and Regression: Guideline for Research Practice. *Communications of the Association for Information Systems*. Vol. 4, pp.1–70.
- Gibson J.M.E. (1998). Using the Delphi to identify the content and context of nurses continuing professional development needs. *Journal of Clinical Nursing*. Vol 7, p.451-459.
- Gibson, E.J. (1979). *Developments in Building Maintenance – 1*. Applied Science Publishers, London.
- Gilder (1989). *Lessons Form Cladding, Design and Construction*. Regent Crest Hotel, England, 7 Nov 1989.
- Glavinich, T. E. (1995). Improving Constructability during Design phase. *Journal of Architecture Engineering*. 1(2) pp.73–76.
- Government of Malaysia (2012). Persidangan Strategi Pengurusan Aset Infrastruktur 2012. [Available from: https://www.jkr.gov.my/news/read/1144](https://www.jkr.gov.my/news/read/1144). [Accessed on 11 Novemebr 2011]. (Retrived on 11/11/2013)
- Government of Malaysia (2009). Pekeliling Am Bilangan 1 Tahun 2009: ManualPengurusan Aset Menyeluruh Kerajaan. Putrajaya, Malaysia: Jabatan PerdanaMenteri.
- Government of Malaysia (2006). *Ninth Malaysian Plan 2006 – 2010*, Economic Planning Unit Prime Minister’s Department, Putrajaya.
- Gracht, H.A., (2012). Consensus measurement in Delphi studies Review and implications for future quality assurance. *Technological Forecasting & Social Change*. Vol. 79 pp. 1525–1536.
- Gray, C. (2002). *Building Design & Management*. Butterworth & Heinemann. England.

- Green, K.C., Armstrong, J.S., and Graefe, A., (2007). Methods to Elicit Forecasts from Groups: Delphi and Prediction Markets Compared. *The International Journal of Applied Forecasting*. 8 pp.17–21.
- Griffin, J. J. (1993). *Life Cycle Cost Analysis: a decision aid*. London: Blackie Academic & Professional.
- Haenlein M. and Kaplan A. M. (2004). A Beginner's Guide to Partial Least Squares Analysis. *Understanding Statistics*. Vol. 3, pp. 283–297.
- Haik, Y (2003). *Engineering Design Process*. USA: Brooks/Cole, Inc Thomson Learning™.
- Hair J. F., Black, W. C., Babin B. J., and Anderson R. E. (2010). *Multivariate Data Analysis*. Pearson.
- Hamilton, B and Wan Salleh, W. I. (2001). *Maintenance of building important. National House Buyers Association*. Available from: <http://www.hba.org.my/archive/focus/COB/pg1.htm>. [Accessed on 3rd February 2012].
- Hardy D, O'Brien A, Gaskin C (2004). Practical application of the Delphi technique in a bicultural mental health nursing study in New Zealand. *Journal of Advanced Nursing*. Vol.46 (1), pp.95-109.
- Hassanain, M. A. (2006). Factors Affecting the Development of Flexible Workplace Facilities. *Journal of Corporate Real Estate*. 8(4) p.213-220.
- Hassanain, M. A., Froese, T. M., and Vanier, D. J. (2003). Framework Model for asset maintenance management. *Journal Perform. Construction Facilities*. 17(1), pp. 51–64.
- Haughey, D (2010). Delphi Technique a Step-by-Step Guide. Project Smart.com.uk. pp.1-2.
- Henriksson, A. (2010). Environmental assessment of residential buildings – What does it take to build Green? *Master of Science Thesis in the Master Degree Programme Industrial Ecology, Department of Energy and Environment Division of Environmental System Analysis, Chalmers*. University of Technology, Göteborg, Sweden.

- Her, B. M. and Russell, J. S. (2002). Maintainability implemented by third-party contractor for public owner. *Journal of Management in Engineering*, Vol. 18 No. 2, pp. 95-102.
- Hinks, J. & McNay, P. (1999). The creation of a management-by-variance tool for facilities management performance assessment. *Facilities*. 17(1/2) pp.31-53.
- Hishamuddin, M. A. and Buang, A. (2006). Real estate education in Malaysia: a new paradigm. in *Proceedings of International Real Estate Research Symposium (IRERS) 2006*, 11– 13th April, 2006, PWTC Kuala Lumpur, Malaysia.
- HKIFM (2010). *11 Areas of Core Competency*. (Available From: [http://www.hkifm.org.hk/public\\_html/core.html](http://www.hkifm.org.hk/public_html/core.html)). [Accessed on 15 May 2014].
- Honstede, W. V. (1990). Research into quality of housing stock in the Netherlands. *Building Maintenance Modernization Worldwide*. 2, pp.659– 668.
- Horner, R.M.W., El-Haram, M.A. and Munns, A.K. (1997). Building maintenance strategy: a new management approach. *Journal of Quality in Maintenance Engineering*. 3(4) pp.273–280.
- Hsu, C., C. and Sandford, B.A. (2007). The Delphi Technique: Making Sense of Consensus. *Practical Assessment, Research & Evaluation*. 12(17), pp. 01-08.
- Ikpo, I. J, (2009) Maintainability indices for public building design. “Journal of Building Appraisal”, Vol. 4, pp. 321–327.
- Ilozor, B. D., Okoroh, M. I., and Egbu, C. E. (2004). Understanding residential house defects in Australia from the State of Victoria. *Build. Environ*. 39(3), pp. 327–337.
- Ismail, N and Mohamad M. I., (2015). Factors in building design that improve building maintainability in Malaysia. In: Raidén, A B and Aboagye-Nimo, E (Eds). *Procs 31st Annual ARCOM Conference, 7-9 September 2015, Lincoln, UK*, Association of Researchers in Construction Management, pp.905-914.
- Ishak, Sr. N.H., Chohan, A.H. and Ramly, A. (2007), Implications of design deficiency on building maintenance at post-occupational stage. *Journal of Building Appraisal*, Vol. 3 No. 2, pp. 115-24.

- Jacobs, J. M. (1996). Essential assessment criteria for physical education teacher education programs: A Delphi study. PhD Dissertation, West Virginia University, Morgantown.
- Jeffery, D., Ley, A., Bennun, I., and McLaren, S. (2000). Delphi survey of opinion on interventions service principles and service organization for severe mental illness and substance misuse problems. *Journal of Mental Health*. Vol 9 (4), pp.371-384.
- JFMA (2006). *What is FM?* (Available From: <http://www.jfma.or.jp/en/whatsFM/index.html> [Accessed on: 15/5/2014]).
- Josephson, P. E., and Hammarlund, Y. (1999). The causes and costs of defects in construction: A study of seven building projects. *Autom. Constr.* Vol 8(6), pp.681–687.
- Kalaian, S. A., and Kasim, R.M. (2012). Terminating Sequential Delphi Survey Data Collection. *Practical Assessment, Research and Evaluation*. Vol 17, (5), pp.1-10.
- Kaplan, B. and Duchon, D. (1988). Combining Qualitative and Quantitative Methods in Information Systems Research: A Case Study. *Management Information System Quarterly*. Vol. 12, pp.571–586.
- Kaplan, L. M. (1971). The use of the Delphi method in organizational communication: A case study. Master's thesis, The Ohio State University, Columbus.
- Kelly, A. (1984). *Maintenance Planning and Control*. UK, Butterworth & Co ltd.
- Kim, Y., Li, S., Pan, C., Zuo, L., (2013). The role of accounting conservatism in the equity market: Evidence from seasoned equity offerings. *The Accounting Review*, forthcoming.
- Kincaid, D. (1994). Integrated facility management. *Facilities*. 12(8) pp.20-23.
- Krebs JR, Davies NB, eds, (1997). *Behavioural ecology: an evolutionary approach*. Oxford: Blackwell Scientific.
- Krstić, H., and Marenjak, S. (2012). Analysis of buildings operation and maintenance costs. *Gradevinar*. Vol. 64 No.4, pp. 293-303.
- Kondo, T., Hatakeyama, S., Isobata, O. (1990). Simplified inspection method for long term maintenance of Existing Buildings. *Building Maintenance & Modernisation Worldwide*. 2 pp.650–8.

- Koo, T.K. (2000). Senior Parliamentary Secretary, Ministry of National Development, MOU Signing on the Establishment of the Centre for Total Building Performance. Accessed from: <http://www.bca.gov.sg/cru/mndpr49.html>. [Accessed on 3rd February 2014].
- Kumar, R. (2005). *Research Methodology, A step by step guide for beginners*. (Second edition). Person Education Australia.
- Laird, S. (1994). Total facilities management. *Facilities*. 12(13) pp. 25-26.
- Lateef, O. A., Khamidi, M. F., and Idrus, A. (2010). Building maintenance management in a Malaysian university campuses: A Case Study. *Australasian Journal of Construction Economics and Building*. 10 (1/2) pp. 76-89.
- Lateef, O. A (2008). Building Maintenance Management in Malaysia. *Journal of Building Appraisal*. Vol 4 (3). Pp. 207–214.
- Lam, K.C. (2000). *Quality assurance in management of building services maintenance. Building Services Engineering Department*. The Hong Kong Polytechnic University, in Southeast Asia Facility Management, May/June 2000 issue.
- Landeta, J. (2006). Current validity of the Delphi method in social sciences. *Technological Forecasting and Social Change*, 73, p.467-482.
- Lee, R. and Wordsworth, P. (2001). *Lee's Building Maintenance Management*. 4th ed., Blackwell Science, Oxford.
- Lee, J.H. (1996). Statistical deterioration models for condition assessment of older buildings. PhD thesis, Wayne State University, Detroit, MI.
- Lee, R. (1987). *Building Maintenance Management*. United Kingdom: Oxford U.K.
- Lim et al., (1991). Maintenance management in Singapore. *Singapore : School of Building and Estate Management, National University of Singapore*.
- Lingeron, J.C. and Lyonnet, P. (1988). *Le Management des grands contrats, Prise en compte des aspects qualite' et su^ rete' de fonctionnement*, Tec et Doc, Lavoisier, Paris.
- Linstone H.A. and Turoff M., (1975). *The Delphi method: techniques and applications*. Addison-Wesley Publishing Co.
- Linstone, H.A., Turoff, M., (2002). *The Delphi Method: Techniques and Applications*. Available from: <http://is.njit.edu/pubs/delphibook/>. [Accessed on 3rd March 2014].

- Liska, R. (1988). *Means Facilities Maintenance Standards*. R. S. Means Company Inc.,
- Loughlin, K.G. and Moore, L.F. (1979). Using Delphi to achieve congruent objectives and activities in a pediatrics department, *J. Med. Educ.* 54, p. 101–106.
- Low, S. P., and Wee, D. (2001). Improving maintenance and reducing building defects through ISO 9000. *Journal Qual. Mainten. Eng.* 7(1) pp.6–24.
- Ludwig, B. (1997). Predicting the future: Have you considered using the Delphi methodology? *Journal of Extension*, 35 (5), pp.1-4.
- Mahmoud, T. (1994). Assessment of the problems facing the maintenance industry in Saudi Arabia. *Thesis of Masters in King Fahd University of Petroleum and Minerals, Saudi Arabia*.
- Maisarah A. R., and Mastura J. (2012). An Assessment of Faulty Public Hospital Design in Malaysia. *Journal of Design and Built* 5(1).
- Marenjak, S., El-Haram, M.A. & Horner, R.M.W (2002). Procjena ukupnih troskova u visokogradnji, *Gradevinar*. 54: p. 393-401.
- Martino, J. P. (1983). *Technological forecasting for decision making*. New York: North-Holland.
- Ma´rquez, A.C. and Herguedas, A.S. (2004). Learning about failure root causes through maintenance records analysis. *Journal of Quality in Maintenance Engineering*. 10(4) pp. 254-62.
- Mayer, P.D. and Brewer, B. (2001). Auditing for durability. *Proceedings of The Whole-Life Performance of Facades, Centre for Window and Cladding Technology, University of Bath, 2001*, Bath, pp. 23-32.
- McQueen and Knussen (2002). *Research Methods for Social Science: A Practical Introduction*. Prentice Hall.
- McKenna, H. P. (1994). The Delphi technique: A worthwhile research approach for nursing? *Journal of Advanced Nursing*, 19, p. 1221-1225.
- McKenna, H. P. (1989). The selection by ward managers of an appropriate nursing model for long-stay psychiatric patient care. *Journal of Advanced Nursing*, 14, p. 762-775.
- Mead, D., and Moseley, L., (2001). The use of Delphi as a research approach. *Nurse Res.* 8(4), pp.4- 23.

- Mills, A., Love P.E.D. and Williams, P. (2009). Defect costs in residential construction. *Journal of Construction Engineering and Management*. 135(1) pp.12-16.
- Mills (1994). *Building maintenance & preservation: a guide to design and management*. 2nd ed. Oxford: Butterworth-Heinemann Ltd.
- Mills, E. D. (1980). *Building Maintenance and Preservation – A Guide to Design and Management*. Butterworths.
- Mohamed, O, F., Nor, M., Abd Karim S. B, and Kho, M.Y. (2007). *The Practice of Life Cycle Costing (LCC) in the Malaysian Construction Industry – Application during Design Stages*. Management in Construction and Researchers Association (MICRA) Meetings and Conference. Shah Alam, Selangor, Malaysia, 28th to 29th August 2007. Malaysia: MICRA. P 1-7.
- Mohd-Noor, N., Hamid, M. Y., Abdul-Ghani, A.A., and, Haron, S.N. (2011). Building Maintenance Budget Determination - An Exploration Study in the Malaysia Government Practice. *Procedia Engineering*. 20 (2011) pp. 435 – 444.
- Mohd Zulakhmar, B. Z. (2006). *Strategic Planning in Maintaining Sports Facilities in Malaysia in Teluk Danga International Games Convention*. Johor, Malaysia.
- Moore, M. & Finch, E. (2004). Facilities management in South East Asia. *Facilities*. 22(9/10) pp. 259-270.
- Mselle, P.C. (1997). *Management of maintenance records and their use in planning*. Proceedings of Fifth International Conference on Inspection, Repairs & Maintenance of Buildings & Structures. pp. 211–15.
- Murry J.W., Hammons J.O., (1995). Delphi: A versatile methodology for conducting qualitative research. *Rev. Higher Educ.* 18(4) pp.423-436.
- Naoum, S. (2007). *Dissertation Research & Writing for Construction Students*. 2<sup>nd</sup> ed. Oxford: Butterworth-Heinemann.
- Nayanthara, D.S et al., (2004), Improving the maintainability of buildings in Singapore. *Journal of Building and Environment*, No. 39, pp. 1243-1251.
- Newsham, G., Mancini, S. and Benjamin, J.B. (2009), “Do LEED-certified buildings save energy? Yes, but”, *Energy and Buildings*, Vol. 41 No. 8, pp. 897–905.
- New Straits Times. (9 September, 2008). No you don't: developer get court injunction to stop residents from “taking over condo” p.



- New Straits Times. (2007, May 4). Cracks Show Up on Jalan Duta Court Complex Wall p14.
- New Straits Times. (2008, August 5). 510 Heritages Building Need Help.
- New Straits Times. (15 September 2008). Dirties among seven nations. p16.
- New Straits Times. (19 September, 2008) 92 Historical Buildings to Be Restored.
- Ngowtanasuwan, G (2012). An Application of Mathematical Model for Decision in Building Plan Design. AicE-Bs2012 Cairo, ASIA Pacific International Conference on Environment-Behaviour Studies Mercure Le Sphinx Cairo Hotel, Giza, Egypt, 31 October 2 November 2012. *Procedia - Social and Behavioral Sciences*. 68 (2012) pp.537 – 548.
- NHS Estate (1996). Re-engineering the facilities management service. *Health Facilities*. Note 16.
- Nicolella, M. (2014). A Methodology for Evaluating Maintainability as a Tool for Durable and Sustainable Buildings. In “13th International Conference on Durability of Building Material and Component”, 2 - 5 Sept 2014, Sao Paulo, Brazil, 1–8. Sao Paulo, Brazil.
- Journal of Nipissing University Research Council (2008). Definition of Research. Nipissing University. Available from: <http://www.nipissingu.ca/research/downloads/DefnofResearchforwebsite.pdf>. [Accessed on 2nd February 2014].
- Nourse, H.O. (1990). *Managerial Real Estate: Corporate Real Estate Asset Management*. USA: Prentice-Hall, Englewood Cliffs.
- Nor Haniza, I., Chohan, A.F. and Ahmad, R. (2007). Implications of design deficiency on Building maintenance at post-occupational stage. *Journal of Building Appraisal*. Vol. 3 (2), pp. 115-24.
- Nutt, B. (2000). Four competing futures for facility management. *Facilities*. 18(3/4) pp.124-132.
- Olbrich, S., Poppelbu, J., and Niehaves, B. (2012). Critical Contextual Success Factors for Business Intelligence: A Delphi Study on Their Relevance, Variability, and Controllability. *45th Hawaii International Conference on System Sciences*. pp. 4148-4157.

- Olubodun, O. F. (1996). An empirical approach to the evaluation of factors in local authority housing maintenance requirements. A Thesis Submitted in partial fulfillment of the Requirements of University of Salford for the degree of Doctor of Philosophy. University of Salford, City of Manchester, Salford, U.K.
- Pasukeviciute, I. and Roe, M. (2000). The politics of oil in Lithuania: strategies after transition, *Energy Policy* 29, p. 383–397.
- Pateman B. (1998). Computer-aided qualitative data analysis: the value of NUD\*IST and other programs. *Nurse Researcher*. 5(3), pp.77-89.
- Peacock (1986). *The Maintenance of Building & Structure*. Municipal Engineer. Vol. 3.
- Peter Lufkin Whitestone Research (2007). *Life Cycle Cost Models for Federal Facilities. Predicting Outcomes from Investments in the Maintenance and Repair of Federal Facilities Board on Infrastructure and the Constructed Environment National Research Council*.
- Powell, C. (2003). The Delphi technique: myths and realities. *Journal of Advance Nursing*. 41(4), pp. 376-382.
- Punch, K.F. (2005). *Introduction to Social Research: Quantitative and Qualitative Approach*. SAGE Publications Limited.
- Ramly, A., Ahmad, N.A. and Ishak, N.H. (2006). The Effects of Design on The Maintenance of Public Housing Buildings in Malaysia – Part One. *Building Engineer*, April, pp. 30-33.
- Ramly, A. (2006). Link between Design and Maintenance. *Builders & Engineers*, Vol. 81 No. 5.
- Rayens, M.K and Hahn, E.J. (2000). Building consensus using the policy Delphi method, *Policy Polit. Nurs. Pract.* 1, pp. 308–315.
- Richardson, B. A. (1991). *Defects and deterioration in buildings*, E&FN Spon, London.
- Rigby, L.V., et al., (1961). *Guide to Integrated System Design for Maintainability*. Report No. ASD-TR-61-424, U.S. Air Force Systems Command, Wright-Patterson Air Force Base, OH.
- Rohana Yusof (2004). *Penyelidikan Sains Sosial*. Bentong: PTS Publications & Distributors.

- Rohrbaugh, J. (1979). Improving the quality of group judgments: social judgment analysis and the Delphi technique. *Organizational Behavior and Human Performance*. Vol. 24, 1979, pp. 73–92.
- Rozita Aris (2006). *Maintenance Factors in Building Design*. Masters Dissertation, Universiti Teknologi Malaysia.
- Ryan, P.A., Wolstenholme, R.P. and Howell, D.M. (1994). *Durability of Cladding: A State of the Art Report*. Thomas Telford, London.
- Saghatforoush, E., Trigunaryyah, B. and Too, E. (2012). Assessment of Operability and Maintainability Success Factors in Provision of Extended Constructability Principles. in *9th International Congress on Civil Engineering, May 8-10, 2012, Isfahan University of Technology, Isfahan, Iran*, pp.1 – 10.
- Sani, U.I.A., Mohammed, A.H., Shukor, F.S.A. and Ezzatul, A. S., (2012). *An Overview Maintenance Culture Determinant Factors*. 3rd International Conference On Business And Economic Research (3rd ICBER 2012). Proceeding Paper. 12 - 13 March 2012. Golden Flower Hotel, Bandung, Indonesia.
- Sapp, D. (2009). *Facilities operation and maintenance*. Whole Building Design Guide, National Institute of Building Sciences, Washington, DC., USA.
- Sarantakos, S. (2005). *Social Research Edn*. Palgrave Macmillan, Basingstoke.
- Saunders, M., Lewis, P., and Thornhill, A. (2009). *Research Methods for Business Students (fifth)*. Pearson Education India.
- Schmidt R.C. (1997) Managing Delphi surveys using nonparametric statistical techniques. *Decision Sciences*. 28, pp.763-774.
- Scheibe, M., Skutsch, M., and Schofer, J. (1975). Experiments in Delphi methodology, in: H.A. Linstone, M. Turoff (Eds.), *The Delphi Method — Techniques and Applications*, Addison-Wesley, Reading, pp. 262–287.
- Seagle, E. and Iverson, M. (2002). Characteristics of the turfgrass industry in 2020: a Delphi study with implications for agricultural education programs, *J South. Agric. Educ. Res.* 52. p. 1–13.
- Seeley, I. H. (1986). *Building technology*. London, UK: Macmillan Education.
- Seeley, I. H. (1976). *Building Maintenance*. Macmillan Press Ltd, London.

- Seeley, I.H. (1987), *Building Maintenance*, Second edition, Macmillan Education, London.
- Sewerage and Drainage Act, Singapore. *Sewerage and Drainage (Sanitary Works) Regulations*. Chapter 294, Section 51 and 74. G.N. No. S167/1000, 1st April 1999, revised edition 2007 (15th May 2007).
- Shabha, G. (2003). A low-cost maintenance approach to high-rise flats. *Facilities*. 21(13/14) pp. 315-22.
- Sharma, D.P., Nair, P.S.C., and Balasubramanian, R., (2003). Analytical search of problems and prospects of power sector through Delphi study: case study of Kerala State India. *Energy Policy*. Vol 31 pp.1245–1255.
- Shelton, F. and Brugh, M (2002). Indirect Costs of Contracts. *Journal of Construction Accounting and Taxation*. pp. 3-9.
- Shen Q, Lo K-K and Wang Q (1998). Priority setting in maintenance management: a modified multi-attribute approach using analytic hierarchy process. *Construction Management and Economics*. 16 pp.693–702.
- Shohet, I. M. (2003). Building Evaluation methodology for setting maintenance priorities in hospital buildings. *Journal of Constr. Manage. Econ.* 21(7) pp.681–692.
- Shohet, I. M., and Perelstein, E. (2004). Decision support model for the allocation of resources in rehabilitation projects. *Journal of Constr. Eng. Manage.* 130(2) pp.249–257.
- Shohet, I. M., Puterman, M., and Gilboa, E. (2002). Deterioration patterns of building cladding components for maintenance management. *Journal of Construction Management. Economy*. 20(4) pp.305–314.
- Silva, N., Ranasinghe, M. and De Silva, C.R (2012). Risk factors affecting building maintenance under tropical conditions. *Journal of Financial Management of Property and Construction*, Vol. 17 No. 3, pp. 235-252.
- Silva, N. and Ranasinghe, M. (2010). Maintainability risks of condominiums in Sri Lanka. *Journal of Financial Management of Property and Construction*, Vol. 15 No. 1, pp. 41-60.

- Silva, N., Dulaimi, M.F., Ling, F.Y.Y. and Ofori, G. (2004). Improving the maintainability of buildings in Singapore. *Building and Environment*, Vol. 39 No. 1, pp. 1243-1251.
- Sivanathan, S., Jibril, J.D., Jivasangeeta, Thanaraju, P., Dodo Y.A. and Shika, S.A. (2012). An Overview of Design Deficiencies on Building Maintenance. *Ontario International Development Agency (OIDA) International Journal of Sustainable Development*. 05:11. pp.105-112.
- Skinner, N.P. (1982). Local authority house maintenance – the variation in expenditure. *Housing Review*. Vol. 31, pp. 92-4.
- Skulmoski, G (2007). The Delphi method for graduate research. *Journal of Information Technology Education*. 6(1), pp.01-2.
- Slavila, C.A., Decreuse, C. and Ferney, M. (2005). Fuzzy Approach for Maintainability Evaluation in the Design Process. *Journal of Concurrent Engineering*, Vol. 13 No. 1, pp. 291-300.
- Slavila, C.A., Decreuse, C., Ferney, M. and Ungureanu, I. (2004). Maintainability Evaluation During the Design Phase. IDMMME 2004, Bath(UK), April 5–7.
- Smith, D.J. and Babb, A.H.,(1973). Maintainability Engineering, John Wiley & Sons, New York.
- Soh, T. C. (1997). Total building performance approach to conservation of buildings. Dissertation, National Univ. of Singapore, Singapore.
- Sommer, R. (1972). Design Awareness. *Monograph on Psychology (General) / Environmental Psychology*, San Francisco, S.N, pp. 142.
- Sommerville, J. (2007). Defects and Rework in New Build: An Analysis of The Phenomenon and Drivers. *Struct. Surv.* 25(5) p. 391–407.
- Sophia, S. (2011). Pegawai Penilaian, Jabatan Penilaian dan Aset, Majlis Perbandaran Johor Bahru Tengah.
- Sterner, E (2000) Life-cycle costing and its use in the Swedish building sector, *Building Research and Information*. 28(5/6), 387-93.
- Stewart, J., O'Halloran, C., Harrigan, P., Spencer, J.A., Barton, J.R. and Singleton, S.J. (1999). Identifying appropriate tasks for the preregistration year: modified Delphi technique, *Br. Med. J.* 319. p.224–229.

- Snyder-Halpern, R., Thompson, C. and Schaffer, J. (2003). Comparison of mailed vs. internet applications of the Delphi Technique in Clinical Informatics Research. Available at: <http://www.amia.org/pubs/symposia/D200120.PDF> Accessed 18th July 2003. [Accessed: April 2014].
- Mohd Sidek, H. (2007). (Chief Secretary to the Government of Malaysia) National Asset and Facilities Management Development. *Special Key Note Address delivered at the National Asset and Facilities Management (NAFAM) Convention, Kuala Lumpur, Malaysia.*
- Tay, L. & Ooi, J.T.L. (2001) Facilities management: a jack of all trades. *Facilities*, 19(10) p.357-362.
- Taylor-Powell, E. (1998). *Questionnaire Design: Asking questions with a purpose.* University of Wisconsin Extension.
- Tesfaye, A. (1997). *A holistic approach towards low maintenance buildings: a case study of sample residential buildings in Botswana.* Proceedings of Fifth International Conference on Inspection, Repairs & Maintenance of Buildings & Structures. pp. 357–79.
- Then, D.S.S. (1999). An integrated resource management view of facilities management. *Facilities*. 17(12/13) p.462-469.
- Thomas, H. & Martin, J. (1996) *Managing Resources for School Improvement* (London, Routledge).
- The Work Health and Safety Act 2011 (2011), “*An Act relating to work health and safety, and for related purposes*”, Australia, pp. 1-146.
- The Star (2007, April 12). Immigration Headquarters Havoc: leak on the seventh floor sends water down five levels pN4.
- The Star. (16 June 2008). Abandoned Quarters Now An Eyesore. pM12
- The Star. (20 April 2007). JB Hospital “sick” again. pN35.
- The New Straits Times. (2008, June 19). Downright Filthy Business p5.
- The Star. (28 August 2008). Residents See Red Over Piping Works. pM6.
- The Star. (22 August 2008). Solution To Stinking Woes In Sight. pM8.
- The Star (2008, June 4). Ambrin Promises Thorough Check: Inspection team to check 94 public buildings pN14.

- The Star (2006, February 20). Ahmad Abdullah Badawi- Billions Wasted to Repair Buildings and Amenities.
- Treasury Task Force (2000). How to Achieve Design Quality in PFI Projects, Technical Note 7. *HMTreasury*, London.
- Uhlik, F. T., and Lores, G. V. (1998). Assessment of constructability practices among general contractors. *Journal of Archit. Eng.* 4(3) p.113–123.
- Underwood, J., and Alshawi, M. (1999). Towards an integrated application for forecasting building element maintenance. *Int. J. Comput. Integrated Design Construction.* 1(1) p.39–48.
- Urbach, N. and Ahlemann, F. (2010). Structural Equation Modeling in Information Systems Research Using Partial Least Squares. *Journal of Information Technology Theory and Application (JITTA)*. Vol. 1, p. 5–40.
- U.S Department of Energy (2011), *Strategic Plan Report*, May 2011, United States, pp. 1-48.
- U.S. Environmental Protection Agency (EPA) and U.S. Department of Energy (DOE), (1999). *Operations and Maintenance Assessments. A Best Practice for Energy Efficient Building Operations*. Prepared with funding from the U.S. EPA and U.S. DOE. Portland Energy Conservation, Inc., Washington, Portland.
- Valerdi, R. (2013). Convergence of Expert Opinion via the Wideband Delphi Method: An Application in Cost Estimation Models.
- Vanier, D.J., Lacasse, M.A. and Parsons, A. (1996). Using product models to represent user requirements. in *CIB Workshop Construction on the Information Highway, Bled, Slovenia, June 10-12, 1996*, pp. 511-524.
- Van Winden, C., and Dekker, R. (1998). Rationalization of building maintenance by Markov decision models: A pilot case study. *J. Oper. Res. Soc.* 49 p.928–935.
- Varcoe, B. (2000). Implications for facility management of the changing business climate. *Facilities*, 18(10/11/12), p. 383-391.
- Vinzi V. E., Chin W.W., Henseler J., and Wang H., editors. (2010). *Handbook of Partial Least Squares: concepts, methods and applications*. Springer-Verlag.
- Waterbury, R. (1985). *Designing Parts for Automated Assembly, Assembly Engineering*. pp. 211–217, February 24–28.

- Williams, P.L. and Webb, C. (1994). The Delphi technique: a methodological discussion, *J. Adv. Nurs.* 19, p. 180–186.
- Whitehead, J.C. (1992). Measuring use value from Recreation Participations. *S.J. Agr Economics.* p.113- 119.
- Whole Building Design Guide (WBDG) (2012). Cost Effective. A Program of The National Institute of Building Sciences. [Online] Available from: [http://www.wbdg.org/design/cost\\_effective.php](http://www.wbdg.org/design/cost_effective.php). [Accessed: 2 December 2013].
- Williamson, A, Williams, C, and Gameson, R (2010). The Consideration of Maintenance Issues during the Design Process in the UK Public Sector. *In Proc "26th Annual ARCOM Conference"*, 6-8 September 2010, 1091–1100. Leeds, UK.
- Wong, P. (2007). Winds of Change: Ensuring Malaysian Builders Win in the Global Race. *Article Master Builders Association Malaysia.* 2nd Quarter. p.54-67.
- Wong, C. W. (1993). Influence of design on maintenance with particular reference to HDB flat. Undergraduate dissertation, National Univ. of Singapore, Singapore.
- Wood, B. (2012). Maintenance Integrated Design and Manufacture of Buildings: Toward a Sustainable Model. *Journal of Architectural Engineering*, Vol.18 No.1, pp. 192-197.
- Wood, B. R. (2009). *Building maintenance*. Oxford, UK: Wiley-Blackwell.
- Wood, B. R. (2007). "Open building maintenance" Open building manufacturing: Core concepts and industrial requirements, M. Hannus, S. Boudjabeur, and A. Malone, eds., Comprehensive Institution Building Programme, European Union (CIB/EU) Manubuild and Technical Research Centre (VTT), Finland.
- Wood, B. R. (2005). Towards innovative building maintenance. *Struct. Surv.* 23(4) p.291–297.
- Wood, B. R. (2003a). Approaching the care-free building. *Facilities.* 21(3–4) p.74–79.
- Wood, B. R. (2003b). *Building care*. Oxford, UK: Blackwell.
- Woodward, D.G. (1997). Life cycle costing-theory, information acquisition and application. *International Journal of Project Management.* 15(6) p.335–44.
- Wordsworth, P. (2001). *Lee's building maintenance management*. 4th Ed., Oxford, UK: Blackwell.



- Wu J. H., Wang S. C., and Lin L. M. (2007). Mobile computing acceptance factors in the healthcare industry: A structural equation model. *International Journal of Medical Informatics*. Vol. 76, p. 66–77, 2007
- Yang, Y.N (2003). Testing the stability of experts' opinions between successive rounds of Delphi studies, Annual Meeting of the American Educational Research Association, Chicago.
- Yin, R. (1984/1994). *Case Study Research: Design and Methods*. Thousand Oaks, London, New Delhi: Sage.
- Yu, W.S. (2003). Accessibility for external facade of buildings. Undergrad B.Sc. (Building) dissertation, School of Design and Environment, National University of Singapore.
- Yousuf, M. (2007). Using Experts' Opinions Through Delphi Technique. *Practical Assessment Research & Evaluation*. Vol 12 (4), pp. 01-08.
- Zainal Abidin, A.C. and Roslan, A. (2006). Maintenance management process model for school buildings': An application of IDEF0 modeling methodology', in Utama, W.P. and Peli, M. (eds). *International Conference on Construction Industry 2006*, 21–24th June, 2006, Indonesia, Padang, pp. 81–87. Available From: [www.fab.utm.my/download/conference seminar. icci 200681pp12.pdf](http://www.fab.utm.my/download/conference_seminar_icci_200681pp12.pdf). [Accessed on: 12 January 2014].
- Zhong, L. and Youchao, S. (2006). Research on Maintainability Evaluation Model Based on Fuzzy Theory. *Chinese Journal of Aeronautics*. 20 p. 402-407.
- Zinn, J., Zalokowski, A., and Hunter, L., (2001). Identifying indicators of laboratory management performance: a multiple constituency approach. *Health Care Manage. Rev.* 26 p.40–53.
- Zuhairuse, M., Ahmad, R., Adi-Irfan, C. and Norngainy, M. (n.d.). Correlational study between facilities management components of multi-ownership housing in Malaysia: a case study of Klang Valley. Available From: <http://www.fab.utm.my/download/ConferenceSemiar/ICCI2006S1PP08.pdf>. [Accessed on 12th March, 20013].