

NON-INTRUSIVE LOAD MANAGEMENT SYSTEM FOR RESIDENTIAL LOADS
USING ARTIFICIAL NEURAL NETWORK BASED ARDUINO
MICROCONTROLLER

ISYAKU ABUBAKAR

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

APRIL 2018

I dedicated this thesis to my mother Hajiya Aishatu Ishaq and my father Alhaji Abubakar Ibrahim for their tireless efforts in ensuring my good upbringing through support, guidance and unlimited prayers. May their soul rest in perfect peace and may Allah grant them Jannatul Firdausi. This dedication is also extended to my late wife Asiya Kabir Suyudi, may her soul rest in perfect peace and may she be granted the Jannatul Firdausi by the almighty Allah. My entire family will also be covered in the reward of this work specifically my wife Binta Kabir, my children Asiya Ishaq, Ibrahim Ishaq, Abubakar Ishaq and Ishaq Ishaq. May Allah assists us in giving you a very good upbringing and may all of us be among those that the prophet peace be upon him will be happy with in the day of judgment.

ACKNOWLEDGEMENT

All praise be to almighty Allah, the most merciful for his guidance in successful completion of my PhD research work. My sincere thanks and appreciations to my supervisor Dr. Saifulnizam Bin Abd. Khalid for his support, guidance, encouragement and patient throughout the research activities. His dedication, support, advice and technical expertise are the key elements to the succesful completion of my doctoral research work. Moreover, I would like to extend my gratitudes to my co-supervisor Prof. Ir. Dr. Mohd Wazir bin Mustafa for his motivations, guidance, encouragement and patience to attend my numerous research challenges. Furthermore I would like to express my appreciation to Associate Prof. Dr. Hussain Shareef for his advices and contributions in the research work. I thank you all for your valuable contributions and may almighty Allah rewards you abundantly.

My appreciation also goes to the technical staff of Power System Lab for observing their various duties in the coordination of the Laboratory activities. I am also grateful to all my research colleagues, especially Mamunu Mustapha, Saleh Y. Abujarad, Mudasiru Mustapha, Jalal, Ameer, Sani Salisu, Raja Masood, Mohammed Olatunji, Abdurrahman Otoze and many others, for their valuable advices and encouragements. Same appreciation goes to all my my friends and colleagues who have been here during our program. The support by Bayero University, Kano and TETFUND is also very much appreciated. Finally, I wish to express honest gratitueds to my parents and my entire relatives for their various supports and prayers. The support and encouragements by my Family is also appreciated specifically my wife Binta Kabir and my children Asiya, Ibrahim, Abubakar and Ishaq. The scrafice made to me by Asiya Ishaq and Ibrahim Ishaq is highly appreciated, may Allah make them great in their future endavours and the entire family, ameen.

ABSTRACT

The energy monitoring is one of the most important aspects of energy management. In fact there is a need to monitor the power consumption of a building or premises before planning technical actions to minimize the energy consumption. In traditional load monitoring method, a sensor or a group of sensors attached to every load of interest to monitor the system, which makes the system costly and complex. On the other hand, by Non-Intrusive Load Monitoring (NILM) the aggregated measurement of the building's appliances can be used to identify and/or disaggregate the connected appliances in the building. Therefore, the method provides a simple, reliable and cost effective monitoring since it uses only one set of measuring sensors at the service entry. This thesis aims at finding a solution in the residential electrical energy management through the development of Artificial Neural Network Arduino (ANN-Arduino) NILM system for monitoring and controlling the energy consumption of the home appliances. The major goal of this research work is the development of a simplified ANN-based non-intrusive residential appliances identifier. It is a real-time ANN-Arduino NILM system for residential energy management with its performance evaluation and the calibration of the ZMPT101B voltage sensor module for accurate measurement, by using polynomial regression method. Using the sensor algorithm obtained, an error of 0.9% in the root mean square (rms) measurement of the voltage is obtained using peak-peak measurement method, in comparison to 2.5% when using instantaneous measurement method. Secondly, a residential energy consumption measurement and control system is developed using Arduino microcontroller, which accurately control the home appliances within the threshold power consumption level. The energy consumption measurement prototype has an accurate power and current measurement with error of 3.88% in current measurement when compared with the standard Fluke meter. An ANN-Arduino NILM system is also developed using steady-state signatures, which uses the feedforward ANN to identify the loads when it received the aggregated real power, rms current and power factor from the Arduino. Finally, the ANN-Arduino NILM based appliances' management and control system is developed for keeping track of the appliances and managing their energy usage. The system accurately recognizes all the load combinations and the load controlling works within 2% time error. The overall system resulted into a new home appliances' energy management system based on ANN-Arduino NILM that can be applied into smart electricity system at a reduced cost, reduced complexity and non-intrusively..

ABSTRAK

Pemantauan tenaga adalah salah satu aspek yang paling penting dalam pengurusan tenaga. Malah, terdapat keperluan untuk memantau penggunaan kuasa sebuah bangunan atau premis sebelum merancang tindakan teknikal untuk meminimumkan penggunaan tenaga. Dalam kaedah pemantauan beban tradisional, satu pengesan atau sekumpulan pengesan dipasangkan kepada setiap beban untuk pemantauan sistem, yang menjadikan sistem itu mahal dan kompleks. Sebaliknya, dengan Pemantauan Bebanan Tidak Robos (NILM) pengukuran teragregat peralatan bangunan boleh digunakan untuk mengenal pasti dan/atau mengasingkan peralatan yang bersambung di bangunan. Oleh itu, kaedah ini menyediakan pemantauan yang mudah, boleh dipercayai dan kos efektif kerana hanya menggunakan satu set pengesan pengukur pada kemasukan perkhidmatan. Tesis ini bertujuan mencari penyelesaian dalam pengurusan tenaga elektrik kediaman melalui pembangunan sistem yang tidak robos untuk memantau dan mengawal penggunaan tenaga peralatan rumah. Matlamat utama penyelidikan ini adalah pembangunan pengenal pasti peralatan kediaman berasaskan Rangkaian Neural Tidak Robos dipermudah. Sistem Rangkaian Neural Buatan (ANN)-Arduino (NILM) adalah masa nyata dalam pengurusan tenaga kediaman dengan penilaian prestasi dan penentuan modul pengesan voltan ZMPT101B untuk pengukuran yang tepat, dengan menggunakan kaedah regresi polinomial. Dengan menggunakan algoritma pengesan yang diperolehi, ralat 0.9% dalam pengukuran voltan punca min kuasa dua (rms) diperolehi menggunakan kaedah pengukuran puncak ke puncak, berbanding 2.5% dengan kaedah pengukuran ketika. Keduanya, sistem pengukuran dan kawalan penggunaan kediaman dibangunkan menggunakan mikropengawal Arduino, yang mengendalikan peralatan rumah secara tepat di dalam tahap penggunaan kuasa ambang. Prototaip pengukuran penggunaan tenaga mempunyai pengukuran kuasa dan arus yang tepat dengan ralat 3.88% dalam pengukuran arus apabila dibandingkan dengan meter piawai Fluke. Sistem ANN-Arduino NILM juga dibangunkan menggunakan signatur keadaan mantap, yang menggunakan ANN suap hadapan untuk mengenalpasti beban apabila menerima kuasa sebenar teragregat, arus rms dan faktor kuasa daripada pada Arduino. Akhir sekali, ANN-Arduino NILM berasaskan sistem pengurusan dan kawalan peralatan dibangunkan untuk mengesan peralatan dan menguruskan penggunaan tenaga mereka. Sistem ini mengenal sepenuhnya dengan tepat semua kombinasi beban dan kawalan kerja beban dalam ralat masa 2%. Sistem keseluruhannya menghasilkan sistem pengurusan tenaga elektrik rumah yang baru berdasarkan ANN-Arduino NILM yang boleh diaplikasikan untuk sistem elektrik pintar dengan kos yang dikurangkan, mengurangkan kerumitan dan tidak robos.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	Error! Bookmark not defined.
	DEDICATION	vi
	ACKNOWLEDGEMENT	vii
	ABSTRACT	viii
	ABSTRAK	ix
	TABLE OF CONTENTS	x
	LIST OF TABLES	xv
	LIST OF FIGURES	xvii
	LIST OF ABBREVIATIONS	xix
	LIST OF SYMBOLS	xxi
	LIST OF APPENDICES	xxii
1	INTRODUCTION	1
	1.1 Background	1
	1.2 Problem Statement	3
	1.3 Objectives of the Research	5
	1.4 Scopes of the Research	5
	1.5 Significance of the Research	6
	1.6 Thesis Organization	7
2	LITERATURE REVIEW	8
	2.1 Introduction	8
	2.2 The Load Monitoring Concept	9
	2.2.1 Traditional Load Monitoring	10
	2.2.2 The Emergence of Non-Intrusive Load Monitoring	10
	2.3 The Electrical Load Monitoring of Appliances	11

2.4 The Load Signature	11
2.4.1 Classification of Load Signatures	13
2.4.1.1 Intrusive Signatures	13
2.4.1.2 Non-Intrusive Signatures	14
2.5 Load Monitoring Devices	15
2.5.1 Measuring Devices	16
2.5.2 Communication Devices	16
2.5.3 Soft Computing Devices	18
2.5.4 Control Device	18
2.5.5 Recognition Devices	19
2.5.6 Display Devices	19
2.6 Intrusive Load Monitoring	20
2.6.1 The ILM Framework	22
2.6.1.1 Activity of Daily Living Recognition	22
2.6.1.2 Occupancy Detection	23
2.6.1.3 User-Appliance Interaction	23
2.6.2 The ILM Structure	23
2.6.3 An Overview of Some ILM Research Works	25
2.7 Non-Intrusive Load Monitoring	28
2.7.1 NILM Framework	32
2.7.1.1 Data Acquisition	33
2.7.1.2 Feature Extraction	34
2.7.1.3 Appliance Classification	34
2.8 NILM Disaggregation and Identification Approaches	34
2.8.1 Steady-State Approaches	35
2.8.2 Transient-State Approaches	37
2.8.3 Approaches Based on Hybrid Analysis	39
2.8.4 Approaches Using Non-traditional Signature Analysis	40
2.9 Event based and Non-event based Detection in NILM	40
2.10 Artificial Intelligent Learning in NILM	41
2.10.1 Supervised Learning	42
2.10.2 Unsupervised Learning	42
2.11 NILM Reviews	43

2.12	General NILM Applications and Future Research Directions	44
2.13	Application of Load Monitoring in Appliances' Energy Management and Control	46
2.13.1	Energy Management Approaches Based on ILM	47
2.13.2	Energy Management Approaches Based on NILM	51
2.14	Energy Savings Techniques for Minimizing Power Consumption.	55
2.15	AC Voltage Measurement Methods	57
2.15.1	Peak Value Method	58
2.15.2	Peak to Peak Value Method	58
2.15.3	Instantaneous Calculation Method	58
2.16	The Regression Analysis	59
2.16.1	Linear Regression	59
2.16.2	Polynomial Regression	60
2.17	Summary	61
3	RESEARCH METHODOLOGY	63
3.1	Introduction	63
3.2	Load Selection and Profiling of the Home Appliances	64
3.3	Sensors Calibration	66
3.3.2	Voltage Sensor Calibration	67
3.3.2.1	Peak to Peak Voltage Measurement Method	68
3.3.2.2	Instantaneous Voltage Measurement Method	69
3.3.2.3	Data Collection and Regression Procedure	69
3.3.2.4	The Programing Code for the Voltage Sensor Calibration	71
3.4	Residential Appliances consumption Measurement and control	71
3.4.1	Appliances Energy Consumption Measurement and Control System Design	73
3.4.2	System Development	74
3.4.3	Energy Measurement and Control Programming Code	75

3.5 Design of the Non-Intrusive Appliance Load Identification System	76
3.5.1 Energy Consumption Data Collection for the NILM System	77
3.5.2 The ANN Training for the NILM System	79
3.5.3 The Arduino Programming for the ANN-NILM System	80
3.6 Development of ANN-Arduino NILM based Residential Appliances Management and Control System	82
3.6.1 Data Collection for the Appliances Management and Control System	84
3.6.2 ANN Training for the Appliances Management and Control System	86
3.6.3 Arduino Programming for the Appliances Management and Control System	86
3.7 Summary	88
4 RESULTS AND DISCUSSIONS	89
4.1 Introduction	89
4.2 The Sensors Calibration	89
4.2.1 The Current sensor Results	90
4.2.2 Calibration of the Voltage Sensor	90
4.2.1 Resulted Polynomial Equations	91
4.2.2.1 The Instantaneous Voltage Method Analysis	92
4.2.2.2 The Peak to peak Voltage Method Analysis	94
4.2.2.3 Comparison between the Instantaneous Method and Peak to Peak Voltage Method and General Analysis	94
4.3 Residential Electrical Energy Consumption Measurement and control system	99
4.3.1 Measurement Analysis of the System	99
4.3.1.1 Voltage Measurement	100
4.3.1.2 Current Measurement	102

4.3.1.3 Power Measurement	102
4.3.3 The Loads Control of the System	103
4.3.4 The System Control when the Highest Priority Load is Greater than the Threshold	104
4.3.5 General Analysis	108
4.4 Development of the Non-Intrusive Appliances Identification System	108
4.4.1 The ANN Training Results of the NILM System	108
4.4.2 The Network Simulation Results	110
4.4.3 System Performance	112
4.4.4 General Analysis	112
4.5 The ANN-Arduino NILM based Residential Appliances Management and Control System	114
4.5.1 ANN Training Results of the Appliances Management and Control System	114
4.5.2 Network Simulation and Testing	116
4.5.3 Comparison with Previous Work	118
4.5.4 Load Monitoring Performance of the Appliances Management and Control System	119
4.5.5 Appliances' Timing and Load Control Performance of the System	119
4.5.6 System Analysis	120
4.6 Comparison of the ANN-Arduino NILM with Support Vector Machine (SVM)	121
4.7 Summary	121
5 CONCLUSIONS AND RECOMMENDATIONS FOR FUTURE WORK	124
5.1 Conclusions	124
5.2 Recommendations for Future Work	125
5.3 Research Contributions	126
REFERENCES	128
Appendices A – G	148 – 155

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Comparison of Communication Methods	17
2.2	Some Key Studies of Energy Management in ILM	49
2.3	Some Key Studies of Energy Management in NILM	54
3.1	The home appliances and their power consumption	65
3.2	The Sample of the Data for one Combination of loads	79
3.3	The Data Distribution for the ANN-NILM system	80
3.4	Pseudo code for the ANN-Arduino NILM	82
3.5	Sample of the Data for a combination of Loads	85
3.6	Data breakdown for the ANN-Arduino appliances management	86
3.7	Pseudo code for the ANN-Arduino NILM appliances management system	88
4.1	The Current Sensor Parameters	90
4.2	Equations from the Polynomial Regression Analysis	91
4.3	Arduino Voltage Measurement Using Instantaneous Method	93
4.4	Arduino Voltage Measurement Using Peak to peak Method	95
4.5	Comparison of the Peak to peak and Instantaneous Methods	96
4.6	Comparison of the Voltage Measurement with Miron Alexe Method [197]	98
4.7	System Voltage Measurement and its Comparison with Commercial Meter	101
4.8	Current measurement of the system	102
4.9	Power measurement of the system	103
4.10	The Loads Control of the System	1055
4.11	The Summary of the ANN for Non-Intrusive Appliances Identification	109
4.12	The System performance	113
4.13	Summary of the ANN for ANN-Arduino NILM based Appliances Management and Control System	115

4.14	The Appliances Timing by the System	120
------	-------------------------------------	-----

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Appliance Signature Classification	14
2.2	Energy Monitoring Devices	20
2.3	Intrusive Load Monitoring	21
2.4	The ILM Approach	24
2.5	Overlapping Cluster in $\Delta P - \Delta Q$ plane	31
2.6	Configuration of NILM System	32
2.7	The NILM Approach	33
2.8	V-I Trajectory of some group of loads	36
2.9	Transient Waveform	38
2.10	Global GHG Emission	53
2.11	AC Supply quantities changing with time	57
3.1	The flowchart for implementation of the research work	64
3.2	The block diagram of the ANN-Arduino system	66
3.3	Analog and Digital Voltages	68
3.4	Flow Chart of the rms Voltage Calculation	72
3.5	The Proposed Block Diagram of the Energy Consumption Measurement and Control System	74
3.6	Flow chart of the Energy Consumption Measurement and Control System	76
3.7	The Block Diagram of the ANN-Arduino NILM Configuration	78
3.8	Flow chart of the ANN-Arduino NILM system	81
3.9	Block diagram of ANN-Arduino appliances management system	85
3.10	The ANN-Arduino NILM Network Training Flowchart	87

4.1	The response of the instantaneous and peak to peak voltage methods when compared with FLUKE meter readings (A) The whole voltage range (B) Section of the graph	97
4.2	Comparison of Voltage Measurement	100
4.3	The Trained ANN for the Non-Intrusive Load Identification system	110
4.4	The Network Simulation Result	111
4.5	The Result of Testing the Network	112
4.6	The Trained ANN for the Load Controlling System	115
4.7	The Network Simulation Result	1177
4.8	The Result of Testing the Network with Different Data	118

LIST OF ABBREVIATIONS

AC	-	Alternating Current
ADC	-	Analog to Digital Conversion
ADL	-	Activity of Daily Living
AFAMAP	-	Additional Factorial Approximate MAP
AIA	-	Artificial Immune Algorithm
ANN	-	Artificial Neural Network
BEMS	-	Buildings Energy Management System
CCTV	-	Closed Circuit Television
CFL	-	Compact Fluorescent Lamp
CT	-	Current Transformer
CVD	-	Continuously Varying Devices
CW	-	Current Waveform
DC	-	Direct Current
DENs	-	Distributed Electricity Networks
DMPR	-	Disjoint Multi Path base Routine
DR	-	Demand Response
DWT	-	Discrete Wavelet Transform
ECM	-	Energy Control Manager
EIG	-	Eigen Values
EM	-	Energy Management
EMCUs	-	Energy Management Control Units
EMS	-	Energy Management System
ESD	-	Edge Symbol Detector
EMPT	-	Electromagnetic Transient Program
FHMM	-	Factorial Hidden Markov's Model
FPGA	-	Field Programmable Gate Array
GHG	-	Greenhouse Gas
GMM	-	Gaussian Mixture Model

HAR	-	Harmonics
HEMS	-	Home Energy Management System
HMM	-	Hidden Markov's Model
IAW	-	Instantaneous Admittance Waveform
iHMES	-	In-Home Energy Management System
ILM	-	Intrusive Load Monitoring
IPW	-	Instantaneous Power Waveform
IR	-	Infrared
k-NN	-	k – Nearest Neighbour rule
LED	-	Light Emitting Diode
LDR	-	Light dependent Resistor
MAP	-	Maximum A posteriori Probability
NBC	-	Naïve Bayes Classifier
NILM	-	Non-Intrusive Load Monitoring
OREM	-	Optimization-based Residential Energy Management
PC	-	Personal Computer
PCAT	-	Power Conservation Analysis Tool
PLC	-	Power Line Communication
PSO	-	Particle Swarm Optimization
PT	-	Potential Transformer
rms	-	root mean square
RMSE	-	Root Mean Square Error
ROC	-	Receiver Operating Characteristic
SDM	-	Supply Demand Matching
SoC	-	System on Chip
STFT	-	Short Term Fourier Transform
STW	-	Switching Transient Waveform
SVM	-	Support Vector Machine
TPW	-	Transient Power Waveform
USD	-	United States Dollar
USEPA	-	United State Environmental Protection Agency
WLAN	-	Wireless Area Networks
WMRA	-	Wavelet Multi-Resolution Analysis
ZEM	-	Zigbee Energy Meter

LIST OF SYMBOLS

I	-	Current
I_{ADC}	-	ADC current
I_{ADCref}		Reference ADC current value
I_i	-	Sampled Current
I_{peak}	-	Peak Current
$I_{peak-peak}$	-	Peak to Peak Current
I_{rms}	-	Root Mean Square Voltage
j	-	Order of a Polynomial
$L1$ to $L4$	-	House Appliances
n	-	Total number of samples
P	-	Power
pf	-	Power Factor
S	-	Apparent Power
Q	-	Reactive Power
U_T	-	Total Transient Energy
V	-	Voltage
V_i	-	Sampled Voltage
V_{peak}	-	Peak Voltage
$V_{peak-peak}$	-	Peak to Peak Voltage
V_{rms}	-	Root Mean Square Voltage
x	-	Independent variable
y	-	Dependent variable
δ	-	Sensitivity of current sensor

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	List of Publications	148
B	Table of Equations for Electrical Quantities	150
C	The System of Residential Appliances	151
D	The Voltage Measurement Experimental Set Up	152
E	The Monitoring and Management System	153
F	The Load Identification for ANN-Arduino NILM based Appliances Management and Control	154
G	The Appliances Control of the ANN-Arduino NILM System	155

CHAPTER 1

INTRODUCTION

1.1 Background

The usage of electricity at home has since become an essential activity in both rural and urban settings throughout the world. Every now and then the demand of electricity is increasing. New electrical devices and appliances are always emerging at the expense of the users, for they have to be paying the utility companies for operating those devices. However through proper usage, a lot of benefits can be achieved by both the consumers and electrical utility companies [1, 2]. Those benefits, which include energy saving and reduction in greenhouse gas emission will surely come as the results of proper monitoring and management of the power usage.

The appliance load monitoring is the prerequisite activity to every load management, in fact it is through proper monitoring that a management decision can be taken on the connected loads to make the best utilization of the energy. This therefore calls for a system that can monitor the appliances and takes a real time action to manage the energy usage [3-6]. The largest amount of electrical energy sources at global level is from oil and gas sector, which are non-renewable in nature and are estimated to exhausted in the near future. Hence the load monitoring with the view of managing and optimizing the sources is essential in order to reduce the risk of energy crises in the world, by taking energy management actions on the monitored loads. Over the last three decades, the non-intrusive load monitoring has witnessed so many contributions by the researchers in all angles of the research area [7-12]. Some of the works attempted to come out with systems for load controls [13, 14]. Several ways of

identifying the connected loads non-intrusively, have existed which include steady-state and transient-state methods of signature extraction [15-17]. Using the steady-state signatures for identifying the home electrical appliances in real time will be more suitable because most of the appliances' operation is in steady-state; therefore a steady-state system can go with the real time load identification of the loads [18]. Previous studies in Non-Intrusive Load Monitoring (NILM) have also indicated the need to use it in energy management of the appliances [2, 19].

The NILM system can be applied in many energy consuming systems to facilitate energy management. For instance, the NILM system can determine the load schedule in an aircraft or motor vehicle from the measurement at the generator level [20-23]. With proper NILM system which is powered by energy consumption data feedback, a very significant saving can be achieved, in fact energy minimization of up to 15% can be achieved from the world wide perspective through changing daily routine of the appliances, low cost stake holding and acquiring more efficient and energy saving electrical appliances [24, 25]. Researchers in the area of energy management pointed out that due to globalization and urbanization of the rural areas, the electricity demand can only be contained by appropriate and efficient energy usage and management [26-28]. Moreover, another analysis found that the residential settings can waste one-third of their energy consumption due to unmonitored operations of various appliances [26].

The home automation through NILM has also been found very useful in helping elderly people to sustain their lifestyle with respect to home daily activities [19]. Also the advances in computer technology, sensor technology and communication facilities will give opportunities for researchers and energy management equipment manufacturers to device many ways of monitoring and managing the load energy consumption [29, 30].

Most of the residential electrical energy management research works are intrusive in nature, which suffers from the weakness of multiple point sensing. The NILM researchers have done a lot in appliances disaggregation and signature extraction, but the NILM systems with real-time energy management capability have

not been treated in the research area. The issue of measuring the performance of NILM is another challenging area of NILM, that is why most of the NILM works use distributive metering to check the performance of the systems [2, 31]. This research work focuses on the development of ANN-Arduino based NILM system in order to develop a single point sensing energy management system to replace the existing multiple points sensing systems. The research will also bridge the gap of non-application of the NILM in real-time residential electrical energy management. Moreover, the evaluation of the ANN-NILM in residential appliances control will be a novel method of measuring the performance of NILM,

1.2 Problem Statement

There is need for accurate, simple and cost effective monitoring and management system in all aspects of electrical power consumption. The electrical power consuming system suffers a lot of energy wastage whether at commercial, industrial or residential settings. The residential settings are prominent in energy wastage due to mismanagement, energy unwanted activities and lack of proper load control. The existing researches on home energy management proposed many works on distributed or intrusive load monitoring for home appliances' management [32-34]. However intrusive load monitoring requires sensors or meters at every load of interest, which makes it complex and costly. On the other hand there are many research works regarding the non-intrusive load monitoring which uses one set of measuring devices at the service entry. Though some of these researches are related to the energy management [35-37], but the studies have reputed the need to have an improved real-time NILM for home appliances management at reduced cost and complexity. Various techniques of NILM had been brought up by the researchers that discovered a lot regarding the load identification accuracy, signature extraction and different identification algorithm [38-41], however there is hardly in the literature the use of steady-state NILM technique for residential electrical energy management especially using ANN-Arduino microcontroller based. The use of ANN-Arduino based NILM system for residential energy management will systematically solve the problem of multiple point sensing in ILM and eventually resulted into a cost effective and simple

residential energy management using NILM, which will promote the present smart electricity system. The following summarises the problems in the efforts to promote the residential appliances energy management using ANN-Arduino NILM.

- The present residential energy management systems all concentrated on the distributed sensing for controlling the loads. This not only make the system complex and costly, but also affects the reliability of the appliances management as the results of system dependent on multiple sensing. The introduction of single point ANN-Arduino based NILM has vital role to play in ensuring a reliable energy management system.
- Using the steady-state load signatures to identify the appliances will provide more identification accuracy because the steady-state condition is the dominant stage of the load operation [31]. Also the ANN has a great capability of mapping the the load signatures into the load identification even with non-linear relationship between them.
- The Arduino microcontroller takes samples from voltage and current sensors to calculate the steady-state quantities of the appliances consumption. Hence there is need to ensure accurate calibration of the sensors, especially the ZMPT101B voltage sensor module which does not have a single sensitivity like the ACS716 current sensor. The calibration of ZMPT101B voltage sensor will provide a universal transfer equation for the sensor.
- There is need to evaluate the ANN-NILM system to see its capability in controlling the home appliances for energy management.

The system can be integrated into smart electricity system to serve as smart home energy monitoring and management system for efficient power consumption. The non-intrusiveness of the NILM system ensures the privacy of the consumers because it can be applied outside the building at meter level.

1.3 Objectives of the Research

The objectives of the research are:

- (i) To develop a real-time ANN- Arduino microcontroller based NILM system for home appliances energy consumption management with energy savings capability.
- (ii) To develop a simplified ANN-based non-intrusive load identifier for home appliances' identification using steady-state load signatures.
- (iii) To develop the voltage sensor algorithm, using polynomial regression analysis for direct and accurate application in the Arduino microcontroller
- (iv) To evaluate the performance of the ANN-NILM system in load controlling applications.

1.4 Scopes of the Research

The scope of the research work are bounded as follows:

- (i) The research work targeted monitoring and management of residential electrical appliances for energy savings.
- (ii) The research work will involve the use of single point measurement, in NILM, to identify the appliances instead of multipoint sensing.
- (iii) Steady-state signatures of the loads, which comprises of the real power, rms current and power factor, with acceptable accuracy, are used in the load identification.
- (iv) ANN model of the load identifier will be developed using MATLAB.
- (v) Arduino microcontroller, current and voltage sensors will be used to develop the system and the ANN model will be implemented in the Arduino.
- (vi) The voltage sensor (ZMPT101B module) is calibrated while a factory settings of the current sensor (ACS716) is used.

The ANN-Arduino NILM presented in this research work is limited to some home appliances consisting of Electric bulbs, Standing fans, Electric toaster, Rice cooker, Electric kettle and Blender. Some other appliances like the continuously varying loads are not considered. Also all the experiments are carried out under the standard voltage supply of Malaysia (240V 50Hz), therefore it may have different performance in different voltage supply scenario like 120V or 110V systems.

1.5 Significance of the Research

Non-Intrusive Load Monitoring is a developing research area with ongoing research activities taking place in the area. The application of modern technology in electrical appliance load monitoring and management will revolutionize the energy consumption so that the consumers will make the best use of the power supply. The significance of this research include but not limited to the following:

- (i) Improvement in load monitoring, control and load management will make significant improvement and advancement in smart electricity system.
- (ii) The sub metering energy monitoring, which involves the monitoring of the appliances in sub groups will benefit immensely from the positive contribution of this research work.
- (iii) The research work will provide an alternative way of ascertaining the home appliances operating conditions non-intrusively.
- (iv) Researches in load identification using NILM contribute immensely in the load monitoring area, which will subsequently facilitate the best economical and efficient electricity consumption.
- (v) The method of residential electrical energy management emanated from this research will be beneficial to the consumers, utility companies, regulatory bodies and all the stakeholders in the nation. As such, the electrical energy monitoring and management is the key factor in conserving the energy resources.

- (vi) The ANN-Arduino NILM system also has the advantage that it can be applied outside the building where the appliances are working. This will allow the system to be accessed without disturbing the customer privacy.

1.6 Thesis Organization

The remaining parts of the thesis structure are organized as follows;

Chapter 2 presents an extensive literature review of techniques and methods of NILM which includes signature extraction, disaggregation and identification techniques. It also includes a general literature about ILM techniques and their applications. The chapter also highlights the application of load monitoring in appliances energy management including some of the future research directions.

In Chapter 3 the research methodology is explained, which provides the step by step methods of conducting the research work. It includes the sensor calibration, load monitoring and load controlling systems design.

Chapter 4 provides the results and discussion of the research work. The results of ZMPT101B voltage sensor calibration, the residential energy consumption management using Arduino microcontroller and the results of the non-intrusive load identification based on ANN-Arduino are given in the chapter. It finally presents the results of ANN-NILM evaluation.

The conclusion of the various aspects of the research and recommendations are given in Chapter 5 which also includes the recommendations for future works.

REFERENCES

- [1] Yung Fei, W., Ahmet Sekercioglu, Y., Drummond, T. and Voon Siong, W. (2013). Recent approaches to non-intrusive load monitoring techniques in residential settings. *IEEE 2013 IEEE Symposium on Computational Intelligence Applications In Smart Grid (CIASG)*. IEEE: 73-79.
- [2] Zoha, A., Gluhak, A., Imran, M. A. and Rajasegarar, S. Non-intrusive load monitoring approaches for disaggregated energy sensing: A survey. *Sensors*. 2012. 12(12): 16838-16866.
- [3] Chang, H.-H. Load identification of non-intrusive load-monitoring system in smart home. *WSEAS Transactions on Systems*. 2010. 9(5): 498-510.
- [4] Das, S., Srikrishna, S., Shukla, A., Harsha, G. and Deb, S. (2013). A low-cost non-intrusive appliance load monitoring system. *IEEE 2013 3rd International Advance Computing Conference (IACC)*. IEEE: 1641-1644.
- [5] Ali, M., Yousaf, A. and Usman, F. (2017). Designing and simulation of load control & monitoring system through Demand Side Management technique. *IEEE 2017 8th International Renewable Energy Congress (IREC)*. IEEE: 1-4.
- [6] Nielsen, J. J., Ganem, H., Jorguseski, L., Alic, K., Smolnikar, M., Zhu, Z., Pratas, N. K., Golinski, M., Zhang, H. and Kuhar, U. Secure Real-Time Monitoring and Management of Smart Distribution Grid using Shared Cellular Networks. *IEEE Wireless Communications*. 2017. 24(2): 10-17.
- [7] Hart, G. W. Nonintrusive appliance load monitoring. *Proceedings of the IEEE*. 1992. 80(12): 1870-1891.
- [8] Marceau, M. L. and Zmeureanu, R. Nonintrusive load disaggregation computer program to estimate the energy consumption of major end uses in residential buildings. *Energy Conversion and Management*. 2000. 41(13): 1389-1403.
- [9] Bijker, A. J., Xia, X. and Zhang, J. (2009). Active power residential non-intrusive appliance load monitoring system. *IEEE 2009 AFRICON*. IEEE: 1-6.
- [10] Hosseini, S. S., Agbossou, K., Kelouwani, S. and Cardenas, A. Non-intrusive load monitoring through home energy management systems: A comprehensive review. *Renewable and Sustainable Energy Reviews*. 2017. 79: 1266-1274.

- [11] Yang, C. C., Soh, C. S. and Yap, V. V. A non-intrusive appliance load monitoring for efficient energy consumption based on Naive Bayes classifier. *Sustainable Computing: Informatics and Systems*. 2017. 14: 34-42.
- [12] Wu, X., Han, L., Wang, Z. and Qi, B. A nonintrusive fast residential load identification algorithm based on frequency-domain template filtering. *IEEE Transactions on Electrical and Electronic Engineering*. 2017. 12(S1).
- [13] Ninad Khandekar, N. P., Kalpak Thube and Dr. P. B. Mane. Non-Intrusive Appliance Load Monitoring System Using Zigbee Protocol. *International Journal of Engineering Research & Technology (IJERT)*. 2014. 3(4): 2415-2417.
- [14] Nguyen, T. K., Dekneuveel, E., Jacquemod, G., Nicolle, B., Zammit, O. and Nguyen, V. C. Development of a real-time non-intrusive appliance load monitoring system: An application level model. *International Journal of Electrical Power & Energy Systems*. 2017. 90: 168-180.
- [15] Chang, H.-H. Non-intrusive demand monitoring and load identification for energy management systems based on transient feature analyses. *Energies*. 2012. 5(11): 4569-4589.
- [16] Feng, C. Y., Hoe, H. M., Abdullah, M. P., Hassan, M. Y. and Hussin, F. (2013). Tracing of energy consumption by using harmonic current. *IEEE 2013 Student Conference on Research and Development (SCOReD)*, *IEEE*: 444-449.
- [17] Jimenez, Y., Duarte, C., Petit, J., Meyer, J., Schegner, P. and Carrillo, G. Steady state signatures in the time domain for nonintrusive appliance identification. *Ingeniería e Investigación*. 2015. 35(1): 58-64.
- [18] Wichakool, W (2011). *Advanced nonintrusive load monitoring system*. PhD Thesis. Massachusetts Institute of Technology.
- [19] Valero Pérez, M. N. (2011). *A non-intrusive appliance load monitoring system for identifying kitchen activities*. PhD Thesis. Aalto University - School of Electrical Engineering, Espoo, Finland.
- [20] Christopher Laughman, K. L., Robert Cox, Steven Shaw, Steven Leeb, Les Norford, and Peter Armstrong. Power Signature Analysis. *IEEE Power & Energy*. 2003. 99(2): 56-63.
- [21] Cox, R. W., Bennett, P., McKay, T., Paris, J. and Leeb, S. B. (2007). Using the non-intrusive load monitor for shipboard supervisory control. *IEEE 2007 Electric Ship Technologies Symposium (ESTS'07)*. *IEEE*: 523-530.

- [22] Shrestha, A., Foulks, E. L. and Cox, R. W. (2009). Dynamic load shedding for shipboard power systems using the non-intrusive load monitor. *IEEE 2009 Electric Ship Technologies Symposium (ESTS)*. IEEE: 412-419.
- [23] DeNucci, T., Cox, R., Leeb, S. B., Paris, J., McCoy, T. J., Laughman, C. and Greene, W. C. (2005). Diagnostic indicators for shipboard systems using non-intrusive load monitoring. *IEEE 2005 Electric Ship Technologies Symposium (ESTS)* IEEE: 413-420.
- [24] Suzdalenko, A. and Galkin, I. (2013). Case study on using non-intrusive load monitoring system with renewable energy sources in intelligent grid applications. *2013 International Conference on Compatibility and Power Electronics (CPE)*. 115-119.
- [25] Berges, M. E., Goldman, E., Matthews, H. S. and Soibelman, L. Enhancing electricity audits in residential buildings with nonintrusive load monitoring. *Journal of industrial ecology*. 2010. 14(5): 844-858.
- [26] Shaikh, P. H., Nor, N. B. M., Nallagownden, P., Elamvazuthi, I. and Ibrahim, T. A review on optimized control systems for building energy and comfort management of smart sustainable buildings. *Renewable and Sustainable Energy Reviews*. 2014. 34: 409-429.
- [27] Kailas, A., Cecchi, V. and Mukherjee, A. (2012). A survey of contemporary technologies for Smart Home energy management. *Handbook of green information and communication systems*. Waltham, USA. Elsevier: 35-56.
- [28] Fernandes, F., Morais, H., Vale, Z. and Ramos, C. Dynamic load management in a smart home to participate in demand response events. *Energy and Buildings*. 2014. 82: 592-606.
- [29] Westergren, K.-E., Högberg, H. and Norlén, U. Monitoring energy consumption in single-family houses. *Energy and buildings*. 1999. 29(3): 247-257.
- [30] Wang, J.-j. and Wang, S. (2010). Wireless sensor networks for home appliance energy management based on ZigBee technology. *IEEE 2010 International Conference on Machine Learning and Cybernetics (ICMLC)*. IEEE: 1041-1046.
- [31] Bonfigli, R., Principi, E., Fagiani, M., Severini, M., Squartini, S. and Piazza, F. Non-intrusive load monitoring by using active and reactive power in additive Factorial Hidden Markov Models. *Applied Energy*. 2017. 28: 1590-1607.

- [32] Hu, Q. and Li, F. Hardware design of smart home energy management system with dynamic price response. *IEEE Transactions on Smart Grid*. 2013. 4(4): 1878-1887.
- [33] Hussain, S., Ikram, M. J. and Arshad, N. (2014). A Low Cost Implementation of Home Area Networks for Home Energy Management Systems. *IEEE 2014 Fourth International Conference on Big Data and Cloud Computing (BdCloud)*. IEEE: 688-695.
- [34] Han, J., Choi, C.-S., Park, W.-K., Lee, I. and Kim, S.-H. Smart home energy management system including renewable energy based on ZigBee and PLC. *Consumer Electronics, IEEE Transactions on*. 2014. 60(2): 198-202.
- [35] Adabi, A., Manovi, P. and Mantey, P. (2016). Cost-effective instrumentation via NILM to support a residential energy management system. *IEEE 2016 International Conference on Consumer Electronics (ICCE)*. IEEE: 107-110.
- [36] Lin, S., Zhao, L., Li, F., Liu, Q., Li, D. and Fu, Y. A nonintrusive load identification method for residential applications based on quadratic programming. *Electric Power Systems Research*. 2016. 133: 241-248.
- [37] Lee, S., Song, B., Kwon, Y. and Kim, J.-h. Non-intrusive Load Monitoring for Home Energy Usage with Multiple Power States Recognition. *Advanced Science and Technology Letters*. 2015. 111: 282-289.
- [38] Dawei, H., Weixuan, L., Nan, L., Harley, R. G. and Habetler, T. G. Incorporating Non-Intrusive Load Monitoring Into Building Level Demand Response. *IEEE Transactions on Smart Grid*. 2013. 4(4): 1870-1877.
- [39] Racines, D. L. and Candelo, J. E. Non Intrusive Load Identification with Power and Impedance obtained from Smart Meters. *International Journal of Engineering & Technology*. 2014. 6(4): 1867-1876.
- [40] Giri, S. and Bergés, M. An energy estimation framework for event-based methods in Non-Intrusive Load Monitoring. *Energy Conversion and Management*. 2015. 90: 488-498.
- [41] Esaa, A., Farahin, N., Abdullah, M. P., Hassan, M. Y. and Hussin, F. Electricity consumption pattern disaggregation using non-intrusive appliance load monitoring method. *Jurnal Teknologi*. 2016. 78(5-7): 29-35.
- [42] Aliyu, G., Khalid, S. B. A., Mustafa, M. W. and Shareef, H. An improved three-phase reactive power measurement algorithm using walsh functions transform. *IEEJ Transactions on Electrical and Electronic Engineering*. 2014. 9(1): 7-14.

- [43] Jazizadeh, F. and Becerik-Gerber, B. A Novel Method for Non Intrusive Load Monitoring of Lighting Systems in Commercial Buildings. *Bridges*. 2014. 10: 523-530.
- [44] Sianaki, O. A., Hussain, O., Dillon, T. and Tabesh, A. R. (2010). Intelligent decision support system for including consumers' preferences in residential energy consumption in smart grid. *IEEE 2010 Second International Conference on Computational Intelligence, Modelling and Simulation (CIMSIM)*. IEEE: 154-159.
- [45] Batra, N., Dutta, H. and Singh, A. (2013). INDiC: Improved Non-intrusive Load Monitoring Using Load Division and Calibration *2013 12th International Conference on Machine Learning and Applications (ICMLA)*. 79-84.
- [46] Wichakool, W. (2011). *Advanced Non-Intrusive Load Monitoring System*. PhD Thesis. Massachusetts Institute of Technology.
- [47] Burbano Acuña, M. D. Intrusive and Non-Intrusive Load Monitoring (A Survey). *Latin American Journal of Computing LAJC*. 2015. 2(1): 1-9.
- [48] Ridi, A. and Hennebert, J. Hidden Markov Models for ILM appliance identification. *Procedia Computer Science*. 2014. 32: 1010-1015.
- [49] McLaughlin, S., McDaniel, P. and Aiello, W. (2011). Protecting consumer privacy from electric load monitoring. *ACM 2011 18th ACM conference on Computer and communications security*: ACM: 87-98.
- [50] Yu-Hsiu, L. and Men-Shen, T. (2012). Application of neuro-fuzzy pattern recognition for Non-intrusive Appliance Load Monitoring in electricity energy conservation. *IEEE 2012 International Conference on Fuzzy Systems (FUZZ-IEEE)*. IEEE: 1-7.
- [51] Liang, J., Ng, S. K., Kendall, G. and Cheng, J. W. Load signature study—Part I: Basic concept, structure, and methodology. *IEEE Transactions on Power Delivery*. 2010. 25(2): 551-560.
- [52] Liang, J., Ng, S. K., Kendall, G. and Cheng, J. W. Load signature study—Part II: Disaggregation framework, simulation, and applications. *Power Delivery, IEEE Transactions on*. 2010. 25(2): 561-569.
- [53] Cheng, J. W., Ng, S. K., Liang, J. and Zhong, J. (2012). An alternative use of power quality information-Load signature studies & applications. *IEEE 2012 15th International Conference on Harmonics and Quality of Power (ICHQP)*, IEEE: 150-155.

- [54] Po-An, C., Chi-Cheng, C. and Ray, I. C. (2012). Automatic appliance classification for non-intrusive load monitoring *IEEE 2012 International Conference on Power System Technology (POWERCON)*. IEEE: 1-6.
- [55] Chang, H.-H., Lin, C.-L. and Lee, J.-K. (2010). Load identification in nonintrusive load monitoring using steady-state and turn-on transient energy algorithms. *IEEE 2010 International Conference on Computer Supported Cooperative Work in Design (CSCWD)*. IEEE: 27-32.
- [56] Hsueh-Hsien, C., Ching-Lung, L. and Hong-Tzer, Y. (2008). Load recognition for different loads with the same real power and reactive power in a non-intrusive load-monitoring system *CSCWD 2008 12th International Conference on Computer Supported Cooperative Work in Design, (CSCWD 2008)*. CSCWD: 1122-1127.
- [57] Bacurau, R., Dante, A., Duarte, L. and Ferreira, E. Experimental Investigation on the Load Signature Parameters for Non-Intrusive Load Monitoring. *Przeegląd Elektrotechniczny*. 2015. 91(8): 86--90.
- [58] Kahl, M., Ul Haq, A., Kriechbaumer, T. and Jacobsen, H.-A. (2017). A Comprehensive Feature Study for Appliance Recognition on High Frequency Energy Data. *ACM 2017 Proceedings of the Eighth International Conference on Future Energy Systems*: ACM: 121-131.
- [59] Tabatabaei, S. M., Dick, S. and Xu, W. Toward non-intrusive load monitoring via multi-label classification. *IEEE Transactions on Smart Grid*. 2017. 8(1): 26-40.
- [60] Esa, N. F., Abdullah, M. P. and Hassan, M. Y. A review disaggregation method in Non-intrusive Appliance Load Monitoring. *Renewable and Sustainable Energy Reviews*. 2016. 66: 163-173.
- [61] Somani, N. A. and Patel, Y. Zigbee: A low power wireless technology for industrial applications. *International Journal of Control Theory and Computer Modelling (IJCTCM)*. 2012. 2: 27-33.
- [62] Batista, N., Melicio, R., Matias, J. and Catalao, J. P. (2012). Zigbee wireless area network for home automation and energy management: Field trials and installation approaches. *IEEE 2012 3rd International Conference and Exhibition on Innovative Smart Grid Technologies (ISGT Europe)*. IEEE: 1-5.

- [63] Ridi, A., Gisler, C. and Hennebert, J. (2014). A survey on intrusive load monitoring for appliance recognition. *IEEE 2014 22nd International Conference on Pattern Recognition (ICPR)*, IEEE: 3702-3707.
- [64] Cottone, P., Gaglio, S., Re, G. L. and Ortolani, M. User activity recognition for energy saving in smart homes. *Pervasive and Mobile Computing*. 2015. 16: 156-170.
- [65] Ridi, A., Gisler, C. and Hennebert, J. (2015). User interaction event detection in the context of appliance monitoring. *IEEE 2015 International Conference on Pervasive Computing and Communication Workshops (PerCom Workshops)*. IEEE: 323-328.
- [66] Villanueva, M. L. G., Dumlao, S. M. G. and Reyes, R. S. (2016). Appliance recognition system for ILM using AGILASx—Dataset of common appliances in the Philippines. *IEEE 2016 Cloudification of the Internet of Things (CIoT)*: IEEE: 1-5.
- [67] Han, D.-M. and Lim, J.-H. Design and implementation of smart home energy management systems based on zigbee. *IEEE Transactions on Consumer Electronics*,. 2010. 56(3): 1417-1425.
- [68] Song, S., Coit, D. W., Feng, Q. and Peng, H. Reliability analysis for multi-component systems subject to multiple dependent competing failure processes. *IEEE Transactions on Reliability*. 2014. 63(1): 331-345.
- [69] Makonin, S. (2012) *Approaches to Non-Intrusive Load Monitoring (NILM) in the Home*. PhD Thesis. Simon Fraser University.
- [70] Aiad, M. and Lee, P. H. (2017). Non-intrusive monitoring of overlapping home appliances using smart meter measurements. *IEEE 2017 Power and Energy Conference at Illinois (PECI)* IEEE: 1-5.
- [71] Srinivasan, G., Anandan, C., Jain, S. A. K., Ahmed, S. S. and Vijayaraghavan, V. (2016). Low-cost non-intrusive device identification system. *IEEE 2016 Dallas Circuits and Systems Conference (DCAS)*, IEEE: 1-4.
- [72] Bouhouras, A. S., Milioudis, A. N. and Labridis, D. P. Development of distinct load signatures for higher efficiency of NILM algorithms. *Electric Power Systems Research*. 2014. 117: 163-171.
- [73] Alcalá, J. M., Ureña, J., Hernández, Á. and Gualda, D. Assessing Human Activity in Elderly People Using Non-Intrusive Load Monitoring. *Sensors*. 2017. 17(2): 351.

- [74] Alahmad, M., Zulfiqar, M. F., Hasna, H., Sharif, H., Sordiashie, E. and Aljuhaishi, N. A. (2011). Green and Sustainable Technologies for the Built Environment *2011 Developments in E-systems Engineering (DeSE)*, DeSE: 521-526.
- [75] Bergman, D., Jin, D., Juen, J., Tanaka, N., Gunter, C. and Wright, A. Nonintrusive load-shed verification. *IEEE Pervasive Computing*. 2011. 10(1): 49-57.
- [76] Anna Bertona, J.-P. V. t., Alexander Tamminga. (2014). Energy Management: can Utilities seize the Opportunity ? A. T. Kearney.
- [77] Aiad, M. and Lee, P. H. Non-intrusive load disaggregation with adaptive estimations of devices main power effects and two-way interactions. *Energy and Buildings*. 2016. 130: 131-139.
- [78] Sudiharto, I., Anggriawan, D. O. and Tjahjono, A. Harmonic Load Identification Based on Fast Fourier Transform and Levenberg Marquardt Backpropagation. *Journal of Theoretical and Applied Information Technology*. 2017. 95(5): 1080.
- [79] Wójcik, A., Winiecki, W. and Kowalik, R. Characterization of electrical appliances based on their immitance. International Society for Optics and Photonics. *2016 Photonics Applications in Astronomy, Communications, Industry, and High-Energy Physics Experiments 2016*: International Society for Optics and Photonics. 10031: 1003121-1003128.
- [80] Chung, T. M. and Daniyal, H. Arduino Based Power Meter Using Instantaneous Power Calculation Method. *ARPN Journal of Engineering and Applied Sciences*. 2006. 10(21): 9791-9795.
- [81] Lin, Y.-H. and Tsai, M.-S. The Integration of a Genetic Programming-Based Feature Optimizer With Fisher Criterion and Pattern Recognition Techniques to Non-Intrusive Load Monitoring for Load Identification. *International Journal of Green Energy*. 2015. 12(3): 279-290.
- [82] Lam, H., Fung, G. and Lee, W. A novel method to construct taxonomy electrical appliances based on load signatures. *IEEE Transactions on Consumer Electronics*,. 2007. 53(2): 653-660.
- [83] Pattem, S. (2012). Unsupervised Disaggregation for Non-intrusive Load Monitoring *2012 11th International Conference on Machine Learning and Applications (ICMLA)*. 515-520.

- [84] Parson, O., Ghosh, S., Weal, M. and Rogers, A. An unsupervised training method for non-intrusive appliance load monitoring. *Artificial Intelligence*. 2014. 217: 1-19.
- [85] Po-An, C. and Ray, I. C. (2013). Unsupervised Adaptive Non-intrusive Load Monitoring System. *IEEE 2013 International Conference on Systems, Man, and Cybernetics (SMC)*, IEEE: 3180-3185.
- [86] Jia, R., Gao, Y. and Spanos, C. J. (2015). A fully unsupervised non-intrusive load monitoring framework. *IEEE 2015 International Conference on Smart Grid Communications (SmartGridComm)*, 2015 IEEE: 872-878.
- [87] Rahimi, S (2012). *Usage Monitoring of Electrical Devices in a Smart Home*. Master Thesis. Carleton University Ottawa, Ontario, Canada, K1S 5B6.
- [88] Ming, D., Meira, P. C. M., Wilsun, X. and Chung, C. Y. Non-Intrusive Signature Extraction for Major Residential Loads. *IEEE Transactions on Smart Grid*. 2013. 4(3): 1421-1430.
- [89] Figueiredo, M. B., de Almeida, A., Ribeiro, B. and Martins, A. Extracting features from an electrical signal of a non-intrusive load monitoring system. *Intelligent Data Engineering and Automated Learning–IDEAL 2010*. Springer. 2010: 210-217.
- [90] Ming, H. H. (2013). *Tracing of Lighting Electricity Consumption Using Non-Intrusive Load Monitoring Method*. Master Thesis. Universiti Teknologi Malaysia, Skudai.
- [91] Sanchez-Gomez, J. I., Morales-Velazquez, L., Osornio-Rios, R. A. and Guillen-Garcia, E. (2016). Fuzzy c-means clustering for steady state events classification of electrical signals. *IEEE 2016 12th Congreso Internacional de Ingeniería (CONIN)*. IEEE: 1-5.
- [92] Hassan, T., Javed, F. and Arshad, N. An Empirical Investigation of VI Trajectory based Load Signatures for Non-Intrusive Load Monitoring. *IEEE Transaction on Smart Grid*. 2014. 2(2): 870-878.
- [93] Iksan, N., Sembiring, J., Haryanto, N. and Supangkat, S. H. (2015). Appliances identification method of non-intrusive load monitoring based on load signature of VI trajectory. *IEEE 2015 International Conference on Information Technology Systems and Innovation (ICITSI)*. IEEE: 1-6.
- [94] Bouhouras, A. S., Vaggos, M., Poulakis, N. and Christoforidis, G. C. (2016). Load signatures enhancement via odd-order harmonic currents. *IEEE 2016 16th*

- International Conference on Environment and Electrical Engineering (EEEIC), 2016 IEEE 16th International Conference on:* IEEE: 1-6.
- [95] Jung, D., Nguyen, H. H. and Yau, D. K. (2015). Tracking appliance usage information using harmonic signature sensing. *IEEE 2015 International Conference on Smart Grid Communications (SmartGridComm), 2015 IEEE:* 459-465.
- [96] Temneanu, M. and Ardeleanu, A. Non-intrusive hybrid energy monitoring system. *Advanced Materials Research:* 2014. 837: 495-499.
- [97] Liu, B., Luan, W. and Yu, Y. Dynamic time warping based non-intrusive load transient identification. *Applied Energy.* 2017. 195: 634-645.
- [98] Duarte, C., Delmar, P., Barner, K. and Goossen, K. (2015). A signal acquisition system for non-intrusive load monitoring of residential electrical loads based on switching transient voltages. *IEEE 2015 Power Systems Conference (PSC) Clemson University.* IEEE: 1-6.
- [99] Norford, L. K. and Leeb, S. B. Non-intrusive electrical load monitoring in commercial buildings based on steady-state and transient load-detection algorithms. *Energy and Buildings.* 1996. 24(1): 51-64.
- [100] Kim, H., Marwah, M., Arlitt, M. F., Lyon, G. and Han, J. (2011). Unsupervised Disaggregation of Low Frequency Power Measurements. *SIAM 2011 SDM:* SIAM: 747-758.
- [101] Bouloutas, A., Hart, G. W. and Schwartz, M. Two extensions of the Viterbi algorithm. *IEEE Transactions on Information Theory,*. 1991. 37(2): 430-436.
- [102] Anderson, K. D., Berges, M. E., Ocneanu, A., Benitez, D. and Moura, J. M. F. (2012). Event detection for Non Intrusive load monitoring *2012 IEEE 38th Annual Conference on IEEE Industrial Electronics Society (IECON).* IEEE: 3312-3317.
- [103] Jiang, L., Luo, S. and Li, J. (2013). Automatic power load event detection and appliance classification based on power harmonic features in nonintrusive appliance load monitoring. *IEEE 2013 8th IEEE Conference on Industrial Electronics and Applications (ICIEA).* IEEE: 1083-1088.
- [104] Barsim, K. S. and Yang, B. Sequential Clustering-Based Event Detection for Non-Intrusive Load Monitoring. *Computer Science & Information Technology.* 2016. 10: 5121.

- [105] De Baets, L., Ruysinck, J., Deschrijver, D. and Dhaene, T. (2016). Event Detection in NILM using Cepstrum smoothing. *2016 3rd International Workshop on Non-Intrusive Load Monitoring*, 1-4.
- [106] Yang, C. C., Soh, C. S. and Yap, V. V. A systematic approach to ON-OFF event detection and clustering analysis of non-intrusive appliance load monitoring. *Frontiers in Energy*. 2015. 9(2): 231-237.
- [107] Kolter, J. Z. and Jaakkola, T. (2012). Approximate inference in additive factorial hmms with application to energy disaggregation. *2012 International conference on artificial intelligence and statistics*, 1472-1482.
- [108] Anderson, K. D. (2014). *Non-Intrusive Load Monitoring: Disaggregation of Energy by Unsupervised Power Consumption Clustering*. PhD Thesis. Carnegie Mellon University Pittsburgh, PA.
- [109] Roos, J. G., Lane, I. E., Botha, E. C. and Hancke, G. P. (1994). Using neural networks for non-intrusive monitoring of industrial electrical loads. *IEEE 1994 Instrumentation and Measurement Technology Conference, (IMTC/94)*. *IEEE*:. 1115-1118.
- [110] Yu-Hsiu, L. and Men-Shen, T. (2011). Applications of hierarchical support vector machines for identifying load operation in nonintrusive load monitoring systems *2011 Congress on Intelligent Control and Automation (WCICA)*. *WCICA*: 688-693.
- [111] Hong-Tzer, Y., Hsueh-Hsien, C. and Ching-Lung, L. (2007). Design a Neural Network for Features Selection in Non-intrusive Monitoring of Industrial Electrical Loads *2007 11th International Conference on Computer Supported Cooperative Work in Design, (CSCWD)*. 1022-1027.
- [112] Figueiredo, M. B., De Almeida, A. and Ribeiro, B. An experimental study on electrical signature identification of non-intrusive load monitoring (nilm) systems. *Adaptive and Natural Computing Algorithms*: Springer. 2011. 6594: 31-40.
- [113] Wild, B., Barsim, K. S. and Yang, B. (2015). A new unsupervised event detector for non-intrusive load monitoring. *IEEE 2015 Signal and Information Processing (GlobalSIP), 2015 IEEE Global Conference on*: IEEE, 73-77.
- [114] Faustine, A., Mvungi, N. H., Kaijage, S. and Michael, K. A Survey on Non-Intrusive Load Monitoring Methodies and Techniques for Energy Disaggregation Problem. *arXiv preprint arXiv*. 2017. 1703: 00785.

- [115] Sadeghianpourhamami, N., Ruysinck, J., Deschrijver, D., Dhaene, T. and Develder, C. Comprehensive Feature Selection for Appliance Classification in NILM. *Energy and Buildings*. 2017. 1703: 00785.
- [116] Zeifman, M. and Roth, K. Nonintrusive appliance load monitoring: Review and outlook. *IEEE Transactions on Consumer Electronics*, 2011. 57(1): 76-84.
- [117] Liu, Y. and Chen, M. (2014). A review of nonintrusive load monitoring and its application in commercial building. *IEEE 2014 4th Annual International Conference on Cyber Technology in Automation, Control, and Intelligent Systems (CYBER)*, IEEE: 623-629.
- [118] Klemenjak, C. and Goldsborough, P. Non-Intrusive Load Monitoring: A Review and Outlook. *arXiv preprint arXiv*. 2016. 1610: 01191.
- [119] Hoyo-Montayo, J. A., Pereyda-Pierre, C. A., Tarín-Fontes, J. M. and Leon-Ortega, J. N. (2016). Overview of Non-Intrusive Load Monitoring: A way to energy wise consumption. *IEEE 2016 13th International Conference on Power Electronics (CIEP)*. IEEE: 221-226.
- [120] Barker, S., Kalra, S., Irwin, D. and Shenoy, P. (2014). NILM redux: The case for emphasizing applications over accuracy *NILM-2014 Workshop. NILM:1-4*,
- [121] Nation, J. C., Abouliah, A., Green, D., Lindahl, P., Donnal, J., Leeb, S. B., Bredariol, G. and Stevens, K. (2017). Nonintrusive monitoring for shipboard fault detection. *IEEE 2017 Sensors Applications Symposium (SAS)*. IEEE: 1-5.
- [122] Campagna, M. M., Dinardo, G., Fabbiano, L. and Vacca, G. Fluid flow measurements by means of vibration monitoring. *Measurement Science and Technology*. 2015. 26(11): 115306.
- [123] Schantz, C., Donnal, J., Sennett, B., Gillman, M., Muller, S. and Leeb, S. Water Nonintrusive Load Monitoring. *Sensors Journal, IEEE*. 2015. 15(4): 2177-2185.
- [124] Borin, V. P., Barriquello, C. H. and Pinto, R. A. (2013). An improved technique for load identification in residential buildings *2013 International Conference on New Concepts in Smart Cities: Fostering Public and Private Alliances (SmartMILE)*. 1-5.
- [125] Muthuselvi, G. and Saravanan, B. Real Time Speech Recognition Based Building Automation System. *ARPN Journal of Engineering and Applied Sciences*. 2014. 9(12): 2831-2839.

- [126] Sawyer, R. L., Anderson, J. M., Foulks, E. L., Troxler, J. O. and Cox, R. W. (2009). Creating low-cost energy-management systems for homes using non-intrusive energy monitoring devices. *IEEE 2009 Energy Conversion Congress and Exposition (ECCE)*. IEEE: 3239-3246.
- [127] Kucuk, S., Arslan, F., Bayrak, M. and Contreras, G. (2016). Load management of industrial facilities electrical system using intelligent supervision, control and monitoring systems. *IEEE 2016 International Symposium on Networks, Computers and Communications (ISNCC)*. IEEE: 1-6.
- [128] Donnal, J. S. (2013). *Home NILM: A Comprehensive Energy Monitoring Toolkit*. Master Thesis. Massachusetts Institute of Technology.
- [129] Rasool, G., Ehsan, F. and Shahbaz, M. A systematic literature review on electricity management systems. *Renewable and Sustainable Energy Reviews*. 2015. 49: 975-989.
- [130] Landry, J. S. and Matthews, H. D. The global pyrogenic carbon cycle and its impact on the level of atmospheric CO₂ over past and future centuries. *Global change biology*. 2017. 23(8):3205-3218.
- [131] Lee, D. and Cheng, C. C. Energy savings by energy management systems: A review. *Renewable and Sustainable Energy Reviews*. 2016. 56: 760-777.
- [132] Schulze, M., Nehler, H., Ottosson, M. and Thollander, P. Energy management in industry—a systematic review of previous findings and an integrative conceptual framework. *Journal of Cleaner Production*. 2016. 112: 3692-3708.
- [133] Rafsanjani, H. N., Ahn, C. R. and Alahmad, M. A review of approaches for sensing, understanding, and improving occupancy-related energy-use behaviors in commercial buildings. *Energies*. 2015. 8(10): 10996-11029.
- [134] Lobaccaro, G., Carlucci, S. and Löfström, E. A Review of Systems and Technologies for Smart Homes and Smart Grids. *Energies*. 2016. 9(5): 1290-1314.
- [135] Lopez-Rodriguez, I., Hernandez-Tejera, M. and Lopez, A. L. Methods for the management of distributed electricity networks using software agents and market mechanisms: A survey. *Electric Power Systems Research*. 2016. 136: 362-369.
- [136] Shen, J., Jiang, C. and Li, B. Controllable load management approaches in smart grids. *Energies*. 2015. 8(10): 11187-11202.

- [137] Nanda, A. K. and Panigrahi, C. Review on smart home energy management. *International Journal of Ambient Energy*. 2016. 37(5): 1-6.
- [138] Du, Y., Du, L., Lu, B., Harley, R. and Habetler, T. (2010). A review of identification and monitoring methods for electric loads in commercial and residential buildings. *IEEE 2010 Energy Conversion Congress and Exposition (ECCE)* IEEE: 4527-4533.
- [139] Vega, A., Santamaria, F. and Rivas, E. Modeling for home electric energy management: A review. *Renewable and Sustainable Energy Reviews*. 2015. 52: 948-959.
- [140] Abedin, Z. U., Shahid, U., Mahmood, A., Qasim, U., Khan, Z. A. and Javaid, N. (2015). Application of PSO for HEMS and ED in Smart Grid. *IEEE 2015 Ninth International Conference on Complex, Intelligent, and Software Intensive Systems (CISIS)*. IEEE: 260-266.
- [141] Kim, W. H., Lee, S. and Hwang, J. Real-time energy monitoring and controlling system based on Zigbee sensor networks. *Procedia Computer Science*. 2011. 5: 794-797.
- [142] Guvensan, M. A., Taysi, Z. C. and Melodia, T. Energy monitoring in residential spaces with audio sensor nodes: TinyEARS. *Ad Hoc Networks*. 2013. 11(5): 1539-1555.
- [143] Anastasi, G., Corucci, F. and Marcelloni, F. (2011). An intelligent system for electrical energy management in buildings. *IEEE 2011 11th International Conference on Intelligent Systems Design and Applications (ISDA), 2011*: IEEE, 702-707.
- [144] Lien, C.-H., Chen, H.-C., Bai, Y.-W. and Lin, M.-B. (2008). Power monitoring and control for electric home appliances based on power line communication. *IEEE 2008 Instrumentation and Measurement Technology Conference Proceedings. (IMTC)*. IEEE: 2179-2184.
- [145] Magno, M., Polonelli, T., Benini, L. and Popovici, E. A Low Cost, Highly Scalable Wireless Sensor Network Solution to Achieve Smart LED Light Control for Green Buildings. *Sensors Journal, IEEE*. 2015. 15(5): 2963-2973.
- [146] Pipattanasomporn, M., Kuzlu, M. and Rahman, S. An algorithm for intelligent home energy management and demand response analysis. *IEEE Transactions on Smart Grid*. 2012. 3(4): 2166-2173.

- [147] Kuzlu, M., Pipattanasomporn, M. and Rahman, S. Hardware demonstration of a home energy management system for demand response applications. *IEEE Transactions on Smart Grid*. 2012. 3(4): 1704-1711.
- [148] Jiang, X., Van Ly, M., Taneja, J., Dutta, P. and Culler, D. (2009). Experiences with a high-fidelity wireless building energy auditing network. *ACM 2009 7th ACM Conference on Embedded Networked Sensor Systems*: ACM: 113-126.
- [149] Ridi, A., Gisler, C. and Hennebert, J. (2013). Automatic identification of electrical appliances using smart plugs. *IEEE 2013 8th International Workshop on Systems, Signal Processing and their Applications (WoSSPA)*. IEEE: 301-305.
- [150] Erol-Kantarci, M. and Mouftah, H. T. Wireless sensor networks for cost-efficient residential energy management in the smart grid. *IEEE Transactions on Smart Grid*,. 2011. 2(2): 314-325.
- [151] Erol-Kantarci, M. and Mouftah, H. T. (2010). Using wireless sensor networks for energy-aware homes in smart grids. *IEEE 2010 Symposium on Computers and Communications (ISCC)*. IEEE: 456-458.
- [152] Erol-Kantarci, M. and Mouftah, H. T. (2010). TOU-aware energy management and wireless sensor networks for reducing peak load in smart grids. *IEEE 2010 72nd Vehicular Technology Conference Fall (VTC 2010-Fall)*. IEEE: 1-5.
- [153] Tsai, M.-S. and Lin, Y.-H. Modern development of an adaptive non-intrusive appliance load monitoring system in electricity energy conservation. *Applied Energy*. 2012. 96: 55-73.
- [154] Nunes, N. J., Pereira, L., Quintal, F. and Berges, M. (2011). Deploying and evaluating the effectiveness of energy eco-feedback through a low-cost NILM solution. *2011 6th International Conference on Persuasive Technology*. 2-5.
- [155] United States Environmental Protection Agency. Global Greenhouse Gas Emissions Data. <https://www3.epa.gov/climatechange/>: Available 10th December, 2014.
- [156] Babu, A. V., Rao, C. U. and Tirupataiah, L. Energy Conservation, Green House Gas Emission Reduction and Management Strategies of VFSTR University: A Case Study. *Journal of Advanced Research and Dynamical Control System (JARDCS)*. 2017. 9(4): 21-27.

- [157] Sreekanth, K. Review on integrated strategies for energy policy planning and evaluation of GHG mitigation alternatives. *Renewable and Sustainable Energy Reviews*. 2016. 64: 837-850.
- [158] Andries Hof, C. B., Angelica Mendoza Beltran, Michel den Elzen. GREENHOUSE GAS EMISSION REDUCTION TARGETS FOR 2030 CONDITIONS FOR AN EU TARGET OF 40%.
- [159] Calvillo, C., Sánchez-Miralles, A. and Villar, J. Energy management and planning in smart cities. *Renewable and Sustainable Energy Reviews*. 2016. 55: 273-287.
- [160] Li, W. J., Tan, X. and Tsang, D. H. (2015). Smart home energy management systems based on non-intrusive load monitoring. *IEEE 2015 2015 IEEE International Conference on Smart Grid Communications (SmartGridComm)*: IEEE: 885-890.
- [161] Lai, Y.-X., Lai, C.-F., Huang, Y.-M. and Chao, H.-C. Multi-appliance recognition system with hybrid SVM/GMM classifier in ubiquitous smart home. *Information Sciences*. 2013. 230: 39-55.
- [162] Garcia, F. C. C., Creayla, C. M. C. and Macabebe, E. Q. B. Development of an Intelligent System for Smart Home Energy Disaggregation Using Stacked Denoising Autoencoders. *Procedia Computer Science*. 2017. 105: 248-255.
- [163] Egarter, D. and Elmenreich, W. (2015). Autonomous Load Disaggregation Approach based on Active Power Measurements. *IEEE 2015 International Conference on Pervasive Computing and Communication Workshops (PerCom Workshops)*. IEEE: 417-422.
- [164] Environment, U. S. Available and Emerging Technologies for Reducing Greenhouse Gas Emissions from Coal-Fired Electric Generating Units. Sector Policies and Programs Division Office of Air Quality Planning and Standards U.S. Environmental Protection Agency Research Triangle Park, North Carolina 27711. 2010.
- [165] Niesten, E. and Alkemade, F. How is value created and captured in smart grids? A review of the literature and an analysis of pilot projects. *Renewable and Sustainable Energy Reviews*. 2016. 53: 629-638.
- [166] Ruth, M., Pratt, A., Lunacek, M., Mittal, S., Wu, H. and Jones, W. (2015). Effects of Home Energy Management Systems on Distribution Utilities and

- Feeders Under Various Market Structures. *2015 23rd International Conference on Electricity Distribution (ICED)*. 1-6 .
- [167] Rodrigues, E., Godina, R., Pouresmaeil, E., Ferreira, J. and Catalão, J. Domestic appliances energy optimization with model predictive control. *Energy Conversion and Management*. 2017. 142: 402-413.
- [168] Tauqeer, T., Ansari, M. A. and Hasan, A. Realization for low cost and energy efficient ceiling fans in the developing countries. *Renewable and Sustainable Energy Reviews*. 2017. 76: 193-201.
- [169] Shen, H.-Y., Chen, Y.-C. and Hsu, C.-H. A Power Frequency Sensing Device Using an Arduino Device and Zero-Crossing Algorithm and Its Implementation on Android App. *Sensors and Materials*. 2017. 29(6): 741-756.
- [170] Jao, C. and Guo, X. PowerBox: The Safe AC Power Meter. *Cit. Cornell.* 2013. 1(04): 1-22.
- [171] Synergy Software. The KaleidaGraph Guide to Curve Fitting www.synergy.com/Tools/curvefitting.pdf. Available 16th March 2016.
- [172] Guo, C., Wang, M., Yang, L., Sun, Z., Zhang, Y. and Xu, J. A review of energy consumption and saving in extra-long tunnel operation ventilation in China. *Renewable and Sustainable Energy Reviews*. 2016. 53: 1558-1569.
- [173] Youngwook, K., Seongbae, K., Rakkyung, K. and Sung-Kwan, J. (2014). Electrical event identification technique for monitoring home appliance load using load signatures. *2014 International Conference on Consumer Electronics (ICCE)*. *IEEE*: 296-297.
- [174] Klein, P., Merckle, J., Benyoucef, D. and Bier, T. (2013). Test bench and quality measures for non-intrusive load monitoring algorithms. *IEEE 2013 39th Annual Conference of the Industrial Electronics Society (IECON 2013)*. *IEEE*: 5006-5011.
- [175] Baraka, K., Ghobril, M., Malek, S., Kanj, R. and Kayssi, A. (2013). Low cost arduino/android-based energy-efficient home automation system with smart task scheduling. *IEEE 2013 Fifth International Conference on Computational Intelligence, Communication Systems and Networks (CICSyN)*. *IEEE*: 296-301.

- [176] Adriansyah, A. and Dani, A. W. (2014). Design of small smart home system based on Arduino. *IEEE 2014 Electrical Power, Electronics, Communications, Controls and Informatics Seminar (EECCIS)*. IEEE: 121-125.
- [177] Marshall, M. N. Sampling for qualitative research. *Family practice*. 1996. 13(6): 522-526.
- [178] Etikan, I., Musa, S. A. and Alkassim, R. S. Comparison of convenience sampling and purposive sampling. *American Journal of Theoretical and Applied Statistics*. 2016. 5(1): 1-4.
- [179] Mekhilef, S., Saidur, R., Said, S., Hong, P. and Islam, M. Techno-economic evaluation of energy efficiency measures in high rise residential buildings in Malaysia. *Clean Technologies and Environmental Policy*. 2014. 16(1): 23-35.
- [180] LLC, A. M. ACS712: Fully Integrated, Hall-Effect-Based Linear Current Sensor IC with 2.1 kVRMS Voltage Isolation and a Low-Resistance Current Conductor. <http://www.allegromicro.com/>.
- [181] Srividya Devi, P., Pusphalatha, D. V. and Sharma, P. M. Measurement of Power and Energy Using Arduino. *Research Journal of Engineering Sciences*. 2013. 2(10): 10-15.
- [182] Global Logica Software Technologies. AC Voltage Sensor (ZMPT101B). www.makemyproduct.com.: Available 22nd December, 2016.
- [183] Ramos, P. M., Brás, N. B. and Serra, A. C. (2006). A new calibration method for current and voltage sensors used in power quality measurements. *IEEE 2006 Instrumentation and Measurement Technology Conference Proceedings (IMTC)*: IEEE: 2283-2288.
- [184] Chang, H.-H., Yang, H.-T. and Lin, C.-L. Load identification in neural networks for a non-intrusive monitoring of industrial electrical loads. *Computer Supported Cooperative Work in Design IV*: Springer. 664-674; 2008.
- [185] Thacker, M. S. and Jhala, M. B. Domestic Load Identification with Single CT Using Artificial Neural Network. *Paripex - Indian Journal of Research*. 2013. 2(4): 90-93.
- [186] Fiorucci, E. The measurement of actual apparent power and actual reactive power from the instantaneous power signals in single-phase and three-phase systems. *Electric Power Systems Research*. 2015. 121: 227-242.

- [187] Bilil, H., Aniba, G. and Gharavi, H. Dynamic Appliances Scheduling in Collaborative MicroGrids System. *IEEE Transactions on Power Systems*. 2017. 32(3): 2276-2287.
- [188] Addabbo, T., Fort, A., Mugnaini, M. and Vignoli, V. Distributed UPS Control Systems Reliability Analysis. *Measurement*. 2017. 110: 275-283.
- [189] Aamir, M., Kalwar, K. A. and Mekhilef, S. Review: Uninterruptible Power Supply (UPS) system. *Renewable and Sustainable Energy Reviews*. 2016. 58: 1395-1410.
- [190] Bagheri, E., Tashakor, N., Farjah, E. and Ghanbari, T. (2017). Single-phase multi-source on-line UPS with isolated battery charger. *IEEE 2017 Power Electronics, Drive Systems & Technologies Conference (PEDSTC)*. IEEE: 223-228.
- [191] Patil, V. R., Biradar, V. I., Shreyas, R., Garg, P., Orosz, M. S. and Thirumalai, N. Techno-economic comparison of solar organic Rankine cycle (ORC) and photovoltaic (PV) systems with energy storage. *Renewable Energy*. 2017. 113: 1250-1260.
- [192] Goel, S. and Sharma, R. Performance evaluation of stand alone, grid connected and hybrid renewable energy systems for rural application: A comparative review. *Renewable and Sustainable Energy Reviews*. 2017. 78: 1378-1389.
- [193] Al-Shamani, A. N., Othman, M. Y. H., Mat, S., Ruslan, M., Abed, A. M. and Sopian, K. Design & Sizing of Stand-alone Solar Power Systems A house Iraq. *Recent Advances in Renewable Energy Sources*. 2013: 145-150.
- [194] Charron, R. and Athienitis, A. Design and Optimization of Net Zero Energy Solar Homes. *ASHRAE transactions*. 2006. 112(2).
- [195] Svozil, D., Kvasnicka, V. and Pospichal, J. Introduction to multi-layer feed-forward neural networks. *Chemometrics and intelligent laboratory systems*. 1997. 39(1): 43-62.
- [196] David, N., Anozie, F. N., Ebuka, F. O. and Nzenweaku, S. A. Design of an Arduino Based Wireless Power Meter. *International Journal of Scientific & Engineering Research*. 2016. 7(9): 446-449.
- [197] Miron-Alexe, V. Iot Power Consumption Monitoring System for Off-Grid Households. *University of Pitesti Scientific Bulletin : Electronics and Computers Science*. 2017. 17(2): 64-71.

- [198] Mnati, M. J., Van den Bossche, A. and Chisab, R. F. A smart voltage and current monitoring system for three phase inverters using an android smartphone application. *Sensors*. 2017. 17(4): 872.
- [199] Mlakić, D., Nikolovski, S. N. and Alibašić, E. Designing Automatic Meter Reading System Using Open Source Hardware and Software. *International Journal of Electrical and Computer Engineering (IJECE)*. 2017. 7(6): 3282-3291.
- [200] Rahman, K., Leman, A., Mubin, M. F., Yusof, M., Hariri, A. and Salleh, M. (2017). Energy Consumption Analysis Based on Energy Efficiency Approach: A Case of Suburban Area. *EDP Sciences 2017 MATEC Web of Conferences: MTEC:87*.
- [201] Winther, O., Lautrup, B. and Zhang, J.-B. Optimal learning in multilayer neural networks. *Physical Review E*. 1997. 55(1): 836.
- [202] Hansel, D., Mato, G. and Meunier, C. Memorization without generalization in a multilayered neural network. *EPL (Europhysics Letters)*. 1992. 20(5): 471.