

**PALM OIL BASED EMULSION LIQUID MEMBRANE FORMULATION FOR  
SUCCINIC ACID EXTRACTION PERFORMANCE**

**NORELA BINTI JUSOH**

**UNIVERSITI TEKNOLOGI MALAYSIA**

PALM OIL BASED EMULSION LIQUID MEMBRANE FORMULATION FOR  
SUCCINIC ACID EXTRACTION PERFORMANCE

NORELA BINTI JUSOH

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Doctor of Philosophy (Chemical Engineering)

Faculty of Chemical and Energy Engineering  
Universiti Teknologi Malaysia

AUGUST 2017

To my beloved parents, family, and friends

## ACKNOWLEDGEMENTS

First and foremost, all praise be to Allah, the Almighty, the Benevolent for His blessings and guidance for giving me the inspiration to embark on this research and instilling in me the strength to see that this thesis becomes a reality. Many people have contributed to the creation and completion of this thesis.

I am especially indebted and grateful to my family members, especially my parents, Mr. Jusoh and Mrs. Mariam for their support and prayers during the years I pursued my PhD. Thank you so much for understanding me and always support whatever decision I have made.

I would like to express my gratitude to my supervisor, Associate Prof Dr. Norasikin binti Othman; her wide knowledge, her logical way of thinking, and her professional guidance provided a good basis for the present thesis. She provided refreshing insight, critical questions and common sense, which were vital for this project. Thank you for your patience, for pushing me to see beyond the results and for teaching me to be independent in my research. Thank you also for your advice which keeping me in the right path. I am also very thankful to my co-supervisor, Prof. Dr. Ani Idris for her kind guidance.

My sincere gratitude also goes to my colleagues: Raja Norimie, Norul Fatiha, Ooi Zing Yi, Nur Alina, Muhammad Bukhari, and Hilmi for their moral support in this research. To those who directly or indirectly assist me in this research, your kindness means a lot to me. Thank you very much. Not to forget, Mr. Mohd Latfi for helping me out during the HPLC analysis.

Last but not least, I would also like to extend my appreciation to Universiti Teknologi Malaysia for providing the facilities vital to the completion of this thesis. Besides, the financial support from Ministry of Higher Education are gratefully acknowledged.

## ABSTRACT

Emulsion liquid membrane (ELM) process has received significant attention due to its simple operation and high selectivity to the target solute. One of the potential applications of ELM is in the separation and purification of succinic acid from fermentation process. The most important aspects for a successful ELM process are liquid membrane formulation and emulsion stability. In this study, the formulation of ELM was investigated to find a suitable carrier, diluent and stripping agent. The stability of water-in-oil (W/O) emulsion was studied by investigating the ratio of organic to internal phase, homogenizer speed, emulsifying time, and surfactant concentration. The stability of water-in-oil-in-water (W/O/W) was investigated by varying sorbitan monooleate (Span 80) and polyoxyethylenesorbitan monooleate (Tween 80) concentrations, agitation speed, and agitation time. Experiments on the effect of stripping agent concentration, treat ratio, carrier concentration, pH of external phase, modifier concentration, extraction time, and agitation speed were carried out in batch process to find the most influencing parameters for succinic acid extraction. The optimum recovery of succinic acid was studied using response surface methodology (RSM). The favourable conditions for ELM application in the succinic acid recovery was determined by varying the external feed concentration and potential of liquid membrane recycling. The results show that palm oil as a diluent, Amberlite LA2 as a carrier, and sodium carbonate ( $\text{Na}_2\text{CO}_3$ ) as a stripping agent were selected in liquid membrane formulation. The most stable condition of W/O emulsion was obtained at 3:1 organic to internal phase ratio, 7000 rpm of homogenizer speed, 5 minutes of emulsification time, and 3% (w/v) of Span 80 concentration. The most stable W/O/W emulsion was obtained at 5% (w/v) Span 80, 1% (w/v) Tween 80, 300 rpm agitation speed, and 3 minutes agitation time. At the best condition of 0.01M  $\text{Na}_2\text{CO}_3$ , 1:3 treat ratio, 0.7M Amberlite LA2, 10% modifier, pH 2, and 3 minutes of extraction time, the extraction of succinic acid was up to 70%. The most significant parameters of stripping agent and carrier concentrations, and treat ratio were selected for RSM optimization study and the results show that 38.9% and 36.3% of succinic acid was recovered from aqueous solution and fermentation broth respectively. The ELM purification of succinic acid showed that at favourable condition, 84% of succinic acid was recovered with almost 100% purity and the liquid membrane is good up to the second cycle. The findings of this study show that ELM process is a promising technology to extract and recover succinic acid from bio-based production.

## ABSTRAK

Proses membran cecair emulsi (ELM) telah mendapat perhatian yang sewajarnya berikutan prosesnya yang mudah dan kememilihan yang tinggi terhadap bahan larut. Salah satu potensi aplikasi ELM ialah dalam proses pemisahan dan penulenan asid suksinik daripada proses penapaian. Perkara yang paling penting bagi menjayakan proses ELM adalah rumusan membran cecair dan kestabilan emulsi. Dalam kajian ini, rumusan ELM dikaji bagi mencari agen pembawa, pelarut, dan agen pelucutan yang sesuai. Kestabilan emulsi air-dalam-minyak (W/O) telah diselidik dengan mengkaji nisbah fasa organik kepada fasa dalaman, kelajuan penghomogenan, masa pengemulsian, dan kepekatan surfaktan. Kestabilan air-dalam-minyak-dalam-air (W/O/W) telah disiasat dengan mengubah kepekatan Span 80 dan Tween 80, kelajuan pengadukan, dan masa pengadukan. Eksperimen untuk kesan kepekatan agen pelucutan, nisbah rawatan, kepekatan pembawa, pH fasa suapan, kepekatan pengubahsuai, masa pengekstrakan, dan kelajuan pengadukan telah dijalankan dalam proses berkelompok untuk mencari parameter yang paling mempengaruhi terhadap pengekstrakan asid suksinik. Perolehan optimum asid suksinik telah dikaji dengan menggunakan kaedah gerak balas permukaan (RSM). Keadaan yang sesuai bagi aplikasi ELM bagi perolehan asid suksinik telah ditentukan dengan mengubah kepekatan suapan luaran dan keupayaan kitar semula membran cecair. Keputusan menunjukkan bahawa minyak sawit sebagai bahan pencair, Amberlite LA2 sebagai pembawa, dan natrium karbonat ( $\text{Na}_2\text{CO}_3$ ) sebagai agen pelucutan telah dipilih dalam rumusan membran cecair. Keadaan W/O yang paling stabil didapati pada nisbah 3:1 bagi fasa organik kepada fasa dalaman, 7000 rpm kelajuan penghomogenan, 5 minit masa pengemulsian, dan 3% (w/v) kepekatan Span 80. Emulsi W/O/W yang paling stabil telah diperolehi pada 5% Span 80, 1% (w/v) Tween 80, 300 rpm kelajuan pengadukan, dan 3 minit masa pengadukan. Pada keadaan terbaik, iaitu 0.01M  $\text{Na}_2\text{CO}_3$ , 1:3 nisbah rawatan, 0.7M Amberlite LA2, 10% kepekatan pengubahsuai, pH 2, dan 3 minit masa pengekstrakan, 70% asid suksinik telah diekstrak. Parameter yang paling mempengaruhi iaitu kepekatan agen pelucutan, pembawa, dan nisbah rawatan telah dipilih dalam kajian pengoptimuman menggunakan RSM, dan keputusan menunjukkan 38.9% dan 36.3% asid suksinik masing-masing telah diperolehi daripada larutan akueus dan air penapaian. Pada keadaan yang bersesuaian, penulenan asid suksinik menunjukkan 84% asid suksinik telah diperolehi dengan hampir 100% ketulenan dan membran cecair boleh digunakan sehingga kitaran kedua. Penemuan kajian ini menunjukkan proses ELM adalah teknologi yang berpotensi untuk mengekstrak dan memperoleh asid suksinik daripada pengeluaran berasaskan bio.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENTS</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF TABLES</b>	xi
	<b>LIST OF FIGURES</b>	xiii
	<b>LIST OF SYMBOLS</b>	xvi
	<b>LIST OF ABBREVIATIONS</b>	xviii
	<b>LIST OF APPENDICES</b>	xix
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Research Background	1
	1.2 Problem Statement	3
	1.3 Objectives of Study	5
	1.4 Research Scopes	5
	1.5 Significance of Study	7
	1.6 Research Outline	7
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>9</b>
	2.1 Succinic Acid	9
	2.1.1 Succinic Acid Market and Applications	10
	2.1.2 Production of Succinic Acid	13
	2.1.3 Downstream Processing of Bio-Based Succinic Acid	15

2.2	Emulsion Liquid Membrane	22
2.2.1	Emulsion Liquid Membrane Process	23
2.2.2	Mass Transfer Mechanism of Liquid Membrane and Driving Forces	24
2.2.2.1	Type I Emulsion Liquid Membrane System	25
2.2.2.2	Type II Emulsion Liquid Membrane System	26
2.2.3	Emulsion Liquid Membrane Component Selection	28
2.2.3.1	Extractant/Carrier	32
2.2.3.2	Diluent/ Solvent	38
2.2.3.3	Emulsifier/ Surfactant	39
2.2.3.4	Stripping Agent	41
2.2.3.5	Modifier	41
2.2.4	Demulsification	42
2.3	Green Emulsion Liquid Membrane	44
2.4	Stability of Emulsion Liquid Membrane	48
2.5	Factor Affecting ELM Extraction Process	52
2.6	Optimization using Response Surface Methodology (RSM)	54
<b>3</b>	<b>MATERIALS AND METHODS</b>	<b>56</b>
3.1	Introduction	56
3.2	Chemicals and Reagents	58
3.3	Experimental Procedures	59
3.3.1	Preparation of Simulated Feed Solution	59
3.3.2	Liquid Membrane Component Screening	60
3.3.2.1	Carrier Screening	60
3.3.2.2	Diluent Screening	61
3.3.2.3	Stripping Agent Screening	62
3.3.3	Preparation of Water in Oil (W/O) Emulsion	62
3.3.4	Stability Study of Primary Emulsion (W/O)	63



3.3.5	Stability Study of Double Emulsion (W/O/W)	64
3.3.6	Emulsion Liquid Membrane Stability, Extraction and Recovery Study	65
3.3.7	Optimization using Response Surface Methodology	67
	3.3.7.1 Design of Experiment (DOE)	67
	3.3.7.2 Data Analysis and Optimization	68
3.3.8	Succinic Acid Fermentation	69
	3.3.8.1 Strain and Inoculum Preparation	70
	3.3.8.2 Fermentation Process	70
3.4	Analytical Procedures	71
3.4.1	Succinic Acid Concentration Analysis	71
3.4.2	pH measurement	72
3.4.3	Emulsion Droplets Diameter measurement	73
3.4.4	Viscosity Measurement	74
<b>4</b>	<b>RESULTS AND DISCUSSION</b>	<b>75</b>
4.1	Introduction	75
4.2	Liquid Membrane Formulation	76
	4.2.1 Carrier Selection	76
	4.2.2 Diluent Selection	79
	4.2.3 Stripping Agent Selection	81
	4.2.6 ELM Transport Mechanism of Succinic Acid	83
4.3	Stability of Emulsion	84
	4.3.1 Stability of Water-in-Oil Emulsion	85
	4.3.1.1 Effect of Organic to Internal (O/I) Ratio	86
	4.3.1.2 Effect of Homogenizer Speed	88
	4.3.1.3 Effect of Emulsification Time	91
	4.3.1.4 Effect of Surfactant Concentration	93
	4.3.2 Stability of Water-in-Oil-in-Water Emulsion	97
	4.3.2.1 Effect of Span 80 Concentration	97

4.3.2.2	Effect of Tween 80 concentration	99
4.3.2.3	Effect of Agitation Speed	101
4.3.2.4	Effect of Agitation Time	103
4.4	Emulsion Liquid Membrane Extraction	105
4.4.1	Effect of Stripping Agent Concentration	106
4.4.2	Effect of Treat Ratio	108
4.4.3	Effect of Carrier Concentration	110
4.4.4	Effect of pH of Feed Phase	113
4.4.5	Effect of Modifier	116
4.4.6	Effect of Extraction Time	118
4.4.7	Effect of Agitation Speed	120
4.5	Recovery Optimization using RSM	122
4.5.1	Analysis of Variance (ANOVA) for Response and Regression Model	124
4.5.2	Interaction Effect of Parameter	127
4.5.3	Optimization Response and Verification Test	133
4.6	Prospect of Recycling and Recovery Process	135
4.6.1	Effect of Feed Phase Concentration	135
4.6.2	Liquid Membrane Recycling	138
<b>5</b>	<b>CONCLUSIONS AND RECOMMENDATIONS</b>	<b>139</b>
5.1	Conclusion	139
5.2	Recommendations	140
	<b>REFERENCES</b>	<b>141</b>
	Appendices A – G	161 – 190

## LIST OF TABLES

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	Physical properties of succinic acid	10
2.2	Market demand and applications of succinic acid	13
2.3	Performance of various succinic acid purification methods	21
2.4	Various carrier, diluent, stripping agents, and surfactants used in ELM study	33
2.5	Basic group amine carriers	37
2.6	Selection of HLB values of surfactant with appropriate application	40
2.7	Studies conducted on vegetable oil-based liquid membrane	46
2.8	Properties of some vegetable oils and conventional petroleum based diluents	47
2.9	Emulsion stability study performance	52
3.1	Chemical used in ELM and its properties	58
3.2	Chemical used in fermentation process	59
3.3	Emulsification condition for investigating primary emulsion stability	63
3.4	Dispersion condition for double emulsion stability study	64
3.5	Experimental range and levels of operating parameters	68
3.6	Overall design of experiment	68
3.7	Condition for organic acid HPLC measurements	72
4.1	Effect of diluent type on the extraction of succinic acid	80
4.2	The droplet size at various parameter study	85
4.3	Best condition from primary emulsion stability study	97
4.4	Effect of Span 80 concentration on W/O/W emulsion stability	98

4.5	Effect of Tween 80 concentration on W/O/W emulsion stability	100
4.6	Effect of agitation speed on W/O/W emulsion stability	102
4.7	Effect of agitation time on W/O/W emulsion stability	104
4.8	Best condition for W/O/W stability study	105
4.9	pH of internal and external phases at different Na <sub>2</sub> CO <sub>3</sub> concentration	107
4.10	Effect of Na <sub>2</sub> CO <sub>3</sub> concentration on internal droplet breakage	108
4.11	Effect of treat ratio on emulsion breakage	110
4.12	Effect of carrier concentration on emulsion breakage	112
4.13	Effect of pH on emulsion breakage	114
4.14	Effect of octanol concentration on emulsion breakage	117
4.15	Effect of extraction time on emulsion breakage	120
4.16	Effect of extraction speed on emulsion breakage	121
4.17	Best operating condition in ELM extraction study	122
4.18	Box-Behnken design matrix along with the experimental results and the predicted values of succinic acid recovery using ELM	123
4.19	Analysis of variance (ANOVA) for quadratic model of succinic acid recovery by ELM	125
4.20	The significance of the parameters in the model	128
4.21	Verification of optimized data for recovery study	133
4.22	Purity of succinic acid in the internal phase	137
4.23	Effect of re-use times on percentage recovery of succinic acid	138

## LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Molecular structure of succinic acid	9
2.2	Various chemicals that can be derived from succinic acid by chemical conversion	12
2.3	Reaction pathway from n-butane to maleic anhydride	14
2.4	A simplified scheme for downstream processing of fermentation products	16
2.5	A schematic flow diagram of an ELM process	23
2.6	Schematic of benzoic acid extraction by Type I ELM	26
2.7	Schematic of zinc extraction by Type II ELM	27
2.8	The mechanism of coupled transport in ELM	28
2.9	Types of carrier	36
2.10	Span 80 molecular structure	41
2.11	World production rate of major vegetable oils from 2010 to 2016	47
2.12	Vegetable oil yields per hectare per year in tonnes	48
3.1	Overall flowchart of experimental procedures	57
3.2	Flowchart of liquid membrane component screening	61
3.3	Flowchart for emulsion liquid membrane extraction	66
3.4	Flowchart of succinic acid fermentation	71
4.1	Effect of carrier types for succinic acid extraction	77
4.2	Effect of Amberlite LA2 concentration on succinic acid extraction	78
4.3	Stoichiometric plot of equilibrium extraction of succinic acid using Amberlite LA2	79
4.4	Effect of stripping agent types on succinic acid extraction	82
4.5	Effect of Na <sub>2</sub> CO <sub>3</sub> concentration on succinic acid extraction	83

4.6	Transport mechanism for succinic acid extraction in ELM	84
4.7	Effect of organic phase to internal phase ratio on emulsion stability	86
4.8	Microscopic images of emulsion at different organic phase to internal phase ratio (O/I) at 10 minutes	87
4.9	Effect of homogenizer speed on emulsion stability	89
4.10	Microscopic images of the emulsion for different homogenizer speed at 10 minutes	90
4.11	Effect of emulsification time on emulsion stability	91
4.12	Microscopic images of the emulsion at different emulsification time	93
4.13	Effect of surfactant concentration on emulsion stability	94
4.14	Microscopic images of the emulsion for different surfactant concentration (% w/v)	95
4.15	Microscopic image of emulsion at different Span 80 concentration at 10 minutes	98
4.16	Microscopic images of emulsion for different surfactant concentration at 10 minutes	101
4.17	Microscopic image of emulsion for different agitation speed at 10 minutes	103
4.18	Microscopic images of emulsion for different agitation time at 10 minutes	104
4.19	Effect of Na <sub>2</sub> CO <sub>3</sub> concentration towards the performance of succinic acid extraction	107
4.20	Effect of treat ratio towards the performance of succinic acid extraction	109
4.21	Effect of carrier concentration towards the performance of succinic acid extraction	111
4.22	Emulsion viscosity at different carrier concentration	112
4.23	Effect of pH on succinic acid extraction	114
4.24	Concentration of succinic acid and ion at different pH	115
4.25	Effect of octanol concentration on succinic acid extraction	116
4.26	Two types of succinic anion	117
4.27	Emulsion viscosity at different octanol concentration	118
4.28	Effect of extraction time on succinic acid extraction	119
4.29	Effect of agitation speed on succinic acid extraction	120

4.30	Comparison of experimental and RSM predicted response values for the recovery of succinic acid	125
4.31	Pareto chart of each parameter coefficient for succinic acid recovery	127
4.32	The 3D surface plot of interaction between carrier concentration and stripping agent concentration for succinic acid recovery	129
4.33	The 3D surface plot of interaction between stripping agent concentration and treat ratio for succinic acid recovery	131
4.34	The 3D surface plot of interaction between carrier concentration and treat ratio for succinic acid recovery	132
4.35	HPLC chromatogram for succinic acid fermentation broth	134
4.36	Effect of external phase concentration on succinic acid recovery	136

## LIST OF SYMBOLS

$[A]_f$	-	Final acid concentration in the external phase
$[A]_i$	-	Initial acid concentration in the external phase
$[A]_{int}$	-	Acid concentration in the internal phase
$C_i$	-	Solute concentration
$D_i$	-	Diffusion coefficient of solute I
$J_i$	-	Diffusive mass transport flux of solute I
$U_T$	-	Rotor speed
$V_{e,f}$	-	Volume of external phase after extraction
$V_{e,i}$	-	Volume of external phase before extraction
$V_{int}$	-	Volume of internal phase
$X_1, X_2, X_3$	-	Independent variables
$d_{32}$	-	Sauter mean diameter
$d_i$	-	Droplet diameter
$k_i$	-	The corresponding mass transport coefficient
$y_{i,exp}$	-	Experimental response value
$y_{i,cal}$	-	Calculated response value
$\beta_i, \beta_{ii}, \beta_{ij}$	-	Regression coefficient
D	-	Dissociation constant
M	-	Molar
pH	-	Logarithmic measure of hydrogen ion concentration
pKa	-	Acid dissociation constant at logarithmic scale
R	-	Coefficient of correlation
$R^2$	-	Coefficient of determination
T	-	Temperature
w/v	-	Weight per volume
x	-	Direction of diffusion



$\gamma$	-	Gamma
$\delta$	-	Hildebrand solubility parameter
$Y$	-	Predicted response
$n$	-	Number of sample
$\delta$	-	Thickness of the diffusional layer

**LIST OF ABBREVIATIONS**

AARD	-	Absolute average relative deviation
ANOVA	-	Analysis of variance
BBD	-	Box-Behnken design
BLM	-	Bulk liquid membrane
BOD	-	Biochemical oxygen demand
CAS	-	Chemical Abstracts Service
CCD	-	Central composite design
DOE	-	Department of Energy
DOE	-	Design of Experiment
ELM	-	Emulsion liquid membrane
HLB	-	Hydrophilic-lipophilic balance
HPLC	-	High performance liquid chromatography
IUPAC	-	International Union of Pure and Applied Chemistry
LLE	-	Liquid-liquid extraction
LM	-	Liquid membrane
O/W	-	Oil-in-water
OFAT	-	One-factor-at-a-time
PB	-	Plackett-Burman
RSM	-	Response surface methodology
SCP	-	Single cell protein
SLM	-	Supported liquid membrane
SSF	-	Solid state fermentation
TR	-	Treat ratio
UV	-	Ultraviolet
W/O	-	Water-in-oil
W/O/W	-	Water-in-oil-in-water

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	List of Publications	161
B	Standard Curve for Concentration of Succinic Acid	162
C	Liquid Membrane Component Selection	163
D	W/O Emulsion Stability Study	164
E	W/O/W Emulsion Stability Study	181
F	Succinic Acid Extraction Study	183
G	Step by Step of Succinic Acid Extraction Procedures	187
H	F Critical Values	188
I	HPLC Chromatogram	190

## **CHAPTER 1**

### **INTRODUCTION**

#### **1.1 Research Background**

Liquid membranes (LMs) are liquids that separate two aqueous phases of the source (feed) and the receiving (product) phases and are immiscible in these phases. These separation systems are being explored widely in many fields such as organic and inorganic chemistry, wastewater treatment, chemical engineering, biomedical engineering, and biotechnology. Research and development activities within these fields involve various applications of LM technology, such as removal of organic compounds, recovery of precious metals, removal of toxic metals, gas separations, and recovery of pharmaceutical compounds and fermentation products.

Liquid membrane technology can be divided into three types which are bulk liquid membrane (BLM), emulsion liquid membrane (ELM), and supported liquid membrane (SLM). Currently, ELM is introduced as an alternative technique to the separation process. ELM process consist of four main stages which are emulsification, dispersion and extraction, settling, and demulsification. Firstly, water-in-oil (W/O) emulsion is formed by emulsifying strip solution and liquid membrane phase in the presence of surfactant. After that, the emulsion is dispersed into an external feed phase containing the solute of interest. When the extraction is complete, the emulsion phase is separated from the external phase, and demulsified to recover the membrane phase and the internal phase.

ELM fulfils the promise of providing several attractive characteristics such as relatively low energy consumption due to it is operated at ambient temperature and pressure (Othman *et al.*, 2006; Chakrabarty *et al.*, 2010), fast extraction and high efficiency due to large available mass transfer area (Kaminski and Kwapinski, 2000; Rajasimman and Karthic, 2010), potential for removing various toxic substances down to very low levels (Frankenfeld and Li, 1987; Skelland and Meng, 1999), high selectivity particularly with the use of carrier agents in the liquid membrane phase that react exclusively with the target solutes (Frankenfeld and Li, 1987; Bartsch and Way, 1996), and easy regeneration of the spent emulsions by a demulsification process (Li and Calo, 1992). With these advantages the ELM process becomes an alternative and a promising technology to apply in research and industry. ELM was invented by Li (1968) for hydrocarbon separations. Since then, the ELM process was widely studied for industrial separations such as in removing various types of metal ions (Zhao *et al.*, 2010; Ahmad *et al.*, 2012; Bjorkegren and Karimi, 2012; Othman *et al.*, 2016), organic compounds (Yordanov and Boyadzhiev, 2004; Mortaheb *et al.*, 2008; Ng *et al.*, 2010; Lee and Kim, 2011; Jiao *et al.*, 2013; Fang *et al.*, 2016), and inorganic compounds (Marr and Koncar, 1993; Anitha *et al.*, 2015; Zhang *et al.*, 2016).

Recent development in the ELM process of organic compound is in downstream process of bio-succinic acid separation. This is due to the increasing demand of succinic acid as a building block chemical such as poly (1,3-propylene succinate), 1,4-butanediol, n-methyl pyrrolidinone,  $\gamma$ -butyrolactone, and tetrahydrofuran (Ranucci *et al.*, 2000; Lee and Hyun, 2010; Lee, 2011). On the other hand, there are various types of application of succinic acid as a specialty chemical such as plant growth stimulants, food ingredients, detergents, chelators, and corrosion inhibitors (Zeikus *et al.*, 1999). Therefore, with a wide range of applications, succinic acid demand is estimated to increase considerably. The current global production of succinic acid is 30,000 to 50,000 tons annually. In addition to that, the market price of succinic acid is US\$ 2,400 – 3,000 per ton (Cheng *et al.*, 2012).

However, the main drawback related to ELM is the emulsion instability which is governed by emulsion breakage. Membrane breakage in ELM systems involves the rupture of the emulsion and leakage of internal phase and extracted solute to the

external phase. This causes the decrease in the volume of the stripping phase (Ho and Kamallesh, 1992). As a result, the driving force for mass transfer, which is concentration gradient is reduced and increases the external feed concentration, thereby lowering the extraction efficiency. The instability can be attributed to the emulsion formulation in terms of the choice of carrier, diluent, surfactant, stripping agent, emulsification procedure, and process condition. The carrier should be selective to the target succinic acid solute while the stripping agent and the type of surfactant must be properly chosen to minimize the co-transport of water during the extraction process.

The diluent is very important, since it is the major component of the membrane phase and is crucial for emulsion stability. Diluent should have a low solubility in water in order to create the membrane phase, it should also provide high carrier solubility, high-boiling point, non-toxic and relatively cheap (Chakraborty *et al.*, 2010; Othman *et al.*, 2011). Most studies have commonly used kerosene as an organic diluent due to its low viscosity, readily available and non-polar character. However, kerosene is not considered environmentally friendly and harmful to human. Alternatively, palm oil (cooking oil) can be chosen as a renewable organic diluent, as it is readily available and may contain natural surface-active agents, which improve the stability of an emulsion (Chow and Ho, 1996). Besides that, palm oil possesses a low melting point, low specific gravity, high flash point and non-volatile. Most importantly, palm oil has a low dielectric constant ( $\sim 3$ ) which makes them non-polar and their aliphatic property allows them to be immiscible in the external phase. In addition, palm oil was proven to work well in extraction of heavy metal, dye, acetic acid, and phenol (Narayanan and Palanivelu, 2008; Muthuraman and Teng, 2009; Badgujar and Rastogi, 2011; Bjorkegren and Karimi, 2012).

## 1.2 Problem Statement

The ELM process is very unique and promising in the extraction of the targeted species due to high interfacial area for mass transfer, economical, low energy

consumption, simultaneous extraction and stripping process, efficient for low solute concentration, and requirement of small quantity of solvent (Hong *et al.*, 2001; Othman *et al.*, 2005; Gupta *et al.*, 2013). Nevertheless, the various advantages of the ELM process still have been limited for industrial applications due to the emulsion globules are unstable against fluid shear.

The prepared emulsion should be sufficiently stable during the dispersion for solute extraction. Unstable emulsion resulted in emulsion breakage or swelling. Emulsion breakage cause release of the internal stripping solution and the extracted solute which reduce the extraction performance (Ho and Kamalesh, 1992; Wan and Zhang, 2002). Meanwhile, emulsion swelling resulting in destructive effect to the system because it can reduce membrane thickness, diluting the recovered solute, and decreasing the driving force for the extraction (Kulkarni *et al.*, 2002; Park *et al.*, 2004). On the contrary, too stable emulsion may result in difficulties during demulsification for solute recovery.

Many studies were carried out to investigate the emulsion liquid membrane stability (Gheorghe *et al.*, 2008; Othman *et al.*, 2009; Sulaiman *et al.*, 2013; Bjorkegren and Karimi, 2015). Their study found that the primary emulsion can be stable, ranging from a few minutes to 24 days, depending on the emulsion formulation and condition of emulsification. Besides that, an appropriate condition also crucial to maintain the emulsion stability during the extraction process. Worst condition can result in 80% of emulsion breakage which is very undesirable (Othman *et al.*, 2009; Hasan *et al.*, 2009). Therefore, the effects of several factors on liquid membrane and emulsion stability were investigated in this study.

On the other hand, an important component of ELM, which is diluent must be properly chosen to promote an environmentally friendly process. An alternative vegetable oil diluent such as palm oil can be used to replace kerosene due to its readily available and possessing the characteristics of a good diluent. Therefore, the possibility of using palm oil as ELM component was investigated in the liquid membrane formulation for the extraction of succinic acid.

In order to obtain a stable emulsion and high performance of succinic acid extraction, the selectivity of the ELM formulation, including the carrier, stripping agent, and diluent is very important. Investigation of process parameters during the extraction also important in order to understand the process of succinic acid extraction using the ELM process. Besides that, the optimization process was carried out using response surface methodology (RSM) method to find the relation between the parameter of succinic acid recovery. In addition, for the prospects of economical process, the capability of recycling liquid membrane was also investigated.

### **1.3 Objectives of Study**

The main focus of this study is to determine the possibility of developing the ELM purification of succinic acid using green formulation. In summary, the objectives of this study are:

- i. To formulate green emulsion liquid membrane for succinic acid extraction;
- ii. To study and optimize the factors affecting stability of emulsion liquid membrane;
- iii. To investigate the affecting parameter of succinic acid extraction using an emulsion liquid membrane followed by recovery optimization using RSM.

### **1.4 Research Scopes**

The aim of this study is to develop green ELM system for the extraction of succinic acid from fermentation broth. First of all, an emulsion liquid membrane was formulated to extract succinic acid. In order to formulate the ELM process, suitable components in the system are required for selectively extract succinic acid from the mixture. Therefore, the formulation was initiated by the screening of liquid membrane components, where liquid-liquid extraction (LLE) was carried out with few types of carriers (TOA, Amberlite LA-2, TDA), diluents (kerosene and palm oil) and stripping agents (NaOH, Na<sub>2</sub>CO<sub>3</sub>). This screening process can determine the appropriate



condition range for extraction of succinic acid from simulated solution. The composition of simulated solution is based on the actual fermentation broth.

Then, the stability of the ELM system was investigated by manipulating the organic to internal ratio (1 to 3), homogenizer speed (5000 to 12000 rpm), emulsifying time (3 to 15 minutes), and concentration of surfactant (1 to 10% w/v) during the emulsification stage. Span 80 was used as the surfactant in this study. Besides that, the stability of water-in-oil-in-water (W/O/W) was also studied by varying Span 80 concentration (1 to 7% w/v), Tween 80 concentration (0 to 4% w/v), agitation speed (200 to 500 rpm), and agitation time (1 to 7 minutes). The influence of these parameters on the emulsion droplets and globules size distribution was determined under the microscope.

Next, the application of liquid membrane for succinic acid extraction was studied. The parameters investigated were the effect of stripping agent concentration (0.005 – 0.01M), emulsion to external treat ratio (1:1 – 1:7), concentration of carrier (0.3 – 1.0M), pH of the external solution (1 – 7), modifier concentration (0 – 15%), extraction time (1 – 7 minutes), and effect of extraction speed (100 – 400 rpm). The influences of different parameters were examined using traditional one-factor-at-a-time (OFAT) approach. These parameters were investigated to determine the optimum condition of ELM process for succinic acid extraction. Meanwhile, the range of the most significant parameters was determined for the next objective.

Research on application of ELM for succinic acid covered the extraction study but very limited in product recovery aspect. Therefore, this study extend the research of ELM by considering recovery and enrichment ratio. Response surface methodology (RSM) was applied to optimize the influencing parameter on the succinic acid recovery. A set of statistical experimental design was created to optimize the process parameters including stripping agent concentration (0.005 – 0.035M), carrier concentration (0.5 – 0.9M), and treat ratio (1:1 – 1:5). A total of 15 experimental runs were required based on a three variable Box Behnken design created using Statistica 8.0 (Stat Soft). Equations of model obtained were validated through statistical tests known as the analysis of variance (ANOVA). Response surfaces were plotted to

determine individual and interactive effects of the test variables on the percentage recovery of succinic acid. The optimum condition obtained from RSM study was applied for succinic acid recovery from simulated and real broth.

In addition, to establish a favourable procedure for succinic acid recovery, the experiment was conducted to determine recovery performance and purity of simulated succinic acid from different external feed concentration (10 – 80 g/l) and real fermentation broth. On the other hand, the capability of recycling liquid membrane was carried out for the prospect of an economical process.

## **1.5 Significance of Study**

Due to the increasing demand of succinic acid in many applications, it is essential to extract and recover succinic acid from biological production. ELM was implemented as promising alternative separation technology to the existing conventional process. It provides tremendous advantages of high transport efficiency due to the large interfacial area for mass transfer, simple operation, low energy consumption, simultaneous extraction and stripping process, efficient for low solute extraction, and low operating cost. Besides, the use of palm oil as diluent can promote a more environmental friendly process.

## **1.6 Research Outline**

This thesis contains five chapters, which are presented in a sequential order. As an introduction, Chapter 1 presents a brief introduction of the research background, problem statement, research objectives and scopes, and significance of the study. Chapter 2 provides a review of succinic acid characteristics and applications, ELM technology, green ELM, ELM stability, ELM extraction of succinic acid, and optimization using RSM. In Chapter 3, the materials and methods including chemical

and reagents used, experimental procedure for liquid membrane component screening, emulsion liquid membrane extraction, RSM optimization, succinic acid fermentation, and analytical procedures were provided. Meanwhile, data obtained were analysed and discussed in Chapter 4. Finally, Chapter 5 suggests the conclusion and recommendation for future work.

## REFERENCES

- Abbassian, K. and Kargari, A. (2016). Modification of Membrane Formulation for Stabilization of Emulsion Liquid Membrane for Extraction of Phenol from Aqueous Solutions. *Journal of Environmental Chemical Engineering*, 4(4), 3926-3933.
- Abismail, B., Canselier, J. P., Wilhelm, A. M., Delmas, H. and Gourdon, C. (1999). Emulsification by Ultrasound: Drop Size Distribution and Stability. *Ultrasonics Sonochemistry*, 6(1-2), 75-83.
- Ahmad, A. L., Kusumastuti, A., Derek, C. J. C. and Ooi, B. S. (2011). Emulsion Liquid Membrane for Heavy Metal Removal: An Overview on Emulsion Stabilization and Destabilization. *Chemical Engineering Journal*, 171(3), 870-882.
- Ahmad, A. L., Kusumastuti, A., Derek, C. J. C. and Ooi, B. S. (2012). Emulsion Liquid Membrane for Cadmium Removal: Studies on Emulsion Diameter and Stability. *Desalination*, 287, 30-34.
- Ahmad, A. L., Shah Buddin, M. M. H., Ooi, B. S. and Kusumastuti, A. (2015a). Cadmium Removal using Vegetable Oil Based Emulsion Liquid Membrane (ELM): Membrane Breakage Investigation. *Jurnal Teknologi (Sciences and Engineering)*, 75(1), 39-46.
- Ahmad, A. L., Shah Buddin, M. M. H., Ooi, B. S. and Kusumastuti, A. (2016). Utilization of Environmentally Benign Emulsion Liquid Membrane (ELM) for Cadmium Extraction from Aqueous Solution. *Journal of Water Process Engineering*, 15, 26-30.
- Ahmad, A. L., Shah, M. M. H. and Ooi, B. S. (2015b). Extraction of Cd(II) Ions by Emulsion Liquid Membrane (ELM) using Aliquat 336 as Carrier. *American Journal of Chemistry*, 5(3A), 1-6.

- Andersson, C. (2009). *Biobased Production of Succinic Acid by Escherichia coli Fermentation*. Doctor of Philosophy, Lulea University of Technology, Sweden.
- Andersson, C., Hodge, D., Berglund, K. A. and Rova, U. (2007). Effect of Different Carbon Sources on the Production of Succinic Acid Using Metabolically Engineered Escherichia coli. *Biotechnology Progress*, 23(2), 381-388.
- Anitha, M., Ambare, D. N., Singh, D. K., Singh, H. and Mohapatra, P. K. (2015). Extraction of Neodymium from Nitric Acid Feed Solutions using an Emulsion Liquid Membrane Containing TOPO and DNPPA as The Carrier Extractants. *Chemical Engineering Research and Design*, 98, 89-95.
- Badgujar, V. and Rastogi, N. K. (2011). Extraction of Phenol from Aqueous Effluent using Triglycerides in Supported Liquid Membrane. *Desalination and Water Treatment*, 36(1-3), 187-196.
- Baker, R. W. (2000). *Membrane Technology and Applications*. New York: McGraw-Hill.
- Balasubramanian, A. and Venkatesan, S. (2012). Removal of Phenolic Compounds from Aqueous Solutions by Emulsion Liquid Membrane Containing Ionic Liquid [BMIM]<sup>+</sup>[PF6]<sup>-</sup> in Tributyl phosphate. *Desalination*, 289, 27-34.
- Bartsch, R. A. and Way, J. D. (1996). *Chemical Separations with Liquid Membranes* (Vol. 642): American Chemical Society.
- Bayazit, S. S., Uslu, H. and Inci, I. (2009). Comparative Equilibrium Studies for Citric Acid by Amberlite LA2 or Tridodecylamine (TDA). *Journal of Chemical and Engineering Data*, 54(7), 1991-1996.
- Bayraktar, E. (2001). Response Surface Optimization of the Separation of DL-Tryptophan using an Emulsion Liquid Membrane. *Process Biochemistry*, 37(2), 169-175.
- Becher, P. (1985). *Encyclopedia of Emulsion Technology* (1<sup>st</sup> ed.). New York: Marcel Dekker.
- Bechthold, I., Bretz, K., Kabasci, S., Kopitzky, R. and Springer, A. (2008). Succinic Acid: A New Platform Chemical for Biobased Polymers from Renewable Resources. *Chemical Engineering and Technology*, 31(5), 647-654.
- Benyahia, N., Belkhouche, N. and Jönsson, J. A. (2014). A Comparative Study of Experimental Optimization and Response Surface Methodology of Bi(III)

- Extraction by Emulsion Organophosphorus Liquid Membrane. *Journal of Environmental Chemical Engineering*, 2(3), 1756-1766.
- Berglund, K. A., Elankovan, P. and Glassner, D. A. (1991). *U. S. Patent No. 5, 034, 105*. Michigan: U. S. Patent Office.
- Bjorkegren, S. and Karimi, R. F. (2012). *A Study of the Heavy Metal Extraction Process using Emulsion Liquid Membranes*. Master, Chalmers University of Technology, Sweden.
- Bjorkegren, S., Fassihi Karimi, R., Martinelli, A., Jayakumar, N. S. and Hashim, M. A. (2015). A New Emulsion Liquid Membrane Based on a Palm Oil for the Extraction of Heavy Metals. *Membranes*, 5(2), 168-179.
- Bizek, V., Horacek, J. and Kousova, M. (1993). Amine Extraction of Citric Acid: Effect of Diluent. *Chemical Engineering Science*, 48(8), 1447-1457.
- Box, G. E. P. and Wilson, K. B. (1951). On the Experimental Attainment of Optimum Conditions. *Journal of the Royal Statistical Society. Series B (Methodological)*, 13(1), 1-45.
- Bozell, J. J. and Petersen, G. R. (2010). Technology Development for the Production of Biobased Products from Biorefinery Carbohydrates. The US Department of Energy's "Top 10" Revisited. *Green Chemistry*, 12(4), 539-554.
- Canari, R. and Eyal, A. M. (2003). Effect of pH on Dicarboxylic Acids Extraction by Amine-Based Extractants. *Industrial and Engineering Chemistry Research*, 42(7), 1293-1300.
- Chakrabarty, K., Saha, P. and Ghoshal, A. K. (2010a). Separation of Lignosulfonate from its Aqueous Solution using Emulsion Liquid Membrane. *Journal of Membrane Science*, 360(1-2), 34-39.
- Chakrabarty, K., Saha, P. and Ghoshal, A. K. (2010b). Separation of Mercury from its Aqueous Solution through Supported Liquid Membrane using Environmentally Benign Diluent. *Journal of Membrane Science*, 350(1-2), 395-401.
- Chakraborty, M., Bhattacharya, C. and Datta, S. (2010). Emulsion Liquid Membranes: Definitions and Classification, Theories, Module Design, Applications, New Directions and Perspectives. In V. S. Kislik (Ed.), *Liquid Membranes* (pp. 141-199). Amsterdam: Elsevier.

- Chakraborty, M., Murthy, Z. V. P., Bhattacharya, C. and Datta, S. (2005). Process Intensification: Extraction of Chromium(VI) by Emulsion Liquid Membrane. *Separation Science and Technology*, 40(11), 2353-2364.
- Chang, S. H. (2014). Vegetable oil as Organic Solvent for Wastewater Treatment in Liquid Membrane Processes. *Desalination and Water Treatment*, 52(1-3), 88-101.
- Chanukya, B. S. and Rastogi, N. K. (2013). Extraction of Alcohol from Wine and Color Extracts using Liquid Emulsion Membrane. *Separation and Purification Technology*, 105, 41-47.
- Chanukya, B. S., Kumar, M. and Rastogi, N. K. (2013). Optimization of Lactic Acid Pertraction using Liquid Emulsion Membranes by Response Surface Methodology. *Separation and Purification Technology*, 111, 1-8.
- Chaouchi, S. and Hamdaoui, O. (2014). Acetaminophen Extraction by Emulsion Liquid Membrane using Aliquat 336 as Extractant. *Separation and Purification Technology*, 129, 32-40.
- Chaouchi, S. and Hamdaoui, O. (2015). Extraction of Endocrine Disrupting Compound Propylparaben from Water by Emulsion Liquid Membrane using Trioctylphosphine Oxide as Carrier. *Journal of Industrial and Engineering Chemistry*, 22, 296-305.
- Chaudhuri, J. B. and Pyle, D. L. (1992). Emulsion Liquid Membrane Extraction of Organic Acids-II. Experimental. *Chemical Engineering Science*, 47(1), 49-56.
- Chemco. (2012). Succinic Acid. Retrieved from <https://thechemco.com/chemical/succinic-acid/> (6 November 2012)
- Chen, X., Jiang, S., Li, X., Pan, L., Zheng, Z. and Luo, S. (2013). Production of Succinic Acid and Lactic Acid by *Corynebacterium Crenatum* under Anaerobic Conditions. *Annals of Microbiology*, 63(1), 39-44.
- Cheng, K. K., Zhao, X. B., Zeng, J., Wu, R. C., Xu, Y. Z., Liu, D. H. and Zhang, J. A. (2012). Downstream Processing of Biotechnological Produced Succinic Acid. *Applied Microbiology and Biotechnology*, 95(4), 841-850.
- Chiha, M., Hamdaoui, O., Ahmedchekkat, F. and Pétrier, C. (2010). Study on Ultrasonically Assisted Emulsification and Recovery of Copper(II) from Wastewater using an Emulsion Liquid Membrane Process. *Ultrasonics Sonochemistry*, 17(2), 318-325.

- Chiha, M., Samar, M. H. and Hamdaoui, O. (2006). Extraction of Chromium (VI) from Sulphuric Acid Aqueous Solutions by a Liquid Surfactant Membrane (LSM). *Desalination*, 194(1), 69-80.
- Chou, K. W., Norli, I. and Anees, A. (2010). Evaluation of the Effect of Temperature, NaOH Concentration and Time on Solubilization of Palm Oil Mill Effluent (POME) using Response Surface Methodology (RSM). *Bioresource Technology*, 101(22), 8616-8622.
- Choudhury, A., Sengupta, S., Bhattacharjee, C. and Datta, S. (2010). Extraction of Hexavalent Chromium from Aqueous Stream by Emulsion Liquid Membrane (ELM). *Separation Science and Technology*, 45(2), 178-185.
- Chow, M. C. and Ho, C. C. (1996). Properties of Palm-Oil-in-Water Emulsions: Effect of Mixed Emulsifiers. *Journal of the American Oil Chemists' Society*, 73(1), 47-53.
- Cornell, J. A. (1990). *How to Apply Response Surface Methodology* (Vol. 8). United States: ASQC.
- Daas, A. and Hamdaoui, O. (2010). Extraction of Anionic Dye from Aqueous Solutions by Emulsion Liquid Membrane. *Journal of Hazardous Materials*, 178(1-3), 973-981.
- Danesi, P. R., Horwitz, E. P., Vandegrift, G. F. and Chiarizia, R. (1981). Mass Transfer Rate through Liquid Membranes: Interfacial Chemical Reactions and Diffusion as Simultaneous Permeability Controlling Factors. *Separation Science and Technology*, 16(2), 201-211.
- Datta, R. (1992). *U. S. Patent No. 5, 143, 833*. Chicago: U. S. Patent Office.
- Datta, R., Glassner, D. A., Jain, M. K. and Vick Roy, J. R. (1992). *U. S. Patent No. 5,168,055*. Chicago: U. S. Patent Office.
- Delhomme, C., Weuster-Botz, D. and Kuhn, F. E. (2009). Succinic Acid from Renewable Resources as a C4 Building Block Chemical. A Review of the Catalytic Possibilities in Aqueous Media. *Green Chemistry*, 11(1), 13-26.
- Devulapalli, R. and Jones, F. (1999). Separation of Aniline from Aqueous Solutions using Emulsion Liquid Membranes. *Journal of Hazardous Materials*, 70(3), 157-170.
- Djenouhat, M., Hamdaoui, O., Chiha, M. and Samar, M. H. (2008). Ultrasonication-Assisted Preparation of Water-In-Oil Emulsions and Application to the Removal of Cationic Dyes from Water by Emulsion Liquid Membrane: Part 2.



- Permeation and Stripping. *Separation and Purification Technology*, 63(1), 231-238.
- Dominguez, A., Fernandez, A., Gonzalez, N., Iglesias, E. and Montenegro, L. (1997). Determination of Critical Micelle Concentration of Some Surfactants by Three Techniques. *Journal of Chemical Education*, 74(10), 1227-1231.
- Draxler, J., Frust, W. and Marr, R. (1988). Separation of Metal Species by Emulsion Liquid Membranes. *Journal of Membrane Science*, 38(3), 281-293.
- Eyal, A. M. and Bressler, E. (1993). Industrial Separation of Carboxylic and Amino Acids by Liquid Membranes: Applicability, Process Considerations, and Potential Advantage. *Biotechnology and Bioengineering*, 41(3), 287-295.
- Eyupoglu, V. and Kumbasar, R. A. (2015). Extraction of Ni(II) from spent Cr-Ni Electroplating Bath Solutions using LIX 63 and 2BDA as Carriers by Emulsion Liquid Membrane Technique. *Journal of Industrial and Engineering Chemistry*, 21, 303-310.
- Fan, H. (1999). *Chemical Reactions and Mass Transport in Emulsion Liquid Membrane*. Doctor of Philosophy, New Jersey Institute of Technology.
- Fang, Z., Liu, X., Zhang, M., Sun, J., Mao, S., Lu, J. and Rohani, S. (2016). A Neural Network Approach to Simulating the Dynamic Extraction Process Of L-Phenylalanine from Sodium Chloride Aqueous Solutions by Emulsion Liquid Membrane. *Chemical Engineering Research and Design*, 105, 188-199.
- Flick, E. W. (2002). *Industrial Solvents Handbook* (5th ed.). New Jersey: Noyes Data Co.
- Frankenfeld, J. W. and Li, N. N. (1987). Recent Advances in Liquid Membrane Technology. In R. W. Rousseau (Ed.), *Handbook of Separation Process Technology* (pp. 840-861). New York: Wiley.
- Frankenfeld, J. W., Cahn, R. P. and Li, N. N. (1981). Extraction of Copper by Liquid Membranes. *Separation Science and Technology*, 16(4), 385-402.
- Gaikwad, S. G. and Pandit, A. B. (2008). Ultrasound emulsification: Effect of Ultrasonic and Physicochemical Properties on Dispersed Phase Volume and Droplet Size. *Ultrasonics Sonochemistry*, 15(4), 554-563.
- Gascon, J., Valenciano, R., Tellez, C., Herguido, J. and Menendez, M. (2006). A Generalized Kinetic Model for the Partial Oxidation of N-Butane to Maleic Anhydride Under Aerobic and Anaerobic Conditions. *Chemical Engineering Science*, 61(19), 6385-6394.

- Gasser, M. S., El-Hefny, N. E. and Daoud, J. A. (2008). Extraction of Co(II) from Aqueous Solution using Emulsion Liquid Membrane. *Journal of Hazardous Materials*, 151(2-3), 610-615.
- Gheorghe, A., Stoica, A. and Floarea, O. (2008). Emulsion Liquid Membrane Stability. *University Politehnica of Bucharest Scientific Bulletin*, 70(3), 23-30.
- Ghoshal, A. K. (2012). Fundamentals of Liquid Membrane. In K. Mohanty and M. K. Purkait (Eds.), *Membrane Technologies and Applications* (pp. 255-278). New York: CRC Press.
- Glassner, D. A. and Datta, R. (1992). Process for the Production and Purification of Succinic Acid: Google Patents.
- Glassner, D. A., Elankovan, P., Beacom, D. R. and Berglund, K. A. (1995). Purification Process for Succinic Acid Produced by Fermentation. *Applied Biochemistry and Biotechnology*, 51(1), 73-82.
- Goyal, R. K., Jayakumar, N. S. and Hashim, M. A. (2011). Chromium Removal by Emulsion Liquid Membrane using [BMIM]<sup>+</sup>[NTf<sub>2</sub>]<sup>-</sup> as Stabilizer and TOMAC as Extractant. *Desalination*, 278(1-3), 50-56.
- GreenPalm (2016). Resources. Retrieved from <http://greenpalm.org/resources/graphs> (13 September 2016)
- Gunstone, F. D. (2002). Production and Trade of Vegetable Oils. In F. D. Gunstone (Ed.), *Vegetable Oils in Food Technology: Composition, Properties and Uses*. USA: Blackwell Publishing.
- Gupta, S., Chakraborty, M. and Murthy, Z. V. P. (2013). Removal of Mercury by Emulsion Liquid Membranes: Studies on Emulsion Stability and Scale Up. *Journal of Dispersion Science and Technology*, 34(12), 1733-1741.
- Haaland, P. D. (1989). *Experimental Design in Biotechnology*. New York: Marcel Dekker Inc.
- Hajarabeevi, N., Mohammed Bilal, I., Easwaramoorthy, D. and Palanivelu, K. (2009). Facilitated Transport of Cationic Dyes Through a Supported Liquid Membrane With D2EHPA as Carrier. *Desalination*, 245(1), 19-27.
- Hall, S., Pacek, A. W., Kowalski, A. J., Cooke, M. and Rothman, D. (2013). The Effect of Scale and Interfacial Tension on Liquid-Liquid Dispersion in in-Line Silverson Rotor-Stator Mixers. *Chemical Engineering Research and Design*, 91(11), 2156-2168.

- Hasan, M. A., Selim, Y. T. and Mohamed, K. M. (2009). Removal of Chromium from Aqueous Waste Solution using Liquid Emulsion Membrane. *Journal of Hazardous Materials*, 168(2-3), 1537-1541.
- Hayworth, H. C., Ho, W. S., Burns, W. A. and Li, N. N. (1983). Extraction of Uranium from Wet Process Phosphoric Acid by Liquid Membranes. *Separation Science and Technology*, 18(6), 493-521.
- Hepburn, A. J. (2011). *The Synthesis of Succinic Acid and Its Extraction from Fermentation Broth Using a Two-Phase Partitioning Bioreactor*. Master, Queen's University, Canada.
- Hepburn, A. J. and Daugulis, A. J. (2012). The use of CO<sub>2</sub> for Reversible pH Shifting, and the Removal of Succinic Acid in a Polymer-Based Two-Phase Partitioning Bioreactor. *Journal of Chemical Technology and Biotechnology*, 87(1), 42-50.
- Hiroshi, T. (1990). *Liquid Membranes: Chemical Applications*. (1st ed.). Japan: CRC Press.
- Ho, W. S. and Kamalesh, K. S. (1992). *Membrane Handbook*. New York: Chapman & Hall.
- Hong, Y., Hong, W. and Chang, H. (2000). Selective Extraction of Succinic Acid from Binary Mixture of Succinic Acid and Acetic Acid. *Biotechnology Letters*, 22(10), 871-874.
- Hong, Y., Hong, W. and Han, D. (2001). Application of Reactive Extraction to Recovery of Carboxylic Acids. *Biotechnology and Bioprocess Engineering*, 6(6), 386-394.
- Hou, W. and Papadopoulos, K. D. (1997). W1/O/W2 and O1/W/O2 Globules Stabilized with Span 80 and Tween 80. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 125(2-3), 181-187.
- Hsu, E. C. and Li, N. N. (1985). Membrane Recovery in Liquid Membrane Separation Process. *Separation Science and Technology*, 20(2-3), 115-130.
- Huh, Y. S., Hong, Y. K., Hong, W. H. and Chang, H. N. (2004). Selective Extraction of Acetic Acid from the Fermentation Broth Produced by *Mannheimia Succiniciproducens*. *Biotechnology Letters*, 26(20), 1581-1584.
- Huh, Y. S., Jun, Y. S., Hong, Y. K., Song, H., Lee, S. Y. and Hong, W. H. (2006). Effective Purification of Succinic Acid from Fermentation Broth Produced by *Mannheimia Succiniciproducens*. *Process Biochemistry*, 41(6), 1461-1465.

- ICIS (2015). BioAmber focuses on more plants. Retrieved from <https://www.icis.com/resources/news/2015/08/07/9912003/bioamber-focuses-on-more-plants/> (7 August 2015).
- Inci, I., Asci, Y. S. and Uslu, H. (2012). LSER Modeling of Extraction of Succinic Acid by Tridodecylamine Dissolved in 2-Octanone and 1-Octanol. *Journal of Industrial and Engineering Chemistry*, 18(1), 152-159.
- Isar, J., Agarwal, L., Saran, S. and Saxena, R. K. (2006). A Statistical Method for Enhancing the Production of Succinic Acid from Escherichia Coli under Anaerobic Conditions. *Bioresource Technology*, 97(13), 1443-1448.
- Jiao, H., Peng, W., Zhao, J. and Xu, C. (2013). Extraction Performance of Bisphenol A from Aqueous Solutions by Emulsion Liquid Membrane using Response Surface Methodology. *Desalination*, 313, 36-43.
- Jiao, J. and Burgess, D. J. (2003). Rheology and Stability of Water-in-Oil-in-Water Multiple Emulsions Containing Span 83 and Tween 80. *AAPS PharmSci*, 5(1), 62-73.
- Joshi, H. C., Pandey, I. P., Kumar, A. and Garg, N. (2012). A Study of Various Factors Determining the Stability of Molecules. *Advances in Pure and Applied Chemistry*, 1(1), 7-11.
- Jun, Y. S., Huh, Y. S., Hong, W. H. and Hong, Y. K. (2005). Kinetics of the Extraction of Succinic Acid with Tri-n-octylamine in 1-Octanol Solution. *Biotechnology Progress*, 21(6), 1673-1679.
- Jun, Y. S., Lee, E. Z., Huh, Y. S., Hong, Y. K., Hong, W. H. and Lee, S. Y. (2007). Kinetic Study for the Extraction of Succinic Acid With TOA in Fermentation Broth; Effects of pH, Salt and Contaminated Acid. *Biochemical Engineering Journal*, 36(1), 8-13.
- Kaminski, W. and Kwapinski, W. (2000). Applicability of Liquid Membranes in Environmental Protection. *Polish Journal of Environmental Studies*, 9(1), 37-43.
- Kargari, A., Kaghazchi, T. and Soleimani, M. (2006). Mathematical Modeling of Emulsion Liquid Membrane Pertraction of Gold (III) From Aqueous Solutions. *Journal of Membrane Science*, 279(1-2), 380-388.
- Karjiban, R. A., Basri, M., Rahman, M. B. A. and Salleh, A. B. (2012). Structural Properties of Nonionic Tween80 Micelle in Water Elucidated by Molecular Dynamics Simulation. *APCBEE Procedia*, 3, 287-297.

- Kataoka, T., Nishiki, T. and Kimura, S. (1989). Phenol Permeation through Liquid Surfactant Membrane-Permeation Model and Effective Diffusivity. *Journal of Membrane Science*, 41, 197-209.
- Kertes, A. S. and King, C. J. (1986). Extraction Chemistry of Fermentation Product Carboxylic Acids. *Biotechnology and Bioengineering*, 28(2), 269-282.
- Keshav, A., Wasewar, K. L. and Chand, S. (2009). Reactive Extraction of Propionic Acid Using Tri-n-octylamine. *Chemical Engineering Communications*, 197, 606-626.
- Kiani, S. and Mousavi, S. M. (2013). Ultrasound Assisted Preparation of Water in Oil Emulsions and Their Application in Arsenic (V) Removal from Water in an Emulsion Liquid Membrane Process. *Ultrasonics Sonochemistry*, 20(1), 373-377.
- Kulkarni, P. S. (2003). Recovery of Uranium (VI) from Acidic Wastes using Tri-n-octylphosphine Oxide and Sodium Carbonate Based Liquid Membrane. *Chemical Engineering Journal*, 92(1), 209-214.
- Kulkarni, P. S. and Mahajani, V. V. (2002). Application of Liquid Emulsion Membrane (LEM) Process for Enrichment of Molybdenum From Aqueous Solutions. *Journal of Membrane Science*, 201(1-2), 123-135.
- Kulkarni, P. S., Mukhopadhyay, S., Bellary, M. P. and Ghosh, S. K. (2002). Studies on Membrane Stability and Recovery of Uranium (VI) from Aqueous Solutions using a Liquid Emulsion Membrane Process. *Hydrometallurgy*, 64(1), 49-58.
- Kumbasar, R. A. (2008a). Selective Separation of Chromium (VI) from Acidic Solutions Containing Various Metal Ions Through Emulsion Liquid Membrane using Trioctylamine as Extractant. *Separation and Purification Technology*, 64(1), 56-62.
- Kumbasar, R. A. (2008b). Studies on Extraction of Chromium (VI) from Acidic Solutions Containing Various Metal Ions by Emulsion Liquid Membrane Using Alamine 336 as Extractant. *Journal of Membrane Science*, 325(1), 460-466.
- Kumbasar, R. A. (2010). Selective Extraction and Concentration of Cobalt from Acidic Leach Solution Containing Cobalt and Nickel Through Emulsion Liquid Membrane using PC-88A as Extractant. *Separation and Purification Technology*, 64(1), 273-279.

- Kumbasar, R. A. (2010). Selective Extraction of Chromium (VI) from Multicomponent Acidic Solutions by Emulsion Liquid Membranes using Tributylphosphate as Carrier. *Journal of Hazardous Materials*, 178(1-3), 875-882.
- Kumbasar, R. A. (2012a). Selective Extraction of Cobalt from Strong Acidic Solutions Containing Cobalt and Nickel Through Emulsion Liquid Membrane using TIOA as Carrier. *Journal of Industrial and Engineering Chemistry*, 18(6), 2076-2082.
- Kumbasar, R. A. (2012b). Selective Transport of Cobalt (II) from Ammoniacal Solutions Containing Cobalt (II) and Nickel (II) By Emulsion Liquid Membranes using 8-Hydroxyquinoline. *Journal of Industrial and Engineering Chemistry*, 18(1), 145-151.
- Kurzrock, T. and Botz, D. W. (2011). New Reactive Extraction Systems for Separation of Bio-Succinic Acid. *Bioprocess and Biosystems Engineering*, 34(7), 779-787.
- Landucci, R., Goodman, B. and Wyman, C. (1994). Methodology for Evaluating the Economics of Biologically Producing Chemicals and Materials from Alternative Feedstocks. *Applied Biochemistry and Biotechnology*, 45(1), 677-696.
- Larson, K., Raghuraman, B. and Wiencek, J. (1994). Electrical and Chemical Demulsification Techniques for Microemulsion Liquid Membrane. *Journal of Membrane Science*, 91(3), 231-238.
- Lee, P. C., Lee, S. Y., Hong, S. H., Chang, H. N. and Park, S. C. (2003). Biological Conversion of Wood Hydrolysate to Succinic Acid by *Anaerobiospirillum Succiniciproducens*. *Biotechnology Letters*, 25(2), 111-114.
- Lee, P. C., Lee, W. G., Lee, S. Y., Chang, H. N. and Chang, Y. K. (2000). Fermentative Production of Succinic Acid from Glucose and Corn Steep Liquor by *Anaerobiospirillum Succiniciproducens*. *Biotechnology and Bioprocess Engineering*, 5(5), 379-381.
- Lee, S. C. (2000). Continuous Extraction of Penicillin G by Emulsion Liquid Membranes with Optimal Surfactant Compositions. *Chemical Engineering Journal*, 79(1), 61-67.
- Lee, S. C. (2011). Extraction of Succinic Acid from Simulated Media by Emulsion Liquid Membranes. *Journal of Membrane Science*, 381(1-2), 237-243.

- Lee, S. C. (2015). Removal of Acetic Acid from Simulated Hemicellulosic Hydrolysates by Emulsion Liquid Membrane with Organophosphorus Extractants. *Bioresource Technology*, 192, 340-345.
- Lee, S. C. and Hyun, K. S. (2010). Development of an Emulsion Liquid Membrane System for Separation of Acetic Acid from Succinic Acid. *Journal of Membrane Science*, 350(1-2), 333-339.
- Lee, S. C. and Kim, H. C. (2011). Batch and Continuous Separation of Acetic Acid From Succinic Acid in a Feed Solution With High Concentrations of Carboxylic Acids by Emulsion Liquid Membranes. *Journal of Membrane Science*, 367(1-2), 190-196.
- Lee, S. C., Lee, K. H., Hyun, G. H. and Lee, W. K. (1997). Continuous Extraction of Penicillin G by an Emulsion Liquid Membrane in a Countercurrent Extraction Column. *Journal of Membrane Science*, 124(1), 43-51.
- Lende, A. B. and Kulkarni, P. S. (2015). Selective Recovery of Tungsten from Printed Circuit Board Recycling Unit Wastewater by Using Emulsion Liquid Membrane Process. *Journal of Water Process Engineering*, 8, 75-81.
- Leon, G. and Guzman, M. A. (2005). Kinetic study of the effect of carrier and stripping agent concentrations on the facilitated transport of cobalt through bulk liquid membranes. *Desalination*, 184(1), 79-87.
- Li, N. N. (1968). *U.S. Patent No.* Washington DC: U. S. Patent Office.
- Li, N. N. and Calo, J. M. (1992). *Separation and Purification Technology*. New York: Marcel Dekker, Inc.
- Li, Q., Wang, D., Wu, Y., Li, W., Zhang, Y., Xing, J. and Su, Z. (2010). One Step Recovery of Succinic Acid from Fermentation Broths by Crystallization. *Separation and Purification Technology*, 72(3), 294-300.
- Lin, C. C. and Long, R. L. (1997). Removal of Nitric Acid by Emulsion Liquid Membrane: Experimental Results and Model Prediction. *Journal of Membrane Science*, 134(1), 33-45.
- Liu, Y. P., Zheng, P., Sun, Z. H., Ni, Y., Dong, J. J. and Zhu, L. L. (2008). Economical Succinic Acid Production from Cane Molasses by *Actinobacillus Succinogenes*. *Bioresource Technology*, 99(6), 1736-1742.
- Lu, G., Lu, Q. and Li, P. (1997). Break-Down of Liquid Membrane Emulsion under High Electric Field. *Journal of Membrane Science*, 128(1), 1-6.

- Luque, R., Lin, C. S. K., Du, C., Macquarrie, D. J., Koutinas, A., Wang, R., Clark, J. H. (2009). Chemical Transformations of Succinic Acid Recovered from Fermentation Broths by a Novel Direct Vacuum Distillation-Crystallisation Method. *Green Chemistry*, 11(2), 193-200.
- Mahmoud, A. S., Ghaly, A. E. and Brooks, M. S. (2007). Removal of Dye from Textile Wastewater Using Plant Oils Under Different pH and Temperature Conditions. *American Journal of Environmental Sciences*, 3(4), 205-218.
- Malik, M. A., Hashim, M. A. and Nabi, F. (2011). Extraction of Metal Ions by ELM Separation Technology. *Journal of Dispersion Science and Technology*, 33(3), 346-356.
- Manna, M. S., Bhatluri, K. K., Saha, P. and Ghoshal, A. K. (2012). Transportation of Catechin ( $\pm$ C) Using Physiologically Benign Vegetable Oil As Liquid Membrane. *Industrial and Engineering Chemistry Research*, 51(46), 15207-15216.
- Manzak, A. and Tutkun, O. (2005). Extraction of Citric Acid Through an Emulsion Liquid Membrane Containing Aliquat 336 as Carrier. *Separation Science and Technology*, 39(10), 2497-2512.
- Marcus, Y. (2004). Principles of Solubility and Solutions. In J. Rydberg, M. Cox, C. Musikas, and G. R. Choppin (Eds.), *Solvent Extraction Principles and Practice*. New York: Marcel Dekker.
- Marr, R. and Koncar, M. (1993). Recovery of Ammonia from Industrial Wastewater. *International Chemical Engineering*, 33(3), 416-425.
- Maruta, C., Mandru, I., Rata, D. and Sandu, M. (2003). Removal Of Uranyl Ions  $UO_2^{2+}$  From Dilute Solutions by Elm Technique. I. Transport Mechanism of Uranyl Ions with Ammonium Quaternary Salts as Carrier. *Analele Universitatii Bucuresti : Chimie*.
- Matsumoto, S., Kita, Y. and Yonezawa, D. (1976). An attempt at preparing water-in-oil-in-water multiple-phase emulsions. *Journal of Colloid and Interface Science*, 57(2), 353-361.
- McKinlay, J. B., Vieille, C. and Zeikus, J. G. (2007). Prospects for a Bio-Based Succinate Industry. *Applied Microbiology and Biotechnology*, 76(4), 727-740.
- Mok, Y. S. and Lee, W. K. (1994). Water Transport in Water-in-Oil-in-Water Liquid Emulsion Membrane System for the Separation of Lactic Acid. *Separation Science and Technology*, 29(6), 743-764.



- Mokhtari, B. and Pourabdollah, K. (2015). Emulsion Liquid Membrane for Selective Extraction of Bi(III). *Chinese Journal of Chemical Engineering*, 23(4), 641-645.
- Mokhtari, B. and Pourabdollah, K. (2013). Inclusion extraction of alkali metals by emulsion liquid membranes bearing nano-baskets. *Journal of Inclusion Phenomena and Macrocyclic Chemistry*, 76(3), 403-413.
- Mortaheb, H. R., Amini, M. H., Sadeghian, F., Mokhtarani, B. and Daneshyar, H. (2008). Study on a New Surfactant for Removal of Phenol from Wastewater by Emulsion Liquid Membrane. *Journal of Hazardous Materials*, 160(2-3), 582-588.
- Mulder, M. F. (1996). *Basic Principles of Membrane Technology*. The Netherlands: Kluwer Academic Publishers.
- Muthuraman, G. and Palanivelu, K. (2005). Selective Extraction and Separation of Textile Anionic Dyes from Aqueous Solution by Tetrabutyl Ammonium Bromide. *Dyes and Pigments*, 64(3), 251-257.
- Muthuraman, G. and Palanivelu, K. (2006). Transport of Textile Dye in Vegetable Oils Based Supported Liquid Membrane. *Dyes and Pigments*, 70(2), 99-104.
- Muthuraman, G. and Teng, T. T. (2009). Use of Vegetable Oil in Supported Liquid Membrane for the Transport Of Rhodamine B. *Desalination*, 249(3), 1062-1066.
- Myers, R. H., Montgomery, D. C. and Anderson, C. C. M. (2009). *Response Surface Methodology: Process and Product Optimization Using Designed Experiments* (3 ed.). New Jersey: John Wiley & Sons.
- Naim, M. M. and Monir, A. A. (2003). Desalination using Supported Liquid Membranes. *Desalination*, 153(1-3), 361-369.
- Narayanan, J. and Palanivelu, K. (2008). Recovery of Acetic Acid by Supported Liquid Membrane using Vegetable Oils as Liquid Membrane. *Recovery of acetic acid by supported liquid membrane using vegetable oils as liquid membrane*, 15, 266-270.
- Ng, Y. S., Jayakumar, N. S. and Hashim, M. A. (2010). Performance Evaluation of Organic Emulsion Liquid Membrane on Phenol Removal. *Journal of Hazardous Materials*, 184(1-3), 255-260.

- Noah, N. F. M. (2015). *Emulsion Liquid Membrane Extraction of Palladium from Simulated Electroplating Wastewater*. Master, Universiti Teknologi Malaysia, Malaysia.
- Noah, N. F. M., Othman, N. and Jusoh, N. (2016). Highly Selective Transport of Palladium from Electroplating Wastewater using Emulsion Liquid Membrane Process. *Journal of the Taiwan Institute of Chemical Engineers*, 64, 134-141.
- Omar, W. N. N. W. and Amin, N. A. S. (2011). Optimization of Heterogeneous Biodiesel Production from Waste Cooking Palm Oil via Response Surface Methodology. *Biomass and Bioenergy*, 35(3), 1329-1338.
- Ooi, Z. Y. (2015). Recovery of Kraft Lignin from Pulping Wastewater using Emulsion Liquid Membrane Process. PhD, Universiti Teknologi Malaysia, Malaysia.
- Ooi, Z. Y., Harruddin, N. and Othman, N. (2015). Recovery of Kraft Lignin from Pulping Wastewater via Emulsion Liquid Membrane Process. *Biotechnology Progress*, 1(5), 1305-1314.
- Ooi, Z. Y., Othman, N. and Mohamed Noah, N. F. (2016). Response Surface Optimization of Kraft Lignin Recovery from Pulping Wastewater through Emulsion Liquid Membrane Process. *Desalination and Water Treatment*, 57(17), 7823-7832.
- Othman, N. (2006). *Selective Emulsion Liquid Membrane Extraction of Silver from Liquid Photographic Waste Industries*. Doctor of Philosophy, Universiti Teknologi Malaysia, Malaysia.
- Othman, N., Mat, H. and Goto, M. (2005). Selective Extraction of Silver from liquid Photographic Waste. *Solvent Extraction Research and Development, Japan*, 12, 27-34.
- Othman, N., Mili, N., Idris, A. and Zailani, S. N. (2012). Removal of Dyes from Liquid Waste Solution: Study on Liquid Membrane Component Selection and Stability. *Sustainable Membrane Technology for Energy, Water, and Environment*, 221-229.
- Othman, N., Mili, N., Zailani, S. N. and Mohammad, N. A. B. (2010). Extraction of Remazol Brilliant Orange 3R from Textile Wastewater using Tetrabutyl Ammonium Bromide. *Jurnal Teknologi*, 53, 29-39.
- Othman, N., Noah, N. F. M., Poh, K. W. and Yi, O. Z. (2016). High Performance of Chromium Recovery from Aqueous Waste Solution Using Mixture of Palm-oil in Emulsion Liquid Membrane. *Procedia Engineering*, 148, 765-773.

- Othman, N., Noah, N. F. M., Shu, L. Y., Ooi, Z.-Y., Jusoh, N., Idroas, M. and Goto, M. (2016). Easy Removing of Phenol from Wastewater Using Vegetable Oil-Based Organic Solvent in Emulsion Liquid Membrane Process. *Chinese Journal of Chemical Engineering* 25(1), 45-52.
- Othman, N., Sadikin, A. N. and Malini, H. (2008). Stability Analysis of Water in Oil Emulsion in Liquid Membrane Process. *Journal of Chemical and Natural Resources Engineering*, 130-138.
- Othman, N., Yi, O. Z., Zailani, S. N., Zulkifli, E. Z. and Subramaniam, S. (2013). Extraction of Rhodamine 6G Dye from Liquid Waste Solution: Study on Emulsion Liquid Membrane Stability Performance and Recovery. *Separation Science and Technology (Philadelphia)*, 48(8), 1177-1183.
- Othman, N., Zailani, S. N. and Mili, N. (2011). Recovery of Synthetic Dye from Simulated Wastewater using Emulsion Liquid Membrane Process Containing Tri-Dodecyl Amine as a Mobile Carrier. *Journal of Hazardous Materials*, 198, 103-112.
- Park, H. J. and Chung, T. S. (2003). Removal of Phenol from Aqueous Solution by Liquid Emulsion Membrane. *Korean Journal of Chemical Engineering*, 20(4), 731-735.
- Park, Y. (2006). *Development and optimization of novel emulsion liquid membranes stabilized by nonnewtonian conversion in taylor-couette flow for extraction of selected organic and metallic contaminants*. PhD, Georgia Institute of Technology.
- Park, Y., Forney, L. J., Kim, J. H. and Skelland, A. H. P. (2004). Optimum Emulsion Liquid Membranes Stabilized by Non-Newtonian Conversion in Taylor-Couette Flow. *Chemical Engineering Science*, 59(24), 5725-5734.
- Park, Y., Skelland, A. H. P., Forney, L. J. and Kim, J. H. (2006). Removal of Phenol and Substituted Phenols by Newly Developed Emulsion Liquid Membrane Process. *Water Research*, 40(9), 1763-1772.
- Pazouki, M. and Panda, T. (1998). Recovery of Citric Acid-A Review. *Bioprocess Engineering*, 19(6), 435-439.
- Peng, W., Jiao, H., Shi, H. and Xu, C. (2012). The Application of Emulsion Liquid Membrane Process and Heat-Induced Demulsification for Removal of Pyridine from Aqueous Solutions. *Desalination*, 286, 372-378.

- Poposka, A. F., Nikolovsky, K. and Tomovska, R. (1998). Mechanism and Mathematical Modeling of Extraction of Citric Acid with Isodecanol/N-Paraffins Solutions of Trioctylamine. *Chemical Engineering Science*, 58, 3227-3237.
- Rajab, A., Sulaeman, A., Sudirham, S. and Suwarno. (2011). A Comparison of Dielectric Properties of Palm Oil with Mineral and Synthetic Types Insulating Liquid under Temperature Variation. *Journal of Engineering and Technological Sciences*, 43(3), 191-208.
- Rajasimman, M. and Karthic, P. (2010). Application of Response Surface Methodology for the Extraction of Chromium (VI) by Emulsion Liquid Membrane. *Journal of the Taiwan Institute of Chemical Engineers*, 41(1), 105-110.
- Ranucci, E., Liu, Y., Söderqvist Lindblad, M. and Albertsson, A.-C. (2000). New Biodegradable Polymers from Renewable Sources. High Molecular Weight Poly(Ester Carbonate)s from Succinic Acid and 1,3-Propanediol. *Macromolecular Rapid Communications*, 21(10), 680-684.
- Ricker, N. L. (1978). *Recovery of Carboxylic Acids and Related Organic Chemicals from Wastewater by Solvent Extraction*. PhD. Dissertation, University of California, Berkeley.
- Ritchey, G. M. and Ashbrook, A. W. (1984). *Solvent Extraction Principles and Applications to Process Metallurgy, Part I*. Amsterdam: Elsevier Science Publisher.
- Rousseau, R. W. (1987). *Handbook of Separation Process Technology*. Canada: John Wiley & Sons.
- Ruppert, M., Draxler, J. and Marr, R. (1988). Liquid-Membrane-Permeation and Its Experiences in Pilot-Plant and Industrial Scale. *Separation Science and Technology*, 23(12-13), 1659-1666.
- Sabry, R., Hafez, A., Khedr, M. and El-Hassanin, A. (2007). Removal of Lead by an Emulsion Liquid Membrane: Part I. *Desalination*, 212(1-3), 165-175.
- Sauer, M., Porro, D., Mattanovich, D. and Branduardi, P. (2008). Microbial Production of Organic Acids: Expanding the Markets. *Trends in Biotechnology*, 26(2), 100-108.

- Schmidts, T., Dobler, D., Nissing, C. and Runkel, F. (2009). Influence of Hydrophilic Surfactants on the Properties of Multiple W/O/W Emulsions. *Journal of Colloid and Interface Science*, 338(1), 184-192.
- Scholler, C., Chaudhuri, J. B. and Pyle, D. L. (1993). Emulsion Liquid Membrane Extraction of Lactic Acid from Aqueous Solutions and Fermentation Broth. *Biotechnology and Bioengineering*, 42(1), 50-58.
- Skelland, A. H. P. and Meng, X. (1999). Non-Newtonian Conversion Solves Problems of Stability, Permeability, and Swelling in Emulsion Liquid Membranes. *Journal of Membrane Science*, 158(1-2), 1-15.
- Song, H. and Lee, S. Y. (2006). Production of Succinic Acid by Bacterial Fermentation. *Enzyme and Microbial Technology*, 39(3), 352-361.
- Song, H., Huh, Y. S., Lee, S. Y., Hong, W. H. and Hong, Y. K. (2007). Recovery of Succinic Acid Produced by Fermentation of a Metabolically Engineered *Mannheimia Succiniciproducens* Strain. *Journal of Biotechnology*, 132(4), 445-452.
- Statistica (2016). Production of Major Vegetable Oils Worldwide. Retrieved from <https://www.statista.com/statistics/263933/production-of-vegetable-oils-worldwide-since-2000/> (13 September 2016).
- Strzelbicki, J. and Charewicz, W. (1980). The Liquid Surfactant Membrane Separation of Copper, Cobalt And Nickel from Multicomponent Aqueous Solutions. *Hydrometallurgy*, 5(2), 243-254.
- Strzelbicki, J., Charewicz, W. A. and Mackiewicz, A. (1984). Permeation of Chromium(VI) and Rhenium(VII) Oxyanions through Liquid Organic Membranes Facilitated by Quaternary Ammonium Chlorides. *Separation Science and Technology*, 19(4-5), 321-336.
- Sulaiman, R. N. R., Othman, N. and Amin, N. A. S. (2013). Recovery of Ionized Nanosilver from Wash Water Solution using Emulsion Liquid Membrane Process. *Jurnal Teknologi (Sciences and Engineering)*, 65(4), 33-36.
- Sulaiman, R. N. R., Othman, N. and Amin, N. A. S. (2013). Stability Study of Water in Oil Emulsion in Emulsion Liquid Membrane Process. *Journal of Science and Technology*.
- Sutton, D. M., Hiles, A. G. and Backes, A. F. (2003). *U.S. Patent No. 6620949*. London: D. P. T. Limited.

- Tadros, T. F. (2013). Emulsion Formation, Stability, and Rheology in *Emulsion Formation and Stability*: Wiley-VCH Verlag GmbH & Co. KGaA.
- Tamada, J. A. (1989). *Extraction of Carboxylic Acids by Amine Extractants*. Ph.D., University of California, Berkeley.
- Tang, B., Yu, G., Fang, J. and Shi, T. (2010). Recovery of High-Purity Silver Directly from Dilute Effluents by an Emulsion Liquid Membrane-Crystallization Process. *Journal of Hazardous Materials*, 177(1-3), 377-383.
- Teramoto, M., Sakai, T., Yanagawa, K., Ohsuga, M. and Miyake, Y. (1983). Modeling of the Permeation of Copper through Liquid Surfactant Membranes. *Separation Science and Technology*, 18(8), 735-764.
- Teramoto, M., Yamashiro, T., Inoue, A., Yamamoto, A., Matsuyama, H. and Miyake, Y. (1991). Extraction of Amino Acids by Emulsion Liquid Membranes Containing Di (2-ethylhexyl)phosphoric Acid as a Carrier Biotechnology; Coupled, Facilitated Transport; Diffusion. *Journal of Membrane Science*, 58(1), 11-32.
- Thakker, C., Martínez, I., San, K.-Y. and Bennett, G. N. (2012). Succinate Production in Escherichia Coli. *Biotechnology Journal*, 7(2), 213-224.
- Venkatesan, S. and Meera, K. M. (2009). Emulsion Liquid Membrane Pertraction of Benzimidazole using a Room Temperature Ionic Liquid (RTIL) Carrier. *Chemical Engineering Journal*, 148(2-3), 254-262.
- Venkateswaran, P. and Palanivelu, K. (2006). Recovery of Phenol from Aqueous Solution by Supported Liquid Membrane using Vegetable Oils as Liquid Membrane. *Journal of Hazardous Materials*, 131(1-3), 146-152.
- Venkateswaran, P., Gopalakrishnan, A. N. and Palanivelu, K. (2007). Di(2-ethylhexyl) Phosphoric Acid-Coconut Oil Supported Liquid Membrane for the Separation of Copper Ions from Copper Plating Wastewater. *Journal of Environmental Sciences*, 19(12), 1446-1453.
- Villora, G. (2013). Liquid Membranes, Supported and Emulsion. In E. M. Hoek and V. V. Tarabara (Eds.), *Encyclopedia of Membrane Science and Technology*. United States: John Wiley & Sons.
- Wan, C., Li, Y., Shahbazi, A. and Xiu, S. (2008). Succinic Acid Production from Cheese Whey using Actinobacillus Succinogenes 130 Z. *Applied Biochemistry and Biotechnology*, 145(1-3), 111-119.

- Wan, Y. and Zhang, X. (2002). Swelling Determination of W/O/W Emulsion Liquid Membranes. *Journal of Membrane Science*, 196(2), 185-201.
- Werpy, T., Holladay, J. and White, J. (2004). *Top Value Added Chemicals From Biomass: I. Results of Screening for Potential Candidates from Sugars and Synthesis Gas*.
- Witek, K. A., Chojnacka, K., Podstawczyk, D., Dawiec, A. and Pokomeda, K. (2014). Application of Response Surface Methodology and Artificial Neural Network Methods in Modelling And Optimization Of Biosorption Process. *Bioresource Technology*, 160, 150-160.
- Wu, H., Jiang, M., Wei, P., Lei, D., Yao, Z. and Zuo, P. (2011). *Chinese Patent No. CN200910025531.5*.
- Yang, S. T., White, S. A. and Hsu, S. T. (1991). Extraction of Carboxylic Acids with Tertiary and Quaternary Amines: Effect of pH. *Industrial and Engineering Chemistry Research*, 30(6), 1335-1342.
- Yao, Z., Wu, H., Liu, H., Li, S. and Jiang, M. (2008). *Chinese Patent No. CN 200610086003*.
- Yordanov, B. and Boyadzhiev, L. (2004). Pertraction of Citric Acid by Means of Emulsion Liquid Membranes. *Journal of Membrane Science*, 238(1-2), 191-197.
- Zeikus, J. G., Jain, M. K. and Elankovan, P. (1999). Biotechnology of Succinic Acid Production and Markets for Derived Industrial Products. *Applied Microbiology and Biotechnology*, 51(5), 545-552.
- Zhang, L., Chen, Q., Kang, C., Ma, X. and Yang, Z. (2016). Rare Earth Extraction from Wet Process Phosphoric Acid by Emulsion Liquid Membrane. *Journal of Rare Earths*, 34(7), 717-723.
- Zhao, L., Fei, D., Dang, Y., Zhou, X. and Xiao, J. (2010). Studies on the Extraction of Chromium(III) by Emulsion Liquid Membrane. *Journal of Hazardous Materials*, 178(1-3), 130-135.
- Zhou, J., Ma, X. M., Qiu, B. H., Chen, J. X., Bian, L. and Pan, L. M. (2013). Parameters Optimization of Supercritical Fluid-CO<sub>2</sub> Extracts of Frankincense using Response Surface Methodology and Its Pharmacodynamics Effects. *Journal of Separation Science*, 36(2), 383-390.