

BIOGRANULATION DEVELOPMENT DURING TREATMENT OF REAL  
TEXTILE WASTEWATER

RANJENI D/O KRISHNEN

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Doctor of Philosophy (Civil Engineering)

Faculty of Civil Engineering  
Universiti Teknologi Malaysia

JANUARY 2018

*In Loving Memory of My Godmother, Reginamary (1955-2014)*

## ACKNOWLEDGEMENT

First and foremost, I praise God, the Almighty for providing me this opportunity, granting me the capability to proceed and for His showers of blessings throughout my research work to complete the research successfully.

I am deeply indebted to my supervisor Prof. Dr. Azmi Aris for his fundamental role in my doctoral work. His dynamism, vision, sincerity and motivation have deeply inspired me. He has taught me the methodology to carry out the research and to present the research works as clearly as possible. He gave me the freedom to do whatever I wanted, at the same time continuing to contribute valuable feedback, advice, and encouragement. It was a great privilege and honor to work under his guidance. I am extremely grateful for what he has offered me. I quite simply cannot imagine a better mentor. I would like to express my deep and sincere gratitude to my research co-supervisor, Assoc. Prof. Dr. Khalida Muda for the trust, thoughtful guidance, warm encouragement and critical comments throughout this research. She had provided me with every bit of guidance, assistance and expertise that I needed. A special thanks to Prof Dr. Zaharah Ibrahim for the insightful discussion, offering valuable advice and for your support during the whole period of the study.

I'm extremely grateful to K&H Computing Solutions Sdn. Bhd. for their technical assistance in dealing with pilot scale reactor. I would like to thank staffs of Ramatex Textile Industrial Sdn. Bhd., American & Effird (M) Sdn. Bhd., Lee Pineapple Company Sdn. Bhd. and Indah Water Konsortium for their cooperation throughout research. I wish to offer my most heartfelt thanks to all the Environmental Engineering Laboratory staffs. I'm sincerely indebted to En.Jimmy and to staffs of Office of Asset and Development UTM, for helping me collect wastewater samples from the factory every week without any complaints. I'm also feeling grateful to my colleagues, Anwar, Hanami, Izan, Malik and Izuan for assisting me during the earlier stages of lab works. To my friend Haniz Omar, thank you so much for helping me with technical issues whenever needed despite of your busy schedule.

I am deeply thankful to my parents for their love and sacrifices for educating and preparing me for my future. I warmly thank my sisters, brother-in law and other family members for their support. Without them, this thesis would never have been written. I dedicate this thesis to the memory of my godmother Regina Mary, whose role in my life was, and remains, immense. This last word of acknowledgment I have saved for my dear friends, who has been with me all these years and has made them the best years of my life. Rehma akka, Alex, Valli and Veni akka, thank you so much for the encouragement and support especially at times when things were going tough.

## ABSTRACT

Over the past decades, effluent discharge from textile industries to neighbouring water bodies can cause severe water pollution if discharged untreated. There are quite a number of treatment systems have been invented to treat textile wastewater, but each treatment system had its own limitations. The most common limitations are low efficiency, inapplicability to treat a wide variety of dyes, production of secondary waste and high cost. Currently, biological treatment using biogranules had showed promising results in treating textile wastewater. However, most studies are being done using synthetic wastewater at lab scale reactor. This study looks at the development and application of biogranules in treating the actual textile wastewater using pilot-scale reactor. A pilot-scale Sequential Batch Reactor (SBR) biogranular system with working volume of 70 L was developed and operated according to SBR's sequence for 24-hr cycle, which includes sequential anaerobic and aerobic reaction phases. Wastewater from two textile mills were used as feed, while sewage and pineapple wastewater were used as co-substrate. After operating the system for 60 days, 30% of the sludge transformed into biogranules and increased to 67% at the end of the study. The biogranules developed in the reactor have sizes ranging from 0.2 mm to 9.5 mm with a mean settling velocity of  $28 \pm 7$  m/hr and Sludge Volume Index (SVI) of 73.9 mL/g. At the end of the development period, the system yields 92% removal of Chemical Oxygen Demand (COD), however color removal fluctuated throughout the development period in the range of 50 to 70%. The efficiency of biogranules in treating textile wastewater was evaluated using lab scale bioreactor with total working volume of 3L. The system was able to achieve 55% of average color removal and 88% of average COD removal at 7%v/v pineapple wastewater concentration during the treatment period. The experiment on treatment of raw textile wastewater without any added nutrient proved the importance of co-substrate in dye degradation. Conversely, the addition of external dye degrader microbes in the reactor had slightly improved color removal. The system obtained 59% of mean color removal and 81% of mean COD removal at 5%v/v pineapple wastewater concentration upon addition of dye degrader microbes into the bioreactor. Microorganisms under genus *Pseudomonas*, *Klebsiella* and *Enterococcus* were identified within the mature biogranules which are considered in the literature as dye degrader microbes. Although the biogranules development is much faster in lab-scale reactor under controlled environment, the findings indicate the feasibility of developing biogranules in a bigger scale reactor using actual textile wastewater and other high-strength biodegradable wastewater as co-substrate.

## ABSTRAK

Sejak beberapa dekad yang lalu, pelepasan air sisa daripada industri tekstil ke badan air berdekatan sungai telah menyumbang kepada pencemaran air yang kritikal jika dilepaskan tanpa dirawat. Terdapat beberapa sistem rawatan yang telah dicipta untuk merawat air sisa tekstil, tetapi setiap sistem rawatan mempunyai had tersendiri. Had yang biasa adalah kecekapan rendah, ketidakupayaan untuk merawat pelbagai jenis pewarna, penghasilan sisa sekunder dan kos yang tinggi. Rawatan menggunakan biogranul telah menunjukkan keputusan yang memuaskan dalam merawat air sisa tekstil. Walau bagaimanapun, kebanyakan kajian telah dilakukan dengan menggunakan air sisa sintetik dalam reaktor berskala kecil. Dalam kajian ini, keupayaan menghasilkan dan menggunakan enapcemar granul bagi mengolah airsisa tekstil dalam satu reaktor berskala loji-pandu dikaji. Satu sistem reaktor berkelompok berjujukan (SBR) biogranular berskala loji-pandu berisipadu 70 L telah dikendalikan mengikut urutan SBR untuk kitaran 24 jam, dengan fasa anaerobik dan aerobik beroperasi secara berselang-seli. Air sisa daripada dua kilang tekstil telah digunakan, manakala kumbahan dan air sisa nenas digunakan sebagai ko-substrat. Setelah beroperasi selama 60 hari, 30% daripada enapcemar telah berubah menjadi biogranul dan telah meningkat kepada 67% di akhir kajian. Biogranul yang terbentuk di dalam reaktor mempunyai saiz diantara 0.2 mm hingga 9.5 mm dengan halaju enapan purata  $28 \pm 7$  m/hr dan mempunyai index isipadu enapcemar (SVI) serendah 73.9 mL/g. Pada akhir kajian ini, 92% penyingkiran COD telah dicapai oleh sistem, tetapi penyingkiran warna berubah-ubah di sepanjang tempoh pembentukan granul dalam lingkungan 50 hingga 70%. Kecekapan biogranul dalam merawat air sisa tekstil dinilai menggunakan reaktor berskala kecil berisipadu 3L. Sistem ini telah berjaya untuk mencapai 55% penyingkiran warna dan 88% penyingkiran COD pada kepekatan 7% v/v airsisa nenas sepanjang tempoh rawatan. Eksperimen menggunakan rawatan airsisa tekstil mentah tanpa sebarang penambahan nutrien membuktikan kepentingan ko-substrat dalam degradasi pewarna. Sebaliknya, penambahan mikrob penyahwarna dalam reaktor telah mempertingkatkan penyingkiran warna dalam kadar yang rendah. Sistem ini telah berjaya mencapai 59% penyingkiran warna dan 81% penyingkiran COD pada kepekatan 5% v/v airsisa nenas dengan penambahan mikrob penyahwarna. Mikroorganisma daripada genus *Pseudomonas*, *Klebsiella* dan *Enterococcus* telah dikenalpasti dalam biogranul matang dan mengikut rujukan merupakan mikrob penyahwarna. Walaupun pembentukan biogranul adalah lebih cepat dalam reaktor berskala kecil dan dalam persekitaran terkawal, hasil kajian menunjukkan keupayaan pembentukan biogranul dalam reaktor skala yang lebih besar menggunakan airsisa tekstil sebenar dan air sisa mudah biorosot kekuatan tinggi lain sebagai ko-substrat.

## TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	<b>DECLARATION</b>	ii
	<b>DEDICATION</b>	iii
	<b>ACKNOWLEDGEMENT</b>	iv
	<b>ABSTRACT</b>	v
	<b>ABSTRAK</b>	vi
	<b>TABLE OF CONTENTS</b>	vii
	<b>LIST OF TABLES</b>	xii
	<b>LIST OF FIGURES</b>	xiv
	<b>LIST OF ABBREVIATIONS</b>	xx
	<b>LIST OF APPENDICES</b>	xxii
<b>1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Preamble	1
	1.2 Problem statement	3
	1.3 Objectives of the study	4
	1.4 Scope of study	5
	1.5 Significance of study	6
	1.6 Organization of thesis	7
<b>2</b>	<b>LITERATURE REVIEW</b>	<b>9</b>
	2.1 Introduction	9
	2.2 Textile wastewater	9
	2.3 Dye	13
	2.4 Azo dyes	15

2.5	Mechanism of azo dye degradation	16
2.5.1	Mechanism of anaerobic dye degradation	17
2.5.2	Mechanism of aerobic dye degradation	19
2.6	Treatment of textile wastewater	20
2.7	Biogranules	29
2.8	Factors affecting granulation	31
2.8.1	Seed sludge	31
2.8.2	Substrate composition	33
2.8.3	Organic loading rate	36
2.8.4	Hydrodynamic shear force	37
2.8.5	Settling time	38
2.8.6	Hydraulic retention time	39
2.8.7	Dissolved oxygen, pH and temperature	39
2.8.8	Exopolysaccharides	41
2.8.9	Volumetric exchange rate	42
2.8.10	Reactor configuration	42
2.9	Factors affecting microbial decolorization	43
2.9.1	Dye structure and concentration	43
2.9.2	Redox mediator, carbon and nitrogen sources	45
2.9.3	Temperature, pH, oxygen and agitation	46
2.10	Reactor system	46
2.10.1	Upflow anaerobic sludge blanket	47
2.10.2	Sequencing batch reactor	50
2.10.3	Integrated treatment systems	52
2.11	Pilot scale application	55
2.12	Conclusions	67
<b>3</b>	<b>METHODOLOGY</b>	<b>68</b>
3.1	Introduction	68
3.2	Materials and equipment	68

3.2.1	Pilot-scale sequential batch reactor	69
3.2.2	Lab-scale sequencing batch reactor system	73
3.3	Analytical methods	74
3.3.1	Characterizations of granules	74
3.3.1.1	Biomass concentration	75
3.3.1.2	Settling velocity	75
3.3.1.3	Sludge volume index	75
3.3.1.4	Granular strength	76
3.3.1.5	Stereo microscopic examination	77
3.3.1.6	Field-emission scanning electron microscope coupled with energy dispersive X-ray analysis	77
3.3.1.7	Next generation sequencing analysis	77
3.3.2	Removal performance analysis	78
3.3.2.1	Determination of dye decolorization	78
3.3.2.2	Determination of dye degradation	79
3.3.3	Determination of sugar concentration in pineapple wastewater	79
3.4	Experimental procedures	80
3.4.1	Cultivation and development of biogranules	80
3.4.2	Effect of co-substrate concentration	83
3.4.3	Effect of dye degrader microbes	84
3.4.4	Characterization and comparison of the granules developed in the pilot-scale against those developed in lab-scale reactor	85



3.5	Data analysis	85
<b>4</b>	<b>RESULTS AND DISCUSSION</b>	<b>86</b>
4.1	Introduction	86
4.2	Characteristics of the wastewater	86
4.3	Biogranules development	91
4.3.1	Biomass concentration	91
4.3.2	Settling velocity and sludge volume index	93
4.3.3	Size of biogranules	94
4.3.4	Granular strength	96
4.3.5	Comparison between biogranule development in lab and pilot-scale reactor	96
4.3.6	Removal performances during development period	98
4.3.7	Removal performance during post-development stage	104
4.4	Effect of pineapple wastewater concentration on removal performance	107
4.5	Effect of dye degrader microbes on removal performance	124
4.6	Biological characteristic of granules	129
4.6.1	Morphological and structural observation of biogranules	129
4.6.2	Mineral and metal content in biogranules	137
4.6.3	Microbial composition of biogranules	143
4.7	Conclusions	150
<b>5</b>	<b>CONCLUSIONS AND RECOMMENDATIONS</b>	<b>150</b>
5.1	Conclusions	151

5.2	Recommendations	153
	<b>REFERENCES</b>	<b>155</b>
	Appendices A-B	198-243

**LIST OF TABLES**

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	An overview of effluents generated during textile production process and characteristics	11
2.2	Natural Dyes vs Synthetic Dyes	14
2.3	The advantages and disadvantages of various methods used in the treatment of textile wastewater	23
2.4	Studies carried out in treating dye wastewater using different co-substrate	34
2.5	UASB applications in treatment of textile wastewater	49
2.6	Strengths and drawbacks of UASB	50
2.7	Advantages and disadvantages of SBR system	52
2.8	SBR system treating textile wastewater	53
2.9	Combined chemical process and biological process applying granulation technology for treatment of textile wastewater	56
2.10	Treatment of various types of wastewater via granulation at pilot scale	58
2.11	Treatment of raw textile wastewater using granulation technology	64
3.1	List of reagents used in the experiment	69
3.2	List of equipment used in the experiment	71
3.3	List of analytical method for removal performance analysis	79

3.4	Modifications in procedures between Muda (2010) and the study	81
3.5	The initial complete cycle of the hybrid biogranular SBR system	82
3.6	One complete cycle of the bioreactor	83
3.7	One complete cycle of the lab-scale bioreactor	84
4.1	Characteristics of wastewater and co-substrates	87
4.2	Settling velocity of granules according to size (after 60 days)	94
4.3	Characteristics of mature granule	98
4.4	Treatment of raw textile wastewater using SBR-biogranulation technology	102
4.5	Percentage (%v/v) of granule before and after treatment with real textile wastewater	109
4.6	Typical infrared absorption frequencies	121
4.7	Percentage of granule presents in reactor at the end of study	126
4.8	Studies on microbial treating actual textile wastewater	130
4.9	Average concentration (wt%) of mineral and metal contents	143
4.10	Percentage of total reads classified at taxonomic level for biogranules during development period	144
4.11	Percentage of total reads classified to taxonomic level for biogranules during treatment period	148
4.12	Selected microorganisms present in mature biogranules	149

**LIST OF FIGURES**

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
2.1	Mechanism involved in azo dye synthesis (Al-Rubaie and Mhessn, 2012)	15
2.2	Degradation pathway of azo dyes (Pielesz, 1999)	17
2.3	Biodegradation of azo dyes in the aerobic and anaerobic zone (Trevor. 2001)	18
2.4	Reduction of azo dyes in anaerobic degradation (Carliell <i>et al.</i> , 1996)	18
2.5	Schematic diagram of different mechanism of anaerobic azo dye reduction, RM= redox mediator, ED= electron donor, b=bacteria (Pandey <i>et al.</i> , 2007)	19
2.6	Mechanism of azo dye degradation under anaerobic and aerobic condition (Van Der Zee, 2002)	21
2.7	Degradation rate of methyl orange [p-MO] is higher than methyl red [p-MR] due to the presence of strong electron withdrawing group (Hsueh and Chen 2008)	44
2.8	Degradation of Methly Orange with sulfo group at para- position ([p-MO]) is faster compared to sulfo group at ortho-position ([o-MO]) due to steric hindrance near azo linkage (Hsueh and Chen 2008)	44
2.9	Main components of a UASB reactor (Lin and Yang, 1991)	48

2.10	Typical Cycle of SBR (Morgenroth and Wilderer, 1998)	51
3.1	Framework of the experimental study	70
3.2	Schematic diagram of the system	72
3.3	Hybrid Biogranular Sludge Reactor	72
3.4	Schematic diagram of lab-scale sequencing batch reactor system	73
3.5	Lab-scale sequencing batch reactor system	74
4.1	Sugar profile of standard sugar solutions	88
4.2	Sugar profile of pineapple wastewater sample	89
4.3	Sugar profile of spiked pineapple wastewater sample	90
4.4	Profile of biomass concentration in reactor and TSS in the effluent	92
4.5	Profile of settling velocity and sludge volume index during the development period	93
4.6	(a) Sludge particles during the initial stage of the experiment; (b) Bioflocs at the start of experiment; (c) Co-existence of flocs with biogranules; and (d) Developed granules at the 60 days of the experiment. Pictures were taken using a stereo microscope with magnification of 6.3X (scale bar = 1mm)	95
4.7	The change in integrity coefficient (representing the granular strength) during the granule development period	97
4.8	Profile of COD removal for AESB's wastewater during development period	99
4.9	Profile of COD removal for RTISB's wastewater during development period	99
4.10	Profile of color removal for AESB's wastewater during development period	100

4.11	Profile of color removal for RTISB's wastewater during development period	100
4.12	Profile of COD removal during post-development period	104
4.13	Profile of color removal during post-development period	105
4.14	Profile of total nitrogen removal during post-development period	106
4.15	Profile of total phosphorus removal during post-development period	106
4.16	Profile of biomass concentration in reactor, TSS in the effluent and sludge volume index (PC: Pineapple wastewater concentration %v/v)	108
4.17	Profile of COD removal under different pineapple wastewater concentration. (PC: Pineapple wastewater concentration %v/v)	110
4.18	Profile of color removal under different pineapple wastewater concentration. (PC: pineapple wastewater concentration %v/v)	111
4.19	Effect of dye concentration and co-substrate concentration on color removal	113
4.20	(a) Images of real textile wastewater and treated wastewater when system operated in mixing ratio of textile wastewater with pineapple wastewater (93%:7%); (b) Images of real textile wastewater and treated wastewater when system operated with 100% textile wastewater	115
4.21	Images of wastewater sample from each phase when system operated with 100% real textile wastewater. (a) Beginning of study (96th day); (b) End of study (108th day)	116

4.22	UV-Vis spectrum of samples from each phase. (a) Beginning of study (96th day) (b) End of study (108th day)	117
4.23	Profile of color value of each phase in one cycle	118
4.24	FT-IR spectrum of sample from each phase at the beginning of study at 96th day. (a) Influent (b) Anaerobic Phase 1, (c) Aerobic Phase 1, (d) Anaerobic Phase 2, (e) Aerobic Phase 2-Effluent	119
4.25	FT-IR spectrum of sample from each phase at the end of study at 108th day. (a) Influent (b) Anaerobic Phase 1, (c) Aerobic Phase 1, (d) Anaerobic Phase 2, (e) Aerobic Phase 2-Effluent	120
4.26	Relationship between OLR with removal performance (Color, COD). (PC: Pineapple wastewater concentration %v/v)	122
4.27	Profile of total nitrogen removal with and without pineapple wastewater as co-substrate. (PC: Pineapple wastewater concentration %v/v)	123
4.28	Profile of total phosphorus removal with and without pineapple wastewater as co-substrate. (PC: Pineapple wastewater concentration %v/v)	124
4.29	Profile of biomass concentration in reactor, TSS in the effluent and sludge volume index. (PC: Pineapple wastewater concentration %v/v)	125
4.30	Profile of color removal at different pineapple wastewater concentration (with dye degrader microbes)	127
4.31	Profile of color removal with and without dye degrader microbes at different initial dye concentration	127
4.32	Profile of COD removal under different pineapple wastewater concentration (dye degrader microbes). (PC: Pineapple wastewater concentration %v/v)	128



4.33	Images of initial sludge and developed granules	132
4.34	a) Granules in size range of 0.30mm; (b) Granules in size range of 0.40mm; (c) Granules in size range of 0.85mm; (d) Granules size range of 1.18mm; (e) Bigger size granules in range of >6.30mm. Pictures were taken using a stereo microscope with magnification of 6.3X (scale bar = 1mm)	133
4.35	a) Sludge particles during the initial stage of the experiment; (b) Bioflocs at the start of experiment; (c) Co-existence of flocs with biogranules; (d) and (e) Formation of granules; (f) Developed granules in size 0.200mm; g) Developed granules at the 60 days of the experiment with different size ranging from 0.2mm to 6.45mm. Pictures were taken using a stereo microscope with magnification of 6.3X (scale bar = 1mm)	134
4.36	a) A week after addition of pineapple wastewater; (b) Disintegration of developed granule; (c) Formation of new greyish granule; (d) Co-existence of black, brown and greyish colored granules in reactor with flocs. Pictures were taken using a stereo microscope with magnification of 6.3X (scale bar = 1mm)	135
4.37	a) Varied size of brown granules and greyish granules present in reactor at the end of research(0.2mm-2.36mm); (b) Big granules present in reactor at the end of research(2.36mm-9.50mm). Pictures were taken using a stereo microscope with magnification of 6.3X (scale bar = 1mm)	136
4.38	(a) Presence of filamentous and rodlike bacteria in sludge mixture at magnification of 10.0k, 15.0k and 25.0k individually; (b) Coccoid bacteria tightly	

	linked to one another in sewage-fed granules at magnification of 10.0k, 15.0k and 25.0k respectively; (c) Spherical bacteria with filamentous structure of pineapple wastewater-fed granule at magnification of 10.0k, 15.0k and 25.0k correspondingly	138
4.39	a(i) and a(ii) Morphology of granule during treatment period at magnification of 15.0k and 20.0k. b (i) and b(ii) Filamentous structure of granule at the end of study with different morphologies intertwined randomly throughout the cross-section of granule respectively at magnification of 1.0k and 20.0k	140
4.40	Morphology of glucose-fed(a) and acetate-fed (b) aerobic granules (Tay et al., 2001c)	140
4.41	EDX spectrum. (a) Sludge; (b) Mature granule; (c) Granule from co-substrate study and (d)Granule from dye-degrader study	142
4.42	Top 8 abundances of various microorganisms. (a) Sewage sludge; (b) Textile sludge; (c) Initial granule; (d) Intermediate granule and (e) Final granule of development period	146
4.43	Top 8 abundances of various microorganisms. (a) Granule sample from development period; (b) Granule sample after study on effect of co-substrate and (c) Granule sample after study on addition of dye degrader	147

## LIST OF ABBREVIATIONS

16S rRNA	-	16 subunit ribosomal ribonucleic acid
ADMI	-	American Dye Manufacturing Index
AESB	-	American & Effird (M) Sdn. Bhd.
COD	-	Chemical oxygen demand (C-mmoL or mg/L or g/L)
DNA	-	Deoxyribonucleic acid
DO	-	Dissolved oxygen (mg/L)
EPS	-	Extracellular polymeric substances
F/M	-	Food-microorganisms ratio
FESEM-EDX	-	Field-emission scanning electron microscope coupled with Energy Dispersive X-ray Analysis
FT-IR	-	Fourier Transformed Infrared Spectroscopy
HRT	-	Hydraulic retention time (h or day)
IC	-	Integrity coefficient (%)
MIDA	-	Malaysian Industrial Department Authority
MLSS	-	Mixed liquor suspended solid (mg/L or g/L)
MLVSS	-	Mixed liquor volatile suspended solid (mg/L or g/L)
N/COD	-	Nitrogen/Chemical oxygen demand
NGS	-	Next Generation Sequencing
OLR	-	Organic loading rate (mg/L·day or kg/m <sup>3</sup> ·day)
ORP	-	Oxidation reduction potential
OUR	-	Oxygen uptake rate (mg/L.h)
P/COD	-	Phosphorus/Chemical oxygen demand
PC	-	Pineapple concentration(%v/v)
RG	-	Residual granules (mg)
RTISB	-	Ramatex Textile Industrial Sdn. Bhd.
SAV	-	Superficial air velocity (cm/s or m/hr)
SBR	-	Sequencing batch reactor

SG	-	Settled granules (mg)
SRT	-	Sludge retention time (day)
SV	-	Settling velocity (cm/s or m/hr)
SVI	-	Sludge volume index (mL/g)
TN	-	Total nitrogen (mg/L)
TP	-	Total phosphorus (mg/L)
TSS	-	Total suspended solid (mg/L or g/L)
UASB	-	Up-flow anaerobic sludge blanket
UV-Vis	-	Ultraviolet visible spectroscopy
VER	-	Volumetric exchange rate

**LIST OF APPENDICES**

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
A	Data and examples of calculation	198
B	Next Generation Sequencing Data Analysis	223

## CHAPTER 1

### INTRODUCTION

#### 1.1 Preamble

Textile industry is a rapid growing industry and an important contributor to the economic growth of numerous Asian countries namely Bangladesh, Cambodia, India, China and Malaysia. Because of the cheap market price, Asian countries are ahead in textile industry as compared to African, European and South American countries (Tang, 2014). Textile industry in Malaysia begun to emerge in the early 1970s as export oriented industrialisation initiative. Over the years, growth of the textiles market has eventually contributed towards the economy of the country. Presently, there are more than 6800 workers working in this field and the industry yields RM13.2billion, placing it as the ten largest export earner in year 2015 (MIDA, 2017).

Nevertheless, the rapid growth of the industry in Malaysia has caused serious environmental problems. The textile industry uses large amount of water in the production and releases wastewater with high load of pollutants. There is a large number of published reports (McMullan *et al.*, 2001; Pearce *et al.*, 2003; Hai *et al.*, 2007; Lotito *et al.*, 2011; Pang and Abdullah, 2013; Chung, 2016) that describe the environmental impact of textile wastewater. Generally, untreated textile wastewater is highly coloured, contains high suspended solid and non-biodegradable organics and released at elevated temperature with variable pH ranging from 5 to 10 (Pushkar and Mungray, 2016). Moreover, poor fixation of dyes on textile fibers results in direct discharge of concentrated dyes into wastewater (Carmen and Daniela, 2012). These highly coloured and non-biodegradable nature of the effluents pose potential threat to human health and environment.

In Malaysia, the discharge of the industrial effluents is regulated through Environmental Quality (Industrial Effluents) Regulations 2009 (Department of Environment of Malaysia, 2015) and the factory management is responsible in ensuring the quality of treated wastewater comply with the legislative requirement. There have been a number of methods used in treating textile industrial effluent. Presently, the main methods in textile wastewater treatment involve physical and chemical processes. However, physico-chemical treatment systems are not favoured for treating textile effluent because of high selectivity towards certain dyes, considerable high capital and operational costs and generation of sludge (Neoh *et al.*, 2016; Holkar *et al.*, 2016). Conversely, most of the dyes could not be treated by conventional biological wastewater treatment processes and will remain in the environment because of their high stability to light, temperature, water, detergents, chemicals, soap and other parameters such as bleach and perspiration (Rajaguru *et al.*, 2000; Ali, 2010).

In the past decades, studies have shown that textile wastewater can be treated by the sequential combination of anaerobic and aerobic processes (Farabegoli *et al.*, 2010; Khouni *et al.*, 2012; Franca *et al.*, 2015; Mata *et al.*, 2015). The anaerobic process is able to decolorize the wastewater, while the following aerobic process further degrades the organics and also removes the amines that are produced during the anaerobic process (Haroun and Idris, 2009). These processes have been carried out using either separate anaerobic and aerobic tanks or in a single sequential batch reactor (SBR) with biomass either in the form of suspended flocs, biofilms or biogranules.

Biogranules has a compact structure formed by agglomeration of microorganisms known as granulation under specific environmental pressures. Biogranules have emerged as powerful medium in treating wide range of organic compound due to the co-existence of comprehensive microorganisms with diverse characteristics. Apart from this, excellent settling ability along with higher biomass retained in the reactor leads to competency of granulation technology.

A great deal of previous research into granulation has focused on the factors involved in granulation mechanism such as organic loading rate, substrate composition, seed sludge, settling time and hydrodynamic shear force (Tay *et al.*, 2005b; Chen *et al.*, 2007; Adav *et al.*, 2008b; Gao *et al.*, 2011; Bindhu and Madhu, 2013; Dahalan *et al.*, 2015). These theories of granulation mechanism provide a useful account of how to further improve the efficiency of biogranular treatment system in treating complex wastewater.

## 1.2 Problem statement

Remarkably, most studies in granules have only been carried out in a lab scale reactor using synthetic wastewater. It is only in recent years, there has been an increasing interest in developing biogranules at pilot scale SBR reactor (Liu *et al.*, 2011; Verawaty *et al.*, 2012; Morales *et al.*, 2013; Pronk *et al.*, 2015; Santana *et al.*, 2016). However, far too little attention has been paid in cultivating biogranules with real industrial wastewater in pilot scale reactor. Much of the research up to now has been focus on domestic wastewater and synthetic wastewater observing significant differences between pilot- and lab-scale results (Pronk *et al.*, 2015; Gouveia *et al.*, 2015; Santana *et al.*, 2016). Environmental factors such as wastewater characteristics, influent substrate concentration and temperature could be precisely controlled at lab-scale as compared to pilot-scale. The main challenge faced by many experiments is the long start-up period in pilot scale reactor (Pronk *et al.*, 2015; Santana *et al.*, 2016). This indicates a need to understand the granulation process in pilot scale reactor using real wastewater in relation to the operating conditions, substrate composition and evolution of the microbial community.

Moreover, the development and characteristic of granules are known to be affected by substrate present in reactor. Various co-substrates contribute to diverse microbial community in granules which eventually influence the performance of granules (Feng *et al.*, 2012; Sirianuntapiboon and Chairattanawan, 2012). Most researchers investigating co-substrate have utilised pure substances such as glucose, ethanol and acetate but only a couple of researchers had introduced biodegradable



industry waste as co-substrate in treating textile wastewater namely sago wastewater, starch wastewater and noodle industry wastewater (Gnanapragasam *et al.*, 2011; Senthilkumar *et al.*, 2011; Sirianuntapiboon and Chairattanawan, 2012). Hence, it is needed to evaluate the feasibility of other readily degradable wastewater as co-substrate in the treatment of real textile wastewater.

Extensive research has been carried out regarding dye degradation by bacteria, yeast and fungi to develop a practical biologic method for dye waste (Kurade *et al.*, 2015; Adnan *et al.*, 2016; Neifar *et al.*, 2016; Sayahi *et al.*, 2016; Younes *et al.*, 2016). There are few studies that inoculate sludge together with consortium of dye degrader microbes during start-up period to enhance the granular system (Muda *et al.*, 2010; Ibrahim *et al.*, 2010; Kee *et al.*, 2015; Franciscon *et al.*, 2015). However, there have been no controlled studies which compare differences in treatment efficiency with and without external dye degrader in treating actual textile wastewater using biogranules.

The present study is regarded as the first study dedicated to the development of biogranules using actual textile wastewater in pilot scale reactor. The system utilizes the concept of sequential anaerobic and aerobic biological reactions for complete degradation of the wastewater. The factors influencing the competency of granular system in treating raw textile wastewater are addressed in this study. Additionally, sewage and pineapple wastewater were tested as potential co-substrate in development of granular system for textile wastewater and the influence of external dye degrader on treatment efficiency were explored.

### **1.3 Objectives of the study**

This study aimed to ascertain how the complex characteristic of textile wastewater affect the granulation process and removal efficiency of organic matter.

The specific objectives of the experimental study are as follows:

- i. To develop biogranules in treating actual textile wastewater in a pilot scale bioreactor with the use of sewage and pineapple wastewater as co-substrate.
- ii. To assess the effect of pineapple wastewater (co-substrate) concentration (%v/v) on the performance of the biogranules.
- iii. To evaluate the effect of dye degrader microbes on the performance of system in terms of color removal and COD removal.
- iv. To characterize and compare the biogranules developed in the pilot-scale against those developed in lab scale reactor in terms of physical, chemical and biological characteristics.

#### **1.4 Scope of study**

This study explores the development of biogranules in pilot scale bioreactor to treat real textile wastewater. The design and operation of the pilot scale bioreactor are based on Muda (2010). The reactor had a working volume of 70 L and was operated according to SBR's sequence for 24-hr cycle, which includes sequential anaerobic and aerobic reaction phases. Wastewater from two textile mills were used as feed, while sewage and pineapple wastewater were used as co-substrate. Along the granulation process, samples of granules were collected and examined in terms of the morphology and physical characteristics namely settling velocity, sludge volume index (SVI), mixed liquor suspended solids (MLSS), mixed liquor volatile suspended solids (MLVSS) and integrity coefficient. Reactor performances were determined based on the COD, color, total nitrogen and total phosphorus removal efficiencies during granulation and maturation phases of the granules. The investigation involved the effect of pineapple wastewater concentration (%v/v) on the organic and nutrient removal in raw textile wastewater by biogranules were performed using lab scale bioreactor as the pilot scale bioreactor was shutdown due to a technical problem. The lab scale bioreactor with 3L working volume were operated in similar operation

parameters to pilot scale bioreactor such as reaction time (anaerobic and aerobic time), volumetric exchange ratio (VER) and hydraulic retention time (HRT).

External dye degrader obtained from Microclear Sdn Bhd was employed for the experiment to assess the influence of dye degrader microbes on the color and COD removal. The degradation of dye was justified by characterizing the untreated and treated wastewater using ultraviolet visible spectroscopy (UV-Vis) together with fourier transformed infrared spectroscopy (FT-IR). Furthermore, field-emission scanning electron microscope coupled with energy dispersive X-ray analysis (FESEM-EDX) was used to inspect the microstructure and elemental composition of biogranule. The study also included analysis of bacterial population within biogranule via next generation sequencing (NGS) analysis. There was no addition of any chemical to control the pH as well as no nutrients were supplied for the growth of microbes throughout the study. In this study, the reactors were operated without controlling the parameters such as pH, temperature, DO, MLSS and MLVSS

## **1.5 Significance of study**

Extensive research has shown that biological treatment has a good prospect in treating textile wastewater attributed to its economical and green technology (Sudha *et al.*, 2014; Parmar and Shukla, 2015; Mahmoud *et al.*, 2017). There is a growing body of literature that recognises the application of biogranular system in treating textile wastewater (Gnanapragasam *et al.*, 2010; Senthilkumar *et al.*, 2011; Baeta *et al.*, 2012; Talouizte *et al.*, 2013; Franca *et al.*, 2015; Mata *et al.*, 2015). However, majority of studies were conducted using synthetic wastewater, mixture of certain dye wastewater and raw textile wastewater at lab scale. Notably, biogranulation study treating actual textile wastewater in an SBR system at a bigger scale is apparently missing. The significance of this study is therefore listed as follows;

- i. As the characteristics of the textile effluent is well known for its low biodegradability and high variation, many practical aspects of the treatment in

developing biogranules need to be explored. Hence, the present research explores, the development of biogranules in the pilot scale reactor using actual textile wastewater as prime substrate.

- ii. This study provides new insights into usage of pineapple wastewater as co-substrate for granulation. Although co-substrates such as glucose and acetate are commonly used in lab-scale study to aid the biogranules development and treatment process, their applications in actual plant is costly unattractive. Therefore, it is required to consider the potentials of a readily degradable wastewater as a co-substrate in the treatment of real textile wastewater.
- iii. The study also provides the effect of using different concentrations of pineapple wastewater in relation to dye degradation by the biogranules. The addition of pineapple wastewater excludes the addition of external nutrients and improve the degradation of textile wastewater which is recalcitrant in nature.
- iv. The findings on bacterial population within biogranule presents basic understanding in the microbial evolution of the biogranules developed using textile wastewater to further enhance the treatment process.

## **1.6 Organization of thesis**

The thesis is composed of five chapters. The first chapter deals with problems generated from the textile industry and the importance of developing biogranules using pilot-scale reactor using actual wastewater. The second chapter focuses on the literature review, mainly discusses on the textile waste, azo dye characteristics, dye degradation mechanisms, granulation process and pilot scale application. Then, the third chapter explains the methodology used for this study and provides the experimental work involved throughout the research. Chapter Four discusses the

findings of the research focusing on each objective. Finally, Chapter Five lays out the conclusions and proposes the recommendation for future research exploration.

## REFERENCES

- Ab Halim, M. H., Anuar, A. N., Azmi, S. I., Jamal, N. S. A., Wahab, N. A., Ujang, Z., . . . Bob, M. M. (2015). Aerobic Sludge Granulation at High Temperatures for Domestic Wastewater Treatment. *Bioresour Technol.* 185, 445-449.
- Abbasi, T., and Abbasi, S. A. (2012). Formation and Impact of Granules in Fostering Clean Energy Production and Wastewater Treatment in Upflow Anaerobic Sludge Blanket (UASB) Reactors. *Renewable and Sustainable Energy Reviews.* 16(3), 1696-1708.
- Abdullah, N., Yuzir, A., Curtis, T. P., Yahya, A., and Ujang, Z. (2013). Characterization of Aerobic Granular Sludge Treating High Strength Agro-Based Wastewater at Different Volumetric Loadings. *Bioresour Technol.* 127, 181-187.
- Abidi, N., Errais, E., Duplay, J., Berez, A., Jrad, A., Schäfer, G. and Trabelsi-Ayadi, M. (2015). Treatment of Dye-Containing Effluent by Natural Clay. *Journal of Cleaner Production.* 86, 432-440.
- Abrahart, E.N. (1977). *Dyes and Their Intermediates.* (2<sup>nd</sup> ed.) London. Edward Arnold Ltd.
- Abu-Ghunmi, L. N., and Jamrah, A. I. (2006). Biological Treatment of Textile Wastewater Using Sequencing Batch Reactor Technology. *Environmental Modeling and Assessment.* 11(4): 333-343.
- Achour, S., Khelifi, E., Ayed, L., Helal, A. N., and Bakhrouf, A. (2014). Response Surface Methodology for Textile Wastewater Decolourization and Biodegradation by A Novel Mixed Bacterial Consortium Developed via Mixture Design. *Desalination and Water Treatment.* 52(7-9), 1539-1549.
- Adav, S. S., and Lee, D.-J. (2011). Characterization of Extracellular Polymeric Substances (EPS) from Phenol Degrading Aerobic Granules. *Journal of the Taiwan Institute of Chemical Engineers.* 42(4), 645-651.

- Adav, S. S., Lee, D. J., and Lai, J. Y. (2009a). Functional Consortium from Aerobic Granules Under High Organic Loading Rates. *Bioresour Technol.* 100(14), 3465-3470.
- Adav, S. S., Lee, D. J., and Lai, J. Y. (2009b). Biological Nitrification-Denitrification with Alternating Oxidic and Anoxic Operations Using Aerobic Granules. *Appl Microbiol Biotechnol.* 84(6), 1181-1189.
- Adav, S. S., Lee, D. J., and Lai, J. Y. (2010). Potential Cause of Aerobic Granular Sludge Breakdown at High Organic Loading Rates. *Appl Microbiol Biotechnol.* 85(5), 1601-1610.
- Adav, S. S., Lee, D. J., and Tay, J. H. (2008b). Extracellular Polymeric Substances and Structural Stability of Aerobic Granule. *Water Res.* 42(6-7), 1644-1650.
- Adav, S. S., Lee, D. J., Show, K. Y., and Tay, J. H. (2008a). Aerobic Granular Sludge: Recent Advances. *Biotechnol Adv.* 26(5), 411-423.
- Adinew, B. (2012). Textile Effluent Treatment and Decolorization Techniques—A Review. *Bulgarian journal of science education.* 21(3), 434-456.
- Adnan, L. A., Hadibarata, T., Sathishkumar, P. and Mohd Yusoff, A. R. (2016), Biodegradation Pathway of Acid Red 27 by White-Rot Fungus *Armillaria* sp. F022 and Phytotoxicity Evaluation. *Clean Soil Air Water.* 44, 239–246.
- Agrawal, S., Tipre, D., Patel, B., and Dave, S. (2014). Optimization of Triazo Acid Black 210 Dye Degradation by *Providencia* Sp. SRS82 and Elucidation of Degradation Pathway. *Process Biochemistry.* 49(1), 110-119.
- Ahmad, A., Ghufuran, R., and Abd Wahid, Z. (2011). Role of Calcium Oxide in Sludge Granulation and Methanogenesis for the Treatment of Palm Oil Mill Effluent Using UASB Reactor. *J Hazard Mater.* 198, 40-48.
- Aiyuk, S., Odonkor, P., Theko, N., Van Haandel, A. and Verstraete, W (2010). Technical Problems Ensuing from UASB Reactor Application in Domestic Wastewater Treatment Without Pre-Treatment. *International Journal of Environmental Science and Development.* 1(5), 392-398.
- Al-Amrani, W.A., Lim, P.E., Seng, C.E. and Ngah, W.S.W. (2014). Factors Affecting Bio-decolorization of Azo Dyes and COD Removal in Anoxic–Aerobic REACT Operated Sequencing Batch Reactor. *Journal of the Taiwan Institute of Chemical Engineers.* 45(2), 609-616.
- Ali, H. (2010). Biodegradation of Synthetic Dyes—A Review. *Water, Air, and Soil Pollution.* 213(1-4), 251-273.

- Alinsafi, A., Evenou.,F , Abdulkarim., E.M., Pons , M.N., Zahraa , O., Benhammou ,A.,Yaacoubi, A. and Nejmeddine, A. (2007). Treatment of Textile Industry Wastewater By Supported Photocatalysis. *Dyes and Pigments*. 74, 439-445.
- Almeida, E. J., and Corso, C. R. (2014). Comparative Study of Toxicity of Azo Dye Procion Red MX-5B Following Biosorption and Biodegradation Treatments with The Fungi *Aspergillus Niger* and *Aspergillus Terreus*. *Chemosphere*. 112, 317-322.
- Al-Rubaie, L. A. A. R., and Mhessn, R. J. (2012). Synthesis and Characterization of Azo Dye Para Red and New Derivatives. *Journal of Chemistry*. 9(1), 465-470.
- Alvarez, J. A., Armstrong, E., Gomez, M., and Soto, M. (2008). Anaerobic Treatment of Low-Strength Municipal Wastewater by A Two-Stage Pilot Plant Under Psychrophilic Conditions. *Bioresour Technol*. 99(15), 7051-7062.
- American Public Health Association, (2005). *Standard Methods for the Examination of Water and Wastewater*. (21<sup>st</sup> ed). Washington, DC, USA American Public Health Association.
- Amin, M. N., and Blackburn, R. S. (2015). Sustainable Chemistry Method to Improve the Wash-off Process of Reactive Dyes on Cotton. *ACS Sustainable Chemistry and Engineering*. 3(4), 725-732.
- Ang, L. I., Yuanyuan, Q. U., Jiti, Z. H. O. U., and Min, G. O. U. (2009). Isolation and Characteristics of a Novel Biphenyl-Degrading Bacterial Strain, *Dyella Ginsengisoli* LA-4. *Journal of Environmental Sciences*. 21(2), 211-217.
- Anjaneya, O., Souche, S. Y., Santoshkumar, M., and Karegoudar, T. B. (2011). Decolorization of Sulfonated Azo Dye Metanil Yellow by Newly Isolated Bacterial Strains: *Bacillus* Sp. Strain AK1 and *Lysinibacillus* Sp. Strain AK2. *J Hazard Mater*. 190(1-3), 351-358.
- Aquino, J. M., Pereira, G. F., Rocha-Filho, R. C., Bocchi, N., and Biaggio, S. R. (2011). Electrochemical Degradation of a Real Textile Effluent Using Boron-Doped Diamond Or B-Pbo 2 As Anode. *Journal of hazardous materials*. 192(3), 1275-1282.
- Aravind, P., Subramanyan, V., Ferro, S., and Gopalakrishnan, R. (2016). Eco-Friendly and Facile Integrated Biological-Cum-Photo Assisted Electrooxidation Process for Degradation of Textile Wastewater. *Water Res*. 93, 230-241.



- Arrojo, B., Mosquera-Corral, A., Garrido, J. M., and Mendez, R. (2004). Aerobic Granulation with Industrial Wastewater in Sequencing Batch Reactors. *Water Res.* 38(14-15), 3389-3399.
- Asgari, G., Ramavandi, B., and Farjadfard, S. (2013). Abatement of Azo Dye from Wastewater using Bimetal-Chitosan. *Scientific World Journal.* 2013, 1-10.
- Ashwin, R., Athinthra, K. S., Sriramvignesh, M., Kathiravan, M. N., and Gopinath, K. P. (2011). Treatment of Textile Effluent using SBR with Pre-and Post-Treatments: Kinetics, Simulation and Optimization of Process Time for Shock Loads. *Desalination.* 275(1-3), 203-211.
- Aspland, J.R. (1997). *Textile Dyeing and Coloration* (1<sup>st</sup> ed) USA. American Association of Textile Chemists and Colorists (AATCC).
- Atashi, H., Ajamein, H. and Ghasemian, S. (2010). Effect of Operational and Design Parameters on Removal Efficiency of a Pilot-Scale UASB Reactor in A Sugar Factory. *World Applied Sciences Journal.* 11 (4), 451-456.
- Ayed, L., Mahdhi, A., Cheref, A., and Bakhrouf, A. (2011). Decolorization and Degradation of Azo Dye Methyl Red by An Isolated *Sphingomonas Paucimobilis*: Biototoxicity and Metabolites Characterization. *Desalination.* 274(1-3), 272-277.
- Aziz, S. Q., Aziz, H. A., Yusoff, M. S., and Mohajeri, S. (2012). Removal of Phenols and Other Pollutants from Different Landfill Leachates Using Powdered Activated Carbon Supplemented SBR Technology. *Environ Monit Assess.* 184(10), 6147-6158.
- Azizi, A., Alavi Moghaddam, M. R., Maknoon, R., and Kowsari, E. (2015). Innovative Combined Technique for High Concentration of Azo Dye AR18 Wastewater Treatment Using Modified SBR and Enhanced Fenton Process as Post Treatment. *Process Safety and Environmental Protection.* 95, 255-264.
- Babu, B.R., Parande, A.K., Raghu, S. and Prem Kumar, T. (2007). An Overview of Wastes Produced During Cotton Textile Processing and Effluent Treatment Methods. *The Journal of Cotton Science.* 11(1), 110–122.
- Baeta, B. E., Aquino, S. F., Silva, S. Q., and Rabelo, C. A. (2012). Anaerobic Degradation of Azo Dye Drimaren Blue HFRL In UASB Reactor In The Presence of Yeast Extract A Source of Carbon and Redox Mediator. *Biodegradation.* 23(2), 199-208.

- Balapure, K., Jain, K., Bhatt, N., and Madamwar, D. (2016). Exploring Bioremediation Strategies to Enhance The Mineralization of Textile Industrial Wastewater Through Sequential Anaerobic-Microaerophilic Process. *International Biodeterioration and Biodegradation*. 106, 97-105.
- Bardi, L., and Marzona, M. (2010). Factors Affecting the Complete Mineralization of Azo Dyes. In *Biodegradation of Azo Dyes*. Springer Berlin Heidelberg. 195-210.
- Bathe, S., Mohan, T.V.K., Wuertz, S. and Hausner, M. (2004). Bioaugmentation of A Sequencing Batch Biofilm Reactor by Horizontal Gene Transfer. *Water Science and Technology*. 49(11–12), 337–344.
- Batstone, D. J., Keller, J., and Blackall, L. L. (2004). The Influence of Substrate Kinetics on The Microbial Community Structure in Granular Anaerobic Biomass. *Water Res.* 38(6), 1390-1404.
- Beun, H.J., Hendricks, A., Van Loosdrecht, M.C.M., Morgenroth, E., Wilderer, P.A. and Heijnen, J.J. (1999). Aerobic Granulation in a Sequencing Batch Reactor. *Water Research*. 33, 2283-2290.
- Beun, J. J., Van Loosdrecht, M. C. M. and Heijnen, J. J. (2002). Aerobic Granulation in A Sequencing Batch Airlift Reactor. *Wat Res.* 36, 702–712.
- Bhuiyan, M. A. R., Rahman, M. M., Shaid, A., Bashar, M. M., and Khan, M. A. (2016). Scope of Reusing and Recycling The Textile Wastewater After Treatment With Gamma Radiation. *Journal of Cleaner Production*. 112, 3063-3071.
- Bindhu, B. K., and Madhu, G. (2013). Influence of Organic Loading Rates on Aerobic Granulation Process for the Treatment of Wastewater. *Journal of Clean Energy Technologies*. 84-87.
- Bisschops, I., and Spanjers, H. (2003). Literature Review on Textile Wastewater Characterisation. *Environ Technol.* 24(11), 1399-1411.
- Blanco, J., Torrades, F., De La Varga, M., and García-Montaña, J. (2012). Fenton and Biological-Fenton Coupled Processes for Textile Wastewater Treatment and Reuse. *Desalination*. 286, 394-399.
- Blumel, S. and Stolz, A. (2003). Cloning and Characterization of the Gene Coding for the Aerobic Azoreductase from *Pigmentiphage kullae* K24. *Appl. Microbiol. Biotechnol.* 62, 186-190.

- Borja, R., Banks, C. J and Sinchez, E. (1996). Anaerobic Treatment of Palm Oil Mill Effluent in A Two-Stage Up-Flow Anaerobic Sludge Blanket (UASB) System. *Journal of Biotechnology*. 45, 125- 135.
- Bos, R., Van Der Mei, H. C. and Busscher, H. J. (1999). Physico-Chemistry of Initial Microbial Adhesive Interactions — Its Mechanisms and Methods For Study. *FEMS Microbiol Rev*. 23, 179–230.
- Bras, R., Gomes, A., Ferra, M. I., Pinheiro, H. M., and Goncalves, I. C. (2005). Monoazo and Diazo Dye Decolourisation Studies in A Methanogenic UASB Reactor. *J Biotechnol*. 115(1), 57-66.
- Brillas, E., and Martínez-Huitle, C. A. (2015). Decontamination of Wastewaters Containing Synthetic Organic Dyes by Electrochemical Methods. An Updated Review. *Applied Catalysis B: Environmental*. 166-167, 603-643.
- Buthiyappan, A., Abdul Aziz, A. R., and Wan Daud, W. M. A. (2016). Recent Advances and Prospects of Catalytic Advanced Oxidation Process in Treating Textile Effluents. *Reviews in Chemical Engineering*. 32(1), 1-47.
- Cardoso, J. C., Bessegato, G. G., and Boldrin Zanoni, M. V. (2016). Efficiency Comparison of Ozonation, Photolysis, Photocatalysis and Photoelectrocatalysis Methods in Real Textile Wastewater Decolorization. *Water Res*. 98, 39-46.
- Carliell, C.M., Barclay, S.J. and Buckley, C.A. (1996). Treatment of Exhausted Reactive Dye bath Effluent using Anaerobic Digestion: Laboratory and Full-Scale Trials. *Water S.A.* 22, 225-233.
- Carmen, Z., and Daniela, S. (2012). Textile Organic Dyes—Characteristics, Polluting Effects and Separation/Elimination Procedures from Industrial Effluents—A Critical Overview. In *Organic Pollutants Ten Years After the Stockholm Convention-Environmental and Analytical Update*. InTech: Croatia. 55-81.
- Caudan, C., Filali, A., Sperandio, M., and Girbal-Neuhauser, E. (2014). Multiple EPS Interactions Involved in The Cohesion and Structure of Aerobic Granules. *Chemosphere*. 117, 262-270.
- Chan, C. H and Lim, P. E (2007). Evaluation of Sequencing Batch Reactor Performance with Aerated and Unaerated FILL Periods in Treating Phenol-Containing Wastewater. *Bioresour Technol*. 98, 1333–1338.

- Chan, Y. J., Chong, M. F., and Law, C. L. (2010). Biological Treatment of Anaerobically Digested Palm Oil Mill Effluent (POME) using a Lab-Scale Sequencing Batch Reactor (SBR). *J Environ Manage*, 91(8), 1738-1746.
- Chen, B. Y., Ma, C. M., Han, K., Yueh, P. L., Qin, L. J., and Hsueh, C. C. (2016). Influence of Textile Dye and Decolorized Metabolites on Microbial Fuel Cell-Assisted Bioremediation. *Bioresour Technol.* 200, 1033-1038.
- Chen, B. Y., Zhang, M. M., Chang, C. T., Ding, Y., Chen, W. M., and Hsueh, C. C. (2011). Deciphering Azo Dye Decolorization Characteristics by Indigenous *Proteus Hauseri*: Chemical Structure. *Journal of the Taiwan Institute of Chemical Engineers.* 42(2), 327-333.
- Chen, H., Wang, R.F. and Cerniglia, C.E. (2004). Molecular Cloning, Overexpression, Purification and Characterization of an Aerobic FMN-Dependent Azoreductase from *Anterococcus faecalis*. *Protein Expression Purif.* 34, 302-310.
- Chen, K. C., Wu, J. Y., Liou, D. J., and Hwang, S. J (2003). Decolorization Of The Textile Dyes By Newly Isolated Bacterial Strains. *Journal Of Biotechnology*, 101, 57-68.
- Chen, Y., Jiang, W., Liang, D. T., and Tay, J. H. (2007). Structure and Stability of Aerobic Granules Cultivated Under Different Shear Force in Sequencing Batch Reactors. *Appl Microbiol Biotechnol.* 76(5), 1199-1208.
- Chen, Y., Jiang, W., Liang, D. T., and Tay, J. H. (2008). Biodegradation and Kinetics of Aerobic Granules Under High Organic Loading Rates in Sequencing Batch Reactor. *Appl Microbiol Biotechnol.* 79(2), 301-308.
- Chen, Y.-Y., and Lee, D.-J. (2015). Effective Aerobic Granulation: Role of Seed Sludge. *Journal of the Taiwan Institute of Chemical Engineers.* 52, 118-119.
- Chieng, H. I., Zehra, T., Lim, L. B., Priyantha, N., and Tennakoon, D. (2014). Sorption Characteristics of Peat of Brunei Darussalam IV: Equilibrium, Thermodynamics and Kinetics Of Adsorption Of Methylene Blue and Malachite Green Dyes from Aqueous Solution. *Environmental Earth Sciences.* 72(7), 2263-2277.
- Chong, S., Sen, T. K., Kayaalp, A., and Ang, H. M. (2012). The Performance Enhancements of Upflow Anaerobic Sludge Blanket (UASB) Reactors for Domestic Sludge Treatment--A State-Of-The-Art Review. *Water Res.* 46(11), 3434-3470.

- Chung, K. T. (2016). Azo Dyes and Human Health: A Review. *J Environ Sci Health C Environ Carcinog Ecotoxicol Rev.* 34(4), 233-261.
- Çınar, Ö., and Demiröz, K. (2010). Biodegradation of Azo Dyes in Anaerobic–Aerobic Sequencing Batch Reactors. *Biodegradation of Azo Dyes* (pp. 59-72). Springer Berlin Heidelberg.
- Coates, J. (2000). *Interpretation of infrared spectra, a practical approach.* Encyclopedia of analytical chemistry.
- Coma, M., Verawaty, M., Pijuan, M., Yuan, Z., and Bond, P. L. (2012). Enhancing Aerobic Granulation for Biological Nutrient Removal from Domestic Wastewater. *Bioresour Technol.* 103(1), 101-108.
- Correia, V.M., Stephenson, T. and Simon, J. (1994). Characterisation Of Textile Wastewaters - A Review. *Environmental Technology.* 15(10), 917-929.
- Couras, C. S., Louros, V. L., Grilo, A. M., Leitão, J. H., Capela, M. I., Arroja, L. M., and Nadais, M. H. (2014). Effects of Operational Shocks on Key Microbial Populations for Biogas Production in UASB (Upflow Anaerobic Sludge Blanket) Reactors. *Energy.* 73, 866-874.
- Crini, G. (2006). Non-Conventional Low-Cost Adsorbents for Dye Removal: A Review. *Bioresour Technol.* 97(9), 1061-1085.
- Cui, M. H., Cui, D., Gao, L., Wang, A. J., and Cheng, H. Y. (2016). Azo Dye Decolorization In An Up-Flow Bioelectrochemical Reactor With Domestic Wastewater As A Cost-Effective Yet Highly Efficient Electron Donor Source. *Water Res.* 105, 520-526.
- Daâssi, D., Mechichi, T., Nasri, M., and Rodriguez-Couto, S. (2013). Decolorization of The Metal Textile Dye Lanaset Grey G by Immobilized White-Rot Fungi. *Journal of Environmental Management.* 129, 324-332.
- Dahalan, F. A., Abdullah, N., Yuzir, A., Olsson, G., Salmiati, Hamdzah, M. and Ujang, Z. (2015). A Proposed Aerobic Granules Size Development Scheme for Aerobic Granulation Process. *Bioresour Technol.* 181, 291-296.
- Dasgupta, J., Sikder, J., Chakraborty, S., Curcio, S., and Drioli, E. (2015). Remediation of Textile Effluents By Membrane Based Treatment Techniques: A State of The Art Review. *J Environ Manage.* 147, 55-72.
- De Jager, D., Sheldon, M. S., and Edwards, W. (2014). Colour Removal from Textile Wastewater using A Pilot-Scale Dual-Stage MBR and Subsequent RO System. *Separation and Purification Technology.* 135, 135-144.

- De Sanctis, M., Di Iaconi, C., Lopez, A. and Rossetti, S. (2010). Granular Biomass Structure and Population Dynamics in Sequencing Batch Biofilter Granular Reactor (SBBGR). *Bioresour Technol.* 101, 2152–2158.
- De Souza, S. M., Bonilla, K. A., and De Souza, A. A. (2010). Removal of COD and Color from Hydrolyzed Textile Azo Dye by Combined Ozonation and Biological Treatment. *J Hazard Mater.* 179(1-3), 35-42.
- Debik, E. and Manav, N. (2010). Sequence Optimization in A Sequencing Batch Reactor for Biological Nutrient Removal from Domestic Wastewater. *Bioprocess Biosyst Eng.* 33, 533–540.
- Department of Environment Malaysia (2015). Environmental Quality Report: Acceptable Conditions for Discharge of Industrial Effluent or Mixed Effluent of Standards A and B. *Environmental Quality (Industry Effluents) Regulations 2009.* (PU (A) 434).
- Deveci, E. Ü., Dizge, N., Yatmaz, H. C., and Aytepe, Y. (2016). Integrated Process of Fungal Membrane Bioreactor and Photocatalytic Membrane Reactor for The Treatment of Industrial Textile Wastewater. *Biochemical Engineering Journal.* 105, 420-427.
- Diaz, C., Baena, S., Fardeau, M. L., and Patel, B. K. (2007). Aminiphilus Circumscriptus Gen. Nov., Sp. Nov., An Anaerobic Amino-Acid-Degrading Bacterium from An Upflow Anaerobic Sludge Reactor. *Int J Syst Evol Microbiol.* 57(8), 1914-1918.
- Ding, Y., Feng, H., Huang, W., Shen, D., and Wang, M. (2015). A Sustainable Method for Effective Regulation Of Anaerobic Granular Sludge: Artificially Increasing The Concentration Of Signal Molecules by Cultivating A Secreting Strain. *Bioresour Technol.* 196, 273-278.
- Dojcinovic, B., Roglic, G., Obradovic, B., Kuraica, M., Tosti, T., Markovic, M., and Manojlovic, D. (2012). Decolorization of Reactive Black 5 using Dielectric Barrier Discharge in The Presence of Inorganic Salts. *Journal of the Serbian Chemical Society.* 77(4), 535-548.
- Dos Santos, A. B., Cervantes, F. J., and van Lier, J. B. (2007). Review Paper on Current Technologies for Decolourisation of Textile Wastewaters: Perspectives for Anaerobic Biotechnology. *Bioresour Technol.* 98(12), 2369-2385.

- Dukkanci, M., Vinatoru, M., and Mason, T. J. (2014). The Sonochemical Decolourisation of Textile Azo Dye Orange II: Effects of Fenton Type Reagents and UV Light. *Ultrason Sonochem.* 21(2), 846-853.
- Duque, A. F., Bessa, V. S., Carvalho, M. F., De Kreuk, M. K., Van Loosdrecht, M. C. M and Castro, P. M. L (2011). 2-Fluorophenol Degradation by Aerobic Granular Sludge in A Sequencing Batch Reactor. *Wat Res.* 45, 6745 -6752.
- Dutta, A., and Sarkar, S. (2015). Sequencing Batch Reactor for Wastewater Treatment: Recent Advances. *Current Pollution Reports.* 1(3), 177-190.
- El-Mamouni, R., Guiot, S.R., Leduc, R. and Costerton, J.W. (1995). Characterization of Different Microbial Nuclei As Potential Precursors of Anaerobic Granulation. *Journal of Biotechnology.* 39, 239-249.
- El-Mamouni, R., Leduc, R., and Guiot, S. R. (1997). Influence of The Starting Microbial Nucleus Type on The Anaerobic Granulation Dynamics. *Applied Microbiology and Biotechnology.* 47(2), 189-194.
- Fang, H. H. P. (2000). Microbial Distribution In UASB Granules And Its Resulting Effects. *Water Science And Technology,* 42(12), 201–208.
- Farabegoli, G., Chiavola, A., Rolle, E. and Naso, M. (2010). Decolorization of Reactive Red 195 by A Mixed Culture in An Alternating Anaerobic–Aerobic Sequencing Batch Reactor. *Biochemical Engineering Journal.* 52, 220–226.
- Feng, Q., Cao, J. S., Chen, L. N., Guo, C. Y., Tan, J. Y., and Xu, H. L. (2012). Effect of Carbon Source on Biological Nitrogen Removal of Aerobic Granules in Sequencing Batch Reactors. *Journal of Food, Agriculture and Environment.* 10(2), 1110-1113.
- Ferrer-Polonio, E., Iborra-Clar, A., Mendoza-Roca, J. A., and Iborra-Clar, M. I. (2015). Combination of Adsorption and Biological Treatment in A SBR for Colour Elimination in Municipal Wastewater with Discharges of Textile Effluents. *Desalination and Water Treatment.* 55(7), 1915-1921.
- Figuerola, M., Rio, A. V., Campos, J. L., Mosquera-Corral, A. and Mendez, R. (2011). Treatment of High Loaded Swine Slurry in An Aerobic Granular Reactor. *Water Science and Technology.* 63(9), 1808-1814.
- Firmino, P. I., da Silva, M. E., Cervantes, F. J., and dos Santos, A. B. (2010). Colour Removal of Dyes from Synthetic and Real Textile Wastewaters in One- and Two-Stage Anaerobic Systems. *Bioresour Technol,* 101(20), 7773-7779.

- Fongsatitkul, P., Elefsiniotis, P., Yamasmit, A., and Yamasmit, N. (2004). Use of Sequencing Batch Reactors and Fenton's Reagent to Treat a Wastewater from A Textile Industry. *Biochemical Engineering Journal*. 21(3), 213-220.
- Franca, R. D., Vieira, A., Mata, A. M., Carvalho, G. S., Pinheiro, H. M., and Lourenco, N. D. (2015). Effect of An Azo Dye on The Performance of An Aerobic Granular Sludge Sequencing Batch Reactor Treating A Simulated Textile Wastewater. *Water Res.* 85, 327-336.
- Franciscon, E., Mendonça, D., Seber, S., Morales, D. A., Zocolo, G. J., Zanoni, M. B., and Umbuzeiro, G. A. (2015). Potential of A Bacterial Consortium to Degrade Azo Dye Disperse Red 1 in A Pilot Scale Anaerobic–Aerobic Reactor. *Process Biochemistry*. 50(5), 816-825.
- Gao, D., Liu, L., Liang, H., and Wu, W. M. (2011). Aerobic Granular Sludge: Characterization, Mechanism of Granulation and Application to Wastewater Treatment. *Critical Reviews in Biotechnology*. 31(2), 137-152.
- García-Martínez, Y., Bengoa, C., Stüber, F., Fortuny, A., Font, J., and Fabregat, A. (2015). Biodegradation of Acid Orange 7 in An Anaerobic–Aerobic Sequential Treatment System. *Chemical Engineering and Processing: Process Intensification*. 94, 99-104.
- Gaval G., and Pernell, J. J. (2003). Impact of The Repetition of Oxygen Deficiencies on The Filamentous Bacteria Proliferation in Activated Sludge. *Water Res.* 37, 1991–2000.
- Gavrilescu, M. (2002). Engineering Concerns and New Developments in Anaerobic Waste-Water Treatment. *Clean Technologies and Environmental Policy*. 3(4), 346-362.
- Ghaly, A. E., Ananthashankar, R., Alhattab, M. V. V. R., and Ramakrishnan, V. V. (2014). Production, Characterization and Treatment of Textile Effluents: A Critical Review. *Journal of Chemical Engineering and Process Technology*. 5(1), 1.
- Ghanbari, F., and Moradi, M. (2015). A Comparative Study of Electrocoagulation, Electrochemical Fenton, Electro-Fenton And Peroxi-Coagulation for Decolorization of Real Textile Wastewater: Electrical Energy Consumption and Biodegradability Improvement. *Journal of Environmental Chemical Engineering*. 3(1), 499-506.



- Ghanbari, F., Moradi, M., Eslami, A., and Emamjomeh, M. M. (2014). Electrocoagulation/Flotation of Textile Wastewater with Simultaneous Application of Aluminum and Iron as Anode. *Environmental Processes*. 1(4), 447-457.
- Ghangrekar, M.M., Asolekar, S.R. and Joshi, S.G. (2005). Characteristics of Sludge Developed under Different Loading Conditions during UASB Reactor Start-up and Granulation. *Water Res.* 39(6), 1123-1133.
- GilPavas, E., Dobrosz-Gomez, I., and Gomez-Garcia, M. A. (2017). Coagulation-Flocculation Sequential with Fenton Or Photo-Fenton Processes as An Alternative for The Industrial Textile Wastewater Treatment. *J Environ Manage.* 191, 189-197.
- Gnanapragasam, G., Arutchelvan, V., Senthilkumar, M., Sivarajan, P., and Nagarajan, S (2010). Recycle in Upflow Anaerobic Sludge Blanket Reactor on Treatment of Real Textile Dye Effluent. *World J Microbiol Biotechnol.* 26, 1093–1098.
- Gnanapragasam, G., Senthilkumar, M., Arutchelvan, V., Velayutham, T., and Nagarajan, S. (2011). Bio-Kinetic Analysis on Treatment of Textile Dye Wastewater Using Anaerobic Batch Reactor. *Bioresour Technol.* 102(2), 627-632.
- Gogol-Döring, A., and Chen, W. (2012). An Overview of The Analysis of Next Generation Sequencing Data. In Wang, J., Tan, A.C., and Tian, T. (Eds.) *Next Generation Microarray Bioinformatics: Methods and Protocols, Methods in Molecular Biology*. (pp. 249-257). Springer New York Dordrecht Heidelberg London: Humana Press.
- González, L., and Silva, E. E. (2012). Biodegradation of a Reactive Red Azo Dye in an Upflow Anaerobic Bioreactor. In *Water Resources in Mexico* (pp. 299-316). Springer Berlin Heidelberg.
- Gosavi, V. D., and Sharma, S. (2014). A General Review on Various Treatment Methods for Textile Wastewater. *J Environ Sci-Computer Sci Eng Technol.* 3(1), 29-39.
- Gouveia, J., Plaza, F., Garralon, G., Fdz-Polanco, F., and Pena, M. (2015). Long-Term Operation of A Pilot Scale Anaerobic Membrane Bioreactor (AnMBR) for The Treatment of Municipal Wastewater Under Psychrophilic Conditions. *Bioresour Technol.* 185, 225-233.

- Grotenhuis, J. T. C., Smit, M., Van Lammeren, A. A. M., Stams, A. J. M. and Zehnder, A. J. B. (1991). Localization and Quantification of Extracellular Polymers In Methanogenic Granular Sludge. *Appl. Microbiol. Biotechnol.* 36, 115–119.
- Guo, F., and Zhang, T. (2012). Profiling Bulking and Foaming Bacteria in Activated Sludge by High Throughput Sequencing. *Water Research.* 46, 2772 – 2782.
- Guo, J., Peng, Y., Huang, H., and Wang, S., Ge, S., Zhang, J. and Wang Z. (2010). Short- and Long-Term Effects of Temperature on Partial Nitrification in A Sequencing Batch Reactor Treating Domestic Wastewater. *Journal of Hazardous Materials.* 179, 471–479.
- Gupta, S. K., Nayunigari, M. K., Misra, R., Ansari, F. A., Dionysiou, D. D., Maity, A., and Bux, F. (2016). Synthesis and Performance Evaluation of a New Polymeric Composite for the Treatment of Textile Wastewater. *Industrial and Engineering Chemistry Research*, 55(1), 13-20.
- Gupta, V. K., Kumar, R., Nayak, A., Saleh, T. A., and Barakat, M. A. (2013). Adsorptive Removal of Dyes from Aqueous Solution onto Carbon Nanotubes: A Review. *Adv Colloid Interface Sci.* 193-194, 24-34.
- Hai, F. I., Yamamoto, K., and Fukushi, K. (2007). Hybrid Treatment Systems for Dye Wastewater. *Critical Reviews in Environmental Science and Technology.* 37(4), 315-377.
- Hao, O. J., Kim, H., and Chiang, P. C. (2000). Decolorization of Wastewater. *Critical Reviews in Environmental Science and Technology.* 30(4), 449-505.
- Haroun, M., and Idris, A. (2009). Treatment of Textile Wastewater With An Anaerobic Fluidized Bed Reactor. *Desalination.* 237(1-3), 357-366.
- Harrelkas, F., Paulo, A., Alves, M. M., El Khadir, L., Zahraa, O., Pons, M. N., and Van Der Zee, F. P. (2008). Photocatalytic and Combined Anaerobic-Photocatalytic Treatment of Textile Dyes. *Chemosphere.* 72(11), 1816-1822.
- Hemalatha, R. and Anbuselvi, S. (2013). Physicochemical Constituents of Pineapple Pulp and Waste. *Journal of Chemical and Pharmaceutical Research.* 5(2): 240-242.
- Hibbing, M. E., Fuqua, C., Parsek, M. R. and Peterson, S. B. (2010). Bacterial competition: surviving and thriving in the microbial jungle. *Nat Rev Micro.* 8, 15-25.

- Holkar, C. R., Jadhav, A. J., Pinjari, D. V., Mahamuni, N. M., and Pandit, A. B. (2016). A Critical Review on Textile Wastewater Treatments: Possible Approaches. *J Environ Manage.* 182, 351-366.
- Hong, Y., Chen, X., Guo, J., Xu, Z., Xu, M. and Sun, G. (2007). Effects of Electron Donors and Acceptors on Anaerobic Reduction of Azo Dyes by *Shewanella decolorationis* S12. *Appl. Microbiol. Biotechnol.* 74, 230-238.
- Hsueh, C. C., and Chen, B. Y. (2007). Comparative Study on Reaction Selectivity of Azo Dye Decolorization by *Pseudomonas Luteola*. *J Hazard Mater.* 141, 842–849.
- Hsueh, C. C., and Chen, B. Y. (2008). Exploring Effects of Chemical Structure on Azo Dye Decolorization Characteristics by *Pseudomonas Luteola*. *J Hazard Mater.* 154, 703-710.
- Hsueh, C. C., Chen, B. Y., and Yen, C. Y. (2009). Understanding Effects of Chemical Structure on Azo Dye Decolorization Characteristics by *Aeromonas Hydrophila*. *J Hazard Mater.* 167, 995-1001.
- Hu, L., Wang, J., Wen, X. and Qian, Y. (2005). The Formation and Characteristics of Aerobic Granules in Sequencing Batch Reactor (SBR) by Seeding Anaerobic Granules. *Process Biochem.* 40, 5-11.
- Huang, R., Liu, Q., Huo, J., and Yang, B. (2017). Adsorption of Methyl Orange onto Protonated Cross-Linked Chitosan. *Arabian Journal of Chemistry.* 10(1), 24-32.
- Huang, W., Li, B., Zhang, C., Zhang, Z., Lei, Z., Lu, B., and Zhou, B. (2015). Effect of Algae Growth on Aerobic Granulation And Nutrients Removal from Synthetic Wastewater by Using Sequencing Batch Reactors. *Bioresour Technol.* 179, 187-192.
- Ibrahim, Z., Amin, M. F., Yahya, A., Aris, A., and Muda, K. (2010). Characteristics of Developed Granules Containing Selected Decolourising Bacteria for The Degradation Of Textile Wastewater. *Water Sci Technol.* 61(5), 1279-1288.
- Ibrahim, Z., Amin, M.F.M., Yahya, A., Aris, A., Umor, N.A., Muda, K. and Sofian, N.S. (2009). Characterisation of Microbial Floccs Formed from Raw Textile Wastewater in Aerobic Biofilm Reactor (ABR). *Water Science and Technology.* 60(3), 683-688.

- Iqbal, M., and Nisar, J. (2015). Cytotoxicity and Mutagenicity Evaluation of Gamma Radiation and Hydrogen Peroxide Treated Textile Effluents using Bioassays. *Journal of Environmental Chemical Engineering*. 3(3), 1912-1917.
- Isanta, E., Suárez-Ojeda, M. E., Val del Río, Á., Morales, N., Pérez, J., and Carrera, J. (2012). Long Term Operation of A Granular Sequencing Batch Reactor at Pilot Scale Treating A Low-Strength Wastewater. *Chemical Engineering Journal*. 198-199, 163-170.
- Işik, M. (2004). Efficiency of Simulated Textile Wastewater Decolorization Process Based on The Methanogenic Activity of Upflow Anaerobic Sludge Blanket Reactor in Salt Inhibition Condition. *Enzyme and Microbial Technology*. 35(5), 399-404.
- Isik, M. and Sponza, D.T. (2004). Decolorization of Azo Dyes Under Batch Anaerobic and Two-Stage Anaerobic/Aerobic Condition. *J. Environ.Sci. Health Part A: Tox. Hazard. Subst. Environ.* 39(4), 1107-1127.
- Işik, M., and Sponza, D. T. (2005). Substrate Removal Kinetics in An Upflow Anaerobic Sludge Blanket Reactor Decolorising Simulated Textile Wastewater. *Process Biochemistry*. 40(3-4), 1189-1198.
- Jadhav, S. B., Phugare, S. S., Patil, P. S., and Jadhav, J. P. (2011). Biochemical Degradation Pathway of Textile Dye Remazol Red and Subsequent Toxicological Evaluation by Cytotoxicity, Genotoxicity and Oxidative Stress Studies. *International Biodeterioration and Biodegradation*, 65(6), 733-743.
- Jain, R. M., Mody, K. H., Keshri, J., and Jha, B. (2014). Biological Neutralization and Biosorption of Dyes of Alkaline Textile Industry Wastewater. *Marine pollution bulletin*. 84(1), 83-89.
- Jegatheesan, V., Pramanik, B. K., Chen, J., Navaratna, D., Chang, C. Y., and Shu, L. (2016). Treatment of Textile Wastewater with Membrane Bioreactor: A Critical Review. *Bioresour Technol.* 204, 202-212.
- Jemaat, Z., Suarez-Ojeda, M. E., Perez, J., and Carrera, J. (2014). Sequentially Alternating Pollutant Scenarios of Phenolic Compounds in A Continuous Aerobic Granular Sludge Reactor Performing Simultaneous Partial Nitrification and O-Cresol Biodegradation. *Bioresour Technol.* 161, 354-361.
- Jiang, X., Yuan, Y., Ma, F., Tian, J., and Wang, Y. (2015). Enhanced Biological Phosphorus Removal by Granular Sludge in Anaerobic/Aerobic/Anoxic SBR

- During Start-Up Period. *Desalination and Water Treatment*. 57(13), 5760-5771.
- Joshi, M. and Purwar, R. (2004). Developments in New Processes for Colour Removal from Effluent. *Rev.Prog.Colour*. 34, 58-71.
- Joshi, S. M., Inamdar, S. A., Telke, A. A., Tamboli, D. P., and Govindwar, S. P. (2010). Exploring the Potential of Natural Bacterial Consortium to Degrade Mixture of Dyes and Textile Effluent. *International Biodeterioration and Biodegradation*. 64(7), 622-628.
- Jungles, M. K., Figueroa, M., Morales, N., Val del Río, Á., da Costa, R. H. R., Campos, J. L., Méndez, R. (2011). Start Up of A Pilot Scale Aerobic Granular Reactor for Organic Matter and Nitrogen Removal. *Journal of Chemical Technology and Biotechnology*. 86(5), 763-768.
- Jungles, M. K., J.L., C., and R.H.R, C. (2014). Sequencing Batch Reactor Operation For Treating Wastewater With Aerobic Granular Sludge. *Brazilian Journal of Chemical Engineering*. 31(1), 27-33.
- Kalyani, D. C., Patil, P. S., Jadhav, J. P., and Govindwar, S. P. (2008). Biodegradation of Reactive Textile Dye Red BLI by An Isolated Bacterium Pseudomonas Sp. SUK1. *Bioresour Technol*. 99(11), 4635-4641.
- Kalyani, D. C., Telke, A. A., Dhanve, R. S., and Jadhav, J. P. (2009). Ecofriendly Biodegradation and Detoxification of Reactive Red 2 Textile Dye by Newly Isolated Pseudomonas Sp. SUK1. *J Hazard Mater*. 163(2-3), 735-742.
- Kalyuzhnyi, S. V., Fedorovich, V. V., and Lens, P. (2006). Dispersed Plug Flow Model for Upflow Anaerobic Sludge Bed Reactors with Focus on Granular Sludge Dynamics. *J Ind Microbiol Biotechnol*. 33(3): 221-237.
- Karatas, M., Dursun, S., and Argun, M. E. (2011). Methane Production From Anaerobic-Aerobic Sequential System Treatment of Azo Dye Reactive Red 24. *Environmental Progress and Sustainable Energy*. 30(1), 50-58.
- Kasiri, M. B., and Safapour, S. (2014). Natural Dyes and Antimicrobials for Green Treatment of Textiles. *Environmental chemistry letters*. 12(1), 1-13.
- Kee, T.C., Bay, H.H., Lim, C.K., Muda, K. and Ibrahim, Z. (2015). Development of Bio-biogranules using Selected Mixed Culture of Decolorizing Bacteria for the Treatment of Textile Wastewater. *Desalination and Water Treatment*. 54(1), 132-139.

- Khalil, N., Sinha, R., Raghav, A. K., and Mittal, A. K. (2008). UASB Technology for Sewage Treatment in India: Experience, Economic Evaluation and Its Potential in Other Developing Countries. In *Twelfth International Water Technology Conference*. 1411-1427.
- Khan, R., Bhawana, P., and Fulekar, M. H. (2013). Microbial Decolorization and Degradation of Synthetic Dyes: A Review. *Rev Environ Sci Biotechnol*. 12, 75–97.
- Khataee, A. R., Vafaei, F., and Jannatkah, M. (2013). Biosorption of Three Textile Dyes from Contaminated Water by Filamentous Green Algal *Spirogyra* Sp.: Kinetic, Isotherm and Thermodynamic Studies. *International Biodeterioration and Biodegradation*. 83, 33-40.
- Khatri, A., Peerzada, M. H., Mohsin, M., and White, M. (2015). A Review on Developments in Dyeing Cotton Fabrics with Reactive Dyes for Reducing Effluent Pollution. *Journal of Cleaner Production*. 87, 50-57.
- Khdem, L. K., and Mageed, N. S. (2013). Removal of Azo Compounds from Aqueous Solutions by the Process of Adsorption on Bentonite Surfaces. *J. Chem. and Cheml. Sci.* 3(3), 117-130.
- Khelifi, E., Ayed, L., Bouallagui, H., Touhami, Y., and Hamdi, M. (2009). Effect of Nitrogen and Carbon Sources on Indigo and Congo Red Decolourization by *Aspergillus Alliaceus* Strain 121C. *J Hazard Mater*. 163(2-3), 1056-1062.
- Khouni, I., Marrot, B., and Amar, R. B. (2012). Treatment of Reconstituted Textile Wastewater Containing a Reactive Dye in An Aerobic Sequencing Batch Reactor Using a Novel Bacterial Consortium. *Separation and Purification Technology*. 87, 110-119.
- Kiernan, J. A. (2001). Classification and Naming of Dyes, Stains and Fluorochromes. *Biotechnic and histochemistry*. 76(5-6), 261-278.
- Kim, S. J., Kweon, O., Jones, R. C., Freeman, J. P., Edmondson, R. D., and Cerniglia, C. E. (2007). Complete and Integrated Pyrene Degradation Pathway in *Mycobacterium Vanbaalenii* PYR-1 Based on Systems Biology. *J Bacteriol*. 189(2), 464-472.
- Koby, M., Bayramoglu, M., and Eyvaz, M. (2007). Techno-Economical Evaluation of Electrocoagulation for The Textile Wastewater Using Different Electrode Connections. *Journal of hazardous materials*. 148(1), 311-318.

- Kobyas, M., Gengec, E., and Demirbas, E. (2016). Operating Parameters and Costs Assessments of A Real Dyehouse Wastewater Effluent Treated by A Continuous Electrocoagulation Process. *Chemical Engineering and Processing: Process Intensification*. 101, 87-100.
- Kondusamy, D., and Kalamdhad, A. S. (2014). Pre-Treatment and Anaerobic Digestion of Food Waste for High Rate Methane Production – A Review. *Journal of Environmental Chemical Engineering*. 2(3), 1821-1830.
- Kong, Q., Ngo, H. H., Shu, L., Fu, R. S., Jiang, C. H., and Miao, M. S. (2014). Enhancement of Aerobic Granulation by Zero-Valent Iron in Sequencing Batch Airlift Reactor. *J Hazard Mater*. 279, 511-517.
- Kong, Y., Liu, Y. Q., Tay, J. H., Wong, F. S. and Zhu, J. (2009). Aerobic Granulation in Sequencing Batch Reactors with Different Reactor Height/Diameter Ratios. *Enzyme and Microbial Technology*. 45(5): 379-383.
- Koupaie, E. H., Moghaddam, M. A., and Hashemi, S. H. (2013). Evaluation of Integrated Anaerobic/Aerobic Fixed-Bed Sequencing Batch Biofilm Reactor for Decolorization and Biodegradation of Azo Dye Acid Red 18: Comparison of Using Two Types of Packing Media. *Bioresour technol*. 127, 415-421.
- Kurade, M. B., Waghmode, T. R., Jadhav, M. U., Jeon, B.-H., and Govindwar, S. P. (2015). Bacterial–Yeast Consortium as An Effective Biocatalyst for Biodegradation of Sulphonated Azo Dye Reactive Red 198. *RSC Adv*. 5(29), 23046-23056.
- Kurade, M. B., Waghmode, T. R., Kagalkar, A. N., and Govindwar, S. P. (2012). Decolorization of Textile Industry Effluent Containing Disperse Dye Scarlet RR by A Newly Developed Bacterial-Yeast Consortium BL-GG. *Chemical Engineering Journal*. 184, 33-41.
- Kushwaha, J.P., Srivastava, V.C. and Mall, I.D. (2013). Sequential Batch Reactor for Dairy Wastewater Treatment: Parametric Optimization; Kinetics and Waste Sludge Disposal. *Journal of Environmental Chemical Engineering*. 1(4), 1036-1043.
- KwarciaK-Kozłowska, A, Bohdziewicz, J., Mielczarek, K. and Krzywicka, A. (2011). The Application of UASB Reactor in Meat Industry Wastewater Treatment. *Civil and Environmental Engineering Reports*. 7, 119-128.

- Lalnunhlimi, S., and Krishnaswamy, V. (2016). Decolorization of Azo Dyes (Direct Blue 151 And Direct Red 31) By Moderately Alkaliphilic Bacterial Consortium. *Brazilian Journal of Microbiology*. 47(1), 39-46.
- Lamichhane, P., Paudel, P.N., and Kafle, B.P. (2015) Optical Absorbance and Fluorescence of Natural Dyes: Prospect of Application in Dye Sensitized Solar Cell and OLEDs. *Research Journal of Pharmaceutical, Biological and Chemical Sciences*. 6(5), 823-828.
- Latif, M. A., Ghufuran, R., Wahid, Z. A., and Ahmad, A. (2011). Integrated Application of Upflow Anaerobic Sludge Blanket Reactor for The Treatment of Wastewaters. *Water Res*. 45(16), 4683-4699.
- Laxman, M. (2009). Pollution and Its Control in Textile Industry. *Dyes and Chemicals*. Retrieved on June 26, 2013 from <http://www.fibre2fashion.com>
- Lee, D. J., Chen, Y. Y., Show, K. Y., Whiteley, C. G., and Tay, J. H. (2010). Advances in Aerobic Granule Formation and Granule Stability in The Course of Storage and Reactor Operation. *Biotechnol Adv*. 28(6), 919-934.
- Lee, Y. H., Lee, S. G., Hwang, E. K., Baek, Y. M., Cho, S., and Kim, H. D. (2017). Dyeing Properties and Deodorizing/Antibacterial Performance of Cotton/Silk/Wool Fabrics Dyed with Myrrh (*Commiphora Myrrha*) Extract. *Textile Research Journal*. 87(8), 973-983.
- Lettinga, G (1995). Anaerobic Digestion and Wastewater Treatment Systems. *Antonie van Leeuwenhoek*. 67, 3-28
- Lettinga, G. A. F. M., Van Velsen, A. F. M., Hobma, S. W., De Zeeuw, W., and Klapwijk, A. (1980). Use of The Upflow Sludge Blanket (USB) Reactor Concept for Biological Wastewater Treatment, Especially for Anaerobic Treatment. *Biotechnology and bioengineering*. 22(4), 699-734.
- Li, A. J., Yang, S. F., Li, X. Y., and Gu, J. D. (2008). Microbial Population Dynamics During Aerobic Sludge Granulation at Different Organic Loading Rates. *Water Res*. 42(13), 3552-3560.
- Li, A. J., Zhang, T., and Li, X. Y. (2010a). Fate of Aerobic Bacterial Granules with Fungal Contamination Under Different Organic Loading Conditions. *Chemosphere*. 78(5), 500-509.
- Li, H.-X., Xu, B., Tang, L., Zhang, J.-H., and Mao, Z.-G. (2015). Reductive Decolorization of Indigo Carmine Dye with *Bacillus* Sp. MZS10. *International Biodeterioration and Biodegradation*. 103, 30-37.



- Li, J., Ding, L. B., Cai, A., Huang, G. X., and Horn, H. (2014). Aerobic Sludge Granulation in A Full-Scale Sequencing Batch Reactor. *Biomed Res Int.* 2014.
- Li, Z., Zhang, T., Li, N. and Wang, X. (2010b). Granulation of Filamentous Microorganisms in A Sequencing Batch Reactor with Saline Wastewater. *Journal of Environmental Sciences.* 22(1), 62–67.
- Libra, J.A., Borchert, M., Vigelahn, L. and Storm, T. (2004). Two Stage Biological Treatment of a Diazo Reactive Textile Dye and the Fate of the Dye Metabolites. *Chemosphere.* 56(2), 167-180.
- Lim, J. X., and Vadivelu, V. M. (2014). Treatment of Agro Based Industrial Wastewater in Sequencing Batch Reactor: Performance Evaluation and Growth Kinetics of Aerobic Biomass. *J Environ Manage.* 146, 217-225.
- Lim, S. J., and Kim, T.-H. (2014). Applicability and Trends of Anaerobic Granular Sludge Treatment Processes. *Biomass and Bioenergy.* 60, 189-202.
- Lin, K. C., and Yang, Z. (1991). Technical Review on The UASB Process. *International Journal of Environmental Studies.* 39(3), 203-222.
- Lin, Y. M., Liu, Y., and Tay, J. H. (2003). Development and Characteristics of Phosphorus-Accumulating Microbial Granules in Sequencing Batch Reactors. *Appl Microbiol Biotechnol.* 62(4), 430-435.
- Linlin, H., Jianlong, W., Xianghua, W. and Yi, Q. (2005). The Formation and Characteristics of Aerobic Granules in Sequencing Batch Reactor (SBR) by Seeding Anaerobic Granules. *Process Biochemistry.* 40(1), 5-11.
- Liu, J., Li, J., Wang, X., Zhang, Q., and Littleton, H. (2017). Rapid Aerobic Granulation in An SBR Treating Piggery Wastewater by Seeding Sludge from A Municipal WWTP. *J Environ Sci (China).* 51, 332-341.
- Liu, Q.S. and Liu.Y (2008). Aerobic Granulation at Different Carbon Sources and Concentration. Liu.Y. *Wastewater Purification: Aerobic Granulation in Sequencing Batch Reactors.* (1-20). Baco Raton, FL: CRC Press.
- Liu, Y. and Tay, J.H. (2002). The Essential Role of Hydrodynamic Shear Force in The Formation of Biofilm and Granular Sludge. *Wat Res.* 36, 1653-65.
- Liu, Y., Kang, X., Li, X., and Yuan, Y. (2015a). Performance of Aerobic Granular Sludge in A Sequencing Batch Bioreactor for Slaughterhouse Wastewater Treatment. *Bioresour Technol.* 190, 487-491.

- Liu, Y. Q., Liu, Y., and Tay, J. H. (2004). The Effects of Extracellular Polymeric Substances on The Formation and Stability of Biogranules. *Appl Microbiol Biotechnol.* 65(2), 143-148.
- Liu, Y. Q., Zhang, X., Zhang, R., Liu, W. T., and Tay, J. H. (2016). Effects of Hydraulic Retention Time on Aerobic Granulation and Granule Growth Kinetics at Steady State with A Fast Start-Up Strategy. *Appl Microbiol Biotechnol.* 100(1), 469-477.
- Liu, Y., Zhang, Y., and Ni, B. J. (2015b). Zero Valent Iron Simultaneously Enhances Methane Production and Sulfate Reduction in Anaerobic Granular Sludge Reactors. *Water Res.* 75, 292-300.
- Liu, Y., and Liu, Q. S. (2006). Causes and Control of Filamentous Growth in Aerobic Granular Sludge Sequencing Batch Reactors. *Biotechnol Adv.* 24(1), 115-127.
- Liu, Y., and Tay, J. H. (2004). State of The Art of Biogranulation Technology for Wastewater Treatment. *Biotechnol Adv.* 22(7), 533-563.
- Liu, Y. Q., and Tay, J. H. (2015). Fast Formation of Aerobic Granules by Combining Strong Hydraulic Selection Pressure with Overstressed Organic Loading Rate. *Water Res.* 80, 256-266.
- Liu, Y., Wang, Z. W., Qin, L., Liu, Y. Q., and Tay, J. H. (2005). Selection Pressure-Driven Aerobic Granulation in A Sequencing Batch Reactor. *Appl Microbiol Biotechnol.* 67(1), 26-32.
- Liu, Y., Xu, H.L., Show, K.Y. and Tay, J.H (2002). Anaerobic Granulation Technology for Wastewater Treatment: A Review. *World Journal of Microbiology and Biotechnology.* 18, 99–113.
- Liu, Y., Yang, S. F., Liu, Q. S., and Tay, J. H. (2003). The Role of Cell Hydrophobicity in The Formation of Aerobic Granules. *Curr Microbiol.* 46(4), 270-274.
- Liu, Y.Q., Kong, Y., Tay, J.-H., and Zhu, J. (2011). Enhancement of Start-Up of Pilot-Scale Granular SBR Fed With Real Wastewater. *Separation And Purification Technology.* 82, 190-196.
- Liu, Y.-Q., Moy, B., Kong, Y.-H., and Tay, J.-H. (2010). Formation, Physical Characteristics and Microbial Community Structure of Aerobic Granules in A Pilot-Scale Sequencing Batch Reactor For Real Wastewater Treatment. *Enzyme and Microbial Technology.* 46(6), 520-525.

- Lohani, S. P., Chhetri, A., and Khanal, S. N. (2015). A Simple Anaerobic System for Onsite Treatment of Domestic Wastewater. *African Journal of Environmental Science and Technology*. 9(4), 292-300.
- Long, B., Yang, C. Z., Pu, W. H., Yang, J. K., Jiang, G. S., Dan, J. F. and Liu, F. B. (2014). Rapid Cultivation of Aerobic Granular Sludge in A Pilot Scale Sequencing Batch Reactor. *Bioresour Technol*. 166, 57-63.
- Lotito, A. M., De Sanctis, M., Di Iaconi, C., and Bergna, G. (2014). Textile Wastewater Treatment: Aerobic Granular Sludge vs Activated Sludge Systems. *Water Res*. 54, 337-346.
- Lotito, A. M., Di Iaconi, C., Fratino, U., Mancini, A., and Bergna, G. (2011). Sequencing Batch Biofilter Granular Reactor for Textile Wastewater Treatment. *N Biotechnol*. 29(1), 9-16.
- Lotito, A. M., Fratino, U., Bergna, G., and Di Iaconi, C. (2012). Integrated Biological and Ozone Treatment of Printing Textile Wastewater. *Chemical Engineering Journal*. 195-196, 261-269.
- Lourenço, N., Novais, J., and Pinheiro, H. (2006). Kinetic Studies of Reactive Azo Dye Decolorization in Anaerobic/aerobic Sequencing Batch Reactors. *Biotechnol Lett*. 28(10), 733-739.
- Lu, X., Yang, B., Chen, J. and Sun, R. (2009). Treatment Of Wastewater Containing Azo Dye Reactive Brilliant Red X-3B Using Sequential Ozonation and Upflow Biological Aerated Filter Process. *J Hazard Mater*. 161(1), 241-245.
- Lu, X., Zhen, G., Estrada, A. L., Chen, M., Ni, J., Hojo, T. and Li, Y. Y. (2015). Operation Performance and Granule Characterization of Upflow Anaerobic Sludge Blanket (UASB) Reactor Treating Wastewater with Starch as The Sole Carbon Source. *Bioresource technology*. 180, 264-273.
- Luo, J., Zhou, J., Qian, G., and Liu, J. (2014). Effective Anaerobic Biodegradation of Municipal Solid Waste Fresh Leachate Using A Novel Pilot-Scale Reactor: Comparison Under Different Seeding Granular Sludge. *Bioresour Technol*. 165, 152-157.
- Lv, Y., Wan, C., Lee, D. J., Liu, X., and Tay, J. H. (2014). Microbial Communities of Aerobic Granules: Granulation Mechanisms. *Bioresour Technol*. 169, 344-351.

- Ma, D. Y., Wang, X. H., Song, C., and Wang, S. G. (2014). Biodegradation of Congo Red by Aerobic Granules in a Sequencing Batch Reactor. *Advanced Materials Research*. 955-959, 656-662.
- Ma, D. Y., Wang, X. H., Song, C., Wang, S. G., Fan, M. H., and Li, X. M. (2011). Aerobic Granulation for Methylene Blue Biodegradation in a Sequencing Batch Reactor. *Desalination*. 276(1), 233-238.
- Mace, S. and Alvarez, J. M (2002). Utilization of SBR Technology for Wastewater Treatment: An Overview. *Ind. Eng. Chem. Res.* 41, 5539-5553.
- Malaysian Investment Development Authority (MIDA). (2017). *Malaysian Industrial Development Authority*. Retrieved on March 24, 2017 from <http://www.mida.gov.my>
- Manavi, N., Kazemi, A. S., and Bonakdarpour, B. (2017). The Development of Aerobic Granules from Conventional Activated Sludge Under Anaerobic-Aerobic Cycles and Their Adaptation for Treatment of Dyeing Wastewater. *Chemical Engineering Journal*. 312, 375-384.
- Manenti, D. R., Módenes, A. N., Soares, P. A., Espinoza-Quiñones, F. R., Boaventura, R. A. R., Bergamasco, R., and Vilar, V. J. P. (2014). Assessment of A Multistage System Based On Electrocoagulation, Solar Photo-Fenton and Biological Oxidation Processes for Real Textile Wastewater Treatment. *Chemical Engineering Journal*. 252, 120-130.
- Mao, Y., Xia, Y., and Zhang, T. (2013). Characterization of Thauera-Dominated Hydrogen-Oxidizing Autotrophic Denitrifying Microbial Communities by Using High-Throughput Sequencing. *Bioresour Technol.* 128, 703-710.
- Mao, Y., Zhang, X., Xia, X., Zhong, H., and Zhao, L. (2010). Versatile Aromatic Compound-Degrading Capacity and Microdiversity of Thauera Strains Isolated from A Coking Wastewater Treatment Bioreactor. *J Ind Microbiol Biotechnol.* 37(9), 927-934.
- Mata, A. M. T., Pinheiro, H. M., and Lourenço, N. D. (2015). Effect of Sequencing Batch Cycle Strategy on The Treatment of A Simulated Textile Wastewater With Aerobic Granular Sludge. *Biochemical Engineering Journal*. 104, 106-114.
- McMullan, G., Meehan, C., Conneely, A., Kirby, N., Robinson, T., Nigam, P., Banat, I. M., Marchant, R. and Smyth, W. F. (2001). Microbial Decolourization and Degradation of Textile Dyes. *Apply Microbial Biotechnology*. 56, 81-87.

- McSwain, B. S., Irvine, R. L., Hausner, M., and Wilderer, P. A. (2005). Composition and Distribution of Extracellular Polymeric Substances in Aerobic Flocs and Granular Sludge. *Appl Environ Microbiol.* 71(2), 1051-1057.
- Mishima, K. and Nakamura, M. (1991). Self-Immobilization Of Aerobic Activated Sludge- A Pilot Study Of The Aerobic Upflow Sludge Blanket Process In Municipal Sewage Treatment. *Water Science And Technology.* 23, 981– 990.
- Mitra, S., and Gupta, S. K. (2014). Pilot-Scale Treatment of a Trichloethylene Rich Synthetic Wastewater in Anaerobic Hybrid Reactor, with Morphological Study of The Sludge Granules. *Clean Technologies and Environmental Policy.* 16(5), 947-956.
- Mohan, S. V., Rao, N. C., Prasad, K. K and Sarma, P. N (2005). Bioaugmentation of An Anaerobic Sequencing Batch Biofilm Reactor(AnSBBR) with Immobilized Sulphate Reducing Bacteria (SRB) for The Treatment of Sulphate Bearing Chemical Wastewater. *Process Biochemistry.* 40, 2849–2857.
- Monsalvo, V. M., Mohedano, A. F., Casas, J. A. and Rodríguez, J. J. (2009). Cometabolic Biodegradation of 4-Chlorophenol by Sequencing Batch Reactors at Different Temperature. *Bioresour Technol.* 100, 4572–4578.
- Morales, N., Figueroa, M., Fra-Vázquez, A., Val del Río, A., Campos, J. L., Mosquera-Corral, A., and Méndez, R. (2013). Operation of An Aerobic Granular Pilot Scale SBR Plant to Treat Swine Slurry. *Process Biochemistry.* 48(8), 1216-1221.
- Morgenroth, E. and Wilderer, P. A (1998). Sequencing Batch Reactor Technology: Concepts, Design and Experiences. *J, Clwem.* 314-321.
- Moussavi, G., Barikbin, B., and Mahmoudi, M (2010). The Removal of High Concentrations of Phenol from Saline Wastewater Using Aerobic Granular SBR. *Chemical Engineering Journal.* 158, 498–504.
- Moy, B.Y.P., Tay, J.H., Toh, S.K., Liu, Y. and Tay, S.T.L. (2002). High Organic Loading Influences the Physical Characteristics of Aerobic Sludge Granules. *Letters in Applied Microbiology.* 34, 407-412.
- Muda, K. (2010). *Facultative Anaerobic Granular Sludge for Textile Dyeing Wastewater Treatment.* Universiti Teknologi Malaysia. Thesis for degree of Doctor of Philosophy (Civil Engineering)
- Muda, K., Aris, A., Salim, M. R., Ibrahim, Z., van Loosdrecht, M. C., Ahmad, A., and Nawahwi, M. Z. (2011). The Effect of Hydraulic Retention Time on Granular

- Sludge Biomass in Treating Textile Wastewater. *Water Res.* 45(16), 4711-4721.
- Muda, K., Aris, A., Salim, M. R., Ibrahim, Z., Yahya, A., Van Loosdrecht, M. C., Nawahwi, M. Z. (2010). Development of Granular Sludge for Textile Wastewater Treatment. *Water Res.* 44(15), 4341-4350.
- Murali, V., Ong, S. A., Ho, L. N., and Wong, Y. S. (2013). Evaluation of Integrated Anaerobic-Aerobic Biofilm Reactor for Degradation of Azo Dye Methyl Orange. *Bioresour Technol.* 143, 104-111.
- Nawahwi, M.Z. (2009). *Degradation of Reactive Red 195 by Selected Bacteria from Textile Wastewater. Master Thesis*
- Nawaz, M. S. and Khan, S. J (2013). Effect of HRT on SBR Performance for Treatability of Combined Domestic and Textile Wastewaters. *J. Chem.Soc. Pak*, 35(2), 527-532.
- Neifar, M., Chouchane, H., Mahjoubi, M., Jaouani, A., and Cherif, A. (2016). *Pseudomonas Extremorientalis* BU118: A New Salt-Tolerant Laccase-Secreting Bacterium with Biotechnological Potential in Textile Azo Dye Decolourization. *3 Biotech.* 6(1), 107.
- Neoh, C. H., Noor, Z. Z., Mutamim, N. S. A., and Lim, C. K. (2016). Green Technology in Wastewater Treatment Technologies: Integration of Membrane Bioreactor with Various Wastewater Treatment Systems. *Chemical Engineering Journal.* 283, 582-594.
- Ni, S. Q., Gao, B. Y., Wang, C. C., Lin, J. G., and Sung, S. (2011). Fast Start-Up, Performance and Microbial Community in A Pilot-Scale Anammox Reactor Seeded with Exotic Mature Granules. *Bioresour Technol.* 102(3), 2448-2454.
- Ni, S.-Q., Sung, S., Yue, Q.-Y., and Gao, B.-Y. (2012). Substrate Removal Evaluation of Granular Anammox Process in A Pilot-Scale Upflow Anaerobic Sludge Blanket Reactor. *Ecological Engineering*, 38(1), 30-36.
- Nidheesh, P. V., Gandhimathi, R., and Ramesh, S. T. (2013). Degradation of Dyes from Aqueous Solution by Fenton Processes: A Review. *Environ Sci Pollut Res Int.* 20(4), 2099-2132.
- Nigam, P., Banat, I. M., Singh, D., and Marchant, R. (1996). Microbial Process for The Decolorization of Textile Effluent Containing Azo, Diazo and Reactive Dyes. *Process biochemistry.* 31(5), 435-442.

- Nnaji, C. C. (2014). A Review of The Upflow Anaerobic Sludge Blanket Reactor. *Desalination and Water Treatment*. 52(22-24), 4122-4143.
- Nourmoradi, H., Zabihollahi, S., and Pourzamani, H. R. (2015). Removal of A Common Textile Dye, Navy Blue (NB), from Aqueous Solutions by Combined Process of Coagulation–Flocculation followed by Adsorption. *Desalination and Water Treatment*. 57(11), 5200-5211.
- Oehmen, A., Lemos, P. C., Carvalho, G., Yuan, Z., Keller, J., Blackall, L. L. and Reis, M. A. M. (2007). Advances in Enhanced Biological Phosphorus Removal: from Micro to Macro Scale. *Water Research*. 41, 2271-2300.
- Ong, S. L., Hu, J. Y., Ng, W. J., and Lu, Z. R. (2002). Granulation Enhancement in Anaerobic Sequencing Batch Reactor Operation. *Journal of environmental Engineering*. 128(4), 387-390.
- Ong, S.-A., Toorisaka, E., Hirata, M., and Hano, T. (2005). Treatment of Azo Dye Orange II in A Sequential Anaerobic and Aerobic-Sequencing Batch Reactor system. *Environmental Chemistry Letters*. 2(4), 203-207.
- Ong, S.-A., Toorisaka, E., Hirata, M., and Hano, T. (2012). Decolorization of Orange II Using an Anaerobic Sequencing Batch Reactor with and without Co-Substrates. *Journal of Environmental Sciences*. 24(2), 291-296.
- Ong, Y. K., Li, F. Y., Sun, S.-P., Zhao, B.-W., Liang, C.-Z., and Chung, T.-S. (2014). Nanofiltration Hollow Fiber Membranes for Textile Wastewater Treatment: Lab-Scale and Pilot-Scale Studies. *Chemical Engineering Science*. 114, 51-57.
- Pan, S., Tay, J. H., He, Y. X., and Tay, S. T. L. (2004). The Effect of Hydraulic Retention Time on The Stability of Aerobically Grown Microbial Granules. *Letters in Applied Microbiology*. 38(2), 158-163.
- Pandey, A., Singh, P. and Iyengar, L. (2007). Bacterial Decolorization and Degradation of Azo Dyes. *International Biodeterioration and Biodegradation*. 59, 73-84.
- Pang, Y. L., and Abdullah, A. Z. (2013). Current Status of Textile Industry Wastewater Management and Research Progress in Malaysia: A Review. *Clean–Soil, Air, Water*. 41(8), 751-764.
- Panswad, T. and Luangdilok, W. (2000). Decolorization of Reactive Dyes with Different Molecular Structures under Different Environmental Conditions. *Water Research*. 34(17), 4177-4184.

- Parmar, N., and Shukla, S. R. (2015). Microbial Decolorization of Reactive Dye Solutions. *CLEAN - Soil, Air, Water*. 43(10), 1426-1432.
- Pasukphun, N. and Vinitnantharat, S. (2003). Degradation of Organic Substances and Reactive Dye in An Immobilized-Cell Sequencing Batch Reactor Operation on Simulated Textile Wastewater. *Journal of Environmental Science and Health, Part A: Toxic/Hazardous Substances and Environmental Engineering*. 38(10), 2019-2028.
- Patel, A. A. (2010). *Studies on Novel Heterocyclic Compounds and their Microbicidal Efficacy*. Veer Narmad South Gujarat University. Thesis for degree of Doctor of Philosophy (Chemistry).
- Pathak, V. V., Kothari, R., Chopra, A. K., and Singh, D. P. (2015). Experimental and Kinetic Studies For Phycoremediation and Dye Removal by *Chlorella Pyrenoidosa* from Textile Wastewater. *J Environ Manage*. 163, 270-277.
- Pazdzior, K., Klepacz-Smolka, A., Ledakowicz, S., Sojka-Ledakowicz, J., Mrozinska, Z., and Zylla, R. (2009). Integration of Nanofiltration and Biological Degradation of Textile Wastewater Containing Azo Dye. *Chemosphere*. 75(2), 250-255.
- Pearce, C.I., Guthrie, J.T. and Lloyd J.R. (2003). The Removal of Colour from Textile Wastewater Using Whole Cell Bacteria: A Review. *Dyes and Pigments*. 58, 179-196.
- Pereira, L. and Alves, M. (2012). Dyes - Environmental Impact and Remediation. In Malik, A. and Grohmann, E. (Eds.). *Environmental Protection Strategies for Sustainable Development: Strategies for Sustainability*. New York. Springer Science - Buisness Media B.V. 111-162.
- Pereira, R. A., Pereira, M. F. R., Alves, M. M., and Pereira, L. (2014). Carbon Based Materials as Novel Redox Mediators for Dye Wastewater Biodegradation. *Applied Catalysis B: Environmental*. 144, 713-720.
- Pevere, A., Guibaud, G., Goin, E., Van Hullebusch, E., and Lens, P. (2009). Effects of Physico-Chemical Factors on The Viscosity Evolution of Anaerobic Granular Sludge. *Biochemical Engineering Journal*. 43(3), 231-238.
- Peyong, Y. N., Zhou, Y., Abdullah, A. Z., and Vadivelu, V. (2012). The Effect of Organic Loading Rates and Nitrogenous Compounds on The Aerobic Granules Developed Using Low Strength Wastewater. *Biochemical Engineering Journal*. 67, 52-59.



- Pham, T. H., Rabaey, K., Aelterman, P., Clauwaert, P., De Schampelaire, L., Boon, N., and Verstraete, W. (2006). Microbial Fuel Cells in Relation to Conventional Anaerobic Digestion Technology. *Engineering in Life Sciences*. 6(3), 285-292.
- Phugare, S. S., Kalyani, D. C., Surwase, S. N., and Jadhav, J. P. (2011). Ecofriendly Degradation, Decolorization and Detoxification of Textile Effluent by A Developed Bacterial Consortium. *Ecotoxicology and environmental safety*. 74(5), 1288-1296.
- Pielesz, A. (1999). The Process of The Reduction of Azo Dyes Used in Dyeing Textiles on The Basis of Infrared Spectroscopy Analysis. *Journal of molecular structure*. 511, 337-344.
- Pijuan, M., Werner, U., and Yuan, Z. (2011). Reducing the Startup Time of Aerobic Granular Sludge Reactors Through Seeding Floccular Sludge with Crushed Aerobic Granules. *Water Res.* 45(16), 5075-5083.
- Pilatin, S., and Kunduhoğlu, B. (2011). Decolorization of Textile Dyes by Newly Isolated *Trametes Versicolor* Strain. *Anadolu University Journal of Science and Technology–C Life Sciences and Biotechnology*. 1(2), 125.
- Ponraj, M., Gokila, K., and Zambare, V. (2011). Bacterial Decolorization of Textile Dye-Orange 3R. *International Journal of Advanced Biotechnology and Research*. 2(1), 168-177.
- Pronk, M., de Kreuk, M. K., de Bruin, B., Kamminga, P., Kleerebezem, R., and van Loosdrecht, M. C. (2015). Full Scale Performance of The Aerobic Granular Sludge Process for Sewage Treatment. *Water Res.* 84, 207-217.
- Puchana-Rosero, M. J., Lima, E. C., Ortiz-Monsalve, S., Mella, B., da Costa, D., Poll, E., and Gutterres, M. (2017). Fungal Biomass as Biosorbent for The Removal of Acid Blue 161 Dye in Aqueous Solution. *Environmental Science and Pollution Research*. 24(4), 4200-4209.
- Pushkar, P., and Mungray, A. K. (2016). Real Textile and Domestic Wastewater Treatment by Novel Cross-Linked Microbial Fuel Cell (CMFC) Reactor. *Desalination and Water Treatment*. 57(15), 6747-6760.
- Puvaneswari, N., Muthukrishnan, J., and Gunasekaran, P. (2006). Toxicity Assessment and Microbial Degradation of Azo Dyes. *Indian Journal of Experimental Biology*. 44, 618-626.

- Qin, L., Liu, Y., and Tay, J.-H. (2004b). Effect of Settling Time on Aerobic Granulation in Sequencing Batch Reactor. *Biochemical Engineering Journal*. 21(1), 47-52.
- Qin, L., Tay, J.-H., and Liu, Y. (2004a). Selection Pressure Is a Driving Force of Aerobic Granulation in Sequencing Batch Reactors. *Process Biochemistry*. 39(5), 579-584.
- Raikar, R. V., Patil, R., and Virupakshi, A. (2015). Degradation of Phenol Using Sequential Batch Reactor. *Int J Res Engineering Technol*. 4, 542-6.
- Rajaguru P., Kalaiselvi K., Palanivel M., and Subburam V (2000). Biodegradation of Azo Dyes in Sequential Anaerobic-aerobic System. *Appl Microbiol Biotechnol*. 54, 268-273.
- Rajee, O., and Patterson, J. (2011). Decolorization of Azo Dye (Orange MR) by An Autochthonous Bacterium, *Micrococcus* sp. DBS 2. *Indian journal of microbiology*. 51(2), 159-163.
- Ramakrishnan, A. and Gupta, S. K. (2006). Anaerobic Biogranulation In a Hybrid Reactor Treating Phenolic Waste. *Journal of Hazardous Materials*. B137, 1488–1495.
- Ramírez, C., Saldaña, A., Hernández, B., Acero, R., Guerra, R., Garcia-Segura, S. and Peralta-Hernández, J. M. (2013). Electrochemical Oxidation of Methyl Orange Azo Dye at Pilot Flow Plant Using BDD Technology. *Journal of Industrial and Engineering Chemistry*. 19(2), 571-579.
- Ren X. (2000). Development Of Environmental Performance Indicators for Textile Process and Product. *Journal of Cleaner Production*. 8, 473–481.
- Ren, T.T., Liu, L., Sheng, G.P., Liu, X.W., Yu, H.Q, Zhang, M.C. and Zhu, J.R. (2008). Calcium Spatial Distribution in Aerobic Granules and Its Effects on Granule Structure, Strength and Bioactivity. *Water Research*. 42, 3343-52.
- Renault, F., Sancey, B., Badot, P. M., and Crini, G. (2009). Chitosan for Coagulation/Flocculation Processes – An Eco-Friendly Approach. *European Polymer Journal*. 45(5), 1337-1348.
- Rezasoltani, S., Shayegan, J., and Jalali, S. (2015). Effect of pH on Aerobic Granulation and Treatment Performance in Sequencing Batch Reactors. *Chemical Engineering and Technology*. 38(5), 851-858.
- Rieger, P. G., Meier, H. M., Gerle, M., Vogt, U., Groth, T., and Knackmuss, H. J. (2002). Xenobiotics in The Environment: Present and Future Strategies to

- Obviate the Problem of Biological Persistence. *Journal of Biotechnology*. 94(1), 101-123.
- Rizvi, H., Ahmad, N., Abbas, F., Bukhari, I. H., Yasar, A., Ali, S., . . . Riaz, M. (2015). Start-Up of UASB Reactors Treating Municipal Wastewater and Effect of Temperature/Sludge Age And Hydraulic Retention Time (HRT) on Its Performance. *Arabian Journal of Chemistry*. 8(6), 780-786.
- Robinson, T., McMullan, G., Marchant, R. and Nigam, P. (2001). Remediation of Dyes in Textile Effluent: A Critical Review on Current Treatment Technologies with A Proposed Alternative. *Bioresource Technology*. 77, 247-255.
- Rocktäschel, T., Klarmann, C., Ochoa, J., Boisson, P., Sørensen, K., and Horn, H. (2015). Influence of the Granulation Grade on the Concentration of Suspended Solids in the Effluent of A Pilot Scale Sequencing Batch Reactor Operated with Aerobic Granular Sludge. *Separation and Purification Technology*. 142, 234-241.
- Rodrigues, C. S. D., Madeira, L. M., and Boaventura, R. A. R. (2014). Synthetic Textile Dyeing Wastewater Treatment by Integration of Advanced Oxidation and Biological Processes – Performance Analysis with Costs Reduction. *Journal of Environmental Chemical Engineering*. 2(2), 1027-1039.
- Rogosa, M. (1969). *Acidaminococcus* Gen. N., *Acidaminococcus Fermentans* Sp. N., Anaerobic Gram-Negative Diplococci Using Amino Acids as The Sole Energy Source for Growth. *Journal of Bacteriology*. 98(2), 756-766.
- Rosman, N. H., Nor Anuar, A., Chelliapan, S., Md Din, M. F., and Ujang, Z. (2014). Characteristics and Performance of Aerobic Granular Sludge Treating Rubber Wastewater at Different Hydraulic Retention Time. *Bioresour Technol*. 161, 155-161.
- Rossetti, S., Tomei, M. C., Nielsen, P. H. and Tandoi, V. (2005). *Microthrix Parvicella*, Lamentous Bacterium Causing Bulking and Foaming in Activated Sludge Systems: A Review of Current Knowledge. *FEMS Microbiol Rev*. 29, 49 –64.
- Saba, B., Khalid, A., Nazir, A., Kanwal, H., and Mahmood, T. (2013). Reactive Black-5 Azo Dye Treatment in Suspended and Attach Growth Sequencing Batch Bioreactor Using Different Co-Substrates. *International Biodeterioration and Biodegradation*. 85, 556-562.

- Sachan, K., and Kapoor, V. P. (2007). Optimization of Extraction and Dyeing Conditions for Traditional Turmeric Dye. *Indian Journal of Traditional Knowledge*. 6(2), 270-278.
- Sadeghi-Kiakhani, M., Arami, M., and Gharanjig, K. (2013). Dye removal from Colored-Textile Wastewater using Chitosan-PPI Dendrimer Hybrid as a Biopolymer: Optimization, Kinetic, and Isotherm Studies. *Journal of Applied Polymer Science*. 127(4), 2607-2619.
- Sahu, O., Mazumdar, B., and Chaudhari, P. K. (2014). Treatment of Wastewater by Electrocoagulation: A Review. *Environ Sci Pollut Res Int*. 21(4), 2397-2413.
- Saleh, M. M. A., and Mahmood, U. F (2004). Anaerobic Digestion Technology for Industrial Wastewater Treatment. *Eighth International Water Technology Conference, Iwtc8, Alexandria, Egypt*. 817-833.
- Samanta, A. K., and Agarwal, P. (2009). Application of Natural Dyes on Textiles. *Indian Journal of Fibre and Textile Research*. 34, 384-399.
- Santana, R. S. d. S., Pretti, A. A., Moreno, J. G., Dacanal, G. C., Tommaso, G., and Ribeiro, R. (2016). Effect of Biomass Configuration on The Behavior of Pilot-Scale Anaerobic Batch Reactors Treating Dairy Wastewater. *International Biodeterioration and Biodegradation*. 106, 80-87.
- Santos, S. C. and Boaventura, R. A. (2015). Treatment of a Simulated Textile Wastewater in a Sequencing Batch Reactor (SBR) with Addition of a Low-Cost Adsorbent. *J Hazard Mater*. 291, 74-82.
- Saratale, R. G., Gandhi, S. S., Purankar, M. V., Kurade, M. B., Govindwar, S. P., Oh, S. E., and Saratale, G. D. (2013). Decolorization and Detoxification of Sulfonated Azo Dye C.I. Remazol Red and Textile Effluent by Isolated *Lysinibacillus* Sp. RGS. *J Biosci Bioeng*. 115(6), 658-667.
- Saratale, R. G., Saratale, G. D., Chang, J. S., and Govindwar, S. P. (2010). Decolorization and Biodegradation of Reactive Dyes and Dye Wastewater by A Developed Bacterial Consortium. *Biodegradation*. 21(6), 999-1015.
- Saratale, R. G., Saratale, G. D., Chang, J. S., and Govindwara, S. P. (2011). Bacterial Decolorization and Degradation of Azo Dyes: A Review. *Journal of the Taiwan Institute of Chemical Engineers*. 42, 138-157.
- Sarayu, K., and Sandhya, S. (2012). Current Technologies for Biological Treatment of Textile Wastewater--A Review. *Appl Biochem Biotechnol*. 167(3), 645-661.

- Sarfaraz, S., Thomas, S., Tewari, U. K and Iyengar, L (2004). Anoxic Treatment of Phenolic Wastewater in Sequencing Batch Reactor. *Wat Res.* 38, 965–971.
- Sarma, S. J., Tay, J. H., and Chu, A. (2017). Finding Knowledge Gaps in Aerobic Granulation Technology. *Trends Biotechnol.* 35(1), 66-78.
- Sarti, A., Silva, A. J., Zaiat, M and Foresti, E. (2009). The Treatment of Sulfate-Rich Wastewater Using an Anaerobic Sequencing Batch Biofilm Pilot-Scale Reactor. *Desalination.* 249, 241–246.
- Sathian, S., Rajasimman, M., Radha, G., Shanmugapriya, V., and Karthikeyan, C. (2014a). Performance of SBR for The Treatment of Textile Dye Wastewater: Optimization and Kinetic Studies. *Alexandria Engineering Journal.* 53(2), 417-426.
- Sathian, S., Rajasimman, M., Rathnasabapathy, C. S., and Karthikeyan, C. (2014b). Performance Evaluation of SBR for The Treatment of Dyeing Wastewater by Simultaneous Biological and Adsorption Processes. *Journal of Water Process Engineering.* 4, 82-90.
- Saxena, S., and Raja, A. S. M. (2014). Natural Dyes: Sources, Chemistry, Application and Sustainability Issues. In *Roadmap to sustainable textiles and clothing.* Springer Singapore.37-80.
- Sayahi, E., Ladhari, N., Mechichi, T., and Sakli, F. (2016). Azo Dyes Decolourization by The Laccase from *Trametes Troglitii*. *The Journal of The Textile Institute.* 1-5.
- Schleinitz, K. M., Schmeling, S., Jehmlich, N., von Bergen, M., Harms, H., Kleinstaub, S. and Fuchs, G. (2009). Phenol Degradation in The Strictly Anaerobic Iron-Reducing Bacterium *Geobacter Metallireducens* GS-15. *Appl Environ Microbiol.* 75(12), 3912-3919.
- Schmidt, J. E and Ahring, B. K. (1994). Extracellular Polymers in Granular Sludge From Different Upflow Anaerobic Sludge Blanket (UASB) Reactors. *Appl. Microbiol Biotechnol.* 42, 457-462.
- Schwarzenbeck, N., Borges, J.M. and Wilderer, P.A. (2005). Treatment of Dairy Effluents in an Aerobic Granular Sludge Sequencing Batch Reactor. *Appl. Microbiol. Biotechnol.* 66, 711–718.
- Segneanu, A. E., Gozescu, I., Dabici, A., Sfirloaga, P., and Szabadai, Z. (2012). Organic Compounds FT-IR Spectroscopy. In *Macro To Nano Spectroscopy.* InTech.

- Sen, S. K., Raut, S., Bandyopadhyay, P., and Raut, S. (2016). Fungal Decolouration and Degradation of Azo Dyes: A Review. *Fungal Biology Reviews*. 30(3), 112-133.
- Senthilkumar, M., Gnanapragasam, G., Arutchelvan, V., and Nagarajan, S. (2011). Treatment of Textile Dyeing Wastewater Using Two-Phase Pilot Plant UASB Reactor with Sago Wastewater as Co-Substrate. *Chemical Engineering Journal*. 166(1), 10-14.
- Shah, M. P. (2014). Microbial Degradation and Decolorization of Acid Orange Dye by Anaerobic/Aerobic Sequential Process. *International Journal of Environmental Bioremediation and Biodegradation*. 2(3), 112-116.
- Shen, C.F and Guiot, S.R (1996). Long-Term Impact of Dissolved O<sub>2</sub> on the Activity of Anaerobic Granules. *Biotechnology and Bioengineering*. 49, 611-620.
- Sheng, G. P., Yu, H. Q., and Li, X. Y. (2010b). Extracellular Polymeric Substances (EPS) of Microbial Aggregates in Biological Wastewater Treatment Systems: A Review. *Biotechnol Adv*. 28(6), 882-894.
- Sheng, G.-p., Li, A.-j., Li, X.-y., and Yu, H.-q. (2010a). Effects of Seed Sludge Properties and Selective Biomass Discharge on Aerobic Sludge Granulation. *Chemical Engineering Journal*. 160(1), 108-114.
- Shivayogimath, C. B and Ramanujam, T. K. (1999). Treatment of Distillery Spentwash by Hybrid UASB Reactor. *Bioprocess Engineering*. 21, 255-259.
- Silva, S. D. Q., Silva, D. C., Lanna, M. C. D. S., Baeta, B. E. L., and Aquino, S. F. D. (2014). Microbial Dynamics During Azo Dye Degradation in A UASB Reactor Supplied with Yeast Extract. *Brazilian Journal of Microbiology*. 45(4), 1153-1160.
- Singh , K., and Arora, S. (2011). Removal of Synthetic Textile Dyes From Wastewaters: A Critical Review on Present Treatment Technologies. *Critical Reviews in Environmental Science and Technology*. 41(9), 807-878.
- Singh, M., and Srivastava, R. K. (2011). Sequencing Batch Reactor Technology for Biological Wastewater Treatment: A Review. *Asia-Pacific Journal of Chemical Engineering*. 6(1), 3-13
- Singh, S. V., and Purohit, M. C. (2012). Applications of Eco-Friendly Natural Dye on Wool Fibers Using Combination of Natural and Chemical Mordants. *Universal Journal of Environmental Research and Technology*. 2(2).

- Sirianuntapiboon, S., and Chairattanawan, K. (2012). Effects of Some Operating Parameters on The Efficiency of A Sequencing Batch Reactor System for Treatment of Textile Wastewater Containing Acid Dyes. *Desalination and Water Treatment*. 50(1-3), 206-219.
- Sirianuntapiboon, S., and Sansak, J. (2008). Treatability Studies with Granular Activated Carbon (GAC) and Sequencing Batch Reactor (SBR) System for Textile Wastewater Containing Direct Dyes. *J Hazard Mater*. 159(2-3), 404-411.
- Sivakumar, D., Gayathri, G., Nishanthi, R., Vijayabharathi, V., Sudeshna, D., and Kavitha, R. (2014). Role of Fungi Species in Colour Removal from Textile Industry Wastewater. *International Journal of ChemTech Research*. 6(9), 4366-4372.
- Slokar, Y.M and Le Marechal, A.M (1998). Methods of Decoloration of Textile Wastewaters. *Dyes and Pigments*. 37(4), 335-356.
- Soares, P. A., Silva, T. F., Manenti, D. R., Souza, S. M., Boaventura, R. A., and Vilar, V. J. (2014). Insights into Real Cotton-Textile Dyeing Wastewater Treatment Using Solar Advanced Oxidation Processes. *Environ Sci Pollut Res Int*. 21(2), 932-945.
- Soares, P. A., Souza, R., Soler, J., Silva, T. F. C. V., Souza, S. M. A. G. U., Boaventura, R. A. R., and Vilar, V. J. P. (2017). Remediation of A Synthetic Textile Wastewater from Polyester-Cotton Dyeing Combining Biological and Photochemical Oxidation Processes. *Separation and Purification Technology*. 172, 450-462.
- Sobeck, D.C. and Higgins, M.J. (2002). Examination of Three Theories for Mechanisms of Cation-Induced Bioflocculation. *Water Research*. 36, 527-538.
- Solís, M., Solís, A., Pérez, H. I., Manjarrez, N., and Flores, M. (2012). Microbial Decolouration of Azo Dyes: A Review. *Process Biochemistry*. 47(12), 1723-1748.
- Somasiri, W., Li, X. F., Ruan, W. Q., and Jian, C. (2008). Evaluation of The Efficacy of Upflow Anaerobic Sludge Blanket Reactor in Removal of Colour and Reduction of COD In Real Textile Wastewater. *Bioresour Technol*. 99(9), 3692-3699.

- Song, Z., Pan, Y., Zhang, K., Ren, N., and Wang, A. (2010). Effect of Seed Sludge on Characteristics and Microbial Community of Aerobic Granular Sludge. *Journal of Environmental Sciences*. 22(9), 1312-1318.
- Song, Z., Ren, N., Zhang, K., and Tong, L. (2009). Influence of Temperature on The Characteristics of Aerobic Granulation in Sequencing Batch Airlift Reactors. *Journal of Environmental Sciences*. 21(3), 273-278.
- Spagni, A. and Marsili-Libelli, S (2009). Nitrogen Removal Via Nitrite in A Sequencing Batch Reactor Treating Sanitary Landfill Leachate. *Bioresour Technol*. 100, 609–614.
- Spagni, A., Casu, S., and Grilli, S. (2012). Decolourisation of Textile Wastewater in A Submerged Anaerobic Membrane Bioreactor. *Bioresource technology*. 117, 180-185.
- Spagni, A., Grilli, S., Casu, S., and Mattioli, D. (2010). Treatment of A Simulated Textile Wastewater Containing The Azo-Dye Reactive Orange 16 in An Anaerobic-Biofilm Anoxiceaerobic Membrane Bioreactor. *International Biodeterioration and Biodegradation*. 64, 676-681.
- Sponza, D. T. (2002). Extracellular Polymer Substances and Physicochemical Properties of Floccs in Steady and Unsteady-State Activated Sludge Systems. *Process Biochemistry*. 37(9), 983-998.
- Sponza, D.T. and Işık, M. (2005). Reactor Performances and Fate of Aromatic Amines through Decolorization of Direct Black 38 Dye under Anaerobic/Aerobic Sequential. *Process Biochemistry*. 40(1), 35-44.
- Srinivasan, A., and Viraraghavan, T. (2010). Decolorization of Dye Wastewaters by Biosorbents: A Review. *J Environ Manage*. 91(10), 1915-1929.
- Sriram, N., and Reetha, D. (2015). Isolation and Characterization of Dye Degrading Bacteria from Textile Dye Effluents. *Central European Journal of Experimental Biology*. 4(2), 5-10.
- Starling, M., Castro, L. A. S., Marcelino, R. B. P., Leao, M. M. D., and Amorim, C. C. (2017). Optimized Treatment Conditions for Textile Wastewater Reuse Using Photocatalytic Processes Under UV and Visible Light Sources. *Environ Sci Pollut Res Int*. 24(7), 6222-6232.
- Subramani, S. E., and Thinakaran, N. (2017). Isotherm, Kinetic and Thermodynamic Studies on the Adsorption Behaviour of Textile Dyes onto Chitosan. *Process Safety and Environmental Protection*. 106, 1-10.



- Subramanyam, R., and Mishra, I. M. (2013). Characteristics of Methanogenic Granules Grown on Glucose in An Upflow Anaerobic Sludge Blanket Reactor. *Biosystems engineering*. 114(2), 113-123.
- Sudha, M., Saranya, A., Selvakumar, G., and Sivakumar, N. (2014). Microbial Degradation of Azo Dyes: A Review. *Int.J.Curr.Microbiol.App.Sci*. 3(2), 670-690.
- Sun, F.-y., Yang, C.-y., Li, J.-y., and Yang, Y.-j. (2006). Influence of Different Substrates on The Formation and Characteristics of Aerobic Granules in Sequencing Batch Reactors. *Journal of Environmental Sciences*. 18(5), 864-871.
- Sun, J., Li, W., Li, Y., Hu, Y., and Zhang, Y. (2013). Redox Mediator Enhanced Simultaneous Decolorization of Azo Dye and Bioelectricity Generation in Air-Cathode Microbial Fuel Cell. *Bioresource technology*. 142, 407-414.
- Syed, M. A., Sim, H. K., Khalid, A., and Shukor, M. Y. (2009). A Simple Method to Screen for Azo-Dye-Degrading Bacteria. *J. Environ. Biol*. 30(1), 89-92.
- Szabo, E., Liebana, R., Hermansson, M., Modin, O., Persson, F., and Wilen, B. M. (2017). Microbial Population Dynamics and Ecosystem Functions of Anoxic/Aerobic Granular Sludge in Sequencing Batch Reactors Operated at Different Organic Loading Rates. *Front Microbiol*. 8, 770.
- Tafesse, T.B., Yetemegne, A. K. and Kumar, S. (2015). The Physico-Chemical Studies of Wastewater in Hawassa Textile Industry. *J Environ Anal Chem*. 2, 153.
- Taheri, E., Khiadani Hajian, M. H., Amin, M. M., Nikaeen, M., and Hassanzadeh, A. (2012). Treatment of Saline Wastewater by A Sequencing Batch Reactor with Emphasis on Aerobic Granule Formation. *Bioresour Technol*. 111, 21-26.
- Talouizte, H., Merzouki, M., and Benlemlih, M. (2013). Treatment of Real Textile Wastewater Using SBR Technology: Effect of Sludge Age and Operational Parameters. *Journal of Biotechnology Letters*. 4(2), 79.
- Tang X.Y. (2014). The Impact of Asian Investment on Africa'a Textile Industries. *Carnegie-Tsinghua Center for Global Policy*, accessed on March 24, 2017. [http://carnegieendowment.org/files/china\\_textile\\_investment.pdf](http://carnegieendowment.org/files/china_textile_investment.pdf)
- Tang, C. J., Zheng, P., Zhang, L., Chen, J. W., Mahmood, Q., Chen, X. G., Yu, Y. (2010). Enrichment Features of Anammox Consortia from Methanogenic Granules Loaded with High Organic and Methanol Contents. *Chemosphere*. 79(6), 613-619.

- Tanksali, A. S. (2013). Treatment of Sugar Industry Wastewater by Upflow Anaerobic Sludge Blanket Reactor. *IPACT-2013[14th – 15th March 2013] National Conference on Industrial Pollution and Control Technology-2013 International Journal of Chemtech Research CODEN (USA)*. 5(3), 1246-1253 April-June 2013.
- Tay, J.H and Yan, Y.G (1997). Anaerobic Biogranulation as Microbial Response to Substrate Adequacy. *J. Environ. Eng.* 123, 1002-1010.
- Tay, J.H., Liu, Q.S. and Liu, Y. (2001a). The Effects of Shear Force on the Formation, Structure and Metabolism of Aerobic Granules. *Appl. Microbiol. Biotechnol.* 57, 227-233.
- Tay, J.H., Liu, Q.S. and Liu, Y. (2001b). The Role of Cellular Polysaccharides in the Formation and Stability of Aerobic Granules. *Lett. Appl. Microbiol.* 33, 222–226.
- Tay, J.H., Liu, Q.S. and Liu, Y. (2001c). Microscopic Observation of Aerobic Granulation in Sequential Aerobic Sludge Reactor. *Journal of Applied Microbiology.* 91, 168-175.
- Tay, J.H., Pan, S., He, Y. and Tay, S.T.L. (2004). Effect of Organic Loading Rate on Aerobic Granulation. I: Reactor Performance. *Journal of Environmental Engineering.* 1094-1101.
- Tay, J.H., Tay, S.T.L., Ivanov, V., Pan, S. and Liu, Q.S. (2003). Biomass and Porosity Profile in Microbial Granules used for Aerobic Wastewater Treatment. *Lett. Appl. Microbiol.* 36, 297-301.
- Tay, S. T. L., Zhuang, W. Q., and Tay, J. H. (2005b). Start-Up, Microbial Community Analysis and Formation of Aerobic Granules in A Tert-Butyl Alcohol Degrading Sequencing Batch Reactor. *Environmental science and technology.* 39(15), 5774-5780.
- Tay, S. T., Moy, B. Y., Maszenan, A. M., and Tay, J. H. (2005a). Comparing Activated Sludge and Aerobic Granules as Microbial Inocula for Phenol Biodegradation. *Appl Microbiol Biotechnol.* 67(5), 708-713.
- Teo, K., Xu, H., and Tay, J. (2000). Molecular Mechanism of Granulation. II: Proton Translocating Activity. *J. Environ. Eng.* 126(5), 411–418.
- Thanh, B. X., Visvanathan, C., and Aim, R. B. (2009). Characterization of Aerobic Granular Sludge at Various Organic Loading Rates. *Process Biochemistry.* 44(2), 242-245.

- Toh, S. K., Tay, J. H., Moy, B. Y., Ivanov, V., and Tay, S. T. (2003). Size-Effect on The Physical Characteristics of The Aerobic Granule in A SBR. *Appl Microbiol Biotechnol.* 60(6), 687-695.
- Toloti, A. A. and Mehrdadi, N. (2011). Wastewater Treatment from Antibiotics Plant (UASB Reactor). *Int. J. Environ. Res.* 5(1), 241-246.
- Tomei, M. C., Annesini, M. C., Luberti, R., Centob, G., and Senia, A. (2003). Kinetics of 4-Nitrophenol Biodegradation in A Sequencing Batch Reactor. *Wat Res.* 37: 3803–3814.
- Tomei, M. C., Pascual, J. S., and Angelucci, D. M. (2016). Analysing Performance of Real Textile Wastewater Bio-Decolourization under Different Reaction Environments. *Journal of Cleaner Production.* 129, 468-477.
- Tony, B. D., Goyal, D., and Khanna, S. (2009). Decolorization of Direct Red 28 by Mixed Bacterial Culture in An Up-Flow Immobilized Bioreactor. *J Ind Microbiol Biotechnol.* 36(7), 955-960.
- Tran, N. H., Ngo, H. H., Uruse, T., and Gin, K. Y. (2015). A Critical Review on Characterization Strategies of Organic Matter for Wastewater and Water Treatment Processes. *Bioresour Technol.* 193, 523-533.
- Trevor H.W.(2001). *Biological Treatment Of A Synthetic Dye Water And An Industrial Textile Wastewater Containing Azo Dye Compounds.* The Charles E.Via.Jr.Department of Civil and Environmental Engineering, Virginia Polytechnic Institute and State University, Thesis of Master of Science in Environmental Engineering.
- Tsuneda, S., Ejiri, Y., Nagano, T. and Hirata, A. (2004). Formation Mechanism of Nitrifying Granules Observed in an Aerobic Upflow Fluidized Bed (AUFB) Reactor. *Water Science and Technology.* 49 (11–12), 27-34.
- Tyrone, L.V. (1994). *Textile Processing and Properties* (1<sup>st</sup> ed) Netherlands. Elsevier Science B.V.
- van den Brand, T. P., Roest, K., Chen, G. H., Brdjanovic, D., and van Loosdrecht, M. C. (2015). Occurrence and Activity of Sulphate Reducing Bacteria in Aerobic Activated Sludge Systems. *World J Microbiol Biotechnol.* 31(3), 507-516.
- van der Zee, F. P., Lettinga, G., and Field, J. A. (2001). Azo Dye Decolourisation by Anaerobic Granular Sludge. *Chemosphere.* 44(5), 1169-1176.
- van Lier, J. B., van der Zee, F. P., Frijters, C. T. M. J., and Ersahin, M. E. (2015). Celebrating 40 Years Anaerobic Sludge Bed Reactors for Industrial

- Wastewater Treatment. *Reviews in Environmental Science and Bio/Technology*. 14(4), 681-702.
- Verawaty, M., Pijuan, M., Yuan, Z., and Bond, P. L. (2012). Determining the Mechanisms for Aerobic Granulation from Mixed Seed of Floccular and Crushed Granules in Activated Sludge Wastewater Treatment. *Water Res.* 46(3), 761-771.
- Verma, A. K., Bhunia, P., Dash, R. R., Tyagi, R. D., Surampalli, R. Y., and Zhang, T. C. (2015). Effects of Physico-Chemical Pre-Treatment on The Performance of An Upflow Anaerobic Sludge Blanket (UASB) Reactor Treating Textile Wastewater: Application of Full Factorial Central Composite Design. *The Canadian Journal of Chemical Engineering*. 93(5), 808-818.
- Verma, A. K., Dash, R. R., and Bhunia, P. (2012). A Review on Chemical Coagulation/Flocculation Technologies for Removal of Colour from Textile Wastewaters. *Journal of environmental management*. 93(1), 154-168.
- Verma, A. K., Nath, D., Bhunia, P., and Dash, R. R. (2016). Application of Ultrasonication and Hybrid Bioreactor for Treatment of Synthetic Textile Wastewater. *Journal of Hazardous, Toxic, and Radioactive Waste*. 21(2), 04016018.
- Vickerstaff, T. (1954). *The Physical Chemistry of Dyeing* (2<sup>nd</sup> ed) London. Oliver and Boyd.
- Vijayalakshmi, S. R., and Muthukumar, K. (2015). Improved Biodegradation of Textile Dye Effluent by Coculture. *Ecotoxicology and Environmental Safety*. 114, 23-30.
- Vijayaraghavan, K., and Yun, Y. S. (2008). Bacterial Biosorbents and Biosorption. *Biotechnol Adv.* 26(3), 266-291.
- Wan, C., Lee, D. J., Yang, X., Wang, Y., Wang, X., and Liu, X. (2015). Calcium precipitate induced aerobic granulation. *Bioresour Technol.* 176, 32-37.
- Wan, C., Yang, X., Lee, D. J., Wang, X. Y., Yang, Q., and Pan, X. (2014). Aerobic granulation of aggregating consortium X9 isolated from aerobic granules and role of cyclic di-GMP. *Bioresour Technol.* 152, 557-561.
- Wang, Z. W., Liu, Y., and Tay, J. H. (2006b). The Role of SBR Mixed Liquor Volume Exchange Ratio in Aerobic Granulation. *Chemosphere*. 62(5), 767-771.
- Wang, Z., Huang, K., Xue, M., and Liu, Z. (2011). Textile Dyeing Wastewater Treatment). *INTECH Open Access Publisher*. 91-116.

- Wang, Z., Liu, L., Yao, J., and Cai, W. (2006a). Effects of Extracellular Polymeric Substances on Aerobic Granulation in Sequencing Batch Reactors. *Chemosphere*. 63(10), 1728-1735.
- Wang, C., Xue, Z. X., Cao, J. S. and Fang, F. (2012). Influence of Hydrodynamic Shear Force on Kinetics Characteristic of Anammox Granular Sludge. *Journal of Food, Agriculture and Environment*. 10 (2), 1012-1016.
- Weber, S. D., Ludwig, W., Schleifer, K. H., and Fried, J. (2007). Microbial Composition and Structure of Aerobic Granular Sewage Biofilms. *Appl Environ Microbiol*. 73(19), 6233-6240.
- Wei, D., Qiao, Z., Zhang, Y., Hao, L., Si, W., Du, B., and Wei, Q. (2013). Effect of COD/N Ratio on Cultivation of Aerobic Granular Sludge in A Pilot-Scale Sequencing Batch Reactor. *Appl Microbiol Biotechnol*. 97(4), 1745-1753.
- Wei, D., Si, W., Zhang, Y., Qiao, Z., Yao, Z., Zhao, W. and Du, B. (2012). Aerobic Granulation and Nitrogen Removal with The Effluent of Internal Circulation Reactor in Start-Up of a Pilot-Scale Sequencing Batch Reactor. *Bioprocess Biosyst Eng*. 35(9), 1489-1496.
- Wijetunga, S., Li, X. F., and Jian, C. (2010). Effect of Organic Load on Decolourization of Textile Wastewater Containing Acid Dyes in Upflow Anaerobic Sludge Blanket Reactor. *J Hazard Mater*. 177(1-3), 792-798.
- Winkler, M. K., Kleerebezem, R., de Bruin, L. M., Verheijen, P. J., Abbas, B., Habermacher, J., and van Loosdrecht, M. C. (2013). Microbial Diversity Differences within Aerobic Granular Sludge and Activated Sludge Flocs. *Appl Microbiol Biotechnol*. 97(16), 7447-7458.
- Wirtz, R.A. and Dague, R.R. (1996). Enhancement of Granulation and Start-Up in Anaerobic Sequencing Batch Reactor. *Water Environmental Research*. 68, 883-892
- Wu, J., Zhou, H. M., Li, H. Z., Zhang, P. C., and Jiang, J. (2009). Impacts of Hydrodynamic Shear Force on Nucleation of Flocculent Sludge in Anaerobic Reactor. *Water Res*. 43(12), 3029-3036.
- Wu, Y., Wang, C., Liu, X., Ma, H., Wu, J., Zuo, J., and Wang, K. (2016). A New Method of Two-Phase Anaerobic Digestion for Fruit and Vegetable Waste Treatment. *Bioresour Technol*. 211, 16-23.

- Wuertz S., Okabe S. and Hausner M (2004). Microbial Communities and Their Interactions in Biofilm Systems: An Overview. *Water Science and Technology*. 49(11–12), 327– 336.
- Xu, H., He, P., Wang, G., and Shao, L. (2011). Effects of Activated Sludge Flocs and Pellets Seeds on Aerobic Granule Properties. *Journal of Environmental Sciences*. 23(4), 537-544.
- Yagub, M. T., Sen, T. K., Afroze, S., and Ang, H. M. (2014). Dye and Its Removal from Aqueous Solution by Adsorption: A Review. *Adv Colloid Interface Sci*. 209, 172-184.
- Yan, Y. G. and Tay, J. H (1997). Characterisation of The Granulation Process During UASB Start-Up. *Wat. Res.* 31(7), 1573-158.
- Yang, S.-F., Tay, J.-H., and Liu, Y. (2003). A Novel Granular Sludge Sequencing Batch Reactor for Removal of Organic and Nitrogen from Wastewater. *J Biotechnol*. 106(1), 77-86.
- Yang, S. F., Liu, Q. S., Tay, J. H., and Liu, Y. (2004). Growth Kinetics of Aerobic Granules Developed in Sequencing Batch Reactors. *Letters in Applied Microbiology*. 38(2), 106-112.
- Yang, Y. C., Liu, X., Wan, C., Sun, S., and Lee, D. J. (2014). Accelerated Aerobic Granulation using Alternating Feed Loadings: Alginate-Like Exopolysaccharides. *Bioresour Technol*. 171, 360-366.
- Yasar, A., and Tabinda, A. B. (2010). Anaerobic Treatment of Industrial Wastewater by UASB Reactor Integrated with Chemical Oxidation Processes; An Overview. *Pol. J. Environ. Stud*. 19(5), 1051-1061.
- Yetilmezsoy, K. and Zengin, Z. S. (2007). Stochastic Modeling Applications for The Prediction of COD Removal Efficiency of UASB Reactors Treating Diluted Real Cotton Textile Wastewater. *Stochastic Environmental Research and Risk Assessment*. 23(1), 13-26.
- Yetilmezsoy, K., Ilhan, F., Sapci-Zengin, Z., Sakar, S., and Gonullu, M. T. (2009). Decolorization and COD Reduction of UASB Pretreated Poultry Manure Wastewater by Electrocoagulation Process: A Post-Treatment Study. *J Hazard Mater*. 162(1), 120-132.
- Younes, S. B., Cherif, I., Dhoub, A., and Sayadi, S. (2016). *Trametes trogii*: A Biologic Powerful Tool for Dyes Decolorization and Detoxification. *Catalysis Letters*. 146(1), 204-211.

- Yu, H. Q., Fang, H. H. P. and Tay, J. H (2001). Enhanced Sludge Granulation in Upflow Anaerobic Sludge Blanket (UASB) Reactors by Aluminium Chloride. *Chemosphere*. 44, 31-36.
- Yu, L. J., Wang, H. Y., Song, H. J., Kong, D. F., and Chen, T. (2013). Performance of a Pilot-Scale Hydrolysis Acidification and Improved UASB Process for the Treatment of Alcohol Wastewater: Sludge Granulation and Treatment Efficiency. *Advanced Materials Research*. 726-731, 2246-2251.
- Yurtsever, A., Sahinkaya, E., Aktas, O., Ucar, D., Cinar, O., and Wang, Z. (2015). Performances of Anaerobic and Aerobic Membrane Bioreactors for the Treatment of Synthetic Textile Wastewater. *Bioresour Technol*. 192, 564-573.
- Zabłocka-Godlewska, E., Przysaś, W., and Grabińska-Sota, E. (2012). Decolourization of Diazo Evans Blue by Two Strains of *Pseudomonas Fluorescens* Isolated from Different Wastewater Treatment Plants. *Water, Air, and Soil Pollution*. 223(8), 5259-5266.
- Zehra, T., Priyantha, N., and Lim, L. B. L. (2016). Removal of Crystal Violet Dye from Aqueous Solution Using Yeast-Treated Peat as Adsorbent: Thermodynamics, Kinetics, and Equilibrium Studies. *Environmental Earth Sciences*. 75(4), 357.
- Zeng, X., Cai, Y., Liao, X., Zeng, X., Luo, S., and Zhang, D. (2012). Anthraquinone Dye Assisted the Decolorization Of Azo Dyes by A Novel *Trametes Troglia* Laccase. *Process Biochemistry*. 47(1), 160-163.
- Zhang, L., Feng, X., Zhu, N., and Chen, J. (2007). Role of Extracellular Protein in The Formation and Stability of Aerobic Granules. *Enzyme and Microbial Technology*. 41(5), 551-557.
- Zhang, Q., Jing, Y. H., Shiue, A., Chang, C. T., Chen, B. Y., and Hsueh, C. C. (2012). Deciphering Effects of Chemical Structure on Azo Dye Decolorization/Degradation Characteristics: Bacterial Vs. Photocatalytic Method. *Journal of the Taiwan Institute of Chemical Engineers*. 43(5), 760-766.
- Zhang, S., Li, A., Cui, D., Yang, J., and Ma, F.(2011b). Performance of Enhanced Biological SBR Process for Aniline Treatment by Mycelial Pellet as Biomass Carrier. *Bioresour Technol*. 102, 4360–4365.

- Zhang, Y., Jing, Y., Zhang, J., Sun, L., and Quan, X. (2011a). Performance of A ZVI-UASB Reactor for Azo Dye Wastewater Treatment. *Journal of Chemical Technology and Biotechnology*. 86(2), 199-204.
- Zhao, L., Zhou, J., Jia, Y., and Chen, J. (2010). Biodecolorization of Acid Red GR by a Newly Isolated *Dyella Ginsengisoli* LA-4 Using Response Surface Methodology. *J Hazard Mater*. 181(1-3), 602-608.
- Zheng, Y.M., Yu, H.Q. and Sheng, G.P. (2005). Physical and Chemical Characteristics of Granular Activated Sludge from a Sequencing Batch Airlift reactor. *Process Biochemistry*. 40(2), 645-650.
- Zhong, C., Wang, Y., Wang, Y., Lv, J., Li, Y., and Zhu, J. (2013). High-Rate Nitrogen Removal and Its Behavior of Granular Sequence Batch Reactor Under Step-Feed Operational Strategy. *Bioresour Technol*. 134, 101-106.
- Zhu, J. and Wilderer, P.A. (2003). Effect of Extended Idle Conditions on Structure and Activity of Granular Activated Sludge. *Water Res*. 37, 2013-2018.
- Zhu, L., Lv, M. L., Dai, X., Yu, Y. W., Qi, H. Y., and Xu, X. Y. (2012). Role and Significance of Extracellular Polymeric Substances on The Property of Aerobic Granule. *Bioresour Technol*. 107, 46-54.
- Zimmermann, T., Gasser, F., Kulla, H. and Leisinger, T. (1984). Comparison of Two Bacterial Azoreductases Acquired during Adaption to Growth on Azo Dyes. *Arch. Microbiol*. 138, 37-43.
- Zita, A. and Hermansson, M. (1997). Effects of Bacterial Cell Surface Structures and Hydrophobicity On Attachment To Activated Sludge Flocs. *Appl. Environ. Microbiol*. 63, 1168-1170.
- Zollinger, H. (2003). *Color Chemistry: Syntheses, Properties and Applications of Organic Dyes and Pigment* (3<sup>rd</sup> ed) Switzerland. Verlag Helvetica Chimica Acta AG and WILEY-VCH GmbH and Co.
- Zuriaga-Agustí, E., Iborra-Clar, M. I., Mendoza-Roca, J. A., Tancredi, M., Alcaina-Miranda, M. I., and Iborra-Clar, A. (2010). Sequencing Batch Reactor Technology Coupled with Nanofiltration for Textile Wastewater Reclamation. *Chemical Engineering Journal*. 161(1-2), 122-128.