

RESPONSE SURFACE METHODOLOGY FOR DAMAGE DETECTION USING
FREQUENCY AND MODE SHAPES

SAREHATI BINTI UMAR

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Master of Engineering (Structure & Materials)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

DECEMBER 2015

DEDICATION

To Mak and Bapa who constantly encouraged and supported their daughter

To Dyana, Luqman and Ida who believed in their sister's ability

To Dylla who kept up her Titiq's spirits

ACKNOWLEDGEMENT

The sincere gratitude is expressed to Dr Norhisham Bakhary who has been an excellent supervisor for this study through his advice and guidance. The valuable time, constant efforts and patient encouragement he gave on the completion of this thesis are greatly indebted. Financial supports from Universiti Teknologi Malaysia and Ministry of Higher Education Malaysia via scholarship of UTM Zamalah Master and Fundamental Research Grant Scheme vote 4F308 are also gratefully acknowledged.

ABSTRACT

The model updating method is one popular method in vibration-based damage detection. However, the conventional model updating method requires a finite element (FE) model for sensitive computation during the iteration process, which leads to the problem of slow convergence and high time consumption. Therefore, the response surface methodology (RSM) has emerged as an alternative tool in FE model updating due to easy implementation and time-efficient processing where the computationally expensive analytical FE model is replaced by the simple and inexpensive response surface (RS) model. A recent RSM application in structural damage detection employs frequency as the sole response feature, limiting its ability to localise the existence of damage due to the inability of the frequency to ascertain damage in a symmetric structure. Therefore, a better RSM employing frequency and mode shapes as the response features is proposed in this study, as both parameters are proven sensitive to damage location. The implementation of the proposed method involves a three-phase procedure; (i) sampling, (ii) RS modelling and (iii) model updating. In order to develop the best RS model, two major parameters in the sampling stage, design of experiments (DOEs) and design spaces are carefully assessed through a series of sensitivity studies based on their damage detectability. The applicability of the technique is applied to detect simulated damage in numerical models of simply supported beam and steel frame structures as well as a laboratory tested steel portal frame. The results from sensitivity studies show that central composite design (CCD) with more sampling points in a small design space has better performance in detecting damages due to dense population of data which adequately represents the design space. The results from numerical study demonstrated that the proposed RSM method has a good ability to detect damage due to noise free data while results from experimental study depicted some false detections. It is concluded that the proposed method is reliable in damage detection provided that the data has good precision. Nevertheless, the presence of noise and errors in real practice are inevitable, thus pollute the measured data. Therefore, it is suggested to incorporate the effect of uncertainties in the proposed RSM to improve its applicability in real practice.

ABSTRAK

Kaedah mengemaskini model merupakan salah satu kaedah yang popular dalam mengesan kerosakan berasaskan getaran. Walau bagaimanapun, kaedah konvensional mengemaskini model memerlukan model unsur terhingga (finite element, FE) bagi pengiraan sensitif semasa proses lelaran yang menyebabkan masalah penumpuan perlahan dan penggunaan masa yang tinggi. Oleh itu, kaedah permukaan tindak balas (response surface methodology, RSM) telah muncul sebagai alternatif dalam mengemaskini model FE kerana pelaksanaan yang mudah dan proses yang efisien di mana pengiraan analisis model FE yang mahal digantikan dengan permukaan tindak balas (response surface, RS) yang mudah dan murah. Aplikasi terbaru RSM dalam mengesan kerosakan struktur menggunakan frekuensi sebagai ciri tindak balas tunggal, telah menghadkan keupayaannya dalam mengenalpasti lokasi kerosakan disebabkan ketidakupayaan frekuensi dalam mengenalpasti kerosakan dalam struktur yang simetri. Oleh itu, RSM yang lebih baik dengan menggunakan frekuensi dan mod bentuk sebagai ciri tindak balas dicadangkan dalam kajian ini kerana kedua-dua parameter ini terbukti sensitif terhadap lokasi kerosakan. Pelaksanaan kaedah yang dicadangkan melibatkan prosedur tiga fasa; (i) persampelan, (ii) permodelan RS dan (iii) mengemaskini model. Bagi membina model RS terbaik, dua parameter utama di fasa persampelan iaitu rekabentuk eksperimen (design of experiments, DOEs) dan ruang rekabentuk, dinilai dengan teliti melalui satu siri kajian sensitiviti berdasarkan keupayaan mengesan kerosakan. Kebolegunaan teknik ini diaplikasikan untuk mengesan kerosakan simulasi dalam model berangka bagi struktur rasuk sokong mudah dan kerangka keluli serta kerangka portal keluli yang diuji di makmal. Hasil kajian sensitiviti menunjukkan bahawa rekabentuk komposit pusat (central composite design, CCD) dengan titik persampelan yang lebih banyak dalam ruang rekabentuk yang kecil mempunyai prestasi yang lebih baik dalam mengesan kerosakan disebabkan oleh populasi data yang padat yang mewakili ruang rekabentuk secukupnya. Hasil kajian berangka menunjukkan bahawa kaedah RSM yang dicadangkan mempunyai keupayaan yang baik untuk mengesan kerosakan yang disebabkan oleh data bebas gangguan manakala hasil kajian eksperimen menunjukkan beberapa pengesanan palsu. Disimpulkan bahawa kaedah yang dicadangkan boleh dipercayai untuk mengesan kerosakan dengan syarat bahawa data yang digunakan mempunyai ketepatan yang baik. Walau bagaimanapun, kewujudan gangguan dan ralat dalam amalan sebenar tidak dapat dielakkan, lantas mencemarkan data diukur. Oleh itu, adalah dicadangkan untuk menggabungkan kesan ketidakpastian dalam RSM yang dicadangkan untuk meningkatkan kebolegunaan dalam amalan sebenar.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF SYMBOLS	xiii
	LIST OF ABBREVIATIONS	xv
	LIST OF APPENDICES	xvii
1	INTRODUCTION	1
	1.0 Introduction	1
	1.1 Background of problem	2
	1.2 Problem statements	3
	1.3 Research objectives	4
	1.4 Significance of study	4
	1.5 Scope of study	5
	1.6 Outline of thesis	6
2	LITERATURE REVIEW	8
	2.1 Structural Health Monitoring	8
	2.2 Vibration-based damage detection	9
	2.2.1 FRF-based method	13

2.2.2	Frequency-based method	15
2.2.3	Methods based on mode shapes and its derivatives	18
2.2.4	Model updating-based method	20
2.3	Response surface methodology	23
2.4	Concluding remarks	27
3	RESEARCH METHODOLOGY	29
3.1	Research design and procedures	29
3.2	Response surface methodology for damage detection	31
3.2.1	Phase I: Sampling	32
3.2.1.1	Input and response features	33
3.2.1.2	Design of experiment	34
3.2.2	Phase II: RS modelling	37
3.2.3	Phase III: Model updating	39
3.3	Numerical models	41
3.3.1	Simply supported beam	42
3.3.2	Portal frame	43
3.4	Sensitivity studies	45
3.4.1	Effect of DOE on RSM performance	46
3.4.2	Effect of design space on damage detectability	47
3.4.3	Comparison of RSM response features on damage detection	47
3.5	Experimental testing	48
4	NUMERICAL STUDY	49
4.1	Numerical example 1: simply supported beam	49
4.1.1	Effect of DOE on RSM performance	50
4.1.1.1	Phase I: Sampling	51
4.1.1.2	Phase II: RS modelling	53
4.1.1.3	Phase III: Model updating and damage detection	56
4.1.2	Effect of design space on RSM detectability	61

	4.1.3	Comparison of response features in damage detection	66
	4.2	Numerical example 2: portal frame	71
	4.3	Discussion and chapter summary	74
5		EXPERIMENTAL STUDY	76
	5.1	Experimental model	76
	5.2	Modal testing	77
	5.3	Experimental results	81
	5.4	Damage detection using RSM	84
	5.4.1	Stage 1: Reference state model updating	85
	5.4.2	Stage 2: Damage state model updating	88
	5.5	Discussion and chapter summary	95
6		CONCLUSIONS AND RECOMMENDATIONS	96
	6.1	Summary and conclusions	96
	6.2	Contributions	99
	6.3	Recommendations	100
		REFERENCES	101
		APPENDICES	112

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Drawbacks of vibration-based damage detection methods	27
3.1	Modal frequencies of undamaged simply supported beam	42
4.1	Damage cases	50
4.2	First three frequencies for the undamaged and damaged beam	51
4.3	Checking criteria for the full quadratic model	53
4.4	Damage cases	61
4.5	Checking criteria of the RS models	62
4.6	Damage cases	71
4.7	Checking criteria	72
5.1	Damage state	81
5.2	Measured frequencies of the frame (Hz)	84
5.3	Checking criteria for the first RSM	86
5.4	Frequencies of the undamaged frame after updating	87
5.5	MAC values of the undamaged frame after updating	87
5.6	Checking criteria for the second RSM	89

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Time domain, frequency domain and modal domain data	11
3.1	General flowchart of research methodology	30
3.2	Flowchart of RSM-based damage detection	32
3.3	Central composite design	35
3.4	Box-Behnken design	36
3.5	General flow of SDTools	41
3.6	Simply-supported beam	42
3.7	First three mode shapes of undamaged model	43
3.8	Finite element model of the steel frame	44
3.9	Nodes and segments on the steel frame	44
3.10	The first four mode shapes and the corresponding natural frequencies of the steel frame	45
3.11	Dimensions of the lab tested steel frame	48
4.1	Graph of prediction versus actual value of λ_1	54
4.2	Graph of prediction versus actual value for $\phi_{2,1}$	55
4.3	Performance of the RS model derived from CCD _{MRV}	57
4.4	Performance of the RS model derived from CCD ₆₄	58
4.5	Performance of the RS model derived from D-optimal	59
4.6	Design space of $E_0 - 0.6E_0$ (RS60)	63
4.7	Design space of $E_0 - 0.3E_0$ (RS30)	64
4.8	Design space of $E_0 - 0.1E_0$ (RS10)	65
4.9	Identified SRF using frequencies	67
4.10	Identified SRF using mode shapes	68
4.11	Identified SRF using frequency combined with mode shapes	69

4.12	Identified SRF	73
5.1	Experimental model	77
5.2	Configuration of modal testing	78
5.3	Accelerometer location and impact points	79
5.4	DEWEsoft display screen during the measurement	80
5.5	Overlay log magnitude of FRF of undamaged frame	80
5.6	Segments on the steel frame	82
5.7	Induced damage	82
5.8	First four mode shapes for the undamaged and damaged frames	83
5.9	Two-stage RSM	85
5.10	Updated Young's modulus (E'_0)	88
5.11	Identified SRF from SR-F	92
5.12	Identified SRF from SR-FMS1	93
5.13	Identified SRF from SR-FMS2	94

LIST OF SYMBOLS

\mathbf{M}	Mass matrix
\mathbf{C}	Damping matrix
\mathbf{K}	Stiffness matrix
\ddot{x}	Vectors of acceleration
\dot{x}	Vectors of velocity
x	Vectors of displacement
ω_i	i^{th} modal natural angular frequency
Φ_i	i^{th} mode shapes
x	Input parameters
y	Response features
f	Approximation function
k	Number of input variables / number of elements
ε	Error
σ^2	Variance
N	Number of total points
n_c	Number of centre points
± 1	Factorial points
$\pm\alpha$	Axial points
D	Determinant
β	Regression coefficients
\mathbf{Y}	Matrix of actual response
$\hat{\mathbf{Y}}$	Matrix of estimated response
n_r	Number of response feature
λ	Modal frequencies
Φ	Mode shapes
m	Number of considered mode

n	Number of considered node
R^2	R-square
R^2_{adj}	Adjusted R-square
R^2_{pred}	Predicted R-square
SS_R	Sum of squares regression
SS_T	Total sum of squares
$PRESS$	Predicted residual error sum of squares.
ω	Weight vector used to control the attainment factor of the goals
γ	Slack element used as a dummy in the optimisation
lb, ub	Lower and upper bounds of design parameters
E_0	Young's modulus in the undamaged state / initial state
E'	Young's modulus in the damaged state
E'_0	Young's modulus of the reference state
I	Moment inertia
D	Density
ρ	Poisson's ratio

LIST OF ABBREVIATIONS

ANN	Artificial neural networks
AR	Auto Regressive
ARMA	Auto Regressive Moving Average
ARX	Auto Regressive with exogenous input
BBD	Box–Behnken design
CCC	Circumscribed central composite
CCD	Central composite design
CCD ₆₄	1/64 fractional factorial design
CCD _{MRV}	Minimum-run resolution V design
COMAC	Co-ordinate Modal Assurance Criterion
DOE	Design of experiment
DOFs	Degrees of freedom
DS	Damage state
DSF	Damage sensitive features
F	Reference state based on the first 4 frequencies only
FBDD	Frequency-based damage detection
FCC	Face-centred composite
FD	Factorial design
FE	Finite element
FFT	Fast Fourier Transform
FMS1	Reference state based on the first 4 frequencies and mode shapes
FMS2	Reference state based on modes 2 to 4 of the frequencies and mode shapes
FRF	Frequency response function
ICA	Independent component analysis
ICC	Inscribed central composite
MAC	Modal Assurance Criterion

MBDD	Mode shapes-based damage detection
MDLAC	Multiple damage location assurance criterion
NDT	Non-destructive tests
PCA	Principal component analysis
POM	Proper orthogonal modes
RC	Reinforced concrete
RS	Response surface
RS10	RS model derived from design space of $E_0 - 0.1E_0$
RS30	RS model derived from design space of $E_0 - 0.3E_0$
RS60	RS model derived from design space of $E_0 - 0.6E_0$
RS-F	RS model constructed from reference state F
RS-FMS1	RS model constructed from reference state FMS1
RS-FMS2	RS model constructed from reference state FMS2
RSM	Response surface methodology
SHM	Structural Health Monitoring
SRF	Stiffness reduction factor
UD	Uniform design

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Example of Matlab Script using SDTools	112
B	Mode Shapes of Numerical Example 1 (Simply Supported Beam)	114
C	Mode Shapes of Numerical Example 2 (Steel Frame)	115
D	Mode Shapes of Experimental Model of Steel Frame	118

CHAPTER 1

INTRODUCTION

1.0 Introduction

Many civil structures such as buildings and bridges are built to provide essential welfare in communities. These valuable assets are normally designed to be in service for a long lifespan. However, throughout their service time, the structures suffer from deterioration due to usage, environmental effects and accidental events such as earthquake. All these factors lead to local or global damage to the structures such as cracks, corrosion, delamination, disintegration and others that affect the integrity of structures. At worst, consequences like catastrophic failure might occur, which results in injuries, loss of human life and long term impacts on social and economic factors.

Several incidents have been reported due to loss of integrity of in-service structures. For example, the sudden collapse of the I-35W bridge over the Mississippi River in Minneapolis, Minnesota, on 01 August 2007 was due to improper structural design of the gusset plates used in the truss structures (Hao, 2010). An incident involving a building was the eight-storey Rana Plaza factory building in Savar, Bangladesh, where the warning to evacuate the building when cracks appeared a day before the collapse of the building on 24 April 2013 had been ignored. This incident resulted in about 2500 injured people and a death toll of more than 1000, and is thus considered as the deadliest structural failure incident (BBC News, 2013). Another building collapse incident reported on 27 September 2013 in Mumbai, India involved a five-story residential building, killing 61 due to improper

renovation and illegal removal of a central wall and supporting beams (Cook, Yan and Udas, 2013). Recently, shoddy renovations and construction were blamed for the collapse of Gyeongju Mauna Resort Gymnasium in Korea (The Star, 2014) and Military Training Center barracks in Omsk, in the south of Russia (Steward, 2105). The occurrences of the aforementioned incidents have shown that an efficient method is vital in inspection and monitoring the safety conditions of the structures. This can be achieved by Structural Health Monitoring (SHM), a tool to diagnose the state of the structure. The application of SHM prolongs the life of structures through early detection of damage, thus minimising the potential for catastrophes.

1.1 Background of problem

SHM can be categorised into local and global methods. In the local method, visual inspection or non-destructive tests (NDT) such as ultrasonic waves, magnetic field, radio-frequency, eddy-current, thermal field and fibre optic are applied to assess the structure. However, the methods are labour-intensive and require clues to the damaged area. Therefore, the global method, namely vibration-based damage detection, has been explored by civil engineers over the past three decades due to its ability to diagnose structures as a whole (Cawley and Adams, 1979). Unlike the NDT local methods, this non-destructive global method is useful for SHM because it does not require prior knowledge of the damage location. Vibration-based methods utilise the fact that the presence of damage will reduce the stiffness and mass properties of the structure and subsequently change its dynamic behaviour. The vibration parameters are categorised into time, frequency and modal domains. The modal domain, which includes the frequency, mode shapes and damping ratio, is commonly employed as damage indicator because it is easier to determine and interpret than the other two domains (Doebeling *et al.*, 1996). By knowing the differences in these parameters between the undamaged and damaged states, damage location and severity information can be obtained.

Abundant research has been performed to develop vibration-based damage detection methods. One method that has received attention is the model updating

method. This method adjusts the mass, stiffness and damping parameters of numerical models for better agreement between the numerical model and test model. Model updating methods are categorised into non-iterative and iterative methods. Non-iterative methods directly update the stiffness and mass matrices of the numerical model through a closed-form direct solution. However, such methods leads to the loss of structural connectivity, and the suggested corrections are not always physically meaningful (Jaishi and Ren, 2006). On the other hand, iterative methods require sensitivity matrices to guide iteration in minimising the objective function. However, the sensitivity-based method seems not practical to be applied to structures with high degrees of freedom (DOFs) as it results in a time-consuming process due to the increase in DOFs. In addition, it also has problems of ill-conditioning and slow convergence due to dependency on the evaluation of the finite element (FE) model in every iteration process.

Therefore, an alternative method has recently been proposed to provide a fast running process by replacing the computationally expensive analytical FE model with a metamodel or surrogate model. A statistical-based surrogate model approach called response surface methodology (RSM) has been used considerably in model updating due to simplicity, and allows fast optimisation because of smooth gradients, thus lessening the convergence problem. The applicability and potential of RSM in reducing computation time and effort in the model updating process in the structural dynamic field have been demonstrated in many studies (Guo and Zhang, 2004; Deng and Cai, 2009; Ren and Chen, 2010; Ren, Fang and Deng, 2010; Han and Luo, 2013). Therefore, this study has made good use of the RSM merit by applying the RSM method for vibration-based damage detection.

1.2 Problem statements

As mentioned previously, the common method used in model updating-based damage detection based on sensitivity matrices is prone to ill-conditioning and is time-consuming due to dependency on the computationally expensive FE model. An alternative has been initiated to replace the complex FE model with simple and

inexpensive surrogate models to reduce the computational complexity via RSM. Many studies have proven the efficiency of RSM in model updating. However, the applications are limited to updating the baseline of the FE model only while studies pertaining to RSM in the application of vibration-based damage detection are somewhat scarce and limited to the employment of modal frequency as the sole response feature. As frequency is a global parameter that is insensitive to spatial information, the frequency-based RSM is less reliable in providing information about damage location. Due to the limitations above, this study proposed a new RSM method for damage detection by considering both frequency and mode shapes for better damage localisation.

1.3 Research objectives

With the aim of developing a new model updating-based method damage detection, this study is undertaken with the following objectives:

- i. To investigate the applicability of RSM for damage detection based on modal data.
- ii. To study the behaviour of RSM parameters in vibration-based damage detection.
- iii. To validate the proposed RSM numerically and experimentally.

1.4 Significance of study

The motivation for this study is the drawbacks of the traditional FE model updating-based damage detection, which as mentioned earlier features convergence difficulty and long computation time, especially for complex structures. During iteration in the model updating process, the updated parameters will be sent to the FE software such as ANSYS to run the FE model with new updated parameters. This back and forth process limits the applications of the model updating-based approach

in real practice of damage detection. By having a new and practical method using RSM, mathematical functions that explain the input-response relationship in structural systems can be expressed explicitly. These explicit functions, called the response surface (RS) model are beneficial as they can be employed to provide an efficient updating process to detect damage. Given that the application of model updating-based RSM in vibration-based damage detection particularly with the use of mode shapes is not yet discovered, the existing RSM-based damage detection is improved by considering combined frequencies and mode shapes as the response features. With this improvement, the accuracy of the output of damage detection can be increased.

1.5 Research scope and limitations

This study is focused on the use of RSM in the application of structural damage detection considering frequency and mode shapes data for better damage localisation. However, the scope of this study is limited as follows:

- i. The comparison between RSM-based and traditional model updating methods is conducted through literature study only since this study focused primarily on the applicability of RSM in damage detection by considering both frequency and mode shapes data.
- ii. The structural damage in this study is solely presented by the changes of stiffness and thus, no alteration is made to the mass property. Another assumption applied in this study is that the stiffness is reflected in the elastic modulus of the structure, hence selected as the RSM updating parameters.
- iii. In the context of vibration data, the modal domain, especially the modal frequencies and mode shapes, are the focus of this study and are subsequently utilised in the RSM method for damage detection. To show the superiority of the proposed RSM method, the method is compared to the existing frequency-based RSM in terms of damage detectability.
- iv. Since a proper sampling is crucial in achieving an adequate representation of the relationship between the selected input parameters and response features

to serve as a surrogate model, a series of sensitivity studies on two sampling parameters are conducted. The purpose of conducting sensitivity studies is to investigate the effect of DOE and design space parameters on the ability of RSM to detect structural damage. Since the quadratic response surface (RS) model is mainly used in this study, only three DOEs comprising CCD, Box–Behnken design (BBD) and D-optimal design are considered due to their wide usage in deriving quadratic RS models.

- v. The applicability of the proposed method is demonstrated through numerical models of a simply supported beam and a portal frame and further verified using a lab tested steel frame. The experiment is conducted within the control condition in a laboratory.

1.6 Outline of thesis

This thesis consists of six chapters and is organised as follows:

Chapter 1 presents the background, problem statements, research objectives, significance, scope of the study and outline of the thesis.

Chapter 2 reviews the studies related to SHM, basic theory of vibration-based damage detection as well as various damage detection methods. The advantages and disadvantages of each method are discussed and the applicability of RSM in model updating and damage detection is also reviewed in the chapter.

Chapter 3 outlines the proposed RSM method employing frequencies and mode shapes through a three-phase procedure: sampling, RS modelling and model updating. The description of numerical models, experimental models and sensitivity studies are also given in the chapter.

Chapter 4 demonstrates the applicability of the proposed method through numerical study using a simply supported beam and a steel frame. Sensitivity study

on the DOEs, design bounds and type of response features to the damage detectability are conducted.

Chapter 5 provides the details of experimental model, modal testing procedures, damage scenarios and damage detection procedures that consist of a two-stage process comprising model updating of the reference state and damaged state.

Chapter 6 summarises the methodology and findings from numerical and experimental studies and finally proposes recommendations for future research related to the subject of the study.

REFERENCES

- Abdel Wahab, M. M., and De Roeck, G. (1999). Damage Detection in Bridges Using Modal Curvatures: Application to a Real Damage Scenario. *Journal of Sound and Vibration* 226(2): 217-235.
- Alvandi, A., and Cremona, C. (2006). Assessment of Vibration-Based Damage Identification Techniques. *Journal of Sound and Vibration* 292(1–2): 179-202.
- Alvarez, L.(2000). *Design Optimization Based on Genetic Programming*. Doctor Philosophy, University of Bradford, UK.
- Avitabile, P. (2001). Experimental Modal Analysis. *Sound and Vibration* 35(1): 20-31.
- Bakhary, N., Hao, H., and Deeks, A. J. (2007). Damage Detection Using Artificial Neural Network with Consideration of Uncertainties. *Engineering structures* 29(11): 2806-2815.
- Bakhary, N., Hao, H., and Deeks, A. J. (2010). Structure Damage Detection Using Neural Network with Multi-Stage Substructuring. *Advances in Structural Engineering* 13(1): 95-110.
- Bakhary, N., Hao, H., and Deeks, A. J. (2010). Substructuring Technique for Damage Detection Using Statistical Multi-Stage Artificial Neural Network. *Advances in Structural Engineering* 13(4): 619-640.
- Bandara, R. P., Chan, T. H. T., and Thambiratnam, D. P. (2014). Frequency Response Function Based Damage Identification Using Principal Component Analysis and Pattern Recognition Technique. *Engineering Structures* 66: 116-128.
- Baruch, M. (1978). Optimization Procedure to Correct Stiffness and Flexibility Matrices Using Vibration Tests. *AIAA Journal* 16(11): 1208-1210.
- Baruch, M., and Bar Itzhack, I. Y. (1978). Optimal Weighted Orttiogonalization of Measured Modes. *AIAA Journal* 16(4): 346-351.

- BBC News. (2013, 10 May). Bangladesh Factory Collapse Toll Passes 1,000. *BBC News*. Retrieved 10 August 2015, from <http://www.bbc.com>.
- Berman, A., and Nagy, E. (1983). Improvement of a Large Analytical Model Using Test Data. *AIAA Journal* 21(8): 1168-1173.
- Bezerra, M. A., Santelli, R. E., Oliveira, E. P., Villar, L. S., and Escaleira, L. A. (2008). Response Surface Methodology (Rsm) as a Tool for Optimization in Analytical Chemistry. *Talanta* 76(5): 965-977.
- Borkowski, J. J., and Valeroso, E. S. (2001). Comparison of Design Optimality Criteria of Reduced Models for Response Surface Designs in the Hypercube. *Technometrics* 43(4): 468-477.
- Box, G. E., and Wilson, K. (1951). On the Experimental Attainment of Optimum Conditions. *Journal of the Royal Statistical Society. Series B (Methodological)* 13(1): 1-45.
- Carden, E. P., and Fanning, P. (2004). Vibration Based Condition Monitoring: A Review. *Structural Health Monitoring* 3(4): 355-377.
- Cawley, P., and Adams, R. (1979). The Location of Defects in Structures from Measurements of Natural Frequencies. *The Journal of Strain Analysis for Engineering Design* 14(2): 49-57.
- Chandrashekhar, M., and Ganguli, R. (2009). Damage Assessment of Structures with Uncertainty by Using Mode-Shape Curvatures and Fuzzy Logic. *Journal of Sound and Vibration* 326(3-5): 939-957.
- Chang, P. C., Flatau, A., and Liu, S. C. (2003). Review Paper: Health Monitoring of Civil Infrastructure. *Structural Health Monitoring* 2(3): 257-267.
- Cheng, J., Li, Q., and Xiao, R. C. (2008). A New Artificial Neural Network-Based Response Surface Method for Structural Reliability Analysis. *Probabilistic Engineering Mechanics* 23(1): 51-63.
- Cook, L., Yan, H., and Udas, S. (2013, September 30). Mumbai Mayor: Decorator Responsible for Building Collapse, Killing 61. *CNN News*. Retrieved 10 August 2105, from <http://edition.cnn.com>.
- Cornwell, P., Doebling, S. W., and Farrar, C. R. (1999). Application of the Strain Energy Damage Detection Method to Plate-Like Structures. *Journal of Sound and Vibration* 224(2): 359-374.

- Cundy, A. L. (2003). *Use of Response Surface Metamodels in Damage Identification of Dynamic Structures*. Doctor Philosophy, Virginia Polytechnic Institute and State University, US.
- Deng, L., and Cai, C. (2009). Bridge Model Updating Using Response Surface Method and Genetic Algorithm. *Journal of Bridge Engineering* 15(5): 553-564.
- Design Expert[®] (2005). Minneapolis, State-Ease Inc.
- Dessi, D., and Camerlengo, G. (2015). Damage Identification Techniques Via Modal Curvature Analysis: Overview and Comparison. *Mechanical Systems and Signal Processing* 52–53(0): 181-205.
- Doebbling, S. W., Farrar, C. R., and Prime, M. B. (1998). A Summary Review of Vibration-Based Damage Identification Methods. *The Shock and Vibration Digest* 30(2): 91-105.
- Doebbling, S. W., Farrar, C. R., Prime, M. B., and Shevitz, D. W. (1996). *Damage Identification and Health Monitoring of Structural and Mechanical Systems from Changes in Their Vibration Characteristics: A Literature Review*. New Mexico, Los Alamos National Laboratory.
- Eun, H. C., Park, S. Y., and Kim, R. J. (2013). Damage Detection of Shear Building Structure Based on Frf Response Variation. *Adv Sci Technol Lett* 32: 18-25.
- Fan, W., and Qiao, P. (2009). A 2-D Continuous Wavelet Transform of Mode Shape Data for Damage Detection of Plate Structures. *International Journal of Solids and Structures* 46(25–26): 4379-4395.
- Fan, W., and Qiao, P. (2011). Vibration-Based Damage Identification Methods: A Review and Comparative Study. *Structural Health Monitoring* 10(1): 83-111.
- Fang, H., Rais-Rohani, M., Liu, Z., and Horstemeyer, M. F. (2005). A Comparative Study of Metamodeling Methods for Multiobjective Crashworthiness Optimization. *Computers & Structures* 83(25–26): 2121-2136.
- Fang, S.-E., and Perera, R. (2009). A Response Surface Methodology Based Damage Identification Technique. *Smart Materials and Structures* 18(6): 065009.
- Fang, S.-E., and Perera, R. (2011). Damage Identification by Response Surface Based Model Updating Using D-Optimal Design. *Mechanical Systems and Signal Processing* 25(2): 717-733.
- Fang, S.-E., Perera, R., and De Roeck, G. (2008). Damage Identification of a Reinforced Concrete Frame by Finite Element Model Updating Using

- Damage Parameterization. *Journal of Sound and Vibration* 313(3–5): 544-559.
- Farrar, C. R., Doebling, S. W., and Nix, D. A. (2001). Vibration-Based Structural Damage Identification. *Philosophical Transactions of the Royal Society of London. Series A: Mathematical, Physical and Engineering Sciences* 359(1778): 131-149.
- Ferreira, S. C., Bruns, R., Ferreira, H., Matos, G., David, J., Brandao, G., da Silva, E. P., Portugal, L., Dos Reis, P., and Souza, A. (2007). Box-Behnken Design: An Alternative for the Optimization of Analytical Methods. *Analytica Chimica Acta* 597(2): 179-186.
- Friswell, M., Penny, J., and Wilson, D. (1994). Using Vibration Data and Statistical Measures to Locate Damage in Structures. *Modal Analysis: The International Journal of Analytical and Experimental Modal Analysis* 9(4): 239-254.
- Fritzen, C.-P., Jennewein, D., and Kiefer, T. (1998). Damage Detection Based on Model Updating Methods. *Mechanical Systems and Signal Processing* 12(1): 163-186.
- Gavin, H. P., and Yau, S. C. (2008). High-Order Limit State Functions in the Response Surface Method for Structural Reliability Analysis. *Structural Safety* 30(2): 162-179.
- Gembicki, F. W.(1974). *Vector Optimization for Control with Performance and Parameter Sensitivity Indices*. Doctor Philosophy, Case Western Reserve University, Cleveland, Ohio.
- Gul, M., and Catbas, F. N. (2010). Damage Assessment with Ambient Vibration Data Using a Novel Time Series Analysis Methodology. *Journal of Structural Engineering* 137(12): 1518-1526.
- Guo, Q., and Zhang, L. (2004). Finite Element Model Updating Based on Response Surface Methodology. *Proceedings of the 22nd IMAC*, Dearborn, USA.
- Gurses, K., Kuran, B., and Gencoglu, C. (2011). *Identification of Material Properties of Composite Plates Utilizing Model Updating and Response Surface Techniques*. Linking Models and Experiments. Proulx, T. New York, Springer. 2: 251-262.
- Han, J. P., and Luo, Y. P. (2013). *Static and Dynamic Finite Element Model Updating of a Rigid Frame-Continuous Girders Bridge Based on Response Surface Method*. Advanced Materials Research. Zhou, X., He, G., Fan, Y.,

- Xiao, Y., Kunnath, S. K. and Monti, G. Switzerland, Trans Tech Publications. 639-640: 992-997.
- Hao, S. (2010). I-35w Bridge Collapse. *Journal of Bridge Engineering* 15(5): 608-614.
- Hu, J., and Liang, R. Y. (1993). An Integrated Approach to Detection of Cracks Using Vibration Characteristics. *Journal of the Franklin Institute* 330(5): 841-853.
- Hu, W., Yao, L. G., and Hua, Z. Z. (2008). Optimization of Sheet Metal Forming Processes by Adaptive Response Surface Based on Intelligent Sampling Method. *Journal of Materials Processing Technology* 197(1-3): 77-88.
- Hua, X. G., Ni, Y. Q., Chen, Z. Q., and Ko, J. M. (2009). Structural Damage Detection of Cable-Stayed Bridges Using Changes in Cable Forces and Model Updating. *Journal of Structural Engineering* 135(9): 1093-1106.
- Ismail, Z. (2012). Application of Residuals from Regression of Experimental Mode Shapes to Locate Multiple Crack Damage in a Simply Supported Reinforced Concrete Beam. *Measurement* 45(6): 1455-1461.
- Ismail, Z., and Ong, Z. C. (2012). Honeycomb Damage Detection in a Reinforced Concrete Beam Using Frequency Mode Shape Regression. *Measurement* 45(5): 950-959.
- Jaishi, B., and Ren, W. X. (2006). Damage Detection by Finite Element Model Updating Using Modal Flexibility Residual. *Journal of Sound and Vibration* 290(1-2): 369-387.
- Jaishi, B., and Ren, W. X. (2007). Finite Element Model Updating Based on Eigenvalue and Strain Energy Residuals Using Multiobjective Optimisation Technique. *Mechanical Systems and Signal Processing* 21(5): 2295-2317.
- Jin, R., Chen, W., and Simpson, T. W. (2001). Comparative Studies of Metamodelling Techniques under Multiple Modelling Criteria. *Structural and Multidisciplinary Optimization* 23(1): 1-13.
- Jin, R., Du, X., and Chen, W. (2003). The Use of Metamodeling Techniques for Optimization under Uncertainty. *Structural and Multidisciplinary Optimization* 25(2): 99-116.
- Kessler, S. S., Spearing, S. M., Atalla, M. J., Cesnik, C. E. S., and Soutis, C. (2002). Damage Detection in Composite Materials Using Frequency Response Methods. *Composites Part B: Engineering* 33(1): 87-95.

- Khiem, N. T., and Lien, T. V. (2001). A Simplified Method for Natural Frequency Analysis of a Multiple Cracked Beam. *Journal of Sound and Vibration* 245(4): 737-751.
- Kim, J.-T., Ryu, Y.-S., Cho, H.-M., and Stubbs, N. (2003). Damage Identification in Beam-Type Structures: Frequency-Based Method Vs Mode-Shape-Based Method. *Engineering Structures* 25(1): 57-67.
- Kim, J. T., and Stubbs, N. (2003). Crack Detection in Beam-Type Structures Using Frequency Data. *Journal of Sound and Vibration* 259(1): 145-160.
- Lee, J. (2009). Identification of Multiple Cracks in a Beam Using Natural Frequencies. *Journal of Sound and Vibration* 320(3): 482-490.
- Lee, S. H., and Kwak, B. M. (2006). Response Surface Augmented Moment Method for Efficient Reliability Analysis. *Structural safety* 28(3): 261-272.
- Lee, U., and Shin, J. (2002). A Frequency Response Function-Based Structural Damage Identification Method. *Computers & Structures* 80(2): 117-132.
- Lee, Y.-S., and Chung, M.-J. (2000). A Study on Crack Detection Using Eigenfrequency Test Data. *Computers & Structures* 77(3): 327-342.
- Li, J., and Hao, H. (2014). Substructure Damage Identification Based on Wavelet-Domain Response Reconstruction. *Structural Health Monitoring* 13(4): 389-405.
- Li, J., Liang, L., Borrer, C. M., Anderson-Cook, C., and Montgomery, D. C. (2009). Graphical Summaries to Compare Prediction Variance Performance for Variations of the Central Composite Design for 6 to 10 Factors. *Quality Technology and Quantitative Management* 6(4): 433-449.
- Link, M. (1999). *Updating of Analytical Models—Basic Procedures and Extensions*. Modal Analysis and Testing, Springer: 281-304.
- Liu, X., Lieven, N. A. J., and Escamilla-Ambrosio, P. J. (2009). Frequency Response Function Shape-Based Methods for Structural Damage Localisation. *Mechanical Systems and Signal Processing* 23(4): 1243-1259.
- Maia, N. M. M., Silva, J. M. M., Almas, E. A. M., and Sampaio, R. P. C. (2003). Damage Detection in Structures: From Mode Shape to Frequency Response Function Methods. *Mechanical Systems and Signal Processing* 17(3): 489-498.

- Majumder, L., and Manohar, C. S. (2003). A Time-Domain Approach for Damage Detection in Beam Structures Using Vibration Data with a Moving Oscillator as an Excitation Source. *Journal of Sound and Vibration* 268(4): 699-716.
- Messina, A., Williams, E., and Contursi, T. (1998). Structural Damage Detection by a Sensitivity and Statistical-Based Method. *Journal of Sound and Vibration* 216(5): 791-808.
- Mojtahedi, A., Ostadi, G. R., and Yaghin, M. L. (2014). Inspection of Uncertainty Effects on Structural Fault Diagnosing of Transmission Towers. *International Journal of Automation and Power Engineering* 3(1).
- Morassi, A. (2001). Identification of a Crack in a Rod Based on Changes in a Pair of Natural Frequencies. *Journal of Sound and Vibration* 242(4): 577-596.
- Morassi, A., and Rollo, M. (2001). Identification of Two Cracks in a Simply Supported Beam from Minimal Frequency Measurements. *Journal of Vibration and Control* 7(5): 729-739.
- Morassi, A., and Rovere, N. (1997). Localizing a Notch in a Steel Frame from Frequency Measurements. *Journal of Engineering Mechanics* 123(5): 422-432.
- Mukhopadhyay, T., Dey, T., Chowdhury, R., and Chakrabarti, A. (2015). Structural Damage Identification Using Response Surface-Based Multi-Objective Optimization: A Comparative Study. *Arabian Journal for Science and Engineering* 40(4): 1027-1044.
- Myers, R. H., Montgomery, D. C., and Anderson-Cook, C. M. (2009). *Response Surface Methodology: Process and Product Optimization Using Designed Experiments*. Hoboken, New Jersey, John Wiley & Sons.
- Myers, W. R., Myers, R. H., and Carter, W. H. (1994). Some Alphabetic Optimal Designs for the Logistic Regression Model. *Journal of statistical planning and inference* 42(1): 57-77.
- Nair, K. K., Kiremidjian, A. S., and Law, K. H. (2006). Time Series-Based Damage Detection and Localization Algorithm with Application to the Asce Benchmark Structure. *Journal of Sound and Vibration* 291(1-2): 349-368.
- Ndambi, J. M., Vantomme, J., and Harri, K. (2002). Damage Assessment in Reinforced Concrete Beams Using Eigenfrequencies and Mode Shape Derivatives. *Engineering Structures* 24(4): 501-515.

- Neoh, C. H., Yahya, A., Adnan, R., Majid, Z. A., and Ibrahim, Z. (2013). Optimization of Decolorization of Palm Oil Mill Effluent (POME) by Growing Cultures of *Aspergillus Fumigatus* Using Response Surface Methodology. *Environmental Science and Pollution Research* 20(5): 2912-2923.
- Owolabi, G., Swamidas, A., and Seshadri, R. (2003). Crack Detection in Beams Using Changes in Frequencies and Amplitudes of Frequency Response Functions. *Journal of Sound and Vibration* 265(1): 1-22.
- Pandey, A., Biswas, M., and Samman, M. (1991). Damage Detection from Changes in Curvature Mode Shapes. *Journal of Sound and Vibration* 145(2): 321-332.
- Patil, D. P., and Maiti, S. K. (2003). Detection of Multiple Cracks Using Frequency Measurements. *Engineering Fracture Mechanics* 70(12): 1553-1572.
- Perera, R., Fang, S.-E., and Huerta, C. (2009). Structural Crack Detection without Updated Baseline Model by Single and Multiobjective Optimization. *Mechanical Systems and Signal Processing* 23(3): 752-768.
- Perera, R., and Ruiz, A. (2008). A Multistage FE Updating Procedure for Damage Identification in Large-Scale Structures Based on Multiobjective Evolutionary Optimization. *Mechanical Systems and Signal Processing* 22(4): 970-991.
- Perera, R., Ruiz, A., and Manzano, C. (2007). An Evolutionary Multiobjective Framework for Structural Damage Localization and Quantification. *Engineering Structures* 29(10): 2540-2550.
- Quanhong, L., and Caili, F. (2005). Application of Response Surface Methodology for Extraction Optimization of Germinant Pumpkin Seeds Protein. *Food Chemistry* 92(4): 701-706.
- Rai, M. M., and Madavan, N. K. (2000). Aerodynamic Design Using Neural Networks. *AIAA Journal* 38(1): 173-182.
- Ratcliffe, C. P. (1997). Damage Detection Using a Modified Laplacian Operator on Mode Shape Data. *Journal of Sound and Vibration* 204(3): 505-517.
- Ren, W.-X., and Chen, H.-B. (2010). Finite Element Model Updating in Structural Dynamics by the Response Surface Method. *Engineering Structures* 32(8): 2455-2465.
- Ren, W. X., Fang, S. E., and Deng, M. Y. (2010). Response Surface-Based Finite-Element-Model Updating Using Structural Static Responses. *Journal of Engineering Mechanics* 137(4): 248-257.

- Ribeiro, J., Teófilo, R., Augusto, F., and Ferreira, M. (2010). Simultaneous Optimization of the Microextraction of Coffee Volatiles Using Response Surface Methodology and Principal Component Analysis. *Chemometrics and Intelligent Laboratory Systems* 102(1): 45-52.
- Rutherford, A., Inman, D., Park, G., and Hemez, F. (2005). Use of Response Surface Metamodels for Identification of Stiffness and Damping Coefficients in a Simple Dynamic System. *Shock and Vibration* 12(5): 317-331.
- Rytter, A. (1993). *Vibrational Based Inspection of Civil Engineering Structures*. Doctor Philosophy, University of Aalborg.
- Salawu, O., and Williams, C. (1994). Damage Location Using Vibration Mode Shapes. *Proceedings of the 12th International Modal Analysis*.
- Salawu, O. S. (1997). Detection of Structural Damage through Changes in Frequency: A Review. *Engineering Structures* 19(9): 718-723.
- Salehi, M., Ziaei-Rad, S., Ghayour, M., and Vaziri-Zanjani, M. A. (2013). A Frequency Response Based Structural Damage Localization Method Using Independent Component Analysis. *Journal of Mechanical Science and Technology* 27(3): 609-619.
- Sampaio, R. P. C., Maia, N. M. M., and Silva, J. M. M. (1999). Damage Detection Using the Frequency-Response-Function Curvature Method. *Journal of Sound and Vibration* 226(5): 1029-1042.
- Schwarz, B. J., and Richardson, M. H. (1999). Experimental Modal Analysis. *CSI Reliability Week* 35(1): 1-12.
- Seyedpoor, S. M. (2012). A Two Stage Method for Structural Damage Detection Using a Modal Strain Energy Based Index and Particle Swarm Optimization. *International Journal of Non-Linear Mechanics* 47(1): 1-8.
- Shi, Z., Law, S., and Zhang, L. (2000). Damage Localization by Directly Using Incomplete Mode Shapes. *Journal of Engineering Mechanics* 126(6): 656-660.
- Shieh, C. J., Liao, H. F., and Lee, C. C. (2003). Optimization of Lipase-Catalyzed Biodiesel by Response Surface Methodology. *Bioresource Technology* 88(2): 103-106.
- Simpson, T. W., Poplinski, J., Koch, P. N., and Allen, J. K. (2001). Metamodels for Computer-Based Engineering Design: Survey and Recommendations. *Engineering with computers* 17(2): 129-150.

- Sohn, H., and Farrar, C. R. (2001). Damage Diagnosis Using Time Series Analysis of Vibration Signals. *Smart Materials and Structures* 10(3): 446–451.
- Sohn, H., Farrar, C. R., Hemez, F. M., Shunk, D. D., Stinemates, D. W., Nadler, B. R., and Czarnecki, J. J. (2004). *A Review of Structural Health Monitoring Literature: 1996-2001*. Los Alamos, Los Alamos National Laboratory.
- Steward, W. (2105, 13 July). Horror at Russian Army Barracks as 23 Soldiers Are Killed When Building Collapses 'Due to Shoddy Renovations'. *Daily Mail*. Retrieved 10 August 2015, from <http://www.dailymail.co.uk>.
- Swiler, L., Slepoy, R., and Giunta, A. (2006). Evaluation of Sampling Methods in Constructing Response Surface Approximations. *Proc. 47th AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference, number AIAA-2006-1827, Newport, RI*.
- Teughels, A., Maeck, J., and De Roeck, G. (2002). Damage Assessment by Fe Model Updating Using Damage Functions. *Computers & Structures* 80(25): 1869-1879.
- The Star. (2014, February 28). Poor Construction Blamed for Fatal Gym Collapse in S. Korea. *The Star*. Retrieved 10 August 2015, from <http://www.thestar.com.my>.
- Tomaszewska, A. (2010). Influence of Statistical Errors on Damage Detection Based on Structural Flexibility and Mode Shape Curvature. *Computers & Structures* 88(3–4): 154-164.
- Trendafilova, I., and Manoach, E. (2008). Vibration-Based Damage Detection in Plates by Using Time Series Analysis. *Mechanical Systems and Signal Processing* 22(5): 1092-1106.
- Umar, S., Bakhary, N., and Mohd Yassin, A. Y. (2015). Comparative Study on Design of Experiment in Frequency-Based Response Surface Methodology for Damage Detection. *Applied Mechanics and Materials*, Trans Tech Publ. 735: 168-173.
- Vincenzi, L., and Savoia, M. (2015). Coupling Response Surface and Differential Evolution for Parameter Identification Problems. *Computer-Aided Civil and Infrastructure Engineering* 30(5): 376-393.
- Wang, G. G., and Shan, S. (2006). Review of Metamodeling Techniques in Support of Engineering Design Optimization. *Journal of Mechanical Design* 129(4): 370-380.

- Wang, X., Xia, Y., Zhou, X., and Yang, C. (2014). Structural Damage Measure Index Based on Non-Probabilistic Reliability Model. *Journal of Sound and Vibration* 333(5): 1344-1355.
- Wang, X., Yang, H., and Qiu, Z. (2010). Interval Analysis Method for Damage Identification of Structures. *AIAA journal* 48(6): 1108-1116.
- Wang, Z., Lin, R., and Lim, M. (1997). Structural Damage Detection Using Measured Frf Data. *Computer Methods in Applied Mechanics and Engineering* 147(1): 187-197.
- Xia, Y., and Hao, H. (2003). Statistical Damage Identification of Structures with Frequency Changes. *Journal of Sound and Vibration* 263(4): 853-870.
- Xia, Y., Hao, H., Brownjohn, J. M. W., and Xia, P.-Q. (2002). Damage Identification of Structures with Uncertain Frequency and Mode Shape Data. *Earthquake Engineering & Structural Dynamics* 31(5): 1053-1066.
- Yan, Y. J., Cheng, L., Wu, Z. Y., and Yam, L. H. (2006). Development in Vibration-Based Structural Damage. *Mechanical Systems and Signal Processing* 21(2007): 2198–2211.
- Yang, Q. W., and Liu, J. K. (2006). A Coupled Method for Structural Damage Identification. *Journal of Sound and Vibration* 296(1–2): 401-405.
- Yao, R., and Pakzad, S. N. (2012). *Structural Damage Detection Using Multivariate Time Series Analysis*. Topics on the Dynamics of Civil Structures, Volume 1, Springer: 299-308.
- Zang, C., and Imregun, M. (2001). Structural Damage Detection Using Artificial Neural Networks and Measured Frf Data Reduced Via Principal Component Projection. *Journal of Sound and Vibration* 242(5): 813-827.
- Zhang, Q. W., Chang, C. C., and Chang, T. Y. P. (2000). Finite Element Model Updating for Structures with Parametric Constraints. *Earthquake Engineering & Structural Dynamics* 29(7): 927-944.
- Zhang, Z., and Xiaofeng, B. (2009). *Comparison About the Three Central Composite Designs with Simulation*. Proceeding of International Conference on Advanced Computer Control. Jianhong, Z. and Xiaoxiao, Z. California, IEEE Computer Society: 163-167.