

CORRELATION BETWEEN FOAM STABILITY AND ELECTROKINETIC
SIGNAL IN FOAM ASSISTED WATER ALTERNATE GAS PROCESS

SHAZIERA BINTI OMAR

UNIVERSITI TEKNOLOGI MALAYSIA

CORRELATION BETWEEN FOAM STABILITY AND ELECTROKINETIC
SIGNAL IN FOAM ASSISTED WATER ALTERNATE GAS PROCESS

SHAZIERA BINTI OMAR

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Petroleum Engineering)

Faculty of Chemical & Energy Engineering
Universiti Teknologi Malaysia

DECEMBER 2017

To my beloved husband, son, mother and family

ACKNOWLEDGEMENTS

In preparing this thesis, I was in contact with many people, researchers, academicians and practitioners. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main thesis supervisor, Ir. Dr. Mohd Zaidi Jaafar for encouragement, guidance, critics and friendship. I am also very thankful to my co-supervisor Associated Professor Abdul Razak Ismail for his guidance, advices and motivation. Without their continued support and interest, this thesis would not have been the same as presented here.

I am also indebted to Malaysia Government for funding my Ph.D. study under MyBrain15 Scholarship Scheme. Technicians and staffs at Reservoir Laboratory and UTM and Librarians at UTM also deserve special thanks for their assistance regarding the experiments and supplying the relevant literatures.

My fellow postgraduate students should also be recognized for their support. My sincere appreciation also extends to all my colleagues and others who have provided assistance at various occasions. Their views and tips are useful indeed. Unfortunately, it is not possible to list all of them in this limited space. I am grateful to all my family members.

ABSTRACT

Foam is purposely used in some of the Enhanced Oil Recovery (EOR) displacement processes in order to control the mobility ratio, hence improving the volumetric sweep efficiency. The efficiency of a foam displacement process in EOR depends largely on the stability of the foam films. In laboratory, foam stability is usually measured through physical observation of the foam bubble in a glass tube. Unfortunately, this direct observation is not possible in the reservoir. Therefore, indirect measurement such as the measurement of electrokinetic signal would be a better alternative. This study aimed to determine the correlation between the foam stability and the associated streaming potential signals which resulted from the flowing fluid in foam assisted water alternate gas (FAWAG) process. The downhole monitoring of streaming potential which uses electrodes mounted on the outside of an insulated casing is a promising new technology for monitoring fluid movement processes in real time. In this study, the experiments were divided into two: Foam stability test and electrokinetic signal measurement. The electrokinetic signals were measured using five non-polarizing Cu/CuCl electrodes, installed along a sand pack model and measurement was recorded continuously using NIDAS and the LabView software. Surfactant alternate gas was used to produce foams inside the porous media using five different Sodium Dodecyl Sulphate (SDS) concentrations, namely 2500, 5000, 7500, 10000 and 12500 ppm. The result from the experiment showed that 10000 ppm was an optimum concentration of SDS. Thus, the voltage (electrokinetic signal) decreased with an increase in foam stability up to optimum SDS concentration. While for 12500 ppm SDS concentration the electrokinetic signal increased as foam stability decreased. The burst of the foam bubbles had changed the pattern of electrokinetic signals. Although the voltage was small, i.e., ranging from 0 to 1 mV, it was still measureable. These results present new findings in the relationship between foam stability and electrokinetic signals generated in the FAWAG process. This fundamental knowledge can lead to developing a new approach in monitoring FAWAG processes in making the EOR process more efficient.

ABSTRAK

Busa digunakan pada sesetengah proses anjakan Perolehan Minyak Tertingkat (EOR) untuk mengawal nisbah mobiliti, seterusnya meningkatkan kecekapan sapuan isipadu. Kecekapan proses anjakan busa dalam EOR bergantung pada kestabilan selaput busa. Di makmal, kestabilan busa biasanya diukur menerusi pemerhatian secara fizikal terhadap gelembung busa di dalam tiub kaca. Malangnya, keadaan ini tidak boleh dilihat di dalam reservoir. Oleh itu, kaedah tak langsung, misalnya pengukuran isyarat elektrokinetik boleh menjadi pilihan yang lebih baik. Kajian ini bertujuan untuk mengenal pasti hubung kait antara kestabilan busa dan isyarat potensi aliran yang terhasil daripada aliran bendalir ketika berlakunya proses suntikan air berselang-seli gas berbantu busa (FAWAG). Pemantauan terhadap potensi aliran di dasar lubang menggunakan elektrod yang dipasang di luar selongsong tertebat ialah teknologi baharu untuk memantau proses pergerakan bendalir masa nyata. Dalam kajian ini, ujikaji dibahagikan kepada dua bahagian: Ujian kestabilan busa dan pengukuran isyarat elektrokinetik. Isyarat elektrokinetik diukur menggunakan lima elektrod tidak mengkutub Cu/CuCl yang dipasang sepanjang model pek pasir. Pengukuran dilaksana secara berterusan menggunakan perisian NIDAS dan perisian LabView. Surfaktan berselang-seli gas diguna dalam kajian ini untuk menghasilkan busa di dalam liang menerusi penggunaan lima kepekatan Natrium Dodesil Sulfat (SDS) yang berlainan, iaitu 2500, 5000, 7500, 10000 dan 12500 ppm. Keputusan kajian menunjukkan bahawa 10000 ppm ialah kepekatan optimum untuk SDS. Oleh itu, voltan (isyarat elektrokinetik) menurun dengan meningkatnya kestabilan busa sehingga ujikaji mencapai kepekatan optimum SDS. Selain itu, untuk SDS dengan kepekatan 12500 ppm, isyarat elektrokinetik meningkat dengan menurunnya kestabilan busa. Gelembung busa yang terletus telah mengubah corak isyarat elektrokinetik. Walaupun nilai voltan adalah kecil, iaitu berjulat dari 0 hingga 1 mV, tetapi nilai itu masih boleh diukur. Keputusan kajian mengetengahkan penemuan baharu bagi hubungan antara kestabilan busa dengan isyarat elektrokinetik yang terhasil dalam proses FAWAG. Pengetahuan asas ini boleh membantu dalam pembangunan kaedah baharu bagi pemantauan terhadap proses FAWAG dengan menjadikan proses EOR lebih cekap.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xii
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATIONS	xv
	LIST OF SYMBOLS	xvii
	LIST OF APPENDICES	xx
1	INTRODUCTION	1
	1.1 Overview	1
	1.2 Problem Statement	3
	1.3 Objectives	5
	1.4 Scope	6
	1.5 Significance of the Research	6
	1.6 Concluding Remarks	7

2	LITERATURE REVIEW	8
2.1	Foam Assisted Water Alternate Gas (FAWAG)	8
2.2	Foam Theory and Properties	10
2.2.1	Structure of Foam	12
2.2.2	Foam in Porous Media	13
2.2.3	Foam Termination Mechanisms in Porous Media	14
2.2.4	Foam Injection Modes	15
2.2.5	Foam Quality	18
2.3	Foam Enhanced EOR Issues and Concerns	19
2.4	Surfactant	20
2.5	Spontaneous Potential	23
2.5.1	Electrochemical Potential	25
2.5.2	Thermoelectric Potential	26
2.5.3	Redox Potential	27
2.5.4	Electrokinetic Potential	30
2.5.4.1	Electrokinetic Phenomena	31
2.6	Charged Surfaces Production in Porous Media	33
2.7	Electrical Double Layer	34
2.7.1	Helmholtz's Model	34
2.7.2	Gouy-Chapman Model	36
2.7.3	Stern and Grahame Modifications of the Diffuse Layer	37
2.8	Streaming Potential	39

2.8.1	Streaming Potential Measurement Technique	40
2.9	Monitoring Technique for FAWAG and Foam Stability	41
2.10	Applications of Electrokinetic Signal Measurements	46
2.11	Potential Future Application	47
2.12	Concluding Remark	47
3	RESEARCH METHODOLOGY	48
3.1	Introduction	48
3.2	Materials	49
3.2.1	Sand Pack Experimental Model	49
3.2.2	Foam Sample	51
3.2.3	Brine Sample	52
3.3	Experimental Procedures	53
3.3.1	Foam Half-life Measurement	53
3.3.2	Foam Size Distribution Measurement	55
3.3.3	Surface Tension of Surfactant Measurement	55
3.3.4	pH Value Determination	57
3.3.5	Porous Medium Characterization Test Apparatus	58
3.3.6	Electrode Preparation	63
3.3.7	Electrokinetic Signal Measurement Set-up	64
3.3.8	Pumping Experiments	67
3.4	Flowchart of Research Design	70

3.5	Concluding Remark	71
4	RESULT AND DISCUSSION	72
4.1	Introduction	72
4.2	Porous Medium Characterization Test	73
4.2.1	Sand Pack Model Properties	73
4.3	Foam Stability Test	74
4.3.1	Foam Half Life	74
4.3.2	Surface Tension	77
4.3.3	Foam Size Distribution	78
4.3.3.1	Foam Size of 2500 ppm SDS Concentration	79
4.3.3.2	Foam Size of 5000 ppm SDS Concentration	80
4.3.3.3	Foam Size of 7500 ppm SDS Concentration	82
4.3.3.4	Foam Size of 10,000 ppm SDS Concentration	83
4.3.3.5	Foam Size of 12,500 ppm SDS Concentration	85
4.3.4	pH Value Determination	88
4.4	Electrokinetic Signal Measurements	89
4.4.1	Measurement of Voltage Baseline	91
4.4.2	Measurement of Voltage and Pressure Different	94
4.4.3	The Correlation of Voltage and Foam Stability	97
4.5	Error Analysis	102

4.6	Concluding Remark	103
5	CONCLUSIONS AND RECOMMENDATIONS	105
5.1	Conclusions	105
5.1.1	Foam Stability Test	106
5.1.2	Electrokinetic Signal Measurements	107
5.2	Recommendations for Future Work	108
	REFERENCES	109
	Appendices A - H	126-146

LIST OF TABLES

TABLE NO.	TITLE	PAGE
3.1	Sand pack model information	50
3.2	Components of foam formulation	52
4.1	Properties of sand pack model	73

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Foam selection and placement in EOR projects	17
2.2	Chemical structure of Sodium Dodecyl Sulphate	23
2.3	Division of Spontaneous Potential	24
2.4	Charge separation in porous medium induces electrochemical potential	25
2.5	Charge separation in porous medium induces thermoelectric potential	27
2.6	The model of geo-battery by Sato and Mooney (1960)	29
2.7	The generation of sedimentation potential by current flow	33
2.8	The Helmholtz's model of Electrical Double Layer	35
2.9	The Gouy-Chapman model of diffuse layer	36
2.10	Modified double layer by Stern (1924) and Grahame (1947)	38
2.11	Electrical resistance technique for measuring foam film drawing	44
3.1	Sand pack experimental model	50
3.2	Air expansion method	54
3.3	Schematic diagram of air expansion method	54
3.4	Schematic diagram of Du Noüy ring method	56

3.5	Porous medium characterization test apparatus	59
3.6	Cross-section through the non-polarizing Cu/CuCl electrode	63
3.7	Schematic diagram for electrokinetic signal measurement set-up	65
3.8	Cross-section through the sand pack model	66
3.9	Flowchart of Research Design	70
4.1	The relationship between foam half life and SDS concentrations	75
4.2	The relationship between surface tension and SDS concentration	77
4.3	The foam size distribution of 2500 ppm SDS Concentration	79
4.4	The foam shape of 2500 ppm SDS concentration	80
4.5	The foam size distribution of 5000 ppm SDS concentration	81
4.6	The foam shape of 5000 ppm SDS concentration	81
4.7	The foam size distribution of 7500 ppm SDS concentration	82
4.8	The foam shape of 7500 ppm SDS concentration	83
4.9	The foam size distribution of 10,000 ppm SDS concentration	84
4.10	The foam shape of 10,000 ppm SDS concentration	84
4.11	The foam size distribution of 12,500 ppm SDS concentration	85
4.12	The foam shape of 12,500 ppm SDS concentration	85
4.13	The foam size distribution for five different SDS concentrations	86
4.14	The pH of SDS solution versus SDS concentration	88
4.15	The graph of voltage baseline for brine, surfactant, gas and foam	92
4.16	The graph between voltage and pressure different against time for different SDS concentrations	95
4.17	The graph between voltage against time for different SDS concentrations	99

LIST OF ABBREVIATIONS

CMC	-	Critical micelle concentration
CSS	-	Cyclic system simulation
EC	-	Electrochemical
EDL	-	Electrical double layer
EK	-	Electrokinetic
EKA	-	Electrokinetic analyzer
EKP	-	Electrokinetic phenomena
EO	-	Electro osmosis
EOR	-	Enhanced oil recovery
EP	-	Electrophoresis
ERT	-	Electrical resistance tomography
FAWAG	-	Foam assisted water alternate gas
GOR	-	Gas oil ratio
HPLC	-	High performance liquid chromatography
ID	-	Inner diameter
IEP	-	Isoelectric point
IFT	-	Interfacial tension
IHP	-	Inner Helmholtz plane
IOR	-	Improved oil recovery
MRI	-	Magnetic resonance imaging
NIDAS	-	National instrument data acquisition system

OHP	-	Outer Helmholtz plane
PGF	-	Perforations generated foam
PZC	-	Point of zero charge
RP	-	Redox potential
SAG	-	Surfactant alternate gas
SDS	-	Sodium dedocyl sulphate
SedP	-	Sedimentation potential
SLS	-	Sodium lauryl sulphate
SP	-	Streaming potential
SSP	-	Static spontaneous potential
TE	-	Thermoelectric
VSP	-	Vertical seismic profiling
WAG	-	Water alternate gas

LIST OF SYMBOLS

μ	-	Viscosity
μ_{app}	-	Apparent viscosity
μm	-	Micrometer
A	-	Surface area
Al^{3+}	-	Aluminium ion
C	-	Coupling coefficient
Cl^-	-	Chloride ion
cm	-	Centimeter
CO_2	-	Carbon dioxide
COOH	-	Carboxylic acid group
cP	-	Centipoises
Cu	-	Copper
CuCl	-	Copper chloride
F	-	Force
f_g	-	Foam quality
g	-	Gram
h	-	Bed thickness
H	-	Hydrogen
k	-	Permeability
l	-	Length
mD	-	Millidarcy
Mg^{2+}	-	Magnesium ion

min	-	Minute
ml	-	Millilitre
mm	-	Millimeter
ms	-	Millisecond
mV	-	Millivolt
N ₂	-	Nitrogen
Na	-	Sodium
Na ⁺	-	Sodium ion
NaCl	-	Sodium chloride
NaOH	-	Sodium Chloride
O	-	Oxygen
ppm	-	Part per million
Q/q	-	Flowrate
q_g	-	Gas flowrate
q_{liq}	-	Liquid flowrate
r	-	Distance from wall to the axis of the capillary
R	-	Lamellae resistance
r_i	-	Inner radius
r_o	-	Outer radius
Rt	-	True resistivity of permeable bed
s	-	Second
S	-	Sulphur
S_{oi}	-	Initial oil saturation
S_{or}	-	Residual oil saturation
S_{wi}	-	Irreducible water saturation
S_{wir}	-	Irreducible residual water saturation
S_{wir}	-	Irreducible water saturation

t	-	Time
V	-	Electrical potential
V_b	-	Bulk volume
V_g	-	Volume of gas
V_l	-	Volume of aqueous dispersion
V_p	-	Pore volume
γ	-	Surface tension
ΔP	-	Pressure gradient
ϕ	-	Porosity

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Displacement pump calibration	126
B	Foam half life measurement data	127
C	Surface tension of SDS solution data	135
D	Foam size distribution data	136
E	Data of pH value of SDS solution	139
F	Voltage baseline measurement data	140
G	The measurement of voltage and pressure different for different SDS concentrations data	141
H	Data of the correlation between voltage and foam stability	146

CHAPTER 1

INTRODUCTION

1.1 Overview

Carbon dioxide (CO₂), nitrogen (N₂), air and hydrocarbon are among the common media used in gas flooding or gas injection. One of the reasons for this is because the primary mechanism of gas injection focuses on displacement efficiency and gas flooding has a better microscopic displacement efficiency compared to water flooding. However, the major challenge when using gas displacement technique is its poor volumetric sweep efficiency. In worst-case scenario, this situation might lead to inexistence of contact between gas and a large area of hydrocarbon in the reservoir (Farajzadeh *et al.*, 2012). The overall hydrocarbon recovery will remain low as a result of this situation.

Ideally, the foam needs to have good stability for it to be considered as alternative solution. Various downhole monitoring techniques have been deployed to minimize reservoir uncertainties, including pressure and temperature sensors, seismic surveys, sonic velocity tools, and resistivity tools. Even though the

measured data will be very useful in describing the situation that is happening downhole, the measurements obtained are mostly limited to near wellbore parameters.

4D Seismic can be utilized to provide data in a deeper range of investigation. However, the resolution of the images is rather low. Measurement of electrokinetic potential has been previously proposed as a detecting tool for water encroachment towards a production well (Jackson *et al.*, 2012). The dynamics of electrically charged fluids whether it is formation fluid or injected fluid could be measured by installing permanent electrodes downhole (Jaafar *et al.*, 2009).

In other industry, specifically the paper industry, electrokinetics measurement has been linked to foam, polymers and surfactant (Hubbe, 2006). Since foam, surfactant and polymers are widely used in enhanced oil recovery (EOR) projects; electrokinetic signals could also be measured to predict the efficiency of the recovery mechanisms since EOR will be efficient if the foam is stable throughout the process and surfactant and polymer do not get adsorbed too much along the way.

Dynamic conditions are always going to be ideal for foam formation (Malysa and Lunkenheimer, 2008). The foam half life is determined by the single foam film stability, depending on the physicochemical processes and quantities like surfactant concentration, salt concentration, adsorption kinetics, and gravitational drainage. Other factors such as gas diffusion through foam films, surface forces, capillary pressure and mechanical fluctuations could also be significant (Farajzadeh *et al.*, 2012; Salleh and Ismail, 2012 and Wiggers *et al.*, 2000). Both the formability and stability of foam are the key factors in ensuring high performance of recovery (Qingfeng *et al.*, 2012). Theoretically, electrokinetic potential signal can be correlated with some of these parameters.

Indirect measurement of foam stability using electrokinetic potential is proposed in this study. The aim of this study is to find the relationship between the foam stability in the reservoir and the generated electrokinetic (EK) potentials during the displacement process by using five non-polarizing Cu/CuCl electrodes installed along the sand pack model. A National Instrument Data Acquisition System (NIDAS) was set to record streaming potential and pressure difference data continuously. This system was directly connected to the computer by using LabView software. The rupture of the foam could change the pattern of the EK signal due to the changes in the phases which are flowing through the media.

The correlation between the foam stability and electrokinetic potential could be identified but it will be highly dependent upon the foam film properties and associated characteristics. Under the right circumstances, data obtained in this study could very well be useful in monitoring the macroscopic and microscopic efficiency of an EOR process. Furthermore, by using electrokinetic potential signal, foam stability should be able to be monitored just from the surface conserving time, cost and environment in the process.

1.2 Problem Statement

There are several causes associated with the low recovery problem; gravity segregation because of the large density difference between oil and gas, viscous fingering in which the more viscous oil is by-passed by the less viscous gas and channelling when the gas flows across the high permeable streaks in heterogeneous reservoir (Farajzadeh *et al.*, 2012). Foam flooding, foam displacement process, or foam assisted water alternate gas (FAWAG) has been singled out as a potential solution to overcome these challenges.

Efficiency of the foam displacement process in EOR relies on the foam film stability. Commonly, in laboratory conditions, foam stability is measured through physical observation of the foam bubble production in a glass tube. Unfortunately, this direct observation is impractical to be done in a reservoir. Alternatively, indirect measurement i.e. the measurement of electrokinetic signal is seen as a more viable option. Measurement of electrokinetic signal is thus a promising approach in overcoming the limited range of detection into a reservoir. However, in this study foam stability measurement in the static conditions was also taken into account in order to get a trend of changes between foam stability and Sodium Dodecyl Sulphate (SDS) concentrations which the concentrations ranging from 2500 up to 12,500 ppm. The analysis of the foam stability tests include foam half-life time, surface tension, foam size and pH value.

Streaming potentials in porous media arises from the electrical double layer which is formed at solid-fluid interfaces (Jaafar, 2009 and Hunter, 1988). The solid surfaces are electrically charged, leading to a formation of a stern layer and a diffused layer in the adjacent fluid which contains excess of counter charges. If this fluid is directed by the external potential gradient to flow tangentially to the interface, some of the excess charge within the diffused layer will be transported along with the flow, raising the streaming current. Electrical potential or also known as streaming potential is the result of the amassment of charges which associated with divergence of the streaming current density (Jaafar, 2009).

However, the magnitude and sign of the electrokinetic signal related to foam stability are still considered as significant uncertainties associated with the interpretation of electrokinetic signal measurement. With regards to a FAWAG process, very few studies have reported the electrokinetic for foam. What happen after the foam rupture is also uncertain. Will the electrokinetic increase after the rupture due to the flow becoming more liquid dominant or will it decrease because the flow becoming more gas dominant? This study aims to solve these uncertainties and determine the correlation between the foam stability with the associated streaming potential signals resulted from the flowing fluid in FAWAG processes.

The foam has been produced by in-situ generation in sand pack model by applying the surfactant alternate gas (SAG) foam technique. Electrokinetic signal measurement has been used in this study in monitoring the changes of foam stability by using Cu/CuCl electrodes together with NIDAS and LabView software.

1.3 Objectives

The aim of this study is to further improve our understanding of the correlation between fluid and electrical potentials particularly when foam is present in the system. The study will delve deeper on application of electrokinetic signal in hydrocarbon reservoir monitoring. These goals have been achieved through comprehensive measurements of the electrokinetic signal in a laboratory environment. The specific objectives are:

- i. To measure the foam stability in the static environment as a result of the changes in the Sodium Dodecyl Sulphate (SDS) concentration.
- ii. To measure the electrokinetic signal as a result of the changes in the foam stability.
- iii. To generate a correlation which enables prediction of foam stability based on electrokinetic signals.

1.4 Scope

The scope defines the project limitation and the extent of coverage. The scopes for this project are as follows:

- i. Designing a FAWAG process by using sand pack with length and diameter of the model fixed at 30.4 cm and 3.4 cm respectively.
- ii. Sodium Dodecyl Sulphate (SDS) was used as a surfactant in FAWAG system in order to enhance the foam stability. The amounts of surfactant added are varied, ranging from 2500 – 12,500 ppm in order to find the ideal foam stability.
- iii. The analysis of the foam stability tests are foam half-life time, surface tension, foam size and pH value.
- iv. The surfactant alternate gas (SAG) foam technique in FAWAG process was applied in order to produce foam by generating in-situ foam in the sand pack model.
- v. Monitoring the changes in electrokinetic potential signal in relation to foam stability by using Cu/CuCl electrodes together with National Instrument Data Acquisition System (NIDAS) and LabView software.
- viii. Applying the following conditions: temperature = 22⁰C - 26⁰C, pressure = 14.7 – 30 psi.

1.5 Significance of the Research

The correlation between foam stability and electrokinetic signals generated in the foam assisted water alternate gas (FAWAG) process presents new findings in this

study. This fundamental knowledge could lead to developing new approach in monitoring FAWAG process. The indirect measurement could be very useful for monitoring the efficiency of the enhanced oil recovery (EOR) method in real-time due to low-cost and easy to use monitoring technique. Application in the real field could benefit the oil and gas industry in term of making the EOR process more efficient and more economic. This project could also contribute to better energy and natural resources management.

1.6 Concluding Remark

Chapter 1 explained the details of problem statement, objectives, scopes and significance of the study. Several objectives were withdrawn from this study which are to measure the foam stability in the static environment as a result of the changes in the Sodium Dodecyl Sulphate (SDS) concentration, to measure the electrokinetic signal as a result of the changes in the foam stability and to generate a correlation which enables prediction of foam stability based on electrokinetic signals.

REFERENCES

- Aarra, M. G., Skauge, A., and Martisen, H. A. (2002). FAWAG: A Breakthrough for EOR in the North Sea. *Proceedings of the SPE Annual Technical Conference and Exhibition*. 29 September-2 October. San Antonio, Texas.
- Abdullah, Z. Z., Zain, Z. M., Anua, N. A., and Singhal, A. (2011). Application of Radiative and Chemical Tracers for Offshore WAG Pilot Project. *Proceedings of the SPE Enhanced Oil Recovery Conference*. 19-21 July. Kuala Lumpur, Malaysia.
- Alkafeef, S. F. and Alajmi, A. F. (2006). Streaming Potentials and Conductivities of Reservoir Rock Cores in Aqueous and Non-aqueous Liquids. *Journal of Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 289, 141-148.
- Alkafeef, S. F. and Alajmi, N. M. (2007). Applications of Streaming Potential Transient Tests to Electrokinetic Characterization of Oil Reservoirs. *Proceedings of the 15th SPE Middle East Oil & Gas Show and Conference*. 11-14 March. Bahrain International Exhibition Centre, Kingdom of Bahrain.
- Amna, G. and Hiroshi, T. (2011). Experimental Study and Modelling of Pressure Loss for Foam Cuttings Mixture Flow in Horizontal Pipe. *Journal of Hydrodynamics*. 23(4), 431-438.
- Andrianov, A., Farajzadeh, R., Nick, M.M., Talanan, M., And Zitha, P.L.J. (2011). Immiscible Foam for Enhancing Oil Recovery: Bulk and Porous Media Experiments. *Proceedings of the SPE Enhanced Oil Recovery Conference*. 19-21 July. Kuala Lumpur, Malaysia.
- Archie, G.E. (1942). The Electrical Resistivity as an Aid in Determining Some Reservoir Characteristics. *Trans., AIME*. 146.

- Aronson, A. S., Bergeron, V., Fagan, M. E., and Radke, C. J. (1994). The Influence of Disjoining Pressure on Foam Stability and Flow in Porous Media. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 8(3), 109.
- Asghari, K. And Torabi, F. (2008). Effect of Miscible and Immiscible Carbon Dioxide Flooding on Gravity Drainage: Experimental and Simulation Results. *Proceedings of the SPE/DOE Symposium on Improved Oil Recovery*. 20-23 April. Tulsa, Oklahoma, USA.
- Asquith, G. B. and Gibson, C. R. (1993). *Basic Well Log Analysis for Geologists*. (1st ed.). American Association of Petroleum Geologists.
- Bales, B. L., Messina, L., Vidal, A., Peric, M. and Nascimento, O. R. (1998). Precision Relative Aggregation Number Determinations of SDS Micelles Using a Spin Probe. A Model of Micelle Surface Hydration. *Journal of Physics and Chemistry*. 102(50): 10347–10358.
- Barigou, M. and Davidson, J. F. (1994). Soap Film Drainage: Theory and Experiment. *Journal of Chemical Engineering Science*. 49, 1807-1819.
- Barigou, M. and Deshpande, N. S. (1999). Effects of Pressure on CO₂ Foam Displacements: A Micromodel Visualization Study. *Proceedings of the SPE/DOE Ninth Symposium on Improved Oil Recovery*. 17-20 April. Tulsa, OK.
- Barigou, M., Deshpande, N. S., and Wiggers, F. N. (2001). An Enhanced Electrical Resistance Technique for Foam Drainage Measurement. *Journal of Colloid and Surfaces. A: Physicochemical and Engineering Aspects*. 189, 237-246.
- Behrens, R. W., Rice, H. L. And Becker, K. W. (1963). A laboratory Method for Screening Foaming Agents Used in Air-Gas Drilling Operations. *Journal of Petroleum Technology*. 15,2.
- Bergeron, V., Fagan, M. E., and Radke, C. J. (1993). Generalized Entering Coefficients: A Criterion for Foam Stability Against Oil in Porous Media. *Langmuir*. 9(7), 1704-13.

- Bernard, G. P. (1965). Microdose Paradox – A New Concept. *Journal of Am Institute of Homoeopathy*. 58, 205-212.
- Bigalke, J. and Grabner, E. W. (1997). The Geobattery Model: A Contribution to Large Scale Electrochemistry, *Electrochim. Acta*. 42, 3443-3452.
- Bikerman, J. J. (1973). *Foams*. (1st ed.). Springer.
- Blaker, T., Aarra, M. G., Skauge, A., Rasmussen, L., H. K., SPE, Martinsen, H. A., and Vassenden, F. (2002). Foam for Gas Mobility Control in the Snorre Field: The FAWAG Project. *Journal of SPE Reservoir Evaluation and Engineering*. 5(4), 317-323.
- Blaker, T., Celius, H. K., Lie, T., Martinsen, H. A., Rasmussen, L., and Vassenden, F. (1999). Foam for Gas Mobility Control in the Snorre Field: The FAWAG Project. *Proceedings of the 1999 SPE Annual Technical Conference and Exhibition*. 3-6 October. Houston, Texas.
- Blauer, R. E. and Kohlhaas, C. A. (1974). Formation Fracturing with Foam. *Proceedings of the 1974 Fall Meeting of the SPE of AIME*. 6-9 October. Houston, Texas.
- Bockris, J., Reddy, A. and Gamboa-Aldeco, M. (2000). *Modern Electrochemistry 2A-Fundamental of Electrodicts*. (1st ed.). Kluwer Academic/ Plenum Publishers, New York.
- Bond, D. C. and Holbrook, O. C. (1958). Gas Drive Oil Recovery Process. *US Patern No. 2. 866, 507*.
- Briggs, D. R. (1928). The Determination of the Zeta Potential on Cellulose-A Method. *Journal of Physical Chemistry*. 32(5), 641-675.
- Brown, A. K., Isbell, C., Gallagher, S., Dodd, P. W., and Varley, J. (2001). An Improved Method for Controlling Foams produced within Bioreactors. *IchemE*. 79, 114-121.
- Butt, H., Graf, K. and Kappl, M. (2003). Normal Capillary Forces. *Physics and Chemistry of Interfaces*. 9, 345-350.

- Casteel, J. F. and Djabbarah, N. F. (1988). Sweep Improvement in CO₂ Flooding by Use of Foaming Agents. *SPE Reservoir and Engineering*. 3(4), 1186-1192.
- Castermant, J., Mendonca, C. A., Revil, A., Troland, F., Bourrie, G. and Linde, N. (2008). Redox Potential Distribution Inferred from Self-potential Measurement during the Corrosion of a Burden Metallic Body. *Geophysical Prospecting*. 56, 269-282).
- Ceccio, S. L. and George, D. L. (1996). A Review of Electrical Impedance techniques for the Measurement of Multiphase Flow. *Journal of Fluid Engineering*. 118, 391-399.
- Chang, S. H. (1999). Effects of Foam Quality and Flowrate on CO₂-Foam Behaviour at Reservoir Temperature and Pressure. *SPE Reservoir Evaluation and Engineering*. 2(3), 248-254.
- Chen, M. Y., Raghuraman, B., Bryant, I., and Supp, M. (2006). Streaming Potential Applications in Oil Fields. *Proceedings of the 2006 SPE Annual Technical Conference and Exhibition*. 24-27 September. San Antonio, Texas, U.S.A.
- Chen, Z., Lin, J. M., Uchiyama, K. and Hobo, T. (2000). Determination of Critical Micelle Concentration on Anionic Surfactants Based on Lignand Exchange Micellar Electrokinetic Chromatography. *Analytica Chimica Acta*. 403, 173.
- Chou, S. I. (1991). Conditions for Generating Foam in Porous Media. *Proceedings of the 66th SPE Annual Technical Conference and Exhibition*. 2-4 April. Oakland, California.
- Cilliers, J. J., Xie, W., Neethling, S. J., Randall, E. W., and Wilkinson, A. J. (2001). Electrical resistance Tomography using a Bi-Directional Current Pulse Technique. *Measurement of Science and Technology*. 12, 997-1001.
- Clark, D. C., Dann, R., Mackie, A. R., Mingins, J., Pinder, A. C., Purdy, P. W., Russell, E. J., Smith, L. J., and Wilson, D. R. (1990). Surface-Diffusion in Sodium Dodecyl Sulphate-stabilised Thin Liquid-films. *Journal of Colloid and Interface Science*. 138, 195-206.

- Clark, N. O. (1948). The Electrical Conductivity of Foam. *Transaction of Faraday Society*. 44, 13-15.
- Cohen, R. R. and Radke, C. J. (1990). Streaming Potentials of Nonuniformly Charged Surfaces. *Journal of Colloid and Interface Science*. 141(2), 338-347.
- Coke, M., Wilde, P. J., Russell, E. J., and Clark, D. C. (1990). The Influence of Surface Composition and Molecular Diffusion on the Stability of Foams Formed from Protein/Surfactant Mixtures. *Journal of Colloid and Interface Science*. 138, 489-504.
- Corwin, R. F. and Hoover, D. B. (1979). The Self-potential Method in Geothermal Exploration. *Geophysics*. 44, 226-245.
- Dame, C., Fritz, C., Pitois, O., and Faure, S. (2005). Relations between Physicochemical Properties and Instability of Decontamination Foams. *Colloids Surface A: Physicochemical Engineering Aspects*. 263, 210-218.
- Darnet, M., Marquis, G. and Sailhac, P. (2006). Hydraulic Stimulation of Geothermal Reservoirs: Fluid Flow, Electric Potential and Microseismicity Relationships. *Geophysical Journal International*. 166, 438-444.
- Datye, A. K., and Lemlich, R. (1983). Liquid Distribution and Electrical Conductivity in Foam. *Journal of International Multiphase Flow*. 9, 627-636.
- David, A. and Maraden, S. S. (1969). The Rheology of Foam. *Proceedings of the 2006 44th Annual Fall Meeting of the SPE of AIME*. 28 September-1 October. Denver, Colorado.
- Delgado, A. V., Caballero, F. G., Hunter, R. J., Koopal, L. K., and Lyklema (2007). Measurement and Interpretation of Electrokinetic Phenomena. *Journal of Colloid and Interface Science*. 309, 194-224.
- Delgado, A. V., Gonzalez-Coballero, F., Hunter, R. J., Koopal, L. K., and Lyklema, J. (1973). Measurement and Interpretation of Electrokinetic Phenomena. *Journal of Pure Applied Chemistry*. 77, 1753.
- Dukhin, S. S., Derjaguin, B. V., and Matievic, E. (1974). *Surface and Colloid Science*. (7th ed.). New York: Wiley-Interscience.

- Engelsen, C. W., Isarin, J. C., Gooijer, H., Warmoeskerken, M. M. C. G. and Groot-Wassink, J. (2002). Bubble Size Distribution of Foam. *AUTEX Research Journal*. 2(1).
- Exerowa, D. and Kruglyakov, P. M. (1998). *Foam and Foam Films*. (1st ed.). Elsevier Science.
- Farajzadeh, R., Andrianov, A., Krastev, R., Hirasaki, G. J., and Rossen, W. R. (2012). Foam–oil Interaction in Porous Media: Implications for Foam Assisted Enhanced Oil Recovery. *Advances in Colloid and Interface Science*. 183–184, 1-13.
- Farajzadeh, R., Krastev, R., and Zitha P. L. J. (2008). Properties of Foam Films Stabilized by AOS Surfactant. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 324, 35-40.
- Farzaneh, S. A. And Sohrabi, M. (2013). Foam Application in Enhanced Oil Recovery. *Proceedings of the 2013 EAGE Annual Conference and Exhibition Incorporating SPE Europec*. 10-13 June. London, UK.
- Fawcett, W. R. (2004). *Liquids: Solutions and Interfaces from Classical Macroscopic Description to Modern Microscopic Details*. (1st ed.). Oxford University Press, New York.
- Feng Li, R.L., Yan, W., Liu, S., Hirasaki, G.J., and Miller, C.A. (2010). Foam Mobility Control for Surfactant Enhanced Oil Recovery. *Proceedings of the SPE/DOE Symposium on Improved Oil Recovery*. 20-23 April. Tulsa, Oklahoma, USA.
- Fournel, B., Lemonnier, H., and Pouvreau, J. (2004). Foam Drainage Characterization by using Impedance Methods. *Proceedings of the 3rd Symposium on Two-Phase Modelling and Experimentation*. 22-24 September. Pisa, Italy.
- Fried, A. N. (1961). The Foam Drive Processes for Increasing the Recovery of Oil. *No. Report of Investigation: 5866, USBM*.

- Friedmann, F. and Jensen, J. A. (1986). Some Parameters Influencing the Formation and Propagation of Foams in Porous Media. . *Proceedings of the 1986 SPE California Regional Meeting*. 2-4 April. Oakland, California.
- Furness, P. (1992). An Evaluation of Spontaneous Mineralization Potentials. *Explorations Geophysics*. 23(2), 141-144.
- Goldie, M. (2002). Self-potentials Associated with the Yanacocha High Sulfidation Gold Deposit in Peru. *Geophysics*. 67, 684-689.
- Gonduin, M. and Scala, C (2002). *Streaming Potential and the SP Log*. Trans AIME. 15, 77-78.
- Gouy, G. (1910). Fundamentals and Applications in the Petroleum Industry. *Journal of Physics Theory Application*. 9(4), 457-468.
- Grahame, D. C. (1947). The Electrical Double Layer and the Theory of Electrocapillarity. *Chemical Reviews*. 41, 441-501.
- Hashimoto, T. and Tanaka, Y. (1995). Self-potential Observations on Unzen Volcano, Shimabara Peninsula, Kyushu Island, Japan. *Geophysics Research Letter*. 22, 191-194.
- Heller, J. P and Taber, J. J. (1980). Development of Mobility Control Methods to Improve Oil Recovery by CO². *Annual Report to the US Department of Energy*. Report No.: DOE/MC/10689-5,1980.
- Heller, P. L., Peterman, Z. E., O'neil, J. R and Shafiqullah, M. (1985). Isotopic Provenance of Sandstones from the Eocene Tyee Formation, Oregon Coast Range. *Geological Society America Bulletin*. 96, 770-780.
- Hettiarachchy, N. S., Sato, K., Marshall, M. R., and Kannan, A. (2012). *Food Proteins and Peptides: Chemistry, Functionality, Interactions and Commercialization*. (1st ed.). Boca Raton, Florida: CRC Press, Taylor and Francis Group.
- Hirasaki, G. J. (1989). The Steam-Foam Process. *Journal of Petroleum Technology*. 41(5), 449-456.

- Holm, L.W. (1998). The Mechanism of Gas and Liquid Flow Through Porous Media in the Presence of Foam. *SPE Journal*. 8(4), 359-369.
- Hubbe, M. A. (2006). *Electrokinetic Potential of Fibres*. BioResources. 1(1), 116-149.
- Huh, D. G. and Handy, L. L. (1989). Comparison of Steady and Unsteady-state Flow of Gas and Foaming Solution in Porous Media. *SPE Reservoir Engineering*. 4(1), 77-84.
- Hunter, R. J. (1988). *Zeta Potential in Colloid Science*. (7th ed.). New York: Academic Press.
- Hutzler, S., Verbist, G., Weaire, D., and Van der Steen, J. A. (1995). Measurement of Foam Density Profiles using AC Capacitance. *Europhysics Letters*. 31, 497-502.
- Jaafar, M. Z., Vinogradov, J., Jackson, M. D., Saunders, J. H., and Pain, C. C. (2009). Measurements of Streaming Potential for Downhole Monitoring in Intelligent Wells. *Proceedings of the 2009 SPE Middle East Oil & Gas Show and Conference*. 15-18 March. Bahrain International Exhibition Centre, Kingdom of Bahrain
- Jackson, M. D., Gulamali, M.Y., Leinov, E., Saunders, J.H., and Vinogradov, J. (2012). Spontaneous Potential in Hydrocarbon Reservoirs During Waterflooding: Application to Water-Front Monitoring. *Proceedings of the 2012 SPE Annual Technical Conference and Exhibition*. 20-22 September. Florence, Italy
- Jackson, M. D., Saunders, J. H., and Addiego-Guevara, E. A. (2005). Development and Applications of New Downhole Technology to Detect Water Encroachment Toward Intelligent Wells. *Proceedings of the 2005 SPE Annual Technical Conference and Exhibition*. 9-12 October. Dallas, Texas
- Janssen, L. (2012). Review of WAG Field Experience. *SPE Reservoir Evaluation and Engineering*. 2(1), 97-106.

- Joffre Viking (1990). *Carbon Dioxide Foam Flooding: Laboratory Model*. (1st ed.). ACS Symposium Series 373, Washington, DC.
- Jouniaux, L., and Pozzi, J. P. (1995). Streaming Potential and Permeability of Saturated Sandstones under Triaxial Stress: Consequences for Electrotelluric Anomalies Prior to Earthquakes. *Journal of Geophysical Research*. 100, 197-209.
- Kanani, N. (2004). *Electroplating: Basic Principles, Processes and Practice*. (1st ed.). Elsevier Advance Technology, Oxford, UK.
- Karapantsios, T. D. and Papara, M. (2008). On the Design of Electrical Conductance Probes for Foam Drainage Applications: Assessment of Ring Electrodes Performance and Bubble Size Effects in Measurements. *Journal of Colloids and Surfaces A: Physicochemical Engineering Aspects*. 323, 139-148.
- Karapantsios, T. D., Paras, S. V. and Karabelas, A. J. (1989). Statistical Characteristics of Free Falling Films at High Reynolds Numbers. *Journal International Multiphase Flow*. 15, 1-21.
- Kato, A., Takahashi, A., Matsudomi, N., and Kobayashi, K. (1983). Determination of Foaming Properties of Proteins by Conductivity Measurements. *Journal of Food Science*. 48, 62-65.
- Kornev, K. G., Niemark, A. V., and Rozhkov, A. N. (1999). Foam in Porous Media: Thermodynamic and Hydrodynamic Peculiarities. *Journal of Colloid Interface Science*. 82, 127-87.
- Kostoglou, M., Georgiou, M., and Karapantsios, T. D. (2010). A New Device for Assessing Film Stability in Foams: Experiment and Theory. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 382, 64-73.
- Kovscek, A. R. and Radke, C. J. (1994). *Fundamentals of Foam Transport in Porous Media in Foams: Fundamentals and Applications in the Petroleum Industry*. Washington, D.C.: Advances in Chemistry Series, American Chemical Society.

- Labo, J. (1987). *A Practical Introduction to Borehole Geophysics*. (1st ed.). Geophysical References Series, Society of Exploration Geophysicists.
- Li, B., Hirasaki, G. J. And Miller, C. A. (2006). Upscaling of Foam Mobility Control to the Three Dimensions. *Proceedings of the 2006 SPE/DOE Symposium on Improved Oil Recovery*. 19-23 April. Tulsa.
- Linde, N. and Revil, A. (1989). Inverting Residual Self-potential Data for Redox Potentials of Contaminant Plumes. *Geophysics Research Letter*. 34, 14302.
- Liu, Y., Grigg, R. B., and Svec, R. K. (2005). CO₂ Foam Behaviour: Influence of Temperature, Pressure and Concentration of Surfactant. *Proceedings of the 2005 SPE Production and Operations Symposium*. 17-19 April 2005. Oklahoma City, OK, USA
- Lorne, B., Perrier, F., and Avouac, J. P. (1999). Streaming Potential Measurements 2. Relationship between Electrical and Hydraulic Flow Patterns from Rock Samples during Deformation. *Journal of Geophysical Research*. 104, 879-896.
- Lowrie, W. (1997). *Fundamentals of Geophysics*. (1st ed.). Cambridge University Press, Cambridge.
- Lu and Hanagud, S. (2007). A Domain Evolution Model for Hysteresis and Piezoelectric Materials. *IEEE Transactions in Ultrasonics, Ferroelectrics and Frequency Control*. 53(7), 1239-1249.
- Lyklema, J. (1995). *Fundamental of Interface and Colloid Science*. (2nd ed.). London: Academic Press.
- Lyklema, J. (2003). Electrokinetics after Smoluchowski. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 222, 5-14.
- Malysa, K. and Lunkenheimer, K. (2008). Foams Under Dynamic Conditions. *Current Opinion in Colloid and Interface Science*. 13, 150-162.
- Manlowe, D. J. and Radke, C. J. (1990). Surfactants: Fundamentals and Applications in the Petroleum Industry. *SPE Reservoir Engineering*. 5, 495-502.

- Marsden, S. S. (1986). *Foam in Porous Media*. (1st ed.). US DOE, Washington, DC.
- Maurdev, G., Saint-Jalmes, A., and Langevin, D. (2006). Bubble Motion Measurements during Foam Drainage and Coarsening. *Journal of Colloids and Interface Science*. 300, 735-743.
- Michael, A. and Irene, A. (2004). *Handbook of Preservatives*. Synapse Info Resources. Endicoot, New York.
- Minor, M., Linde, A. J. V. D., Leeuwen, H. P. V., and Lyklema, J. (1998). Streaming Potentials and Conductivities of Porous Silica Plugs. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*. 14(2), 165-173.
- Moore, D. W. (1955). *An Experimental Investigation of Streaming Potentials in Field Drilling Muds*. MS Thesis, University of Oklahoma.
- Morgan, F. D., Williams, E. and Madden, T. R. (1989). Streaming Potential Properties of Westerly Granite with Applications . *Geophysics Research Letter*. 94, 12449-12461.
- Moulin, P. and Roques, H. (2003). Zeta Potential Measurement of Calcium Carbonate. *Journal of Colloid and Interface Science*. 261(1), 115-126.
- Mounce, W. D. and Rust, W. M. Jr. (1944). Natural Potentials in Well Logging. *Trans. AIME*. 155, 49.
- Mukerjee, P. P. and Mysels, K. J. (1971). *Critical Micelle Concentration of Aqueous Surfactant Systems*. (1st ed.). US. Government Printing Office. Washington, DC.
- Mysels, K. J., Shinoda, K., and Frankel, S. (1959). *Soap Films: Studies of Their Thinning and a Bibliography*. (1st ed.). Pergamon, New York.
- Naudet, V., Revil, A. and Bottero, J. Y. (2003). Relationship between Self-potential (SP) Signals and Redox Conditions in Contaminated Groundwater. *Geophysics Research Letter*. 30(21), 2091.

- Nourbehect, B. (1963). *Irreversible Thermodynamic Effects in Inhomogeneous Media and Their Applications in Certain Geoelectric Problems*. PhD Thesis. M.I.T.
- Nyquist, J. E. and Corry, C. E. (2002). Self-potential: The Ugly Duckling of Environmental Geophysics. *The Leading Edge*. 21, 446-451.
- Overbeek, J. T. G. (1952). *Kinetics of Flocculation*. (1st ed.). Elsevier Publishing Company.
- Papara, M., Karapantsios, T. D., and Doxastakis, G. (2006). A Novel Electrical Conductance Technique for Studying Foam Stability. *Proceedings of the 6th European Conference on Foams, Emulsions and Applications (EUROFOAM 2006)*. 2-6 July. Potsdam, Germany.
- Pavel, L. T., Moreno, R. A. and Alvarez, J. M. (2012). Micromodel Foam Flow Study. *Proceedings of the SPE Annual Technical Conference and Exhibition*. 29 September – 2 October. San Antonio, Texas.
- Peng, S. and Wu, C. (2001). Surfactant Effect on pH and Temperature Sensitivities of Poly (N-Vinylcaprolactam-co-sodium acrylate) Microgels. *Journal of American Chemical Society*. 34(3), 568-571.
- Phianmongkhol, A. and Varley, J. (1999). A Multi Point Conductivity Measurement System for Characterization of Protein Foams. *Colloids Surface B: Biointerfaces*. 12, 247-259.
- Qingfeng, H., Youyi, Z., Yousong, L., and Rui, W. (2012). Studies on Foam Flooding EOR Technique for Daqing Reservoirs After Polymer Flooding. *Proceedings of the 18th SPE Improved Oil Recovery Symposium*. 14-18 April. Tulsa, Oklahoma, USA.
- Revil, A. (1999). Ionic Diffusivity, Electrical Conductivity, Membrane and Thermoelectric Potentials in Colloids and Granular Porous Media: A Unified Model. *Journal of Colloid and Interface Science*. 212(2), 503-522.
- Revil, A. and Glover, P. W. J. (1998). Nature of Surface Electrical Conductivity in Natural Sands, Sandstones and Clays. *Geophysics Research Letter*. 25.

- Revil, A. and Leroy, P. (2001). Hydroelectric Coupling in a Clayey Materials . *Geophysics Research Letter*. 28, 1643-1646.
- Revil, A., Linde, N., Cerepi, A., Jougnot, D., Matthai, S. and Finsterle, S. (2006). Electrokinetic Coupling in Unsaturated Porous Media. *Journal of Colloid and Interface Science*. 313, 315-327.
- Rojas, Y., Kakadjian, A., Aponte, A., Marquez, R., and Sanchez, G. (2001). Stability and Rheological Behaviour of Aqueous Foams for Underbalanced Drilling. *Proceedings of the 2001 International Symposium on Oilfield Chemistry*. 13-16 February 2001. Houston, Texas.
- Rossen, W. R. (1996). *Foams in Enhanced Oil Recovery in Foams: Theory, Measurements and Application*. Prud'homme, R. K., and Khan, S. (1st ed.). New York: Marcel Dekker.
- Saint-Jalmes, A. and Langevin, D. (2002). Time Evolution of Aqueous Foams: Drainage and Coarsening. *Journal of Physics Condensate Matters*. 14, 9397-9412.
- Salleh, N. R. and Ismail, I. (2012). *The Performance of Xanthan Gum and Glass Beads as Stabilizer and Lubricant in Foam Drilling Fluid*. Bachelor Degree Thesis. Universiti Teknologi Malaysia.
- Sanchez, C. C. and Patino, J. M. R. (2005). Interfacial, Foaming and Emulsifying Characteristics of Sodium Caseinate as Influenced by Protein Concentration in Solution. *Food Hydrocolloids*. 19, 407-416.
- Sato, M. and Mooney, H. M. (1960). The Electrochemical Mechanisms of Sulphide Self-potentials. *Geophysics*. 25, 226-249.
- Saunders, J. H., Jackson, M. D., and Pain, C. C. (2006). A New Numerical Model of Electrokinetic Potential Response during Hydrocarbon Recovery. *Geophysical Research Letters*. 33, 1029.
- Saunders, J. H., Jackson, M. D., and Pain, C. C. (2008). Fluid Flow Monitoring in Oilfields using Downhole Measurements of Electrokinetic Potential. *Geophysics*. 73, 1190.

- Schlumberger (1989). *Spontaneous Potential and Natural Gamma Ray Logs, Log Interpretation Principles/Applications*. (1st ed.). Schlumberger Educational Services, Houston, Texas.
- Schlumberger, C. and Leonardon, E. G. (1934). Electrical Exploration of Water-Covered Areas. *Transactions of the American Institute of Mining and Metallurgical Engineers*. 110, 122-134.
- Schramm, L. L. (2000). *Surfactants: Fundamentals and Applications in the Petroleum Industry*. (1st ed.). Cambridge, United Kingdom: Cambridge University Press.
- Schramm, L.L. and Wassmuth, F. (1994). *Foams: Basic Principles in Foams: Fundamentals & Applications in the Petroleum Industry*. (1st ed.). Washington, D.C: American Chemical Society Publications.
- Shaw, J. D. (1992). *Introduction to Colloid and Surface Chemistry*. (4th ed.). Oxford: Butterworth Heinemann.
- Sill, W. R. (1983). Self-potential Modelling from primary Flows. *Geophysics*. 48, 76-86.
- Simjoo, M., Dong, Y., Andrianov, A., Talanana, M., and Zitha, P. L. J. (2012). Novel Insight into Foam Mobility Control. *Proceedings of the International Petroleum Technology Conference*. 7-9 February. Bangkok, Thailand
- Skauge, A., Aarra, M. G., Surhuchev, L., Martinsen, H. A., and Rasmussen, L. (2002). Foam-assisted WAG: Experience from the Snorre Field. *Proceedings of the 2002 SPE/DOE Improved Oil Recovery Symposium*. 13-17 April. Tulsa, Oklahoma, USA.
- Sparnaay, M. J. (1972). *The Electrical Double Layer: Properties of Interfaces*. (1st ed.). Pergaman Press, Oxford.
- Stool, J., Bigalke, J. and Grabner, E. W. (1995). Electrochemical Modelling of Self-potential Anomalies. *Surveys in Geophysics*. 16, 107-120.

- Tiab, D. and Donaldson, E. C. (2003). *Petrophysics: Theory and Practise of Measuring Reservoir Rock and Fluid Transport Properties*. (1st ed.). Gulf Professional Publishing.
- Tunio, S. Q. and Chandio, T. A. (2012). Recovery Enhancement with Application of FAWAG for a Malaysian Field. *Journal of Applied Sciences, Engineering and Technique*. 4(1), 8-10.
- Turta, A. T. and Singhal, A. K. (1998). Field Foam Applications in Enhanced Oil Projects: Screening and Design Aspects. *Proceedings of the 1998 SPE International Oil and Gas Conference and Exhibition*. 2-6 November. Beijing, China.
- Turta, A. T. and Singhal, A. K. (2002). Field Foam Applications in Enhanced Oil Recovery Projects: Screening and Design Aspects. *Journal of Canadian Petroleum Technology*. 41(10).
- Vaidya, R. N. and Fogler, H. S. (1990). Formation Damage Due to Colloidally Induced Fines Migration. *Colloids and Surfaces*. 50, 215-229.
- Wang, M. and Cilliers, J. J. (1999). Detecting Non-Uniform Foam density using Electrical resistance Tomography. *Chemical Engineering Science*. 54, 707-712.
- Weaire, D. and Hutzler, S. (1999). *The Physics of Foams*. (1st ed.). Oxford:Oxford University Press.
- Weaire, D., Findlay, S., and Verbist, G. (1995). Measurement of Foam Drainage Using AC Conductivity. *Journal of Physics Condensed Matter*. 7(16), L217-L222.
- Weaire, D., Hutzler, S., Verbist, G., and Peters, E. (1997). A Review of Foam Drainage. *Advances in Chemical Physics*. 102, 315-374.
- Wiggers, F. N., Deshpande, N. S., and Barigou, M. (2000). The Flow of Foam in Vertical Tubes. *Trans Institution of Chemical Engineers*. 78, Part A.
- Wilbert, M. C., Delagah, S. and Pallegirino, J. (1999). Variance of Streaming Potential Measurements. *Journal of Membrane Science*. 161, 247-261.

- Wilde, P. J. (1996). Foam Measurement by the Microconductivity Technique: An Assessment of Its Sensitivity to Interfacial and Environmental Factors. *Journal of Colloid and Interface Science*. 178, 733-739.
- Wilkes, R. B. (1998). Foam Displacement Modelling in CO₂ Flooding Processes. *Proceedings of the 1998 SPE/DOE Tenth Symposium of Improved Oil Recovery*. 21-24 April. Tulsa, OK.
- Wright, D. J. and Hemmant, W. (1987). Foaming of Protein Solutions: Comparison of Large-Scale Whipping and Conductimetric Methods. *Journal of Food Science*. 35, 361-371.
- Wu, C. H. (1983). Modelling Foam Displacement with the Local Equilibrium Approximation. *SPE Journal*. 34, 171-183.
- Wyllie, M. R. J. (1952). An Investigation of Electrokinetic Component of the Self-potential Curve. *Trans. AIME*. 192, 1.
- Wyllie, M. R. J. (1963). *The Fundamental of Electric Log Interpretation*. (1st ed.). Academic Press, New York.
- Yamanaka, T., Tano, T., Kamegaya, O., Exerowa, D., and Cohen, R. D. (1994). Effects of Metal Ions on the Equilibrium Thicknesses of Foam Films Stabilized by Lysophosphatidylcholine as Studied by FT-IR Spectroscopy. *Journal of Langmuir*. 10(6), 1871-1876.
- Yang, K. L., Yiacoumi, S. and Tsouris, C. (2004). *Electrical Double-Layer Formation*. (1st ed.). Taylor and Francis, London.
- Yang, Y., Zhang, Q., Wang, T. and Yang, Y. (2013). Determination of the Critical Micelle Concentration of Sodium Dodecyl Sulphate in Aqueous Solution in the Presence of an Organic Additive of Acetonitrile by Conductometry and an Inorganic Additive of Phosphate by Fluorometry. *Asian Journal of Chemistry*. 25(12), 6657-6660.
- Zanganeh, M. N. and Rossen, W. (2013). Optimization of Foam Enhanced Oil Recovery: Balancing Sweep and Injectivity. *SPE Reservoir and Engineering*. 16,1.

Zhang, S., Moskalenko, C., Berguiga, L., Elezgaray, J. and Argoul, F. (2007). Gouy Diffuse Layer Modelling in Phosphate Buffers. *Journal of Electroanalytical Chemistry*. 603, 107-112.

Zitha, P.L.J., Nguyen, Q. P., Currie, P. K., and Buijse, M. A. (2006). Coupling of Foam Drainage and Viscous Fingering in Porous Media Revealed by X-ray Computed Tomography. *Transport in Porous Media*. 64(3), 301-313.