

CHARACTERIZATION OF MULTIWALLED CARBON NANOTUBES BY DC
ARC DISCHARGE IN METHANE UNDER MAGNETIC FIELD INFLUENCE

ZULKIFLI BIN AZMAN

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Master of Engineering (Electrical)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

MARCH 2018

Specially dedicated to my wife, kids, parents and family.
Thank you for your sacrifice, patient and *dua*’.
May Allah grant all of us Jannah.

ACKNOWLEDGEMENT

In the name of Allah, the Most of Gracious, and the Most of Merciful. Alhamdulillah, thanks to Allah with the strength and patience given, this research was successfully completed as planned.

High appreciation to the key people in helping me completing this works especially my project supervisor, Assoc. Professor. Dr. Zokafle Bin Buntat, the one who always gives guidance, encourages, and helps from any aspects. I really appreciate that. To my family who always giving motivation, helps and *dua*', especially my wife, Norain Binti Sahari, kids, parents and family from both sides. Thank you for your support and understanding.

To all colleagues which helping either direct or indirectly. Piah, Alia, Izzah, Helmi, Bella, Yana, Zainab and others, all of you are really wonderful friends. Thanks to IVAT's technical staff for helping in experimental setup and always ensure the works run smoothly with highest safety precaution. Special thanks to UIRL's and MiNT's staff which helping in analysing the research outcomes.

Finally, thanks to Dr. Abu Bakar Suleiman, Aizat, Dr. Feri, Kusnanto, Mr. Hisham Walat, lecturers and individuals which contribute ideas, material resources, motivations, as well as advise in completing this study. Thank you very much. May Allah bless and forgive all our sins and grant all of us His Jannah. Insha'Allah.

ABSTRACT

Carbon nanotubes (CNTs) have gained many interest among researchers over the last two decades due to its remarkable mechanical, electrical, optical and thermal properties. High quality CNTs are in demand especially for application in nano electronics where CNTs are required to be in high crystallinity, straight and aligned orientation, having uniform diameter and less impurities to achieve the best performance. Literally, hydrogen gas is reported as the best buffer gas in producing high crystallinity and less impurities attached to CNTs by arc discharge method. However, it is not suitable for large scale CNTs synthesis due to unstable plasma formation. Recently, methane gas which contains hydrogen atoms is being studied in producing multiwalled carbon nanotubes (MWCNTs). This leads to the opportunity of investigating methane as buffer gas in producing high quality CNTs. On the other hand, the usage of magnetic field in arc discharge has been reported to have the ability to enhance the quality of CNTs in terms of narrow and uniform diameter as well as reducing impurities. Thus, this work presents a comparative study on the effect of three different arc discharge configurations to the yield of MWCNTs in methane environment. The first configuration known as Configuration A where no magnetic field assistance during CNTs arc discharge synthesis. Configuration B utilises four (4) magnets which are placed surrounding inter electrode gap while two (2) magnets are placed at anode for Configuration C. Arc discharge is generated at fixed 750 mbar of chamber pressure and fixed current about 60 A in the voltage range of 30 ~ 32 V. As a result, needle like shapes with straight orientation of individual MWCNTs for all configurations is observed under Scanning Electron Microscope. Narrow diameters are observed in configuration B with standard deviation of 2.71 nm followed by configuration C of 5.7 nm and configuration A of 8.05 nm. The results show the influence of magnetic field in producing MWCNTs with narrow and uniform diameter compared to no magnetic field assistance. The diameter distribution trend is confirmed by X-Ray powder diffraction results. High crystalline MWCNTs is confirmed by Transmission Electron Microscope images for configuration B with uniform MWCNTs inner diameter at average 2 nm. Raman spectrum shows low ratio of D band intensity over G band intensity at 0.53 for configuration B while configuration A at 0.79 which suggest fewer wall defects of MWCNTs produced in configuration B. Therefore, magnetic field assistance in methane arc discharge is proved to produce smaller and uniform diameter of MWCNTs with less wall defects. MWCNTs produced in this study can be further investigated in nanoelectronics applications such as nanowires and conductive nanofiller

ABSTRAK

Nanotub karbon (CNTs) telah menarik minat di kalangan para penyelidik dalam tempoh dua dekad yang lalu disebabkan oleh ciri-ciri mekanikal, elektrik, optik dan termal yang luar biasa. CNTs berkualiti tinggi diperlukan terutamanya untuk aplikasi nanoelektronik di mana CNTs perlu mempunyai kehabluran yang tinggi, orientasi lurus dan sejajar, mempunyai diameter seragam dan kurang bendasing untuk memperoleh prestasi terbaik. Secara harfiah, gas hidrogen dilaporkan sebagai yang terbaik dalam menghasilkan kehabluran yang tinggi dan kurang bendasing yang melekat pada CNTs dengan kaedah discas arka. Walau bagaimanapun, ia tidak sesuai untuk sintesis CNTs berskala besar disebabkan pembentukan plasma yang tidak stabil. Baru-baru ini, gas metana yang mengandungi atom hidrogen mula dikaji dalam menghasilkan nanotub karbon berbilang lapisan (MWCNTs). Ini membuka peluang kepada penyiataan metana sebagai gas penampakan dalam menghasilkan CNTs berkualiti tinggi. Sebaliknya, penggunaan medan magnet dalam discas arka dilaporkan mempunyai keupayaan untuk meningkatkan kualiti CNTs dari segi pengecilan diameter yang seragam serta mengurangkan bendasing. Oleh itu, kerja ini membentangkan perbandingan kesan medan magnet pada tiga konfigurasi berbeza terhadap penghasilan MWCNTs dalam persekitaran metana. Konfigurasi pertama disebut konfigurasi A di mana tiada sokongan medan magnet dalam penghasilan CNTs. Konfigurasi B menggunakan empat (4) magnet yang diletak sekeliling pembahagi antara elektrod sementara dua (2) magnet diletakkan pada anod sebagai Konfigurasi C. Discas arka dilakukan pada tekanan tetap 750 mbar dan arus tetap pada 60 A dalam julat voltan 30 ~ 32V. Hasilnya, imej *Scanning Electron Microscope* menunjukkan MWCNTs dihasilkan berbentuk jarum dengan orientasi lurus untuk semua konfigurasi. Diameter kecil diperhatikan dalam konfigurasi B dengan sisihan piawai pada 2.71 nm. Diikuti konfigurasi C pada 5.7 nm dan konfigurasi A pada 8.05 nm yang menunjukkan pengaruh medan magnet dalam penghasilan MWCNTs dengan diameter kecil dan seragam berbanding tanpa medan magnet. Ianya juga dibuktikan dengan data *X-Ray powder diffraction* (XRD). Kehabluran MWCNTs yang tinggi dapat dilihat pada imej *Transmission Electron Microscope* untuk Konfigurasi B dengan diameter dalaman MWCNTs seragam pada purata 2 nm. Spektrum Raman menunjukkan nisbah intensiti jalur D terhadap intensiti jalur G yang rendah pada 0.53 bagi Konfigurasi B berbanding tanpa medan magnet pada 0.79 bagi Konfigurasi A menunjukkan kurang kerosakan pada dinding MWCNTs yang dihasilkan dalam Konfigurasi B. Oleh itu, dengan sokongan medan magnet dalam discas arka metana telah terbukti menghasilkan diameter MWCNTs yang kecil dan seragam serta kurang kerosakan pada dindingnya. MWCNTs yang dihasilkan dalam kajian ini boleh dikaji lebih lanjut untuk aplikasi nanoelektronik seperti wayar nano dan pengisi nano yang bersifat konduktif.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATION	xv
	LIST OF SYMBOLS	xvii
	LIST OF APPENDICES	xviii
1	INTRODUCTION	1
	1.1 Background of Study	1
	1.2 Problem Statement	3
	1.3 Research Objectives	5
	1.4 Scope of Project	5
	1.5 Thesis Layout	6
2	LITERATURE REVIEW	7
	2.1 Introduction to Carbon Nanotubes	7
	2.2 Types of Carbon Nanotubes	8
	2.2.1 Single Walled Carbon Nanotubes	9
	2.2.2 Multi Walled Carbon Nanotubes	11

2.3	Carbon Nanotubes Properties	12
2.3.1	Electrical and Electronics Properties	12
2.3.2	Mechanical Properties	13
2.3.4	Thermal Properties	14
2.4	Synthesis Methods of Carbon Nanotubes	14
2.4.1	Chemical Vapour Deposition	14
2.4.2	Laser Ablation	15
2.4.3	Arc Discharge	16
2.5	Influence of the Arc Discharge Parameter on CNT Growth	18
2.5.1	Buffer Gas	19
2.5.2	DC, AC or Pulse Power Supply	20
2.5.3	Arc Current	23
2.5.4	Arc Voltage	23
2.5.5	Carbon Precursor	24
2.5.6	External Magnetic Field	25
2.6	Common CNT Characterization Methods	27
2.6.1	Transmission Electron Microscopy (TEM)	27
2.6.2	Scanning Electron Microscopy (SEM)	28
2.6.3	X-Ray Powder Diffraction	29
2.6.4	Raman Spectroscopy	30
3	METHODOLOGY	33
3.1	Introduction	33
3.2	Arc Discharge System Design and Fabrication	35
3.3	Experimental Setup	37
3.3.1	Simulation of Magnetic Field Distribution	38
3.3.1.1	Configuration B - Four Magnets Surrounding Interelectrode Gap	38
3.3.1.2	Configuration C - Two Magnets Place at Anode	40

3.3.2	Apparatus Arrangement and Experimental Procedures	43
3.3.2.1	Apparatus Arrangement	44
3.3.2.2	Experimental Procedures	44
3.4	Post Synthesis: MWCNTs Characterization Method	46
3.4.1	Scanning Electron Microscope	47
3.4.2	Transmission Electron Microscope	48
3.4.3	X-Ray Powder Diffraction	49
3.4.4	Raman Spectroscopy	50
4	RESULTS AND DISCUSSION	52
4.1	Introduction	52
4.2	Arc Plasma Formation	53
4.3	Carbon Deposits	56
4.4	MWCNTs Morphology by SEM and TEM	57
4.4.1	Scanning Electron Microscopy Analysis	57
4.4.2	Transmission Electron Microscopy Analysis	68
4.5	Diameter and Crystallinity Assessments by XRD	77
4.6	Wall Defect and MWCNTs Quality Assessments	85
4.7	Summary	89
5	CONCLUSION AND RECOMMENDATION	91
5.1	Conclusion of Study	91
5.2	Contribution of Works	93
5.3	Recommendation for Future Work	94
	References	95
	Appendices A – F	101-106

LIST OF TABLES

TABLE NO.	TITLE	PAGE
3.1	Parameters in arc discharge MWCNTs synthesis	38
4.1	Summary of CNTs produced in all configurations based on SEM micrograph	66
4.2	Summarized of important parameters in XRD	84

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Structure of carbon allotropes	8
2.2	TEM image of SWCNTs	10
2.3	Schematic diagram of zigzag, chiral and armchair CNTs	10
2.4	TEM image of MWCNTs	11
2.5	Schematic representation for CNTs synthesized using CVD	15
2.6	Schematic representation for CNTs synthesized using laser ablation	16
2.7	Schematic representation for CNTs synthesized using arc discharge	18
2.8	Schematic of CNTs formation using different power supply (a) DC, (b) AC and (c) Pulse power supply [10]	21
2.9	SEM images of MWCNTs produced with (a) and without (b) magnetic field [15]	25
2.10	Schematic figure of magnetic field configuration and photographs of the arc without/with magnetic field. [70]	26
2.11	TEM images of as-synthesized CNTs without (a) and with (b) magnetic field [70]	26
2.12	Image of TEM equipment with schematic of TEM basic principle	28
2.13	Image of SEM machine with schematic diagram of its basic principle operation	28

2.14	Image of XRD machine and Bragg's Law derivation	30
2.15	Example of Raman Spectrometer setup and principle of operation	31
3.1	Overall process flow chart	34
3.2	Stainless steel arc discharge chamber	35
3.3	Pure graphite electrodes, anode (left) and cathode (right)	36
3.4	PWM controller with DPDT switch	36
3.5	Schematic diagram of arc discharge system	37
3.6	Schematic diagram of Configuration B	39
3.7	Configuration B (a) magnets holder assembly, (b) inside arc discharge chamber, and (c) magnetic field distribution	40
3.8	Schematic diagram of configuration C	41
3.9	Configuration C (a) illustration of cross-section, (b) inside arc discharge chamber, and (c) magnetic field distribution	42
3.10	Apparatus setup of DC arc discharge CNT synthesis	43
3.11	Carbon deposited at cathode tip	46
3.12	Scanning Electron Microscope (Carl Zeiss Supra 35VP)	47
3.13	Transmission Electron Microscope (Hitachi HT7700)	48
3.14	Fisher Scientific FB15051 Sonic Bath and (inset) 0.8mg/ml sample solution	49
3.15	Rigaku Smart Lab X-Ray Diffractometer	50
3.16	Raman Spectroscopy (HORIBA Xplora Plus)	51
4.1	Formation of arc plasma starts from initial stage, middle stage and final stage (left to right)	53

4.2	Voltage and current response during arc discharge MWCNTs synthesis (a) configuration A, (b) configuration B and (c) configuration C	55
4.3	Average of arc current and average of arc voltage	55
4.4	Carbon deposits (a) configuration A, (b) configuration B, and (c) configuration C	56
4.5	SEM micrograph of CNTs grown in configuration A (a) – (d) at various locations	59
4.6	SEM micrograph of CNTs grown in configuration B (a) – (d) at various locations	62
4.7	SEM micrograph of CNTs grown in configuration C (a) – (d) at various locations	64
4.8	Graphical representation of MWCNTs grown in configuration A, B and C	65
4.9	Diameter distribution of MWCNTs grown in configuration A estimated by SEM	67
4.10	Diameter distribution of MWCNTs grown in configuration B estimated by SEM	67
4.11	Diameter distribution of MWCNTs grown in configuration C estimated by SEM	68
4.12	TEM micrograph of MWCNTs grown in configuration A (a) – (e) MWCNTs images at various locations	70
4.13	TEM micrograph of MWCNTs grown in configuration B (a) – (e) images of MWCNTs at various locations	71
4.14	TEM micrograph of MWCNTs grown in configuration C (a) – (e) images of MWCNTs at various locations	73
4.15	Diameter distribution of MWCNTs grown in configuration A (a) outer and (b) inner diameter	74
4.16	Diameter distribution of MWCNTs grown in configuration B (a) outer and (b) inner diameter	75

4.17	Diameter distribution of MWCNTs grown in configuration C (a) outer and (b) inner diameter	76
4.18	Defects and non-uniform interlayer spacing of MWCNTs in configuration A	77
4.19	XRD pattern for MWCNTs in configuration A; (a) highest peak with Miller indices and (b) curve fitting by Lorentzian method	78
4.20	XRD pattern for MWCNTs in configuration B (a) highest peak with Miller indices and (b) curve fitting by Lorentzian method	80
4.21	XRD pattern for MWCNTs in configuration C (a) highest peak with Miller indices and (b) curve fitting by Lorentzian method	81
4.22	Angle position of 002 peak for each configuration	82
4.23	FWHM variation	83
4.24	Average crystallite size calculated from XRD data	84
4.25	Average crystallite size by SEM, TEM and XRD with respect to each configuration	85
4.26	Raman spectra for MWCNTs in configuration A	86
4.27	Raman spectra for MWCNTs in configuration B	87
4.28	Raman spectra for MWCNTs in configuration C	88
4.29	Waterfall graph of Raman Spectrum for all configuration	88
4.30	I_D/I_G ratio for configuration A, B, and C	89

LIST OF ABBREVIATION

CNTs	- Carbon Nanotubes
MWCNTs	- Multiwalled Carbon Nanotubes
SWCNTs	- Single Walled Carbon Nanotubes
CH ₄	- Methane
DC	- Direct Current
A	- Ampere
NdFeb	- Neodymium
PWM	- Pulse Width Modulator
SEM	- Scanning Electron Microscopy
TEM	- Transmission Electron Microscopy
XRD	- X-Ray Powder Diffraction
MHz	- Mega Hertz
AFM	- Atomic Force Microscopy
1D	- One Dimensional
CVD	- Chemical Vapour Deposition
AC	- Alternating Current
Co	- Cobalt
Ni	- Nickel
Fe	- Ferum
C	- Carbon
He	- Helium

Ar	- Argon
DWCNTs	- Double Walled Carbon Nanotubes
N ₂	- Nitrogen
H ₂	- Hydrogen
CNF	- Carbon Nanofiber
CCD	- Charge Coupled Device
DPDT	- Double Pole Double Throw
FEMM	- Finite Element Method Magnetic
RMS	- Root Mean Square
FWHM	- Full Width at Half Maximum
RBM	- Radial Breath Mode

LIST OF SYMBOLS

%	- Percentage
K	- Kelvin
°C	- Celsius
D_v	- Average nano-crystallite size
λ	- Radiation wavelength
θ	- Angle of XRD peak
ω	- Vibrational frequency

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Methane – Safety Data Sheet	101
B	Ethanol – Safety Data Sheet	102
C	Weldon IA2500 – Specification	103
D	Linear Actuator – Product Information	104
E	K&J MAGNETIC, INC – DX08BR-N52	105
F	K&J MAGNETIC, INC – RX054BR-N52	106

CHAPTER 1

INTRODUCTION

1.1 Background of Study

In modern science nowadays, extensive research on nanotechnology is rapidly growing. The application of nanotechnology is in wide areas such as agriculture, food processing, cosmetic, electronics, astronomy research, military technology for defence, etc. All electronic devices nowadays getting smaller yet their performance cannot be compromised. Thus, nanomaterial studies always become important among researchers to improve daily life routine by nanotechnology implementation especially in electronics application.

Carbon nanotubes, (CNTs) often said as one of promising nanoscale material in electronics application to be used as nanowires, sensing element, optoelectronic devices, field emitter for display, and transistor channel [1-3]. CNTs being investigated in the past 20 years since founded by Japanese scientist, Sumio Iijima in 1991 [4]. During that time, arc discharge was the first method known to produce CNTs. A few years later, CNTs was successfully produced by chemical vapour deposition and laser ablation method [5, 6]. Among them, arc discharge is considered the best method in producing high crystalline CNTs with fewer defects whilst not producing hazardous toxic gas and considered as an environmental friendly method in producing CNTs [7-9].

Basically, arc discharge is electrical breakdown phenomena which resulting the creation of hot plasma due to high current. In CNTs synthesis application, arc discharge system consists of two electrodes acting as anode and cathode, power supply and carbon precursor such as pure graphite which actually acting as anode for anodic arc discharge. It can be happening in tight chamber filled with certain gas at certain pressure as well as in liquid environment by submerged both anode and cathode. However, the large number of reports found to produced CNTs in tight chamber filled with certain gas [10].

In arc discharge method, both electrodes (anode and cathode) was brought to contact at initial stage allow for current flowing, causing resistive heating that increases electrode temperature [10]. Sudden change of interelectrode gap led to electrical breakdown in gaseous environment hence resulting the formation of plasma between electrodes. The stability of plasma corresponds to the stability of anode and cathode voltage which related to interelectrode gap. This continuous hot plasma formation converts the carbon precursor into carbon vapour state. The basic fundamental of CNTs growth in arc discharge is the phase change of carbon precursor from solid to carbon vapour and then turn to liquid state before solidify again and stick at cathode tip which much cooler compared to anode. The carbon deposited at cathode tip usually contain CNTs.

Several arc discharge parameters were taken into account in producing CNTs in better yield such as arc current, arc voltage, type of gas, chamber pressure, type of power supply, catalyst used, shape and type of electrodes as well as carbon precursor itself. The variation of these parameters has gone through along the past 20 years to understand the optimal condition in producing CNTs in high quality and high quantity. Until this report is written, both studies on the synthesis and application of CNTs still running in parallel however, there is still much more to be understood in the production of quality CNTs by arc discharge method. A lot of improvement has been achieved yet there is still a gap in academic research field to produce much better CNTs as required to be used efficiently in electronics application that need specific structure, diameter and length of CNTs.

In the beginning, CNTs was grown in Argon environment at 100 Torr of chamber pressure [4]. Since then, other types of gases being investigated to evaluate the yield of CNTs produce. Different types of gases have different ionization potential and have unique thermal characteristic which plays important role in achieving breakdown condition hence led to formation of plasma. Due to its highest thermal conductivity, Hydrogen is said as the best gas for promoting the growth of CNTs with less carbonaceous materials [7]. However, in large scale CNTs production, it was found that Hydrogen is difficult to control due to unstable plasma formation [11]. Thus, most of works later reported using Helium tested at various parameters. Other gases have been investigated including Nitrogen, Air, and hydrocarbon such as Methane, CH₄ [12-14]. However, only a few works reported conducting arc discharge CNTs synthesis with hydrocarbon as buffer gas. Limited reports on the use of hydrocarbons in the production of CNTs by arc discharge method have opened up opportunity for researchers to explore more on the capabilities of hydrocarbon in producing good quality CNTs.

The external magnetic field introduced in arc discharge CNTs synthesis reported increases the yield of CNTs [15-17]. It has been confirmed that plasma confinement and other plasma parameters in arc discharge can be controlled by magnetic field [18]. Thus, the exploitation of magnetic field in assisting CNTs synthesis is worth to be expanded and understandable in combination with other arc discharge CNTs parameters such as type of gas and pressure, arc voltage and arc current as well as carbon precursor. Types of magnet, configuration and magnetic strength also play important role to the formation of stable confined plasma and hence producing better quality of CNTs.

1.2 Problem Statement

In electronics application, Single Walled Carbon Nanotubes (SWCNTs) often gets more attention due to its remarkable electronics properties where it can demonstrate both metallic and semiconducting behaviour depend on its chirality.

Multi Walled Carbon Nanotubes (MWCNTs) is said to always exhibit metallic behaviour. However, it also demanded for many applications such as flat panel display, electron source in cathode ray tube, individual nanoprobe, high brightness beam in electron microscope, nanoscale X-Ray source and nanoscale linear bearings [19-24].

Basically, there are three usually employed methods in synthesis MWCNTs. The three methods are chemical vapour deposition, laser ablation and arc discharge methods. Among three of them, arc discharge is said capable of producing well graphitized MWCNTs [25, 26] . Moreover, arc discharge does not require metal catalyst in synthesis MWCNTs. Previously, hydrogen was claimed by Zhao et al. as the best gas in producing high quality MWCNTs by arc discharge method [27]. However, it was not suitable for large scale production due to unstable plasma formation [28]. As option, Ando et al. suggested the use of CH₄ in synthesising MWCNTs since the decomposition of hydrogen atom contained in CH₄ molecules produces high crystallinity MWCNTs [29]. More recently, there is a work also uses CH₄ as buffer gas at various chamber pressures with different arc currents [14].

In order to fulfil demand for high quality MWCNTs to well suit to the application mentioned above, high crystallinity MWCNTs with uniform diameter formed in well-arranged and straight structure are required. Many reports have mentioned the use of magnetic field in arc discharge has improved the yield of SWCNTs in term of high crystallinity, high quantity, increasing the length and narrows down the diameter of SWCNTs [16, 17, 30-32]. A few works reported of producing less impurities in MWCNTs with magnetic field assistance [15, 33]. To the best of the author's knowledge, there is no report on the production of high crystallinity MWCNTs with uniform diameter formed in well-arranged structure by arc discharge method. Thus, this work presents the effect of combination magnetic field and CH₄ to the diameter distribution, quantity, high crystallinity, structural defect, shape and orientation as well as impurity level of MWCNTs produced.

1.3 Research Objectives

Based on problem statement and current situation, three research objectives have been defined as in the following:

- i. To investigate the effect of magnetic field in different configurations to diameter distribution of MWCNTs grown by DC arc discharge in CH₄.
- ii. To investigate the influence of combination of magnetic field and CH₄ in producing high crystallinity and less defect of MWCNTs structure.
- iii. To learn the ability of magnetic field in controlling the shape and orientation of MWCNTs produced in CH₄ environment.

1.4 Scope of Project

In order to fulfil project timeline while successfully achieving all three objectives, the research parameters are confined as mention in the following:

- i. MWCNTs grown in CH₄ environment at fixed 750 mbar of chamber pressure.
- ii. Arc discharge controlled at fixed 60A of DC current for all configurations (with and without magnetic field assistance).
- iii. The magnets used are Neodymium, (NdFeB) permanent magnet in grade N52 with axially magnetized direction.
- iv. All CNTs synthesis experiment last at approximately 60 seconds.
- v. Interelectrode gap distance maintained manually by Pulse Width Modulator, PWM linear motor controller.
- vi. High purity graphite (99.99%) were used as anode and cathode.
- vii. CNTs were characterized by Scanning Electron Microscopy, Transmission Electron Microscopy, X-Ray powder diffraction, Raman Spectroscopy.

1.5 Thesis Layout

This thesis consists of five chapters which explained as follows:

Chapter 1 starts with the background study to introduce briefly about the subject under study. The problem statement described in this chapter to highlight the gap in recent works related to synthesis of CNTs by arc discharge method, the effect of magnetic field in CNTs formation as well as the gas has been used as buffer gas. This chapter also highlights the objectives of study as well as research scopes.

Chapter 2 explains the introduction of CNTs to give understanding about the core material which being under study. Three main methods in producing CNTs also described. In this chapter, previous works from other researcher related to synthesis of CNTs by arc discharge method with magnetic field assisted, growth of CNTs in various buffer gas as well as the effect of buffer gas in CNTs production by arc discharge method are presented. As additional, common characterization methods of CNTs in also included.

In Chapter 3, the research methodology is presented. The detail on experimental setup, magnetic field configuration study, equipment used as well as the experimental procedure are described. The overall research works are graphically illustrated in a process flow chart for ease of understanding. Preparation and steps taken for CNTs characterization and analysis are also discussed.

Experimental results are presented in Chapter 4. In this chapter, characterization of CNTs produced are explained and discussed. The results were including morphology of CNTs analysed by Scanning Electron Microscopy, and TEM, spectroscopic analysis by Raman Spectrometer and crystalline structure study analysed by XRD method.

Finally, Chapter 5 gives the conclusion of the findings in Chapter 4. It also highlights the contribution of the research work based on results achieved as well as recommendation related to this topic for future research.

REFERENCES

1. C. Stampfer, E. Schurtenberger, F. Molitor, J. Guttinger, T. Ihn, and K. Ensslin, "Tunable graphene single electron transistor," *Nano letters*, vol. 8, pp. 2378-2383, 2008.
2. J. Kong, N. R. Franklin, C. Zhou, M. G. Chapline, S. Peng, K. Cho, *et al.*, "Nanotube molecular wires as chemical sensors," *science*, vol. 287, pp. 622-625, 2000.
3. P. R. Bandaru, "Electrical properties and applications of carbon nanotube structures," *Journal of nanoscience and nanotechnology*, vol. 7, pp. 1239-1267, 2007.
4. S. Iijima, "Helical microtubules of graphitic carbon," *nature*, vol. 354, p. 56, 1991.
5. S. Hofmann, C. Ducati, J. Robertson, and B. Kleinsorge, "Low-temperature growth of carbon nanotubes by plasma-enhanced chemical vapor deposition," *Applied Physics Letters*, vol. 83, pp. 135-137, 2003.
6. P. Nikolaev, "Catalytic growth of single-walled nanotubes by laser vaporization," Rice University, 1996.
7. M. Jinno, S. Bandow, and Y. Ando, "Multiwalled carbon nanotubes produced by direct current arc discharge in hydrogen gas," *Chemical physics letters*, vol. 398, pp. 256-259, 2004.
8. Z. Wang, N. Li, Z. Shi, and Z. Gu, "Low-cost and large-scale synthesis of graphene nanosheets by arc discharge in air," *Nanotechnology*, vol. 21, p. 175602, 2010.
9. M. Keidar, A. Shashurin, J. Li, O. Volotskova, M. Kundrapu, and T. S. Zhuang, "Arc plasma synthesis of carbon nanostructures: where is the frontier?," *Journal of Physics D: Applied Physics*, vol. 44, p. 174006, 2011.
10. N. Arora and N. Sharma, "Arc discharge synthesis of carbon nanotubes: Comprehensive review," *Diamond and related materials*, vol. 50, pp. 135-150, 2014.
11. X. Zhao, S. Inoue, M. Jinno, T. Suzuki, and Y. Ando, "Macroscopic oriented web of single-wall carbon nanotubes," *Chemical physics letters*, vol. 373, pp. 266-271, 2003.
12. S. Cui, P. Scharff, C. Siegmund, D. Schneider, K. Risch, S. Klötzer, *et al.*, "Investigation on preparation of multiwalled carbon nanotubes by DC arc discharge under N₂ atmosphere," *Carbon*, vol. 42, pp. 931-939, 2004.
13. H. H. Kim and H. J. Kim, "Preparation of carbon nanotubes by DC arc discharge process under reduced pressure in an air atmosphere," *Materials Science and Engineering: B*, vol. 133, pp. 241-244, 2006.

14. K. Chaudhary, Z. Rizvi, K. Bhatti, J. Ali, and P. Yupapin, "Multiwalled carbon nanotube synthesis using arc discharge with hydrocarbon as feedstock," *Journal of Nanomaterials*, vol. 2013, p. 145, 2013.
15. K. Anazawa, K. Shimotani, C. Manabe, H. Watanabe, and M. Shimizu, "High-purity carbon nanotubes synthesis method by an arc discharging in magnetic field," *Applied Physics Letters*, vol. 81, pp. 739-741, 2002.
16. M. Keidar, I. Levchenko, T. Arbel, M. Alexander, A. M. Waas, and K. Ostrikov, "Increasing the length of single-wall carbon nanotubes in a magnetically enhanced arc discharge," *Applied Physics Letters*, vol. 92, p. 043129, 2008.
17. M. Keidar, I. Levchenko, T. Arbel, M. Alexander, A. M. Waas, and K. K. Ostrikov, "Magnetic-field-enhanced synthesis of single-wall carbon nanotubes in arc discharge," *Journal of Applied Physics*, vol. 103, p. 094318, 2008.
18. M. Keidar, I. Beilis, R. Boxman, and S. Goldsmith, "2D expansion of the low-density interelectrode vacuum arc plasma jet in an axial magnetic field," *Journal of Physics D: Applied Physics*, vol. 29, p. 1973, 1996.
19. Y. Saito and S. Uemura, "Field emission from carbon nanotubes and its application to electron sources," *Carbon*, vol. 38, pp. 169-182, 2000.
20. Y. Saito, S. Uemura, and K. Hamaguchi, "Cathode ray tube lighting elements with carbon nanotube field emitters," *Japanese Journal of Applied Physics*, vol. 37, p. L346, 1998.
21. H. Dai, J. H. Hafner, A. G. Rinzler, D. T. Colbert, and R. E. Smalley, "Nanotubes as nanoprobe in scanning probe microscopy," *Nature*, vol. 384, p. 147, 1996.
22. N. De Jonge, Y. Lamy, K. Schoots, and T. H. Oosterkamp, "High brightness electron beam from a multi-walled carbon nanotube," *Nature*, vol. 420, p. 393, 2002.
23. H. Sugie, M. Tanemura, V. Filip, K. Iwata, K. Takahashi, and F. Okuyama, "Carbon nanotubes as electron source in an x-ray tube," *Applied Physics Letters*, vol. 78, pp. 2578-2580, 2001.
24. J. Cumings and A. Zettl, "Low-friction nanoscale linear bearing realized from multiwall carbon nanotubes," *Science*, vol. 289, pp. 602-604, 2000.
25. Y. Ando and S. Iijima, "Preparation of carbon nanotubes by arc-discharge evaporation," *JAPANESE JOURNAL OF APPLIED PHYSICS PART 2 LETTERS*, vol. 32, pp. L107-L107, 1993.
26. T. Ebbesen and A. P M, "Large-scale synthesis of carbon," *Nature*, vol. 358, p. 16, 1992.
27. X. Zhao, M. Ohkohchi, M. Wang, S. Iijima, T. Ichihashi, and Y. Ando, "Preparation of high-grade carbon nanotubes by hydrogen arc discharge," *Carbon*, vol. 35, pp. 775-781, 1997.
28. Y. Ando, X. Zhao, S. Inoue, and S. Iijima, "Mass production of multiwalled carbon nanotubes by hydrogen arc discharge," *Journal of Crystal Growth*, vol. 237, pp. 1926-1930, 2002.
29. Y. Ando, X. Zhao, T. Sugai, and M. Kumar, "Growing carbon nanotubes," *Materials today*, vol. 7, pp. 22-29, 2004.
30. O. Im, J. Li, M. Wang, L. Zhang, and M. Keidar, "Biomimetic 3D nanocrystalline hydroxyapatite and magnetically synthesized SWCNT chitosan nanocomposite for bone regeneration," *International Journal of Nanomedicine*, vol. 7, pp. 2087-2099, 2012.

31. O. Volotskova, I. Levchenko, A. Shashurin, Y. Raitses, K. Ostrikov, and M. Keidar, "Single-step synthesis and magnetic separation of graphene and carbon nanotubes in arc discharge plasmas," *Nanoscale*, vol. 2, pp. 2281-2285, 2010.
32. J. Li, A. Shashurin, M. Kundrapu, and M. Keidar, "Simultaneous synthesis of single-walled carbon nanotubes and graphene in a magnetically-enhanced arc plasma," *Journal of visualized experiments: JoVE*, 2012.
33. M. Farbod and M. M Hasani Matin, "Effect of magnetic field on the purity of carbon nanotubes fabricated by arc discharge method probed by raman spectroscopy," *Current Nanoscience*, vol. 7, pp. 794-796, 2011.
34. K. S. Novoselov, A. K. Geim, S. V. Morozov, D. Jiang, Y. Zhang, S. V. Dubonos, *et al.*, "Electric field effect in atomically thin carbon films," *science*, vol. 306, pp. 666-669, 2004.
35. J.-P. Salvetat, J.-M. Bonard, N. Thomson, A. Kulik, L. Forro, W. Benoit, *et al.*, "Mechanical properties of carbon nanotubes," *Applied Physics A*, vol. 69, pp. 255-260, 1999.
36. N. Sinha and J.-W. Yeow, "Carbon nanotubes for biomedical applications," *IEEE transactions on nanobioscience*, vol. 4, pp. 180-195, 2005.
37. Y. Wang and J. T. Yeow, "A review of carbon nanotubes-based gas sensors," *Journal of Sensors*, vol. 2009, 2009.
38. P. Bondavalli, P. Legagneux, and D. Pribat, "Carbon nanotubes based transistors as gas sensors: state of the art and critical review," *Sensors and Actuators B: Chemical*, vol. 140, pp. 304-318, 2009.
39. W. Choi, D. Chung, J. Kang, H. Kim, Y. Jin, I. Han, *et al.*, "Fully sealed, high-brightness carbon-nanotube field-emission display," *Applied physics letters*, vol. 75, pp. 3129-3131, 1999.
40. S. Iijima and T. Ichihashi, "Single-shell carbon nanotubes of 1-nm diameter," *nature*, vol. 363, pp. 603-605, 1993.
41. D. Bethune, C. H. Kiang, M. De Vries, G. Gorman, R. Savoy, J. Vazquez, *et al.*, "Cobalt-catalysed growth of carbon nanotubes with single-atomic-layer walls," *Nature*, vol. 363, pp. 605-607, 1993.
42. A. Garg and S. B. Sinnott, "Effect of chemical functionalization on the mechanical properties of carbon nanotubes," *Chemical Physics Letters*, vol. 295, pp. 273-278, 1998.
43. G. Gao, T. Cagin, and W. A. Goddard III, "Energetics, structure, mechanical and vibrational properties of single-walled carbon nanotubes," *Nanotechnology*, vol. 9, p. 184, 1998.
44. M. J. Treacy, T. Ebbesen, and J. Gibson, "Exceptionally high Young's modulus observed for individual carbon nanotubes," *Nature*, vol. 381, p. 678, 1996.
45. M. R. Falvo, G. Clary, R. Taylor Ii, and V. Chi, "Bending and buckling of carbon nanotubes under large strain," *nature*, vol. 389, p. 582, 1997.
46. Y. Zhu, T. Sekine, T. Kobayashi, E. Takazawa, M. Terrones, and H. Terrones, "Collapsing carbon nanotubes and diamond formation under shock waves," *Chemical physics letters*, vol. 287, pp. 689-693, 1998.
47. R. S. Ruoff and D. C. Lorents, "Mechanical and thermal properties of carbon nanotubes," *carbon*, vol. 33, pp. 925-930, 1995.
48. J. P. Gore and A. Sane, "Flame synthesis of carbon nanotubes," in *Carbon Nanotubes-Synthesis, Characterization, Applications*, ed: InTech, 2011.

49. R. Bacon, "Growth, structure, and properties of graphite whiskers," *Journal of Applied Physics*, vol. 31, pp. 283-290, 1960.
50. W. Krätschmer, L. D. Lamb, K. Fostiropoulos, and D. R. Huffman, "Solid C60: a new form of carbon," *Nature*, vol. 347, pp. 354-358, 1990.
51. S. Karthikeyan, P. Mahalingam, and M. Karthik, "Large scale synthesis of carbon nanotubes," *Journal of Chemistry*, vol. 6, pp. 1-12, 2009.
52. C. Journet, W. Maser, P. Bernier, and A. Loiseau, "Large-scale production of single-walled carbon nanotubes by the electric-arc technique," *Nature*, vol. 388, p. 756, 1997.
53. Z. Huang, J. Xu, Z. Ren, J. Wang, M. Siegal, and P. Provencio, "Growth of highly oriented carbon nanotubes by plasma-enhanced hot filament chemical vapor deposition," *Applied physics letters*, vol. 73, pp. 3845-3847, 1998.
54. U. Cvelbar, B. Markoli, I. Poberaj, A. Zalar, L. Kosec, and S. Spaić, "Formation of functional groups on graphite during oxygen plasma treatment," *Applied surface science*, vol. 253, pp. 1861-1865, 2006.
55. F. J. Gordillo-Vazquez, V. J. Herrero, and I. Tanarro, "From Carbon Nanostructures to New Photoluminescence Sources: An Overview of New Perspectives and Emerging Applications of Low-Pressure PECVD," *Chemical Vapor Deposition*, vol. 13, pp. 267-279, 2007.
56. I. Stepanek, G. Maurin, P. Bernier, J. Gavillet, A. Loiseau, R. Edwards, *et al.*, "Nano-mechanical cutting and opening of single wall carbon nanotubes," *Chemical Physics Letters*, vol. 331, pp. 125-131, 2000.
57. Y. Saito, M. Inagaki, H. Shinohara, H. Nagashima, M. Ohkohchi, and Y. Ando, "Yield of fullerenes generated by contact arc method under He and Ar: dependence on gas pressure," *Chemical physics letters*, vol. 200, pp. 643-648, 1992.
58. Y. S. Park, K. S. Kim, H. J. Jeong, W. S. Kim, J. M. Moon, K. H. An, *et al.*, "Low pressure synthesis of single-walled carbon nanotubes by arc discharge," *Synthetic metals*, vol. 126, pp. 245-251, 2002.
59. I. Hinkov, S. Farhat, and C. Scott, "Influence of the gas pressure on single-wall carbon nanotube formation," *Carbon*, vol. 43, pp. 2453-2462, 2005.
60. S. Farhat, M. Lamy de La Chapelle, A. Loiseau, C. D. Scott, S. Lefrant, C. Journet, *et al.*, "Diameter control of single-walled carbon nanotubes using argon-helium mixture gases," *The Journal of Chemical Physics*, vol. 115, pp. 6752-6759, 2001.
61. X. Wang, X. Lin, V. Dravid, J. Ketterson, and R. Chang, "Carbon nanotubes synthesized in a hydrogen arc discharge," *Applied Physics Letters*, vol. 66, pp. 2430-2432, 1995.
62. L. Li, F. Li, C. Liu, and H.-M. Cheng, "Synthesis and characterization of double-walled carbon nanotubes from multi-walled carbon nanotubes by hydrogen-arc discharge," *Carbon*, vol. 43, pp. 623-629, 2005.
63. J. Zhao, L. Wei, Z. Yang, and Y. Zhang, "Continuous and low-cost synthesis of high-quality multi-walled carbon nanotubes by arc discharge in air," *Physica E: Low-dimensional Systems and Nanostructures*, vol. 44, pp. 1639-1643, 2012.
64. Y. Su, H. Wei, T. Li, H. Geng, and Y. Zhang, "Low-cost synthesis of single-walled carbon nanotubes by low-pressure air arc discharge," *Materials Research Bulletin*, vol. 50, pp. 23-25, 2014.
65. S. Iijima, "Helical microtubules of graphitic carbon," *nature*, vol. 354, pp. 56-58, 1991.

66. H. Zeng, L. Zhu, G. Hao, and R. Sheng, "Synthesis of various forms of carbon nanotubes by AC arc discharge," *Carbon*, vol. 36, pp. 259-261, 1998.
67. M. Ohkohchi, "Synthesis of single-walled carbon nanotubes by AC arc discharge," *Japanese journal of applied physics*, vol. 38, p. 4158, 1999.
68. T. Matsuura, K. Taniguchi, and T. Watanabe, "A new type of arc plasma reactor with 12-phase alternating current discharge for synthesis of carbon nanotubes," *Thin Solid Films*, vol. 515, pp. 4240-4246, 2007.
69. N. Parkansky, R. Boxman, B. Alterkop, I. Zontag, Y. Lereah, and Z. Barkay, "Single-pulse arc production of carbon nanotubes in ambient air," *Journal of Physics D: Applied Physics*, vol. 37, p. 2715, 2004.
70. T. Sugai, H. Omote, S. Bandow, N. Tanaka, and H. Shinohara, "Production of fullerenes and single-wall carbon nanotubes by high-temperature pulsed arc discharge," *The Journal of Chemical Physics*, vol. 112, pp. 6000-6005, 2000.
71. K. Imasaka, Y. Kanatake, Y. Ohshiro, J. Suehiro, and M. Hara, "Production of carbon nanotubes and nanotubes using an intermittent arc discharge in water," *Thin solid films*, vol. 506, pp. 250-254, 2006.
72. E. G. Gamaly and T. W. Ebbesen, "Mechanism of carbon nanotube formation in the arc discharge," *Physical Review B*, vol. 52, p. 2083, 1995.
73. M. Cadek, R. Murphy, B. McCarthy, A. Drury, B. Lahr, R. Barklie, *et al.*, "Optimisation of the arc-discharge production of multi-walled carbon nanotubes," *Carbon*, vol. 40, pp. 923-928, 2002.
74. H. Nishizaka, M. Namura, K. Motomiya, Y. Ogawa, Y. Udagawa, K. Tohji, *et al.*, "Influence of carbon structure of the anode on the production of graphite in single-walled carbon nanotube soot synthesized by arc discharge using a Fe-Ni-S catalyst," *Carbon*, vol. 49, pp. 3607-3614, 2011.
75. T. Matsuura, Y. Kondo, and N. Maki, "Selective mass production of carbon nanotubes by using multi-layered and multi-electrodes AC arc plasma reactor," *International Plasma Chemistry Society*, 2009.
76. D. He, T. Zhao, Y. Liu, J. Zhu, G. Yu, and L. Ge, "The effect of electric current on the synthesis of single-walled carbon nanotubes by temperature controlled arc discharge," *Diamond and Related Materials*, vol. 16, pp. 1722-1726, 2007.
77. S. Scalese, V. Scuderi, S. Bagiante, S. Gibilisco, G. Faraci, and V. Privitera, "Order and disorder of carbon deposit produced by arc discharge in liquid nitrogen," *Journal of Applied Physics*, vol. 108, p. 064305, 2010.
78. J. B. Donnet, H. Oulanti, and T. Le Huu, "Mechanism growth of multiwalled carbon nanotubes on carbon black," *Diamond and Related Materials*, vol. 17, pp. 1506-1512, 2008.
79. S. Doherty and R. Chang, "Synthesis of multiwalled carbon nanotubes from carbon black," *Applied physics letters*, vol. 81, pp. 2466-2468, 2002.
80. S. Doherty, D. Buchholz, and R. Chang, "Semi-continuous production of multiwalled carbon nanotubes using magnetic field assisted arc furnace," *Carbon*, vol. 44, pp. 1511-1517, 2006.
81. J. Qiu, Z. Wang, Z. Zhao, and T. Wang, "Synthesis of double-walled carbon nanotubes from coal in hydrogen-free atmosphere," *Fuel*, vol. 86, pp. 282-286, 2007.
82. J. Qiu, G. Chen, Z. Li, and Z. Zhao, "Preparation of double-walled carbon nanotubes from fullerene waste soot by arc-discharge," *Carbon*, vol. 48, pp. 1312-1315, 2010.

83. T. Okada, T. Kaneko, and R. Hatakeyama, "Conversion of toluene into carbon nanotubes using arc discharge plasmas in solution," *Thin Solid Films*, vol. 515, pp. 4262-4265, 2007.
84. L. Murr, D. Brown, E. Esquivel, T. Ponda, F. Martinez, and A. Virgen, "Carbon nanotubes and other fullerenes produced from tire powder injected into an electric arc," *Materials characterization*, vol. 55, pp. 371-377, 2005.
85. Y.-H. Wang, S.-C. Chiu, K.-M. Lin, and Y.-Y. Li, "Formation of carbon nanotubes from polyvinyl alcohol using arc-discharge method," *Carbon*, vol. 42, pp. 2535-2541, 2004.
86. S. Zhao, R. Hong, Z. Luo, H. Lu, and B. Yan, "Carbon nanostructures production by AC arc discharge plasma process at atmospheric pressure," *Journal of Nanomaterials*, vol. 2011, p. 14, 2011.
87. J. P. Lu, "Novel magnetic properties of carbon nanotubes," *Physical review letters*, vol. 74, p. 1123, 1995.
88. D. Walters, M. Casavant, X. Qin, C. Huffman, P. Boul, L. Ericson, *et al.*, "In-plane-aligned membranes of carbon nanotubes," *Chemical Physics Letters*, vol. 338, pp. 14-20, 2001.
89. T. Belin and F. Epron, "Characterization methods of carbon nanotube review," *Materials Science and Engineering: B*, vol. 119, pp. 105-118,