

DESIGN AND CALIBRATION OF A SPECIALIZED
POLYDIOPTIC CAMERA RIG

OSAMA MAZHAR

UNIVERSITI TEKNOLOGI MALAYSIA

DESIGN AND CALIBRATION OF A SPECIALIZED
POLYDIOPTIC CAMERA RIG


OSAMA MAZHAR

A project report submitted in partial fulfilment of the
requirements for the award of the degree of Master of
Engineering (Mechatronic and Automatic Control)

UNIVERSITI TEKNOLOGI MALAYSIA

JULY, 2016

I declare that this project report entitled “*Design and Calibration of a Specialized Polydioptric Camera Rig*”, is a result of my own research except as cited in the references. This project report has not been submitted in candidature of any other programme.

Signature : 

Name : Osama Mazhar

Date : July 24, 2016

This work has been dedicated to my family, supervisor and friends for their support both financially and spiritually.

ACKNOWLEDGMENT

All praise is due to God, the Beneficent, and the Merciful. I would like to express my sincere gratitude to my supervisors Prof. David Fofi, Olivier Morel and Ralph Seulin for their support and help, which allowed me to complete this thesis on time.

Thanks to Prof. David Fofi especially for several long discussions we had during the thesis, for his appreciation and kind gestures for encouragement throughout the work. Thanks to Cansen Jiang for his involvement and help in many critical parts of the thesis.

I would like to extend my sincere thanks to my family for their well-wishes and support throughout, by all means. Thanks to my friends for their moral and technical support wherever needed. And thanks to all those who appreciate me for any good they see.

ABSTRACT

The development of advanced computational machines does not necessarily provide solutions to all the scientific problems in the research. It has been observed in the nature that all creatures have evolved highly exclusive sensory organs depending on their habitat and the form of availability of the resources they utilize for their survival. In this project, a novel omnidirectional camera rig is proposed that is exclusively designed to operate for highly specified operations and tasks in the field of mobile robots. Navigation problems on uneven terrains and detection of the moving objects while the robot is itself in motion are the core problems that omnidirectional systems tackle. The proposed omnidirectional system is a compact and a rigid vision system with dioptric cameras that provide a 360° field-of-view in horizontal and vertical, with no blind spot in their site plus a high resolution stereo camera is mounted to monitor anterior field-of-view for precise results with depth information of the scene. Structure from motion algorithm is adapted and implemented to prove the validity of the design of the proposed camera rig and a toolbox is developed to calibrate similar systems.

ABSTRAK

Pembangunan mesin pengkomputeran canggih tidak semestinya memberikan penyelesaian kepada setiap permasalahan saintifik dalam bidang penyelidikan. Melalui pemerhatian secara semula jadi, organ-organ deria semua makhluk telah dicipta dengan sangat eksklusif bergantung kepada habitat dan sumber-sumber yang digunakan untuk kelangsungan hidup mereka. Dalam projek ini, pelantar kamera semua arah yang dicadangkan direka hanya untuk beroperasi dalam operasi dan tugas yang sangat terperinci dalam bidang robot mudah-alih. Masalah utama yang dapat ditangani adalah pelayaran di bentuk muka bumi yang tidak rata dan mengesan objek yang bergerak ketika robot sedang bergerak. Sistem omnidirectional yang dicadangkan adalah sistem penglihatan yang kecil dan padat dengan kamera dioptrik yang menyediakan pemandangan 360 ° dalam keadaan mendatar dan menegak, tanpa titik buta semasa penggambaran serta dilengkapi juga dengan kamera stereo resolusi tinggi yang padat dipasang untuk memantau pemandangan untuk hasil yang lebih tepat beserta maklumat yang terperinci di tempat penggambaran. Struktur dari pergerakan algoritma disesuaikan dan dilaksanakan untuk membuktikan kesahihan reka bentuk pelantar kamera yang dicadangkan dan kotak penyimpanan dibangunkan untuk pengujian sistem yang sama.

TABLE OF CONTENTS

| CHAPTER | TITLE | PAGE |
|----------------|--------------------------------------|-------------|
| | DECLARATION | ii |
| | DEDICATION | iii |
| | ACKNOWLEDGMENT | iv |
| | ABSTRACT | v |
| | ABSTRAK | vi |
| | TABLE OF CONTENTS | vii |
| | LIST OF TABLES | ix |
| | LIST OF FIGURES | x |
| 1 | INTRODUCTION | |
| | 1.1 Introduction | 1 |
| | 1.2 Proposed Camera Rig | 2 |
| 2 | LITERATURE REVIEW | |
| | 2.1 Omni-Directional Cameras | 4 |
| | 2.2 Camera Modelling and Calibration | 6 |
| | 2.3 Polydioptric Cameras | 10 |
| | 2.4 Omni-Structure from Motion | 12 |

| | | |
|----------|-----------------------------------------------------------------|----|
| 3 | METHODOLOGY | |
| 3.1 | Unified Spherical Camera Model | 13 |
| 3.2 | Omnidirectional Epipolar Geometry | 17 |
| 3.3 | Triangulation for Omnidirectional Cameras | 22 |
| 4 | RESULTS AND DISCUSSION | |
| 4.1 | Overview | 24 |
| 4.2 | Estimation of Intrinsic Parameters of Fisheye Cameras | 24 |
| 4.3 | Intrinsic Parameters Estimation of ZED Camera | 29 |
| 4.4 | Estimation of Extrinsic Parameters of the Proposed Rig | 29 |
| 4.5 | Toolbox for Calibration of the Proposed and Similar Camera Rigs | 37 |
| 4.6 | Structure from Motion | 37 |
| 5 | CONCLUSION | |
| 5.1 | Overview | 45 |
| 5.2 | Contributions | 45 |
| 5.3 | Fisheye Cameras Vs Catadioptric Cameras | 46 |
| 5.4 | Calibration of the Camera Rig | 46 |
| 5.5 | Structure from Motion | 48 |
| 6 | REFERENCES | 49 |

LIST OF TABLES

| TABLE NO. | TITLE | PAGE |
|------------------|----------------------------------------------------------------|-------------|
| 4.1 | Intrinsic parameters of left and right fisheye cameras | 25 |
| 4.2 | Intrinsic parameters of ZED-camera (stereo-camera) | 29 |
| 4.3 | Summary of solving epipolar geometry using synthetic data | 39 |
| 4.4 | Summary of solving epipolar geometry with noisy synthetic data | 40 |

LIST OF FIGURES

| FIGURE NO. | TITLE | PAGE |
|------------|---------------------------------------------------------------------------|------|
| 1.1 | Proposed Omnivision Camera Rig | 2 |
| 2.1 | Illustration of a Sphere of View for a truly omnidirectional image | 5 |
| 2.2 | Illustration of (a) dioptric (fisheye) camera and (b) catadioptric camera | 6 |
| 2.3 | A full-frame fisheye lens layout; invented by T. Ogura | 7 |
| 2.4 | Polydioptric Cameras | 10 |
| 2.5 | Stereo Cameras | 12 |
| 3.1 | Steps of unifying model proposed by Barreto | 14 |
| 3.2 | The paraboloid model for dioptric cameras with radial distortion | 15 |
| 3.3 | Mei's z-axis convention; towards the camera but outwards | 16 |
| 3.4 | Mei's camera projection model | 18 |
| 3.5 | Epipolar geometry of fisheye cameras | 19 |
| 4.1 | Images used for calibration of right fisheye camera | 25 |
| 4.2 | Projection of the left fisheye camera image onto the unit sphere. | 26 |
| 4.3 | ξ estimation set-up | 27 |
| 4.4 | Illustration of the iterative estimation of ξ | 28 |
| 4.5 | Selection of overlapping feature points in two camera images | 30 |
| 4.6 | Feature points projected onto unit sphere for estimation of the rigid | 31 |
| 4.7 | Spherical approximation; estimation of pure rotation | 32 |
| 4.8 | Screen shots of the Omnivision sphere | 33 |
| 4.9 | Overlapping field-of-view | 35 |
| 4.10 | Images of the fused fisheye and RGB-D images from the ZED camera | 36 |
| 4.11 | Screen shot of the Matlab based toolbox developed | 37 |

| | | |
|------|------------------------------------------------------------------|----|
| 4.12 | Three dimensional scene reconstruction using synthetic data | 38 |
| 4.13 | Scene reconstruction with noisy data | 39 |
| 4.14 | Feature matching in two different poses | 42 |
| 4.15 | Manual point selection between two poses, approximately 3m apart | 43 |
| 4.16 | Three dimensional reconstruction of the scene | 44 |

CHAPTER 1

INTRODUCTION

1.1 Introduction

The rapid development in computing systems and their availability to the consumer market, soon made researchers realize that computational inability may not necessarily be the only handicap in all scientific problems. If observed in nature, all creatures have evolved very unique and highly specified anatomical and physiological traits that depends in the habitat they live and the availability of the resources their survival is dependent on. The artificial vision systems with larger field-of-view are always appreciated in computer vision research. These are specialized systems that offer a possibility to acquire more information with less equipment/image-data used. Omnidirectional or panoramic cameras have become an affordable and popular photographic tool that allows to capture 360° panoramic images [1].

Some of the applications of the omnidirectional cameras are, but not limited to, robot localization and mapping [2-5], robot navigation [6-9], object tracking [10-12], visual servoing [13-16], structure-from-motion [17-20], and virtual-reality/visual-telepresence [21-23].



Figure 1.1 Proposed Omnivision Camera Rig

Omnidirectional cameras are also used in geo-localization [24] and lately a similar feature for google maps, that utilize omni-vision i.e. a 360° panoramic images, is embedded into the street maps. The use of visual-sensors/omnidirectional-cameras for the aforementioned applications, offers several advantages over other optical (laser) or ultrasonic sensors. Such systems provide improved results as compared to those obtained by the use of conventional perspective cameras as they require minimal physical motion of the robot/sensor to recover information about the environment [25].

1.2 Proposed Camera Rig

An omnivision camera rig has been developed using two fisheye cameras with 185° field-of-view each, which are fixed opposite to each other facing laterally, so as to cover 360° in horizontal and vertical. A depth camera, namely “ZED Camera”, is also mounted in front of the rig that covers the anterior view providing high-resolution RGB + depth image.

REFERENCES

1. Knill, O. and J. Ramirez-Herran, *Space and camera path reconstruction for omni-directional vision*. arXiv preprint arXiv:0708.2442, 2007.
2. Hart, C., *A Low-cost Omni-directional Visual Bearing Only Localization System*. 2014, Case Western Reserve University.
3. Kim, S.-H., J.-H. Park, and I.-K. Jung. *Global Localization of Mobile Robot using an Omni-Directional Camera*. in *Proceedings of the International Conference on Image Processing, Computer Vision, and Pattern Recognition (IPCV)*. 2014. The Steering Committee of The World Congress in Computer Science, Computer Engineering and Applied Computing (WorldComp).
4. Liu, M. and R. Siegwart, *Topological mapping and scene recognition with lightweight color descriptors for an omnidirectional camera*. *Robotics, IEEE Transactions on*, 2014. **30**(2): p. 310-324.
5. Lukierski, R., S. Leutenegger, and A.J. Davison. *Rapid free-space mapping from a single omnidirectional camera*. in *Mobile Robots (ECMR), 2015 European Conference on*. 2015. IEEE.
6. Zhang, C., et al. *Development of an omni-directional 3D camera for robot navigation*. in *Advanced Intelligent Mechatronics (AIM), 2012 IEEE/ASME International Conference on*. 2012. IEEE.

7. Watanabe, K., et al., *Obstacle Avoidance Based on Plane Estimation from 3D Edge Points by Mobile Robot Equipped with Omni-directional Camera*, in *Intelligent Autonomous Systems 12*. 2013, Springer. p. 15-24.
8. Delgado-Galvan, J., et al., *Vision-Based Humanoid Robot Navigation in a Featureless Environment*, in *Pattern Recognition*. 2015, Springer. p. 169-178.
9. Hart, C., et al. *A low-cost robot using Omni-directional vision enables insect-like behaviors*. in *Robotics and Automation (ICRA), 2015 IEEE International Conference on*. 2015. IEEE.
10. Cogal, O., et al. *A new omni-directional multi-camera system for high resolution surveillance*. in *SPIE Sensing Technology+ Applications*. 2014. International Society for Optics and Photonics.
11. Depraz, F., et al. *Real-time object detection and tracking in omni-directional surveillance using GPU*. in *SPIE Security+ Defence*. 2015. International Society for Optics and Photonics.
12. Sablak, S., *Omni-directional intelligent autotour and situational aware dome surveillance camera system and method*. 2015, Google Patents.
13. Caron, G., E. Marchand, and E.M. Mouaddib, *Photometric visual servoing for omnidirectional cameras*. *Autonomous Robots*, 2013. **35**(2-3): p. 177-193.
14. Liu, M., C. Pradalier, and R. Siegwart, *Visual homing from scale with an uncalibrated omnidirectional camera*. *Robotics, IEEE Transactions on*, 2013. **29**(6): p. 1353-1365.
15. Markovic, I., F. Chaumette, and I. Petrovic. *Moving object detection, tracking and following using an omnidirectional camera on a mobile robot*. in *Robotics and Automation (ICRA), 2014 IEEE International Conference on*. 2014. IEEE.

16. Pasteau, F., et al., *A visual servoing approach for autonomous corridor following and doorway passing in a wheelchair*. Robotics and Autonomous Systems, 2016. **75**: p. 28-40.
17. Chang, P. and M. Hebert. *Omni-directional structure from motion*. in *Omnidirectional Vision, 2000. Proceedings. IEEE Workshop on*. 2000. IEEE.
18. Micusik, B. and T. Pajdla, *Structure from motion with wide circular field of view cameras*. Pattern Analysis and Machine Intelligence, IEEE Transactions on, 2006. **28**(7): p. 1135-1149.
19. Kawanishi, R., A. Yamashita, and T. Kaneko. *Construction of 3D environment model from an omni-directional image sequence*. in *Proceedings of the 3rd Asia International Symposium on Mechatronics, TPI-3 (2)*. 2008.
20. Kim, S. and S.-Y. Oh, *SLAM in indoor environments using omni-directional vertical and horizontal line features*. Journal of Intelligent and Robotic Systems, 2008. **51**(1): p. 31-43.
21. Li, D., et al. *Motion Interactive System with Omni-Directional Display*. in *Virtual Reality and Visualization (ICVRV), 2013 International Conference on*. 2013. IEEE.
22. Kawauchi, K. and J. Rekimoto. *Quantized reality: automatic fine-grained spherical images acquisition for space re-construction*. in *Proceedings of the 13th ACM SIGGRAPH International Conference on Virtual-Reality Continuum and its Applications in Industry*. 2014. ACM.
23. Kasahara, S. and J. Rekimoto. *JackIn head: immersive visual telepresence system with omnidirectional wearable camera for remote collaboration*. in *Proceedings of the 21st ACM Symposium on Virtual Reality Software and Technology*. 2015. ACM.

24. Ramalingam, S., et al. *Geolocalization using skylines from omni-images*. in *Computer Vision Workshops (ICCV Workshops), 2009 IEEE 12th International Conference on*. 2009. IEEE.
25. Geyer, C. and K. Daniilidis, *A unifying theory for central panoramic systems and practical implications*, in *Computer Vision—ECCV 2000*. 2000, Springer. p. 445-461.
26. Rees, D.W., *Hyperbolic ellipsoidal real time display panoramic viewing installation for vehicles*. 1966, Google Patents.
27. Rees, D.W., *Panoramic television viewing system*. 1970, Google Patents.
28. Yagi, Y., S. Kawato, and S. Tsuji, *Real-time omnidirectional image sensor (COPIS) for vision-guided navigation*. *Robotics and Automation, IEEE Transactions on*, 1994. **10**(1): p. 11-22.
29. Nayar, S.K. *Catadioptric omnidirectional camera*. in *Computer Vision and Pattern Recognition, 1997. Proceedings., 1997 IEEE Computer Society Conference on*. 1997.
30. Gluckman, J. and S.K. Nayar. *Ego-motion and omnidirectional cameras*. in *Computer Vision, 1998. Sixth International Conference on*. 1998. IEEE.
31. Neumann, J., C. Fermüller, and Y. Aloimonos. *Polydioptric camera design and 3d motion estimation*. in *Computer Vision and Pattern Recognition, 2003. Proceedings. 2003 IEEE Computer Society Conference on*. 2003. IEEE.
32. Nayar, S.K. and S. Baker. *Catadioptric image formation*. in *Proceedings of the 1997 DARPA Image Understanding Workshop*. 1997.

33. Barreto, J.P., *Unifying image plane liftings for central catadioptric and dioptric cameras*, in *Imaging Beyond the Pinhole Camera*. 2006, Springer. p. 21-38.
34. Barreto, J.P., *A unifying geometric representation for central projection systems*. *Computer Vision and Image Understanding*, 2006. **103**(3): p. 208-217.
35. Courbon, J., Y. Mezouar, and P. Martinet, *Evaluation of the Unified Model of the Sphere for Fisheye Cameras in Robotic Applications*. *Advanced Robotics*, 2012. **26**(8-9): p. 947-967.
36. Beauchemin, S.S. and R. Bajcsy, *Modelling and removing radial and tangential distortions in spherical lenses*, in *Multi-Image Analysis*. 2001, Springer. p. 1-21.
37. Hartley, R. and A. Zisserman, *Multiple view geometry in computer vision*. 2003: Cambridge university press.
38. Basu, A. and S. Licardie, *Alternative models for fish-eye lenses*. *Pattern Recognition Letters*, 1995. **16**(4): p. 433-441.
39. Klančar, G., M. Kristan, and R. Karba, *Wide-angle camera distortions and non-uniform illumination in mobile robot tracking*. *Robotics and Autonomous Systems*, 2004. **46**(2): p. 125-133.
40. Hartley, R. and S.B. Kang, *Parameter-Free Radial Distortion Correction with Center of Distortion Estimation*. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 2007. **29**(8): p. 1309-1321.
41. Barreto, J.P., R. Swaminathan, and J. Roquette. *Non parametric distortion correction in endoscopic medical images*. in *3DTV Conference, 2007*. 2007. IEEE.

42. Scaramuzza, D., A. Martinelli, and R. Siegwart. *A flexible technique for accurate omnidirectional camera calibration and structure from motion*. in *Computer Vision Systems, 2006 ICVS'06. IEEE International Conference on*. 2006. IEEE.
43. Mei, C. and P. Rives. *Single view point omnidirectional camera calibration from planar grids*. in *Robotics and Automation, 2007 IEEE International Conference on*. 2007. IEEE.
44. Ma, C., et al., *3D Reconstruction from Full-view Fisheye Camera*. arXiv preprint arXiv:1506.06273, 2015.
45. Milford, M., *Vision-based place recognition: how low can you go?* The International Journal of Robotics Research, 2013. **32**(7): p. 766-789.
46. Kim, S.-B., et al., *Ground vehicle navigation in harsh urban conditions by integrating inertial navigation system, global positioning system, odometer and vision data*. Radar, Sonar & Navigation, IET, 2011. **5**(8): p. 814-823.
47. Nguyen, J.S., S.W. Su, and H.T. Nguyen. *Spherical vision cameras in a semi-autonomous wheelchair system*. in *Engineering in Medicine and Biology Society (EMBC), 2010 Annual International Conference of the IEEE*. 2010. IEEE.
48. Kim, J.-S., M. Hwangbo, and T. Kanade, *Spherical approximation for multiple cameras in motion estimation: Its applicability and advantages*. Computer Vision and Image Understanding, 2010. **114**(10): p. 1068-1083.
49. Hartley, R.I. and P. Sturm, *Triangulation*. Computer vision and image understanding, 1997. **68**(2): p. 146-157.
50. Ayache, N. and F. Lustman, *Trinocular stereo vision for robotics*. IEEE Transactions on Pattern Analysis & Machine Intelligence, 1991(1): p. 73-85.

51. Kumar, S., D. Gupta, and S. Yadav, *Sensor fusion of laser and stereo vision camera for depth estimation and obstacle avoidance*. International Journal of Computer Applications, 2010. **1**(25): p. 20-25.
52. Longuet-Higgins, H.C., *A computer algorithm for reconstructing a scene from two projections*. Readings in Computer Vision: Issues, Problems, Principles, and Paradigms, MA Fischler and O. Firschein, eds, 1987: p. 61-62.
53. Geyer, C. and K. Daniilidis. *Mirrors in motion: Epipolar geometry and motion estimation*. in *Computer Vision, 2003. Proceedings. Ninth IEEE International Conference on*. 2003. IEEE.
54. Svoboda, T., T. Pajdla, and V. Hlaváč, *Epipolar geometry for panoramic cameras*, in *Computer Vision—ECCV'98*. 1998, Springer. p. 218-231.
55. Torr, P.H.S. and D.W. Murray, *The Development and Comparison of Robust Methods for Estimating the Fundamental Matrix*. International Journal of Computer Vision, 1997. **24**(3): p. 271-300.
56. Bouguet, J.-Y., *Camera calibration toolbox for matlab*. 2004.
57. Lébraly13, P., et al., *Calibration of non-overlapping cameras-application to vision-based robotics*. 2010.
58. Harris, C. and M. Stephens. *A combined corner and edge detector*. in *Alvey vision conference*. 1988. Citeseer.
59. Lowe, D.G., *Distinctive image features from scale-invariant keypoints*. International journal of computer vision, 2004. **60**(2): p. 91-110.
60. Bay, H., T. Tuytelaars, and L. Van Gool, *Surf: Speeded up robust features*, in *Computer vision—ECCV 2006*. 2006, Springer. p. 404-417.

61. Donoser, M. and H. Bischof. *Efficient maximally stable extremal region (MSER) tracking*. in *Computer Vision and Pattern Recognition, 2006 IEEE Computer Society Conference on*. 2006. IEEE.

62. Hane, C., et al. *Real-time direct dense matching on fisheye images using plane-sweeping stereo*. in *3D Vision (3DV), 2014 2nd International Conference on*. 2014. IEEE.