

SYNTHESIS AND CHARACTERIZATION OF OIL PALM FROND BASED
CRYOGEL FOR HEAVY METALS REMOVAL

NUR SHAHIRAH BINTI RUSLI

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Master of Engineering (Chemical)

Faculty of Chemical and Energy Engineering
Universiti Teknologi Malaysia

APRIL 2016

In the Name of ALLAH, The Most Gracious and The Most Merciful

*Specially dedicated to
my beloved Mak & Abah and my lovely husband..*

Thanks for your endless support and prayers..

They mean the world to me...

ACKNOWLEDGEMENT

Alhamdulillah. First and foremost I thank to Allah the Almighty for his Grace, Mercy and Guidance that awarded me the strength to complete this research. A memorable journey that I will always treasure.

First and foremost, my deepest gratitude's goes to my respectful supervisor, Dr Norzita Binti Ngadi, for all her dedications, counsels, encouragements and outstanding supervisions in accomplishing these whole works. Thanks a lot for all the guidance. May your good deed be rewarded by Allah SWT.

My sincere thanks and appreciations to my beloved parents, Maznah Senawi and Rusli Ismail, for all the strength and motivation given throughout my whole life. Words are not enough to express how grateful I am to have you in this journey. Not to forget, to my supportive family, thanks for your warming support.

My special thanks also goes to my dearest husband, Mohamad Arif Mohd Sulaiman, who always there for me. Thanks a lot for your love and understanding. I will always love you and forever grateful to have you by my side.

Not to forget all my friends who forever besides me and aiding my research to be successfully completed. Finally, thousand thanks to all who involved in this research project. I hope this thesis will be valuable to Islam and ummah. May Allah grants us a continued blessing. Thank you.

ABSTRACT

Heavy metal pollution has become one of the most serious environmental problems today and treatment for this problem, which is environmentally friendly, is vigorously sought. Realising that a large portion of the biomass from the oil palm plantation is just left to rot and returned to the field as fertiliser, this research aims to investigate and explore the preparation of cryogel from the lignin of oil palm frond (OPF). The potential of ultrasound-assisted extraction to extract lignin from OPF as compared to conventional heating was studied. The extraction was carried out using sodium hydroxide solution as a solvent and factors such as solvent concentration and extraction temperature effects were also examined. The presence of lignin in the corresponding extracts was confirmed by Fourier transform infrared spectroscopy (FTIR) analysis and thermogravimetric analysis (TGA). The extracted lignin was then reacted with furfural to synthesize resin before being freeze-dried to obtain cryogel. The cryogel was characterized for their morphology and physical properties using FTIR, field emission scanning electron microscopy, x-ray diffraction, Brunauer, Emmet and Teller (BET) and TGA. The performance of cryogel towards the removal of heavy metals ions (zinc (Zn(II)), copper (Cu(II)) and chromium (Cr(VI))) via adsorption process was performed. The adsorption was also described through adsorption kinetics, isotherm and thermodynamic properties. The result obtained showed that the extraction of OPF assisted with ultrasound was more efficient in giving higher lignin yield compared to conventional heating and the optimum lignin yield was 26%. Other than that, the reaction temperature was lowered and the reaction time was also shortened when the extraction was assisted by ultrasound. From FTIR analysis, OPF lignin showed similar spectra in terms of functional groups but slightly different in intensity when compared to commercial lignin. Overall, under optimum conditions of adsorption, Zn(II) gave the highest adsorption capacity followed by Cu(II) and Cr(VI) (i.e. Zn(II)>Cu(II)>Cr(VI)). The adsorption capacity for these heavy metals were 0.995, 0.935 and 0.4895 mg/g for Zn(II), Cu(II) and Cr(VI), respectively. The experimental data were appropriately described by the Langmuir model. This was validated by the R^2 values of the Langmuir model (0.999 to 0.9689) that were higher than the Freundlich model (0.8343 to 0.9539) and the Temkin model (0.8409 to 0.9502) for all the heavy metals tested. The adsorption kinetics followed the pseudo-second order. The negative values of the Gibbs free energy change indicated the adsorption was spontaneous. The negative value of enthalpy change and entropy change confirmed the exothermic nature and showed the decrement of structural changes at solid-solution interface during adsorption process, respectively. It can be concluded that the synthesized cryogel derived from OPF lignin provides a potential performance for heavy metals removal.

ABSTRAK

Pencemaran logam berat telah menjadi salah satu masalah alam sekitar yang serius pada hari ini dan langkah penyelesaian yang mesra alam bagi masalah ini adalah dicari. Menyedari bahawa sebahagian besar biojisim dari ladang kelapa sawit hanya dibiarkan mereput dan sebagai baja, kajian ini bertujuan untuk mengkaji dan meneroka penyediaan kriogel daripada lignin pelepah kelapa sawit (OPF). Potensi pengekstrakan dengan bantuan ultrabunyi untuk mengekstrak lignin dari OPF berbanding pemanasan konvensional telah dikaji. Pengekstrakan ini telah dijalankan dengan menggunakan larutan natrium hidroksida sebagai pelarut dan faktor-faktor seperti kepekatan pelarut dan suhu pengekstrakan juga diperhatikan. Kehadiran lignin dalam ekstrak tersebut telah disahkan melalui analisis spektroskopi inframerah transformasi Fourier (FTIR) dan analisis termogravimetri (TGA). Lignin itu kemudian telah ditindak balaskan bersama furfural untuk menghasilkan resin sebelum dibeku-kering bagi menghasilkan kriogel. Ciri-ciri morfologi dan fizikal kriogel telah diperiksa menggunakan FTIR, mikroskop pengimbas elektron pancaran medan, teknik pembelauan sinar-x, Breuner, Emmer dan Teller (BET) dan TGA. Prestasi kriogel terhadap penyingkiran ion-ion logam berat (zink (Zn(II)), kuprum (Cu(II)) dan kromium (Cr(VI))) melalui proses penjerapan telah diuji. Penjerapan juga diterangkan melalui kinetik penjerapan, isoterma dan sifat-sifat termodinamik. Keputusan yang diperoleh menunjukkan bahawa pengekstrakan OPF dengan bantuan ultrabunyi adalah lebih berkesan kerana memberikan hasil lignin yang lebih tinggi berbanding pemanasan konvensional dan hasil lignin optimum yang dicatatkan adalah 26%. Selain itu, tindak balas juga boleh dilakukan pada suhu yang lebih rendah dan masa tindak balas juga adalah lebih pendek dengan bantuan ultrabunyi. Melalui analisis FTIR, lignin OPF menunjukkan spektrum kumpulan berfungsi yang sama dengan lignin komersil tetapi dalam intensiti yang berbeza. Secara keseluruhan, pada keadaan penjerapan yang optimum, Zn(II) memberikan kapasiti penjerapan yang paling tinggi diikuti dengan Cu(II) dan Cr(VI) (i.e. Zn(II)>Cu(II)>Cr(VI)). Kapasiti penjerapan logam berat ini adalah masing-masing 0.995, 0.935 dan 0.4895 mg/g bagi Zn(II), Cu(II) dan Cr(VI). Data ujikaji ini adalah sesuai digambarkan oleh model Langmuir. Ini telah disahkan oleh nilai R^2 model Langmuir (0.999-0.9689) yang lebih tinggi daripada model Freundlich (0.8343-0.9539) dan model Temkin (0.8409-0.9502) untuk semua logam berat yang diuji. Kinetik penjerapan pula mengikut tertib pseudo-kedua. Nilai negatif perubahan tenaga bebas Gibbs menunjukkan penjerapan adalah spontan. Nilai negatif perubahan entalpi dan perubahan entropi pula masing-masing mengesahkan sifat eksotermik dan menunjukkan susutan perubahan struktur di permukaan larutan pepejal semasa proses penjerapan. Kesimpulannya, kriogel yang dihasilkan daripada lignin OPF ini mempunyai potensi untuk digunakan dalam penyingkiran logam berat.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATIONS	xvi
	LIST OF SYMBOLS	xvii
	LIST OF APPENDICES	xix
1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement	3
	1.3 Research Objectives	4
	1.4 Scope of Study	4
	1.5 Significance of study	5
2	LITERATURE REVIEW	7
	2.1 Oil Palm	7
	2.1.1 Use of Oil Palm Fronds	9
	2.2 Lignin	11
	2.2.1 Utilization of Lignin	13

2.2.2	Lignin Extraction Method	14
2.2.3	Ultrasound-assisted extraction method	16
2.3	Carbon Gel	17
2.3.1	Type of Carbon Gel	18
2.3.2	Carbon Gel versus Activated Carbon	19
2.3.3	Carbon Cryogel as Adsorbent in Adsorption Process	21
2.4	Heavy Metals Problems	22
2.4.1	Heavy Metals Removal	24
2.4.2	Use of Activated Carbon for Heavy Metal Removals	26
2.4.3	Zinc, Copper and Chromium Removal from Wastewater	28
2.4.4	Factors Affecting Adsorption Efficiency	31
2.4.5	Types of Adsorption	33
2.5	Isotherm, Kinetic and Thermodynamic Study	34
2.5.1	Adsorption Isotherms	35
2.5.1.1	Langmuir Isotherm	35
2.5.1.2	Freundlich Isotherm	36
2.5.1.3	Temkin Isotherm	37
2.5.2	Adsorption Kinetics	37
2.5.2.1	Pseudo-First Order Equation	37
2.5.2.2	Pseudo-Second Order Equation	38
2.5.2.3	Intraparticle Diffusion Model	39
2.5.3	Thermodynamic Adsorption	40
3	RESEARCH METHODOLOGY	42
3.1	Introduction	42
3.2	Experimental Components	44
3.2.1	Raw Material	44
3.2.2	Chemicals and Reagents	44
3.2.3	Materials and Equipment	45
3.3	Sample Preparation	45
3.4	Extraction of Lignin from OPF	46

3.4.1	Lignin Characterization	50
3.4.1.1	FTIR Analysis of Lignin	50
3.4.1.2	TGA Analysis of Lignin	50
3.5	Synthesis and Characterization of Cryogel	51
3.5.1	Synthesis of Cryogel	51
3.5.2	Characterization of Cryogel	52
3.5.2.1	BET Analysis of Cryogel	52
3.5.2.2	XRD Analysis of Cryogel	52
3.5.2.3	FTIR Analysis of Cryogel	53
3.5.2.4	FESEM Analysis of Cryogel	53
3.5.2.5	TGA Analysis of Cryogel	53
3.6	Adsorption Study	53
3.6.1	Preparation of Metal Ion Solutions	53
3.6.2	Preliminary Adsorption Test	54
3.6.3	Adsorption Test for the Heavy Metal Removal	54
3.6.4	Analysis of Heavy Metals	55
4	RESULT AND DISCUSSION	56
4.1	Extraction of Lignin from OPF	56
4.1.1	Effect of Sodium Hydroxide, OPF Source and Presence of Ultrasound on Lignin Yield	56
4.1.2	Effect of Temperature on Lignin Yield	59
4.1.3	FTIR Analysis of Lignin	61
4.1.4	TGA Analysis of Lignin	62
4.2	Synthesis and Characterization of Cryogel	64
4.2.1	Cryogels Screening	65
4.2.2	Nitrogen Adsorption Isotherm Analysis	68
4.2.3	X-Ray Diffraction (XRD)	70
4.2.4	Fourier Transform Infrared Spectroscopy (FTIR)	71
4.2.5	Field Emission Scanning Electron Microscopy (FESEM)	72
4.2.6	Thermogravimetric Analysis (TGA)	73
4.3	Adsorption of Heavy Metals Study	74

4.3.1	Effect of Time on Adsorption Capacity of Zn(II), Cu(II) and Cr(VI)	74
4.3.2	Effect of Initial Concentration on Adsorption Capacity of Zn(II), Cu(II) and Cr(VI)	77
4.3.3	Effect of pH on Adsorption Capacity of Zn(II), Cu(II) and Cr(VI)	78
4.3.4	Effect of Adsorbent Dosage on Adsorption Capacity of Zn(II), Cu(II) and Cr(VI)	80
4.3.5	Effect of Temperature on Adsorption Capacity of Zn(II), Cu(II) and Cr(VI)	81
4.4	Adsorption Isotherm	82
4.5	Adsorption Kinetics	86
4.6	Thermodynamic Study	91
5	CONCLUSIONS AND RECOMMENDATIONS	94
5.1	Conclusions	94
5.2	Recommendations for Future Works	96
	REFERENCES	97
	APPENDIX A-C	109

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Amount of lignocellulosic component in different type of biomass	12
2.2	Similarities and differences between carbon gel and activated carbon (Al-Muhtaseb & Ritter, 2003; Shrestha <i>et al.</i> , 2011)	20
2.3	The standards industrial effluents for the most hazardous heavy metals (Lakherwal, 2014; Alluri <i>et al.</i> , 2007)	23
2.4	Advantage and disadvantage of several heavy metal wastewater treatment techniques (Fu and Wang 2011)	25
2.5	Heavy metals removals by using activated carbon derived from biomass	27
2.6	Physical and chemical properties of zinc, copper and chromium	30
2.7	Zinc, copper and chromium removal method	30
2.8	Factor influencing the extent of adsorption (Cloirec and Faur, 2006)	32
2.9	Comparison between physical adsorption and chemical adsorption (Al-Anber 2011)	34
3.1	Chemicals and reagents used according to experimental scopes	44
3.2	Materials and equipment used according to experimental scopes	45
4.1	Langmuir, Freundlich and Temkin parameters for the adsorption of heavy metals onto cryogel	86

4.2	Kinetic parameter of the Pseudo-first and second order and intraparticle diffusion model for the adsorption of heavy metals	89
4.3	Thermodynamic parameters for adsorption of heavy metals onto cryogel	92

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Oil palm frond	8
2.2	Representation of lignocellulose structure (Mussatto and Teixeira, 2010)	11
3.1	Research flowchart	43
3.2	Images of grinded OPF (a) Fresh OPF (b) Old OPF	46
3.3	Process flow for lignin extraction process	49
4.1	Percentage of lignin yield	57
4.2	Percentage of lignin yield (based on lignin content in OPF studied by Hussin <i>et al.</i> (2013))	58
4.3	Lignin yield increment	59
4.4	Percentage of lignin yield with the effect of temperature	60
4.5	FTIR spectra of commercial lignin and OPF lignin	61
4.6	(a) TG curve and (b) DTG curve for OPF lignin	63
4.7	Adsorption capacity at different amount of furfural used	66
4.8	Adsorption capacity at different amount of phenol used	67

4.9	Adsorption and desorption isotherms of nitrogen on cryogel at 77K	68
4.10	Pore size distribution of cryogel sample	69
4.11	X-Ray diffractogram of cryogel sample	70
4.12	FTIR spectrogram of cryogel sample	71
4.13	FESEM images of cryogel sample (a) 2500x (b) 5000x (c) 10000x magnification	72
4.14	(a) TG curve and (b) DTG curve of cryogel sample	73
4.15	Effect of varying contact time on heavy metals adsorption capacity of cryogel	75
4.16	Effect of varying contact time on heavy metals adsorption capacity of cryogel (0-30 minutes)	76
4.17	Effect of varying initial adsorbate concentration on heavy metals adsorption capacity of cryogel	77
4.18	Effect of pH on heavy metals adsorption capacity of cryogel	79
4.19	Effect of adsorbent dosage on heavy metals adsorption capacity of cryogel	81
4.20	Effect of temperature on heavy metals adsorption capacity of cryogel	82
4.21	Linearised Langmuir isotherm plots for heavy metals adsorption by cryogel : (a) zinc (b) copper (c) chromium	83
4.22	Linearised Freundlich isotherm plots for heavy metals adsorption by cryogel : (a) zinc (b) copper (c) chromium	84
4.23	Linearised Temkin isotherm plots for heavy metals adsorption by cryogel : (a) zinc (b) copper (c) chromium	85
4.24	Pseudo-first order kinetics for adsorption of heavy metals onto cryogel sample	87

4.25	Pseudo-second order kinetics for adsorption of heavy metals onto cryogel sample	88
4.26	Intraparticle diffusion plot for adsorption of heavy metals onto cryogel sample	90
4.27	Plot of $\ln K_d$ versus $1/T$ for estimation of thermodynamic parameters for the adsorption of heavy metals onto cryogel	91

LIST OF ABBREVIATIONS

A-CCB	-	Activated carbon cryogel bead
AC	-	Activated carbon
BET	-	Breuner, Emmer and Teller
CCB	-	Carbon cryogel bead
DTA	-	Derivative thermogravimetric
EPA	-	Environmental Protection Agency
FESEM	-	Field Emission Scanning Electron Microscopy
FRIM	-	Forest Research Institute Malaysia
FTIR	-	Fourier Transform Infrared Spectroscopy
HCl	-	Hydrochloric acid
HPLC	-	High performance liquid chromatography
IUPAC	-	International Union of Pure and Applied Chemistry
KBr	-	Potassium bromide
MPOB	-	Malaysian Palm Oil Board
NaOH	-	Sodium hydroxide
OH	-	Hydroxyl
OPF	-	Oil palm frond
PAN	-	Polyacrylonitrile
R&D	-	Research and Development
RF	-	Resorcinol-formaldehyde
RSM	-	Response Surface Methodology
S_{BET}	-	BET surface area
TG	-	Thermogravimetry
TGA	-	Thermogravimetric Analysis
XRD	-	X-Ray Diffraction
[BMIM]Cl	-	1-Butyl-3-Methylimidazolium Methyl Chloride

LIST OF SYMBOLS

C_e	-	Equilibrium concentration
C_o	-	Initial concentration
Hr	-	Hours
K	-	Kelvin
K_1	-	Equilibrium rate constant
K_f	-	Freundlich coefficient factor
k_1	-	Pseudo-first order equilibrium rate constant
k_2	-	Pseudo-second order equilibrium rate constant
k_{dif}	-	Intraparticle diffusion rate constant
L	-	Liter
M	-	Meter
mg	-	Miligram
min	-	Minutes
ml	-	Mililiter
mm	-	Milimeter
nm	-	Nano-meter
P	-	Gas pressure at time
P_o	-	Initial equilibrium gas pressure at time
q_e	-	Amount of adsorbent at equilibrium
q_t	-	Equilibrium rate constant
R^2	-	Correlation Coefficient
R_L	-	Langmuir constant
V	-	Volume of solution
wt%	-	Weight percent
wt/wt	-	Weight per weight
$^{\circ}C$	-	Degree Celcius

%	-	Percent
Å	-	Angstrom (10^{-9})
ΔG	-	Free Energy Change
ΔH	-	Enthalpy Change
ΔS	-	Entropy Change
μm	-	Micrometer
θ	-	Angle
i.e.	-	It is
>	-	Greater than
<	-	Less than
Rpm	-	Revolutions per minute
Cu	-	Copper
Cr	-	Chromium
Zn	-	Zinc

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Calculation of lignin yield	109
B	Calculation of adsorption capacity	110
C	Publication of research	111

CHAPTER 1

INTRODUCTION

1.1 Research Background

Disposal of effluents from industries like battery manufactures, leather tanning, painting, paper, electroplating and metal finishing has resulted in serious industrial wastewater problems, especially in terms of heavy metals contamination. Various metals such as zinc, nickel, chromium, copper, cadmium and mercury have harmful effects not only to human's health but also to the environment. Nowadays, the contamination of lakes and streams due to the presence of these heavy metals has become one of the serious problems faced by the country. Heavy metals can be easily absorbed by living organism as they have high solubility in aquatic environments. The problem of these heavy metals, especially those originating from industries, domestic sewage and landfills, has been a subject of research for a very long time. As one of the prevention steps to mitigate this problem, the United States Environmental Protection Agency, or EPA, has sanctioned for these heavy metals to be reduced to acceptable levels before the wastewater is discharged into the environment.

Nowadays, numerous methods are available to treat heavy metals. Some of the methods include adsorption, chemical precipitation, ion exchange and membrane filtration. Each of these treatment methods also has their own advantages and limitations. Adsorption is identified to be among the best and most practical method among the available techniques as it offers flexibility in their design and operation.

Other than that, adsorption also can give a high-quality treated effluent and most of the adsorbents can be regenerated for several times (Gayatri, 2010).

Recently, carbon cryogels showed a very high potential to be used as adsorbent in adsorption process. Conventionally, resorcinol-formaldehyde (RF) cryogels were synthesized by sol-gel polycondensation of resorcinol with formaldehyde and freeze-drying was carried out with t-butanol. Carbon cryogels were then obtained by pyrolyzing RF cryogels in an inert atmosphere (Babić *et al.*, 2004). According to Babić *et al.* (2004), characterization by nitrogen adsorption showed that carbon cryogels were micro and mesoporous materials with high surface areas ($500 \text{ m}^2/\text{g} < S_{\text{BET}} < 750 \text{ m}^2/\text{g}$). The porous structure of carbon cryogels is potentially advantageous as an adsorbent for treating wastewater containing heavy metals and organic pollutants (Dilaeleyana *et al.*, 2012).

However, even with all the advantages that carbon cryogels have, there are still some drawbacks in them. Carbon cryogels are costly when synthesized from conventional combination of alcohols such as resorcinol and phenol with formaldehydes. Besides that, phenol and resorcinol are categorized as harmful substances and the use of these two substances need to be reduced or eliminated as much as possible. Therefore, alternatives for phenolic compound that is low in cost, yet still effective as an adsorbent are vigorously being sought out. Consequently, it has been reported by several researchers that lignocellulosic biomasses can be used as raw materials in the substitution of phenolic compound for production of phenol-formaldehyde resin.

Lignin is one of the predominant compounds that exist in the lignocellulosic materials. Lignin is originally a macromolecule that is presented as the second major constituent after cellulose (Collinson and Thielemans, 2010). Compared to other wood components (cellulose and hemicelluloses), lignin is a much more complex polymer and has been considered for a long time as a low-quality and low-added-value material. However, new developing technologies allow the extraction of high-purity lignin which can be converted into various high-value chemicals and products such as phenol, carbon fibre and also vanillin (Ngadi *et al.*, 2014a). Many efforts

have been made to improve the reactivity of lignin as the substitute for phenol in phenol-formaldehyde resin synthesis. One of the methods is to modify the chemical structure of lignin to increase its potential reactive sites toward formaldehyde. Other methods, including reduction, oxidation and hydrolysis have also been studied to improve the reactivity of lignin as well as to produce phenolic compounds from lignin (Hu *et al.*, 2011).

The ecological, techno-economic and agro-climatic conditions in Malaysia are tending to be suitable for large scale planting of the oil palm. The industry grew rapidly and today, 4.69 million hectares of land in Malaysia is under oil palm cultivation and this contributes to about 37.3% of the world's total palm oil production. It is a known fact that Malaysia is the leading producer and exporter of palm oil in the world and oil palm has been as one of the major drivers for the country's economic growth. At this time, the amount of biomass that had been left to rot and returned to the field as fertilizer is vaulting. Malaysia has generated approximately 51 million tonnes of oil palm frond (OPF), accounting for 53% of the total palm biomass in 2008 (Goh *et al.*, 2010). From this number, it is expected that the ideas of extracting the lignin from OPF is very feasible to be explored.

1.2 Problem Statement

The application of carbon cryogel beads (CCBs) as an adsorbent in adsorption of heavy metals from wastewater had earned serious attention from time to time. Conventional preparations of CCBs usually involve the use of formaldehyde and phenol. However, massive usages of these two chemicals are unsafe to human health and can cause environmental pollution problems. The use of less harmful substances and raw materials that are cheaper in price is very important and vigorously been sought nowadays. One of the possibilities to significantly decrease the harmfulness and production cost is by using natural resources derived from biomass as the precursor. Many researchers have developed various studies involving lignin derived from biomass as phenol substitute in the synthesis of lignin modified resin.

Therefore, this study was aimed to investigate and explore an easier preparation method of cryogel from lignin of a renewable source, which is oil palm frond (OPF), without any addition of phenol during the synthesis process. In addition, the effect of ultrasound application during the process of lignin liquefaction was also studied. The use of ultrasound is believed to enhance and increase the production of lignin and shorten the process reaction time by inhibiting the formation of large molecular structures during liquefaction process (Kunaver *et al.*, 2012). Other than that, the performance of synthesized cryogel as a potential adsorbent to remove heavy metals from synthetic wastewater through adsorption, kinetic and thermodynamic study was employed. Successive utilization of OPF as a renewable resource will lead to a sustainable development that can help our palm oil industry to comply with zero-waste strategy and generate additional profits for the palm oil industry and promote the benefits of waste to wealth programme.

1.3 Research Objectives

The objectives of this study are:

- 1) To extract lignin from oil palm frond (OPF) via ultrasound-assisted method.
- 2) To synthesize and characterize cryogel produced from OPF.
- 3) To study the performance of synthesized cryogel as potential adsorbent for removal of heavy metal ions.

1.4 Scope of Study

In order to achieve the objectives, this research was extended into more specialized scope. Two types of OPF, which were fresh OPF and old OPF, were used as the raw materials of lignin extraction. For lignin extraction, two types of heating approaches; ultrasound assisted method and conventional heating, were used during the liquefaction process. Subsequently, two other variables, which were the

cooking liquor concentration (0-6.25M) and temperature (30-80°C) were manipulated in order to obtain the optimum conversion of the OPF and lignin yield.

In this study, the formation of cryogels was employed by sol-gel polycondensation of lignin-OPF with furfural, followed by freeze drying. Synthesis condition of these cryogels was manipulated by using different amounts of lignin to furfural ratio (1:1 – 1:4) and lignin to phenol ratio (1:0 – 1:0.075) during the sol-gel polycondensation process. Then, the physical properties of the best cryogels were characterized using BET, XRD, FTIR, FESEM and TGA.

The performance of the cryogels for the removal of simulated heavy metals through adsorption study was also investigated. Three types of heavy metal were used in these experiments, which were zinc, copper and chromium. The adsorption capacity was determined by using adsorption and kinetic study. The experimental conditions for adsorption test included time (1-360 minutes), initial concentration of adsorbate (0.2-5.0 mg/L), pH (2-12), weight of adsorbent (100-500 mg), and temperature (30-80°C).

For determination of heavy metals adsorption rate mechanism, kinetic studies of pseudo first-order, pseudo second-order and intraparticle diffusion were applied. Meanwhile, adsorption isotherm was determined through Langmuir, Freundlich and Temkin equations and the effect of temperature on the adsorption of heavy metals were determined based on the adsorption thermodynamic.

1.5 Significance of Study

This research is an industrial-driven research approach since it is based on the future need of the local waste water treatment. Normally, the production of cryogels involves the addition of phenol or resorcinol substance. The synthesis of cryogel from OPF is seems to be very promising as lignin extracted from OPF has the potential to substitute phenol in cryogel. The synthesis of cryogels was further

REFERENCES

- Acharya, J., Sahu, J. N., Sahoo, B. K., Mohanty, C. R., and Meikap, B. C. (2009). Removal of chromium(VI) from Wastewater by Activated Carbon Developed from Tamarind Wood Activated with Zinc Chloride. *Chemical Engineering Journal*, 150(1), 25–39.
- Achmad, A., Kassim, J., Suan, T. K., Amat, R. C., and Seey, T. L. (2012). Equilibrium, Kinetic and Thermodynamic Studies on the Adsorption of Direct Dye onto a Novel Green Adsorbent Developed from Uncaria Gambir Extract, 23(1), 1–13.
- Ahmadzadeh, A., Zakaria, S., and Rashid, R. (2009). Liquefaction of Oil Palm Empty Fruit Bunch (EFB) into Phenol and Characterization of Phenolated EFB Resin. *Industrial Crops and Products*, 30(1), 54–58.
- Aksu, Z., and Kutsal, T. (1991). A Bioseparation Process for Removing lead(II) Ions from Waste Water by Using *Chlorella Vulgaris*. *Journal of Chemical Technology and Biotechnology*, 52(1), 109–118.
- Al-Anber, M. A. (2011). Thermodynamics Approach in the Adsorption of Heavy Metals. *Thermodynamics - Interaction Studies - Solids, Liquids and Gases*, (ISBN: 978-953-307-563-1).
- Alluri, H. K., Ronda, S. R., Settalluri, V. S., Singh, J., Suryanarayana, V., and Venkateshwar, P. (2007). Biosorption: An Eco-Friendly Alternative for Heavy Metal Removal. *Journal of Biotechnology*, 6(25), 2924–2931.
- Alma, M. H., and Basturk, M. A. (2006). Liquefaction of Grapevine Cane (*Vitis Vinisera* L.) Waste and Its Application to Phenol-Formaldehyde Type Adhesive. *Industrial Crops and Products*, 24(2), 171–176.
- Al-Muhtaseb, S. a., and Ritter, J. a. (2003). Preparation and Properties of Resorcinol-Formaldehyde Organic and Carbon Gels. *Advanced Materials*, 15(2), 101–114.

- Alriols, M. G., Tejado, a., Blanco, M., Mondragon, I., and Labidi, J. (2009). Agricultural Palm Oil Tree Residues as Raw Material for Cellulose, Lignin and Hemicelluloses Production by Ethylene Glycol Pulping Process. *Chemical Engineering Journal*, 148(1), 106–114.
- Anirudhan, T. S., and Sreekumari, S. S. (2011). Adsorptive Removal of Heavy Metal Ions from Industrial Effluents Using Activated Carbon Derived from Waste Coconut Buttons. *Journal of Environmental Sciences*, 23(12), 1989–1998.
- Arriagada, R., Bello, G., García, R., Rodríguez-Reinoso, F., and Sepúlveda-Escribano, A. (2005). Carbon Molecular Sieves from Hardwood Carbon Pellets. the Influence of Carbonization Temperature in Gas Separation Properties. *Microporous and Mesoporous Materials*, 81(1-3), 161–167.
- Asakura, Y., Nishida, T., Matsuoka, T., and Koda, S. (2008). Effects of Ultrasonic Frequency and Liquid Height on Sonochemical Efficiency of Large-Scale Sonochemical Reactors. *Ultrasonics Sonochemistry*, 15(3), 244–250.
- Babić, B., Kaluđerović, B., Vračar, L., and Krstajić, N. (2004). Characterization of Carbon Cryogel Synthesized by Sol–gel Polycondensation and Freeze-Drying. *Carbon*, 42(12-13), 2617–2624.
- Balch, C. C. (1983). Protein Nutrition in Ruminants. *Agricultural Systems*, 11(2), 127–128.
- Basta, A. H., Fierro, V., El-Saied, H., and Celzard, A. (2009). 2-Steps KOH Activation of Rice Straw: An Efficient Method for Preparing High-Performance Activated Carbons. *Bioresource Technology*, 100(17), 3941–3947.
- Becquer, T., Quantin, C., Sicot, M., and Boudot, J. P. (2003). Chromium Availability in Ultramafic Soils from New Caledonia. *Science of the Total Environment*, 301(1-3), 251–261.
- Bhattacharya, a, Naiya, T., Mandal, S., and Das, S. (2007). Adsorption, Kinetics and Equilibrium Studies on Removal of Cr(VI) from Aqueous Solutions Using Different Low-Cost Adsorbents. *Chemical Engineering Journal*, 137, 529–541.
- Bilal, M., Shah, J. A., Ashfaq, T., Gardazi, S. M. H., Tahir, A. A., Pervez, A., Mahmood, Q. (2013). Waste Biomass Adsorbents for Copper Removal from Industrial Wastewater-A Review. *Journal of Hazardous Materials*, 263, 322–333.
- Björkman, A. (1954). Isolation of Lignin from Finely Divided Wood with Neutral Solvents. *Nature*.

- Boudrahem, F., Soualah, a., and Aissani-Benissad, F. (2011). Pb(II) and Cd(II) Removal from Aqueous Solutions Using Activated Carbon Developed from Coffee Residue Activated with Phosphoric Acid and Zinc Chloride. *Journal of Chemical & Engineering Data*, 56(5), 1946–1955.
- Bulut, Y., and Tez, Z. (2007). Removal of Heavy Metals from Aqueous Solution by Sawdust Adsorption. *Journal of Environmental Sciences*, 19(2), 160–166.
- Casas, A., Oliet, M., Alonso, M. V., and Rodríguez, F. (2012). Dissolution of Pinus Radiata and Eucalyptus Globulus Woods in Ionic Liquids under Microwave Radiation: Lignin Regeneration and Characterization. *Separation and Purification Technology*, 97, 115–122.
- Cloirec, P. Le, and Faur, C. (2006). Activated Carbon Surfaces in Environmental Remediation. *Interface Science and Technology*, 7, 375–419.
- Collinson, S. R., and Thielemans, W. (2010). The Catalytic Oxidation of Biomass to New Materials Focusing on Starch, Cellulose and Lignin. *Coordination Chemistry Reviews*.
- Corbo, M. D., and Lam, J. (2013). Zinc Deficiency and Its Management in the Pediatric Population: A Literature Review and Proposed Etiologic Classification. *Journal of the American Academy of Dermatology*, 69(4), 616–624.
- Corley, and Tinker. (2003). The Origin and Development of the Oil Palm Industry. In *The Oil Palm* (pp. 1–26). Blackwell Science Ltd.
- Cui, M., Jang, M., Cho, S.-H., and Khim, J. (2010). Kinetic and Thermodynamic Studies of the Adsorption of Heavy Metals on to a New Adsorbent: Coal Mine Drainage Sludge. *Environmental Technology*, 31(11), 1203–1211.
- Dahlan, I. (2000). Oil Palm Frond, a Feed for Herbivores. *Asian-Australasian Journal of Animal Sciences*, 13(SUPPL. C), 300–303.
- De Mello Ferreira, A., Marchesiello, M., and Thivel, P. X. (2013). Removal of Copper, Zinc and Nickel Present in Natural Water Containing Ca^{2+} and HCO_3^- Ions by Electrocoagulation. *Separation and Purification Technology*, 107, 109–117.
- Demirbas, E., Kobya, M., Senturk, E., and Ozkan, T. (2004). Adsorption Kinetics for the Removal of Chromium (VI) from Aqueous Solutions on the Activated Carbons Prepared from Agricultural Wastes. *Water SA*, 30(4), 533–539.
- Dilaeleyana A. B. S. (2013). *Synthesis and Characterization of Renewable Carbon*

Cryogel Beads from Empty Fruit Bunch for Adsorption of Ethyl Orange.
Universiti Teknologi Malaysia : Master's Thesis.

- Dilaeleyana, A. B. S., Norzita, N., Aishah, S. A. N., and Haw, K. E. (2012). Synthesis and Characterization of Renewable Carbon Cryogel Beads from Empty Fruit Bunch. *International Journal of Chemical and Environmental Engineering*, 3(2), 15–19.
- Duman, G., Onal, Y., Okutucu, C., Onenc, S., and Yanik, J. (2009). Production of Activated Carbon from Pine Cone and Evaluation of Its Physical , Chemical , and Adsorption Properties, 65(9), 2197–2204.
- Ebringerova, A., and Hromadkova, Z. (2010). An Overview on the Application of Ultrasound in Extraction, Separation and Purification of Plant Polysaccharides. *Central European Journal of Chemistry*, 8(2), 243–257.
- Evbuomwan, B. O., Agbede, A. M., and Atuka, M. M. (2013). A Comparative Study of the Physico-Chemical Properties of Activated Carbon from Oil Palm Waste (Kernel Shell and Fibre), 2(19), 75–79.
- Fu, F., and Wang, Q. (2011). Removal of Heavy Metal Ions from Wastewaters: A Review. *Journal of Environmental Management*, 92(3), 407–18.
- García, A., Erdocia, X., González Alriols, M., and Labidi, J. (2012). Effect of Ultrasound Treatment on the Physicochemical Properties of Alkaline Lignin. *Chemical Engineering and Processing: Process Intensification*, 62, 150–158.
- Gayatri, L. (2010). Adsorption Technique for the Removal of Phenolic Compounds from Wastewater Using Low-Cost Natural Adsorbents. *Assam University Journal of Science and Technology*, 156–166.
- Ge, F., Li, M.-M., Ye, H., and Zhao, B.-X. (2012). Effective Removal of Heavy Metal Ions Cd^{2+} , Zn^{2+} , Pb^{2+} , Cu^{2+} from Aqueous Solution by Polymer-Modified Magnetic Nanoparticles. *Journal of Hazardous Materials*, 211-212, 366–72.
- Girgis, B. S., Attia, A. A., and Fathy, N. A. (2011). Potential of Nano-Carbon Xerogels in the Remediation of Dye-Contaminated Water Discharges. *Desalination*, 265(1-3), 169–176.
- Girgis, B. S., El-Sherif, I. Y., Attia, A. A., and Fathy, N. A. (2012). Textural and Adsorption Characteristics of Carbon Xerogel Adsorbents for Removal of Cu (II) Ions from Aqueous Solution. *Journal of Non-Crystalline Solids*, 358(4), 741–747.

- Goh, C. S., Tan, H. T., Lee, K. T., and Mohamed, A. R. (2010). Optimizing Ethanolic Hot Compressed Water (EHCW) Cooking as a Pretreatment to Glucose Recovery for the Production of Fuel Ethanol from Oil Palm Frond (OPF). *Fuel Processing Technology*, 91(9), 1146–1151.
- Goh, C. S., Tan, K. T., Lee, K. T., and Bhatia, S. (2010). Bio-Ethanol from Lignocellulose: Status, Perspectives and Challenges in Malaysia. *Bioresource Technology*, 101(13), 4834–41.
- Grishechko, L. I., Amaral-Labat, G., Szczurek, a., Fierro, V., Kuznetsov, B. N., and Celzard, a. (2013). Lignin-Phenol-Formaldehyde Aerogels and Cryogels. *Microporous and Mesoporous Materials*, 168, 19–29.
- Gueu, S., Yao, B., Adouby, K., and Ado, G. (2007). Kinetics and Thermodynamics Study of Lead Adsorption on to Activated Carbons from Coconut and Seed Hull of the Palm Tree. *International Journal of Environmental Science & Technology*, 4(1), 11–17.
- Hameed, B. H., and El-Khaiary, M. I. (2008). Batch Removal of Malachite Green from Aqueous Solutions by Adsorption on Oil Palm Trunk Fibre: Equilibrium Isotherms and Kinetic Studies. *Journal of Hazardous Materials*, 154(1-3), 237–244.
- Hassim, H. A., Lourenço, M., Goel, G., Vlaeminck, B., Goh, Y. M., and Fievez, V. (2010). Effect of Different Inclusion Levels of Oil Palm Fronds on in Vitro Rumen Fermentation Pattern, Fatty Acid Metabolism and Apparent Biohydrogenation of Linoleic and Linolenic Acid. *Animal Feed Science and Technology*, 162(3-4), 155–158.
- Ho, Y. S., and McKay, G. (1998). A Comparison of Chemisorption Kinetic Models Applied To Pollutant Removal on Various Sorbents. *Process Safety and Environmental Protection*, 76(November), 332–340.
- Ho, Y. S., McKay, G., Wase, D. a. J., and Forster, C. F. (2009). Study of the Sorption of Divalent Metal Ions on to Peat. *Adsorption Science & Technology*, 18(7), 639–650.
- Holmberg, J., P. (2006). Competitive Adsorption and Displacement Behaviour of Heavy Metals on Peat. Chalmers University of Technology : Master's Thesis.
- Hu Lihong, Pan, Hui Zhou, Yonghong Zhang, M. (2011). Methods to Improve Lignin's Reactivity as a Phenol Substitute and as Replacement for Other Phenolic Compounds: A Brief Review. *Bioresources*, 6(3), 3515–3525.

- Huang, X. (2009). Fabrication and Properties of Carbon Fibers. *Materials*, 2(4), 2369–2403.
- Hussin, M. H., Rahim, A. A., Mohamad Ibrahim, M. N., and Brosse, N. (2013). Physicochemical Characterization of Alkaline and Ethanol Organosolv Lignins from Oil Palm (*Elaeis Guineensis*) Fronds as Phenol Substitutes for Green Material Applications. *Industrial Crops and Products*, 49, 23–32.
- Iqbal, M., and Saeed, A. (2002). Removal of Heavy Metals from Contaminated Water by Petiolar Felt-Sheath of Palm. *Environmental Technology*, 23(10), 1091–1098.
- Job, N., Théry, A., Pirard, R., Marien, J., Kocon, L., Rouzaud, J. N., Pirard, J. P. (2005). Carbon Aerogels, Cryogels and Xerogels: Influence of the Drying Method on the Textural Properties of Porous Carbon Materials. *Carbon*, 43(12), 2481–2494.
- Jonoobi, M., Harun, J., Shakeri, A., Misra, M., and Oksmand, K. (2009). Chemical Composition, Crystallinity, and Thermal Degradation of Bleached and Unbleached Kenaf Bast (*Hibiscus Cannabinus*) Pulp and Nanofibers. *BioResources*, 4(2), 626–639.
- Joshi, J., and Sahu, O. (2014). Adsorption of Heavy Metals by Biomass. *Journal of Applied and Environmental Microbiology*, 2(1), 23–27.
- Kennedy, L. J., Vijaya, J. J., and Sekaran, G. (2004). Effect of Two-Stage Process on the Preparation and Characterization of Porous Carbon Composite from Rice Husk by Phosphoric Acid Activation. *Industrial & Engineering Chemistry Research*, 43(8), 1832–1838.
- Kraiwattanawong, K., Sano, N., and Tamon, H. (2011). Low-Cost Production of Mesoporous Carbon/carbon Composite Cryogels. *Carbon*, 49(11), 3404–3411.
- Kriaa, A., Hamdi, N., and Srasra, E. (2010). Removal of Cu (II) from Water Pollutant with Tunisian Activated Lignin Prepared by Phosphoric Acid Activation. *Desalination*, 250(1), 179–187.
- Kunaver, M., Jasiukaitytė, E., and Cuk, N. (2012). Ultrasonically Assisted Liquefaction of Lignocellulosic Materials. *Bioresource Technology*, 103(1), 360–6.
- Lakherwal, D. (2014). Adsorption of Heavy Metals: A Review. *International Journal of Environmental Research and Development*, 4(1), 41–48.

- Li, M.-F., Sun, S.-N., Xu, F., and Sun, R.-C. (2012). Ultrasound-Enhanced Extraction of Lignin from Bamboo (*Neosinocalamus Affinis*): Characterization of the Ethanol-Soluble Fractions. *Ultrasonics Sonochemistry*, 19(2), 243–9.
- Li, W. C., Lu, A. H., and Guo, S. C. (2001). Characterization of the Microstructures of Organic and Carbon Aerogels Based upon Mixed Cresol-Formaldehyde. *Carbon*, 39(13), 1989–1994.
- Liang, L., Mao, Z., Li, Y., Wan, C., Wang, Ti., Zhang, L., and Zhang, L. (2006). Liquefaction of Crop Residues for Polyol. *Bioresources*, 1, 1–9.
- Lignimatch. (2010). Future Use of Lignin in - a Roadmap for Possible Nordic / Baltic, 16.
- Lim, S. H., Ibrahim, D., and Che Omar, I. (2012). Oil Palm Frond for the Production of Bioethanol. *International Journal of Biochemistry and Biotechnology*, 1(1), 7–11.
- Lozano-Castelló, D., Lillo-Ródenas, M. A., Cazorla-Amorós, D., and Linares-Solano, A. (2001). Preparation of Activated Carbons from Spanish Anthracite - I. Activation by KOH. *Carbon*, 39(5), 741–749.
- Lu, F., and Ralph, J. (2010). Lignin. *Cereal Straw as a Resource for Sustainable Biomaterials and Biofuels* (1st ed.). Elsevier.
- Mahvi, A.H., Maleki, A., Eslami, A. (2004). Potential of Rice Husk and Rice Husk Ash for Phenol Removal in Aqueous Systems. *I(4)*, 321–326.
- Mainka, H., Hilfert, L., Busse, S., Edelmann, F., Haak, E., and Herrmann, A. S. (2015). Characterization of the Major Reactions during Conversion of Lignin to Carbon Fiber. *Journal of Materials Research and Technology*.
- Maldhure, A. V., and Ekhe, J. D. (2011). Preparation and Characterizations of Microwave Assisted Activated Carbons from Industrial Waste Lignin for Cu(II) Sorption. *Chemical Engineering Journal*, 168(3), 1103–1111.
- Malherbe, S., and Cloete, T. E. (2002). Lignocellulose Biodegradation: Fundamentals and Applications. *Reviews in Environmental Science and Bio/Technology*, 1(2), 105–114.
- Mason, T. (1996). The Uses of Ultrasound in Food Technology. *Ultrasonics Sonochemistry*, 3(3), S253–S260.
- McCrary, E. (1991). The Nature of Lignin. *Alkaline Paper Advocate*, 4(4), 33–34.
- McKendry, P. (2002). Energy Production from Biomass (part 1): Overview of Biomass. *Bioresource Technology*.

- Michael, H. J., and Ayebaemi, I. S. (2005). Effects of Temperature on the Sorption of Pb^{2+} and Cd^{2+} from Aqueous Solution by *Caladium Bicolor* (Wild Cocoyam) Biomass. *Electronic Journal of Biotechnology*, 8(2), 162–169.
- Michot, L. J., and Villie, F. (2006). Surface Area and Porosity. *Science*.
- Mirbagheri, S. A., and Hosseini, S. N. (2005). Pilot Plant Investigation on Petrochemical Wastewater Treatment for the Removal of Copper and Chromium with the Objective of Reuse. *Desalination*, 171(1), 85–93.
- Mohamad Ibrahim, M. N., Nadiah, M. Y. N., Norliyana, M. S., Sipaut, C. S., and Shuib, S. (2008). Separation of Vanillin from Oil Palm Empty Fruit Bunch Lignin. *CLEAN – Soil, Air, Water*, 36(3), 287–291.
- Mohamad Ibrahim, M. N., Zakaria, N., Sipaut, C. S., Sulaiman, O., and Hashim, R. (2011). Chemical and Thermal Properties of Lignins from Oil Palm Biomass as a Substitute for Phenol in a Phenol Formaldehyde Resin Production. *Carbohydrate Polymers*, 86(1), 112–119.
- Mohan, D., Singh, K. P., and Singh, V. K. (2008). Wastewater Treatment Using Low Cost Activated Carbons Derived from Agricultural Byproducts - A Case Study. *Journal of Hazardous Materials*, 152(3), 1045–53.
- Mohtar, S. S., Tengku Malim Busu, T. N. Z., Md Noor, A. M., Shaari, N., Yusoff, N. A., Bustam Khalil, M. A., and Mat, H. B. (2015). Extraction and Characterization of Lignin from Oil Palm Biomass via Ionic Liquid Dissolution and Non-Toxic Aluminium Potassium Sulfate Dodecahydrate Precipitation Processes. *Bioresource Technology*, 192, 212–218.
- Mussatto, S., and Teixeira, J. (2010). Lignocellulose as Raw Material in Fermentation Processes. *Applied Microbiology and Microbial Biotechnology*, 2, 897–907.
- Ngadi, N., Halim, N., and Ibrahim, M. (2014a). Isolation and Characterization of Vanillin from Coconut Husk Lignin via Alkaline Nitrobenzene Oxidation. *Jurnal Teknologi*, 4, 19–23.
- Ngadi, N., Jusoh, M., Rahman, R., and Mohamad, Z. (2014b). Synthesis and Application of Carbon Cryogel Beads Using Coconut Husk for Dye Removal. *Applied Mechanics and Materials*, 695, 183–186.
- Pérez, J., Muñoz-Dorado, J., De La Rubia, T., and Martínez, J. (2002). Biodegradation and Biological Treatments of Cellulose, Hemicellulose and Lignin: An Overview. *International Microbiology*.

- Pierre, A. C., and Pajonk, G. M. (2002). Chemistry of Aerogels and Their Applications. *Chemical Reviews*, 102(11), 4243–4265.
- Rao, M. M., Rao, G. P. C., Seshaiyah, K., Choudary, N. V, and Wang, M. C. (2008). Activated Carbon from Ceiba Pentandra Hulls, an Agricultural Waste, as an Adsorbent in the Removal of Lead and Zinc from Aqueous Solutions. *Waste Management (New York, N.Y.)*, 28(5), 849–58.
- Rasat, M. S. M., Razak, W., Othman, S., Janshah, M., Aminuddin, M., Tamer, A. T., and Izyan, K. (2011). Properties of Composite Boards From Oil Palm Frond Agricultural Waste. *BioResources*, 6(4), 4389–4403.
- Rencoret, J., Gutiérrez, A., Nieto, L., Jiménez-Barbero, J., Faulds, C. B., Kim, H., and Del Río, J. C. (2011). Lignin Composition and Structure in Young versus Adult Eucalyptus Globulus Plants. *Plant Physiology*, 155(2), 667–82.
- Rodrigues, S., and Pinto, G. a. S. (2007). Ultrasound Extraction of Phenolic Compounds from Coconut (Cocos Nucifera) Shell Powder. *Journal of Food Engineering*, 80(3), 869–872.
- Salman, J. M. (2014). Optimization of Preparation Conditions for Activated Carbon from Palm Oil Fronds Using Response Surface Methodology on Removal of Pesticides from Aqueous Solution. *Arabian Journal of Chemistry*, 7(1), 101–108.
- Sari, A., Tuzen, M., Citak, D., and Soylak, M. (2007). Equilibrium, Kinetic and Thermodynamic Studies of Adsorption of Pb(II) from Aqueous Solution onto Turkish Kaolinite Clay. *Journal of Hazardous Materials*, 149(2), 283–291.
- Shrestha, R. M., Pradhananga, R. R., Varga, M., and Varga, I. (2011). Preparation of Activated Carbon for the Removal of Pb (II) from Aqueous Solutions, 28(Ii), 94–101.
- Sidik, D. A. B., Ngadi, N., and Amin, N. A. S. (2013). Optimization of Lignin Production from Empty Fruit Bunch via Liquefaction with Ionic Liquid. *Bioresource Technology*, 135, 690–6.
- Silva, B., Figueiredo, H., Neves, I. C., and Tavares, T. (2009). The Role of pH on Cr (VI) Reduction and Removal by Arthrobacter Viscosus. *Journal of Radioanalytical and Nuclear Chemistry*, (Vi), 100–103.
- Singh, R. P., Ibrahim, M. H., Esa, N., and Iliyana, M. S. (2010). Composting of Waste from Palm Oil Mill: A Sustainable Waste Management Practice. *Reviews in Environmental Science and Biotechnology*.

- Srivastava, N. K., and Majumder, C. B. (2008). Novel Biofiltration Methods for the Treatment of Heavy Metals from Industrial Wastewater. *Journal of Hazardous Materials*, 151(1), 1–8.
- Sulaiman, F., Abdullah, N., Gerhauser, H., and Shariff, a. (2010). A Perspective of Oil Palm and Its Wastes. *Journal of Physical Science*, 21, 67–77.
- Sun, F., and Chen, H. (2008). Enhanced Enzymatic Hydrolysis of Wheat Straw by Aqueous Glycerol Pretreatment. *Bioresource Technology*, 99(14), 6156–6161.
- Sun, R., and Tomkinson, J. (2002). Comparative Study of Lignins Isolated by Alkali and Ultrasound-Assisted Alkali Extractions from Wheat Straw. *Ultrasonics Sonochemistry*, 9(2), 85–93.
- Szczurek, a., Amaral-Labat, G., Fierro, V., Pizzi, a., Masson, E., and Celzard, a. (2011). The Use of Tannin to Prepare Carbon Gels. Part I: Carbon Aerogels. *Carbon*, 49(8), 2773–2784.
- Szczurek, A., Amaral-Labat, G., Fierro, V., Pizzi, A., and Celzard, A. (2013). New Families of Carbon Gels Based on Natural Resources. *Journal of Physics: Conference Series*, 416, 012022.
- Tamon, H., Ishizaka, H., Yamamoto, T., and Suzuki, T. (1999). Preparation of Mesoporous Carbon by Freeze Drying. *Carbon*, 37(12), 2049–2055.
- Tamon, H., Tamon, H., Ishizaka, H., Ishizaka, H., Mikami, M., Mikami, M., and Okazaki, M. (1997). Porous Structure of Organic and Carbon Aerogels Synthesized by Sol-Gel Polycondensation of Resorcinol with Formaldehyde. *Science*, 35, 791.
- Tan, K. T., Lee, K. T., Mohamed, A. R., and Bhatia, S. (2009). Palm Oil: Addressing Issues and towards Sustainable Development. *Renewable and Sustainable Energy Reviews*, 13(2), 420–427.
- Toma, M., Vinatoru, M., Paniwnyk, L., and Mason, T. J. (2001). Investigation of the Effects of Ultrasound on Vegetal Tissues during Solvent Extraction. *Ultrasonics Sonochemistry*, 8(2), 137–142.
- Treviño-Cordero, H., Juárez-Aguilar, L. G., Mendoza-Castillo, D. I., Hernández-Montoya, V., Bonilla-Petriciolet, a., and Montes-Morán, M. a. (2013). Synthesis and Adsorption Properties of Activated Carbons from Biomass of *Prunus Domestica* and *Jacaranda Mimosifolia* for the Removal of Heavy Metals and Dyes from Water. *Industrial Crops and Products*, 42(1), 315–323.

- Tsai, W. T., Chang, C. Y., Wang, S. Y., Chang, C. F., Chien, S. F., and Sun, H. F. (2001). Cleaner Production of Carbon Adsorbents by Utilizing Agricultural Waste Corn Cob. *Resources, Conservation and Recycling*, 32(1), 43–53.
- Tymchyshyn, M., and Xu, C. C. (2010). Liquefaction of Bio-Mass in Hot-Compressed Water for the Production of Phenolic Compounds. *Bioresource Technology*, 101(7), 2483–2490.
- United Nations Environmental Programme, Division of Technology, Industry and Economics International Environmental Technology Centre Osaka/Shiga, J. (2009). Converting Waste Agricultural Biomass into a Resource. *United Nations Environmental Programme*, 1–437.
- Vani, S., Sridevi, Y. V., and Lakshmi, M. V. V. C. (2012). A Review on Adsorption of Heavy Metals from Aqueous Solution. *Journal of Chemical , Biological and Physical Sciences*. 2(3), 1585–1593.
- Vijayakumar, G., Tamilarasan, R., and Dharmendirakumar, M. (2012). Adsorption, Kinetic, Equilibrium and Thermodynamic Studies on the Removal of Basic Dye Rhodamine-B from Aqueous Solution by the Use of Natural Adsorbent Perlite, 3(1), 157–170.
- Wadenbäck, J., Clapham, D., Gellerstedt, G., and Von Arnold, S. (2004). Variation in Content and Composition of Lignin in Young Wood of Norway Spruce. *Holzforschung*, 58(2), 107–115.
- Wang, X. S., Tang, Y. P., and Tao, S. R. (2009). Kinetics, Equilibrium and Thermodynamic Study on Removal of Cr (VI) from Aqueous Solutions Using Low-Cost Adsorbent Alligator Weed. *Chemical Engineering Journal*, 148(2-3), 217–225.
- Wanrosli, W. D., Zainuddin, Z., Law, K. N., and Asro, R. (2007). Pulp from Oil Palm Fronds by Chemical Processes. *Industrial Crops and Products*, 25(1), 89–94.
- Watkins, D., Nuruddin, M., Hosur, M., Tcherbi-Narteh, A., and Jeelani, S. (2014). Extraction and Characterization of Lignin from Different Biomass Resources. *Journal of Materials Research and Technology*, 4(1), 26–32.
- Yalçın Tepe, A. (2014). *Encyclopedia of Food Safety*. *Encyclopedia of Food Safety*. Elsevier.
- Yamamoto, T., Kim, S.-I., Chaichanawong, J., Apiluck, E., and Ohmori, T. (2009). Removal of Aqueous Organic Pollutants by Adsorption-Catalytic Process Using

- Mesoporous Carbon Beads Loaded with Metal Oxides. *Applied Catalysis B: Environmental*, 88(3-4), 455–461.
- Yamamoto, T., Ohmori, T., and Kim, Y. H. (2008). Preparation and Characterization of Monodisperse Carbon Cryogel Microspheres. *Microporous and Mesoporous Materials*, 112(1-3), 211–218.
- Yi, Z., Yao, J., Wang, F., Chen, H., Liu, H., and Yu, C. (2012). Removal of uranium(VI) from Aqueous Solution by Apricot Shell Activated Carbon. *Journal of Radioanalytical and Nuclear Chemistry*, 295(3), 2029–2034.
- Yoldas, B. E., Annen, M. J., and Bostaph, J. (2000). Chemical Engineering of Aerogel Morphology Formed under Nonsupercritical Conditions for Thermal Insulation. *Chemistry of Materials*, 12(8), 2475–2484.
- Yu, J., Zhang, J., He, J., Liu, Z., and Yu, Z. (2009). Combinations of Mild Physical or Chemical Pretreatment with Biological Pretreatment for Enzymatic Hydrolysis of Rice Hull. *Bioresource Technology*, 100(2), 903–908.
- Zainol, M. M., Amin, N. A. S., and Asmadi, M. (2015). Synthesis and Characterization of Carbon Cryogel Microspheres from Lignin–furfural Mixtures for Biodiesel Production. *Bioresource Technology*, 190, 44–50.
- Zhang, H., Tang, Y., Cai, D., Liu, X., Wang, X., Huang, Q., and Yu, Z. (2010). Hexavalent Chromium Removal from Aqueous Solution by Algal Bloom Residue Derived Activated Carbon: Equilibrium and Kinetic Studies. *Journal of Hazardous Materials*, 181(1-3), 801–8.
- Zhang, J., Zhou, Q., and Ou, L. (2012). Kinetic, Isotherm, and Thermodynamic Studies of the Adsorption of Methyl Orange from Aqueous Solution by Chitosan/alumina Composite. *Journal of Chemical and Engineering Data*, 57(2), 412–419.