

SWITCHABLE DIELECTRIC RESONATOR ANTENNA ARRAY FOR FIFTH
GENERATION APPLICATIONS

NOR HIDAYU BINTI SHAHADAN

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Electrical Engineering)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

APRIL 2018

Dedicated and thankful appreciation to,

My beloved husband, Mohd Zuhrie Mustamam

My precious daughter, Damia Syakirah & Damia Zulaikha

My supportive parents, Hj Shahadan & Hjh Misyah

My understanding parents-in-law, Hj Mustamam & Hjh Rahmah

*My supportive and inspirational supervisors, Dr Muhammad Ramlee Kamarudin,
Assoc. Prof. Dr. Mohd Haizal Jamaluddin & Prof. Dr. Yoshihide Yamada*

and also to my siblings, friends, lecturers & WCC Staffs

Thank you for the endless support and motivation.

ACKNOWLEDGEMENT

Alhamdulillah, all praise to Allah S.W.T, for His guidance and grace which had inspired and assisted me in every stage of this research journey, until I finally produced this valuable manuscript.

I would like to express my deepest gratitude to my supervisors Dr. Muhammad Ramlee bin Kamarudin, Assoc. Prof. Dr. Mohd Haizal Jamaluddin, and Prof. Dr. Yoshihide Yamada for their invaluable role, guidance, continuous motivations and courage throughout my study's journey. I would like to thank Kementerian Pendidikan Malaysia for sponsoring my study.

I would also like to take this opportunity to acknowledge technicians, Mr. Norhafizul Ismail, and Mr. Sharul Shaari for their technical assistance. Thank you also for WCC staffs for their support and courage. Also, I am grateful to have supportive friends, Huda, Amirah, Ros, Ainniesafina, Fazreen, Aliya, Liya, Azimah, Nurhafizah, Low, Raghu, Hashim, Shazwani, Nazleen, Inshirah, Shafina and Zareen.

My greatest gratitude to my family especially to my mother Misyah Hamir, my father Shahadan Mansor, my mother in-law Rahmah Sya'ban, my father in-law Mustamam Darus, my dearest siblings Noraza, Nor Hisham, Norhaida, and Norazlin, and my husband Mohd Zuhrie for their support and understanding that kept me going all the way through my PhD's study. I'm highly indebted to them.

Lastly, thanks to all my friends and people who have helped and supported me in different ways. Their contributions are greatly appreciated.

ABSTRACT

A new generation in telecommunication technology has evolved into 5G. Due to its shorter wavelength compared to the previous generation, this technology requires a wide bandwidth and high gain antenna to compensate for the added losses at a higher frequency. Therefore, a phased array capable of steering the direction of beam with high gain can be used to recover any additional losses. A dielectric resonator (DR) with a dielectric constant of 10 is used in the phased array antenna design and integrated on Rogers/RT Duroid 5880 with a conductor coating of 17.5 μm , a thickness of 0.254 mm, dielectric constant, ϵ_s of 2.2 and loss tangent, δ_{tan} of 0.001. All designs are simulated using Ansoft High Frequency Structural Simulator (HFSS) and the numerical analysis involved is done by using MATLAB. The performance of the reflection coefficient and the bandwidth of the fabricated antenna are verified using Vector Network Analyzer (VNA) while the radiation pattern and the antenna gain are tested in an anechoic chamber. The proposed switchable dielectric resonator antenna (DRA) array at 15 GHz is formed through three design stages. The first stage is formed by a single element DRA placed on the ground plane and fed through a narrow aperture. The impedance bandwidth achievable is 2.5 GHz for DRA excited in $TE_{1\delta 3}^y$ mode compared to 1.8 GHz for DRA excited in $TE_{1\delta 1}^y$ mode. Besides, the gain of the antenna has improved approximately by 10 dBi in comparison to 5.6 dBi when it was excited in $TE_{1\delta 1}^y$ mode. Then, a design is formed using three elements of DR named as DRA sub-array design. The driven DR at port 1 is fed by radio frequency (RF) source and the parasitic DRs at port 2 and 3 are excited by the driven DR through mutual coupling effect. A steerable beam is achieved by switching the termination capacitor on the parasitic elements. Then, two DRA sub-array configurations are designed and named as configuration A and configuration B, respectively. Both configurations are excited by a driven DR in $TE_{1\delta 3}^y$ mode while the parasitic DRs for configurations A and B are excited in the $TE_{1\delta 3}^y$ mode and $TE_{1\delta 1}^y$ mode, respectively. From the observation, configuration B demonstrates improved performance with $\pm 32^\circ$ steering angle and maximum gain of 9.63 dBi. Furthermore, configuration B has a narrower beamwidth compared to configuration A. The final stage design is formed by incorporating configuration B with a combination of two driven DRs using power divider and phase switching. The switchable DRA array achieved a maximum gain and bandwidth of 12.8 dBi and 3.1 GHz, respectively. Moreover, the switchable DRA array is able to steer at three various steering angles which are 0° , -30° and $+30^\circ$ with 3 dB beamwidth around 24° by using only 2 ports. Hence, the switchable DRA array is capable to cover 60° sector which is considered suitable for 5G applications.

ABSTRAK

Generasi baharu teknologi telekomunikasi telah berkembang kepada 5G. Disebabkan panjang gelombang yang lebih pendek berbanding generasi sebelumnya, teknologi ini memerlukan lebar jalur yang luas dan gandaan antena yang tinggi untuk mengimbangi penambahan kehilangan kuasa pada frekuensi tinggi. Oleh itu, tatasusunan berfasa yang berkebolehan untuk memandu arah alur dengan gandaan yang tinggi boleh digunakan untuk memulih sebarang kehilangan kuasa tambahan. Dielektrik resonator (DR) dengan pemalar dielektrik bernilai 10 digunakan di dalam rekabentuk tatasusunan antena berfasa dan disepadukan pada Rogers/RT Duroid 5880 dengan salutan pengalir $17.5 \mu\text{m}$, ketebalan 0.254 mm , pemalar dielektrik, ϵ_s 2.2 dan tangen kehilangan, δ_{tan} 0.001. Kesemua rekabentuk disimulasi dengan menggunakan *Ansoft High Frequency Structural Simulator* (HFSS) dan analisis berangka yang terlibat dilaksanakan menggunakan MATLAB. Prestasi pekali pantulan dan lebar jalur fabrikasi antena ditentusahkan menggunakan Penganalisis Rangkaian Vektor (VNA) manakala corak radiasi dan gandaan antena diuji di dalam kebuk tak bergema. Tatasusunan dielektrik resonator antena (DRA) bolehubah yang dicadangkan pada 15 GHz terbentuk melalui tiga peringkat rekabentuk. Peringkat pertama dibentuk daripada elemen tunggal DRA yang diletakkan disisi satah bumi dan disuap melalui bukaan sempit. Galangan lebar jalur boleh capai ialah 2.5 GHz untuk DRA yang diuja dalam mod $TE_{1\delta 3}^y$ berbanding 1.8 GHz untuk DRA yang diuja dalam mod $TE_{1\delta 1}^y$. Selain itu, gandaan antena telah diperbaiki lebih kurang 10 dBi berbanding 5.6 dBi apabila diuja dalam mod $TE_{1\delta 1}^y$. Kemudian, rekabentuk dibentuk menggunakan tiga elemen DR yang dinamakan rekabentuk subtatasusunan DRA. Pemacu DR di terminal 1 disuap oleh sumber frekuensi radio (RF) dan parasit-parasit DR di terminal 2 dan 3 diuja oleh pemacu DR melalui kesan gandingan bersama. Bolehpandu alur tercapai dengan mengubah kapasitor penamatan pada elemen-elemen parasit. Setelah itu, dua konfigurasi subtatasusunan antena direkabentuk dan dinamakan sebagai konfigurasi A dan konfigurasi B. Kedua-dua konfigurasi diuja oleh pemacu DR dalam mod $TE_{1\delta 3}^y$ manakala parasit DR untuk konfigurasi A dan konfigurasi B diuja dalam mod $TE_{1\delta 3}^y$ dan mod $TE_{1\delta 1}^y$, masing-masing. Daripada pemerhatian, konfigurasi B menunjukkan prestasi yang lebih baik dengan sudut pandu $\pm 32^\circ$ dan gandaan maksimum 9.63 dBi. Tambahan pula, konfigurasi B mempunyai lebar alur yang lebih sempit berbanding konfigurasi A. Peringkat rekabentuk terakhir dibentuk dengan menggunakan konfigurasi B yang menggabungkan dua pemacu DR dan digunakan bersama kuasa pembahagi dan fasa bolehubah. Tatasusunan DRA bolehubah telah mencapai gandaan maksimum dan lebar jalur masing-masing pada 12.8 dBi dan 3.1 GHz. Selain itu, tatasusunan DRA bolehubah mampu untuk memandu pada tiga sudut pandu iaitu 0° , -30° dan $+30^\circ$ dengan lebar alur 3 dB sekitar 24° dengan menggunakan hanya 2 terminal. Oleh itu, tatasusunan DRA bolehubah mampu untuk meliputi sektor 60° yang dianggap sesuai untuk aplikasi 5G.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xiii
	LIST OF ABBREVIATIONS	xx
	LIST OF SYMBOLS	xxii
	LIST OF APPENDICES	xxiii
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Problem Statement	3
	1.3 Objective of the Research	5
	1.4 Scope of the Research	6
	1.5 Contribution of the Research	7
	1.6 Thesis Outline	8
2	LITERATURE REVIEW	10
	2.1 Introduction	10
	2.2 5G technology	10
	2.3 Reviews on Dielectric Resonator Antenna	13
	2.4 Feeding Techniques of Dielectric Resonator Antenna	18
	2.5 Gain Enhancement of Dielectric Resonator Antenna	23
	2.5.1 Stacking Dielectric Resonator Antenna	23
	2.5.2 Integration of Additional Structure	24

	2.5.3	Dielectric Superstrates	25
	2.5.4	Excitation of Higher-order Mode	26
2.6		Bandwidth Enhancement of Dielectric Resonator Antenna	28
2.7		Antenna Array Characteristics	32
	2.7.1	Array Factor	33
	2.7.2	Directivity, Gain and Beamwidth	35
2.8		Phased Array Antenna	36
	2.8.1	Power divider	37
	2.8.2	Review on Beam Steering Antenna by using Parasitic Elements for Different Applications	38
	2.8.3	Review on related work for 5G Applications	43
2.9		Summary	48
3		RESEARCH METHODOLOGY	51
	3.1	Introduction	51
	3.2	Design Specifications	51
	3.3	Research Method Framework	53
	3.4	The Selection of Substrate	59
	3.5	Antenna Fabrication Process	60
	3.6	Antenna Testing and Measurement Process	62
	3.6.1	Reflection Coefficient Measurement	62
	3.6.2	Radiation Pattern and Gain Measurement	63
	3.7	Summary	66
4		SINGLE ELEMENT DIELECTRIC RESONATOR ANTENNA	67
	4.1	Introduction	67
	4.2	Geometry of the Single Element Dielectric Resonator Antenna	68
	4.3	Single Element DRA Excited in the Higher-order Mode, $TE_{1\delta 5}^y$ at 28 GHz	70
	4.3.1	Microstrip Line (ML) Feed	70
	4.3.2	Microstrip Slot Aperture (MSA) Feed	73
	4.3.3	Open-end Coplanar Waveguide (OECPW) Feed	75

4.3.4	Performance Comparison of Three Different Feeding Techniques	77
4.3.5	Performance of Different RT/Duroid 5880 Thickness	80
4.4	Single Element DRA Excited in the Fundamental Mode, $TE_{1\delta 1}^y$ at 15 GHz	82
4.5	Gain and Bandwidth Enhancement of Single Element DRA Excited in the Higher-order Mode, $TE_{1\delta 3}^y$ at 15 GHz	87
4.5.1	The Q -factor Analysis of Single Element DRA Excited in the $TE_{1\delta 3}^y$ mode through Control of Coupling Amount for bandwidth enhancement	90
4.5.2	Verification of the Single Element DRA Excited in the $TE_{1\delta 3}^y$ with Enhanced Gain and Bandwidth	96
4.6	Summary of the Proposed Single Element DRA	100
5	SWITCHABLE DIELECTRIC RESONATOR ANTENNA SUBARRAY	101
5.1	Introduction	101
5.2	Theoretical Basis of Beam Steering DRA with Parasitic Elements and Capacitor Loading	102
5.3	Design of the Switchable DRA Subarray Configuration A	107
5.3.1	Analysis of the DRA Subarray Configuration A with Implementation Parasitic Elements Excited in the $TE_{1\delta 3}^y$ mode.	108
5.3.2	Verification of the DRA Subarray Configuration A with Implementation Parasitic Elements Excited in the $TE_{1\delta 3}^y$ mode	122
5.4	Design of the Switchable DRA Subarray Configuration B	125
5.4.1	Analysis of the DRA Subarray Configuration B with Implementation of Parasitic Elements Excited in the $TE_{1\delta 1}^y$ mode.	126
5.4.2	Verification of the DRA Subarray Configuration B with Implementation Parasitic Elements Excited in the $TE_{1\delta 1}^y$ mode	135

5.5	Summary of the Proposed Switchable DRA Subarray design	139
6	HIGH-GAIN SWITCHABLE DIELECTRIC RESONATOR ANTENNA ARRAY	142
6.1	Introduction	142
6.2	Configuration of the Incorporated DRA Subarray	142
6.3	Power Divider and Switched-Line Phase Shifter	144
6.4	Configuration of the High-Gain Switchable DRA Array	152
6.5	Verification of the High-Gain Switchable Dielectric Resonator Antenna Array	155
6.6	Summary of the Proposed High-Gain Switchable DRA array	160
7	CONCLUSION AND FUTURE WORKS	161
7.1	Introduction	161
7.2	Conclusion	161
7.3	Future Works	162
	REFERENCES	164
	Appendices A – D	176 – 179

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Comparison of all generations	11
2.2	The summary on beam steering antenna by using parasitic elements	49
2.3	The proposed high-gain DRA array compared to the previous work	50
3.1	The parameters and specifications of the proposed design	52
3.2	The properties of RT/Duroid 5880	59
4.1	Design parameters for ML feed	73
4.2	Design parameters for MSA feed	75
4.3	Design parameters for OECPW feed	76
4.4	The volume to surface ratio in the DR excited in the $TE_{1\delta 1}^y$ mode at 15 GHz	83
4.5	Aperture coupled parameters for the single element DRA excited in the fundamental mode, $TE_{1\delta 1}^y$ at 15 GHz	84
4.6	The volume to surface ratio in the DR excited in the $TE_{1\delta 3}^y$ mode	91
4.7	Aperture coupled parameters for the single element DRA excited in the fundamental mode, $TE_{1\delta 3}^y$	93
4.8	Comparison between the calculated and simulated bandwidth at various widths of the microstrip line (W) of the DRA excited in the $TE_{1\delta 3}^y$ mode	95
4.9	The performance comparison of the designed single element DRA at 15 GHz	99
5.1	The radiation pattern characteristics of the Configuration A design	117
5.2	The switching configuration of the switchable DRA subarray Configuration A	121
5.3	Summarized results for various cases of the switchable DRA subarray Configuration A	125

5.4	Characteristics of the affected radiation pattern for the Configuration B design	133
5.5	The switching configuration of the switchable DRA subarray Configuration B	135
5.6	Summarized results for various cases of the switchable DRA subarray Configuration B	139
5.7	The performance comparison of the DRA subarray with the Configuration A and the Configuration B	140
5.8	Performance of the proposed DRA subarray compared to the previous work	141
6.1	The summarized dimension of power divider network	146
6.2	The switching configuration of the high-gain DRA array	153
6.3	Summarized results for various cases of the high gain DRA array	158
6.4	The performance comparison between high-gain switchable DRA array and conventional phased array DRA	159
6.5	Performance of the proposed high-gain DRA array compared to the previous work	160

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Millimeter wave spectrum. (a) Potential available bandwidth (b) LMDS bands	12
2.2	Experimental trials of six world-leading mobile technology vendors	13
2.3	Various shapes of DRAs	15
2.4	Geometry of rectangular DR on a ground plane	16
2.5	Field configuration for TE^y mode rectangular DR on the ground plane	18
2.6	Probe-fed rectangular DRA	19
2.7	Field distribution using probe feed to a rectangular DR (a) Side view (b) Top view	19
2.8	Microstrip line fed rectangular DRA	20
2.9	Field distribution using microstrip line feed to a rectangular DR (a) Side view (b) Top view	20
2.10	Field distribution using microstrip slot aperture feed to a rectangular DR (a) Side view (b) Top view	21
2.11	Microstrip slot aperture fed rectangular DRA (a) three dimensional view (b) cross-sectional view	21
2.12	Coplanar waveguide fed rectangular DRA	22
2.13	Field distribution using coplanar waveguide feed to a rectangular DR (a) Side view (b) Top view	22
2.14	Geometry of stacked cylindrical DRA	23
2.15	Geometry of stacked rectangular DRA	24
2.16	Configuration of surface mounted short horn as suggested in	24
2.17	High-gain mushroom shaped DRA structure as presented in	25
2.18	Cylindrical DRA with superstrate as presented in	26
2.19	Circularly Polarized Dielectric Resonator Antenna Based on FSS Superstrate as presented in	26
2.20	Gain enhancement by exciting in higher-order mode as suggested in	27

2.21	Electric field distributions of the HEM_{212} mode in the DRA	27
2.22	DRA excited by cavity backed with circular aperture	29
2.23	Wideband U-shaped slot fed dielectric resonator antenna	30
2.24	Configuration of the U-slot-excited hemispherical DRA	31
2.25	DRA excited with H shaped slot (a) construction view (b) H slot dimension	31
2.26	DRA excited with rectangular slot aperture	32
2.27	Pattern multiplication	33
2.28	A linear array of K radiating element	34
2.29	Antenna beamwidth definition	35
2.30	Conventional structure of beam steering	36
2.31	Three port network (T-junction)	37
2.32	Configuration of power divider with quarter-wave transformers	38
2.33	Configuration of Yagi Uda antenna	39
2.34	Configuration of three element steerable patch antenna	40
2.35	Configuration of three element steerable patch antenna with tuning stub	41
2.36	Configuration of beam steering patch antenna	41
2.37	Configuration of five element steerable patch antenna	42
2.38	Configuration of three element steerable DRA	43
2.39	Dielectric resonator based on MIMO antenna presented in	44
2.40	Configuration of dipole phased array antenna	44
2.41	Planar DRA array proposed in	45
2.42	Configuration of beam steerable antenna	45
2.43	Layout of switch beam antenna array presented in	46
2.44	4 x 4 phased array antenna	47
2.45	3 x 3 phased array antenna	47
3.1	The flow chart of the overall research framework	53
3.2	The flow chart of the single element DRA framework	56
3.3	The flow chart of the switchable DRA subarray framework	57
3.4	The flow chart of the high-gain switchable DRA array framework	58
3.5	The flow chart of the antenna fabrication process	61
3.6	The process to attach the DR	62
3.7	The S -parameter measurement using a VNA	63
3.8	The setup for radiation pattern and gain measurement	64
3.9	The control room setup	64
3.10	The block diagram of gain-transfer method	66

4.1	Rectangular DRA geometry	68
4.2	Configuration of the DRA with ML feed (a) 3D view (b) Top view	72
4.3	Reflection coefficients of the single DRA at various S with ML feed	72
4.4	Configuration of the DRA with MSA feed (a) 3D view (b) Top view	74
4.5	Characteristics of the reflection coefficients of the MSA feed	75
4.6	Configuration of the DRA with OECPW feed (a) 3D view (b) Top view	76
4.7	Characteristics of the reflection coefficients of the OECPW feed	76
4.8	Comparison of the simulated reflection coefficients for three different feeding techniques	77
4.9	3D simulated gain of the DRA for three different feeding technique (a) ML feed (b) MSA feed (c) OECPW feed	78
4.10	Comparison of the simulated radiation pattern of the DRA for three different feeding techniques (a) E -plane (x-z plane) (b) H -plane (y-z plane)	79
4.11	Comparison of the simulated E -fields of the DRA for three different feeding technique (a) ML feed (b) MSA feed (c) OECPW feed	79
4.12	Simulated reflection coefficients for different thickness of substrate	81
4.13	Simulated gain for different thickness of substrate	81
4.14	Simulated directivity for different thickness of substrate	82
4.15	Configuration of the DRA excited in the fundamental mode, $TE_{1\delta 1}^y$ at 15 GHz (a) 3D view (b) Top view	83
4.16	Simulated normalized $ H_y $ - field of the single element DRA excited in the $TE_{1\delta 1}^y$ at 15 GHz	83
4.17	Impedance matching of the single element DRA excited in the $TE_{1\delta 1}^y$ at 15 GHz	84
4.18	Total magnetic field for the single element DRA excited in the $TE_{1\delta 1}^y$ at 15 GHz	85
4.19	Photographs of the fabricated DRA excited in the fundamental mode, $TE_{1\delta 1}^y$ at 15 GHz (a) Top view without DR (b) 3D view with DR (b) Back view	85
4.20	Reflection coefficients of the single element DRA excited in the $TE_{1\delta 1}^y$ at 15 GHz	86

4.21	Verification dimension of the fabricated DR excited in the $TE_{1\delta 1}^y$ mode at 15 GHz (a) w and d (b) h	86
4.22	Radiation pattern of the single element DRA excited in the fundamental mode, $TE_{1\delta 1}^y$ at 15 GHz (a) E - plane (b) H - plane	87
4.23	Magnetic dipole model of the single element DRA excited in the $TE_{1\delta 3}^y$ at 15 GHz	88
4.24	Configuration of the DRA excited in the higher-order mode, $TE_{1\delta 3}^y$ at 15 GHz (a) 3D view (b) Top view	89
4.25	Gain at various height of the DR excited in the higher-order mode, $TE_{1\delta 3}^y$ at 15 GHz	89
4.26	Simulated normalized $ H_y $ - field of the single element DRA excited in the $TE_{1\delta 3}^y$ at 15 GHz	90
4.27	Characteristics of the impedance bandwidth performance of the DRA excited in the $TE_{1\delta 3}^y$ mode with (a) different slot widths, W_s (b) different stub lengths, S (c) different microstrip line widths, W	92
4.28	Total magnetic field for the DRA excited in the (a) $TE_{1\delta 3}^y$ mode before optimization (b) $TE_{1\delta 3}^y$ mode after optimization	94
4.29	Normalized total H -field for various widths of the microstrip line, W	95
4.30	Loaded Q -factor influenced by coupling mechanism	96
4.31	Photographs of the fabricated DRA excited in the higher-order mode, $TE_{1\delta 3}^y$ at 15 GHz (a) Top view without DR (b) 3D view with DR (c) Back view	97
4.32	Impedance matching of the single element DRA excited in the $TE_{1\delta 3}^y$ at 15 GHz	97
4.33	Reflection coefficients of the single element DRA excited in the $TE_{1\delta 3}^y$ at 15 GHz	98
4.34	Verification dimension of the fabricated DR excited in the $TE_{1\delta 3}^y$ mode at 15 GHz (a) w and d (b) h	98
4.35	Radiation pattern of the single element DRA excited in the fundamental mode, $TE_{1\delta 3}^y$ at 15 GHz	99
5.1	The DRA subarray lying along the y -axis	103
5.2	The top view layout of the DRA subarray with driven and parasitic elements	103
5.3	3 - port network diagram	105
5.4	DRA subarray Configuration A with 3-port network	107

5.5	Characteristics of the mutual impedance (Z_{21}) for the Configuration A design with various distances, d	108
5.6	Characteristics of the reflection coefficients (Port 1) for the Configuration A design with various distances, d	109
5.7	Variation of Γ with capacitance C_A for the Configuration A design (a) magnitude of Γ (b) phase of Γ	110
5.8	Variation of (a) the current ratio and (b) the phase difference with the capacitance C_B for the Configuration A design	111
5.9	Normalized array factor (AF) for the Configuration A design with capacitive load	112
5.10	DRA subarray Configuration A with the capacitor loading	113
5.11	Characteristics of the reflection coefficient for Configuration A design with various length, L (a) $C_A = C_B = 0.01 pF$ (main beam) (b) $C_A = 0.01 pF$, $C_B = 1 pF$ (steered beam)	114
5.12	Characteristics of the radiation pattern for Configuration A design with various length, L (a) $C_A = C_B = 0.01 pF$ (main beam) (b) $C_A = 0.01 pF$, $C_B = 1 pF$ (steered beam)	115
5.13	Simulated radiation pattern at H -plane of the Configuration A design (a) $C_A = C_B$ (b) $C_A > C_B$ (c) (b) $C_A < C_B$	116
5.14	Simulated 3-D beam pattern with H -field inside the DR of the Configuration A design at $\pm 26^\circ$ steering angles	117
5.15	H_y -field distribution of the Configuration A design in the H -plane (a) $C_A = C_B = 0.01 pF$ (b) $C_A = 0.1 pF$, $C_B = 0.01 pF$ (c) $C_A = 0.01 pF$, $C_B = 0.1 pF$ (d) $C_A = 1 pF$, $C_B = 0.01 pF$ (e) $C_A = 0.01 pF$, $C_B = 1 pF$	118
5.16	The equivalent circuit of DRA subarray with capacitor loading	119
5.17	The geometrical of the switchable DRA Subarray Configuration A (a) Top view (b) 3D view	120
5.18	Analysis of the capacitor position for the Configuration A design (a) 0.1 pF (b) 1 pF	121
5.19	A prototype of the fabricated switchable DRA subarray Configuration A (a) Top view without DR (b) Top view with DR (c) 3D view (d) Back view	122
5.20	Reflection coefficient of various cases for the switchable DRA subarray Configuration A (a) Simulated (b) Measured	123
5.21	Simulated and measured normalized beam pattern of the Configuration A design (a) Case I; (b) Case II and Case III; (c) Case IV and Case V.	124

5.22	DRA subarray Configuration B with 3-port network	126
5.23	Comparison characteristics of the mutual impedance (Z_{21}) with various distance, d	127
5.24	Characteristics of the reflection coefficients for the Configuration B design with various distance, d	127
5.25	Variation of Γ with capacitance C_A for the Configuration B design	128
5.26	The comparison variation of (a) the current ratio and (b) the phase difference with the capacitance C_B	128
5.27	The comparison of normalized array factor (AF) with capacitive load	129
5.28	DRA subarray Configuration B with capacitor loading	129
5.29	Characteristics of the reflection coefficient of Configuration B design with various length, L (a) $C_A = C_B = 0.01 \text{ pF}$ (main beam) (b) $C_A = 0.01 \text{ pF}$, $C_B = 1 \text{ pF}$ (steered beam)	130
5.30	Characteristics of the radiation pattern Configuration B design with various length, L (a) $C_A = C_B = 0.01 \text{ pF}$ (main beam) (b) $C_A = 0.01 \text{ pF}$, $C_B = 1 \text{ pF}$ (steered beam)	131
5.31	Simulated radiation pattern at H -plane of the Configuration B design (a) $C_A = C_B$ (b) $C_A > C_B$ (c) (b) $C_A < C_B$	132
5.32	H_y -field distribution of the Configuration B design (a) $C_A = C_B = 0.01 \text{ pF}$ (b) $C_A = 0.1 \text{ pF}$, $C_B = 0.01 \text{ pF}$ (c) $C_A = 0.01 \text{ pF}$, $C_B = 0.1 \text{ pF}$ (d) $C_A = 1 \text{ pF}$, $C_B = 0.01 \text{ pF}$ (e) $C_A = 0.01 \text{ pF}$, $C_B = 1 \text{ pF}$	133
5.33	The geometrical of the switchable DRA Subarray Configuration B (a) Top view (b) 3D view	134
5.34	A prototype of the fabricated DRA subarray Configuration B (a) Top view without DR (b) Top view with DR (c) 3D view (d) Back view	136
5.35	Reflection coefficient of various cases for the DRA subarray Configuration B (a) Simulated (b) Measured	137
5.36	Simulated and measured normalized beam pattern of the Configuration B design (a) Case I; (b) Case II and Case III; (c) Case IV and Case V.	138
6.1	Configuration of the high-gain DRA array	143
6.2	Radiation pattern of the high-gain DRA array with two excitation ports	144
6.3	Layout of power divider with quarter-wave transformers	145
6.4	Top view layout dimensions of power divider network	146

6.5	<i>S</i> -parameter analysis by varying a in the reference arm (a) S_{11} (b) S_{21} (c) S_{31}	147
6.6	Phase difference characteristics by varying a in the reference arm	148
6.7	Dimension of top view layout of power divider network with switched-line phase shifter	148
6.8	<i>S</i> -parameter analysis by varying l_d in the delay arm (a) S_{11} (b) S_{21} (c) S_{31}	150
6.9	Phase response characteristics by varying the length l_d	151
6.10	Phase difference characteristics by varying the length l_d	151
6.11	The geometrical of the high-gain switchable DRA array (a) Top view (b) 3D view	152
6.12	Surface current distribution of the high-gain switchable DRA array (a) Case A (b) Case B (c) Case C	154
6.13	A prototype of the fabricated high-gain switchable DRA array (a) Top view without DR (b) Top view with DR (c) 3D view (d) Back view	155
6.14	Simulated and measured reflection coefficient for various cases of the high gain DRA array (a) Case A; (b) Case B; (c) Case C	156
6.15	Simulated and measured normalized beam pattern for various cases of the high gain DRA array (a) Case A; (b) Case B; (c) Case C	157
6.16	Configuration of the conventional phased array DRA excited in the $TE_{1\delta 3}^y$ mode	159

LIST OF ABBREVIATIONS

HFSS	-	High Frequency Structural Simulator
VNA	-	Vector Network Analyzer
DRA	-	Dielectric Resonator Antenna
DR	-	Dielectric Resonator
RF	-	Radio Frequency
AMPS	-	Advance Mobile Phone Service
GSM	-	Global System for Mobile
WCDMA	-	Wideband Code Division Multiple Access
LTE	-	Long Term Evaluation
LTE-A	-	Long Term Evaluation-Advanced
3GPP	-	3rd Generation Partnership Project
1G	-	First Generation
2G	-	Second Generation
3G	-	Third Generation
4G	-	Fourth Generation
5G	-	Fifth Generation
LMDS	-	Local Multipoint Distribution Services
PCB	-	Printed Circuit Board
ESPAR	-	Electronically Steerable Passive Array Radiator
ML	-	Microstrip Line
MSA	-	Microstrip Slot Aperture
OECPW	-	Open-end Coplanar Waveguide
CPW	-	Coplanar Waveguide
HPBW	-	Half Power Beamwidth
mmW	-	Millimeter Wave
CSPA	-	Circular Switched Parasitic Array
PTFE	-	Polytetrafluoroethylene

EP	-	Element Pattern
AF	-	Array Factor

LIST OF SYMBOLS

$\%$	-	Percentage
μ_0	-	Permeability of freespace
ω	-	Angular frequency
k_0	-	Wavenumber
θ	-	Angle
β	-	progressive phase shift
η	-	Efficiency
t_s	-	Thickness of substrate
c	-	Velocity of light
ε_s	-	Dielectric constant/Relative permittivity of substrate
ε_r	-	Dielectric constant/Relative permittivity of DR
ε_{eff}	-	Effective dielectric constant
ε_e	-	Slot effective permittivity
λ	-	Wavelength
λ_g	-	Guided Wavelength
Ω	-	Ohm
δ	-	Loss tangent/Dissipation factor
Γ	-	Reflection Coefficient
$\Delta\phi$	-	Differential phase shift
χ	-	Coupling amount

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	List of Publications	176
B	Datasheet of Rogers RT/Duroid 5880	177
C	Matlab Programming for DRA Dimension	178
D	Datasheet of Capacitor	179

CHAPTER 1

INTRODUCTION

1.1 Introduction

Telecommunication innovation has advanced quickly from the original (1G) to the fifth generation (5G). The 1st generation (1G) was pioneered for voice service in early 1980's, where almost all of them were using analog systems in the frequency band 824-894 MHz. It was based on a technology known as Advance Mobile Phone Service (AMPS) [1]. Then, the 2nd generation (2G) was accomplished in 1990's in the frequency band 850-1900 MHz intended for Global System for Mobile (GSM) technology. In the frequency band 1.8 - 2.5 GHz, 3rd generation (3G) based on Wideband Code Division Multiple Access (WCDMA) technologies was introduced to offer high speed wireless internet access in addition to the conventional voice service. Although the 3G technologies deliver significantly higher bit rates than 2G technologies, consumers and business professionals keep demanding for the high quality services, low latency, and the improved system capacity and coverage. Hence, the solution is Long Term Evolution (LTE) that was standardized by the 3rd Generation Partnership Project (3GPP), the next generation network beyond 3G. The LTE operates over different frequency bands from 400 MHz up to 4 GHz with bandwidth from 1.4 to 20 MHz [2]. The 4th generation (4G) usually refers to the successor of the 3G and 2G standards. The LTE release 10, also known to as LTE-Advanced (LTE-A), is claimed to be the true 4G evolution step with the frequency band from 2 GHz to 8 GHz [3].

Presently, telecommunication technology has significantly changed everyday life of individuals with expanding interest in boundless access to data and information sharing [4]. Considering the path ahead, there are a few patterns that will debilitate the abilities of existing media transmission, for example, explosive development of data traffic, a massive increase in the number of interconnected devices and the consistent rise of new services and application scenarios. To coordinate the patterns, 5G is

expected to penetrate into every aspect of the future society to create a user-centric information ecosystem. The 5G technology is expected to complete the 4G technology and provide solutions to the shortage arising from 4G technologies. It includes all kinds of advanced features which make it most forceful and immense request in the near future. Consequently, the increase in usage and the demand for simultaneous communication between devices cause interference, especially at higher frequencies in 5G. Therefore, as a 5G requirements, a smart device embedded with a bandwidth more than 1 GHz [5] and the antenna gain more than 12 dBi [6] is required to encounter the increasing traffic demands and to address the interference problems [7][8].

Subsequently, this technology has drawn attention to millimeter-wave bands in a frequency spectrum from 3-300 GHz with reduced wavelengths ranging from 100 mm to 1 mm [5]. Meanwhile, the Federal Communications Commission (FCC) has allocated the entire spectrum for different services and auctioned the spectrum for Local Multipoint Distribution Services (LMDS) [9]. The LMDS operating on frequencies from 28 to 30 GHz was conceived as a broadband, fixed wireless and point-to-multipoint technology. Apart from that, Ofcom has stated that the spectrum above 6 GHz has gained so much attention for future networks and 15 GHz is one of the potential 5G spectrum bands as mentioned by Ericsson [10]. Hence, this frequency has been attracted the interest of researchers to conduct research towards 5G applications [11][12][13][14].

Based on Friss formula, it is often assumed that higher frequencies propagate poorly in free space compared to the lower frequencies. The reason for this misconception is the underlying assumption often used in equation (1.1) that the path loss is calculated at a specific frequency between two isotropic antennas [9]

$$L_{FSL} = 92.4 + 20 \log_{10} f + 20 \log_{10} R \quad (1.1)$$

where f = frequency (GHz) and R = distance between two isotropic antennas (km). The $20 \log_{10} f$ indicates that the loss is frequency dependent due to losses exist in the spreading beam from point to point at the speed of light.

Consequently, the antenna gain needs to be increased to compensate the anticipated incremental loss. In addition, a directional antenna is also indispensable

to satisfy the necessities of a long distance communication [15]. Therefore, the case of directional transmit antenna with transmission gain, G_t are considered as stated in equation (1.2) [16][17].

$$G_t = \frac{4\pi A_{eff}}{\lambda^2} \quad (1.2)$$

For the same antenna aperture areas (A_{eff}), shorter wavelengths (higher frequencies), λ should not have any inherent disadvantage compared to longer wavelengths (lower frequencies) in terms of free space loss. However, with shorter wavelengths more antennas can be packed into the same area [18].

Accordingly, in order to fulfill the 5G requirements as stated previously, multiple antennas in the phased array that is capable of steering the direction beam with the gain more than 12 dBi [6] can be used to recover the additional loss as well as to support the required access and the reconfigurable backhaul link [19]. Backhaul can be reconfigured to allow transmission between point to point and point to multipoint applications. In addition, more than 1 GHz of the antenna bandwidth is needed to meet the requirements [5]. Thereby, in this thesis, antenna array designed with phased shift capability is presented. The following section highlights the motivation towards this research study.

1.2 Problem Statement

The complex phased array design that incorporates power distribution network, phase shifter and bias component has produced a larger overall dimension [20][21]. Meanwhile, phase shifters are expensive and require intricate feeding networks that will introduce more losses at higher frequencies [20][22]. Thus, to solve the problem, new phased arrays need to be developed by using different techniques. The switchable antenna array can be constructed by using a linear array which consists of only one driven element and the remaining are of parasitic elements. In this light, the phase shift between elements is adjustable by switching the capacitive loading of the parasitic elements. In the interest to have the switchable antenna array that fulfills the 5G

requirements, there are crucial issues need to be concerned starting with the single element design.

Microstrip patch antennas built on printed circuit board (PCB) substrate, are attractive due to their various features such as, light weight, low cost and easy fabrication. However, the microstrip element is affected by the inherent limitation of narrow impedance bandwidth causing poor performance due to high substrate losses and low radiation efficiency at mm-wave frequencies [23][24][25][26]. Recent studies also indicated that DRAs have an intriguing advantages as a promising candidate to replace traditional radiating elements at high frequencies, especially at millimeter waves and beyond [27][28][29][30][31]. This is mainly attributed to the fact that DRAs do not suffer from conduction losses and are characterized by high radiation efficiency when excited properly [24][32][33]. In addition, single element DRAs are normally excited in the fundamental mode with an ordinary gain of about 5 dBi, when employed on a large ground plane [34]. Several approaches in [35], [36], [37], [38] and [39] are suggested to increase the gain of the DRAs. In some of these cases, it can also improve the impedance bandwidth of the antenna. Nevertheless, most of these methods caused a significant increase in surface area, complexity and costs. Altering the single element DRA by utilizing higher-order radiation modes is another technique to increase the gain [40]. However, the impedance bandwidth decreases as the height of the dielectric resonator (DR) is increased. This is due to the larger ratio of volume (V) to surface (S) in the higher-order mode compared to the fundamental mode that can also cause the Q -factor to increase.

Past researchers had conducted electronically steerable passive array radiator (ESPAR) investigations on patch elements [41] and wire [42] to steer the antenna beam without using any phase shifters. However, the microstrip ESPAR had a limited steer angle at the boresight direction, while the steerable beam in [22] just achieved the angle of $\pm 20^\circ$ and in [43], it achieved $\pm 15^\circ$. Besides that, the microstrip ESPAR has produced a narrow impedance bandwidth and the performance of antenna gain was less than 8.0 dBi [44][45][46]. Thus, in comparison to the microstrip antennas, the DRA have shown various benefits, such as wider bandwidth and low loss. In recent years, the dielectric resonator antenna (DRA) ESPAR was fed through the microstrip line [47], which is typically excited in the fundamental mode without considering the effect of mutual impedance by the different distance between the DR and the effect of H -field distribution inside the DR. Despite that, the impedance bandwidth between DRA ESPAR in [47] and microstrip ESPAR in [43] was more or less the same. Thus, this research proposes a new concept of DRA ESPAR by using higher-order mode

excitation that have never been studied in ESPAR design. This will significantly result in a higher gain, wider bandwidth and better of steering capability.

By taking the 5G's specification requirements into consideration, the antenna design should achieve the gain of more than 12 dBi [6]. With that, related work has been done in [48], [49] , and [50] in determining potential frequency of 5G and meet the specifications. Consequently, it has increased the antenna elements and the number of phase controls, resulted in increase of cost and complexity of the design.

Based on these concerns, to secure a high-gain DRA array that is capable of switching the direction beam, new high-gain DRA array design will be proposed with a goal to steer the direction beam without using any external phase shifter. The implementation of a new concept DRA ESPAR resulted in reducing the number of antenna elements and phase controls.

1.3 Objective of the Research

This research is based on the following accompanying objectives:

1. To design and analyze a single element DRA by improving the gain (more than 5 dBi) and bandwidth (more than 1 GHz) that will be used to form a DRA subarray.
2. To apply the selected most practicable design of single element DRA in constructing the DRA subarray with switchable beam capability operating at 15 GHz.
3. To design high-gain (more than 12 dBi) switchable DRA array that consists of the incorporated DRA subarray at 15 GHz.

By achieving the stated objectives with good performance results, the proposed high-gain switchable DRA array can be a potential design solutions for 5G applications.

1.4 Scope of the Research

This research focuses on the design of high-gain switchable DRA array that is suitable for 5G applications requirement as stated in section 1.1. A high-gain switchable DRA array, consists of switchable DRA subarray and power divider network that is being integrated with switched-line phase shifter. In order to develop a high-gain switchable DRA array, the scope of this research is divided into three parts, which is single element DRA, switchable DRA subarray and high-gain switchable DRA array. Prior to that, various investigation on different feeding techniques of the single element DRA excited in the higher-order mode are studied at frequency 28 GHz. However, when the DRA is mounted on a ground plane, only odd mode can exist in the z -direction of DR. Therefore, mode 5 ($TE_{1\delta 5}^y$) in the z -direction is used to investigate the different feeding technique for DRA after considering mode 3 is nearly to the fundamental mode ($TE_{1\delta 1}^y$). Three techniques of the feeding structures, which is microstrip line (ML), microstrip slot aperture (MSA) and open-end coplanar waveguide (OECPW) are designed, simulated and optimized. The studies are carried out in order to identify the best feeding technique that is most appropriate for 5G requirements in terms of bandwidth, radiation pattern and gain of the single element DRA especially those excited in the higher-order mode. The design, simulation and optimization process are performed using Ansoft High Frequency Structural Simulator (HFSS) ver. 16.0.

Next, based on the best feeding technique chosen, the single element DRA is designed at 15 GHz for the realization of the fabrication and measurement process. This is due to the limited range of the measurement facilities that up to 20 GHz. According to research done in [51] and [52], there is not much difference in radiation pattern behavior between the 28 GHz and 15 GHz antennas. However, the antenna dimension at 15 GHz is slightly larger than 28 GHz due to its wavelength. The analytical study of the single element which involved the DRA excited in the fundamental mode ($TE_{1\delta 1}^y$) and higher-order mode ($TE_{1\delta 3}^y$) will be performed to observe and compare the behavior in 5G performance. Then, the determining factors of the coupling amount that can reduce the Q -factor and increased the bandwidth of the antenna in the higher-order mode ($TE_{1\delta 3}^y$) will be established. In this regard, the higher-order mode is stipulated with an index numbers $m = 1$ and $n = 3$ at 15GHz. With the excitation index number, n more than 3, it will increase the height of DRA and resulted in very limited practical applications at 15 GHz.

Subsequently, the best performance of the single element DRA will be

promoted as a driven element in the construction of DRA subarray. In order to steer the beam, a phased array with analog beam steering capability will be designed. It will conveniently be adjustable by changing the reactance of capacitors on the parasitic elements. The investigation with regards to the beam steering in theory and based on the simulation, as well as the six controlling ideal switches embedded in the feed line of the parasitic elements are explained to manage the beam switching.

Lastly, the DRA subarray design is used and incorporated into a high-gain DRA array by using power divider network. While, the phase shift between the DRA subarray will be achieved by integrating the switched-line phase shifter at one of the transmission line in the power divider network. The performance of high-gain DRA array will be analyzed and investigated at 15 GHz. All fabricated design are verified and experimentally tested by using a vector network analyzer (VNA) and measured in an Anechoic Chamber. The simulated and measured results, including reflection coefficients, bandwidth, gain and switching angle, are then analyzed and discussed.

1.5 Contribution of the Research

In this thesis, four major contributions are presented. The first contribution is the determination of microstrip slot aperture (MSA) as the best feeding technique of the single element DRA excited in the higher-order mode, $TE_{1\delta 5}^y$ at 28 GHz compared to microstrip line (ML) and open-end coplanar waveguide (OECPW). This investigation neither being done nor reported by other researchers and publications.

The second contribution is a design of higher-order mode DRA with enhanced bandwidth and gain at 15 GHz. The higher-order, $TE_{1\delta 3}^y$ mode has been utilized by increasing the dimension of DR in normal to ground plane directions with the spacing between the short magnetic dipole corresponds to 0.46λ . It has achieved the antenna gain at 9.76 dBi in comparison to 5.6 dBi for the fundamental mode. Then, the amount of coupling involving the slot width (W_s), the stub lengths (S), and the microstrip line widths (W) is altered to reduce the Q -factor of the higher-order mode DRA. This causes significant impact to the impedance bandwidth such that it achieved 2.5 GHz for the single element DRA excited in the $TE_{1\delta 3}^y$ mode compared to 1.8 GHz for DRA excited in $TE_{1\delta 1}^y$ mode.

The third contribution is a new design and analysis of DRA subarray that

consists of one driven DR and two parasitic DRs. The implementation of higher-order mode ($TE_{1\delta 3}^y$) DR as a driven element while fundamental mode ($TE_{1\delta 1}^y$) DR as the parasitic element has successfully achieved a strong mutual impedance between the elements that improved the switching angle. In addition, the design has produced a narrower half-power beamwidth (HPBW) particularly when the beam is switched due to no degeneration occurs between the driven DR ($TE_{1\delta 3}^y$ mode) and the parasitic DRs ($TE_{1\delta 1}^y$ mode).

Then, the last contribution is concerning the new design of high-gain switchable DRA array. The design is formed by incorporating two switchable DRA subarray with power divider network. Meanwhile, the phase shift between the DRA subarray is achieved by integrating the switched-line phase shifter at one of the transmission line in the power divider network. Apart from using external phase shifter, the design contributes in reducing the number of antenna and control elements with the best switching angle at ± 30 degrees that is capable in covering 60° sector. Accordingly, with specifications accomplished from the proposed design, it can be considered as a great potential for 5G applications.

1.6 Thesis Outline

This section discusses the thesis outline which is divided into seven chapters. Chapter 1, which discusses the overview of the whole project, comprises research background, problem statement, objectives of the research, scope of the research, contributions of the research, and lastly, thesis outline.

Meanwhile in Chapter 2, it focuses on the literature reviews, where the basic concept of dielectric resonator antenna with bandwidth and gain enhancement, antenna array and beam steering techniques are elaborated. Furthermore, previous works are reviewed, which mainly focus on beam steering techniques by using parasitic elements and related work for 5G applications.

In Chapter 3, the methodology of this research is discussed. The research work flows of the whole research are presented, which includes design specifications, research method framework, selection of substrate and the process of antenna fabrication, testing and measurement.

Next, in Chapter 4, design of single element DRA with different excitation mode are presented and described. Initially, the performance of single element DRA excited in the $TE_{1\delta 5}^y$ mode with three different feeding techniques which are ML feed, MSA feed and OECPW feed are investigated at 28 GHz. Then, the best feeding technique is selected and used to determine the best thickness of the RT/Duroid 5880 substrate for the optimum antenna performance. Subsequently, the single element DRA excited in the fundamental mode, $TE_{1\delta 1}^y$ with the best feeding technique is designed at 15 GHz for realization of the fabrication and measurement process. Correspondingly, the higher-order, $TE_{1\delta 3}^y$ mode DRA is designed and analyzed to enhance the gain and bandwidth. The Q -factor is further reduced by controlling the amount of coupling that involves the slot width (W_s), the stub lengths (S), and the microstrip line widths(W).

In Chapter 5, two types of switchable DRA subarray configuration designs are proposed by utilizing the higher-order, $TE_{1\delta 3}^y$ mode DR as a driven element. Performance of the both configuration are observed and compared especially in terms of gain, bandwidth, angle of switching and HPBW. The analysis and performance of the designed switchable DRA subarray are described and discussed thoroughly in this chapter. The best configuration is selected to be incorporated in the construction of the high-gain switchable DRA array in Chapter 6.

In Chapter 6, the high-gain switchable DRA array are designed and presented. The design consist of the DRA subarray integrated with the power divider network and switched-line phase shifter. The results of the power divider network and switched-line phase shifter are elaborated and analyzed. Also, comparison of various designs' performances with the other related work is further explained in this chapter.

Lastly, in Chapter 7, the conclusion is drawn. The findings of the research, contributions and recommendations for future works are proposed and described. Additionally, the list of references and appendices are provided at the end of this thesis.

REFERENCES

1. Sapakal, R. S. and Kadam, S. S. 5G Mobile Technology. *International Journal of Advanced Research in Computer Engineering & Technology (IJARCET)*, 2013. 2(2): 568–571.
2. M.Mustaqim, Khan, K. and M.Usman. LTE-Advanced:Requirements and technical challenges for 4G cellular network. *J. Emerging Trends Comput. Inf. Sci*, 2012. 3(5): 665–671.
3. Hossain, S. 5G Wireless Communication Systems. *American Journal of Engineering Research (AJER)*, 2013. 2(10): 344–353.
4. Militano, L., Araniti, G., Condoluci, M. and Iera, A. Device-to-Device Communications for 5G Internet of Things. *EAI Endorsed Transactions on Internet of Things*, 2015. 1(1): 1–15.
5. Pi, Z. and Khan, F. An introduction to millimeter-wave mobile broadband systems. *IEEE Communications Magazine*, 2011. 49(6): 101–107.
6. Sulyman, A. I., Nassar, A. T., Samimi, M. K., R., G., Jr., M., Rappaport, T. S. and Alsanie, A. Radio Propagation Path Loss Models for 5G Cellular Networks in the 28 GHz and 38 GHz Millimeter-Wave Bands. *IEEE Communication Magazine*, 2013: 78–86.
7. Bello, O. and Zeadally, S. Intelligent Device-to-Device Communication in the Internet of Things. *IEEE Systems Journal*, 2016. 10(3): 1172–1182.
8. Okasaka, S., Weiler, R. J., Keusgen, W., Pudeyev, A., Maltsev, A., Karls, I. and Sakaguchi, K. Proof-of-Concept of a Millimeter-Wave Integrated Heterogeneous Network for 5G Cellular. *Sensors*, 2016. 16(9): 1–21.
9. *Local Multipoint Distribution Service (LMDS)*. Technical report. Federal Communications Commission. March 1997. URL <https://www.fcc.gov/document/local-multipoint-distribution-service-lmlds-0>.
10. *Spectrum above 6 Ghz for future mobile communications*. Technical report. Ofcom. September 2016. URL <http://stakeholders.ofcom.org.uk/binaries/consultations/above-6ghz/summary/>

spectrum_above_6_GHz_CFI.pdf.

11. Xu, B., Zhao, K., Thors, B., Colombi, D., Lundberg, O., Ying, Z. and He, S. Power Density Measurements at 15 GHz for RF EMF Compliance Assessments of 5G User Equipment. *IEEE Transactions on Antennas and Propagation*, 2017. 65(12): 6584–6595.
12. Monavar, F. M., Shamsinejad, S., Mirzavand, R., Melzer, J. and Mousavi, P. Beam-Steering SIW Leaky-Wave Subarray With Flat-Topped Footprint for 5G Applications. *IEEE Transactions on Antennas and Propagation*, 2017. 65(3): 1108–1120.
13. Sani, Y. M. and Rahim. 15 GHz grid array antenna for 5G mobile communications system. *Microwave and Optical Technology Letters*, 2016. 58(12): 2977–2980.
14. Zebiri, C. E., Lashab, M., Sayad, D., Elfergani, I. T. E., Sayidmarie, K. H., Benabdelaziz, F., Abd-Alhameed, R. A., Rodriguez, J. and Noras, J. M. Offset Aperture-Coupled Double-Cylinder Dielectric Resonator Antenna With Extended Wideband. *IEEE Transactions on Antennas and Propagation*, 2017. 65(10): 5617–5622.
15. Boccardi, F., Heath, R. W., Lozano, A., Marzetta, T. L. and Popovski, P. Five disruptive technology directions for 5G. *IEEE Communications Magazine*, 2014. 52(2): 74–80.
16. Pozar, D. M. *Microwave Engineering*. New York: Wiley. 2005.
17. Balanis, C. A. *Antenna Theory*. 3rd ed. Hoboken, New Jersey: Wiley-Interscience. 2005.
18. Roh, W., Seol, J.-Y., Park, J., Lee, B., Lee, J., Kim, Y., Cho, J. and Cheun, K. Millimeter-Wave Beamforming as an Enabling Technology for 5G Cellular Communications: Theoretical Feasibility and Prototype Results. *IEEE Communications Magazine*, 2014.
19. Feng, W., Li, Y., Jin, D., Su, L., Chen, S. and Arslan, H. Millimetre-Wave Backhaul for 5G Networks: Challenges and Solutions. *Sensors*, 2016. 16(892): 1–17.
20. Goel, P. and Vinoy, K. J. A low-cost phased array antenna integrated with phase shifters cofabricated on the laminate. *Progress In Electromagnetics Research B*, 2011. 30: 255–277.
21. Nikfalazar, M., Mehmood, A., Sohrabi, M., Mikolajek, M., Wiens, A., Maune, H., Kohler, C., Binder, J. R. and Jakoby, R. Steerable Dielectric

- Resonator Phased-Array Antenna Based on Inkjet-Printed Tunable Phase Shifter With BST Metal-Insulator-Metal Varactors. *IEEE Antennas and Wireless Propagation Letters*, 2016. 15: 877–880.
22. Yusuf, Y. and Gong, X. A Low-Cost Patch Antenna Phased Array With Analog Beam Steering Using Mutual Coupling and Reactive Loading. *IEEE Antennas and Wireless Propagation Letters*, 2008. 7: 81–84.
 23. Guha, D. Microstrip and printed antenna. *6th International Conference on Telecommunications in Modern Satellite*. 2003, vol. 1. 39–44.
 24. Lai, Q., Almpanis, G., Fumeaux, C., Benedickter, H. and Vahldieck, R. Comparison of the radiation efficiency for the dielectric resonator antenna and the microstrip antenna at Ka Band. *IEEE Transaction on Antennas and Propagation*, 2008. 56(11): 3589–3592.
 25. Afoakwa, S. and Jung, Y. B. Wideband Microstrip Comb-Line Linear Array Antenna Using Stubbed-Element Technique for High Sidelobe Suppression. *IEEE Transactions on Antennas and Propagation*, 2017. 65(10): 5190–5199.
 26. Sun, W., Li, Y., Zhang, Z. and Feng, Z. Broadband and Low-Profile Microstrip Antenna Using Strip-Slot Hybrid Structure. *IEEE Antennas and Wireless Propagation Letters*, 2017. PP(99): 1–1.
 27. Nor, N. M., Jamaluddin, M. H., Kamarudin, M. R. and Khalily, M. Rectangular Dielectric Resonator Antenna Array for 28GHz Applications. *Progress In Electromagnetics Research C*, 2016. 63: 53–61.
 28. Varshney, G., Pandey, V. S. and Yaduvanshi, R. S. Dual-band fan-blade-shaped circularly polarised dielectric resonator antenna. *IET Microwaves, Antennas Propagation*, 2017. 11(13): 1868–1871.
 29. Abdallah, M., Wang, Y., Abdel-Wahab, W. M. and Safavi-Naeini, S. Design and Optimization of SIW Center Fed Series Rectangular Dielectric Resonator Antenna (DRA) Array with 45 Linear Polarization. *IEEE Transactions on Antennas and Propagation*, 2017. PP(99): 1–1.
 30. Abdalrazik, A., El-Hameed, A. S. A. and Abdel-Rahman, A. A Three-Port MIMO Dielectric Resonator Antenna using Decoupled Modes. *IEEE Antennas and Wireless Propagation Letters*, 2017. PP(99): 1–1.
 31. Chowdhury, R., Mishra, N., Sani, M. M. and Chaudhary, R. K. Analysis of a Wideband Circularly Polarized Cylindrical Dielectric Resonator Antenna With Broadside Radiation Coupled With Simple Microstrip Feeding. *IEEE Access*, 2017. 5: 19478–19485.

32. Keyrouz, S. and Caratelli, D. Dielectric Resonator Antennas: Basic Concepts, Design Guidelines, and Recent Developments at Millimeter-Wave Frequencies. *International Journal of Antennas and Propagation*, 2016. 2016: 1–20.
33. Guha, D. and Kumar, C. Microstrip Patch versus Dielectric Resonator Antenna Bearing All Commonly Used Feeds: An experimental study to choose the right element. *IEEE Antennas and Propagation Magazine*, 2016. 58(1): 45–55.
34. Petosa, A. *Dielectric Resonator Antenna Handbook*. MA: Artech House. 2007.
35. Luk, K. M. and Leung, K. W. *Dielectric Resonator Antennas*. Hertfordshire, England, UK.: Research Studies Press Ltd. 2002.
36. Nannini, C., Ribero, J. M., Dauvignac, J. Y. and Pichot, C. Bifrequency behaviour and bandwidth enhancement of a dielectric resonator antenna. *Microwave and Optical Technology Letters*, 2004. 42(5): 432–434.
37. Nasimuddin and Esselle, K. P. Antennas with dielectric resonators and surface mounted short horns for high gain and large bandwidth. *IET Microwaves, Antennas Propagation*, 2007. 1(3): 723–728.
38. Carrie, J., Esselle, K., Roscoe, D. J., Ittipiboon, A., Sebak, A. and Shafai, L. A K-band circularly polarized cavity backed dielectric resonator. *IEEE Antennas and Propagation Society International Symposium. 1996 Digest*. 1996, vol. 1. 734–737 vol.1.
39. Antar, Y. M. M. Antennas for wireless communication: recent advances using dielectric resonators. *IET Circuits, Devices Systems*, 2008. 2(1): 133–138.
40. Petosa, A. and Thirakoune, S. Rectangular Dielectric Resonator Antennas with Enhanced Gain. *IEEE Transactions on Antennas and Propagation*, 2011. 59(4): 1385–1389.
41. Nguyen, D.-T., Siragusa, R. and Tedjini, S. Beam steering patch antenna using reactive loading and Yagi-antenna concept. *Microwave and Optical Technology Letters*, 2015. 57(2): 417–421.
42. Kawakami, H. and Ohira, T. Electrically steerable passive array radiator (ESPAR) antennas. *IEEE Antennas and Propagation Magazine*, 2005. 47(2): 43–50.
43. Luther, J. J., Ebadi, S. and Gong, X. A Microstrip Patch Electronically Steerable Parasitic Array Radiator (ESPAR) Antenna With Reactance-Tuned

- Coupling and Maintained Resonance. *IEEE Transactions on Antennas and Propagation*, 2012. 60(4): 1803–1813.
44. Islam, M. R. and Ali, M. A 900 MHz Beam Steering Parasitic Antenna Array for Wearable Wireless Applications. *IEEE Transactions on Antennas and Propagation*, 2013. 61(9): 4520–4527.
 45. Jusoh, M., Aboufoul, T., Sabapathy, T., Alomainy, A. and Kamarudin, M. R. Pattern-Reconfigurable Microstrip Patch Antenna With Multidirectional Beam for WiMAX Application. *IEEE Antennas and Wireless Propagation Letters*, 2014. 13: 860–863.
 46. Islam, M. R. and Ali, M. Elevation Plane Beam Scanning of a Novel Parasitic Array Radiator Antenna for 1900 MHz Mobile Handheld Terminals. *IEEE Transactions on Antennas and Propagation*, 2010. 58(10): 3344–3352.
 47. Nikkhah, M. R., Rashed-Mohassel, J. and Kishk, A. A. Compact Low-Cost Phased Array of Dielectric Resonator Antenna Using Parasitic Elements and Capacitor Loading. *IEEE Transactions on Antennas and Propagation*, 2013. 61(4): 2318–2321.
 48. Nor, N. M., Jamaluddin, M. H., Kamarudin, M. R. and Ambia, S. Z. N. Z. Design of Planar Dielectric Resonator Antenna Array at 28 GHz. *Indonesian Journal of Electrical Engineering and Computer Science*, 2017. 5(3): 622–627.
 49. Khalily, M., Tafazolli, R., Rahman, T. A. and Kamarudin, M. R. Design of Phased Arrays of Series-Fed Patch Antennas With Reduced Number of the Controllers for 28-GHz mm-Wave Applications. *IEEE Antennas and Wireless Propagation Letters*, 2016. 15: 1305–1308.
 50. Abdellatif, A., Safavi-Naeini, S. and Mohajer, M. Novel low cost compact phased array antenna for millimeter-wave 3D beam scanning applications. *2014 IEEE Antennas and Propagation Society International Symposium (APSURSI)*. 2014. 1145–1146.
 51. Zhao, K., Gustafson, C., Liao, Q., Zhang, S., Bolin, T., Ying, Z. and He, S. Channel Characteristics and User Body Effects in an Outdoor Urban Scenario at 15 and 28 GHz. *IEEE Transactions on Antennas and Propagation*, 2017. 65(12): 6534–6548.
 52. Zhao, K., Ying, Z. and He, S. EMF Exposure Study Concerning mmWave Phased Array in Mobile Devices for 5G Communication. *IEEE Antennas and Wireless Propagation Letters*, 2016. 15: 1132–1135.
 53. Wang, C. X., Haider, F., Gao, X., You, X. H., Yang, Y., Yuan, D., Aggoune,

- H. M., Haas, H., Fletcher, S. and Hepsaydir, E. Cellular architecture and key technologies for 5G wireless communication networks. *IEEE Communications Magazine*, 2014. 52(2): 122–130.
54. Rao, R. G. S. and Sai, R. 5G Introduction and Future of Mobile Broadband Communication Redefined. *International Journal of Electronics, Communication and Instrumentation Engineering Research and Development*, 2013. 3(4): 119–124.
55. Gohil, A., Modi, H. and Patel, S. K. 5G technology of mobile communication: A survey. *2013 International Conference on Intelligent Systems and Signal Processing (ISSP)*. 2013. 288–292.
56. Harada, A., Inoue, Y., Kurita, D. and Obara, T. 5G Trials with Major Global Vendors. *NTT Docomo Technical Journal*, 2106. 17(4).
57. *Docomo to Conduct 5G Experimental Trials with World-leading Mobile Technology Vendors*. Technical report. NTT Docomo. May 2014. URL https://www.nttdocomo.co.jp/english/info/media_center/pr/2014/0508_00.html.
58. Rappaport, T. S., Gutierrez, F., Ben-Dor, E., Murdock, J. N., Qiao, Y. and Tamir, J. I. Broadband Millimeter-Wave Propagation Measurements and Models Using Adaptive-Beam Antennas for Outdoor Urban Cellular Communications. *IEEE Transaction on Antennas and Propagation*, 2013. 61(4): 1850–1859.
59. Agiwal, M., Roy, A. and Saxena, N. Next Generation 5G Wireless Networks: A Comprehensive Survey. *IEEE Communications Surveys Tutorials*, 2016. 18(3): 1617–1655.
60. Richtmyer, R. D. Dielectric Resonators. *Journal of Applied Physics*, 1939. 10(6): 391–398.
61. Wang, C. and Zaki, K. A. Dielectric Resonators and Filters. *IEEE Microwave Magazine*, 2007. (5): 115–127.
62. Long, S. A., McAllister, M. W. and Shen, L. C. The resonant cylindrical dielectric cavity antenna. *IEEE Transaction on Antennas and Propagation*, 1983. 31: 406–412.
63. McAllister, M. W., Long, S. A. and Conway, G. L. Rectangular dielectric resonator antenna. *Electronic Letters*, 1983. 18: 218–219.
64. McAllister, M. W. and Long, S. A. Resonant hemispherical dielectric antenna. *Electronic Letters*, 1984. 20: 657–659.

65. Sadiku, M. *Elements of electromagnetics*. The Oxford Series in Electrical and Computer Engineering Series. Oxford University Press, Incorporated. 2007.
66. Kishk, A. A., Auda, H. A. and Ahn, B. C. Radiation characteristics of cylindrical dielectric resonator antennas with new applications. *IEEE Antennas and Propagation Society Newsletter*, 1989. 31(1): 6–16.
67. Chair, R., Kishk, A. A. and Lee, K. F. Wideband simple cylindrical dielectric resonator antennas. *IEEE Microwave and Wireless Components Letters*, 2005. 15(4): 241–243.
68. DeYoung, C. S. and Long, S. A. Wideband Cylindrical and Rectangular Dielectric Resonator Antennas. *IEEE Antennas and Wireless Propagation Letters*, 2006. 5(1): 426–429.
69. Huynh, A. P., Jackson, D. R., Long, S. A. and Wilton, D. R. A Study of the Impedance and Pattern Bandwidths of Probe-Fed Cylindrical Dielectric Resonator Antennas. *IEEE Antennas and Wireless Propagation Letters*, 2011. 10: 1313–1316.
70. Mongia, R. K. and Ittipiboon, A. Theoretical and experimental investigation on rectangular dielectric resonator antenna. *IEEE Transactions on Antennas and Propagation*, 1997.
71. Madhuri, R. G., Hadalgi, P. and Hunagund, P. V. Design of high-permittivity rectangular dielectric resonator antenna. *Microwave and Optical Technology Letters*, 2011. 53(5): 1077–1079.
72. Makwana, G. D. and Vinoy, K. J. Design of a compact rectangular dielectric resonator antenna at 2.4 GHz. *Progress In Electromagnetics Research C*, 2009. 11: 69–79.
73. Wong, K. L., Chen, N. C. and Chen, H. T. Analysis of a hemispherical dielectric resonator antenna with an airgap. *IEEE Microwave and Guided Wave Letters*, 1993. 3(10): 355–357.
74. Petosa, A., Ittipiboon, A. and Cuhaci, M. Array of circular-polarised cross dielectric resonator antennas. *Electronics Letters*, 1996. 32(19): 1742–1743.
75. Simeoni, M., Cicchetti, R., Yarovoy, A. and Caratelli, D. Plastic-Based Supershaped Dielectric Resonator Antennas for Wide-Band Applications. *IEEE Transactions on Antennas and Propagation*, 2011. 59(12): 4820–4825.
76. Soren, D., Ghatak, R., Mishra, R. K. and Poddar, D. R. Dielectric resonator antennas: designs and advances. *Progress In Electromagnetics Research B*, 2014. 60: 195–213.

77. Bladel, J. V. On the resonances of a dielectric resonator of very high permittivity. *IEEE Transaction Microwave Theory Technology*, 1975. MTT-23: 199–208.
78. Harrington, R. *Time-harmonic electromagnetic fields*. McGraw-Hill electrical and electronic engineering series. McGraw-Hill. 1961.
79. Kranenburg, R. A. and Long, S. A. Microstrip transmission line excitation of dielectric resonator antennas. *Electronics Letters*, 1988. 24(18): 1156–1157.
80. Huitema, L. and Monediere, T. Dielectric Materials for Compact Dielectric Resonator Antenna Applications. In: Silaghi, M. A., ed. *Dielectric Material*. Rijeka: InTech, chap. 02. 2012.
81. Leung, K.-W., Luk, K.-M., Lai, K. Y. A. and Lin, D. Theory and experiment of an aperture-coupled hemispherical dielectric resonator antenna. *IEEE Transactions on Antennas and Propagation*, 1995. 43(11): 1192–1198.
82. Turcan, M. G., Moni, M. V. and Banciu, G. Studies of aperture-coupled rectangular dielectric resonator antenna arrays. *2016 International Conference on Communications (COMM)*. 2016. 115–120.
83. Kranenburg, R. A., Long, S. A. and Williams, J. T. Coplanar waveguide excitation of dielectric resonator antennas. *IEEE Transactions on Antennas and Propagation*, 1991. 39(1): 119–122.
84. Ghosh, B., Antar, Y. M. M., Petosa, A. and Ittipiboon, A. CPW feed to rectangular DRA. *Microwave and Optical Technology Letters*, 2005. 45(3): 210–216.
85. Kishk, A. A., Ahn, B. and Kajfez, D. Broadband stacked dielectric resonator antennas. *Electronics Letters*, 1989. 25(18): 1232–1233.
86. Luk, K. M., Leung, K. W. and Chow, K. Y. Bandwidth and gain enhancement of a dielectric resonator antenna with the use of a stacking element. *Microwave and Optical Technology Letters*, 1997. 14(4): 215–217.
87. Pan, Y. M. and Zheng, S. Y. A Low-Profile Stacked Dielectric Resonator Antenna With High-Gain and Wide Bandwidth. *IEEE Antennas and Wireless Propagation Letters*, 2016. 15: 68–71. ISSN 1536-1225.
88. Denidni, T. A., Coulibaly, Y. and Boutayeb, H. Hybrid Dielectric Resonator Antenna With Circular Mushroom-Like Structure for Gain Improvement. *IEEE Transactions on Antennas and Propagation*, 2009. 57(4): 1043–1049.
89. Cicchetti, R., Faraone, A., Miozzi, E., Ravanelli, R. and Testa, O. A High-Gain Mushroom-Shaped Dielectric Resonator Antenna for Wideband

- Wireless Applications. *IEEE Transactions on Antennas and Propagation*, 2016. 64(7): 2848–2861.
90. Warad, M., Sharma, A., Prasad, C. S. and Biswas, A. A high gain aperture coupled cylindrical dielectric resonator antenna with metamaterial superstrate. *2016 IEEE International Symposium on Antennas and Propagation (APSURSI)*. 2016. 133–134.
 91. Akbari, M., Gupta, S., Farahani, M., Sebak, A. R. and Denidni, T. A. Gain Enhancement of Circularly Polarized Dielectric Resonator Antenna Based on FSS Superstrate for MMW Applications. *IEEE Transactions on Antennas and Propagation*, 2016. 64(12): 5542–5546.
 92. Mrnka, M. and Raida, Z. Enhanced-Gain Dielectric Resonator Antenna Based on the Combination of Higher-Order Modes. *IEEE Antennas and Wireless Propagation Letters*, 2016. 15: 710–713.
 93. Zhong, L., Hong, J. S. and Zhou, H. C. A Novel Pattern-Reconfigurable Cylindrical Dielectric Resonator Antenna With Enhanced Gain. *IEEE Antennas and Wireless Propagation Letters*, 2016. 15: 1253–1256.
 94. Pan, Y. M., Leung, K. W. and Luk, K. M. Design of the Millimeter-wave Rectangular Dielectric Resonator Antenna Using a Higher-Order Mode. *IEEE Transactions on Antennas and Propagation*, 2011. 59(8): 2780–2788.
 95. Mongia, R. K., Ittipiboon, A., Cuhaci, M. and Roscoe, D. Radiation Q-factor of rectangular dielectric resonator antennas: theory and experiment. *Proceedings of IEEE Antennas and Propagation Society International Symposium and URSI National Radio Science Meeting*. 1994, vol. 2. 764–767 vol.2.
 96. Rotaru, M. and Sykulski, J. K. Numerical investigation on compact multimode dielectric resonator antennas of very high permittivity. *IET Science, Measurement Technology*, 2009. 3(3): 217–228.
 97. Rezaei, P., Hakkak, M. and Forooghi, K. Design of wide-band dielectric resonator antenna with a two-segment structure. *Progress In Electromagnetics Research*, 2006. 6: 111–124.
 98. Antar, Y. M. M. and Fan, Z. Theoretical investigation of aperture-coupled rectangular dielectric resonator antenna. *IEE Proceedings - Microwaves, Antennas and Propagation*, 1996. 143(2): 113–118.
 99. Leung, K. W., Wong, W. C., Luk, K. M. and Yung, E. K. N. Annular slot-coupled dielectric resonator antenna. *Electronics Letters*, 1998. 34(13): 1275–1277.

100. Leung, K. W. and Leung, C. K. Wideband dielectric resonator antenna excited by cavity-backed circular aperture with microstrip tuning fork. *Electronics Letters*, 2003. 39(14): 1033–1035.
101. Li, T.-W. and Sun, J.-S. A wide U-shape slot fed broadband dielectric resonator antenna. *11th International Symposium on Antenna Technology and Applied Electromagnetics [ANTEM 2005]*. 2005. 1–3.
102. Lam, H. Y. and Leung, K. W. Analysis of U-slot-excited dielectric resonator antennas with a backing cavity. *IEE Proceedings - Microwaves, Antennas and Propagation*, 2006. 153(5): 480–482.
103. Jamaluddin, M. H., Eu, G. C., Rahim, S. K. A. and Dzulkipli, N. I. Wideband Aperture-Coupled Dielectric Resonator Antenna at 5.8 GHz. *Jurnal Teknologi*, 2014. 69(1): 25–30.
104. Rashidian, A. and Klymyshyn, D. M. Very low permittivity slot-fed dielectric resonator antennas with improved bandwidth for millimetre-wave applications. *2009 3rd European Conference on Antennas and Propagation*. 2009. 3554–3557.
105. Visser, H. J. *The Linear Broadside Array Antenna*, John Wiley & Sons, Ltd. 2006, 123–135.
106. Stutzman, W. L. and Thiele, G. A. *Antenna Theory and Design*. New York: John Wiley & Sons. 1998.
107. Visser, H. J. *Antenna Parameters*, John Wiley & Sons, Ltd. 2006, 83–121.
108. Uchendu, I. and Kelly, J. R. Survey of beam steering techniques available for millimeter wave applications. *Progress In Electromagnetics Research B*, 2016. 68: 35–54.
109. Zarb-Adami, K., Faulkner, A., de Vaate, J. G. B., Kant, G. W. and Picard, P. Beamforming techniques for large-N aperture arrays. *2010 IEEE International Symposium on Phased Array Systems and Technology*. 2010. 883–890.
110. S.Keul and Bhat, B. *Microwave and Millimeter wave phase shifters*. MA: Artech House. 1991.
111. Zhang, J., Cheung, S. W. and Zhu, Q. Design of 180-switched-line Phase Shifter with Constant Phase Shift Using CRLH TL. *2014 IEEE Antennas and Propagation Society International Symposium (APSURSI)*. 344–345.
112. Sun, C., Hirata, A., Ohira, T. and Karmakar, N. C. Fast beamforming of electronically steerable parasitic array radiator antennas: theory and

- experiment. *IEEE Transactions on Antennas and Propagation*, 2004. 52(7): 1819–1832.
113. Han, Q., Hanna, B., Inagaki, K. and Ohira, T. Mutual Impedance Extraction and Varactor Calibration Technique for ESPAR Antenna Characterization. *IEEE Transactions on Antennas and Propagation*, 2006. 54(12): 3713–3720.
114. Lu, J., Ireland, D. and Schlub, R. Dielectric embedded ESPAR (DE-ESPAR) antenna array for wireless communications. *IEEE Transactions on Antennas and Propagation*, 2005. 53(8): 2437–2443.
115. Shibata, O. and Furuhi, T. Dual-band ESPAR antenna for wireless LAN applications. *2005 IEEE Antennas and Propagation Society International Symposium*. 2005, vol. 2B. 605–608 vol. 2B.
116. Bertuch, T., Joseph, R. and Herbertz, K. Size-Limited Q-Band Circular Switched Parasitic Array Antenna With Small Elevation Beamwidth. *IEEE Transactions on Antennas and Propagation*, 2015. 63(11): 4749–4758.
117. Kamarudin, M. R. and Hall, P. S. Disc-loaded monopole antenna array for switched beam control. *Electronics Letters*, 2006. 42(2): 66–68.
118. Sharawi, M. S., Podilchak, S. K., Hussain, M. T. and Antar, Y. M. M. Dielectric resonator based MIMO antenna system enabling millimetre-wave mobile devices. *IET Microwaves, Antennas Propagation*, 2017. 11(2): 287–293.
119. Wang, Y., Wang, H. and Yang, G. Design of dipole beam-steering antenna array for 5G handset applications. *2016 Progress in Electromagnetic Research Symposium (PIERS)*. 2016. 2450–2453.
120. Allayioti, M. and Kelly, J. R. Side lobe level reduction for beam steerable antenna design. *2016 10th European Conference on Antennas and Propagation (EuCAP)*. 2016. 1–5.
121. Huang, F., Chen, W. and Rao, M. Switched-beam antenna array based on butler matrix for 5G wireless communication. *2016 IEEE International Workshop on Electromagnetics: Applications and Student Innovation Competition (iWEM)*. 2016. 1–3.
122. Nour, A. A., Fezai, F. and Monediere, T. Comparison of different feeding techniques of a low-profile dual-band circularly polarized microstrip antenna. *2016 10th European Conference on Antennas and Propagation (EuCAP)*. 2016. 1–5.
123. Chair, R., Kishk, A. A. and Lee, K. F. Comparative Study on Different

- Feeding Techniques for Dual Polarized Dielectric Resonator Antennas. *2006 IEEE Antennas and Propagation Society International Symposium*. 2006. 2495–2498.
124. Chakravarthy, S. S., Sarveshwaran, N., Sriharini, S. and Shanmugapriya, M. Comparative study on different feeding techniques of rectangular patch antenna. *2016 Thirteenth International Conference on Wireless and Optical Communications Networks (WOCN)*. 2016. 1–6.
 125. Corporation, R. RT/duroid® 5870 /5880 High Frequency Laminates, 2016. URL <https://www.rogerscorp.com/documents/606/acs/RT-duroid-5870-5880-Data-Sheet.pdf>.
 126. Ahmed, B., Saleem, I., Zahra, H., Khurshid, H. and Abbas, S. M. Analytical Study on Effects of Substrate Properties on the Performance of Microstrip Patch Antenna. *International Journal of Future Generation Communication and Networking*, 2012. 5(4): 113–122.
 127. Petosa, A. and Ittipiboon, A. Dielectric Resonator Antennas: A Historical Review and the Current State of the Art. *IEEE Antennas and Propagation Magazine*, 2010. 52(5): 91–116.
 128. Giauffret, L., Laheurte, J. M. and Papiernik, A. Study of various shapes of the coupling slot in CPW-fed microstrip antennas. *IEEE Transactions on Antennas and Propagation*, 1997. 45(4): 642–647.
 129. Beilenhoff, K., Klingbeil, H., Heinrich, W. and Hartnagel, H. L. Open and short circuits in coplanar MMIC's. *IEEE Transactions on Microwave Theory and Techniques*, 1993. 41(9): 1534–1537.
 130. Ain, M. F., Qasaymeh, Y. M., Ahmad, Z. A., Zakariya, M. A. and Ullah, U. An Equivalent Circuit of Microstrip Slot Coupled Rectangular Dielectric Resonator Antenna. *Progress In Electromagnetics Research Symposium Proceedings*. 2012. 1837–1840.
 131. Hong, J. S. *Transmission Lines and Components*, John Wiley & Sons, Inc. 2011, 75–111.
 132. Edwards, T. C., Steer, M. B., Edwards, T. C. and Steer, M. B. *Microstrip and Stripline at High Frequencies*, John Wiley & Sons, Ltd. 2013, 113–159.