

TROPOSPHERIC SCINTILLATION FOR KU-BAND SATELLITE
COMMUNICATION LINK IN EQUATORIAL MALAYSIA

IBTIHAL FAWZI ELSHAMI

UNIVERSITI TEKNOLOGI MALAYSIA

TROPOSPHERIC SCINTILLATION FOR KU-BAND SATELLITE
COMMUNICATION LINK IN EQUATORIAL MALAYSIA

IBTIHAL FAWZI ELSHAMI

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Electrical Engineering)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

SEPTEMBER 2016

To my beloved parents, my husband Ali Elgayar, my daughter Fawzia Elgayar and my son Ibrahim Elgayar for their encouragement and support”

ACKNOWLEDGEMENT

First of all, gratefulness of thanks to our Creator, “ALLAH”, who enabled us to complete this thesis.

Special thanks go to Assoc. Prof. Dr. Jafri Din, for giving this opportunity to work under his supervision and for sharing his great knowledge and experience with me.

Many thanks to the colleagues of the propagation group in Radio Communication Engineering, Faculty of Electrical Engineering, Universiti Teknologi Malaysia, especially Dr Lam Hong Yin, Dr Khalid Ibrahim, Idrissa Abubakar, Manhal Alhelaly, Mawarni binti Mohamed and Dr Jong Siat Ling for their idea’s sharing and discussions.

Finally, Special thanks to my parents, my husband, my children, family and all my lovely friends for their continuous encouragement and support throughout the time.

ABSTRACT

Tropospheric scintillation is a rapid fluctuation of the amplitude of received signal causes propagation impairments that affect satellite communication systems operating above 10 GHz. This work concentrates on those aspects in equatorial Johor Bahru, Malaysia, based on a two-year K_u -band propagation measurement campaign, utilizing the equipment of Direct Broadcast Receiver (DBR) and Automatic Weather Station (AWS). The study is divided into two parts. First, the investigation of clear sky scintillation through classification and analysis of a time-series satellite broadcasting signals, followed by comparison of the statistical results with existing scintillation prediction models. A new processing method is proposed to enhance the estimation of dry scintillation, specifically for the diurnal behavior of scintillation variance. Second, this study focuses to investigate the relationship between wet scintillation and rain attenuation using experimental measurement, and concentrate on the probability density function (PDF) of different scintillation parameters. From the results, it is concluded that wet scintillation intensity increases with rain attenuation. Thus, the relationship can be phrased by linear equations or power-law. The PDFs of wet scintillation intensity, adapted to a given rain attenuation level, are found lognormally distributed, leading to selection of method for determining the relation between conditional PDFs and rain attenuation. Finally, seasonal and diurnal variations of wet scintillation are also investigated. It is found that wet scintillation fade is likely to occur in the afternoon from 3 pm to 6 pm. Meanwhile, wet scintillation intensity of the inter-monsoon shows a relatively higher rate of change of attenuation. The results can provide system operators and radio communication engineers with critical information on the fluctuations of tropospheric scintillation variance of the satellite signal during a typical day, taking into the account of local meteorological peculiarities.

ABSTRAK

Kelipan troposfera merupakan perubahan mendadak bagi amplitud isyarat penerima yang boleh menyebabkan rosotan perambatan yang mempengaruhi sistem komunikasi satelit pada frekuensi melebihi 10 GHz. Kajian ini menumpukan kepada aspek-aspek tersebut di Johor Bahru, Malaysia, yang berada pada jalur Khatulistiwa berdasarkan dua tahun kempen pengukuran perambatan jalur- K_u yang merangkumi peralatan Penerima Langsung Penyiaran (DBR) dan Stesen Cuaca Automatik (AWS). Kajian ini terbahagi kepada dua bahagian. Pertama, kajian terhadap kelipan langit cerah melalui klasifikasi dan analisis dari isyarat siri masa penyiaran satelit dan seterusnya dibandingkan dengan keputusan model statistik kelipan sedia ada. Satu kaedah pemrosesan baru telah dicadangkan bagi menambahbaik penganggaran kelipan kering, khususnya tingkahlaku diurnal bagi varians kelipan. Kedua, kajian ini menumpukan kepada kajian terhadap hubungan antara kelipan basah dan gangguan hujan menggunakan pengukuran, dan tumpuan kepada fungsi ketumpatan kebarangkalian (PDF) bagi parameter kelipan berbeza. Ianya menunjukkan bahawa intensiti kelipan basah meningkat dengan kadar pengecilan hujan. Maka, hubungan antara keduanya boleh difrasakan kepada linear atau hukum kuasi. PDF bagi keamatan kelipan basah, disesuaikan dengan tahap gangguan hujan taburan lognormal yang membawa kepada kaedah pemilihan bagi menentukan hubungan antara PDF bersyarat dan pengecilan hujan. Akhir sekali, variasi bermusim dan diurnal bagi kelipan basah juga dikaji. Didapati bahawa pemudaran kelipan basah adalah kerap berlaku pada petang dari jam 3 hingga 6 petang. Manakala, intensiti kelipan basah bagi peralihan musim menunjukkan kadar perubahan gangguan hujan yang tinggi. Keputusan kajian memberikan operator dan jurutera komunikasi radio maklumat kritikal mengenai ayunan varians kelipan troposfera bagi isyarat satelit pada selang masa sepanjang hari biasa dengan mengambil kira ciri-ciri meteorologi tempatan.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xii
	LIST OF SYMBOLS	xviii
	LIST OF ABBREVIATIONS	xix
	LIST OF APPENDICES	xx
1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement	2
	1.3 Research Objectives	4
	1.4 Scope of Work	5
	1.5 Research Contributions	6
	1.6 Thesis Outline	7
2	LITERATURE REVIEW	9
	2.1 Introduction	9
	2.2 Characteristics of Climate in Equatorial Malaysia	9

2.2.1	Seasonal Variation	11
2.2.2	Diurnal Variation	13
2.3	Clear Sky Scintillation Prediction Models	15
2.3.1	Karasawa Scintillation Model	16
2.3.2	ITU-R Scintillation Prediction Model	18
2.3.3	Otung Scintillation Prediction Model	19
2.3.4	Ortgies Prediction Models	20
2.3.5	Marzano STH2 and STN2 Prediction Models	21
2.3.6	Modification of Scintillation Prediction Models	22
2.3.7	Evaluation of Scintillation Models	24
2.4	Characteristics of Rain Attenuation and Scintillation	27
2.4.1	Relationship between Rain Attenuation and Scintillation	30
2.4.2	Thin Layer Model	30
2.5	Statistical Distribution of Scintillation Parameters	35
2.5.1	Distribution of Scintillation Amplitude	35
2.5.2	Distribution of Scintillation Standard Deviation	36
2.5.2.1	Gamma Distribution	37
2.5.2.2	Log-normal Distribution	37
2.5.2.3	Logistic Distribution	40
2.6	Review of MEASAT-1/3 Satellite System	40
2.7	Review of Syracuse- 3A Satellite System	43
2.8	Summary	44
3	METHODOLOGY	45
3.1	Introduction	45
3.2	Overview of Methodology	45
3.3	Experimental Setup	50
3.3.1	Setup of K _u Band Direct Broadcast Receiver	50
3.3.2	Setup of K _a Band Beacon Receiver	53
3.3.3	Setup of Automatic Weather Station (AWS)	55
3.3.4	Maintenance and Calibration	58
3.3.5	Availability of Recorded Data	58

3.4	Data Processing	59
3.4.1	Received Signal Data Processing	61
3.4.2	Scintillation Signal Level	66
3.4.3	Clear Sky Reference Level and Rain Attenuation	67
3.5	Diurnal Model of Equatorial Tropospheric Scintillation	70
3.6	Relationship between Wet Scintillation and Rain Attenuation	71
3.7	Seasonal and Diurnal Variation of Wet Scintillation	72
3.8	Summary	73
4	ANALYSIS OF CLEAR SKY SCINTILLATION	74
4.1	Introduction	74
4.2	Relationships between Scintillation and Meteorological Parameters	74
4.3	Statistical Distribution of Scintillation Parameters	78
4.3.1	Statistical Distribution of Scintillation Variance	78
4.3.2	Statistical Distribution of Scintillation Amplitude	81
4.4	Seasonal Variations	83
4.5	Diurnal Variations	84
4.5.1	Relationships of Diurnal Scintillation Variance and Surface Meteorological Data	85
4.5.2	Prediction of Scintillation Parameters	88
4.6	Clear Sky Scintillation for K_a Band Beacon Satellite	91
4.6.1	Conditional Distribution of Scintillation Amplitude	92
4.6.2	Diurnal Variation of Clear Sky Scintillation	94
4.7	Summary	96
5	ANALYSIS OF THE EFFECT OF RAIN ATTENUATION ON SCINTILLATION	98
5.1	Introduction	98
5.2	The Relationship between Rain Rate and Rain Attenuation	98
5.3	Statistical Analysis of Rain Attenuation and Scintillation	99
5.3.1	The Relationship between Attenuation and Scintillation Intensity	100

5.3.2	Conditional Distribution of Scintillation Amplitude	103
5.3.3	Long Term PDF of Scintillation Intensity	105
5.3.4	Long Term PDF of Scintillation amplitude	107
5.4	Seasonal and Diurnal Variations	108
5.4.1	Seasonal Variation	109
5.4.2	Diurnal Variation	114
5.5	Wet Scintillation for K_a Band Beacon Satellite	119
5.5.1	Statistical Analysis of Rain Attenuation and Scintillation	119
5.5.2	Conditional Distribution of Scintillation Amplitude	120
5.5.3	The Relationship between Attenuation and Scintillation Intensity	122
5.6	Summary	125
6	CONCLUSIONS	126
6.1	Conclusions	126
6.2	Future Works	128
	REFERENCES	129
	Appendices A - G	137 - 156

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Specification of the scintillation prediction models.	24
2.2	MEASAT-3 K _u -band transponder and performance specification.	41
3.1	MEASAT-1 Satellite, site and antenna specifications.	50
3.2	MEASAT-3 Satellite, site and antenna specifications.	51
3.3	Syracuse-3A satellite, sites and antenna specifications.	54
3.4	Input parameters for the ($T&H$), ($T&N_{wet}$) prediction models.	70
4.1	Results of the statistical regression comparison to estimate the normalized log variances on an hourly basis.	89
4.2	Regression coefficients of (2.28) and (2.29).	89
4.3	Satellite and antenna parameters.	92
5.1	Mean and RMS error of fitting expression power law, thin layer (eq 2.30) and linear relationship with the experimental data.	102
5.2	Parameters of the lognormal fitting to the conditional probability density functions $\ln(\sigma_x/A)$.	106
5.3	Type of rain event as collected in Johor Bahru.	114
5.4	Type of rain event as collected in UTM and UTHM, for July 2015.	121
5.5	Regression coefficients of different relationship between the scintillation standard deviation and rain attenuation for UTHM site.	124
5.6	Mean and RMS error of fitting expression, linear relation, exponential relation, power law, thin layer model (linear) and thin layer model (nonlinear) with the experimental data.	124

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
2.1	Mean annual rainfall map of the world for 40 years obtained from ECMWF databases.	10
2.2	Annually mean surface temperature.	11
2.3	Seasonal wind direction: a) Northeast monsoon season, b) Southwest monsoon season.	12
2.4	Annual and seasonal cumulative distributions of scintillation variance (dB^2) measured in Kuala Lumpur.	12
2.5	Comparison between wet season and dry season. a) Diurnal temperature. b) Diurnal humidity.	14
2.6	Seasonal and diurnal dependence of 1 min scintillation intensity.	15
2.7	Comparison of prediction models against CCDF of scintillation fade collected from the JCSAT3 satellite at 12.247 GHz and 64.7 ° in Bandung, Indonesia.	25
2.8	Cumulative distributions of scintillation fade for prediction models and data measurement collected in Italy, using the beacon of 39.6 GHz.	26
2.9	Comparison between prediction models and mean monthly values of scintillation variance collected at 19.7 GHz of the Eutelsat HB-6 satellite beacon in Madrid.	26
2.10	Sample of power spectral density on 21 September 1992.	28
2.11	Sample of power spectral density on 5 October 1992.	28
2.12	Sample power spectral density in 10 August 1992.	29
2.13	CCDF of scintillation intensity σ_x (dB) as a function of rain attenuation A , in intervals 2 dB wide, for two locations, Spino d'Adda, solid lines. Darmstadt, dotted lines.	32

2.14	Scintillation intensity σ_x , as a function of rain attenuation A for data collected at 50 GHz frequency and 40° elevation angle in Madrid. Best fit with the thin layer model, and a linear relationship.	32
2.15	Two-year tropospheric scintillation of data collected at K_u band JCSAT3 satellite and 64.7° of elevation angle during rainy season months and dry season months in Bandung, Indonesia.	33
2.16	Scatter plots of scintillation standard deviation σ_x against rain attenuation A for two rain events in Kolkata. a) The linear fit indicated thin layer turbulence. b) The linear fit indicated thick layer turbulence.	34
2.17	Examples of PDFs of scintillation amplitude dependent to scintillation intensity and its fitted normal distributions.	36
2.18	Cumulative distributions of measured scintillation variance collected in Milan 19.77 GHz, and best fitting by log-normal distribution.	39
2.19	Histogram of probability distributions of scintillation intensity measured in Madrid and lognormal distribution fits. (a) Rain attenuation: 4–5 dB (b) Rain attenuation: 8–9dB.	39
2.20	MEASAT-3 satellite. (a) Location. (b) The coverage beam.	42
2.21	The coverage of Syracuse-3A.	43
3.1	Flow diagram of research methodology for clear sky scintillation.	47
3.2	Flow diagram of research methodology for wet scintillation.	49
3.3	Block diagram of MEASAT satellite receiving system.	52
3.4	Outdoor unit of receiving system. The antenna's focus point is concealed under a plastic shelter.	52
3.5	Indoor unit of MEASAT receiving system. The indoor unit consists of a splitter, a spectrum analyser, a signal decoder, a personal computer and a television.	53
3.6	Block diagram of beacon receiving system.	54
3.7	Outdoor unit of beacon receiving system.	55

3.8	Indoor unit of beacon receiving system.	55
3.9	Block diagram of meteorology station setup.	56
3.10	Automatic Weather Station in UTM, Johor Bahru.	57
3.11	Hobo tipping bucket rain gauge sensor in AWS.	57
3.12	A sample of received signal and noise floor level during clear sky conditions; a) MEASAT-3, b) Beacon.	60
3.13	Flow chart of the process of time series of scintillation and rain attenuation.	61
3.14	Abnormal signal (sudden drop).	62
3.15	a) Power spectral density, b) corresponding time series of received signal on 31st December 2013 for MEASAT-3.	63
3.16	a) Power spectral density, b) corresponding time series of received signal on 30 July 2015 for Beacon receiver.	64
3.17	MEASAT-3 received signal level. a) Without filter, b) With LPF, c) With HPF.	65
3.18	Beacon received signal level. a) Without filter, b) With LPF, c) With BPF.	65
3.19	Typical example of tropospheric scintillation and its variance: a) MEASAT-1, b) beacon receiver.	67
3.20	Process of obtaining time series of rain attenuation: a) Time series of received signal, b) Time series of rain rate, c) Time series of rain attenuation obtained from the process.	68
3.21	Noise floor level during clear sky and rainy conditions: a) MEASAT-3, b) Beacon.	69
4.1	Temperature in Johor Bahru International Airport (SENAI) for year 2001, 2002.	75
4.2	Humidity in Johor Bahru International Airport (SENAI) for year 2001, 2002.	75
4.3	Diurnal and seasonal variation of 11.075 GHz MEASAT; a) Scintillation variance, b) Ground temperature, c) Ground relative humidity, (d) Ground wet refractivity index N_{wet} for 2001 as measured in Skudai, Johor.	78

4.4	Measured probability distributions of scintillation variance at 11 GHz, for the whole year of 2001, and lognormal distributions with the input parameters taken from the measurements.	81
4.5	Complementary cumulative distribution function (CCDF) of the measured scintillation fade and enhancement in equatorial Johor compared with the various statistical scintillation prediction models.	82
4.6	Annual and seasonal cumulative distributions of scintillation amplitude extracted from the MEASAT-1 broadcasting satellite signal; a) scintillation fade, b) scintillation enhancement.	84
4.7	Measured diurnal behaviour of the scintillation intensity extracted from the MEASAT-1 broadcasting satellite signal.	85
4.8	Normalized scintillation log-variance ($\ln\langle\sigma_x^2\rangle_n$) on an hourly basis as a function of surface temperature (a) and surface relative humidity (b), derived from the one-year data set.	87
4.9	Normalized scintillation log-variance ($\ln\langle\sigma_x^2\rangle_n$) on an hourly basis as a function of surface wet refractivity.	88
4.10	MEASAT measured scintillation variance at 11GHz and 75° elevation angle compare with the estimated variance on an hourly basis.	90
4.11	Root mean square value of the error for prediction of diurnal variations scintillation variance. Comparison between local models and Marzano model.	91
4.12	Complementary cumulative distribution function (CCDF) of the measured scintillation fade and enhancement at low elevation angle for K _a -band Beacon satellite in equatorial Johor.	93
4.13	CCDF of the measured scintillation fade and enhancement at low elevation angle for K _a -band Beacon satellite in equatorial Johor compared with the various statistical scintillation prediction models.	94
4.14	Beacon measured scintillation variance at 20.245 GHz and low elevation angle 25.24° for UTM site and 26.15° UTHM site.	95

5.1	a) Time series of rain rate, b) received signal measured during a rain event recorded on 3rd April 2013.	99
5.2	Comparison of received signal level during a rain event recorded on 3rd April 2013. a) Without filter. b) With LPF. c) With HPF.	100
5.3	Scatter plot of scintillation standard deviations σ_x (dB) and rain attenuation A (dB) for all data, 1-min intervals, Skudai, Johor. Best fitting with the power law relationship, thin layer model, (eq 2.30), and a linear relationship.	102
5.4	Conditional distributions of scintillation fade (dB) as a function of rain attenuation, from 0–2 dB to 8–16 dB. (a) One year. (b) Nine months. (c) Six months.	105
5.5	Measured probability distributions of scintillation intensity dependent on rain attenuation, and lognormal fits. (a) Rain attenuation: 2–4 dB. (b) Rain attenuation: 6–8 dB.	107
5.6	PDF of scintillation amplitude for various attenuation levels. Measured distribution, normal fitting and logistic fitting.	108
5.7	Histogram of wind direction recorded by weather station for four seasons: a) NE monsoon, b) SW monsoon, c) Pre-NE monsoon and d) Pre-SW monsoon.	111
5.8	Seasonal CCDFs of rain attenuation for different seasons.	112
5.9	Seasonal CCDFs of scintillation amplitude for different seasons.	113
5.10	Standard deviation of fade slope as a function of attenuation for each season.	114
5.11	Hourly rain attenuation availability.	115
5.12	CCDFs of rain attenuation on a diurnal basis in Johor Bahru.	116
5.13	CCDFs of scintillation fade on a diurnal basis in Johor Bahru.	117
5.14	Diurnal variation of scintillation intensity based on seasonal variation.	118
5.15	Diurnal variation of availability of rainfall based on seasonal variation.	118

5.16	Comparison of K_a -band received signal level. a) Without filter. b) With LPF. c) With BPF.	120
5.17	CCDF of the measured wet scintillation fade and enhancement for K_a -band beacon satellite for UTM and UTHM locations.	121
5.18	CCDF of the scintillation fade for three rain events.	122
5.19	Scatter plot of scintillation standard deviations (dB) and rain attenuation A (dB) for July 2015, 1-min intervals, with some relationship models. a) UTM site. b) UTHM site.	123

LIST OF SYMBOLS

A	-	Attenuation
D_a	-	Antenna diameter
D_{eff}	-	Effective antenna diameter
e_s	-	Saturated water vapor pressure
f	-	Frequency
G	-	Antenna aperture averaging factor
H	-	Relative humidity
h	-	Height of the turbulent layer
L	-	Effective path length
N_{wet}	-	Wet reflectivity
p	-	Time percentage
$p(x)$	-	Probability density function
R	-	Effective radius of circular antenna
T	-	Surface temperature
x	-	Scintillation amplitude
σ_x	-	Scintillation intensity
θ	-	Elevation angle
η	-	Antenna efficiency
σ_{ref}	-	Refractivity-dependent term
η_f	-	Frequency dependent term
η_θ	-	Elevation angle dependent term
η_D	-	Antenna aperture term
λ	-	Wavelength
η_A	-	Fade percentage factors
η_E	-	Enhancement percentage factors
σ_x^2	-	Scintillation variance
$\Gamma()$	-	Gamma function

LIST OF ABBREVIATIONS

Astro	-	All-Asian Satellite Television and Radio Operator
AWS	-	Automatic Weather Station
BPF	-	Band Pass Filter
CCDF	-	Complementary Cumulative Distribution Function
DBR	-	Direct Broadcast Receiver
ECMWF	-	European Centre for Medium-Range Weather Forecasts
EIRP	-	Effective Isotropically Radiated Power
HPF	-	High Pass Filter
IF	-	Intermediate Frequency
ITALSAT	-	Italian Satellite
ITU-R	-	International Telecommunication Union, Radio communication sector
LNB	-	Low Noise Block down Converter
LPF	-	Low Pass Filter
MEASAT	-	Malaysia East Asia Satellite
NE	-	Northeast
PDF	-	Probability Density Function
QoS	-	Quality of Service
RMSE	-	Root Mean Square Error
SatCom	-	Satellite Communication
SW	-	Southwest
Syracuse	-	Satellite-based radio communication system
UTHM	-	Universiti Tun Hussein Onn Malaysia
UTM	-	Universiti Teknologi Malaysia

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	List of Publications.	137
B	Low Pass Filter (LPF)	138
C	Fresnel Ellipsoid	142
D	Spectrum Analyser Calibration Certificate	143
E	Probability Density Function (PDF) of Scintillation Intensity	145
F	Probability Density Function (PDF) of Scintillation Amplitude	147
G	Examples of Three Rain Events	151
H	Curve Fitting Technique	155

CHAPTER 1

INTRODUCTION

1.1 Research Background

Satellite communication systems operating at low fade margins with a frequency above 10 GHz are generally exposed to the turbulent fluctuations of the refractive index, which cause random fading and enhancement of the received signal. This propagation mechanism, which affects the received signal level, is known as (tropospheric scintillation). The rapid fluctuation of the received signal amplitude can range up to several decibels. The intensity of the fluctuations in the refractive index can produce significant impairments, as the margin of the communications systems decreases. This is common in places having frequencies above 10 GHz, particularly in tropical and equatorial regions like Malaysia, which has uniform temperature, high humidity and heavy rainfall. It is therefore of key importance to investigate the characteristics of this phenomenon for the optimization of channel capacity (Garcia-del-Pino, Riera et al. 2012).

Generally, the fluctuation of the electromagnetic wave signal passing through the atmospheric medium is primarily due to turbulent irregularities in temperature, humidity and pressure (Van de Kamp, Riva et al. 1999). The impact of the behaviour or a feature of those parameters on scintillation is of key importance, particularly in the equatorial region that is often dominated by local climatic peculiarities (Rahim, Islam et al. 2013).

Nevertheless, numerous propagation measurement campaigns have been actively carried out to characterise the behaviour of clear sky scintillation experienced by satellite radio links. Unfortunately, most of the concentrated studies are only based on the measurement database in temperate regions (Karasawa, Yamada et al. 1988, Ortgies 1993, Otung 1996, Marzano and D'Auria 1998, ITU-R 2015) which have different climate compared with tropical and equatorial regions. The findings or model proposed for the temperate region certainly do not reflect the scintillation structure in equatorial and tropical areas. Furthermore, there is very limited number of investigations clear sky scintillation carried out regarding equatorial and tropical region (Akhondi and Ghorbani 2005, Mandeep, Yee et al. 2011, Abdul Rahim, Islam et al. 2012, Rahim, Islam et al. 2013, Yee, Mandeep et al. 2013, Chen and Singh 2014). In relation to that, only a few propagation studies of wet scintillation have been carried in the past few decades regarding equatorial and tropical region (Suryana, Utoro et al. 2005, Maitra and Adhikari 2010, Adhikari and Maitra 2011).

As a consequence, the statistics of clear-sky scintillation in the equatorial zone remains an interesting topic for investigation. Therefore, this study intends to explore those statistics in an equatorial site by exploiting the propagation measurements carried out at Universiti Teknologi Malaysia (UTM) in Johor Bahru, Malaysia. This work will be a helping hand in providing knowledge for characterising wet scintillation, by investigating the relationship between wet scintillation and rain attenuation.

1.2 Problem Statement

As briefly mentioned above, characteristics of the scintillation effect play an important role in the optimization of the channel capacity for satellite communication system. In this respect, several problem statements that need to be addressed and resolved in this thesis work are summarized as below:

The improvement of clear sky scintillation model specifically for heavy rain region is necessary. This is due to the typically lower prediction accuracy of the models currently available (with respect to temperate region). Several studies have been concentrated to predict clear-sky tropospheric scintillation, in particular using diurnal behaviour related to the hour of the day. Unfortunately, most of the models developed are only based on the measurement database in temperate regions (Karasawa, Yamada et al. 1988, Ortgies 1993, Otung 1996, Marzano and D'Auria 1998, ITU-R 2015). Similar studies that focus on this aspect in heavy rain regions are still very rare, with the exception of studies by (Mandeep, Yee et al. 2011, Abdul Rahim, Islam et al. 2012, Chen and Singh 2014). Therefore, it is worthwhile to further investigate the diurnal variations of scintillation in this heavy rain region, as well as their relationship with meteorological parameters, such as temperature, humidity and atmospheric refractive index.

In addition to the specific diurnal scintillation model on clear sky condition, the estimation of the amount of signal drop due to the concurrent occurrence of the rain attenuation and wet scintillations is significant (Filip and Vilar 1990). This is prominent, especially in tropical and equatorial regions where convective rain is most frequent, although there have been some studies to understand and estimate the relationship between wet scintillation and rain attenuation in the temperate region (Matricciani, Mauri et al. 1996, Matricciani, Mauri et al. 1997, Matricciani and Riva 2008, Garcia-del-Pino, Riera et al. 2012). However, there are only limited experimental results of wet scintillation in equatorial and tropical regions (De, Chakraborty et al. , Suryana, Utoro et al. 2005, Maitra and Adhikari 2010, Adhikari and Maitra 2011). Therefore, it is worthwhile to further investigate and estimate the natural characteristics of wet scintillation in Malaysia with respect to the experimental database available and relationships between wet scintillation and rain attenuation models from the established literature.

Besides the estimation of wet scintillation characteristics, seasonal and diurnal variations of wet scintillation also provide good insight in the design and implementation of fade margin. However, only a few researchers have performed analyses on seasonal and diurnal variation of wet scintillation in tropical and equatorial regions (Dao, Md Rafiqul et al. 2013, Mandeep and Islam 2014).

Therefore, the aim of this study is to investigate and provide detailed analysis of seasonal and diurnal variations of wet scintillation in an equatorial site.

In addition, scintillation distribution is one of the important parameters in analysing scintillation effects. Most studies show that normal and lognormal distributions of clear sky scintillation are suitable in accordance to scintillation amplitude and scintillation intensity, respectively (Moulsley and Vilar 1982, Ortgies 1985). although, their physical mechanisms are slightly different between clear sky scintillation and wet scintillation. Nevertheless, the statistical properties of wet scintillation can be derived from similar distributions used for clear sky scintillation, only differ by considering explicitly the rain attenuation level (Mertens and Vanhoenacker-Janvier 2001, Garcia-del-Pino, Riera et al. 2012). Based on this consideration, it is required to further investigate to derive probability density functions (PDFs) of wet scintillation using an integration of conditional PDFs and rain attenuation in equatorial regions.

1.3 Research Objectives

The objectives of this research are:

- i. To propose an improved diurnal clear sky scintillation model for satellite communication application in equatorial Malaysia.
- ii. To obtain the relationship between wet scintillation and rain attenuation, as well as statistically characterize the probability density function (PDF) of wet scintillation in equatorial Johor Bahru.
- iii. To analyse diurnal and seasonal characteristics of wet scintillation for the K_u -band earth-space propagation link in equatorial Malaysia.

1.4 Scope of Work

The scope of this research work consists of two parts, scintillation analysis under clear-sky conditions and the analysis of the effect of rain attenuation on scintillation.

Firstly, the studies in this thesis work focus on several frequencies in Ku, Ka-band, such as 11.075 GHz (MEASAT-1 satellite), 12.2 GHz (MEASAT-3 satellite) and 20.245 GHz (Syracuse-3A satellite using beacon receiver). The locations of the analyses in this work are restricted only to the two locations in southern Peninsula Malaysia namely Skudai (UTM) (for MEASAT satellite and satellite beacon receiver) and Batu Pahat (UTHM) (for satellite beacon receiver only).

The research begins with analyzing the clear sky scintillation characteristics based on one year of measurements data collected throughout the year 2001 in UTM, followed by a comparison of clear sky scintillation using the current existing prediction models. Then, seasonal and diurnal variations of clear sky scintillation have been investigated based on one year of measurements data collected throughout the year 2001 in UTM. Consequently, current diurnal clear sky scintillation models for the satellite communication has been improved, with considerations of effects of temperature, humidity, and wet refractivity in this hot and humid region.

The second part of this work is to evaluate the relationship between rain attenuation and wet scintillation characteristics based on one year of measurements data collected throughout the year 2013 in this heavy rain region. Thus, seasonal and diurnal variations of wet scintillation and rain attenuation in equatorial Malaysia have been analyzed based on one year of attenuation data recorded throughout the year 2013. Consequently, the probability density functions (PDFs) of wet scintillation intensity as a function of rain attenuation have been investigated. Whereas, a new method using an integration of distribution input parameters and rain attenuation has been provided in equatorial regions.

In additional, the characteristic of clear sky scintillation and wet scintillation have been analyzed for one-month measurement data, collected from satellite beacon receiver in 2015 at UTM and UTHM locations.

1.5 Research Contributions

Current and future satellite communication systems are operating at any frequency above 10 GHz in tropical and equatorial regions, and frequently suffer from Quality of Service (QoS) due to tropospheric scintillation. In order to establish reliable Earth-space communication services in these equatorial regions, accurate propagation channel models with respect to the local characteristic of tropospheric scintillation are required. Thus, the present work focuses mainly on the characterization of local tropospheric scintillation, specifically devoted to clear sky scintillation and wet scintillation behavior. The main contributions are as follows:

- i. The first contribution is proposal of two enhance diurnal scintillation prediction models, named as Temperature and Humidity ($T & H$) and Temperature and Wet refractivity ($T & N_{wet}$). These models are capable of predicting the clear sky scintillation variance on an hourly basis from the input of link parameters (i.e. frequency, elevation angle and antenna diameter), and meteorological data (i.e. temperature, relative humidity).
- ii. The second contribution focuses on the statistical analysis of wet scintillation characteristics, particularly on the relationships between rain attenuation and scintillation intensity, which are directly derived from the local measurement data in the heavy rain region.
- iii. The third contribution concerns the statistical of probability density functions (PDFs) of wet scintillation intensity as a function of local measured rain attenuation in equatorial Malaysia. New relationships are to be made between conditional PDFs and rain attenuation.
- iv. The fourth contribution focuses on the analysis of seasonal and diurnal variations of wet scintillation and rain attenuation in equatorial Johor Bahru.

These characteristics will help to provide essential information to the design and implementation of fade margin.

1.6 Thesis Outline

This thesis contains six chapters. Chapter 1 provides an overview of the research background on the topic of interest and identifies the problem statements that need to be resolved. This section outlines the research objectives, scope of work and highlights the contributions of this work.

Chapter 2 begins by providing the climatology characteristics of the equatorial region, particularly equatorial Malaysia. These characteristics include seasonal and diurnal variations of tropospheric scintillation in this heavy rain region. Next, prediction models for estimating clear sky scintillation from meteorological parameters are reviewed. Review is continued with explanation on the specifications of filters to separate wet scintillation and rain attenuation, followed by the characteristics of wet scintillation and the relationship between wet scintillation and rain attenuation. A review on scintillation amplitude distribution and scintillation intensity distribution is also included. Finally is brief introduction to MEASAT and Syracuse satellites communication system.

Chapter 3 focuses on the methodology and concept used in this work. It begins by providing an overview of the methodology of this work; flow chart is included for ease of understanding. Three sets of equipment, Direct Broadcast Receiver (DBR), satellite beacon receiver and Automatic Weather Station (AWS) are described. Discussion continues by description on scintillation signals fluctuation processing, followed by a detailed rain attenuation data processing description. In addition, necessary input parameters for the diurnal behaviour of scintillation variance model are provided, and some key concepts of $(T \& H)$ and $(T \& N_{wet})$ models are briefly discussed. Finally, specific information is provided for the relationship between wet scintillation and rain attenuation.

Chapter 4, which provides the results of scintillation analysis in a K_u and K_a band under clear-sky conditions, is divided into three parts. Firstly is discussion on the evaluation of the statistical distribution of scintillation parameters collected in Universiti Teknologi Malaysia (UTM) Johor, Malaysia. Secondly is discussion on the statistical analysis of diurnal variations of scintillation for K_u band in a heavy rainfall region. This is followed by analyses on the performances of surface temperature and humidity ($T&H$), and proposal of the use of surface temperature and wet refractivity ($T&N_{wet}$) prediction models to estimate hourly scintillation variance in an equatorial region. Lastly is discussion on the analysis of clear sky scintillation for K_a -band using low elevation angle, obtained from the measurement campaign carried out at Universiti Teknologi Malaysia (UTM), Johor Bahru, and Universiti Tun Hussein Onn Malaysia (UTHM), BatuPahat, Malaysia.

Chapter 5 presents the analysis on the effect of rain attenuation on scintillation. In relation to this, statistical analysis of rainfall rate database from Automatic Weather Station (AWS) located in Universiti Teknologi Malaysia (UTM) is presented. In addition, the effects of rain attenuation on the wet scintillation analysis, with seasonal and diurnal variations for both phenomena, are discussed. Finally, the statistical analyses of wet scintillation using K_a -band beacon satellite are presented.

Chapter 6 summarises the conclusions obtained from the results, followed by some recommendations for future work.

REFERENCES

- Abdul Rahim, N., M. Islam, J. Mandeep and H. Dao (2012). Comparison of tropospheric scintillation models on earth-space paths in tropical region. *Research Journal of Applied Sciences, Engineering and Technology*. 4(11), 1616-1623.
- Abdullah, N., S. Shuhaimi, Y. Toh, A. Shafee and M. Maznorizan (2011). The Study of Seasonal Variation of PM10 Concentration in Peninsula, Sabah and Sarawak. *Malaysian Meteorological Department*. (9).
- Adhikari, A. and A. Maitra (2011). Studies on the inter-relation of Ku-band scintillations and rain attenuation over an Earth-space path on the basis of their static and dynamic spectral analysis. *Journal of atmospheric and solar-terrestrial physics*. 73(4), 516-527.
- Agunlejika, O., T. Raji and O. Adeleke (2007). Tropospheric scintillation prediction for some selected cities in Nigeria's tropical climate. *International Journal of Basic and Applied Science*. 9(10), 12-19.
- Akhondi, M. and A. Ghorban (2005). Long-Term cumulative distribution modeling of tropospheric scintillation for the earth-satellite links in the 40/50 GHz band. *4th WSEAS International Conference on Electrical, Hardware., Wirel. and Optical Commmunication*.
- Akhondi, M. and A. Ghorbani (2005). New model for tropospheric scintillation fluctuations and intensity in the V-band for the earth-satellite links. *4th WSEAS International Conference on Electronics, Hardware, Wireless and Optical Communications (EHAC' 05), Salzburg, Austria*.
- Ambardar, A. (2006). *Digital Signal Processing-A Modern Introduction*, Thomson-Engineering.

- Banjo, O. and E. Vilar (1987). The dependence of slant path amplitude scintillations on various meteorological parameters. *5th International Conference on Antennas and Propagation*.
- Banjo, O. P. and E. Vilar (1986). Measurement and modeling of amplitude scintillations on low-elevation earth-space paths and impact on communication systems. *Communications, IEEE Transactions on*. 34(8), 774-780.
- Bendat, J. S. and A. G. Piersol (2011). Random data: analysis and measurement procedures, *John Wiley & Sons*.
- Bernard, S. (2001). Digital communications fundamentals and applications. *Prentice Hall, USA*.
- Chen, C. Y. and M. J. Singh (2014). Comparison of tropospheric scintillation prediction models of the Indonesian climate. *Earth, Planets and Space*. 66(1), 1-12.
- Dao, H., I. Md Rafiqul, J. Chebil and K. Al-Khateeb (2013). Scintillation measurement on Ku-band satellite path in tropical climate. *RF and Microwave Conference (RFM), 2013 IEEE International, IEEE*.
- De, A., R. Chakraborty and A. Maitra. Studies on rain induced scintillation during convective events over Kolkata.
- Del Pino, P. G., J. M. Garcia, J. M. Riera and A. Benarroch. Tropospheric scintillation measurements on a Ka-Band satellite link in Madrid.
- Fiebig, U.-C. and C. Riva (2004). Impact of seasonal and diurnal variations on satellite system design in V band. *Antennas and Propagation, IEEE Transactions on*. 52(4), 923-932.
- Filip, M. and E. Vilar (1990). Optimum utilization of the channel capacity of a satellite link in the presence of amplitude scintillations and rain attenuation. *Communications, IEEE Transactions on*. 38(11), 1958-1965.
- Garcia-del-Pino, P., J. M. Riera and A. Benarroch (2012). Tropospheric scintillation with concurrent rain attenuation at 50 GHz in Madrid. *Antennas and Propagation, IEEE Transactions on*. 60(3), 1578-1583.
- Garcia-Rubia, J. M., J. M. Riera, P. García-del-Pino and A. Benarroch (2011). Propagation in the Ka Band: Experimental characterization for satellite applications. *Antennas and Propagation Magazine, IEEE*. 53(2), 65-76.

- Hossain, M. S. and M. A. Samad (2015). The tropospheric scintillation prediction of earth-to-satellite link for Bangladeshi climatic condition. *Serbian Journal of Electrical Engineering*. 12(3), 263-273.
- Islam, M. R., K. Al-Khateeb, F. Mohd Isa, H. Dao, H. Salleh and M. Ghazali (2014). Rain Induced Scintillation Measurement on Satellite Link in Tropical Climate. *Computer and Communication Engineering (ICCCE), 2014 International Conference on, IEEE*.
- ITU-R. (2001). Annual mean surface temperature given in Recommendation ITU-R P.1510-0. Retrieved October, 2015, from <https://www.itu.int/rec/R-REC-P.1510-0-200102-I/en>.
- ITU-R. (2012). Fascicle Concerning the Rainfall Rate Model Given in Annex 1 to Recommendation ITU-R P. 837-6. Retrieved October, 2015, from <https://www.itu.int/oth/R0A0400006B/en>.
- ITU-R. (2015). Effects of tropospheric refraction on radiowave propagation given in Recommendation ITU-R P.834. Retrieved November, 2015, from <https://www.itu.int/rec/R-REC-P.834/en>.
- ITU-R (2015). "Propagation data and prediction methods required for the design of Earth-space telecommunication systems." Recommendation ITU-R: 618-612.
- Johnston, E., D. Bryant, D. Maiti and J. Allnutt (1991). Results of low elevation angle 11 GHz satellite beacon measurements at Goonhilly. *Antennas and Propagation, 1991. ICAP 91., Seventh International Conference on (IEE), IET*.
- Jong, S. L., H. Y. Lam, J. Din and M. D'Amico (2014). The relationship between ground wind direction and seasonal variation of rain attenuation at Ku band satellite broadcasting services. *General Assembly and Scientific Symposium (URSI GASS), 2014 XXXIth URSI, IEEE*.
- Kamp, v. d. M. (1999). Climatic radiowave propagation models for the design of satellite communication systems, *Technische Universiteit Eindhoven*.
- Karasawa, Y. and T. Matsudo (1991). Characteristics of fading on low-elevation angle earth-space paths with concurrent rain attenuation and scintillation. *Antennas and Propagation, IEEE Transactions on*. 39(5), 657-661.
- Karasawa, Y., M. Yamada and J. E. Allnutt (1988). A new prediction method for tropospheric scintillation on earth-space paths. *Antennas and Propagation, IEEE Transactions on*. 36(11), 1608-1614.

- Karasawa, Y., K. Yasukawa and M. Yamada (1988). Tropospheric scintillation in the 14/11-GHz bands on Earth-space paths with low elevation angles. *Antennas and Propagation, IEEE Transactions on*. 36(4), 563-569.
- Kassianides, C. and I. Otung (2003). Dynamic model of tropospheric scintillation on earth-space paths. *IEE Proceedings-Microwaves, Antennas and Propagation*. **150**(2), 97-104.
- Lam, H. Y., L. Luini, J. Din, C. Capsoni and A. D. Panagopoulos (2012). Investigation of rain attenuation in equatorial Kuala Lumpur. *Antennas and Wireless Propagation Letters, IEEE*. 11, 1002-1005.
- Maitra, A. and A. Adhikari (2010). Scintillations of Ku Band Satellite Signal Related to Rain Attenuation at a Tropical Location. *National Workshop on Atmospheric and Space Sciences*.
- Mandeep, J. (2011). Experimental analysis of tropospheric scintillation in Northern Equatorial West Malaysia. *Int. J. Phys. Sci.* 6(7), 1673-1676.
- Mandeep, J., S. Hassan, M. Ain and K. Igarashi (2008). Tropospheric scintillation measurement in Malaysia at Ku-band. *Journal of Electromagnetic Waves and Applications*. 22(8-9), 1063-1070.
- Mandeep, J. and M. Islam (2014). Effect of seasonal variation on tropospheric scintillation at Ku-band in equatorial climate. *Indian Journal of Physics*. 88(6), 541-545.
- Mandeep, J., A. C. C. Yee, M. Abdullah and M. Tariqul (2011). Comparison and analysis of tropospheric scintillation models for Northern Malaysia. *Acta Astronautica*. 69(1), 2-5.
- Mandeep, J. S., A. CHENG CHEN YEE, M. Abdullah and M. T. Islam (2011). Tropospheric scintillation measurements in Ku-band satellite signals on Earth-space paths with low elevation angle. *Idojárás*. 115(4), 265-273.
- Mandeep, J. S. and Y. Y. Ng (2010). Satellite beacon experiment for studying atmospheric dynamics. *Journal of Infrared, Millimeter, and Terahertz Waves*. 31(8), 988-994.
- Marsault, T., L. De Montera, J. Hermant, C. Mallet, L. Barthès and P. Golé (2009). Statistical analysis of the Syracuse 3 satellite EHF propagation experiment. *Antennas and Propagation, 2009. EuCAP 2009. 3rd European Conference on, IEEE*.

- Marsault, T., L. De Montera, J. Hermant, J. Penn, L. Barthes, C. Mallet and P. Gole (2007). EHF propagation experiment with SYRACUSE 3 satellite: First results. *Antennas and Propagation, 2007. EuCAP 2007. The Second European Conference on, IET*.
- Marzano, F. S. and G. D'Auria (1998). Model-based prediction of amplitude scintillation variance due to clear-air tropospheric turbulence on Earth-satellite microwave links. *Antennas and Propagation, IEEE Transactions on*. 46(10), 1506-1518.
- Matlab (2002). Curve fitting toolbox: for use with MATLAB. MathWorks, Inc.
- Matricciani, E. (1994). Physical-mathematical model of dynamics of rain attenuation with application to power spectrum. *Electronics Letters*. 30(6), 522-524.
- Matricciani, E., M. Mauri and C. Riva (1995). Scintillation and simultaneous rain attenuation at 49.5 GHz. *Antennas and Propagation, 1995., Ninth International Conference on* (Conf. Publ. No. 407), IET.
- Matricciani, E., M. Mauri and C. Riva (1996). Relationship between scintillation and rain attenuation at 19.77 GHz. *Radio Science*. 31(2), 273-279.
- Matricciani, E., M. Mauri and C. Riva (1997). Scintillation and simultaneous rain attenuation at 12.5 GHz to satellite Olympus. *Radio Science*. 32(5), 1861-1866.
- Matricciani, E. and C. Riva (2008). 18.7 GHz tropospheric scintillation and simultaneous rain attenuation measured at Spino d'Adda and Darmstadt with Italsat. *Radio Science*. 43(1).
- Mayer, C. E. (2002). Evaluation of 8 scintillation models. *Proceedings of the URSI General Assembly*.
- MEASAT. (2015). Retrieved November, 2015, from <http://www.measat.com/>.
- Merlo, U., E. Fionda and J. Wang (1988). Ground level refractivity and scintillation in space-earth links. *Applied optics*. 27(11), 2247-2252.
- Mertens, D. and D. Vanhoenacker-Janvier (2001). Rain fade dependence model of long-term scintillation amplitude distribution at 12.5 GHz. *Electronics Letters*. 37(10), 657-658.
- Meteorological, M. (2002). Monthly abstract and annual summary of meteorological observations.

- Moulsley, T. J. and E. Vilar (1982). Experimental and theoretical statistics of microwave amplitude scintillations on satellite down-links. *Antennas and Propagation, IEEE Transactions on*. 30(6), 1099-1106.
- Ortgies, G. (1985). Probability density function of amplitude scintillations. *Electronics Letters*. 21(4), 141-142.
- Ortgies, G. (1993). Prediction of slant-path amplitude scintillations from meteorological parameters. *Proc. Int. Symp. Radio Propagat.*
- Ortgies, G. and F. Rücker (1985). Diurnal and seasonal variations of OTS amplitude scintillations. *Electronics Letters*. 21(4), 143-145.
- Otung, I. and B. Evans (1995). Short term distribution of amplitude scintillation on a satellite link. *Electronics Letters*. 31(16), 1328-1329.
- Otung, I., M. S. Mahmoud and J. Norbury (1995). Radiowave amplitude scintillation intensity: Olympus satellite measurements and empirical model. *Electronics Letters*. 31(21), 1873-1875.
- Otung, I. E. (1996). Prediction of tropospheric amplitude scintillation on a satellite link. *Antennas and Propagation, IEEE Transactions on*. 44(12), 1600-1608.
- Peeters, G., F. S. Marzano, G. d'Auria, C. Riva and D. Vanhoenacker-Janvier (1997). EVALUATION OF STATISTICAL MODELS FOR CLEAR-AIR SCINTILLATION PREDICTION USING OLYMPUS SATELLITE MEASUREMENTS. *International journal of satellite communications*. 15(2), 73-88.
- Premarathne, U. and K. Samarasinghe (2010). Analysis of short term scintillation effects of Ku band satellite links in Sri Lanka. *Wireless And Optical Communications Networks (WOCN), 2010 Seventh International Conference On, IEEE*.
- Rahim, N. B. A., M. R. Islam, J. Mandeep, H. Dao and S. O. Bashir (2013). Tropospheric scintillation prediction models for a high elevation angle based on measured data from a tropical region. *Journal of Atmospheric and Solar-Terrestrial Physics*, 105: 91-96.
- Satbeam. (2015). Retrieved November, 2015, from <http://www.satbeams.com/footprints>.
- Smith, S. W. (1997). The scientist and engineer's guide to digital signal processing.

- Suryana, J., S. Utoro, K. Tanaka, K. Igarashi and M. Iida (2005). Two years characterization of concurrent Ku-band rain attenuation and tropospheric scintillation in Bandung, Indonesia using JCSAT3. *Information, Communications and Signal Processing, 2005 Fifth International Conference on, IEEE*.
- SYRACUSE-3A. (2016). Retrieved June, 2016, from <https://satellitecoverage.net/satellite-tracking/?satellite=28885>.
- Tatarski, V. I., R. A. Silverman and N. Chako (2009). Wave propagation in a turbulent medium. *Physics Today*. 14(12), 46-51.
- Touw, S. and M. Herben (1996). Short-term frequency scaling of clear-sky and wet amplitude scintillation. *Microwaves, Antennas and Propagation, IEE Proceedings, IET*.
- Van de Kamp, M. (2000). Experimental verification of asymmetrical short-term scintillation distribution model. *Electronics letters*. 36(7), 663-664.
- Van de Kamp, M. M. (1999). Climatic radiowave propagation models for the design of satellite communication systems.
- Van de Kamp, M. M., C. Riva, J. K. Tervonen and E. T. Salonen (1999). Frequency dependence of amplitude scintillation. *Antennas and Propagation, IEEE Transactions on*. 47(1), 77-85.
- Vander Vorst, A., D. Vanhoenacker and L. Mercier (1982). Fluctuations on OTS-earth copolar link against diurnal and seasonal variations. *Electronics Letters*. 18(21), 915-917.
- Vogel, W., G. Torrence and J. Allnutt (1993). Scintillation fading on a low elevation angle satellite path: Assessing the Austin experiment at 11.2 GHz. *Antennas and Propagation, 1993., Eighth International Conference on, IET*.
- Yang, R., Z. Wu and Y. Li (2003). Analysis of tropospheric scintillation due to clear-air and meteorological elements on slant microwave links. *Third International Asia-Pacific Environmental Remote Sensing Remote Sensing of the Atmosphere, Ocean, Environment, and Space, International Society for Optics and Photonics*.
- Yee, C., J. Mandeep and M. Islam (2013). Modification of Karasawa tropospheric scintillation model for Malaysia climate. *Indian Journal of Physics*. 87(9), 841-845.

- Yu, P., I. Glover, P. Watson, O. Davies, S. Ventouras and C. Wrench (2006). Review and comparison of tropospheric scintillation prediction models for satellite communications. *International journal of satellite communications and networking*. 24(4), 283-302.
- Yusoff, M. M., N. Sengupta, C. Alder, I. Glover, P. Watson, R. Howell and D. L. Bryant (1997). Evidence for the presence of turbulent attenuation on low-elevation angle Earth-space paths. I. Comparison of CCIR recommendation and scintillation observations on a 3.3° path. *Antennas and Propagation, IEEE Transactions on*. 45(1), 73-84.