

CO₂ Total Site Planning with Centralised Multiple Headers

Jeffelee Sanghuang^a, Sharifah Rafidah Wan Alwi^{a,*}, Wan Norlinda Roshana Mohd Nawi^b, Zainuddin Abdul Manan^a, Jiří Jaromír Klemeš^c

^aProcess System Engineering (PROSPECT), Research Institute for Sustainable Environment (RISE), School of Chemical and Energy Engineering, Universiti Teknologi Malaysia (UTM), 81310 Johor Bahru, Malaysia

^bFaculty of Chemical Engineering & Natural Resources, Universiti Malaysia Pahang (UMP), 26300 Kuantan, Pahang Malaysia

^cSustainable Process Integration Laboratory (SPIL), NETME Centre, FME, Brno University of Technology – VUT Brno 616 00, Brno, Czech Republic
syarifah@utm.my

CO₂ Capture, Utilisation and Storage (CCUS) has been gearing towards the technology viable for CO₂ removal from the atmosphere. The successful implementation of an integrated CCUS system would open up the opportunity to develop high CO₂ gas field as well ensures the sustainability of gas production while minimising the impact on the environment. A methodology of CO₂ integration management by maximising the recovery of CO₂ for future utilisation and minimising CO₂ to be sent for sequestration through centralised CO₂ headers or known as CO₂ Total Site has been developed. It consists of one high-purity header that is attached to CO₂ storage or reservoir and low-purity headers that accept CO₂ sources at different purity to satisfy CO₂ demands. The multiple headers with consideration of different purity range of headers and a different number of headers are studied in this work. The application of the CO₂ Total Site-Problem Table Analysis (CTS-PTA) has potentially resulted in an optimal CO₂ target with the reduction of carbon storage of 32 % with a lower risk of CO₂ leakage and low CO₂ emission.

1. Introduction

The carbon emission is increasing with the continuous increase in world energy consumption. In a combination of CO₂ capture and storage and utilisation (CCUS), the CO₂ emissions can be reduced by capturing CO₂ and injecting it into geological storage or through utilisation. The CO₂ capture and storage (CCS) technology involves the capturing of CO₂ from the exhaust gases from large industrial facilities and appropriately storing it in geological storage sites such as depleted oil and/or gas reservoirs. However, integrated CO₂ capture and utilisation have been reported as a promising route toward economically viable chains of values (Stuardi et al., 2019). Pinch Analysis based methodology has been widely used in planning CO₂ capture and storage such as storage planning and CO₂ sources and sinks matches (Diamante et al., 2014). This methodology has emerged as an important branch of Process Integration (PI) for problems involving the management of CO₂ emissions (Tapia et al., 2018). An approach using CO₂ Pinch Total Site methodology was developed to manage CO₂ capture and CO₂ demands from various plants into centralised header before send to storage or sequestration (Mohd Nawi et al., 2015). The algebraic method for targeting the optimum CO₂ utilisation and storage based on the Pinch Analysis approach was introduced (Mohd Nawi et al., 2016). An extended methodology with consideration of different purity range of headers and a different number of headers is proposed in this paper to enhance the systematic planning and management of CO₂ emission for a sustainable potential alternative which can directly be related to the industrial symbiosis.

2. Methodology

A methodology development of the Total Site CO₂ Integration (TSCI) targeting technique for optimal carbon target of CO₂ utilisation and storage is described. Generally, the methodology comprises of four main steps which are setting the header, data extraction, constructing problem table algorithm and analysing the result.

2.1 Step 1: Setting CCUS header

A potential area is selected for the implementation of TSCI planning. The area has to consist of a number of CO₂ sources and demands. The decision on the number of TSCI centralised headers is within the flue gas purity of CO₂ sources and demands. The highest flue gas purity of CO₂ from demand is about 99 %, so the acceptability of one of the headers must be within the range so that the demand can extract the required CO₂ supply from the centralised header. The rest of the centralised headers are set at lower acceptable purity range to satisfy demands which have lower purity requirement. Since this is an end-of-pipe solution, the header with high purity range is designed for reservoir storage as the final destination. For the flue gas within the centralised headers with lower acceptable purity range has to be fully consumed by the last demand at the end of its pipeline.

2.2 Step 2: Data extraction

The limiting data for the CO₂ sources and CO₂ demand in the selected potential area are identified and extracted based on their location along the headers from the beginning of the pipeline until the identified end. A flue gas consists of CO₂ gas and other various gases such as nitrogen (N₂), oxygen (O₂), carbon monoxide (CO), nitrogen oxide (NO_x), and sulphur oxide (SO_x). The extracted data includes the flue gas flow (F_T) and the gas CO₂ purity (P_{CO_2}). The amount of CO₂ (F_{CO_2}) and other gases flow rates (F_{OG}) can be calculated using equations adapted from Mohd Nawi et al. (2016).

2.3 Step 3: Problem Table Algorithm construction

An algorithmic method is developed for the planning and managing the CO₂ sources and demands using centralised headers. The problem table algorithm, namely CO₂ Total Site Problem Table Algorithm (CTS-PTA), is extended to target the maximum amount of CO₂ that will be utilised with the minimum amount of sequestered CO₂ for multiple headers. CTS-PTA is based on the TS concept, provides the insight-based solution which can be used as a tool for CCUS planners and mechanisms to maximise the CO₂ utilised and minimise the CO₂ stored based on the location of sources and demands along the centralised header instead of their purities. By taking Header 1 (H1) as an example, the step-wise description of performing CTS-PTA is detailed in this section. Starting from the beginning of the centralised header, the sources and demands are matched by performing F_T ($Cum F_T$) and F_{CO_2} ($Cum F_{CO_2}$) cascade, the accumulation of F_T and F_{CO_2} cascade using equations adapted from Mohd Nawi et al. (2016). Meanwhile, the header CO₂ purity (P_{H1}) after going through each source also can be calculated using equations adapted from Mohd Nawi et al. (2016).

At demands' locations, F_T and F_{CO_2} are accumulated from the top to the bottom row with the flow values of gases from header to specific location ($F_{T,H1-D}$, $F_{T,H1-H2}$, $F_{T,H1-H3}$, $F_{CO_2,H1-D}$, $F_{CO_2,H1-H2}$, and $F_{CO_2,H1-H3}$) needs to be considered, as given in Eq(1) and Eq(2). There are two TSCI utilisation rules 1 or 2 need to satisfy for CO₂ demands as adapted in Mohd Nawi et al. (2016). TSCI utilisation rule 1 is for the demand requires a higher CO₂ purity ($P_{CO_2,D,i}$) (example 99%) than that accumulation of header CO₂ purity ($P_{H1,i-1}$) in the header (example 86%). A mixture of pure CO₂ from the CO₂ generator is required to satisfy the requirement of high purity demands. TSCI utilisation rule 2 is for the demand requires equal or lower CO₂ purity ($P_{CO_2,D,i}$) than the accumulated CO₂ purity in the header. Any F_T from the header can directly be supplied to the demand by assuming that the demand can accept equal or higher purity sources.

The minimum target of F_T and F_{CO_2} that is to be sent to the dedicated geological storage can refer to the last row of Column 7 ($Cum F_T$) and Column 8 ($Cum F_{CO_2}$) respectively. The total fresh CO₂ required from the centralised pure CO₂ generator is the summation of Column 12 ($F_{CO_2,FC}$). For the subsequent headers, the same procedures are applied except the fresh CO₂ supply from the centralised CO₂ generator. The cleaner flue gas from the header with higher acceptable purity range has the potential to be utilised instead of using pure CO₂ to satisfy higher CO₂ purity demands for TSCI utilisation rule 1. The amount of F_T taken from H2 ($F_{T,H2-D}$) and H1 ($F_{T,H1-D}$) to satisfy demand at H2 can be calculated using Eq(3) and Eq(4).

$$Cum F_{T,H2,i} = Cum F_{T,H2,i-1} + F_{T,H2-D,i} + F_{T,H2-H3,i} \quad (1)$$

$$Cum F_{CO_2,H2,i} = Cum F_{CO_2,H2,i-1} + F_{CO_2,H2-D,i} + F_{CO_2,H2-H3,i} \quad (2)$$

$$F_{T,H2-D,i} = (F_{T,D,i} \cdot P_{H1,i-1} - F_{T,D,i} \cdot P_{D,i}) / (P_{H1,i-1} - P_{H2,i-1}) \quad (3)$$

$$F_{T,H1-D,i} = F_{T,D,i} - F_{T,H2-D,i} \quad (4)$$

For the situation where CO₂ in the header with a lower purity range is a deficit to supply to a demand in the header. Instead of using fresh, pure CO₂, the surplus of CO₂ from another header with higher purity range can direct referring the amount of needed CO₂ with neglecting the purity demand in the header since it tends to be ideally below than the other headers. For example, in header 3 (H3), the surplus of CO₂ from H1 can supply to H3 to solve the deficit problem in H3 to satisfy the requirement of demand in H3. Eq(5) and Eq(6) described the gases transportation between other headers to H3, listed in Column 29 and Column 31 (Table 2c).

$$F_{T,H1-H3,i} = Cum F_{T,H3,i-1} + F_{T,D,i} \quad (5)$$

$$F_{T,H2-H3,i} = Cum F_{T,H3,i-1} + F_{T,D,i} - F_{T,H1-H3,i} \quad (6)$$

As only H1 is designed to be sent to geological storage, the last row of $Cum F_{T,H2}$ (Column 16) and $Cum F_{T,H3}$ (Column 24) should not give any access where the surplus value of F_T should be reduced by part of the sources, preferably the source with lower purity. When the last row of $Cum F_T$ gives a zero value, that is the Pinch Point of the TSCI system.

3. Results and discussion

The CTS-PTA method was demonstrated with a combined case study data from Texas by Hasan et al. (2014) and another case study from an industrial site by Munir et al. (2012). The arrangement of the sources and demands across the headers is assumed as shown in Table 1. As the mentioned sign of flow rate, the positive values indicate CO₂ input flow rate into the header whereas the negative values are output flow rate from the header. A CTS-PTA is performed to optimise the carbon target of CCUS with a few scenarios. The effect of different acceptable purity range and number of headers are analysed through the application of CTS-PTA on five different scenarios.

Table 1: Arrangement of CO₂ sources and demands across the header

S/D	Description	P _{CO₂} (%)	F _T (t/h)	F _{CO₂} (t/h)	F _{OG} (t/h)
S1	Cement	90	138.8	124.9	13.9
S2	Refineries/Chemical	70	608.5	425.9	182.5
S3	Power (coal based)	85	1,174.3	998.2	176.1
D1	Beverage plant	99	-50.0	-49.5	-0.5
S4	Power (NG based)	88	101.5	89.3	12.2
S5	Agricultural	65	69.9	45.4	24.4
D2	Enhance oil recovery	80	-208.3	-166.6	-41.7
S6	Petrochemical	80	615.4	492.3	123.1
S7	Gas processing	90	36.5	32.8	3.6
S8	Iron & Steel (corex)	95	27.9	26.5	1.4
D3	Methanol Production	50	-83.3	-41.7	-41.7
D4	Micro Algae Production	10	-220.0	-22.0	-198.0

3.1 Example scenario 1

In this scenario, TSCI is studied by using one header approach. All the CO₂ sources and demands are integrated into one header. The minimum amount of remaining CO₂ in Column 8 after cascading is 1,821.2 t/h which is needed to be sent to geological reservoirs for CO₂ storage. There is 47.4 t/h amount of fresh CO₂ from the CO₂ generator is needed to blend with the header gas in order to reach the requirement of the demand. The CO₂ purity in the stream header at the end is accumulated to 81 % which is still under the acceptable range as the assumption of only 80 % and above purity can enter geological storage.

3.2 Example scenario 2,3,4

In this scenario, TSCI is studied by using two header approaches. Each of the headers is set to a certain purity range. Each of the headers is set to a certain purity range. For Scenario 2, H1 is set to 80 - 99.99 % while H2 is set to 50 - 79.99 %. For Scenario 3, H1 is set to 90 - 99.99 % while H2 is set to 50 - 89.99 %. For Scenario 4, H1 is set to 85 - 99.99 % while H2 is set to 50 - 84.99 %. However, H2 for all scenarios (2,3,4) does not have access to storage. For this reason, any of an excess CO₂ in the last row ($Cum F_{T,H2}$) needs to be deducted with the sources from H2. This is the Pinch Point of the system where the CO₂ from the H2 which cannot be stored, might still be emitted to the environment. After performing the CTS-PTA, the minimum of amount of remaining of CO₂ in Column 8 (H1) after cascading is 1,582.6 t/h, 179.8 t/h, and 917.2 t/h for Scenario 2, 3, and 4.

3.3 Example scenario 5

For further scenario, three headers were set with a purity range between 90 – 99.99 % for H1, 70 – 89.99 % for H2 and 50 – 69.99 % for H3. The results are shown in Table 2a, 2b and 2c.

Table 2a: CTS-PTA Scenario 5 for H1

	1	2	3	4	5	6	7	8	9	10	11	12		
i	S/ D	Hea der	P _{CO2,S/D} (%)	F _{T^{H1},S/D} (t/h)	F _{CO2^{H1},S/D} (t/h)	F _{OG^{H1},S/D} (t/h)	Cum (t/h)	F _{T,H1} (t/h)	Cum (t/h)	F _{CO2,H1} (t/h)	P _{CO2,H1} (t/h)	F _{CO2,H1-D} (t/h)	F _{T,H1-D} (t/h)	F _{CO2,FC-D} (t/h)
1	S1	H1	90.0	138.8	124.9	13.9								
2	S2	H2	70.0				138.8	124.9	0.90					
3	S3	H2	85.0				138.8	124.9	0.90					
4	D1	H1	99.0	-50.0	-49.5	-0.5	138.8	124.9	0.90			-4.5	-5.0	45.0
5	S4	H2	88.0				133.8	120.4	0.90					
6	S5	H3	65.0				133.8	120.4	0.90					
7	D2	H2	80.0				133.8	120.4	0.90					
8	S6	H2	80.0				133.8	120.4	0.90					
9	S7	H1	90.0	36.5	32.9	3.7	170.3	153.3	0.90					
10	S8	H1	95.0	27.9	26.5	1.4	198.2	179.8	0.91					
11	D3	H3	50.0				184.8	167.6	0.91					
12	D4	H3	10.0				0.0	0.0	0.00					

Table 2b: CTS-PTA Scenario 5 for H2

	1	2	3	13	14	15	16	17	18	19	20		
i	S/ D	Header	P _{CO2,S/D} (%)	F _{T^{H2},S/D} (t/h)	F _{CO2^{H2},S/D} (t/h)	F _{OG^{H2},S/D} (t/h)	Cum (t/h)	F _{T,H2} (t/h)	Cum (t/h)	F _{CO2,H2} (t/h)	P _{CO2,H2} (t/h)	F _{CO2,H2-D} (t/h)	F _{T,H2-D} (t/h)
1	S1	H1	90.0										
2	S2	H2	70.0	608.5	426.0	182.6							
3	S3	H2	85.0	1,174.3	998.2	176.1	608.5	426.0	0.70				
4	D1	H1	99.0				1,782.8	1,424.1	0.80				
5	S4	H2	88.0	101.5	89.3	12.2	1,782.8	1,424.1	0.80				
6	S5	H3	65.0				1,884.3	1,513.4	0.80				
7	D2	H2	80.0	-208.3	-166.6	-41.7	1,884.3	1,513.4	0.80			-167.3	-208.3
8	S6	H2	80.0	615.4	492.3	123.1	1,676.0	1,346.1	0.80				
9	S7	H1	90.0				2,291.4	1,838.4	0.80				
10	S8	H1	95.0				2,291.4	1,838.4	0.80				
11	D3	H3	50.0				2,291.4	1,838.4	0.80				
12	D4	H3	10.0				2,291.4	1,838.4	0.80				
							2,256.2	1,810.2	0.80				

Table 2c: CTS-PTA Scenario 5 for H3

	1	3	21	22	23	24	25	26	27	28	29	30	31	32
i	S/D	$P_{CO_2,S/D}$ (%)	$F_{T,H^3,S/D}$ (t/h)	$F_{CO_2,H^3,S/D}$ (t/h)	$F_{OG,H^3,S/D}$ (t/h)	Cum F_{T,H^3} (t/h)	Cum F_{CO_2,H^3} (t/h)	P_{CO_2,H^3}	F_{CO_2,H^3-D} (t/h)	F_{T,H^3-D} (t/h)	F_{T,H^1-H^3} (t/h)	F_{CO_2,H^1-H^3} (t/h)	F_{T,H^2-H^3} (t/h)	F_{CO_2,H^2-H^3} (t/h)
1	S1	90.0												
2	S2	70.0												
3	S3	85.0												
4	D1	99.0												
5	S4	88.0												
6	S5	65.0	69.9	45.4	24.5	69.9	45.4	0.65						
7	D2	80.0				69.9	45.4	0.65						
8	S6	80.0				69.9	45.4	0.65						
9	S7	90.0				69.9	45.4	0.65						
10	S8	95.0				69.9	45.4	0.65						
11	D3	50.0	-83.3	-41.7	-41.7	0.0	0.0		-54.1	-83.3	-13.4	-12.2		
12	D4	10.0	-220.0	-22.0	-198.0	220.0	195.9	0.89		-220.0	-184.8	-167.6	-35.2	-28.2
						0.0								

In Scenario 5, there is no excess amount of CO₂ in H1 after cascading, a zero value at the last row of Cum F_{CO₂} (Column 8 in Table 2a). This is due to the deficit in CO₂ supply at H3. There is about 13.4 t/h of flue gas supplied to H3 at the location of D3 in order to cover the CO₂ supply deficit to satisfy the demand. Besides, an amount of 184.8 t/h flue gas from H1 and an amount of 35.2 t/h flue gas from H2 are supplied into H3 to fulfil the requirement of demand 4. Refer to Table 2a, it can be seen there is excess flue gas in H2, there is about 2,256.2 t/h Cum F_{T,H²} at the last row of Column 16. The same procedure is carried out to deduct the amount of CO₂ supply from the sources that supply into H2, which are S2, S3 and S8. All the amount of sources are eliminated from supplying to H2 except for the S3. The supply amount of flue gas from S3 is changed to 142 t/h from 1,174.3 t/h. There is no excess accumulation of CO₂ at the end of H2. As mentioned previously, there is about 35.2 t/h of flue gas is needed to inject into H3 to satisfy the D4 which is one of the demands that extract flue gas from the header. However, there is also a large amount of captured CO₂ might still emit into the environment which up to 1,795.8 t/h.

The result obtained from all the scenarios is analysed and compared as shown in Table 3. Table 3 includes the base case study as the reference to the CCS without CCUS concept applied. The adjustment of purity range and number on the headers gave impact in the amount and purity of CO₂ which is sent to geological storage. The amount of fresh CO₂ and the carbon emission are also affected by the mentioned factors. With the consideration of TSCI, Scenario 3 and 5 are giving a negative result as there is a large potential CO₂ emission as the captured carbon from the sources might still be emitted into the environment although they have high percentage reduction of carbon storage with a low amount of CO₂ sent to geological storage.

The amount of CO₂ sent to geological storage in Scenario 2 and 4 are lower than in Scenario 1. However, there is an amount of captured CO₂ from sources that cannot be stored and might still be emitted to the atmosphere as the Pinch Point of H2 is achieved. In Scenario 1, there is no Pinch Point should be considered and no captured CO₂ released into the atmosphere and all the excess CO is sent to storage. The result of purity in sequestered CO₂ for Scenario 1 is barely lower than 80 % which prove that one header approach would create uncertain storage condition and lead to difficulty in controlling the CO₂ purity from various emission sources. In short, Scenario 1 might still be a questionable selection of CCUS planning depending on the condition of sources and demands. For Scenario 2 and 4, the lower flow rate required in fresh CO₂ results in a reduction of overall

capital cost when compared to the base case without utilisation consideration. Scenario 2 gives a lower carbon emission, but higher in the amount of CO₂ sent to geological storage.

In contrast, Scenario 4 gives a better result in minimising the amount of CO₂ sequestered but higher amount of CO₂ emission. The carbon emissions storage life capacity is estimated for both Scenarios; there is a potential of extending storage life about 10.3 % and 34.6 % for Scenario 2 and 4. As the objective of this study is the optimal carbon target of CCUS, Scenario 2 has higher potential in the low carbon emission planning with the optimal CCUS condition compared to Scenario 4.

Table 3: Summary of results between CCS (base case) and all the scenarios (1,2,3,4,5)

	Base Case: CCS (without utilisation header)	Scenario 1	Scenario 2	Scenario 3	Scenario 4	Scenario 5
CO ₂ sequestered in storage (t/h)	1,764 (sources with ≥ 80 % purity)	1,821.2	1,582.5	179.8	1,153.1	0
Purity of CO ₂ sequestered	84 %	81 %	84 %	91 %	86 %	-
Fresh/outsource of CO ₂ needed (t/h)	279.8	47.4	46.5	45.0	46.5	45.0

4. Conclusions

An extended methodology of TSCI has been developed by the numerical technique which is known as CTS-PTA to analyse the impact of purification range and number of headers. This newly developed method has contributed significantly to addressing the maximum utilisation of CO₂ and minimum CO₂ to be stored in geological storage. With all the scenarios given, the most optimal CO₂ target can reduce a 32 % of CO₂ storage with a lower risk of CO₂ leakage and low potential of CO₂ emitted into the environment. The technique is now available for CCUS planners to design their future headers according to CCUS mechanisms for significant CO₂ reduction planning and management.

Acknowledgements

The authors would like to thank Universiti Teknologi Malaysia (UTM) under Vote Number Q.J130000.3509.05G96, Q.J130000.2509.19H34, Malaysia Ministry of Education under Fundamental Research Grant Scheme R.J130000.7809.4F918 and EC project for Sustainable Process Integration Laboratory-SPIL (Project No. CZ.02.1.01/0.0/0.0/15_003/0000456) funded by Czech Republic Operational Program Research and Development, Education, Priority 1: Strengthening capacity for quality research in collaboration agreement with Universiti Teknologi Malaysia (UTM), for providing research funds for this project.

References

- Diamante, J. A. R., Tan, R. R., Foo, D. C. Y., Ng, D. K. S., Aviso, K. B., Bandyopadhyay, S., 2014. Unified Pinch Approach for Targeting of Carbon Capture and Storage (CCS) Systems with Multiple Time Periods and Regions. *Journal of Cleaner Production*, 71, 67-74.
- Hasan, M. M. F., Boukouvala, F., First, E. L., Floudas, C. A., 2014. Nationwide, Regional, and Statewide CO₂ Capture, Utilization, and Sequestration Supply Chain Network Optimization. *Industrial & Engineering Chemistry Research*, 53, 7489-7506.
- Mohd Nawi, W. N. R., Wan Alwi, S. R., Manan, Z. A., Klemeš, J. J., 2015. A New Algebraic Pinch Analysis Tool for Optimising CO₂ Capture, Utilisation and Storage. *Chemical Engineering Transactions*, 45, 265-270
- Mohd Nawi, W. N. R., Wan Alwi, S. R., Manan, Z. A., Klemeš, J. J., 2016. Pinch Analysis targeting for CO₂ Total Site planning. *Clean Technologies and Environmental Policy*, 10.1007/s10098-016-1154-7.
- Munir, S. M., Abdul Manan, Z., Wan Alwi, S. R., 2012. Holistic Carbon Planning for Industrial Parks: A Waste-To-Resources Process Integration Approach. *Journal of Cleaner Production*, 33, 74-85.
- Stuardi, F. M., MacPherson, F., Leclaire, J., 2019. Integrated CO₂-capture and utilization: a priority research direction. *Current Opinion in Green and Sustainable Chemistry*, 10.1016/j.cogsc.2019.02.003.
- Tapia, J. F. D., Lee, J., Ooi, R. E. H., Foo, D. C. Y., Tan, R. R. (2018). A review of optimization and decision-making models for the planning of CO₂ capture, utilization and storage (CCUS) systems. *Sustainable Production and Consumption*, 13, 1-15.