

CUTTINGS LIFTING IMPROVEMENT OF DIFFERENT DRILLED CUTTING  
SIZES USING POLYPROPYLENE BEADS WITH AND WITHOUT PIPE  
ROTATION

HALIMATUN SAADIAH BINTI HARUN AMIN RASHID

A thesis submitted in fulfilment of the  
requirements for the award of the degree of  
Master of Philosophy

School of Chemical and Energy Engineering  
Faculty of Engineering  
Universiti Teknologi Malaysia

JANUARI 2020

## ACKNOWLEDGEMENT

First and foremost, I am profoundly grateful to Allah, the Ever-Magnificent, the Ever-Thankful, for His help and bless. I am absolutely certain that this work would have never become truth without His guidance.

I am profoundly grateful and wish to express my deepest gratitude to Associate Professor Issham Bin Ismail, my main supervisor who always there through ups and downs from the beginning till the completion of the present research, who always supported me and have patiently guided me and giving excellent supervision. I am deeply appreciative for his invaluable guidance, the long time and tremendous effort to offer every possible help to finish this thesis. It was a great honour to finish this work under his supervision.

I would like to extend my deepest appreciation to Professor Dr Ariffin Bin Samsuri, my compassionate co-supervisor, for his continuous support and guidance during the master degree process. He was a tremendous asset who provided outstanding mentoring. His insight, constructive feedback and recommendations have added depth to the project, and his attention to this project was instrumental to the success of thesis completion.

I am absolutely grateful to have such a loving and phenomenal husband, Ahmad Kamarul Anwar, who knew the timely words of affirmation and motivation that kept me moving forward. Your unyielding love, sacrifices, prayers, supports, and encouragement throughout this journey was priceless and will always be recalled. I am blessed to have such understanding sons Darwisy Mustaffa and Qaiser Malik. You have inspired me in ways that you may never understand, and I love you both so much.

I would like to express my wholehearted thanks to my family and in-law for the generous support through the process of pursuing the master degree. Because of their unconditional love and prayers, I have the chance to complete this thesis. I would like to take this opportunity to say warm thanks to all my beloved friends, who have been so supportive along the way of doing my thesis. Last but not least, sincerest thanks go to all people who took part in making this thesis real.

## ABSTRACT

Directional wells become a successful field-development method to meet higher energy demands worldwide and to increase the recovery factor. However, the most challenging problem encountered in drilling such wells is inefficient wellbore cleaning. Therefore, this study was conducted to investigate the performance of polypropylene copolymer (PP) beads in water-based mud to hamper the wellbore cleaning issue. The study includes sample characterization and investigation of the effect on mud rheological and filtration properties. The presence of ethylene in the PP beads composition has led to an increase in their melting point up to 159°C (318°F), which is higher than typical reservoir temperature reported in Malay Basin. Therefore, the mud rheological and filtration properties tests were conducted up to 250°F only. Also, the PP beads were discovered to degrade at 278.59°C (533.46°F). The effect of hole cleaning have been scrutinized using a flow loop test section (20-ft of transparent PVC having a 3.042-inch ID simulated as wellbore, and a rotatable Class B carbon steel with 1.346-inch OD which simulates a drill pipe) and were compared with basic water-based mud (WBM) at various wellbore inclination angles (from 0° to 90°) and pipe rotation speed (from 0 to 150 rpm). The experimental work was executed using several PP beads concentrations (from 0 to 10 ppb), which were introduced in water-based mud, and their performances were compared with basic WBM in terms of rheological properties and cuttings transport performance (CTP). CTP is an extent measure to lift unwanted cuttings out of the wellbore and was performed by employing 0.25% (by volume) of different cutting sizes, ranging from 0.5 to 4.0 mm, in the prepared mud. The comparison also made based on PP beads concentration, cutting sizes, wellbore angles, and pipe rotation speed with basic WBM. The experimental results showed that the rheological properties are slightly increased when mingling the PP beads with mud, and the opposite outcome was obtained for filtration properties. Furthermore, the CTP improved once commingled with PP beads for all different cutting sizes and hole angles due to the buoyancy and impulsive effects. This experiment also detects the critical angle between 30° to 60°, which indicates by decreasing of CTP and the lowest CTP was found at 60°. Since buoyancy and impulsive force at the horizontal hole is negligible, a combination effect of pipe rotation, mud rheology (mud viscosity of 15 cP) and flow regime (turbulent flow) has rendered improvement towards lifting performance. Besides, smaller cuttings appeared to be easier to be transported compared to the larger cuttings in both vertical and deviated wells, for each rotary speed and drilling muds. Additionally, pipe rotation contributes to cuttings transport by increasing the CTP for all experimental variables. Conclusively, the presence of PP beads in the mud has reduced the cuttings concentration in the wellbore for all cutting sizes and hole angles, and thereby enhances the CTP. Henceforth, making the PP beads a promising additive for drilling mud in lifting drilled cuttings out of the hole effectively.

## ABSTRAK

Telaga berarah menjadi kaedah yang berjaya dalam medan pembangunan bagi memenuhi permintaan tenaga yang tinggi di seluruh dunia dan meningkatkan faktor perolehan. Walau bagaimanapun, masalah yang paling mencabar yang dihadapi dalam penggerudian telaga ialah ketidakcekapan dalam pembersihan lubang telaga. Oleh itu, kajian ini dilaksanakan untuk mengkaji prestasi manik kopolimer polipropilena (PP) dalam lumpur dasar air untuk menghalang masalah pembersihan lubang telaga. Kajian termasuk pencirian sampel dan kesannya terhadap sifat-sifat reologi lumpur dan penurasan. Kehadiran etilena dalam komposisi PP manik telah membawa kepada peningkatan kadar lebur sehingga 159°C (318°F), lebih tinggi daripada suhu reservoir di Lembangan Melayu. Oleh itu, ujian sifat reologi lumpur dan penurasan telah dilaksanakan sehingga 250°F sahaja. Juga, manik PP didapati merosot pada 278.59°C (533.46°F). Kesan pembersihan lubang telah diteliti menggunakan seksyen ujian gelung aliran (20-kaki PVC lutsinar yang berdiameter 3.042-inci bagi mensimulasikannya sebagai telaga dan keluli karbon Kelas B berputar dengan diameter luar 1.346-inci disimulasi sebagai paip gerudi) dan dibandingkan dengan lumpur dasar air (WBM) pada pelbagai sudut kecondongan telaga (dari 0° sehingga 90°) dan kelajuan putaran paip (dari 0 sehingga 150 rpm). Uji kaji dilaksanakan menggunakan beberapa kepekatan PP (dari 0 hingga 10 ppb), yang dicampurkan dengan lumpur dasar air, dan prestasinya dibandingkan dengan WBM dari segi sifat reologi dan prestasi pengangkutan rincisan (CTP). CTP ialah ukuran bagi keupayaan mengangkut keratan yang tidak diingini keluar dari lubang telaga dan dilaksanakan dengan menggunakan 0.25% (berdasarkan isipadu) jumlah rincisan pelbagai saiz, dari 0.5 mm sehingga 4.0 mm, dalam lumpur yang disediakan. Perbandingan juga dibuat berdasarkan kepekatan PP, saiz keratan, sudut lubang telaga, dan kelajuan putaran paip dengan WBM. Hasil ujikaji menunjukkan bahawa sifat reologi sedikit meningkat apabila manik PP bercampur dengan lumpur, dan hasil yang bertentangan diperoleh bagi sifat penurasan. Tambahan pula, CTP bertambah baik apabila bercampur dengan manik PP untuk semua saiz rincisan dan semua sudut lubang berikutan kesan keapungan dan impulsif. Kajian turut mengenal pasti sudut kritikal iaitu dari 30° sehingga 60° yang menyebabkan berlakunya penurunan CTP dengan CTP paling rendah berlaku pada 60°. Memandangkan daya keapungan dan impulsif pada lubang mendatar adalah kecil, kesan kombinasi putaran paip, reologi lumpur (kelikatan lumpur 15 cP) dan rejim aliran (aliran bergelora) telah meningkatkan prestasi pengangkutan. Selain itu, rincisan yang lebih kecil kelihatan lebih mudah untuk diangkut berbanding rincisan yang lebih besar bagi kedua-dua telaga tegak dan condong pada semua kelajuan berputar dan lumpur gerudi. Selain itu, putaran paip menyumbang kepada pengangkutan rincisan dengan meningkatnya CTP untuk semua pembolehubah eksperimen. Kesimpulannya, kehadiran manik PP dalam lumpur telah mengurangkan kepekatan rincisan dalam lubang telaga bagi semua saiz rincisan dan sudut lubang, dan dengan itu meningkatkan CTP. Seterusnya, menjadikan manik PP sebagai bahan tambah lumpur yang berpotensi besar bagi mengangkut rincisan gerudi keluar dari lubang secara berkesan.

## TABLE OF CONTENTS

	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>TABLE OF CONTENTS</b>	<b>vii</b>
	<b>LIST OF TABLES</b>	<b>xii</b>
	<b>LIST OF FIGURES</b>	<b>xiv</b>
	<b>LIST OF ABBREVIATIONS</b>	<b>xviii</b>
	<b>LIST OF SYMBOLS</b>	<b>xx</b>
	<b>LIST OF UNITS</b>	<b>xxiii</b>
	<b>LIST OF APPENDICES</b>	<b>xxv</b>
<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 Background of Study	1
	1.2 Statement of Problem	3
	1.3 Hypotheses of Study	5
	1.4 Objective of Study	6
	1.5 Research Scope	6
	1.6 Significance of the Study	7
	1.7 Thesis Overview	8
	1.8 Chapter Summary	9
<b>CHAPTER 2</b>	<b>LITERATURE REVIEW</b>	<b>11</b>
	2.1 Drilling Fluid Rheology	11
	2.2 Mud Rheological Model (Fluid Flow Behaviour)	14
	2.2.1 Bingham Plastic Model	15
	2.2.2 Power-Law Model	16

2.2.3	Herschel-Buckley Model (Yield-Power Law Model)	17
2.2.4	Casson Model	18
2.2.5	Robertson-Stiff Model	18
2.3	Overview of Hole Cleaning	19
2.4	Cuttings Transport Mechanism	21
2.4.1	Force Analysis	22
2.4.2	Cuttings Transport Flow Patterns	26
2.4.3	Mechanism of Cuttings Transport	28
2.5	Parameters Affecting Hole Cleaning	30
2.5.1	Effect of Operational Parameters upon Hole Cleaning	31
2.5.1.1	Hole Inclination	31
2.5.1.2	Pipe Rotation Speed	36
2.5.1.3	Rate of Penetration (ROP)	41
2.5.1.4	Pipe eccentricity	42
2.5.1.5	Annular/Hole size	46
2.5.2	Effect of Fluid Parameters on Transportation of Cuttings	47
2.5.2.1	Mud Weight (Mud Density)	47
2.5.2.2	Mud Type	49
2.5.2.3	Mud Rheology	51
2.5.2.4	Mud Flow Rate (Related to Annular Velocity)	55
2.5.3	Effect of Cuttings Parameter on Cuttings Transport	60
2.6	Previous Works on the Application of Beads in Cuttings Transport	66
2.7	Chapter Summary	72
<b>CHAPTER 3</b>	<b>RESEARCH METHODOLOGY</b>	<b>73</b>
3.1	Research Design	73
3.2	Materials Preparation	76
3.2.1	Preparation of Simulated Cuttings	77

3.2.2	Analysis of Procured Polymer Beads	79
3.2.2.1	Thermogravimetric Analysis (TGA) on Polymer Beads	81
3.2.2.2	Fourier Transform Infrared Spectroscopy (FTIR Analysis)	83
3.2.3	Preparation of Drilling Fluid System	84
3.3	Equipment and Procedures for Drilling Fluid Performance Evaluation	88
3.3.1	Mud Weight Measurement	89
3.3.2	Viscosity Measurement	90
3.3.3	Gel Strength Measurement	91
3.3.4	pH Determination	91
3.3.5	Fluid Loss Determination	92
3.3.6	Aging Analysis of Drilling Fluid	94
3.3.7	Mud Rheological Model Test	95
3.4	Flow Loop Experimental Program	97
3.4.1	Cuttings Transport Flow Loop (Rig Simulator)	97
3.4.2	Mud Tank	101
3.4.3	Pump and Piping System	103
3.4.4	Annular Test Section	106
3.4.5	Inclination Angle System	109
3.4.6	Drill Pipe Rotation System	111
3.4.7	Flow Rate Measurement System	112
3.4.8	Cuttings Injection System	113
3.4.9	Cuttings Collection and Separation System	114
3.5	Experimental Procedures	116
3.6	Chapter Summary	120
<b>CHAPTER 4</b>	<b>RESULTS AND DISCUSSION</b>	<b>123</b>
4.1	Characterization of Polypropylene Copolymer (PP) Beads	123
4.1.1	Thermal Degradation of Polymer Beads	123
4.1.2	Fourier Transform Infrared Spectroscopy (FTIR) on PP Beads	124

4.2	Rheological Model (Fluid Flow Behavior)	127
4.3	Mud Rheological Properties	128
4.3.1	Apparent Viscosity	129
4.3.2	Plastic Viscosity	131
4.3.3	Yield Point	132
4.3.4	Gel Strength	134
4.4	pH Level	136
4.5	Fluid Loss Control	137
4.6	Mud Cake Thickness	138
4.7	Cuttings Transport Performance (CTP) without Pipe Rotation	140
4.7.1	Effect of Hole Inclination on CTP without Pipe Rotation	140
4.7.2	Force Analysis	145
4.7.2.1	Buoyancy Force	145
4.7.2.2	Impulsive Force	146
4.7.3	Effect of Polymer Beads Concentration on CTP without Pipe Rotation	147
4.8	Cuttings Transport Performance with Pipe Rotation	152
4.8.1	Effect of Pipe Rotation Speed on CTP	152
4.8.2	Effect of Simulated Cuttings Size on CTP with Pipe Rotation	157
4.9	The Optimum of Polymer Beads Concentration	163
4.10	The Optimum of Pipe Rotation Speed	164
4.11	Chapter Summary	166
<b>CHAPTER 5</b>	<b>CONCLUSION AND RECOMMENDATIONS</b>	<b>167</b>
5.1	Research Conclusions	167
5.1.1	Cuttings Transport Flow Loop/Rig	167
5.1.2	Characterization, Fluid Flow Behavior (Rheological Model), Rheological Properties and Filtration Properties	168
5.1.3	Cuttings Transport Performance (CTP) at Various Wellbore Inclination Angles (0° to 90°) and Drill Pipe Rotation in Lifting Different Drilled Cuttings Sizes	169



5.2	Recommendations and Suggestions for Future Research	170
-----	---	-----

<b>REFERENCES</b>	<b>173</b>
-------------------	------------

## LIST OF TABLES

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Table 2.1	Degree of influencing parameters in hole cleaning (Sifferman and Becker, 1992)	31
Table 2.2	Summary of hole inclination versus hole angle	33
Table 2.3	Previous works on pipe rotation versus hole cleaning	37
Table 2.4	Works on ROP versus hole cleaning	41
Table 2.5	Previous studies on the effect of pipe eccentricity on hole cleaning	43
Table 2.6	Annular/Hole size versus hole cleaning performance	46
Table 2.7	Mud weight (mud density)	48
Table 2.8	The effect of mud type on cuttings removal performance	50
Table 2.9	Previous works on the effect of mud rheology on hole cleaning performance	53
Table 2.10	The effect of mud flow rate and annular velocity on cuttings transport	56
Table 2.11	The impact of cuttings characteristics on cuttings transport	62
Table 2.12	Comparison between previous works regarding the use of polymer beads for cuttings transport and the focus of this research	68
Table 3.1	Simulated cuttings size with aggregate name and coding	77
Table 3.2	The concentration of polymer beads and its weight added for both 350 ml of laboratory scale and 150 litres of drilling fluid prepared	81
Table 3.3	The drilling fluid formulation recommended by M-I SWACO based on one laboratory barrel (equivalent to 350 ml)	86
Table 3.4	Basic WBM rheological properties	86
Table 3.5	Mud formulation of WBM with five different concentrations of PP beads based on one laboratory barrel of mud sample (equivalent to 350 ml)	87

Table 3.6	Mud formulation of basic WBM and WBM with five different concentrations of PP beads based on 150 L of total mud volume	88
Table 3.7	Experimental equipment and its technical capacity	100
Table 3.8	Piping material specification	105
Table 3.9	Specification of a rotating motor	111
Table 3.10	Configuration parameters of ultrasonic flow meter	113
Table 3.11	Specification of plain weave wire mesh	115
Table 4.1	Fluid flow behaviour index for all drilling mud samples	127
Table 4.2	CTP improvement percentage for different hole angles and cuttings sizes between 2-ppb and 10-ppb mud	151

## LIST OF FIGURES

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 2.1	Viscosity profile of non-Newtonian fluid (Adewale <i>et al.</i> , 2017)	15
Figure 2.2	Forces acting on cuttings lying on the lower side of the wellbore (Luo and Bern, 1992)	22
Figure 2.3	Flow Pattern for cuttings transport in deviated holes (Luo and Bern, 1992; Skalle; 2012)	26
Figure 2.4	Major factors influencing hole cleaning and its controllability at the field (Adari <i>et al.</i> , 2000)	31
Figure 2.5	Helical or whirling motion with a rotating drill pipe (Hemphill, 2015)	36
Figure 2.6	Situation in the narrow side of an eccentric annulus: (a) No flow at the narrow gap with no pipe rotation, (b) pipe rotation helps the fluid flow in the narrow gap (Moroni <i>et al.</i> , 2009)	37
Figure 3.1	Experimental flowchart of cuttings transport using polymer beads in water-based mud	75
Figure 3.2	A TGA Q500 by TA Instruments, a research-grade thermogravimetric analyser	82
Figure 3.3	A FTIR spectrometer model IRTracer-100 by Shimadzu	83
Figure 3.4	Flowchart of mud sample preparation	85
Figure 3.5	IKA RW-20 Digital - Overhead stirrer	87
Figure 3.6	A conventional mud balance	89
Figure 3.7	Brookfield 8-speed rotating viscometer	90
Figure 3.8	A pH meter model CyberScan pH 510 from Eutech Instruments	92
Figure 3.9	API static filtration test: (a) API filter press, (b) mud cake thickness measurement using vernier calliper	93
Figure 3.10	A complete apparatus of FANN Series 387 (175 ml) HPHT filter press	94
Figure 3.11	Stainless steel pressure cells (aging cells)	94
Figure 3.12	A roller oven; can be in static or roll mode	95

Figure 3.13	A RST Coaxial Cylinder Rheometer with labelling components	96
Figure 3.14	An overview of cuttings transport flow loop	98
Figure 3.15	A schematic diagram of cuttings transport flow loop	99
Figure 3.16	A mud tank with capacity of 350 litres	101
Figure 3.17	A stirrer/agitator with four-blade propeller near to the bottom tank	102
Figure 3.18	A stirrer motor mounted on the tank and its close up	102
Figure 3.19	A slurry pump with three-phase induction motor of 15 hp (11 kW)	103
Figure 3.20	A Variable Speed Drive (VSD) for controlling pump frequency	104
Figure 3.21	Bypass section linking mud tank and mud pump including the valves	105
Figure 3.22	Flexible hose used to link the pump with annular test section	106
Figure 3.23	Annular test section	107
Figure 3.24	(a) First flange bearing, (b) Bearing set at rotation motor	113
Figure 3.25	(a) Entrance connection	108
Figure 3.25	(b) Exit connection	109
Figure 3.26	A protractor attached on an existing mast structure of the test section	109
Figure 3.27	Wellbore inclination angle system for various set angle: (a) vertical, (b) 30°, (c) 60°, (d) horizontal	110
Figure 3.28	A drill pipe rotary motor	111
Figure 3.29	Ultrasonic flow meter with clamp-on transducer	112
Figure 3.30	Cuttings feed hopper with control valves	114
Figure 3.31	A separation tank equipped with vibrator system	115
Figure 3.32	Third main valve for separation and returning process	117
Figure 3.33	The collected cuttings and polymer beads were washed and separated before evaluating cuttings recovery	118
Figure 3.34	Drying process on recovered cuttings using lab oven	119
Figure 4.1	Thermogravimetric curves for PP beads	124

Figure 4.2	FTIR spectra of polypropylene copolymer (PP beads)	125
Figure 4.3	Viscosity versus shear rate for different drilling fluid samples	127
Figure 4.4	Apparent viscosity of all drilling mud samples over different temperatures (at ambient and elevated temperatures)	131
Figure 4.5	Plastic viscosity of all drilling mud samples over different temperatures (at ambient and elevated temperatures)	132
Figure 4.6	Yield point of all drilling mud samples over different temperatures (at ambient and elevated temperatures)	134
Figure 4.7	Gel strength (10-seconds) of all drilling mud samples over different temperatures (at ambient and elevated temperatures)	136
Figure 4.8	Gel strength (10-minutes) of all drilling mud samples over different temperatures (at ambient and elevated temperatures)	136
Figure 4.9	pH value of all drilling mud samples over different temperatures (at ambient and elevated temperatures)	137
Figure 4.10	Filtrate loss volume for all drilling mud samples over different temperatures	138
Figure 4.11	Mud cake thickness for all mud samples over different temperatures (ambient and elevated temperatures)	139
Figure 4.12	CTP at various inclination angles without pipe rotation in transporting different cuttings sizes	143
Figure 4.13	The buoyancy force generated by PP beads at various hole angles	146
Figure 4.14	Impulsive force versus concentration of PP beads for different hole inclinations	146
Figure 4.15	Impulsive force for different concentration of PP beads versus hole inclination using Sand 1	147
Figure 4.16	CTP of different concentrations of polymer beads in water-based mud at various inclination angles	148
Figure 4.17	Average improvement percentage of CTP for different wellbore angles between 2-ppb and 10-ppb mud	151
Figure 4.18	Average improvement percentage of CTP for different cuttings sizes between 2-ppb and 10-ppb mud	151

Figure 4.19	CTP versus pipe rotation of different PP beads concentrations at various hole inclinations for Sand 1	153
Figure 4.20	CTP versus pipe rotation of different PP beads concentrations at various hole inclinations for Sand 2	155
Figure 4.21	CTP versus pipe rotation of different cutting sizes in different PP beads concentrations at 30° hole	158
Figure 4.22	CTP versus pipe rotation of different cutting sizes in different PP beads concentrations at 60° hole	161
Figure 4.23	The CTP for different cuttings sizes at a critical angle of 60° and pipe rotational speed of 150 rpm	164
Figure 4.24	The CTP of different wellbore angles at various pipe rotation speed for Sand 6 using 8-ppb mud	165

## LIST OF ABBREVIATIONS

API	-	American Petroleum Institute
AV	-	Apparent Viscosity
CCI	-	Cutting Carrying Index
CFD	-	Computational Fluid Dynamics
CFR	-	Minimum Cuttings Flow Rate
CTE	-	Cuttings Transport Efficiency
CTP	-	Cuttings Transport Performance
CTR	-	Cuttings Transport Ratio
ECD	-	Equivalent Circulating Density
FTIR	-	Fourier Transform Infrared Spectroscopy
GS	-	Gel Strength
HDPE	-	High-Density Polyethylene
HPHT	-	High Pressure High Temperature
ID	-	Internal Diameter
JDA	-	Joint Development Area
LDPE	-	Low-Density Polyethylene
MSDS	-	Material Safety Data Sheets
MTV	-	Minimum Transport Velocity
MW	-	Mud Weight (Mud Density)
NPS	-	Nominal Pipe Size
NPT	-	Non-Productive Time
OBM	-	Oil-Based Mud
OD	-	Outer Diameter
PE	-	Polyethylene
PP	-	Polypropylene Copolymer Beads
PV	-	Plastic Viscosity
PVC	-	Polyvinyl Chloride
ROP	-	Rate of Penetration
SWG	-	Standard Wire Gauge
TGA	-	Thermogravimetric Analysis



TI	-	Transport Index
VSD	-	Variable Speed Drive
WBM	-	Water-Based Mud
YP	-	Yield Point
YP/PV	-	Yield point to plastic viscosity ratio

## LIST OF SYMBOLS

$\theta_{300}$	-	300-rpm reading (rheometer)
$\theta_{600}$	-	600-rpm reading (rheometer)
$g$	-	Acceleration due to gravity
$a$	-	Acceleration of an object
$A_{an}$	-	Annular area
$v_{an}$	-	Annular velocity
$A$	-	Area
$v_{mean}$	-	Average maximum velocity
$F_b$	-	Buoyancy force
$K_c$	-	Casson plastic viscosity (Casson model constant)
$\tau_{yc}$	-	Casson yield stress
$\rho_c$	-	Cuttings density
$d_c$	-	Cuttings diameter
$^{\circ}$	-	Degree
$^{\circ}\text{C}$	-	Degree Celsius
$^{\circ}\text{F}$	-	Degree Fahrenheit
$\rho_p$	-	Density of polymer beads
$\emptyset$	-	Diameter
$d$	-	Diameter of PP beads
$\Delta v$	-	Difference between fluid velocity and polymer beads velocity
$C_D$	-	Drag coefficient
$F_D$	-	Drag force
$d_p$	-	Drill pipe diameter
$Q$	-	Flow rate
$\rho_f$	-	Fluid density
$n$	-	Fluid flow behaviour index
$F$	-	Force
$f_s$	-	Friction coefficient between cuttings and annular wall under “wet” condition

$F_f$	-	Frictional force
$F_g$	-	Gravitational force
$K$	-	Herschel-Buckley fluid consistency index
$\theta$	-	Hole angle
$d_h$	-	Hole diameter
$F_{imp}$	-	Impulsive force
$v_i$	-	Initial velocity
$S$	-	Length of test section
$C_L$	-	Lift coefficient
$F_L$	-	Lift force
$m_c$	-	Mass of cuttings
$m_p$	-	Mass of polymer bead
$v_{max}$	-	Maximum velocity
$F_{net}$	-	Net force
$v_t$	-	Net velocity
$N_{Re}$	-	Particle Reynolds number
$v_{sl}$	-	Particle settling velocity
$\mu_p$	-	Plastic viscosity
$KBr$	-	Potassium Bromide
$k$	-	Power Law consistency coefficient
$P$	-	Pressure gradient
$v_c$	-	Representative velocity of the fluid in the vicinity of the particles (Cuttings velocity)
$F_{ga}$	-	Resolved gravitational force parallel to hole axis
$F_{gva}$	-	Resolved gravitational force perpendicular to hole axis
$F_{axial}$	-	Resultant force in axial direction
$A$	-	Robertson-Stiff consistency index
$B$	-	Robertson-Stiff fluid flow behaviour index
$\gamma$	-	Shear rate
$C$	-	Shear rate correction factor
$\gamma_y$	-	Shear rate in Robertson-Stiff model
$\tau$	-	Shear stress
SG	-	Specific gravity

$t$	-	Time taken
$*$	-	Unknown value
$v_f$	-	Velocity final
$v_p$	-	Velocity of polymer bead
$\mu$	-	Viscosity
$V_p$	-	Volume of polymer beads
$W$	-	Weight
$\tau_y$	-	Yield point or yield stress

## LIST OF UNITS

<i>cP</i>	-	Centipoise (unit of viscosity)
<i>cm<sup>3</sup></i>	-	Cubic centimetre (volume unit)
<i>ft<sup>3</sup>/s</i>	-	Cubic feet per second (unit of flow rate)
<i>m<sup>3</sup>/s</i>	-	Cubic metre per second (unit of flow rate)
<i>ft/hr</i>	-	Feet per hour
<i>ft</i>	-	Foot
<i>ft/s</i>	-	Foot per second
<i>gpm</i>	-	Gallons per minute (unit of flow rate)
<i>g</i>	-	Gram
<i>hp</i>	-	Horsepower
<i>kg/m<sup>3</sup></i>	-	Kilogram per cubic metres (unit of density)
<i>kW</i>	-	Kilowatt (unit of power)
<i>l</i>	-	Litres
<i>m</i>	-	Metre
<i>m/hr</i>	-	Metre per hour
<i>m/s</i>	-	Metre per second (unit of velocity)
<i>m/s<sup>2</sup></i>	-	Metre per square seconds (unit of acceleration)
<i>ml</i>	-	Millilitres
<i>mm</i>	-	Millimetre
<i>mPa · s</i>	-	Millipascal-second
<i>N</i>	-	Newton
<i>N/m<sup>2</sup></i>	-	Newton per square metres
<i>Ns/m<sup>2</sup></i>	-	Newton-seconds per square metres
<i>ppb</i>	-	Parts per billion (unit of concentration)
<i>Pa</i>	-	Pascal
<i>Pa/m</i>	-	Pascal per metre
<i>Pa · s</i>	-	Pascal-second
<i>dynes/cm<sup>2</sup></i>	-	Poise
<i>lb/in<sup>3</sup></i>	-	Pound per cubic inch

<i>ppg</i>	-	Pound per gallon (unit of density)
<i>pcf</i>	-	Pound-force per cubic foot (unit of material density)
<i>psi</i>	-	Pound-force per square inch (unit of pressure)
lb/100 ft <sup>2</sup>	-	Pounds per hundred square feet
<i>cm</i> <sup>-1</sup>	-	Reciprocal centimetres (unit of wavenumber)
<i>sec</i> <sup>-1</sup>	-	Reciprocal seconds
<i>rpm</i>	-	Revolutions per minute
<i>s</i>	-	Seconds
<i>V</i>	-	Volt (unit of voltage)

## LIST OF APPENDICES

<b>APPENDIX</b>	<b>TITLE</b>	<b>PAGE</b>
Appendix A	Wellbore Cleaning Calculation	189
Appendix B	Rheological Properties of Drilling Fluids	199
Appendix C	CTP for Vertical Hole	202
Appendix D	CTP for 30° Hole	204
Appendix E	CTP for 45° Hole	206
Appendix F	CTP for 60° Hole	208
Appendix G	CTP for 75° Hole	210
Appendix H	CTP for Horizontal Hole	212
Appendix I	Flow Behaviour Calculation	214
Appendix J	Typical IR Spectra for Polypropylene	215
Appendix K	Recommended Rheological and Filtration Properties for WBM	216
Appendix L	CTP versus Pipe Rotation for Sand 3	217
Appendix M	CTP versus Pipe Rotation for Sand 4	219
Appendix N	CTP versus Pipe Rotation for Sand 5	221
Appendix O	CTP versus Pipe Rotation for Sand 6	223
Appendix P	CTP versus pipe rotation at vertical hole	225
Appendix Q	CTP versus pipe rotation at 45° hole	227
Appendix R	CTP versus pipe rotation at 75° hole	229
Appendix S	CTP versus pipe rotation at horizontal hole	231
Appendix T	Cuttings Transport Flow Loop Calculation	233
Appendix U	Calculation of CTP Improvement in Percentage	238

# CHAPTER 1

## INTRODUCTION

This preliminary chapter offers a quick overview of the whole thesis content. The chapter begins with a brief background on the advancement of new drilling technology, which has been taking place since the beginning of petroleum history, including designing new drilling fluids. As the petroleum exploration and production operations keep going, the directional drilling becomes a great pace to meet the market demands. However, many problems have been encountered, and one of the most significant challenges facing by the crews is wellbore cleaning, which becomes the main interest and ground to this research work. The following section described the problem to be investigated, the aims of the study to be achieved, and what works or tests that should be done and not to be done, which are described in the scope and limitation sections. The importance and the solution to the gap of literature on wellbore cleaning are delineated in the following section.

### 1.1 Background of Study

In the past decade, technology advancement is not all simply random evolutionary advances, yet represent a step-change in drilling technology. These technologies breakthrough have shifted the older cable-tool drilling to the rotary drilling techniques, which have been employed until now (Inglis, 2013). The rotary drilling techniques cannot produce a satisfactory cost-effective drilling operation alone but have to be complemented by other imperative components, and drilling fluid circulation is no exception to such contributions. Therefore, the circulation of drilling fluid becomes an integral part in optimizing a drilling operation (Adari *et al.*, 2000).

Among the numerous functions performed by drilling fluid, the most significant is its ability to transport drilled cuttings generated by a bit from the bottom



of the borehole, through the annulus space between the drill pipe and the wellbore's wall, up to the surface, which is referred to as the carrying capacity of the muds (Williams and Bruce, 1951). The term of carrying capacity is also called as cuttings lifting capacity (Samsuri and Hamzah, 2011). Failure to withdraw the unwanted cuttings out of the hole efficiently may lead to several expensive drilling problems, namely bit wear, wellbore enlargement, high torque and drag, poor cementing jobs, slow drilling rate, increased equivalent circulating density, lost circulation, and for the worst case, drill pipe sticking may occur (Adari *et al.*, 2000; Samsuri and Hamzah, 2011; Egenti, 2014). It may result in side-tracking or complete loss of the well. However, the most critical of these is the pipe sticking, as this problem requires a costly remedy (Adari *et al.*, 2000).

The increased demand for petroleum from time to time and coupled with the technology advancement has led to more exploration activities in remote and hostile areas as a part of enhanced recovery from reservoirs. Some of these targets can only be achieved via deviated or horizontal holes. Therefore, the directional drilling becomes more favourable to reach a pre-determined target in the earth's crust, which typically may not be accessed by vertical drilling, especially to thin and tight reservoirs (Inglis, 2013). When dealing with a near-vertical hole, some minor complications may occur, yet still controllable. Increase the fluid viscosity and flow rates would be the wise choice to improve the cuttings transport performance in near-vertical holes (Ozbayoglu *et al.*, 2008). However, the removal of drilled cuttings from a wellbore (later known as wellbore cleaning) during drilling highly inclined well has become one of the great challenges in the upstream industry ever since (Ozbayoglu *et al.*, 2008). Hence, the financial benefits become the most concerned among the numerous problems and dangers which surround the drilling process of highly inclined or horizontal holes (Kelin *et al.*, 2013).

These days, drill a directional hole becomes a routine process in all geographic areas around the world, including horizontal holes. On top of that, the economic benefits are firmly established in field practice. Nevertheless, the performance of cuttings transport is reduced with increasing wellbore inclination angle as higher cuttings concentration was discovered in the wellbore (Busahmin *et al.*, 2017). Good

hole cleaning demands higher capability of mud to suspend drilled cuttings with slower particle settling velocities, whereas it reversed for directional wells. Besides that, the formation of a cuttings bed becomes dominant as the wellbore inclination angle increases, especially for near-horizontal holes. They also addressed the particle dwell time in the annular space for such wells increased and caused the net volume of cuttings in the wellbore to escalate. Furthermore, several studies have reported that a very complex condition was encountered when drilling directionally, as accumulation of cuttings may result either in the form of stationary bed with hole angle above 50° or in a moving, churning bed with lower hole angles (Sifferman and Becker, 1992; Clark and Bickham, 1994).

Over the past decades, transportation of cuttings in vertical holes have been covered extensively by many researchers with the earliest investigation was delved by Pigott (1941), and continuing (William and Bruce, 1951; Sifferman *et al.*, 1973; Mohammadsalehi and Malekzadah, 2011). Typically, the efficiency of cuttings transportation in vertical holes is influenced by the settling velocity. This settling velocity is dependent on three significant components, namely, cuttings parameters (i.e., cuttings size, density and shape), drilling fluid parameters (i.e., rheology and velocity), and lastly, is operational features such as hole and pipe configurations (Chien, 1994). Studies of cuttings transportation in vertical holes have been well-documented, and not much problem has been recognized, and all are still controllable. Meanwhile, the concern is raised when dealing with directional drilling, especially highly deviated and horizontal holes, due to unexpected problems encountered (Becker and Azar, 1985; Tomren *et al.*, 1986; Okrajni and Azar, 1986). Even though enormous breakthrough and improvement were achieved on that particular drilling covering both experimental (Okrajni and Azar, 1986; Brown *et al.*, 1989; Sanchez *et al.*, 1999) and modelling (Larsen *et al.*, 1997; Hemphill and Ravi, 2010), but the ultimate solution is not yet to be found (Yu *et al.*, 2007).

## **1.2 Statement of Problem**

Removal of drilled cuttings out of the hole, which can be termed as a hole cleaning process is vital to ensure a smooth drilling operation. The circulation of

drilling fluid is expected to make a ‘downward and upward’ movement. This action may occasionally be true when drilling vertical wells, but it is seldom in the case of drilling high angle holes (Sifferman and Becker, 1992). Since high inclination holes may result in hole cleaning problems, however, it is mandated as the necessity to drill into inaccessible reservoirs, but to deflect the troublesome formations, side-tracking and horizontal drilling require some deviation angles from the vertical (Azar and Sanchez, 1997). Furthermore, the tendency of drilled cuttings accumulation and drop onto the low side of the hole is higher when the hole inclination angle increases. This phenomenon would worsen the torque and drag problems and consequently affect the drilled cuttings lifting efficiency. Therefore, the effect of the hole inclination angle on the effectiveness of cuttings transport is considered in this experimental investigation.

Furthermore, as a common, the production of fine solids becomes an unsurprised issue as drilling into soft and unconsolidated formations. It should be noticed that the fine solid particles generated may lead to poor hole cleaning as it is difficult to lift those particles out of the hole (Duan *et al.*, 2006). The problem worsens as the hole angle and the position of pipe in the hole, i.e., drill string eccentricity, are increasing. Naturally, gravity acceleration leads the drillstring to slide and land on the low side of the hole, where it produces a very low fluid velocity in the narrow gap below that string (Azar and Sanchez, 1997). As in turn, the accumulation of drilled cuttings, especially those of smaller size, will increase in the gap area (Peden *et al.*, 1990). The presence of wellbore pressure complements the formation of cuttings bed as compaction of cuttings takes place and more leads to the pipe sticking. Thus, the consideration to remove the bed erosion is highly appreciable as facilitated by pipe rotation. Sanchez *et al.* (1999) presented the influence of pipe rotation in cuttings bed erosion. The improvement of drilling performance can be attained by optimizing the use of pipe rotation. Therefore, pipe rotation is added as one of the parameters involved in this project to comprehend the effect of pipe rotation on cuttings transport efficiency.

This study was raised as a result of the need for accurate, precise, and realistic data to assist in designing the optimum conditions for drilling fluid used in directional drilling. Consequently, the development of a field-oriented cuttings transport model that accounts for the most important factors affecting particle and fluid dynamics in

directional holes is the main objective for this research. Besides that, this experimental investigation also involved the design and fabrication of a cuttings transport flow loop to simulate a drilling rig operation, in order to evaluate the effect of different parameters on hole cleaning while observing the mechanism of cuttings transport. Polypropylene random copolymer beads are added into a basic water-based mud system to improve the performance of cuttings lifting as a requirement of good hole cleaning. Polypropylene copolymer beads, which are lighter than the mud provides a buoyancy force, and the collision between the polymer beads and cuttings has induced an impulsive force, which can significantly improve the efficiency of cuttings transport to the surface.

### **1.3 Hypotheses of Study**

The hypotheses of this research works are as follows:

- (1) The presence of polypropylene copolymer beads possibly render a slight effect on the mud rheological properties due to its inert properties (chemically inactive), which is a good candidate to be used in the drilling mud, should one intended not to disrupt the mud properties immensely yet have another benefit such as in cutting lifting performance.
- (2) The presence of the polypropylene copolymer beads could improve cuttings lifting via buoyancy effect and collision between the cuttings and polymer beads enhance the impulsive force, which accelerates the cuttings upward to the surface.
- (3) Drill pipe rotation may plays an important role in improving cuttings lifting performance with polypropylene copolymer beads enriched in water-based mud as it creates a mechanical agitation to shook out the cuttings from bed and yields a whirling and orbital motion to the flowing mud, which accelerates cuttings way up to surface especially in inclined holes, and results in improvement of cuttings lifting.
- (4) Increase the drill pipe rotary speed beyond its optimum speed may lead to an insignificant contribution towards cuttings lifting performance.

- (5) A turbulent flow could be advantageous in transporting drilled cuttings in directional wells, especially those smaller in size.

#### **1.4 Objective of Study**

The main focus of this study is to evaluate the effect of using polypropylene copolymer beads as a means to ameliorate Cuttings Transport Performance (CTP), as well as understanding in-depth the influential parameters associated to the cuttings transport problem. Hence, in order to accomplish it, the following objectives have been set explicitly:

- (1) To characterize the rheological properties and flow behaviour of basic water-based mud with and without polypropylene copolymer beads.
- (2) To improve different sizes of drilled cuttings lifting using polypropylene copolymer beads enriched water-based mud with pipe rotation.

#### **1.5 Research Scope**

As measures to accomplish the research objectives, the scopes were set forth as follows:

- (1) The water-based mud was formulated according to the M-I SWACO industry specification and was prepared with a constant density of 10 ppg each.
- (2) The mud rheological properties and fluid loss of 10 ppg water-based mud with and without polypropylene copolymer beads were observed and evaluated.
- (3) A cuttings transport flow loop was designed, constructed and commissioned to simulate cuttings transport in an inclined and horizontal wellbore.
- (4) Simulated drilled cuttings were collected from Desaru beach, Johor, and their densities were measured using ASTM D4253-16, and a similar standard test method was applied for polypropylene copolymer beads.

- (5) The performances of polypropylene copolymer beads in water-based mud to transport drilled cuttings to the surface were analyzed based on the following research variables:
- a) Six different sand sizes (simulated cuttings), namely 0.5 – 1.0 mm, 1.0 – 1.4 mm, 1.4 – 1.7 mm, 1.7 – 2.0 mm, 2.0 – 2.8 mm, and 2.8 – 4.0 mm. The mass of simulated cuttings injected into the system was constant throughout the experiment, which was about 0.25% (by volume), approximately 993.75g.
  - b) Five different concentrations of polypropylene copolymer beads were added into water-based mud, i.e., 2 ppb, 4 ppb, 6 ppb, 8 ppb, and 10 ppb.
  - c) Six different hole inclination angles were used; vertical ( $0^\circ$ ), inclined (i.e.,  $30^\circ$ ,  $45^\circ$ ,  $60^\circ$ , and  $75^\circ$ ), and horizontal ( $90^\circ$ ).
  - d) Five drill pipe rotary speeds were employed, namely 0 rpm, 60 rpm, 90 rpm, 120 rpm, and 150 rpm.

## 1.6 Significance of the Study

High demand for oil and gas, from various industries around the world, has driven the petroleum companies to increase their exploration activities in order to elevate their hydrocarbon production. Thus, one of the approaches is by increasing the measured depths and horizontal displacements of the well to enhance their recovery of crude petroleum from remote and complex reservoirs. Besides that, the technology getting more advanced and sophisticated to ensure the growth of multilateral and high angle wells. However, those technologies still cannot overcome the hole cleaning problems, which become the primary concern of petroleum companies over the past decades until now (Mangor *et al.*, 2008; Egenti, 2014). Numerous novel methods (Li *et al.*, 1999; Mohammadsalehi and Malekzadah, 2011) have been studied to find the best solution to remediate this issue, yet those methods are still not efficient in hindering the occurrence of the problem.

This research investigation was conducted to understand the concept of the removal of drilled cuttings and lift them out of the hole in order to ensure a good hole cleaning in drilling practices. The use of polypropylene copolymer beads in water-based mud is considered because they provide buoyancy force and generate impulsive force due to their collision with drilled cuttings in the circulation fluid. In these conditions, the slip velocity of cuttings would reduce, and the formation of cuttings bed would mitigate significantly. Thereby, it could provide an alternative method to improve the efficiency of hole cleaning. Once the hole cleaning is improved, the rate of penetration (ROP) would increase, which subsequently reduces the Non-Productive Time (NPT) and cost during drilling operations. On that account, the companies' profit will increase, which contributes to the economic development of Malaysia.

## **1.7 Thesis Overview**

This dissertation embarks by outlining the broad view of drilling technology advancement concurrently with the increasing demands in petroleum production, which leads to the focus of the research issue – hole cleaning problem. The problem investigation, research's aim and scope of the study, and the reasons for conducting the research work and its importance are unambiguously stated. The overview, as well as the organizational structure of this thesis, are discussed in this section. The thesis comprises five chapters, and each of the chapters is organized as follows.

Chapter 2: Literature Review critically reviews relevant literature on issues pertaining to hole cleaning problems. A table summary of previous works on hole cleaning also embedded in this chapter. Parameters that affect the efficiency of hole cleaning and hole cleaning mechanism in different sections of the wellbore with varying hole inclinations are also discussed to give a tremendous intensive knowledge for the concerning issue. A concise summary is provided in the latter part of the chapter.

Chapter 3: Research Methodology explicates the strategies of research and techniques used in the study and their justification for investigating particular issues

highlighted in the literature review. It describes the data collection techniques, the data analysis framework and discusses the limitations of the research. The validation of these methods is crucial as it informs the reader how conclusions in this study have been arrived at.

Chapter 4: Results and Discussion part presents a factual reporting of the research results. These findings are organized around the objectives and within the scope and limitation of the research work. All the data collected are interpreted and analyzed thoroughly, which corresponds to the theory obtained in Chapter 2. A summary of the research findings is presented at the end of this chapter.

Chapter 5 summarizes the thesis with four key conclusions that can be drawn from the collective findings of preceding chapters and reflecting on the extent to which the objectives of the research work were achieved. Recommendations are presented, relying upon the findings and the analysis to help rectify the identified problem. The implications of the research findings are discussed and also include implications for practise as well as implications for future research directions, which can be approached with the tools and understanding developed in this thesis. Findings are incorporated with the theory employed in Chapter 1 and the body knowledge presented in Chapter 2.

## **1.8 Chapter Summary**

This chapter presents the overview of the whole thesis, which encompasses the background study, problem statement, hypotheses, objectives, scopes, the significance of the study, and lastly, the thesis overview. This study was conducted to offer an alternative approach by introducing the polypropylene copolymer beads into water-based mud to enhance the transportation of cuttings in the borehole. The problem of hole cleaning has arisen due to an increase in the wellbore inclination angles as more cuttings tend to settle at the lower side of the borehole. However, by injecting the polymer beads to the mud system, it is hoped to increase the buoyancy effect by counteracting the gravitational force imposed on the cuttings and also raising the



impulsive force of the cuttings by introducing more polymer beads to collide with the cuttings in the mud system. Previous studies have proved the effectiveness of using polymer beads in the water-based mud to ameliorate the hole cleaning performance, but none was done involving the rotary pipe. Therefore, this research was performed to fill the enigma of employing the pipe rotation to enhance cuttings transport performance.

## REFERENCES

- Adari, R.B., Miska, S., Kuru, E., Bern, P. and Saasen, A. (2000) Selecting Drilling Fluid Properties and Flow Rates for Effective Hole Cleaning in High-Angle and Horizontal Wells. *2000 SPE Annual Technical Conference and Exhibition*. 1-4 October. Dallas, Texas: SPE 63050, 1-9.
- Adewale, F.J., Lucky, A.P., Oluwabunmi, A.P. and Boluwaji, E.F. (2017) 'Selecting the Most Appropriate Model for Rheological Characterization of Synthetic Based Drilling Mud', *International Journal of Applied Engineering Research*, 12(18), 7614-7629.
- Aftab, A., Ismail, A.R. and Ibupoto, Z.H. (2017) 'Enhancing the rheological properties and shale inhibition behaviour of water-based mud using nanosilica, multi-walled carbon nanotube, and graphene nanoplatelet', *Egyptian Journal of petroleum*, 26(2), 291-299. doi: <http://dx.doi.org/10.1016/j.ejpe.2016.05.004>
- Ahmad, K.M., Turzo, Z. and Federer, G. (2018) 'An experimental study to investigate the influence of temperature and pressure on the rheological characteristics of "Glydril" water-based muds', *Journal of Oil, Gas and Petrochemical Sciences*, 1(2), 48-52.
- Akhshik, S., Behzad, M. and Rajabi, M. (2015) 'CFD–DEM approach to investigate the effect of drill pipe rotation on cuttings transport behaviour', *Journal of Petroleum Science and Engineering*, 127, 229-244.
- Alakbari, F., Elkatatny, S., Kamal, M.S. and Mahmoud, M. (2018) Optimizing the Gel Strength of Water-Based Drilling Fluid using Clays for Drilling Horizontal and Multi-Lateral Wells. *SPE Kingdom of Saudi Arabia Annual Technical Symposium and Exhibition*. 23-26 April. Dammam, Saudi Arabia: SPE-192191-MS, 1-16.
- Al-Haleem, A.A., Al-Razzaq, A., Dabbaj, A.A. and Hadi, F.M. (2016) 'Optimization of hole cleaning in Iraqi directional oil wells', *Journal of Engineering*, 22(7), 108-117.
- Al-Kayiem, H.H., Ismail, M.Z.A., Zaki, N.M. and Elfeel, M.E. (2010) 'Simulation of the cuttings cleaning during the drilling operation', *American Journal of Applied Sciences*, 7(6), 800-806.

- Amani, M., Al-Jubouri, M. and Shadravan, A. (2012) 'Comparative study of using oil-based mud versus water-based mud in HPHT fields', *Advances in Petroleum Exploration and Development*, 4(2), 18-27.
- Anawe, P.A.L. and Adewale F.J. (2018a) 'Data analyses on temperature-dependent behaviour of water-based drilling fluid rheological models', *Data in Brief*, 21, 289-298. doi: <http://dx.doi.org/10.1016/j.dib.2018.09.100>
- Anawe, P.A.L. and Adewale, F.J. (2018b) 'Modification of Bingham plastic rheological model for better rheological characterization of synthetic based drilling mud', *Journal of Engineering and Applied Sciences*, 13(10), 3573-3581.
- Arslan, E., Yener, M.E. and Esin, A. (2005) 'Rheological characterization of tahin/pekmez (sesame paste/concentrated grape juice) blends', *Journal of Food Engineering*, 69(2), 167-172.
- Avila, R.J., Pereira, E.J., Miska, S.Z. and Takach, N.E. (2008) 'Correlations and analysis of cuttings transport with aerated fluids in deviated wells', *SPE Drilling & Completion*, 23(02), 132-141. SPE 87180.
- Azar, J.J. and Sanchez, R.A. (1997) Important Issues in Cuttings Transport for Drilling Directional Wells. *Fifth Latin American and Caribbean Petroleum Engineering Conference and Exhibition*. 30 August-3 September. Rio de Janeiro, Brazil: SPE 39020, 1-4.
- Azar, J.J., and Samuel, G.R. (2007) *Drilling Engineering*. Tulsa, Oklahoma, USA: PennWell Corporation. ISBN 1-59370-072-5.
- Bahrainian, S.S., Nabati, A. and Hajidavalloo, E. (2018) 'Improved rheological model of oil-based drilling fluid for South-Western Iranian oilfields', *Journal of Petroleum Science and Technology*, 8(3), 53-71.
- Becker, T.E. and Azar, J.J. (1985) 'Mud-weight and hole-geometry effects on cuttings transport while drilling directionally', *SPE Journal of Society of Petroleum Engineers*. Richardson, Texas, USA: SPE 14711, 1-34.
- Becker, T.E., Azar, J.J. and Okrajni, S.S. (1991) 'Correlations of mud rheological properties with cuttings-transport performance in directional drilling', *SPE Drilling Engineering*, 6(01), 16-24. SPE 19535.
- Bilgesu, H.I., Mishra, N. and Ameri, S. (2007) Understanding the Effects of Drilling Parameters on Hole Cleaning in Horizontal and Deviated Wellbores Using

- Computational Fluid Dynamics. *2007 SPE Eastern Regional Meeting*. 17-19 October. Lexington, Kentucky, USA: SPE 111208, 1-7.
- Bizhani, M. and Kuru, E. (2018a) 'Critical review of mechanistic and empirical (semimechanistic) models for particle removal from sandbed deposits in horizontal annuli with water', *Society of Petroleum Engineers Journal*, 23(02), 237-255. SPE 187948.
- Bizhani, M. and Kuru, E. (2018b) 'Assessment of the equivalent sandbed roughness and the interfacial friction factor in hole cleaning with water in a fully eccentric horizontal annulus', *Society of Petroleum Engineers Journal*, 23(05), 1748-1767. SPE 191133.
- Bizhani, M., Rodriguez Corredor, F.E. and Kuru, E. (2016) 'Quantitative evaluation of critical conditions required for effective hole cleaning in coiled-tubing drilling of horizontal wells', *SPE Drilling & Completion*, 31(03), 188-199. SPE 174404.
- Boyoun, N.V., Ismail, I., Hamzah, M.H. and Uche, O.M.D. (2018) 'Polypropylene beads in water-based mud for cuttings transportation improvement', *Chemical Engineering Transactions*, 63, 787-792.
- Boyoun, N.V., Ismail, I., Sulaiman, W.R.W., Haddad, A.S., Husein, N., Hui, H.T. and Nadaraja, K. (2019) 'Experimental investigation of hole cleaning in directional drilling by using nano-enhanced water-based drilling fluids', *Journal of Petroleum Science and Engineering*, 176, 220-231.
- Brown, N.P., Bern, P.A. and Weaver, A. (1989) *Cleaning Deviated Holes: New Experimental and Theoretical Studies. 1989 SPE/IADC Drilling Conference*. 28 February-3 March. New Orleans, Louisiana: SPE 18636, 171-180.
- Bui, B.T. and Tutuncu, A.N. (2016) 'A generalized rheological model for drilling fluids with cubic splines', *SPE Drilling & Completion*, 31(01), 26-39. SPE 169527.
- Busahmin, B., Saeid, N.H., Alusta, G. and Zahran, E.S.M.M. (2017b) 'Review on hole cleaning for horizontal wells', *ARPN Journal of Engineering and Applied Sciences*, 12(16), 4697-4708. ISSN 1819-6608.
- Busahmin, B., Saeid, N.H., Hasan, U.H.B.H. and Alusta, G. (2017a) 'Analysis of hole cleaning for a vertical well', *Open Access Library Journal*, 4(5), 1-10.

- Caenn, R., Darley, H.C.H., and Gray, G.R. (2017) *Composition and properties of drilling and completion fluids*. 7<sup>th</sup> edn. Oxford, UK: Gulf Professional Publishing. ISBN 978-0-12-804751-4
- Chenevert, M.E. and Dewan, J.T. (2001) 'A model for filtration of water-base mud during drilling: determination of mudcake parameters', *Petrophysics*, 42(03), 237-250.
- Chien, S.F. (1994) 'Settling velocity of irregularly shaped particles', *SPE Drilling & Completion*, 9(04), 281-289. SPE 26121.
- Cho, H., Shah, S.N. and Osisanya, S.O. (2001) Effects of fluid flow in a porous cuttings-bed on cuttings transport efficiency and hydraulics. *2001 SPE Annual Technical Conference and Exhibition*. 30 September-3 October. New Orleans, Louisiana: SPE 71374, 1-14.
- Cho, H., Subhash, N.S. and Samuel, O.O. (2000) A Three-Segment Hydraulic Model for Cuttings Transport in Horizontal and Deviated Wells. *2000 SPE/Petroleum Society of CIM International Conference on Horizontal Well Technology*. 6-8 November. Calgary, Alberta, Canada: SPE/Petroleum Society of CIM 65488, 1-16.
- Clark, R.K. and Bickham, K.L. (1994) A Mechanistic Model for Cuttings Transport. *SPE 69<sup>th</sup> Annual Technical Conference and Exhibition*. 25-28 September. New Orleans, LA, USA: SPE 28306, 139-153.
- Costa, S.S., Stuckenbruck, S., Da Fontoura, S.A.B. and Martins, A.L. (2008) Simulation of Transient Cuttings Transportation and ECD in Wellbore Drilling. *2008 SPE Europec/EAGE Annual Conference and Exhibition*. 9-12 June. Rome, Italy: SPE 113893, 1-6.
- Dai, C. and Zhao, F. (2018) *Drilling Fluid Chemistry*. In *Oilfield Chemistry*. Qingdao, Shandong, China: China University of Petroleum Press, 21-84.
- Duan, M., Miska, S., Yu, M., Takach, N., Ahmed, R. and Zettner, C. (2008) 'Transport of small cuttings in extended reach drilling', *SPE Drilling & Completion Journal*, 23(03), 258-265. SPE 104192.
- Duan, M., Miska, S., Yu, M., Takach, N.E., Ahmed, R.M. and Hallman, J.H. (2010) 'Experimental study and modeling of cuttings transport using foam with drillpipe rotation', *SPE Drilling & Completion*, 25(03), 352-362. SPE 116300.

- Egenti, N.B. (2014) Understanding Drill-Cuttings Transportation in Deviated and Horizontal Wells. *SPE Nigeria Annual International Conference and Exhibition*. 5-7 August. Lagos, Nigeria: SPE 172835, 1-13.
- Epelle, E.I. and Gerogiorgis, D.I. (2018) ‘CFD modelling and simulation of drill cuttings transport efficiency in annular bends: Effect of particle sphericity’, *Journal of Petroleum Science and Engineering*, 170, 992-1004.
- Færgestad, I.M. (2016) Rheology. *Oilfield Review – The Defining Series*. Cambridge, England: Schlumberger. Available at: [www.slb.com/defining](http://www.slb.com/defining)
- Gao, E. and Young, A.C. (1995) Hole Cleaning in Extended Reach Wells-Field Experience and Theoretical Analysis Using a Pseudo-Oil (Acetal) Based Mud. *1995 SPE/IADC Drilling Conference*. 28 February-2 March. Amsterdam, Netherlands: SPE/IADC 29425, 793-808.
- Gbadamosi, A.O., Junin, R., Abdalla, Y., Agi, A. and Oseh, J.O. (2019) ‘Experimental investigation of the effects of silica nanoparticle on hole cleaning efficiency of water-based drilling mud’, *Journal of Petroleum Science and Engineering*, 172, 1226-1234.
- Ghassem, A. and Nickdel, T. (2007) ‘Effects of salinity, PH and temperature on CMC polymer and XC polymer performance’, *International Journal of Engineering. Transactions B: Applications*, 20(3), 283-290.
- Goud, M. (2017) *Mud engineering simplified*. India: Becomesakespeare.com.
- Guan, Z.C., Liu, Y.M., Liu, Y.W. and Xu, Y.Q. (2016) ‘Hole cleaning optimization of horizontal wells with the multi-dimensional ant colony algorithm’, *Journal of Natural Gas Science and Engineering*, 28, 347-355.
- Hakim, H., Katende, A., Sagala, F., Ismail, I. and Nsamba, H. (2018) ‘Performance of polyethylene and polypropylene beads towards drill cuttings transportation in horizontal wellbore’, *Journal of Petroleum Science and Engineering*, 165, 962-969. doi: <https://doi.org/10.1016/j.petrol.2018.01.075>
- Hamid, N.A.A. (2019) Personal Communication – *Email*, 10 June 2019.
- Hareland, G., Azar, J.J. and Rampersad, P.R. (1993) Comparison of cuttings transport in directional drilling using low-toxicity invert emulsion mineral-oil-based and water-based muds. *Low Permeability Reservoirs Symposium*. 12-14 April. Denver, Colorado, USA: SPE 25871, 323-330.
- Harry, T.F., Ademiluyi, F.T., Joel, O.F. and Oduola, K. (2017) ‘Rheological model parameters for bentonite drilling mud treated with local cassava starch’, *Asian*

- Research Publishing Network (ARPN) Journal of Engineering and Applied Sciences*, 12(02), 609-619.
- Hemphill, T. (2015) Advances in the Calculation of Circulating Pressure Drop with and without Drillpipe Rotation. *SPE/IADC Drilling Conference and Exhibition*. 17-19 March. London, United Kingdom: SPE/IADC 173054, 1-11.
- Hemphill, T. and Ravi, K. (2006) Pipe Rotation and Hole Cleaning in Eccentric Annulus. *IADC/SPE Drilling Conference*. 21-23 February. Miami, Florida, USA: IADC/SPE 99150, 1-5.
- Hemphill, T. and Ravi, K. (2010) Modeling the Effect of Drill Pipe Rotation Speed on Wellbore Cleanout. *IADC/SPE Asia Pacific Drilling Technology Conference and Exhibition*. 1-3 November 2010. Ho Chi Minh City, Vietnam: IADC/SPE 135703, 1-5.
- Hemphill, T., Campos, W. and Pilehvari, A. (1993) ‘Yield-Power law model more accurately predicts mud rheology’, *Oil and Gas Journal*, 91(34), 45-50.
- Herzhaft, B., Peysson, Y., Isambourg, P., Delepoulle, A. and Abdoulaye, T. (2001) Rheological properties of drilling muds in deep offshore conditions. *SPE/IADC Drilling Conference*. 27 February-1 March. Amsterdam, The Netherlands: SPE/IADC 67736, 344-350.
- Heydari, O., Sahraei, E. and Skalle, P. (2017) ‘Investigating the impact of drillpipe's rotation and eccentricity on cuttings transport phenomenon in various horizontal annuluses using computational fluid dynamics (CFD)’, *Journal of Petroleum Science and Engineering*, 156, 801-813. doi: <http://dx.doi.org/10.1016/j.petrol.2017.06.059>
- Higgins, F. (2012) *Determination of percent polyethylene in polyethylene/polypropylene blends using cast film FTIR techniques*. Danbury, Connecticut, USA: Agilent Technologies.
- Hopkin, E.A. (1967) ‘Factors affecting cuttings removal during rotary drilling’, *Journal of Petroleum Technology*, 19(06), 807-814. SPE 1697.
- Hussaini, S.M. and Azar, J.J. (1983) ‘Experimental study of drilled cuttings transport using common drilling muds’, *Society of Petroleum Engineers Journal*, 23(01), 11-20. SPE 10674.
- Igwilo, K.C., Ikoru, G., Okoli, N., Osueke, G.O., Odu, J. and Anawe, P.A.L. (2017) ‘Modeling the effects of temperature on oil base mud viscosity using

- polynomial equation', *International Journal of Petroleum and Petrochemical Engineering*, 3(2), 16-22.
- Inglis, T. (2013) *Directional drilling*. 2<sup>nd</sup> edn. The Netherlands: Springer Science & Business Media. doi: <https://doi.org/10.1007/978-94-017-1270-5>
- Irawan, S., Kinif, I. and Bayuaji, R. (2018) 'Maximizing Drilling Performance through Enhanced Solid Control System', *Platform: A Journal of Engineering*, 1(1), 66-82.
- Ismail, A.R., Hassan, Z. and Moherei, M.A.M. (2002) Drilling Fluids and Wellbore Cleaning Technology. *Proceedings of Regional Symposium of Chemical Engineering*. 28-30 October. Petaling Jaya, Malaysia, 239-246. ISBN 983-41147-0-2.
- Ismail, I., Onuoha, M.D.U., Ismail, A.R., Piroozian, A., Sulaimon, W.R.W. and Abba, S.M. (2017) 'Improving drilled cuttings lifting using polypropylene beads in water-based mud at different annular mud velocities', *International Journal of Engineering and Technology*, 9(4), 1-10.
- Iyoho, A.W., Horeth, J.M. and Veenkant, R.L. (1988) 'A computer model for hole-cleaning analysis', *Journal of Petroleum Technology*, 40(09), 1-183.
- Jordi, M. (2014) *FTIR for Identification of Contamination*. Mansfield, Massachusetts, USA: Jordi Labs LLC.
- Jung, M.R., Horgen, F.D., Orski, S.V., Rodriguez, V., Beers, K.L., Balazs, G.H., Jones, T.T., Work, T.M., Brignac, K.C., Royer, S.J. and Hyrenbach, K.D. (2018) 'Validation of ATR FT-IR to identify polymers of plastic marine debris, including those ingested by marine organisms', *Marine pollution bulletin*, 127, 704-716.
- Kelessidis, V.C. and Bandelis, G.E. (2004) 'Flow patterns and minimum suspension velocity for efficient cuttings transport in horizontal and deviated wells in coiled-tubing drilling', *SPE Drilling & Completion*, 19(04), 213-227. SPE 81746
- Kelessidis, V.C., Bandelis, G.E. and Li, J. (2007) 'Flow of dilute solid-liquid mixtures in horizontal concentric and eccentric annuli', *Journal of Canadian Petroleum Technology*, 46(5), 56-61.
- Kelin, W., Tie, Y., Xiaofeng, S., Shuai, S. and Shizhu, L. (2013) 'Review and analysis of cuttings transport in complex structural wells', *The Open Fuels & Energy Science Journal*, 6(1), 9-17.



- Khataniar, S., Chukwu, G. A. and Xu, H. (1994) 'Evaluation of rheological models and application to flow regime determination', *Journal of Petroleum Science and Engineering*, 11(2), 155-164.
- Kudaikulova, G. (2015) 'Rheology of drilling muds', *Journal of Physics: Conference Series*, 602(1), 1-5. doi: <https://doi.org/10.1088/1742-6596/602/1/012008>
- Larsen, T.I., Pilehvari, A.A. and Azar, J.J. (1997) 'Development of a new cuttings-transport model for high-angle wellbores including horizontal wells', *SPE Drilling & Completion*, 12(02), 129-136. SPE 25872.
- Lavrov, A. (2016) *Lost circulation: mechanisms and solutions*. Oxford, UK: Gulf Professional Publishing. ISBN 978-0-12-803916-8.
- Li, J. and Walker, S. (2001) 'Sensitivity analysis of hole cleaning parameters in directional wells', *SPE Journal*, 6(04), 356-363. SPE 74710.
- Lockett, T.J., Richardson, S.M. and Worraker, W.J. (1993) The Importance of Rotation Effects for Efficient Cuttings Removal During Drilling. *1993 SPE/IADC Drilling Conference*. 23-25 February. Amsterdam: SPE/IADC 25768, 861-869.
- Luo, Y. and Bern, P.A. (1992) Flow-Rate Predictions for Cleaning Deviated Wells. *1992 IADC/SPE Drilling Conference*. 18-21 February. New Orleans, Louisiana: IADC/SPE 23884, 367-376.
- Lyons, W.C., Plisga, G.J. and Lorenz, M.D. (2016) *Standard Handbook of Petroleum and Natural Gas Engineering*. 3<sup>rd</sup> edn. Oxford, UK: Gulf Professional Publishing. ISBN 978-0-12-383846-9.
- Maglione, R., Robotti, G. and Romagnoli, R. (2000) 'In-situ rheological characterization of drilling mud', *SPE Journal*, 5(04), 377-386. SPE 66285.
- Makinde, F.A., Adejum, A.D., Ako, C.T. and Efeovbokhan, V.E. (2011) 'Modelling the effects of temperature and aging time on the rheological properties of drilling fluids', *Petroleum & Coal*, 53(3), 167-182.
- Mamaril, F. (2016) Personal Communication – *Email*, 5 May 2016.
- Mamat, N.S., Ismail, I., Hashim, S., Kamis, A. and Razak, A.H.A. (2013) 'The performance of polymer beads in water-based mud and its application in high-temperature well', *Journal of Petroleum Exploration and Production Technology*, 3(3), 151-158.
- Mangesana, N., Chikuku, R.S., Mainza, A.N., Govender, I., Van der Westhuizen, A.P. and Narashima, M. (2008) 'The effect of particle sizes and solids concentration

- on the rheology of silica sand based suspensions', *Journal of the Southern African Institute of Mining and Metallurgy*, 108(4), 237-243.
- Mangor, H., Elder, R., Boulet, J. and Monnet, A. (2008) 'Maximizing drilling efficiency in Bunga-Kekwa's high-angle wells', *World Oil*, 229, 55-60.
- Martin, M., Georges, C., Bisson, P. and Konirsch, O. (1987) Transport of cuttings in directional wells. *1987 SPE/IADC Drilling Conference*. 15-18 March. New Orleans, LA: SPE/IADC 16083, 293-303.
- Martins, A.L., Sa, C.H.M., Lourenco, A.M.F. and Campos, W. (1996) Optimizing Cuttings Circulation in Horizontal Well Drilling. *International Petroleum Conference and Exhibition of Mexico*. 5-7 March. Villahermosa, Mexico: SPE 35341, 295-304.
- Mellot, J.W.C. (2006) Technological Improvements in Wells Drilled Utilizing a Pneumatic Fluid as the Primary Circulating Medium. *IADC/SPE Drilling Conference*. 21-23 February. Miami, Florida, USA: SPE 99162, 1-7.
- Miller, A., Minton, R.C., Colquhoun, R.L. and Ketchion, M. (2011) The Continuous Measurement and Recording of Drilling Fluid Density and Viscosity. *SPE/IADC Drilling Conference and Exhibition*. 1-3 March. Amsterdam, The Netherlands: SPE 140324, 1-4.
- Miyazawa, T. (1964) 'Infrared spectra and chemical structure of polypropylene', *Journal of Polymer Science Part B: Polymer Letters*, 2(9), 847-850.
- Mohammadsalehi, M. and Malekzadah, N. (2011) Application of New Hole Cleaning Optimization Method within All Ranges of Hole Inclinations. *International Petroleum Technology Conference*. 7-9 February 2012. Bangkok, Thailand: IPTC 14154, 1-8.
- Moraveji, M.K., Sabah, M., Shahryari, A. and Ghaffarkhah, A. (2017) 'Investigation of drill pipe rotation effect on cutting transport with aerated mud using CFD approach', *Advanced Powder Technology*, 28(4), 1141-1153.
- Moroni, N., Ravi, K., Hemphill, T. and Sairam, P. (2009) Pipe rotation improves hole cleaning and cement-slurry placement: Mathematical modeling and field validation. *2009 SPE Offshore Europe Oil and Gas Conference & Exhibition*. 8-11 September. Aberdeen, UK: SPE 124726, 1-11.

- Muherei, M.A. and Basaleh, S.S. (2016) 'True power law drilling fluid model: effect of its rheological parameters on static particle settling velocity', *International Research Journal of Engineering and Technology (IRJET)*, 03(01), 77-88.
- Muherei, M.A., Basaleh, S.S. and Bamaga, M.A. (2015) 'Hole cleaning in horizontal and highly deviated wellbores drilled with coiled tubing: Drillpipe rotation drawback is it significant?', *International Research Journal of Engineering and Technology (IRJET)*, 02(09), 2280-2286.
- Naganawa, S. and Nomura, T. (2006) Simulating Transient Behaviour of Cuttings Transport Over Whole Trajectory of Extended-Reach Well. *IADC/SPE Asia Pacific Drilling Technology Conference and Exhibition*. 13-15 November. Bangkok, Thailand: IADC/SPE 103923, 1-9.
- Naganawa, S., Oikawa, A., Masuda, Y., Tetsuo, Y., Hoshino, M. and Acuna, P. (2002) Cuttings Transport in Directional and Horizontal Wells While Aerated Mud Drilling. *IADC/SPE Asia Pacific Drilling Technology*. 8-11 September. Jakarta, Indonesia: SPE 77195, 1-8.
- Nance, W.B., Muncy, D.D., Garrett, M.M., Gault, A.D. and Kortlang Jr, W.F. (1983) A Comparative Analysis of Drilling Results Obtained with Oil Mud Vs. Water-Base Mud at High Island Block A-270. *IADC/SPE Drilling Conference*. 20-23 February. New Orleans, Louisiana: SPE 11357, 27-30.
- Nazari, T., Hareland, G. and Azar, J.J. (2010) Review of Cuttings Transport in Directional Well Drilling: Systematic Approach. *SPE Western Regional Meeting*. 27-29 May. Anaheim, California, USA: SPE 132372, 1-15.
- Nazir, F. (2010) *The Performance of Polymer and Glass Beads in Water-based Mud as a Lubricating Agent*. PhD Thesis, Universiti Teknologi Malaysia, Skudai.
- Nguyen, D. and Rahman, S.S. (1998) 'A three-layer hydraulic program for effective cuttings transport and hole cleaning in highly deviated and horizontal wells', *SPE Drilling & Completion*, 13(03), 182-189. SPE 51186.
- O'Brien, T.B. and Dobson, M. (1985) Hole Cleaning: Some Field Results. *SPE/IADC Drilling Conference*. 6-8 March. New Orleans, Louisiana: SPE 13442, 183-187.
- Ofei, T.N. (2016) 'Effect of yield power law fluid rheological properties on cuttings transport in eccentric horizontal narrow annulus', *Journal of Fluids*, 2016, 1-10. doi: <http://dx.doi.org/10.1155/2016/4931426>.

- Ofesi, S.F., Onwukwe, S.I. and Duru, U.I. (2017) ‘Optimizing hole cleaning using low viscosity drilling fluid’, *Advances in Petroleum Exploration and Development*, 14(1), 55-61. doi: <https://doi.org/10.3968/9658>.
- Ogunrinde, J.O. and Dosunmu, A. (2012) Hydraulics Optimization for Efficient Hole Cleaning in Deviated and Horizontal Wells. *2012 SPE Nigerian Annual International Conference and Exhibition*. 6-8 August. Abuja, Nigeria: SPE 162970, 1-16.
- Okrajni, S. and Azar, J.J. (1986) ‘The effects of mud rheology on annular hole cleaning in directional wells’, *SPE Drilling Engineering*, 1(04), 297-308. SPE 14178.
- Onuoha, M.D.U., Ismail, I., Piroozian, A., Mamat, N.S. and Ismail, A.S. (2015) ‘Improving the cuttings transport performance of water-based mud through the use of polypropylene beads’, *Sains Malaysiana*, 44(4), 629-634.
- Osman, M.N. and Maung, M. (1983) Development Drilling Problems Offshore Malaysia. *Southeast Asia Show*. 21-24 February. Singapore: SPE 12437, 40-56.
- Ozbayoglu, M.E., Miska, S.Z., Reed, T. and Takach, N. (2004) Analysis of the effects of major drilling parameters on cuttings transport efficiency for high-angle wells in coiled tubing drilling operations. *SPE/ICoTa Coiled Tubing Conference and Exhibition*. 23-24 March. Houston, Texas, USA: SPE 89334, 1-8.
- Ozbayoglu, M.E., Saasen, A., Sorgun, M. and Svanes, K. (2008) Effect of Pipe Rotation on Hole Cleaning for Water-Based Drilling Fluids in Horizontal and Deviated Wells. *IADC/SPE Asia Pacific Drilling Technology Conference and Exhibition*. 25-27 August. Jakarta, Indonesia: SPE 114965, 1-11.
- Pagès, P. (2005) ‘Characterization of polymer materials using FT-IR and DSC techniques’, *Thermal analysis: Fundamentals and applications to material characterization*, 1, 121-140.
- Pang, B., Wang, S., Jiang, X. and Lu, H. (2019b) ‘Effect of orbital motion of drill pipe on the transport of non-Newtonian fluid-cuttings mixture in horizontal drilling annulus’, *Journal of Petroleum Science and Engineering*, 174, 201-215.
- Pang, B., Wang, S., Lu, C., Cai, W., Jiang, X. and Lu, H. (2019a) ‘Investigation of cuttings transport in directional and horizontal drilling wellbores injected with pulsed drilling fluid using CFD approach’, *Tunnelling and Underground Space Technology*, 90, 183-193.

- Papageorgiou, D.G., Bikiaris, D.N. and Chrissafis, K. (2012) 'Effect of crystalline structure of polypropylene random copolymers on mechanical properties and thermal degradation kinetics', *Thermochimica acta*, 543, 288-294.
- Peden, J.M., Ford, J.T. and Oyenehin, M.B. (1990) Comprehensive Experimental Investigation of Drilled Cuttings Transport in Inclined Wells Including the Effects of Rotation and Eccentricity. *Europec '90*. 22-24 October. The Hague, Netherlands: SPE 20925, 393-404.
- Philip, Z., Sharma, M.M. and Chenevert, M.E. (1998) The role of Taylor vortices in the transport of Drill Cuttings. *1998 SPE India Oil and Gas Conference and Exhibition*. 7-9 April. New Delhi, India: SPE 39504, 1-7.
- Pigott, R.J.S. (1941) 'Mud flow in drilling', *Production bulletin*, 226, 26-31.
- Piroozian, A., Ismail, I., Yaacob, Z., Babakhani, P. and Ismail, A.S.I. (2012) 'Impact of drilling fluid viscosity, velocity and hole inclination on cuttings transport in horizontal and highly deviated wells', *Journal of Petroleum Exploration and Production Technology*, 2(3), 149-156.
- Ramadan, A., Skalle, P. and Johansen, S.T. (2003) 'A mechanistic model to determine the critical flow velocity required to initiate the movement of spherical bed particles in inclined channels', *Chemical Engineering Science*, 58(10), 2153-2163.
- Ramsey, M.S. (2019) *Practical wellbore hydraulics and hole cleaning*. Oxford, UK: Gulf Professional Publishing. ISBN 978-0-12-817088-5.
- Robertson, R.E. and Stiff Jr, H.A. (1976) 'An improved mathematical model for relating shear stress to shear rate in drilling fluids and cement slurries', *Society of Petroleum Engineers Journal*, 16(01), 31-36. SPE 5333.
- Rooki, R., Ardejani, F.D., Moradzadeh, A., Mirzaei, H., Kelessidis, V., Maglione, R. and Norouzi, M. (2012) 'Optimal determination of rheological parameters for herschel-bulkley drilling fluids using genetic algorithms (GAs)', *Korea-Australia Rheology Journal*, 24(3), 163-170.
- Saasen, A. (1998) Hole cleaning during deviated drilling-The effects of pump rate and rheology. *1998 SPE European Petroleum Conference*. 20-22 October. The Hague, The Netherlands: SPE 50582, 161-167.
- Saasen, A. and Løklingholm, G. (2002) The effect of drilling fluid rheological properties on hole cleaning. *IADC/SPE Drilling Conference*. 26-28 February. Dallas, Texas: SPE 74558, 1-5.

- Samsuri, A. and Hamzah, A. (2011) 'Water based mud lifting capacity improvement by multiwall carbon nanotubes additive', *Journal of Petroleum and Gas Engineering*, 5(2), 99-107.
- Sanchez, R.A., Azar, J.J., Bassal, A.A. and Martins, A.L. (1999) 'Effect of drillpipe rotation on hole cleaning during directional-well drilling', *SPE Journal*, 4(02), 101-108. SPE 56406.
- Sarah, A.A. and Isehunwa, S.O. (2015) Temperature and time-dependent behaviour of a water base mud treated with maize (*Zea mays*) and Cassava (*Manihot esculanta*) Starches', *Journal of Scientific Research and Reports*, 5(7), 591-597. doi: <https://doi.org/10.9734/JSRR/2015/14870>.
- Sarker, M., Rashid, M.M. and Molla, M. (2012) 'Waste polypropylene plastic conversion into liquid hydrocarbon fuel for producing electricity and energies', *Environmental technology*, 33(24), 2709-2721.
- Sayindla, S., Lund, B., Ytrehus, J.D. and Saasen, A. (2017) 'Hole-cleaning performance comparison of oil-based and water-based drilling fluids', *Journal of Petroleum Science and Engineering*, 159, 49-57.
- Seeberger, M.H., Matlock, R.W. and Hanson, P.M. (1989) Oil Muds in Large-Diameter, Highly Deviated Wells: Solving the Cuttings Removal Problem. 1989 SPE/IADC Drilling Conference. 28 February-3 March. New Orleans, Louisiana: SPE/IADC 18635, 161-178.
- Selamat, S.B., Teletzke, G.F., Patel, P.D., Darman, N.B. and Shuhaimi, M.A. (2008) EOR: The new frontier in the Malay basin development. *International Petroleum Technology Conference*. 3-5 December. Kuala Lumpur, Malaysia: IPTC 12805, 1-15.
- Sifferman, T.R. and Becker, T.E. (1992) 'Hole cleaning in full-scale inclined wellbores', *SPE Drilling Engineering*, 7(02), 115-120. SPE 20422.
- Sifferman, T.R., Myers, G.M., Haden, E.L. and Wahl, H.A. (1974) 'Drill cutting transport in full scale vertical annuli', *Journal of Petroleum Technology*, 26(11), 1-295. SPE 4514.
- Simpson, J.P. (1971) 'Drilling fluids-today and tomorrow', *Journal of Petroleum Technology*, 23(11), 1-294. SPE 3714.
- Sivalingam, G. and Saroop, M. (2014) 'Rapid estimation of comonomer content in polyolefins by FTIR', *Chemical Engineering World*, 49(11), 48 and 52-55.

- Skaare, L.E., Klaeboe, P., Nielsen, C.J. and Gundersen, G. (1992) ‘Spectroscopic studies of ethylene-propylene copolymers in the near-and mid-infrared regions’, *Vibrational spectroscopy*, 3(1), 23-33.
- Skalle, P. (2015) *Drilling fluid engineering*. 6<sup>th</sup> edn. Frederiksberg, Denmark: Ventus Publishing ApS. ISBN 978-87-403-1139-6.
- Song, X., Xu, Z., Wang, M., Li, G., Shah, S.N. and Pang, Z. (2017) ‘Experimental study on the wellbore-cleaning efficiency of microhole-horizontal-well drilling’, *SPE Journal*, 22(04), 1-189. SPE 185965.
- Sun, X., Wang, K., Yan, T., Shao, S. and Jiao, J. (2014) ‘Effect of drillpipe rotation on cuttings transport using computational fluid dynamics (CFD) in complex structure wells’, *Journal of Petroleum Exploration and Production Technology*, 4(3), 255-261. doi: <https://doi.org/10.1007/s13203-014-0118-x>.
- Tomren, P.H., Iyoho, A.W. and Azar, J.J. (1986) ‘Experimental study of cuttings transport in directional wells’, *SPE Drilling Engineering*, 1(01), 43-56. SPE 12123.
- Türkçü, H.N. (2004) *Investigation of The Crystallinity and Orientation of Polypropylene with Respect to Temperature Changes Using FT-IR, WRD, And Raman Techniques*. PhD Thesis, Bilkent University.
- Vipulanandan, C. and Mohammed, A.S. (2014) ‘Hyperbolic rheological model with shear stress limit for acrylamide polymer modified bentonite drilling muds’, *Journal of Petroleum Science and Engineering*, 122, 38-47.
- Walker, S. and Li, J. (2000) The Effects of Particle Size, Fluid Rheology, Pipe Eccentricity on Cuttings Transport. *2000 SPE/ICoTA Coil Tubing Roundtable*. 5-6 April. Houston, Texas: SPE 60755, 1-10.
- Wang, F., Tan, X., Wang, R., Sun, M., Wang, L. and Liu, J. (2012) ‘High temperature and high-pressure rheological properties of high-density water-based drilling fluids for deep wells’, *Petroleum Science*, 9(3), 354-362.
- Weickey, Y., Sinha, S.L. and Dewangan, S.K. (2018) ‘Advances in rheological measurement of drilling fluid – a review’, *Progress in Petrochemical Science*, 2(1), 1-3. ISSN 2637-8035.
- Williams Jr, C.E. and Bruce, G.H. (1951) ‘Carrying capacity of drilling muds’, *Journal of Petroleum Technology*, 3(4), 111-120. SPE 951111.
- Winter, A. (2014) *Organic chemistry I for dummies*. 2<sup>nd</sup> edn. Hoboken, New Jersey: John Wiley & Sons.

- Yeu, W.J., Katende, A., Sagala, F. and Ismail, I. (2019) ‘Improving hole cleaning using low density polyethylene beads at different mud circulation rates in different hole angles’, *Journal of Natural Gas Science and Engineering*, 61, 333-343.
- Yi, T.T., Ismail, I., Katende, A., Sagala, F. and Mugisa, J. (2017) ‘Experimental investigation of cuttings lifting efficiency using low- and high-density polyethylene beads in different hole angles’, *Journal of Materials Sciences and Application*, 3(5), 71-78.
- Ytrehus, J.D., Lund, B., Taghipour, A., Kosberg, B.R., Carazza, L., Gyland, K.R. and Saasen, A. (2018) Cuttings Bed Removal in Deviated Wells. *Proceedings of the ASME 2018 37th International Conference on Ocean, Offshore and Arctic Engineering – volume 8: Polar and Arctic Sciences and Technology; Petroleum Technology*. 17-22 June. Madrid, Spain: ASME, 1-7.
- Yu, M., Takach, N.E., Nakamura, D.R. and Shariff, M.M. (2007) An Experimental Study of He Cleaning Under Simulated Downhole Conditions. *2007 SPE Annual Technical Conference and Exhibition*. 11-14 November. Anaheim, California, USA: SPE 109840, 1-14.
- Zakerian, A., Sarafranz, S., Tabzar, A., Hemmati, N. and Shadizadeh, S.R. (2018) ‘Numerical modeling and simulation of drilling cutting transport in horizontal wells’, *Journal of Petroleum Exploration and Production Technology*, 8(2), 455-474.
- Zhang, F., Miska, S., Yu, M., Ozbayoglu, E. and Takach, N. (2017) ‘A fast graphic approach to estimate hole cleaning for directional drilling’, *SPE Drilling & Completion*, 32(01), 51-58. SPE 173681.
- Zhou, L. (2008) ‘Hole cleaning during underbalanced drilling in horizontal and inclined wellbore’, *SPE Drilling & Completion*, 23(03), 267-273. SPE 98926.
- Zou, L., Patel, M.H. and Han, G. (2000) A New Computer Package for Simulating Cuttings Transport and Predicting Hole Cleaning in Deviated and Horizontal Wells. *SPE International Oil and Gas Conference and Exhibition*. 7-10 November. Beijing, China: SPE 64646, 1-12.