

CONTROL STARTUP SLUGS OF UNDULATING MULTIPHASE PIPELINE  
DURING END OF LIFE OPERATION USING OLGA SIMULATION

KARUNAKARAN SELVARAJ

A project report submitted in fulfilment of the  
requirements for the award of the degree of  
Master of Petroleum Engineering

Department of Petroleum Engineering  
School of Chemical & Energy Engineering  
Universiti Teknologi Malaysia

January 2020

## ABSTRACT

Shut-in and cooldown of multiphase pipeline will cause accumulation of condensed liquid at all the low points of undulating sections of the pipeline. Successful startup of pipeline from this equilibrium condition, requires sufficient pressure at upstream to overcome hydrostatic pressure of accumulated liquid and high frictional pressure losses during movement of startup slug in the pipeline. During end of life operation, Shut-in Well Head Pressure, may not be adequate for pipeline startup due to depletion of reservoir inventory or the required inlet pressure during startup may exceed the pipeline design pressure. The objective of this project is to study the formation of startup slugs in undulating pipeline and its impact on operating parameters through OLGA simulation. It is also to establish optimum control methods and design for handling startup slugs with low inlet pressure. Using OLGA, startup slug mitigations options such as flaring from Slug Catcher or utilising drag reducing agent (DRA) injection in the feed or gas injection at riser base or requirement of combination of these methods were analysed. By comparing the simulation results, appropriate mitigation method is proposed for optimal benefit. The thermal-physical property table for the fluid, which is the input for OLGA simulator is generated with PVTsim software. Depressurising the pipeline by flaring (Method 1) from slug catcher is helpful to control startup slug due to increase in available differential pressure across pipeline, reduced liquid hold-up in pipeline by vaporization at low pressure and increased superficial gas velocity. Gas injection (Method 2) at riser base can also be helpful, as it can reduce startup pressure requirement by reducing the riser liquid head. DRA injection (Method 3) can reduce the pressure requirement at upstream of pipeline by minimizing frictional pressure losses when startup slugs moves through long pipeline. From simulation analysis, it is concluded that all three methods helped to reduce the inlet pressure requirement within allowable limit. Therefore, combination methods options are not necessary. Through techno economic analysis, startup with flaring (Method 1) is concluded as most optimal method for control of startup slug.

## ABSTRAK

Penutupan dan penyejukan pelbagai fasa paip akan menyebabkan pengumpulan cecair terkondensasi pada lokasi rendah pada bahagian paip yang beralun. Start-up saluran paip yang berjaya daripada kondisi equilibrium memerlukan tekanan yang mencukupi untuk mengatasi tekanan hidrostatik pada cecair terkondensasi dan kehilangan tekanan geseran yang tinggi semasa pergerakan start-up slug dalam paip. Semasa operasi Akhir hayat, Shut-in Well Head Pressure (SIWHP) mungkin tidak mencukupi untuk start-up disebabkan oleh kekurangan reservoir inventori atau tekanan semasa start-up boleh mengatasi design pressure saluran paip berkenaan. Objektif projek ini untuk mengkaji pembentukan start-up slug dalam saluran paip beralun yang bersaiz 24 inci besar dan 150 km panjang untuk Rich Associated Gas feed dan impaknya terhadap parameter operasi melalui simulasi OLGA. Ia juga untuk mewujudkan keadah kawalan dan reka bentuk yang optimum untuk mengendalikan start-up slug dengan inlet pressure yang rendah daripada available shut-in well head pressure atau design pressure paip, mana-mana yang lebih rendah. Menggunakan OLGA, kaedah mitigasi start-up slug seperti flaring dari Slug Catcher atau menggunakan drag reducing agent (DRA) injection di feed atau gas injection di pangkal riser atau keperluan untuk menggunakan gabungan kaedah kaedah akan dianalisis. Dengan membandingkan keputusan simulasi, mitigasi yang sesuai akan dicadangkan untuk faedah yang optimum. Thermal-physical property table untuk cecair, yang merupakan input untuk simulator OLGA akan dihasilkan dengan perisian PVTsim. Depressurising saluran paip dengan flaring (Kaedah 1) dari Slug Catcher membantu untuk mengawal startup slug kerana peningkatan available differential pressure merentasi saluran paip, penyusutan liquid hold-up dalam saluran paip dengan penguapan pada tekanan rendah dan peningkatan superficial gas velocity. Gas injection (Kaedah 2) pada pangkalan riser juga boleh membantu, kerana ia dapat mengurangkan keperluan startup pressure dengan mengurangkan riser liquid head. DRA injection (Kaedah 3) boleh mengurangkan keperluan tekanan di hulu saluran paip dengan meminimumkan kehilangan tekanan geseran apabila startup slugs bergerak melalui saluran paip yang panjang. Dari analisis simulasi, ia disimpulkan bahawa ketiga-tiga kaedah ini membantu mengurangkan keperluan inlet pressure dalam had yang dibenarkan. Oleh itu, pilihan kaedah gabungan tidak diperlukan. Melalui analisis techno economic, startup dengan flaring (Kaedah 1) disimpulkan sebagai kaedah yang paling optimum untuk mengawal startup slug.

## TABLE OF CONTENTS

	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	<b>iii</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>TABLE OF CONTENTS</b>	<b>vii</b>
	<b>LIST OF TABLES</b>	<b>xi</b>
	<b>LIST OF FIGURES</b>	<b>xii</b>
	<b>LIST OF ABBREVIATIONS</b>	<b>xv</b>
	<b>LIST OF SYMBOLS</b>	<b>xvi</b>
<b>CHAPTER 1</b>	<b>INTRODUCTION</b>	<b>1</b>
	1.1 General Overview	1
	1.2 Problem Statement	5
	1.3 Study Objectives	7
	1.4 Scope of Study	7
	1.5 Significance of Study	8
<b>CHAPTER 2</b>	<b>LITERATURE REVIEW</b>	<b>10</b>
	2.1 Introduction	10
	2.2 Flow Regimes	11
	2.3 Definition and Types of Slugs	12
	2.3.1 Terrain Slug	13
	2.3.2 Hydrodynamic Slug	15
	2.3.3 Pigging Slug	16

2.3.4	Startup Slug	17
2.3.5	Rate Changes Slug	17
2.4	Multiphase Flow Simulation	18
2.4.1	OLGA Software Introduction	18
2.4.2	OLGA Model Basics	19
2.4.3	Fluid Properties in OLGA	22
2.4.4	Heat Transfer Calculations in OLGA	24
2.4.5	Slug Tracking in OLGA	26
2.4.6	Compare OLGA Prediction with Experiment	27
2.5	Slug Control Methods	29
2.5.1	Slug Catchers and Separators Sizing	30
2.5.2	Pipe Diameter Regulation	30
2.5.3	Gas Injection at Riser Base	31
2.5.4	Pipe Insertion or Self Induced Gas Lift	32
2.5.5	Slug control by Choking	32
2.5.6	Use of Flow Improver or Drag Reducing Agent	34
2.5.7	Other Operational Changes Slug Mitigation	35
2.6	Merits and Limitations of Slug Control Methods	36
2.6.1	Slug Catchers and Separators Design Limitations	36
2.6.2	Pipe Diameter Regulation Method Limitations	37
2.6.3	Gas Injection at Riser Base Method Limitations	37
2.6.4	Self-Induced Gas Lift Method Limitations	38
2.6.5	Choking Method Limitation	38
2.6.6	Limitations of Other Slug Mitigation Methods	39
2.7	Conclusions	39
<b>CHAPTER 3</b>	<b>METHODOLOGY</b>	<b>42</b>
3.1	Introduction	42
3.2	Study Flow Chart	43
3.3	Basis of Study and Assumptions	43
3.3.1	Software	43

3.3.2	Model Database	45
3.3.3	Fluid Characterization	49
3.3.4	Well Fluid Composition	49
3.3.5	Phase Envelope	50
3.3.6	Environmental Data	51
3.3.7	Pipeline Properties	52
3.3.8	Model Boundary Conditions	53
3.3.9	Model Building and Tuning	53
3.3.10	Model Validation	55
3.3.11	Method 1 Flaring from Slug Catcher	55
3.3.12	Method 2 DRA Injection	57
3.3.13	Method 3 Gas Injection at Outlet Riser	58
<b>CHAPTER 4</b>	<b>RESULTS AND DISCUSSIONS</b>	<b>61</b>
4.1	Introduction	61
4.2	Steady State Analysis Base Case	62
4.3	Steady State Analysis with DRA Injection	64
4.3.1	Roughness Factor Estimation	64
4.3.2	DRA Injection Quantity	65
4.3.3	Simulation Results	66
4.4	Dynamic Simulation Analysis	69
4.4.1	Shut-in and Cooldown Base Case Scenario	70
4.4.2	Startup Scenario - Base Case	72
4.4.3	Startup Scenario - Modified Event Sequence	76
4.4.4	Startup Scenario – With Flaring	79
4.4.5	Startup Scenario – With Gas Lift	82
4.4.6	Shut-in and Cooldown With DRA Injection	86
4.4.7	Startup With DRA Injection	89
4.5	Merits and Demerits of Startup Methods	93
4.5.1	Merits and Demerits – Startup with Flaring	93
4.5.2	Merits and Demerits – Startup with Gas Lift	93

4.5.3	Merits and Demerits – Startup with DRA Injection	94
<b>CHAPTER 5</b>	<b>CONCLUSIONS</b>	<b>96</b>
5.1	Overall Conclusion	96
5.2	Recommended Startup Method	97
<b>REFERENCES</b>		<b>99</b>

## LIST OF TABLES

<b>TABLE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Table 2.1	Selection of PVT Methods (User manual OLGA Version 2016.2)	23
Table 3.1	Pipeline Configuration	46
Table 3.2	Pipeline Wall Properties	48
Table 3.3	Production Fluid Composition	50
Table 3.4	Environment Data	51
Table 3.5	Pipeline Design Properties	52
Table 3.6	Pipeline Thermal Data	52
Table 3.7	Model Boundary Condition	53
Table 4.1	Steady State Base Case Results Summary	62
Table 4.2	Production Fluid Properties at Slug Catcher Condition	66
Table 4.3	Steady State with DRA Injection Results Summary	67
Table 4.4	Event Sequence for Shut-in and Cool Down Base Case	70
Table 4.5	Event Sequence for Startup Base Case	73
Table 4.6	Modified Event Sequence for Startup	76
Table 4.7	Event Sequence for Startup with Flaring	80
Table 4.8	Event Sequence for Startup with Gas Lift	83
Table 4.9	Event Sequence for Shut-in and Cooldown with DRA Injection	87
Table 4.10	Event Sequence for Startup with DRA Injection	89
Table 5.1	Recommended Sequence for Startup Slug Control	97



## LIST OF FIGURES

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 1.1	Flow Assurance Challenges with Multiphase Pipeline (Hill, 2018)	2
Figure 1.2	Slug Flow in Horizontal Pipeline (Omowunmi et al., 2013)	2
Figure 1.3	Terrain Slugging in Flowline Riser (BP Multiphase Design Manual, 1994)	3
Figure 2.1	Flow Regime Map – Horizontal Pipeline (Seminar at Aker Solutions, 2011)	11
Figure 2.2	Flow Regime Map – Vertical Pipeline (Seminar at Aker Solutions, 2011)	12
Figure 2.3	Terrain Slugging Cycle (Flow Assurance Design Guideline, Intec Engineering, 2001)	14
Figure 2.4	Formation of Hydrodynamic Slugs (Deepstar Multiphase Design Guideline, 2001)	16
Figure 2.5	OLGA Calculation Basics Schematic Drawing (User manual OLGA Version 2016.2)	19
Figure 2.6	Temperature-Pressure Equidistant Fluid Table (User manual OLGA Version 2016.2)	24
Figure 2.7	Boundary Temperature for Pipe with Three Wall Layers (User manual OLGA Version 2016.2)	25
Figure 2.8	Formation of Level Slugs	26
Figure 2.9	Computed Vs Experiment Results for USG and USL (Staff et al., 2015)	28
Figure 2.10	Computed Vs Experiment Results for Liquid Holdup for 12 inch 5° inclined pipeline (Staff et al., 2015)	28
Figure 2.11	Slug Control by Gas Injection at Riser Base	31
Figure 2.12	Self Induced Gas Lift Slug Control Method (Tengesdal and Sarcia, 2000)	32
Figure 2.13	Schematic Diagram of ABB Slugcon Control System (Anayo, 2011)	33
Figure 2.14	Pressure Gradient Vs Superficial Gas Velocity (Kang and Jepson, 1999)	34
Figure 3.1	Study Flow Chart	44

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 3.2	RAG Feed End of Life Composition - Phase Envelope	51
Figure 3.3	Pipeline Elevation Profile	54
Figure 3.4	OLGA Model Schematic Diagram	54
Figure 4.1	Steady State Trend - Pressure, Flow and Accumulated Liquid	63
Figure 4.2	Steady State Profile – Flow Regime and Superficial Velocity	63
Figure 4.3	Steady State Profile – Elevation, Liquid Holdup, Pressure and Temperature	64
Figure 4.4	Steady State Trend - Pressure, Flow and Accumulated Liquid	68
Figure 4.5	Steady State Profile – Flow Regime and Superficial Velocity	68
Figure 4.6	Steady State Profile – Elevation, Liquid Holdup, Pressure and Temperature	69
Figure 4.7	Shut-in Cooldown trend – Pressure, Accumulated Liquid and Flow	71
Figure 4.8	Profile After Cooldown – Elevation, Holdup, Pressure, Temperature and Flow	72
Figure 4.9	Startup Base Case trend – Pressure, Accumulated Liquid and Flow	74
Figure 4.10	Profile Start-up Base Case at t=20min – Elevation, Holdup and Pressure	75
Figure 4.11	Profile Start-up Base Case at t=25min – Elevation, Holdup and Pressure	75
Figure 4.12	Startup Modified Sequence trend – Pressure, Accumulated Liquid and Flow	78
Figure 4.13	Profile Start-up Modified Sequence at t=21min – Elevation, Holdup and Pressure	78
Figure 4.14	Profile Start-up Modified Sequence at t=30min – Elevation, Holdup and Pressure	79
Figure 4.15	Startup with Flaring trend – Pressure, Accumulated Liquid and Flow	81
Figure 4.16	Start-up – Pipeline Profile before flaring – Elevation, Holdup and Pressure	82
Figure 4.17	Start-up – Pipeline Profile after flaring – Elevation, Holdup and Pressure	82

<b>FIGURE NO.</b>	<b>TITLE</b>	<b>PAGE</b>
Figure 4.18	Startup with Gas Injection Trend – Pressure, Accumulated Liquid, Feed Flow and Gas Injection Flow	84
Figure 4.19	Start-up with Gas Injection: Profile at initial condition – Elevation, Holdup and Pressure	85
Figure 4.20	Start-up with Gas Injection – Profile with Riser Injection Gas in Circulation – Elevation, Holdup and Pressure	85
Figure 4.21	Start-up with Gas Injection – Profile after steady state – Elevation, Holdup and Pressure	86
Figure 4.22	Shut-in Cooldown trend – Pressure, Accumulated Liquid and Flow	88
Figure 4.23	Profile After Cooldown – Elevation, Holdup, Pressure, Temperature and Flow	88
Figure 4.24	Startup with DRA Injection Trend – Pressure, Accumulated Liquid and Flow	91
Figure 4.25	Start-up with DRA: Profile at initial condition – Elevation, Holdup and Pressure	91
Figure 4.26	Start-up with DRA – Profile after equalisation with slug catcher – Elevation, Holdup and Pressure	92
Figure 4.27	Start-up with DRA – Profile after steady state – Elevation, Holdup and Pressure	92

## LIST OF ABBREVIATIONS

DRA	-	Drag Reducing Agent
FWS	-	Full Well Stream
GLR	-	Gas Liquid Ratio
GOR	-	Gas Oil Ratio
H&MB	-	Heat and Material Balance
HSE	-	Health, Safety and Environment
IFE	-	Institute for Energy Research
Leda Flow	-	Hydraulics and Thermodynamics Simulation Software
Multiflash	-	Fluid Properties Simulation Software
OLGA	-	Hydraulics and Thermodynamics Simulation Software
PFD	-	Process Flow Diagram
PI Values	-	Proportional and Integral Tuning Constants
P&ID	-	Piping and Instrumentation Diagram
PR	-	Peng-Robinson Equation of State
Promax	-	Fluid Properties Simulation Software
PVTSim	-	Fluid Properties Simulation Software
PVT		Pressure Volume Temperature Relationship
RAG	-	Rich Associated Gas
SIWHP	-	Shut-in Well Head Pressure
USG	-	Superficial Gas Velocity
USL	-	Superficial Liquid Velocity
UTM	-	Universiti Teknologi Malaysia

## LIST OF SYMBOLS

$\partial t$	-	Differentiation in time
$\partial z$	-	Spatial differentiation
$g$	-	Acceleration due to gravity
$\phi$	-	Pipe angle relative to gravitational vector
$P_i$	-	Pressure force
$F_w$	-	Wall friction
$\Psi_{ji}$	-	Momentum contributions corresponding to mass transfer between j-th and i-th mass field
$m_g$	-	Mass associated with gas
$m_h$	-	Mass associated with oil
$m_w$	-	Mass associated with water
$E_i$	-	Field energy
$H_i$	-	Field enthalpy
$S$	-	Enthalpy source/sink
$Q$	-	Heat flux through pipe wall
$T_{ij}$	-	Energy transfer between fields
$q_i$	-	Heat flow from the fluid
$T_f$	-	Average fluid temperature
$T_{iw}$	-	Inner wall surface temperature
$h_i$	-	Inner wall heat transfer coefficient
$q_{amb}$	-	Heat flow from outer wall surface
$T_{ow}$	-	Wall surface temperature
$T_{amb}$	-	Ambient temperature
$h_{amb}$	-	Heat transfer coefficient
$F_{sL}$	-	Slug frequency
$D$	-	Pipeline diameter
$L$	-	Pipeline length
$U_{Sl}$	-	Superficial liquid velocity

# CHAPTER 1

## INTRODUCTION

### 1.1 General Overview

Satellite platforms are generally used to produce from marginal oil and gas fields as well as from the fields located in harsh environment. Due to economic reasons, the multiphase produced fluid consisting of hydrocarbon gas, hydrocarbon liquid and formation water are transported directly from well head platform to on-shore processing facilities or offshore centralised processing platform through long distance multiphase pipelines. This results in large cost savings by not having to duplicate separation, dehydration, compression and utilities for new facilities. It also reduces the risk to people as less people are working at offshore facilities. It also reduces risk to environment by having less hydrocarbon inventory at top sides and having fewer routes for release of hydrocarbon to environment. Flow assurance studies for multiphase pipelines involves analysing thermal, hydraulic and production chemistry related issues in order to ensure safe, reliable and economical transportation of fluids from production facility to processing facility. The use of multiphase pipelines presents major challenges in design and operation of the facility.

Figure 1.1 shows various flow related and fluid related flow assurance challenges associated with multiphase pipeline. The list of issues shown at the top left are flow related issues and bottom right are fluid related issues.




Figure 1.1 Flow Assurance Challenges with Multiphase Pipeline (Hill, 2018)

This project focus on slugging issues in the pipeline. Slug flow is a liquid gas two phase flow in which the gas phase exists as large bubbles separated by liquid slugs. Figure 1.2 shows the slug flow pattern in the case of horizontal pipeline.




Figure 1.2 Slug Flow in Horizontal Pipeline (Omowunmi et al., 2013)

Slugs are normally classified based on mode of formation. The slug flow formed by flow instabilities such as Kelvin-Helmholts instability (Sharma, Ihara and Manabe, 2002) are called as hydrodynamic slugs. If the slug formation is due to geometry of the pipeline, they are called terrain slugs. Slug formation in riser pipe and in hilly terrain are examples for terrain slug. Formation and movement of riser slug is shown schematically in Figure 1.3 along with velocity and pressure trend at riser bottom. Similar to riser pipe slug, liquid accumulation at low points in the pipeline will cause temporary blockage. This can cause gas pressure behind the blockage to increase and expel the liquid as slug.

The next type of slugs are operational slugs, which are formed due to transient changes in pressure and flowrate during various operating modes of the multiphase pipeline. Some of the types of operational slugs are start-up slug, ramp-up slug, pigging slug and depressurisation operation slug.




Figure 1.3 Terrain Slugging in Flowline Riser (BP Multiphase Design Manual, 1994)



These liquid slugs moves at much higher velocity than the average liquid velocity. This type of flow can cause severe vibrations in pipeline systems due to impact of high velocity slugs against fittings such as bend, tee etc. This can also cause other flow assurance issues such as increased back pressure, fatigue failure, erosion and unsteady gas and liquid flow into downstream processing equipment of separator. The unsteady gas and liquid flow through pipeline can cause tripping of downstream compression system, which in turn can cause overpressure in the separator. Therefore, managing slug flow is one of the critical aspect of flow assurance in multiphase pipeline. The slug flow behaviour is greatly influenced by thermal, hydraulic and production chemistry related factors and is transient in nature. Following are the examples of those factors affecting the slug flow behaviour in multiphase pipeline:

- (a) Thermal factors: Viscosity, density and heat transfer capacity
- (b) Hydraulic factors: Pipe diameter, length, elevation and roughness
- (c) Chemistry related factors: Hydrocarbon composition, water cut and GOR

Therefore, analysing and controlling slug flow is complex in nature and usually carried out using dynamic simulation software tools such as OLGAs and Leda Flow along with fluid characterising software such as Multiflash, Promax and PVTsim software.

The slug analysis and control should also consider changes to operation parameters such as feed composition, pressure, temperature, production profiles, ambient conditions throughout the operating life of the reservoir. This will avoid any requirement for major modification to the facility during operation phase, which is usually expensive when compared to designing the facility compatible for entire operating life of the reservoir. The design of multiphase pipeline system should also consider various operating modes such as startup, normal operation, production turn-down, production ramp up, production ramp down and shutdown. This will improve safety, reliability, operation flexibility, controllability and will optimise production and cost.

This study is to understand operational slug issue in long multiphase pipeline on undulating terrain during pipeline start-up and to contribute in addressing the issue. For slug analysis, this project has considered full well stream (FWS) of Rich Associated Gas fluid transported through subsea pipeline of length 150 kilometres and 16 inches diameter.

## **1.2 Problem Statement**

Liquid holdup in a pipeline during end of life operation is larger than early life operation due to low gas velocity in the pipeline. From steady state operating condition, pipelines are shut down for maintenance reason or for emergency situations. During shutdown of FWS pipelines, the valves at upstream of inlet riser and downstream of outlet riser are isolated under pressurised condition. This will cause the pipeline pressure to get equalised and reaches settle out pressure. During this time, liquid in the pipeline gets accumulated in the lowest points of pipeline depending on the elevation profile of the pipeline. Produced fluid trapped in the pipeline is further cooled by exchanging heat with surrounding water for subsea pipeline section and with atmospheric air for above sea pipeline and piping sections. This cooldown process causes additional trapped gas to condense and get accumulated at low points due to gravity. If the pipeline is laid over undulating terrain, the condensed liquid gets accumulated at all the low points of the undulating sections of the pipeline. During start-up, pipeline inlet and outlet shutdown valves are opened. Fluid pressure at the inlet of the pipeline will increase to overcome the hydrostatic pressure of accumulated liquid following shutdown and frictional pressure loss due to movement of fluid through the pipeline. Majority of the liquid holdup is evacuated from the pipeline as large liquid slugs into the downstream separator. This is called operational slug of pipeline start-up.

During early phase of life of reservoir, produced fluid will have enough energy to overcome the hydrostatic pressure and frictional pressure loss. During end of life operation, the Shut-in Well Head Pressure (SIWHP) available at upstream of choke valve will be much lesser than early life operation due to depletion of reservoir inventory. In addition to that, liquid phase of production fluid will be enriched with

heavier hydrocarbon and will normally have high water cut. This will cause increased liquid fraction in the pipeline, which will cause high hydrostatic liquid head following shutdown. Low gas velocity in the pipeline will also cause increased liquid holdup in the pipeline. Due to these operating characteristics, the available SIWHP during end of life operation may not be sufficient to overcome hydrostatic fluid head and frictional pressure loss during pipeline start-up. Therefore, flow cannot be established through pipeline during start-up. In some cases, the required pressure at inlet of pipeline to mobilize the start-up may exceed the allowable design pressure limit of the pipeline.

Lack of knowledge on operational slugs can severely affect production flow through the pipeline. The existing slug control design and methodologies practiced in industries might be inadequate for startup towards end of life operation of reservoir on undulating pipeline. This is due to large liquid accumulation at many low points, low available pressure at pipeline inlet or the inlet pressure exceeding the design pressure limit of the pipeline. This study will focus on handling startup slug in long multiphase pipeline on an undulating terrain during start-up with required inlet pressure below the design limit of the pipeline and SIWHP during end of life operation.

OLGA is the dynamic simulation tool, which can provide better insight of thermal and hydraulic transient behaviours of multiphase pipeline (Enilari, 2015). In this study, OLGA is used to predict the liquid hold-up following pipeline shutdown and is also used to analyse various methodologies to handle operational slugs during start-up, when production could not be restored due to low available SIWHP or due to high required inlet pressure, which exceeds the design limit. The following mitigation techniques are analysed through simulation studies to overcome the above issue:

- (a) Depressurizing the pipeline by flaring
- (b) Gas injection at outlet riser base
- (c) Drag Reducing Agent injection with feed
- (d) Combination of the above methods, if above methods alone is unsuccessful

### **1.3 Study Objectives**

The major objectives of this project are:

- (a) To study the formation of startup slugs in undulating pipeline and its impact on operating parameters through OLGA simulation;
- (b) To establish optimum control method and design for handling startup slugs with pipeline upstream pressure below the design pressure limit or available shut in wellhead pressure (SIWHP) during end of life operation.

### **1.4 Scope of Study**

The overall scope of study involves analysing the following:

- (a) Modelling the carbon steel pipeline system of length 150 km and diameter 24 inches. Large undulation are assumed at 10 sections of the pipeline and small undulations at 3 sections of the pipeline. These undulations are evenly spread across the entire length of the pipeline. The elevation changes at large undulated sections vary between 6 m and 13 m. The inlet and outlet risers elevation change are 112 m and 50 m respectively.
- (b) Establishing optimal design and/or operational mitigation method for handling startup slugs by the following 3 methods:
  - i. Method 1: Flaring from slug catcher
  - ii. Method 2: Gas injection at riser base
  - iii. Method 3: DRA injection in the feed

Note: Combination of above methods are to be analysed only if startup by above methods alone is unsuccessful.

- (c) Comparing the results from all the above methods and propose the appropriate method for optimal benefit.

### **1.5 Significance of Study**

This study is useful to understand the background of flow assurance issues due to startup slugs in the undulating multiphase pipeline;

This study aimed to provide optimum design option to handle startup slugs during end of life operation of reservoir, when available SIWHP is not enough to drive the accumulated liquid in the pipeline and production flow cannot be established through multiphase pipeline during start-up.

This study is also useful to establish optimum operating philosophy for handling startup slugs, so that transient operating conditions are within safe operating envelope for the entire system. This will also enable reliable and efficient operation of the unit by minimising production interruptions caused by process trips during pipeline startup operation.

## REFERENCES

- Anayo Issac Ogazi (2011), *Multiphase Severe Slug Flow Control*. PhD Thesis, Cranfield University, PP 22-47
- BP Exploration (1994), *BP Multiphase Design Manual*, Issue 2, December 1994, P 26.
- Enilari, B. T. (2015) ‘Slug Flow and it’s Mitigation Techniques in the Oil and Gas Industry’ *Annual International Conference and Exhibition in Lagos, Nigeria, August 2015*, p. 2.
- Fard, Mehrdad P.; Godhavn, John-Morten; Sagatun, Svein I. (2006) ‘Modeling of Severe Slug and Slug Control With OLGA’ *SPE International Symposium and Exhibition on formation Damage Control, Lafayette, Louisiana, March*, p. 1.
- Hill, T. J. (2018) ‘Research in multiphase flow developed into new global discipline of flow assurance’, *11th North American Conference on Multiphase Production Technology, 6-8 June, Banff, Canada*, p.9
- Intec Engineering, Inc. (2001), ‘Deepstar IV Project, Flow Assurance Design Guideline’, p. 779.
- Issa, R.I. (2005), ‘Computer Prediction of Slug Flow in Pipelines: Potential for Industrial Applications’, *12th International Conference on Multiphase Production Technology, May 2005*, pp 1-3
- Jansen, F.E.; Shoham, Ovadia, (1994), ‘Methods for Eliminating Pipeline-Riser Flow Instabilities’, *SPE Western Regional Meeting, California, March 1994*, pp 2-4

- Kang, C.; Jepson, W.P. (1999), 'Multiphase Flow Conditioning Using Drag-Reducing Agents', SPE Annual Technical Conference and Exhibition, Houston, Texas, October 1999, pp 1-7
- Mayadah, A., (2019), 'Supervised Machine Learning in Predicting Multiphase Flow Regimes in Horizontal Pipes', Abu Dhabi International Petroleum Exhibition & Conference held in Abu Dhabi, UAE, November 2019, p. 4.
- Omowunmi, S.C., Abdulssalam, M., Janssen, R. and Otigbah, P. (2013) 'Methodology for Characterising Slugs and Operational Mitigation Strategy Using OLGA Slug Tracking Module – Egina Deepwater Project', *11<sup>th</sup> Offshore Mediterranean Conference and Exhibition in Ravenna, Italy, March 2013*, pp. 2-6.
- Rezzonico, Ricardo A. and Carp, Ariel (2007), 'Transient Analysis of Flowlines and Slug Catcher Level Control', *Latin American & Caribbean Petroleum Engineering Conference, Buenos Aires, Argentina, April 2007*, pp 1-4
- Schlumberger, (2016), 'OLGA 2016, Version 2016.2 User Manual', pp. 9-74
- Sharma, Y., Ihara, M., and Manabe, R. (2002) 'Simulating Slug Flow in Hilly-Terrain Pipelines', *International Petroleum Conference and Exhibition in Villahermosa, Mexico, February 2002*, p. 1.
- Staff, G. ; Biberg, D. ; Vanvik, T. ; Hoyer, N. ; Nossen, J. ; Holm, H. ; Johansson, P. S. (2015) 'Validation of OLGA HD Against Transient and Pseudotransient Experiments from the SINTEF Large Diameter High Pressure Flow-Loop', *17th International Conference on Multiphase Production Technology, Cannes, France, September 2015*, pp 6-16
- Tengesdal, J.Ã.; Sarica, Cem; Thompson, Leslie (2003) 'Severe Slugging Attenuation for Deepwater Multiphase Pipeline and Riser Systems', *SPE Annual Technical Conference and Exhibition, September 2003*, pp 1-2

University of Stavanger, Flow Assurance and Multiphase Flow Seminar at Aker  
Solutions (2011), May 2011, pp. 10-11