

IMPROVEMENT OF 4 ½ INCHES CEMENTED MONOBORE DESIGN TO  
REDUCE WELL COST

SITI RODHIAH BINTI FAZILAH

A dissertation submitted in partial fulfillment of the  
requirements for the award of the degree of  
Master of Petroleum Engineering

School of Chemical and Energy Engineering  
Universiti Teknologi Malaysia

SEPTEMBER 2020

## **ACKNOWLEDGEMENT**

Alhamdulillah, praise to Allah SWT for the countless blessing for me to be able to complete this thesis throughout the wonderful journey of this Master Program. I am truly humbled to experience this journey with the leadership and guidance form Assoc. Prof. Issham Ismail. Your dedication and passion really inspire me to become a better person.

To my parents especially my Umi, Mashita Abu Talib, thank you for your unconditional love and doa. To my loving and supporting husband Abdul Razak Ibrahim, thank you for patiently keeping up with me and taking care of our kids Hidayah and Muhammad Farhan during this journey. I would not have made it without both of you.

To my UTM batch mates, Azureen, Hakim, Buwa, Bior, Fikri and Fahmi, thank you for the unconditional support and motivation to accomplish this Master Program. It is a pleasure to know all of you.

Last but not least, to PETRONAS for the experience and knowledge provided especially to Besar project team well completion engineers Anas and Mahirah for the dedication throughout the project planning and execution.

## ABSTRACT

This study focuses on the improvement of 4½ inches cemented monobore completion conceptual design through a detailed engineering analysis where it is one of the efforts to reduce well cost without jeopardizing safety and well integrity. A thorough planning on well completion design is imperative to ensure successful delivery of the well. In this research work, the initial plan was to develop overpressured K reservoir with 4½ inches tieback monobore completion. It is a proven concept which can deliver the well safely and without any well integrity issues. During the conceptual design planning in 2013, the oil price was high at USD110/bbl and the tieback monobore well completion design was optimized to 4½ inches cemented monobore with lower cost to improve the project economics. When the detail design planning in 2016, the global oil price crash to USD30/bbl and high MYR vs. USD exchange rate was observed. There was a need to redesign the cemented monobore well to further reduce the overall well cost and improve the project economic of the well. The study also focused on collaborative well planning with multi-disciplinaries teams, selection of critical well completion equipment, and tubing stress analysis using WELLCAT™ simulation program to improve the cemented monobore well design to lower the cost without jeopardizing safety and well integrity. The improved cemented monobore design has reduced the well casing schemes; from five casing schemes to four casing schemes through the collaborative well planning initiative. The selection of Weatherford multi-latch in plug, Welltec well annular barrier, and Halliburton SP cement-thru TRSV as critical well completion equipment for cement plug and accessories, and cement-thru packer have preserved the well safety and integrity. The 4½ inches, 12.6 ppf, 13Cr-L80, JFE BEAR tubing string and 9⅝ inches, 47 ppf, L80, JFE BEAR casing string satisfy the tubing load and the annular fluid expansion requirement from WELLCAT™ simulation.

## ABSTRAK

Kajian ini tertumpu kepada kerja untuk menambah baik reka bentuk konsep pelengkapan monolubang tersimen bersaiz 4½ inci menerusi analisis terperinci kejuruteraan sebagai satu daripada usaha bagi mengurangkan kos telaga tanpa mengabaikan aspek keselamatan dan integritinya. Perancangan yang teliti tentang reka bentuk telaga adalah penting demi kebolehpengeluaran telaga terbabit. Dalam kajian ini, perancangan awal adalah untuk membangunkan reservoir K yang bertekanan tinggi menerusi pelengkapan monolubang rentetan ikat bersaiz 4½ inci. Konsep telaga itu jelas terbukti selamat dan bebas daripada permasalahan integriti. Ketika perancangan reka bentuk konsep itu pada tahun 2013, harga minyak mentah dunia adalah tinggi, iaitu USD110 setong, tetapi reka bentuk itu kemudiannya terpaksa dirombak kepada pelengkapan monolubang tersimen bagi mengurangkan kos demi kelestarian ekonomi projek. Ketika perancangan reka bentuk terperinci pada tahun 2016, berlaku kejatuhan teruk harga minyak dunia hingga ke paras USD30 setong serta kadar pertukaran wang asing MYR vs. USD yang tinggi. Berikutan itu, timbul keperluan untuk menilai semula konsep telaga monolubang tersimen bagi mengurangkan lagi kos keseluruhan telaga demi kelestarian ekonomi projek. Kajian ini turut memberikan tumpuan terhadap permuafakatan dengan pasukan berlatar belakang pelbagai disiplin, pemilihan peralatan kritikal pelengkapan telaga, dan analisis tegasan rentetan tetiub menerusi penyelaku WELLCAT™ bagi meningkatkan kualiti reka bentuk telaga monolubang tersimen serta mengurangkan lagi kos tanpa menjejaskan keselamatan dan integriti telaga. Reka bentuk monolubang tersimen yang diperbaik berjaya mengurangkan bilangan rentetan selongsong; daripada lima rentetan selongsong kepada empat rentetan selongsong berikutan usaha permuafakatan terbabit. Pemilihan palam pelbagai selak Weatherford, sawar anulus telaga Welltec, dan TRSV simen lalu SP Halliburton sebagai peralatan kritikal pelengkapan telaga masing-masing untuk palam simen dan aksesori simen, dan penyندات simen lalu telah menjamin keselamatan dan integriti telaga. Hasil penyelakuan daripada WELLCAT™ menunjukkan bahawa rentetan tetiub 4½ inci, 12.6 ppf, 13Cr-L80, JFE BEAR dan rentetan selongsong 9⅝ inci, 47 ppf, L80, JFE BEAR masing-masing telah memenuhi keperluan beban tetiub dan keperluan pengembangan cecair anulus.

## TABLE OF CONTENT

	<b>TITLE</b>	<b>PAGE</b>
	<b>DECLARATION</b>	<b>ii</b>
	<b>DEDICATION</b>	<b>iii</b>
	<b>ACKNOWLEDGEMENT</b>	<b>iv</b>
	<b>ABSTRACT</b>	<b>v</b>
	<b>ABSTRAK</b>	<b>vi</b>
	<b>TABLE OF CONTENT</b>	<b>vii</b>
	<b>LIST OF TABLES</b>	<b>ix</b>
	<b>LIST OF FIGURES</b>	<b>x</b>
	<b>CHAPTER 1 INTRODUCTION</b>	<b>1</b>
1.1	Background	1
1.2	Problem Statement	2
1.3	Objectives	7
1.4	Hypotheses	7
1.5	Research Scope	7
1.6	Significance of study	8
1.7	Chapter Summary	8
	<b>CHAPTER 2 LITERATURE REVIEW</b>	<b>9</b>
2.1	Marginal Field	9
2.2	Cemented Monobore Well	9
2.3	Collaborative Well Planning	10
2.4	Well Completion	16
2.5	Monobore Completion	20

2.6	Cemented monobore's advantages over other completion designs	26
2.7	Cemented monobore challenges	27
2.8	Completion Accessories	31
2.9	Chapter Summary	31
<b>CHAPTER 3 METHODOLOGY</b>		<b>33</b>
3.1	Detail design of 4½ inches cemented monobore design	33
3.2	Collaborative Well Planning	35
3.3	Selection of Well Completion Equipment	35
3.4	Tubing Stress Analysis	37
3.5	Chapter summary	39
<b>CHAPTER 4 RESULTS &amp; DISCUSSION</b>		<b>41</b>
4.1	Collaborative Well Planning	41
4.2	Selection of Well Completion Equipment	60
4.3	Tubing Stress Analysis	75
4.4	Improved cemented monobore design	94
4.5	Chapter summary	97
<b>CHAPTER 5</b>		<b>99</b>
5.1	Conclusions	99
5.2	Recommendation	100
<b>REFERENCES</b>		<b>101</b>

## LIST OF TABLES

TITLE	PAGE
<b>Table 2. 1</b> Well completion procedures for each type of completion	26
<b>Table 3. 1</b> Minimum design factor (PETRONAS,2015)	38
<b>Table 4. 1</b> Wellbore azimuth and inclinations for MWC generation	47
<b>Table 4. 2</b> Fluid density of cementing program	61
<b>Table 4.3 ( a )</b> Cement-thru TRSV Engineering Data Sheet (Halliburton, 2017)	71
<b>Table 4.3 ( b )</b> Cement-thru TRSV Engineering Data Sheet (Halliburton, 2017)	72
<b>Table 4.3 ( c )</b> Cement-thru TRSV Engineering Data Sheet (Halliburton, 2017)	73
<b>Table 4. 4</b> Casing and tubing configuration input	75
<b>Table 4. 5</b> Annulus content inside 9 <sup>5</sup> / <sub>8</sub> inches	75
<b>Table 4. 6</b> Casing and tubing connection input	76
<b>Table 4. 7</b> Packer setting depth	76

## LIST OF FIGURES

TITLE	PAGE
<b>Figure 1. 1</b> 4½ inches tieback monobore (PETRONAS, 2012)	3
<b>Figure 1. 2</b> Planned 4½ inches cemented monobore (PETRONAS, 2013)	5
<b>Figure 1. 3</b> Five years global oil price trend (Infomine, 2018)	6
<b>Figure 2. 1</b> Multi-tier cross disciplinary application system (Rosland et al, 2010)	13
<b>Figure 2. 2</b> 3D viewer workspace for well planning (Rosland et al., 2010)	13
<b>Figure 2. 3</b> Collaborative well planning workflow (Rosland et al., 2010)	14
<b>Figure 2. 4</b> Visualization centre for CWP (Rosland et al., 2010)	15
<b>Figure 2. 5</b> Single completion (PETRONAS,2016)	16
<b>Figure 2. 6</b> Single completion with flexibility (PETRONAS,2016)	17
<b>Figure 2. 7</b> Dual completion (PETRONAS,2016)	18
<b>Figure 2. 8</b> Dual completion with flexibility (PETRONAS,2016)	19
<b>Figure 2. 9</b> Tieback monobore (PETRONAS, 2016)	23
<b>Figure 2. 10</b> Polish Bore Receptacle (PBR)-tieback monobore (PETRONAS, 2016)	24
<b>Figure 2. 11</b> Cemented monobore (PETRONAS,2016)	25
<b>Figure 2. 12</b> Overshot completion contingency plan (PETRONAS,2016)	29
<b>Figure 2. 13</b> Cemented monobore with cement-thru packer (PETRONAS,2016)	30
<b>Figure 3. 1</b> workflow to improve cemented monobore design	34
<b>Figure 4. 1</b> Well B-A1 initial casing setting depth	42
<b>Figure 4. 2</b> Workflow to construct and analyse the 3D geomechanical model including WMC and NWG analysis	45
<b>Figure 4. 3</b> (a) Distribution of minimum horizontal stress and (b) maximum horizontal stress throughout top K20	46
<b>Figure 4. 4</b> Breakout mud weight (ppg) for vertical well	48
<b>Figure 4. 5</b> Breakout mud weight (ppg) for horizontal well drilled towards SHMax (North-South)	48



<b>Figure 4. 6</b> Breakout mud weight (ppg) for horizontal well drilled towards Shmin (East-West)	49
<b>Figure 4. 7</b> Mud weight window (ppg) for vertical well	49
<b>Figure 4. 8</b> Mud weight window (ppg) for horizontal well drilled towards SHMax (North-South)	50
<b>Figure 4. 9</b> Mud weight window (ppg) for horizontal well drilled towards Shmin (East-West)	50
<b>Figure 4. 10</b> Fracture gradient distribution	51
<b>Figure 4. 11</b> Mud weight window, casing setting depth and plan mud weight for well A-1	53
<b>Figure 4. 12</b> The mud weight window, proposed mud weight (red line) and the 3D NWG simulation results showing the potential plastic strain for well B-A1	54
<b>Figure 4. 13</b> The mud weight window and 3D NWG simulation results showing the total strain (elastic and plastic strain) for well B-A1	54
<b>Figure 4. 14</b> The effect of fault plane on the development of plastic strain along the wellbore for well B-A1	55
<b>Figure 4. 15</b> The effect of pressurising the annulus (up to the seepage loss limit) at the wellbore-fault for well B-A1	56
<b>Figure 4. 16</b> The mud weight window and casing setting depth after 3D optimization for Besar A1 well in 1D-MEM	57
<b>Figure 4. 17</b> Improved well B-A1 casing setting depth	59
<b>Figure 4. 18</b> Improved well B-A1 4½ inches cemented monobore	60
<b>Figure 4. 19</b> Weatherford Multi Latch-in Plug (a) float shoe and calibration plug, (b) landing collar and bottom plug, (c) dual top plug	64
<b>Figure 4. 20</b> Well Annular Barrier (WAB) packer envelope	67
<b>Figure 4. 21</b> WAB compensation mechanism	69
<b>Figure 4. 22</b> Well Schematic of well B-A1	77
<b>Figure 4. 23</b> API connection design limit for 4½ inches tubing	79
<b>Figure 4. 24</b> Premium connection design Limit for 4½ inches tubing	80
<b>Figure 4. 25</b> Cement-thru packer operating envelop for 4½ inches tubing	81
<b>Figure 4. 26</b> API connection design limit 4½ inches tubing AFE	84
<b>Figure 4. 27</b> Premium connection design limit 4½ inches tubing AFE	85
<b>Figure 4. 28</b> Premium connection design limit 9⅝ inches casing AFE analysis	86
<b>Figure 4. 29</b> API connection design limit 9⅝ inches casing AFE analysis	87

<b>Figure 4. 30</b> Internal pressure of 9 <sup>5</sup> / <sub>8</sub> inches casing	88
<b>Figure 4. 31</b> Internal pressure of 9 <sup>5</sup> / <sub>8</sub> inches casing with API triaxial safety factor 1.25	89
<b>Figure 4. 32</b> Internal pressure of 9 <sup>5</sup> / <sub>8</sub> inches casing with API triaxial safety factor 1.1	90
<b>Figure 4. 33</b> 9 <sup>5</sup> / <sub>8</sub> inches 53.5 ppf casing technical data sheet (JFE,2019)	91
<b>Figure 4. 34</b> 9 <sup>5</sup> / <sub>8</sub> inches 47 ppf casing technical data sheet (JFE,2019)	92
<b>Figure 4. 35</b> API connection design limit of 9 <sup>5</sup> / <sub>8</sub> inches 53.5 ppg	93
<b>Figure 4. 36</b> Planned 4-1/2 inches Cemented Monobore (PETRONAS, 2013)	95
<b>Figure 4. 37</b> Improved well completion design (PETRONAS, 2016)	96

# CHAPTER 1

## INTRODUCTION

### 1.1 Background

Monobore completion design is a standard completion design for gas well in PETRONAS operations in Malaysia. Majority of the gas fields have been completed with 7 inches, 5½ inches and 4½ inches monobore completions. Monobore completion comprises a completion tubing which has a uniform internal diameter throughout its entire length (Simonds and Swan, 2000). A monobore completion design involves the installation of lower completion in the open-hole section and tie back the upper completion with the same tubing size as per the lower completion. It is also known as tieback monobore completion.

Monobore completion can reduce well completion days and improve well economics compared to conventional completion (Mohammad and Maung, 2000). The monobore completion technology improves the project economics by reducing drilling and completion cost in relation to conventional completion (Mieres *et al.*, 2015). Conventional completion is a cased hole completion design namely single completion, single selective completion, dual completion, and dual completion with selectivity. These types of completion are completed with 9⅝ inches casing or 7 inches casing with either 2⅜ inches, 2⅞ inches, or 3½ inches production tubing string with accessories such as sliding side door (SSD), landing nipple, production packer and subsurface safety valve (Mieres *et al.*, 2015).

A marginal gas field located in offshore Peninsular Malaysia. The development plan was to complete the K reservoir with 4½ inches monobore completion — Besar well completion. K reservoir has high unconfined compressive strength (UCS) with no potential sand production issue. Lower completion proposed design was cemented


liner. Besar's well completion design had been challenged to improve the economics of the well in the high oil price environment. Since the well has no sand production issue, cemented monobore design concept was proposed to further optimize the well completion design.

In a cemented monobore completion design, the completion string is run and cemented straight into the reservoir open hole after the well has been drilled to cover the producing zone. It is a proven design that provides opportunity to reduce completion cost and improve well completion operation days without impacting safety and well integrity (Salahaldeen *et al.*, 2015).

This study focuses on detail engineering design of the first 4½ inches cemented monobore completion. The objective is to further improve the conceptual design at a lower cost without jeopardizing safety and well integrity. The areas of improvement comprise the well construction improvement, selection of the completion equipment, and tubing stress analysis to ensure the final design meets the design criteria.

## **1.2 Problem Statement**

The initial plan was to develop overpressured K reservoir with 4½ inches tieback monobore completion. An offset well was completed with tieback monobore completion concept that had production hole cased with 9⅝ inches × 7 inches liner hanger tapered to 4½ inches liner and cemented for lower completion. The 4½ inches upper completion with 9⅝ inches production packer rated to ISO 14310 V0 was tied back to the lower completion as per Figure 1.1. The 9⅝ inches production packer rated to ISO 14310 V0 which was a gas tight packer acts as a double barrier against cemented liner hanger to prevent well integrity issues such as sustained casing pressure (SCP). The design had been successfully run and become a standard design in completing gas well. It is a proven concept such that it can deliver the well safely and without any well integrity issues.



**Figure 1. 1** 4½ inches tieback monobore (PETRONAS, 2012)


The tieback monobore completion operation required the 4½ inches liner to be run into the open hole with a 9⅝ inches × 7 inches liner hanger and cemented as the lower completion. A dedicated wellbore clean out (WBCO) was needed to be run in hole (RIH) to clean the casing from the drilling mud and changed over to completion fluid. The 4½ inches upper completion would be run with 9⅝ inches production packer to complete the well (Taoutaou *et al.*, 2007).

In 2013, the oil price was high at USD110/bbl (Brent crude oil price). Contracted rig service rate, well completion equipment and completion related

services were on the high side at the time of the design cost estimate. The high daily rig spread rate had a big impact on the number of well completion operation days to complete the well. Tieback monobore well completion design was challenged to be optimized and delivered with lower cost to improve the project economics. The optimized well design should not compromise safety and integrity of the well during the well construction and production life of the well.

Cemented monobore has an advantage of optimizing the well completion design and operation days. The cemented monobore design concept was proposed for the well completion strategy as per Figure 1.2. The well construction design was with five casing schemes with 6 inches production hole. The 4½ inches tubing string would be run and cemented in place after drilling the production zone. Besar's economic evaluation passed the threshold value for all scenarios except for the low price scenario.

The global oil price crashed to USD30/bbl (Brent crude oil price) and high MYR vs USD exchange rate were seen in 2016. Figure 1.3 shows five years oil price trend from 2013 to 2018. A study conducted by Harvard Business School shows that USD50/bbl oil price puts some producing countries under considerable stress as they struggle with less oil revenue in their national budgets (Hartmaan & Sam, 2016). There was a need to redesign the cemented monobore well to further reduce the overall well cost and improve the project economic of the well.



**Figure 1. 2** Planned 4½ inches cemented monobore (PETRONAS, 2013)



**Figure 1. 3** Five years global oil price trend (Infomine, 2018)



### **1.3 Objectives**

The objective of this study is to conduct a detail engineering design of 4½ inches cemented monobore completion from conceptual design at a lower cost without sacrificing well safety and integrity.

### **1.4 Hypotheses**

The hypotheses of this study are as follow:

- (1) An improved cemented monobore design may produce hydrocarbon without sacrificing well integrity.
- (2) The improved design may further reduce the overall well construction cost of cemented monobore design.
- (3) The cemented monobore design may improve project economics especially for marginal fields.

### **1.5 Research Scope**

The scope of this research work are as follow:

- (1) Perform collaborative well planning to design the well cemented monobore well. Multidiscipline input from geology, subsurface, production technology and wells team.
- (2) Selection of well completion equipment for cemented monobore completion.
- (3) Tubing stress analysis using Landmark WELLCAT™ design with multiple scenario during the life of the well.

## **1.6 Significance of study**

The success of the detailed design planning of the well would result in the success of the first cemented monobore well in PETRONAS.

## **1.7 Chapter Summary**

Cemented monobore has an advantage over tieback monobore in terms of number of well completion days. Oil price crash from USD110/day in 2013 to USD30/day in 2016 required cemented monobore to be redesigned to reduce the well cost. The objective of the study is to improve the conceptual design of cemented monobore established in 2013 in terms of detail engineering design of the 4½ inches cemented monobore completion. The aim is to deliver an improved cemented monobore well which meets the design standard as per PETRONAS standard at a lower cost without jeopardizing safety and well integrity. The research scope involves collaborative well planning, selection of well completion equipment, and tubing stress analysis. This study has a significant impact on the success of the first cemented monobore well in PETRONAS.

## REFERENCES

- Almasmoom, S. S., Gonzalez, J. I., Ramos, D. A., & Al-Faraj, O. A. (2015). *A New Completion Approach in Saudi Aramco for Unconventional Gas Wells Using Full Monobore 4 1/2" Cemented Casing Completion*. SPE Saudi Arabia Section Annual Technical Symposium and Exhibition. doi:10.2118/177977-ms
- Ariyanto, P., Najwani, M. A., Najwani, Y., Al Lawati, H., Pfeiffer, J., & Al Abri, M. (2015). *Achieving Cementing Improvement in Horizontal Tight Gas Field Development*. SPE Middle East Unconventional Resources Conference and Exhibition. doi:10.2118/172937-ms
- Brandl, A., Acorda, E. P. R., Doherty, D. R., & Rajaneekornkrilas, V. (2011). *Lightweight Cementing Design Improves Zonal Isolation on Challenging High Temperature Offshore Thailand Wells*. SPE Annual Technical Conference and Exhibition. doi:10.2118/147012-ms
- Denney, D. (1999). *Monobores Improve Life-Cycle Cost*. Journal of Petroleum Technology, 51(02), 69–70. doi:10.2118/0299-0069-jpt
- Edwards, T., Saunders, M., & Moore-Cernoch, K. (2006). *Advanced Collaborative Environments In BP*. Intelligent Energy Conference and Exhibition. doi:10.2118/100113-ms
- Fjeldskaar, W., Mykkeltveit, J., Johansen, H., Langfeldt, J. M., Christie, O. H. J., Tyvand, P., Bjorkum, P. A. (1990, September 1). *Interactive 2D Basin Modeling on Workstations*. Society of Petroleum Engineers. doi:10.2118/20350-PA

- Goobie, R. B., Allen, W. T., Lasley, B. M., Corser, K., & Perez, J. P. (2015). *A Guide to Relief Well Trajectory Design using Multidisciplinary Collaborative Well Planning Technology*. SPE/IADC Drilling Conference and Exhibition. doi:10.2118/173097-ms
- Grace, R. D. (1974, January 1). *Planning a Well (1974 DPM Chapter 4)*. Society of Petroleum Engineers. doi:NA
- Greenip, J. F. (1977, January 1). *Determining Stress In Tubing Using Triaxial Evaluation*. Society of Petroleum Engineers. doi:10.2118/6760-MS
- Ingvarsdn, D., & Kritzler, J. H. (2009). *Monobore Completion Systems Provide Low Cost Completion Option*. SPE Annual Technical Conference and Exhibition. doi:10.2118/124797-ms
- Johnson, R., Jellison, M. J., & Klementich, E. (1987, September 1). *Triaxial-Load-Capacity Diagrams Provide a New Approach to Casing and Tubing Design Analysis*. Society of Petroleum Engineers. doi:10.2118/13434-PA
- JPT staff, \_ . (2004, February 1). *Software Application Optimizes Well-Planning and Risk-Assessment Process*. Society of Petroleum Engineers. doi:10.2118/0204-0026-JPT
- JPT staff, \_ . (2006, October 1). *Techbits: Developing Marginal Offshore Fields*. Society of Petroleum Engineers. doi:10.2118/1006-0028-JPT
- Kaeng, G. C., Natepracha, J., Sausan, S., Chongrueanglap, P., Anansatitporn, N., & Srisuriyon, K. (2016, March 22). *Behind Fault Well Planning: The Strong Influence of Geological Structure in Planning Complex Well Trajectories in the Gulf of Thailand*. Offshore Technology Conference. doi:10.4043/26745-MS

- Keller, S. R., Crook, R. J., Haut, R. C., & Kulakofaky, D. S. (1987). *Deviated-Wellbore Cementing: Part 1 - Problems*. *Journal of Petroleum Technology*, 39(08), 955–960. doi:10.2118/11979-pa
- Kikuchi, S. (1993, January 1). *2D and 3D Well Planning for Horizontal Wells*. Society of Petroleum Engineers. doi:10.2118/25647-MS
- Lee, J. M., Bt Mohd Zain, S. N. M., AB Malek, A. B., B. Nordin, M. H., Rahaman, A. T. B. A., Hermawan, H., & B. Nasrudin, K. A. (2018). *The Road to Low Cost Well - A Case Study of Successful Cost Optimization Strategies to Remain Relevant in Low Oil Price Environment, Offshore Malaysia*. Offshore Technology Conference Asia. doi:10.4043/28459-ms
- Luna, D., Bezbourah, P., & Omar, M. (2015, November 9). *First Cemented Completion in Egypt*. Society of Petroleum Engineers. doi:10.2118/177650-MS
- Wilson, M. A., & Sabins, F. L. (1988). *A Laboratory Investigation of Cementing Horizontal Wells*. *SPE Drilling Engineering*, 3(03), 275–280. doi:10.2118/16928-pa
- Mieres, K. R., Prieto, V., Banzer, C., & Molina, F. (2015, November 18). *Well Completion with Monobore Technology for Gas Production in the B6 LL 370 Reservoir in the Tia Juana Field, Lake Maracaibo, Venezuela*. Society of Petroleum Engineers. doi:10.2118/177208-MS
- Milton, A. (1980). *A Progressive Approach to Marginal Field Development in S.E. Asia*. Offshore South East Asia Show. doi:10.2118/8851-ms
- Mitchell, R. F. (1982, October 1). *Buckling Behavior of Well Tubing: The Packer Effect*. Society of Petroleum Engineers. doi:10.2118/9264-PA

- Mohammad, A., & Maung, U. M. (2000, January 1). *The Drilling And Completion Of The First Monobore Well In Peninsular Malaysia*. Society of Petroleum Engineers. doi:10.2118/62773-MS
- Pathy, K. A. T., Kumar, P. A. K., Kaeng, G. C., Mansor, A. B., & Sausan, S. (2016, March 22). *Collaborative Well Planning as a Key to Efficient and Successful Complex Geological Sidetracks Planning And Monitoring in Overpressured Deepwater Environment: A Case Study From Malaysia's Fast-Track Deepwater Well*. Offshore Technology Conference. doi:10.4043/26858-MS
- Raja, H. Z., Carpenter, G. F., & Oliver, D. S. (2011). *Workflows and Methods to Optimize Well Construction through a Collaborative Environment*. SPE Digital Energy Conference and Exhibition. doi:10.2118/143600-ms
- Rosland, H. A., Peytchev, P. A., Sarkar, S., Mukherjee, S., Govind, B., & Malik, S. D. (2010). *Collaborative Well Planning and Optimisation of Well Placement: A Case Study from Mangala Field Development, Rajasthan India*. SPE Oil and Gas India Conference and Exhibition. doi:10.2118/127344-ms
- Samsudin, A. R., & bin Mohamed, M. S. (2001). *Peninsular Malaysia Gas Utilisation Project - Challenges In Gas Supply Planning*. SPE Asia Pacific Oil and Gas Conference and Exhibition. doi:10.2118/68681-ms
- Simonds, R., & Swan, T. (2000, January 1). *Development of a Large-Bore Monobore Completion System for Gas Production*. Society of Petroleum Engineers. doi:10.2118/64279-MS
- Taoutaou, S., Schreuder, R., Bosma, M. G. R., Schoenmakers, J., Vandervegt, R., & Stewart, D. (2007). *New Approach To Ensure Long-Term Zonal Isolation for Land Gas Wells Using Monobore Cemented Completion*. EUROPEC/EAGE Conference and Exhibition. doi:10.2118/107433-ms

Teh, Y. H., Theseira, K., Abdul Karim, A. H., Hashim, N. S., Yakob, A. R., Musa, A. S., Sykahar, M. W. (2008). *Preparing a Gas Field Development Plan: Tangga Barat Cluster Gas Project*. International Petroleum Technology Conference. doi:10.2523/iptc-12488-ms