

INTERPRETATION ON PILE CAPACITY FROM INSTRUMENTED
SACRIFICIAL PILE LOAD TEST FOR DEEP FOUNDATION SYSTEM

NURUL HUSNA BINTI ABDUL RAZAK

A project report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering (Geotechnics)

School of Civil Engineering
Faculty of Engineering
Universiti Teknologi Malaysia

SEPTEMBER 2020

DEDICATION

This master project is dedicated to my outmost supporter of all, my Glorious Allah S.W.T., the Ultimate Helper of all being, The Compassionate and Most Merciful. In all capacity which are truly by Him, I'm trying to realise my little roles in this world on the word of '*iqra*' and '*caliph*' appreciating my tiny existence.

ACKNOWLEDGEMENT

Alhamdulillah, I am very grateful to Allah S.W.T. for His grace and mercy for giving me the strength and will to complete this Master Project. In preparing this project, I was in contact with many people, researchers, academicians, and practitioners. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main master project supervisor, Professor Ir. Dr. Hj. Ramli bin Nazir for encouragement, guidance, critics and constructive comments from beginning until the end of this project. Without his continued advices, support and interest, this master project would not have been the same as presented here.

I am also thankful to Universiti Teknologi Malaysia (UTM) for accepting me as their student which allow me to expose to their credible lecturer and academician where it helps broaden my perspective in engineering especially geotechnical engineering. Their sacrificial time during the tenure has been very fruitful and gratifying.

A special thanks also is dedicated to my beloved family member, who was behind my backbone; in all means is indescribable. My fellow postgraduate student should also be recognised for their support, the sleepless night we go through together are definitely a road of memories to cherish. My sincere appreciation also extends to all my colleagues and others who have provided assistance at various occasions. Their views and tips are useful indeed. Unfortunately, it is not possible to list all of them in this limited space, which I was always indebt of their supportive action directly or indirectly.

ABSTRACT

A deep foundation system often offers a lot of uncertainty even though it is the only option for the demanded highly loaded structure to be able to construct. Hence, to increase the level of confidence in the design, a lot of method and procedure have been established to evaluate the certainty of the pile design. This paper will discuss the prediction of geotechnical capacity of the pile from the instrumented pile load test conducted at very deep strata of more than 30m below ground level in a residual soil originated from the youngest metasedimentary rocks; Kenny Hill formation in Kuala Lumpur area. A sacrificial instrumented pile load test using both traditional static load method which is top-down maintained load test via anchor reaction system and alternative test using bi-directional load test with an axially compressive load are assessed to find and compare the behaviour of the geotechnical pile capacity. The comparison of pile capacity was attempted by using various method of interpretation such as Van der Veen, Chin, Decourt's extrapolation, Fuller and Hoy, Butler and Hoy, De Beer, and the Davisson method. From the study, the method of interpretation has been grouped accordingly namely as mathematical method group by Van der Veen, Chin and Decourt's extrapolation; settlement limitation group by Fuller & Hoy, Butler & Hoy and De Beer; and lastly the graphical construction group by the Davisson method. This grouping method is suggested by Hirany & Kulhawy, 1988. From the study, it can be concluded that the settlement limitation method is the most suitable to be adopted since the result are found consistent in producing the lower bound between three interpretation group. The skin friction evaluation also has been access using the said method and resulted in a good agreement with the pile capacity trend, hence it can be assured that the method of interpretation can be applied to find both total geotechnical capacity and skin friction of the geotechnical parameter in foundation design. In addition, the study has also helped to eliminate the variability of independent factor by having a similar type of sacrificial replacement pile namely barrette pile cast-in situ, cases are using static pile load test with similar axially compressive load and located in the identical region of ground profile. From this, it is found out that both type of pile load test is able to produce identical result irrespective the chosen traditional by head down top load method or even bidirectional method, irrespective the deep strata of soil condition and also irrespective the higher load applied at relatively more than 40MN. The comparison of these interpretation method could help the designers to interpret the most suitable prediction analysis for deep foundation analysis for a more robust and confidence design.

ABSTRAK

Sistem asas dalam sering kali memberikan banyak ketidakpastian walaupun merupakan satu-satunya pilihan untuk membina struktur yang membawa beban yang tinggi. Oleh itu, untuk meningkatkan tahap keyakinan terhadap reka bentuk, banyak kaedah dan prosedur telah dibuat untuk menilai kepastian reka bentuk cerucuk. Kajian ini dilakukan bertujuan membincangkan ramalan kapasiti geoteknik cerucuk dari ujian beban cerucuk berinstrumen yang dilakukan pada strata yang sangat dalam lebih dari 30m di bawah permukaan tanah di tanah baki yang berasal dari batuan metasedimen termuda; Formasi Kenny Hill di kawasan Kuala Lumpur. Ujian beban cerucuk instrumen pengorbanan menggunakan kedua-dua kaedah beban statik tradisional iaitu ujian beban dikekalkan dari atas ke bawah melalui sistem reaksi sauh dan ujian alternatif menggunakan ujian beban dua arah dengan beban mampatan paksi dinilai untuk mencari dan membandingkan tingkah laku cerucuk geoteknik kapasiti. Perbandingan kapasiti cerucuk dicuba dengan menggunakan pelbagai kaedah tafsiran seperti Van der Veen, Chin, ekstrapolasi Decourt, Fuller and Hoy, Butler and Hoy, De Beer, dan kaedah Davisson. Dari kajian tersebut, kaedah pentafsiran telah dikelompokkan dengan tepat iaitu sebagai kumpulan kaedah matematik oleh Van der Veen, Chin dan ekstrapolasi Decourt; kumpulan had enapan oleh Fuller & Hoy, Butler & Hoy dan De Beer; dan terakhir kumpulan pembinaan grafik dengan kaedah Davisson. Kaedah pengelompokan ini disarankan oleh Hirany & Kulhawy, 1988. Dari kajian ini, dapat disimpulkan bahawa kaedah had enapan adalah yang paling sesuai untuk digunakan kerana hasilnya didapati konsisten dalam menghasilkan batas bawah antara tiga kumpulan interpretasi. Penilaian geseran kulit juga dapat dicapai dengan menggunakan metode tersebut dan menghasilkan kesepakatan yang baik dengan tren kapasiti cerucuk, oleh itu dapat dipastikan bahawa kaedah penafsiran dapat diterapkan untuk menemukan kedua-dua kapasiti geoteknikal dan geseran kulit parameter geoteknik dalam reka bentuk asas. Di samping itu, kajian ini juga membantu menghilangkan variabel faktor bebas dengan mempunyai jenis tiang penggantian pengorbanan yang serupa iaitu barrette pile cast-in situ, kes menggunakan ujian beban tiang statik dengan beban mampatan paksi yang serupa dan terletak di kawasan yang sama profil tanah. Dari ini, didapati bahawa kedua-dua jenis ujian beban tiang dapat menghasilkan hasil yang sama tanpa mengira kaedah tradisional dengan kaedah beban atas atau kaedah dua arah, tanpa mengira lapisan tanah yang dalam dan juga tanpa beban yang lebih tinggi yang dikenakan pada lebih daripada 40MN. Perbandingan kaedah tafsiran ini dapat membantu para pereka untuk menafsirkan analisis ramalan yang paling sesuai untuk analisis asas mendalam untuk reka bentuk yang lebih mantap dan yakin.

TABLE OF CONTENTS

	TITLE	PAGE
	DECLARATION	iii
	DEDICATION	iv
	ACKNOWLEDGEMENT	v
	ABSTRACT	vi
	ABSTRAK	vii
	TABLE OF CONTENTS	viii
	LIST OF TABLES	x
	LIST OF FIGURES	xii
	LIST OF ABBREVIATIONS	xvi
	LIST OF SYMBOLS	xviii
	LIST OF APPENDICES	xix
CHAPTER 1	INTRODUCTION	1
	1.1 Overview of Topic	1
	1.2 Problem Background	2
	1.3 Problem Statement	3
	1.4 Research Aims	4
	1.4.1 Research Objectives	4
	1.5 Scope of Work	4
	1.5.1 Limitation of Research	5
	1.6 Expected Finding	5
CHAPTER 2	LITERATURE REVIEW	7
	2.1 Introduction	7
	2.2 Static Load Test	13
	2.3 Pile Capacity	21
	2.4 Mathematical Model	32
	2.4.1 Van Der Veen's Method	32

2.4.2	Chin’s Method	34
2.4.3	Decourt Extrapolation Method	35
2.5	Settlement limits	35
2.5.1	Fuller-Hoy’s Method	36
2.5.2	De Beer’s Method	37
2.5.3	Butler – Hoy’s Method	38
2.6	Graphical Construction Method	39
2.6.1	Davisson’s Method	39
2.7	Continual Method of Pile Load Test Interpretation	41
2.8	Summary	51
CHAPTER 3	RESEARCH METHODOLOGY	53
3.1	Introduction	53
3.1.1	Determining the Study Area	54
3.1.2	Data Collection	56
3.1.2.1	Geological Subsoil Profile and Assessment	56
3.1.2.2	Pile Load Test Data	58
3.1.3	Data Analysis	64
3.1.3.1	Pile capacity	65
3.1.3.2	Skin friction	66
CHAPTER 4	ANALYSIS AND RESULTS	69
4.1	General	69
4.2	Analysis and Evaluation of Load Test Interpretation Method	72
4.3	Summary on Analysis and Evaluation	100
CHAPTER 5	CONCLUSION AND RECOMMENDATIONS	103
5.1	Conclusion	103
5.2	Recommendation	104
REFERENCES		105

LIST OF TABLES

TABLE NO.	TITLE	PAGE
Table 2.1	Minimum loading times for a maintained load compression test (Reproduced from Institution of Civil Engineers (2007) (SPERW, 2007))	14
Table 2.2	Rate of settlement to be used along with minimum hold times (Reproduced from Institution of Civil Engineers (2007) (SPERW, 2007))	14
Table 2.3	Rate of penetration for CRP test according to few code of practice/guideline (excerpt from ICE,2012)	15
Table 2.4	Design Parameter limitation according to Meyerhof	30
Table 2.5	Pile load test methods interpretation methods selected for evaluation (few tabulation excerpts from Karim et. al 2016)	31
Table 2.6	Commentary by Hirany,Kulhawy,1980 on selected interpretation method	49
Table 2.7	Researcher preference on the selected interpretation method Hirany,Kulhawy,1980	50
Table 3.1	Summary of layer of soil for both PTP 1 and PTP 2	57
Table 3.2	Example summary of mobilised skin friction , average SPT-N area and mobilised skin friction factor, k_s	67
Table 3.3	Example summary of average mobilised skin friction factor, k_s	68
Table 4.1	Summary of pile capacity from various method of interpretation	73
Table 4.2	Summary comparison of working load	82
Table 4.3	Summary of mobilised skin resistance (kN/mm^2) from various method of interpretation (PTP-1)	83
Table 4.4	Summary of mobilised skin resistance(kN/mm^2) from various method of interpretation (PTP-2)	84
Table 4.5	Summary of average skin resistance factor, k_s from various method of interpretation (PTP-1)	85
Table 4.6	Summary of average skin resistance factor, k_s from various method of interpretation (PTP-2)	85

Table 4.7	Comparison on interpreted skin friction over 2N for PTP-1	86
Table 4.8	Comparison on interpreted skin friction over 2N for PTP-2	93

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
Figure 2.1	Illustration of bearing pile (Tomlinson,2008)	7
Figure 2.2	a. Smaller scale rapid pile load test using a crawler mounted system; b. Larger scale of rapid pile load test with attendance crane (Federation of Piling Specialists (FPS) (2006))	9
Figure 2.3	a. Static pile load test using Kentledge system; b. Static pile load test using reaction system (Federation of Piling Specialists (FPS) (2006))	9
Figure 2.4	Load train (Federation of Piling Specialists (FPS) (2006))	9
Figure 2.5	Series of stress wave data by rapid pile load test. ICE,Brown et al. (2006).	10
Figure 2.6	Comparison of load-settlement graph between rapid pile load test (Statnamic in loading cycles) and static load test (CRP and MLT) Reproduced from ICE,Brown et al. (2006).	11
Figure 2.7	Schematic of the stress wave travel in a pile ICE,Brown et al. (2006).	11
Figure 2.8	Example of static load test arrangement via reaction pile (Ishibashi,2015)	15
Figure 2.9	Example of typical installation of O-cell/ hydraulic jack cast inside the pile	16
Figure 2.10	Example of typical bi-directional pile load test arrangement (Federation of Piling Specialists (FPS) (2006))	17
Figure 2.11	Typical classification behaviour of load settlement relationship using resistance versus movement plot (Fellinius,2017).	19
Figure 2.12	Example on the searching of secant stiffness of concrete(Fellinius,2017).	19
Figure 2.13	Example on the searching of tangent modulus of concrete (Fellinius,2017).	21
Figure 2.14	Illustration of derivation on geotechnical capacity for a pile.	24
Figure 2.15	Example of Van Der Veen method of interpretation	33

Figure 2.16	Example of Chin method of interpretation for ultimate pile capacity	34
Figure 2.17	Example of Decourt Exploration method of interpretation for ultimate pile capacity	35
Figure 2.18	Example of Fuller and Hoy method of interpretation for ultimate pile capacity	37
Figure 2.19	Example of De Beer method of interpretation for ultimate pile capacity	38
Figure 2.20	Example of Butler Hoy method of interpretation for ultimate pile capacity	39
Figure 2.21	Example of Davisson method of interpretation for ultimate pile capacity showing the elastic line	40
Figure 2.22	The typical load settlement curve for pile load test (Hirany, 1988)	41
Figure 2.23	The typical stress-strain curve in working stress method	42
Figure 2.24	Simulation on bias of absolute settlement limit upon variation of stiff and Soft load-settlement curve	44
Figure 2.25	Example of settlement per unit load interpretation	45
Figure 2.26	The improve graphical construction method using tangent intersection method	48
Figure 3.1	Methodology flowchart	53
Figure 3.2	Formation class for Kuala Lumpur geological stratigraphy(Kuala Lumpur topography map Series L7010 Sheet 94 (National Mapping Malaysia, 1974)	54
Figure 3.3	Kuala Lumpur topography map Series L7010 Sheet 94 (National Mapping Malaysia, 1974)	55
Figure 3.4	Reference borehole for PTP 1 (NCBH 102) and PTP 2 (NCBH 105)	57
Figure 3.5	Plan view of the configuration maintain pile for load test using anchor reaction system	59
Figure 3.6	Section A-A view of the configuration maintain pile for load test using anchor reaction system	60
Figure 3.7	Installation of O-cell/ hydraulic jack inside the reinforcement bar casing of barrette pile	61
Figure 3.8	Instrumented level of strain gauge versus the soil profile	62
Figure 3.9	The strain gauge load distribution	62

Figure 3.10	Load settlement graph	63
Figure 3.11	Bi-directional pile load test instrument device orientation layout plan	64
Figure 3.12	Example of skin friction (2N vs interpretation) graph	68
Figure 4.1	Load settlement relationship for PTP-1	69
Figure 4.2	Load settlement relationship for PTP-2	70
Figure 4.3	Comparison of equivalent load settlement between bi-directional and traditional maintain load test	71
Figure 4.4	Pile capacity using Van Der Veen method (PTP-1)	73
Figure 4.5	Pile capacity using Chin method (PTP-1)	74
Figure 4.6	Pile capacity using Decourt Exploration method (PTP-1)	74
Figure 4.7	Pile capacity using Fuller Hoy method (PTP-1)	75
Figure 4.8	Pile capacity using De Beer method (PTP-1)	75
Figure 4.9	Pile capacity using Butler Hoy method (PTP-1)	76
Figure 4.10	Pile capacity using Davisson method (PTP-1)	76
Figure 4.11	Pile capacity using Van Der Veen method (PTP-2)	77
Figure 4.12	Pile capacity using Chin method (PTP-2)	77
Figure 4.13	Pile capacity using Decourt Exploration method (PTP-2)	78
Figure 4.14	Pile capacity using Fuller Hoy method (PTP-2)	79
Figure 4.15	Pile capacity using De Beer method (PTP-2)	79
Figure 4.16	Pile capacity using Butler Hoy method (PTP-2)	80
Figure 4.17	Pile capacity using Davisson method (PTP-2)	80
Figure 4.18	Illustration of area of SPT-N and hydraulic jack/O-cell location	82
Figure 4.19	PTP-1 Skin friction (2N vs Van der Veen interpretation) graph	86
Figure 4.20	PTP-1 Skin friction (2N vs Chin interpretation) graph	87
Figure 4.21	PTP-1 Skin friction (2N vs Decourt Exploration interpretation) graph	88
Figure 4.22	PTP-1 Skin friction (2N vs Fuller Hoy interpretation) graph	89
Figure 4.23	PTP-1 Skin friction (2N vs De Beer interpretation) graph	90

Figure 4.24	PTP-1 Skin friction (2N vs Butler Hoy interpretation) graph	91
Figure 4.25	PTP-1 Skin friction (2N vs Davisson interpretation) graph	92
Figure 4.26	PTP-2 Skin friction (2N vs Van der Veen interpretation) graph	93
Figure 4.27	PTP-2 Skin friction (2N vs Chin interpretation) graph	94
Figure 4.28	PTP-2 Skin friction (2N vs Decourt Exploration interpretation) graph	95
Figure 4.29	PTP-2 Skin friction (2N vs Fuller Hoy interpretation) graph	96
Figure 4.30	PTP-2 Skin friction (2N vs De Beer interpretation) graph	97
Figure 4.31	PTP-2 Skin friction (2N vs Butler Hoy interpretation) graph	98
Figure 4.32	PTP-2 Skin friction (2N vs Davisson interpretation) graph	99

LIST OF ABBREVIATIONS

A_b	-	Area of pile base
A_c	-	Cross-sectional area of concrete
A_s	-	Area of pile shaft
A_{st}	-	Cross-sectional area of steel
ASSHTO	-	American Association of State Highway and Transportation Officials
ASTM	-	American Standard Testing Method
BS	-	British Standard
CRP	-	Cone Rate Penetration
CIRIA	-	Construction Industry Research and Information Association
DVL	-	Design Verification Load
E_c	-	Concrete modulus
E_s	-	Young's modulus of elastic in steel
E_{total}	-	Total modulus
f_{cu}	-	Characteristic strength of concrete
FHWA	-	Federal Highway Administration, United States of America
FS_b	-	Design safety factor for Base resistance, minimum 3.0
FS_s	-	Design safety factor for Shaft resistance, minimum 2.0
ICE	-	Institution of Civil Engineers, United Kingdom
JKR	-	Jabatan Kerja Raya Malaysia
K_b	-	Coefficient of base resistance factor
K_s	-	Coefficient of shaft resistance factor
N_s	-	N values along the pile shaft from Standard Penetration Test
N_b	-	N values at pile base from Standard Penetration Test
m	-	meter
mbgl	-	Meter below ground level
mm	-	millimeter

mRL	-	Meter reduced level
MLT	-	Maintain Load Test
MPa	-	MegaPascal
PTP	-	Preliminary Test Pile
O-cell	-	Osterberg cell
Q_b	-	Ultimate end bearing resistance
Q_{ps}	-	Positive ultimate skin friction resistance
Q_{ult} , P_{ult}	-	Ultimate pile capacity
SPERW	-	Specification for Piling and Embedded Retaining Walls
SPT	-	Standard Penetration Test
SS CP4	-	Singapore Standard Code of Practice 4
SWL	-	Specified working Load
UTM	-	Universiti Teknologi Malaysia
WL	-	Design Resistance of Single Pile

LIST OF SYMBOLS

δ	-	Displacement,differential
ε	-	Stran
σ	-	Stress,load
A	-	Area
D	-	Diameter
E	-	Young's modulus
L	-	length
P	-	Load

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
Appendix A	Design Consideration with Respect to Type Of Piles (Excerpts from JKR Guidelines for Piling Works,2017)	109
Appendix B	Maximum Load Criteria for Axial Compression Test (Excerpts from Hirany and Kulhawy 1988)	110

CHAPTER 1

INTRODUCTION

1.1 Overview of Topic

Throughout the history of engineering, founding a structure are always divided into two categories which is shallow foundation and deep foundation. During the design stage, the soil-structure interaction between the structural capacity of the founding structure and geotechnical capacity of the founding strata need to be scrutinized in order to have a more reliable, economical and robust design.

More often, the geotechnical capacity which comprises of skin resistance and end bearing are more critical where the certainty of the soil performance in the subsurface are more complex in a confined space underneath the ground. To cater this, the verification of the geotechnical parameters is introduced using in-situ soil testing. For a pile foundation, in-situ pile load test is commonly selected to justify the design assumption which could be tested on both whether on working pile or preliminary pile. However, as the pile load test is an in-situ test, the interpretation of the result would be vary considering the uncertainty of the ground response or behaviour, hence even though few methods currently available to interpret the result obtain, the end results still occupied at least only three quarter of design conformance. Hence, in this study, the comparison on the interpretation of maintain load test will be investigated to find a trend that suit a more reliable pile test interpretation for a residual soil overlying highly weathered limestone of Kenny Hill formation in Kuala Lumpur, Malaysia.

1.2 Problem Background

According to British Standard BS 8400, pile load test generally was made in purpose on finding the expected load-settlement behaviour or even determining the ultimate bearing capacity of the pile. Loading tests on pile can be classified either by static load test or by dynamic load tests. The static pile load test is conducted at low strain where the loading rate may have taken more than 24 hours which takes longer time than the dynamic pile load test, which is conducted at considerably higher strain. Dynamic pile load test consists of estimating soil resistance and its distribution from force and velocity measurements obtained near the top of a pile by impacting a hammer or drop weight as a simulation of loading rate hence the result obtain is more immediate (Hussein et.al. 2012).

While, for a static load test, several subdivisions of the test can be further categorized based on type of load imposed to i.e (compression load, tension load or lateral load). A compression load which normally be applied vertically to represent load transfer from the above superstructure to foundation are the most common pile load test adopted in the industry currently. It is also known that the pile load test using compression load also have developed into few methods of implementation namely statically vertical maintain load test, quick maintained load test, cone rate penetration and also bi-directional pile load test. Each method is unique on their own and the designer should use their sound engineering judgement to choose the suitable method to suit their objective. A conventional maintain load test is always come in a costly and timely consuming rather than dynamic pile load test, hence, the choice of the pile load test procedure relatively concurs due to many reasons.

There are two type of maintained pile load test that will be study which is Maintained pile load test via reaction pile and bi-directional pile load test. Both tests are using the same dimension of pile test which is barrette pile of a size 2.8m width and 1.5m breadth. These instrumented pile load tests are simulated for a replacement type of pile which taking a pile load test at almost three times working load of 57,300 kN for PTP-1 and 48,879kN for PTP-2 respectively. The test is meant for a pile to load until failure by assuming a test load of almost three times working load. The pile length

for PTP-1 which are using bi-directional test is 57.5m while for PTP-2 using static load test by anchor reaction system, the pile length is 27.3m respectively. These pile tests are conducted in a residual soil overlying limestone bedrock with a layer of highly weathered limestone interfacing both layers.

1.3 Problem Statement

In construction works, to substantiate the piling work for structure with high loading in difficult ground condition often require either greater penetration length of pile or a total of summation of high amount of pile group. This is relatively not probable for a constraint workspace especially in term of construction mobilisation accessibility where the activity may require more space to place a huge or numerous numbers of machinery to accommodate the longer pile length. Greater penetration length of pile use in the design may also post a query on the reliability of the design whether it is design in an overly conservative approach. Hence, to cater this issue, pile test usually would be conducted to verify the design even though the cost incurred is high for a short term finding, but in term of overall cost of the design, it is very prudent to conduct pile test for a greater saving on the whole project. As such, once a pile test result is obtained, the interpretation of the result is another set of challenge. Often, the interpretation of the result is aiming to find the geotechnical capacity of the test field. The interpretation can be in term of many approach available in the literature which will give a misperception of which method is the best to be adopted. This study aims to find the suitability of different method of pile load test interpretation for a deep pile with layer of soil containing a range of residual soil and highly weathered limestone.

1.4 Research Aims

This research aims to study the interpretation of static pile load test namely maintained load test and bi-directional load test with respect to Kenny Hill geological formation of Kuala Lumpur on sacrificial barrette pile using various method of interpretation. The interpretation will cover all three type of method of interpretation which is mathematical model, settlement limitation and graphical construction.

1.4.1 Research Objectives

The objectives of the research are:

- a. To determine the pile capacity of the pile load test using various method of interpretation
- b. To determine the mobilised skin friction of the pile load test using various method of interpretation
- c. To evaluate the suitable method in interpretation of pile capacity and skin friction

1.5 Scope of Work

The study is carried out based on Maintain Load Test (MLT) using anchor reaction and Bi directional with single layer of O-cell. The load test is performed for axially loaded compression piles up to some pre-assigned load cycle or load up to failure. The chosen pile is barrette pile where it can be grouped as replacement pile. The case area for this study is residual soil in Kenny Hill formation of Kuala Lumpur, Malaysia which is one of the major geological formation of Kuala Lumpur particularly where the geological stratigraphy could also be classified under a group of sedimentary rock formation.

1.5.1 Limitation of Research

The following limitation used in this study also listed as below:

- (a) The field subsurface of this study is classified as residual soil which originated from limestone; also known as Kenny Hill formation, the youngest known metasedimentary rocks in Kuala Lumpur area.
- (b) The method of interpreting the pile load test data is by empirical methods such as Van der Veen, Chin, Decourt's extrapolation, Fuller and Hoy, Butler and Hoy, De Beer, and the Davisson method
- (c) The comparison of the interpretation will be limited to the method used in this study
- (d) This study will look into the skin friction only.

1.6 Expected Finding

The expected finding in this study is to generate a pile capacity and mobilised skin friction from the interpretation method. The result will then be compared to find the most suitable interpretation method for a deep replacement pile casted in a layer of soil containing a range of residual soil and highly weathered limestone in Kuala Lumpur, Malaysia.

REFERENCES

- AASHTO, "Load and Resistance Factors Design (LRFD) Bridge Design Specifications", Section 10: Foundations, 2007.
- ASTM D-1143/D1143M, 2007, "Standard Test Methods for Deep Foundations under Static Axial Compressive Load".
- ASTM D 1143-81, 1994, "Standard Test Method for Piles under Static Axial Compressive Load".
- ASTM D1143 - 07(2013) Standard Test Methods for Deep Foundations Under Static Axial Compressive Load
- ASTM D8169 Standard Test Methods for Deep Foundations Under Bi-Directional Static Axial Compressive Load
- ASTM D 3689-90, 1995, "Standard Test Method for Individual Piles Under Static Axial Tensile Load".
- ASTM D 3966-90, 1995, "Standard Test Method for Piles Under Lateral Loads".
- ASTM D 3966-07, 2007: Standard Test Methods for Deep Foundations Under Lateral Load, American Society for Testing and Materials, Philadelphia.
- Birid, Kedar. (2017). Evaluation of Ultimate Pile Compression Capacity from Static Pile Load Test Results. 1-14. 10.1007/978-3-319-61642-1_1.
- Brown, M. (2012). Chapter 98 Pile capacity testing. In ICE manual of geotechnical engineering (pp. 1451-1469). Thomas Telford Ltd.
- BS8004 (1986), Code of Practice for Site Investigation, British Standard Institution, London.
- Butler, H.D. and Hoy, H.E., 1977, "User's Manual for the Texas Quick Load Method for Foundation Load Testing", FHWA, Office of Development, Washington, D.C., FHWA-IP-77-8, pp. 59.
- Chin, F.K., 1970, "Estimation of Pile Not Carried to Failure", Proceedings 2nd Southeast Asian Conference on Soil Engineering, Singapore, pp. 81-90.
- Davisson, M.T., "High capacity piles" Proc. Innovations in Foundation Construction, ASCE, Illinois Section, 1972, 52p.

- Decourt, L., 1999, "Behavior of Foundations Under Working Load Conditions", Proc. of the 11th Pan-American Conf. on Soil Mechanics and Geotechnical Engineering, Dolguassu, Brazil, V. 4, pp. 453-488.
- De Beer, E.E. and Wallays, M., 1989, "Franki Piles with Over expanded Bases", La Technique des Travaux, No:333, pp. 48.
- Eurocode 7: Geotechnical design - Part 1: General rules EN 1997-1:2004
- England, M. and Cheeseman, P. (2010). Design benefits of bi-directional load testing of barrettes. In Proceedings of the 11th International Conference on Piling and Deep Foundations, 26–28 May 2010, London, UK.
- Federation of Piling Specialists (FPS) (2006). Handbook on Pile Load Testing. Kent, UK: FPS, www.fps.org.uk
- Fellenius, B.H., Riker, R. E., O'Brien, A. J. and Tracy, G. R., 1989. Dynamic and static testing in a soil exhibiting setup. ASCE Journal of Geotechnical Engineering, 115(7) 984-1001.
- Fellenius, B. (2017). Basics of foundation design.
- FHWA Brown, D. A., Turner, J. P., Castelli, R. J., & Americas, P. B. (2010). Drilled shafts: Construction procedures and LRFD design methods (No. FHWA-NHI-10-016). United States. Federal Highway Administration.
- FHWA Hannigan, P. J., Rausche, F., Likins, G. E., Robinson, B., Becker, M., & Berg, R. R. (2016). Design and construction of driven pile foundations—Volume I (No. FHWA-NHI-16-009). National Highway Institute (US).
- Fleming, K., Weltman, A., Randolph, M., & Elson, K. (2009). Piling engineering. (3rd ed.), Taylor and Francis, Oxon .
- Frank, R. (2004). Designers' guide to EN 1997-1 Eurocode 7: Geotechnical design- General rules (Vol. 17). Thomas Telford.
- Fuller, F.M. and Hoy, H.E., 1970, "Pile Load Tests Including Quick Load Test Method Conventional Methods and Interpretations", Highway Research Record No.333, pp. 78-89, Transportation Research Board, USA.
- GEO (Geotechnical Engineering Office Hong Kong). (2006). Foundation design and construction.
- Hirany A. and Kulhawy F. H., “Conduct and interpretation of load tests on drilled shaft foundations” Research Project Final Report EL-5915, Vol. 1, 1988, Cornell University.

- Hussein, M. H., McGillivray, R. T., & Brown, D. A. (2012). Knowledge is Bliss-A Case for Supplemental Pile Testing to Ascertain Fidelity. In *Full-Scale Testing and Foundation Design: Honoring Bengt H. Fellenius* (pp. 322-332).
- Institution of Civil Engineers (ICE) (2007). *ICE Specification for Piling and Embedded Retaining Walls (SPERW)* (2nd edition). London: Thomas Telford.
- Ishibashi, I., & Hazarika, H. (2015). *Soil mechanics fundamentals and applications*. CRC Press.
- Jabatan Kerja Raya (JKR) Malaysia. (2017). *Guidelines for Piling Works*. Unit Kejuruteraan Geoteknik,CPKA Kuala Lumpur: JKR Publication
- Karim, A., Zein, M., & Ayoub, E.M. (2016). Evaluation Of Measured And Interpreted Failure Loads Of Bored Piles In Alluvial Soil Deposits. *International Journal of Geomate*, 10, 1636-1643.
- Kondner R. (1963). Hyperbolic Stress-Strain Response of Cohesive Soils, *J of SMFD*, ASCE, Vol.89, SM1, pp. 115-143.
- Malaysian Standard MS 1756:2004: Code of Practice of Foundations.
- Meyerhof G.G. (1956), Penetration Test and Bearing Capacity of Cohesionless Soil, *Soil Mech. Found. Vol. 82*
- Meyerhof G.G., Bearing Capacity and Settlement of Pile Foundations, *ASCE J. of Geotechnical Eng.*, 1976, GT3, 195–228.
- NeSmith W. and Siegel, T. (2009) Shortcomings of the Davisson Offset Limit Applied to Axial Compressive Load Tests on Cast-in-Place Piles. *Proceedings of Contemporary Topics in Deep Foundations, International Foundation Congress and Equipment Expo 2009, Orlando, Florida, United States, March 15-19, 2009*, pp. 568-574.
- Olgun, Murat & Hanati, & Yenginar, Yavuz. (2017). Prediction of Pile Capacity from Field Loading Test Results by Using Different Methods.
- Randolph, M. F. (2003). Science and empiricism in pile foundation design. *Géotechnique* 53(10), 847–875. DOI: 10.1680/ geot.53.10.847.37518.
- Rybak, J., & Król, M. (2018). Limitations and risk related to static capacity testing of piles–“unfortunate case” studies. In *MATEC Web of Conferences* (Vol. 146, p. 02006). EDP Sciences.
- Standard, S. (2003). *Code of practice for foundations*. CP4: 2003.
- Terzaghi, K. and Peck, R. B. (1967). *Soil mechanics in engineering practice*, 2nd Ed., Wiley, New York.

Tomlinson, M. J., & Boorman, R. (2001). Foundation design and construction. (7th Edition). Pearson education

Tomlinson, M. and Woodward, J. (2008). Pile Design and Construction Practice (5th Edition). London: Taylor & Francis.