

HYDROGEN PRODUCTION FROM SEWAGE SLUDGE VIA UPDRAFT
GASIFICATION PROCESS IN A BENCH – SCALE FIXED BED REACTOR

NUR FATIN AIMILIA BINTI ROZUKI

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Master of Philosophy

School of Chemical and Energy Engineering
Faculty of Engineering
Universiti Teknologi Malaysia

SEPTEMBER 2019

DEDICATION

Specially dedicated to my beloved parents
(Rozuki Bin Abdullah and Tina Binti Zainal Abidin)
who have been an inspiration to me

ACKNOWLEDGEMENT

Alhamdulillah, praise to Allah the Almighty for giving me strength to accomplish my master research successfully. A special thanks to my supervisor, Dr. Norazana Binti Ibrahim for her kindness and guidance throughout my entire research. She encouraged me by her positive advices and academic supports during my master period.

My sincere appreciation also extends to Gas Combustion Laboratory Instructor, En. Jamal Asri Bin Othman who has been one of the great support to me in my research. His friendly and helpful personality has always created a positive atmosphere and motivated me to work. In this opportunity also, I would like to thank all the lectures and staffs in School of Chemical and Energy Engineering, Faculty of Engineering, Universiti Teknologi Malaysia for their invaluable assistance. I am indebted to Universiti Teknologi Malaysia for providing research grants for smooth research progress.

Last but not least, I would like to thank my best friends for their great support during my research. Their views and tips are useful indeed. My thanks also goes to my parents for their blessings and encouragements throughout my life.

ABSTRACT

Sewage sludge, the solid waste produced from the municipal wastewater treatment plant has created environmental problem due to continuous increasing number of sewage sludge production. Thus, finding solutions for sewage sludge treatment and discharge are essential, to address the issues. Nowadays, the utilization of sewage sludge as solid fuel for energy recovery is one of the convenient solutions to improve waste management system whilst the gasification is one of the preferable thermochemical conversion process to convert the sewage sludge to higher yield of combustible light gases due to its simple and efficient process. Therefore, this study focuses on the conversion of sewage sludge into energy via updraft gasification process and to investigate the performance of the fixed bed gasifier ($L = 1.549$ m, $D = 0.114$ m) for maximum production of hydrogen and total syngas yield (H_2 , CH_4 , CO , CO_2 and N_2). The reactor temperature was ranged between 600 to 900°C with equivalence ratio (ER) of 0.10 to 0.20, with different gasifying agents i.e. air and steam. The produced syngas at different operating conditions was collected using gas sample bag and analysed using residual gas analyzer to identify the syngas yield. Results showed that the maximum hydrogen yield of 3.18 % was obtained at 800°C with ER of 0.20 while optimum total syngas yield was obtained at 63.43 % for 800°C and ER of 0.15. For comparison, the steam gasification was also was carried out and it was found that 4.40 % and 70.40 % was observed for maximum hydrogen yield and optimum total syngas yield, respectively. Further, the effect of gasifying agent on total syngas yield was found to be higher for air gasification at reactor temperature of 600 and 700°C while at 800 and 900°C, the total syngas yield was found to be higher for steam gasification. It can be said that steam gasification gives more H_2 yield (> 2.4 %) than air gasification. In conclusion, energy recovery from sewage sludge can be utilized by using gasification process, and thus, minimizing the environmental pollution. In addition, the produced syngas from these processes has a potential to be used for heat and power generation application.

ABSTRAK

Enap cemar kumbahan, sisa pepejal dihasilkan daripada loji olahan air sisa perbandaran menghasilkan masalah alam sekitar disebabkan peningkatan berterusan jumlah pengeluaran enap cemar kumbahan. Oleh itu, mencari penyelesaian untuk rawatan dan pembuangan enap cemar kumbahan adalah penting untuk menangani isu – isu tersebut. Pada masa kini, penggunaan enap cemar kumbahan sebagai bahan api pepejal untuk perolehan tenaga adalah salah satu penyelesaian mudah untuk memperbaiki sistem pengurusan sisa, sementara penggasan adalah salah satu proses penukaran termokimia yang lebih baik untuk menukar enap cemar kumbahan kepada hasil lebih tinggi untuk gas ringan mudah terbakar kerana prosesnya mudah dan cekap. Oleh itu, kajian ini memberi tumpuan kepada penukaran enap cemar kumbahan kepada tenaga melalui proses penggasan arus menaik dan mengkaji prestasi penggas lapisan tetap ($P = 1.549$ m, $D = 0.114$ m) untuk pengeluaran hidrogen maksimum dan jumlah hasil singas (H_2 , CH_4 , CO , CO_2 and N_2). Suhu reaktor ditetapkan pada julat antara 600 hingga 900°C dengan nisbah kesetaraan (ER) antara 0.10 hingga 0.20, dengan agen penggasan berbeza iaitu udara dan wap. Singas yang dihasilkan pada keadaan operasi yang berbeza telah dikumpulkan menggunakan beg sampel gas dan telah dianalisis menggunakan penganalisis gas sisa untuk menentukan hasil singas. Keputusan menunjukkan bahawa hasil hidrogen maksimum iaitu 3.18 % telah diperolehi pada 800°C dengan ER bersamaan 0.20 manakala jumlah hasil singas optimum telah diperolehi pada 63.43% untuk 800°C dan ER bersamaan 0.15. Untuk perbandingan, penggasan wap juga telah dijalankan dan mendapati bahawa 4.40 % and 70.40 % telah diperolehi masing – masing untuk hasil hidrogen maksimum dan jumlah hasil singas optimum. Selanjutnya, kesan agen penggasan pada jumlah hasil singas telah didapati lebih tinggi untuk penggasan udara pada suhu reaktor 600 and 700°C manakala pada 800 dan 900°C, jumlah hasil singas telah didapati lebih tinggi untuk penggasan wap. Boleh dikatakan bahawa penggasan wap memberi lebih banyak hasil H_2 ($> 2.4\%$) daripada penggasan udara. Kesimpulannya, tenaga daripada enap cemar kumbahan boleh digunakan dengan menggunakan proses penggasan, dan dengan itu, meminimumkan pencemaran alam sekitar. Tambahan lagi, singas yang dihasilkan daripada proses ini mempunyai potensi untuk digunakan untuk aplikasi penjanaan haba dan kuasa.

TABLE OF CONTENTS

	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATIONS	xii
	LIST OF SYMBOLS	xiv
	LIST OF APPENDICES	xv
CHAPTER 1	INTRODUCTION	1
	1.1 Research Background	1
	1.2 Problem Statement	4
	1.3 Research Objectives	5
	1.4 Research Scopes & Limitations	5
	1.5 Significant of Study	6
	1.6 Thesis Organization	7
CHAPTER 2	LITERATURE REVIEW	9
	2.1 Introduction	9
	2.2 Overview of Gasification Process	9
	2.3 Gasification Principles	13
	2.3.1 Drying	13
	2.3.2 Pyrolysis	14
	2.3.3 Oxidation	15
	2.3.4 Reduction	16

2.4	Overview of Utilization of Sewage Sludge in Malaysia	16
2.5	Gasification of Sewage Sludge	18
2.6	Types of Gasifier	23
	2.6.1 Updraft Fixed Bed Gasifier	23
	2.6.2 Downdraft Fixed Bed Gasifier	25
2.7	Types of Gasifying Agent	27
	2.7.1 Air	29
	2.7.2 Steam	30
2.8	Factors Affecting the Gasification Process	33
	2.8.1 Reactor Temperature	33
	2.8.2 Equivalence Ratio	34
	2.8.3 Steam to Biomass Ratio	35
	2.8.4 Feedstock Particle Size	36
	2.8.5 Feedstock Moisture Content	37
2.9	Summary	41
CHAPTER 3	METHODOLOGY	43
3.1	Introduction	43
3.2	Sewage Sludge Preparations and Characterizations	43
3.3	Gasification Facility and Operation	45
3.4	Gasification Experiments and Procedures	48
	3.4.1 Air Gasification Experiments	48
	3.4.2 Steam Gasification Experiments	50
3.5	Syngas Characterizations	52
CHAPTER 4	RESULTS AND DISCUSSION	55
4.1	Introduction	55
4.2	The Characteristics of Sewage Sludge	55
4.3	Air Updraft Gasification of Sewage Sludge	58
	4.3.1 The Effect of Reactor Temperature on Production of Syngas	58
	4.3.2 The Effect of Equivalence Ratio on Production of Syngas	62

4.4	Steam Updraft Gasification of Sewage Sludge	65
4.4.1	The Effect of Reactor Temperature on Production of Syngas	65
4.5	Comparison of Air and Steam Updraft Gasification of Sewage Sludge	69
4.6	Summary	73
CHAPTER 5	CONCLUSION AND RECOMMENDATION	75
5.1	Conclusion	75
5.2	Recommendations	76
REFERENCES		77

LIST OF TABLES

TABLE NO.	TITLE	PAGE
Table 2.1	Biomass category (Halder, Paul and Beg, 2014)	11
Table 2.2	Different studies of gasification using various type of biomass	12
Table 2.3	Summary of literature on the gasification of sewage sludge	22
Table 2.4	Name of the ratio for different gasifying agents (Couto <i>et al.</i> , 2013)	27
Table 2.5	Advantages of different types of gasifying agent (Sansaniwal, Rosen and Tyagi, 2017)	28
Table 2.6	Gasification process of different types of the gasifying agent (Wang <i>et al.</i> , 2008)	29
Table 2.7	Summary of literature on the air and steam gasification	32
Table 2.8	Summary of literature on the factors affecting the gasification process	39
Table 3.1	Gasifier technical specifications	46
Table 3.2	List of air gasification experiments	49
Table 3.3	List of steam gasification experiments	51
Table 4.1	Characteristics of sewage sludge	56

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
Figure 2.1	Green technology applications (IWK, 2014)	17
Figure 2.2	Schematic view of (a) updraft (b) downdraft fixed bed gasifier (Couto <i>et al.</i> , 2013)	25
Figure 3.1	Operational framework	44
Figure 3.2	Naturally dried sewage sludge on a sludge drying bed	45
Figure 3.3	Schematic diagram of the gasification unit	47
Figure 3.4	Residual Gas Analyzer Model Cirrus 2 (MKS Instruments, MA, USA)	53
Figure 4.1	The effect of reactor temperature on total syngas yield via air updraft gasification at fixed ER of 0.15	59
Figure 4.2	The effect of reactor temperature on syngas composition via air updraft gasification at fixed ER of 0.15	60
Figure 4.3	The effect of equivalence ratio on total syngas yield via air updraft gasification at fixed reactor temperature of 800°C	62
Figure 4.4	The effect of equivalence ratio on syngas composition via air updraft gasification at fixed reactor temperature of 800°C	63
Figure 4.5	The effect of reactor temperature on total syngas yield via steam updraft gasification at fixed S/B of 1.09	66
Figure 4.6	The effect of reactor temperature on syngas composition via steam updraft gasification at fixed S/B of 1.09	67
Figure 4.7	The effect of gasifying agent on total syngas yield (included syngas composition) via updraft gasification at fixed ER of 0.15 for air gasification and at S/B of 1.09 for steam gasification	70
Figure 4.8	The effect of gasifying agent on hydrogen yield via updraft gasification at fixed ER of 0.15 for air gasification and S/B of 1.09 for steam gasification	72

LIST OF ABBREVIATIONS

amu	-	Atomic mass units
C	-	Carbon content
CH ₄	-	Methane
CO	-	Carbon monoxide
CO ₂	-	Carbon dioxide
d.b. wt. %	-	Dry basis by weight percent
daf	-	Dry ash-free basis
DOE	-	Department of Environment
ER	-	Equivalence ratio
GC-MS	-	Gas Chromatography – Mass Spectrometry
GCV	-	Gross calorific value
GR	-	Gasifying ratio
H	-	Hydrogen content
H ₂	-	Hydrogen
H ₂ O	-	Water vapour
HC	-	Hydrocarbon
HHV	-	Higher heating value
IC	-	Internal combustion
LHV	-	Lower heating value
MFC	-	Mass flow controller
N ₂	-	Nitrogen
na	-	Not available
NO _x	-	Nitrogen oxides
O ₂	-	Oxygen
PAHs	-	Polycyclic aromatic hydrocarbons
PCBs	-	Polychlorinated biphenyls
RDF	-	Refuse Derived Fuel
RGA	-	Residual Gas Analyzer
S	-	Sulphur content
S/B	-	Steam to biomass ratio
SO _x	-	Sulphur oxides
SS	-	Sewage sludge
STP	-	Sewage treatment processes

SWPCM	-	Solid Waste and Public Cleansing Management
TGA	-	Thermogravimetric analyzer
V	-	Valve
w.b. wt. %	-	Wet basis by weight percent

LIST OF SYMBOLS

%	-	Percentage
% pp	-	Partial pressure percentage
% vol	-	Volume percentage
$m_{H_2O(g)}$	-	Produced water vapour mass
$m_{H_2O(l)}$	-	Moisture content mass in feedstock
~	-	Approximate
<	-	Less than
°C	-	Degree Celsius
bar (g)	-	bar (gauge)
g/g SS daf	-	Gram of gasifying agent mass flow per gram of dry ash-free basis sewage sludge mass flow
g/min	-	Gram per minute
in.	-	Inches
kg/h	-	Kilogram per hour
kg/p.e/year	-	Kilogram per population equivalent per year
kJ/mol	-	Kilo Joule per mole
L	-	Litre
m^3 STP/kg SS daf	-	Standard temperature and pressure cubic meter per kilogram of dry ash-free basis sewage sludge
MJ/kg	-	Mega Joule per kilogram
MJ/m ³	-	Mega Joule per cubic meter
MJ/Nm ³	-	Mega Joule per normal cubic meter
mTorr	-	milliTorr
MW	-	Megawatt
sccm	-	Standard cubic centimetre per minute
V	-	Volt

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
Appendix A	Sample Calculation of Total Syngas Yield and Syngas Composition	88

CHAPTER 1

INTRODUCTION

1.1 Research Background

Thermochemical and biochemical processes are the two conversion processes that convert biomass to energy. A thermochemical process is the implementation of heat together with chemical processes to produce energy products from biomass while a biochemical process is the involvement of enzymes, bacteria and other microorganisms to produce liquid fuels by breaking down biomass chemical structures. Although biochemical process can generate energy but thermochemical process have some advantages over biochemical process. Thermochemical process allows an extensive range of feedstock while biochemical processes only allows certain type and quality of feedstock. Even though biochemical process or also known as enzymatic process is highly developed but it is still operate in batch process and time consuming. In addition, other advantages of the thermochemical process are that its overall efficiency is higher and the cost of production is lower (Balat and Kirtay, 2010). These reasons caused researchers to work more on thermochemical process for production of energy from biomass.

Techniques of thermochemical process include combustion, pyrolysis and gasification. These techniques are available for the production of secondary fuels (Parthasarathy and Narayanan, 2014). The most common technique for woody biomass is combustion and the process takes place in an oxygen sufficient quantity environment to fully oxidise the fuel for the production of heat energy. Another biomass conversion technique to produce useful products is pyrolysis and the process takes place in the absence of oxygen environment by thermal degradation of a substance to produce bio fuels which are used for transportation and related applications. On the other hand, gasification process takes place in an oxygen insufficient quantity environment or also known as partial oxidation process to allow

the fuel to be partially oxidised. Through this technique, both power and heat generation conditions can be met more efficiently, effectively and eco-friendly (Sansaniwal *et al.*, 2017).

During biomass gasification process, biomass is converted in a gasifier into a mixture of combustible and non-combustible gas (producer gas) with the presence of oxygen (lower than the stoichiometric combustion). Various advantages including wider variety of feedstock, high efficiencies and higher commercial value of produces syngas are offered by gasification. Currently, biomass is the common feedstock that widely studied for gasification process due to its low cost and relatively easier preparation and it has been acknowledged as the most preferred feedstock for the production of heat and electricity. Biomass can be roughly categorized as wood and woody biomass, animal and human wastes, aquatic biomass, herbaceous and agricultural biomass, contaminated biomass and industrial wastes as well as biomass blends (Ramos *et al.*, 2018). Municipal solid waste such as sewage sludge is categorized under contaminated biomass and industrial wastes.

Nowadays, urban communities are producing a large volume of municipal wastewater and urging greater technology for sewage treatment and discharge as well as residual sludge safe handling and disposal. Sewage sludge is the solid waste produced from the municipal and industrial wastewater treatment plant. It is estimated that the production of solid waste is generated at 1.2 kg per capita per day in 2007 and more than 1.7 kg per capita per day in 2010 (Fauziah and Agamuthu, 2010). Although there are methods to consolidate, stabilize and dewater the sewage sludge but most of the sludges ended up to be disposed by landfill even after treated. Landfill has become importance in municipal solid waste management. However, landfill is only a temporary solution for the disposal of sewage sludge waste because there is limited space for the sludge waste to be disposed (Kang, 2016).

Recently, an increasing number of researches on sewage sludge thermochemical conversion have been reported due to its inherent improvement in the reduction of waste volume and energy production (Jayaraman and Gökalp, 2015) and gasification is one of the most preferred thermochemical conversion used to

convert sewage sludge into high yield of combustible light gases. Gasification offers cleaner alternative solution for waste treatment with energy recovery as compared with the predominant applied technology of combustion (incineration) where problems commonly encountered with incineration such as emissions of sulphur oxides, nitrogen oxides and heavy metals can be circumvented (Manara and Zabaniotou, 2012). Besides, gasification also offers fast process and large volume reduction as compared to anaerobic digestion, a common way of revaluating bio solids (Oladejo *et al.*, 2018).

The following types of gasifier are the most commonly used gasifier: fixed bed and fluidized bed gasifier. Fluidized bed gasifier has been frequently used as it tolerate wider particle size range (Bosmans *et al.*, 2013). However, this gasifier produced high dust content in the gas phase and required additional cleaning (Warnecke, 2000). Hence, this study was focusing on fixed bed gasifier and this gasifier can be categorized into two modes: updraft and downdraft mode. The downdraft mode has been widely studied for small-scale applications because the producer gas has relatively low quantity of tars compared to other types of gasifiers (Pang, 2016). Meanwhile, the updraft mode seems to attract less attention from the researchers might be due to high tar levels in the gases (Bridgwater, 2003). However, the disadvantages of downdraft gasifier are related to difficulties in handling biomass with high moisture contents and relatively low overall thermal efficiency while updraft gasifier able to handle biomass with high moisture content and is thermally efficient (Bermudez and Fidalgo, 2016; Richardson *et al.*, 2015).

Thus, in this research, the gasification of sewage sludge for the production of hydrogen was investigated and the effect of reactor temperature and equivalence ratio using air and steam as gasifying agent via updraft fixed bed gasifier was thoroughly studied.

1.2 Problem Statement

The most popular method to store dewatered and treated sewage sludge is by transferring the sewage sludge from the dewatering unit to sludge storage area names hopper or yard where the sewage sludge is stored before off – site disposal. In Malaysia, the simplest route for sewage sludge disposal is landfilling (Malaysia, 2015). However, the sewage sludge production has been dramatically increased due to urbanization and economic development thus requiring more space and creating environmental problem such as water, soil and air pollution. In Malaysia, sewage sludge is produced mostly from domestic with the generation rate amount of 7.40 million m³ and light industrial area with the generation rate amount of 9.90 million m³ (Ujang and Salmiati, 2011).

The sewage sludge production has been estimated to increase to 7 million metric tons in the year of 2020 (Roslan, Ghazali and Asli, 2013). This increasing trend hits Malaysia's waste managers due to absence of an integrated waste management system. Therefore, it is crucial to improve waste management system especially landfilling practices as it become unsustainable and is challenging sector for waste managers to invest in thus resulting in many premature shutting down of these disposal sites. Moreover, non-sanitary landfills and open dumps are now prohibited and are being eliminated. These stringent regulations are stated in the Solid Waste and Public Cleansing Management (SWPCM) Act 2007. Hence, converting sewage sludge into useful energy is one of the solution to solve the sewage sludge disposal problem as well as produced useful energy recovery for the mankind.

Presently, energy recovery from sewage sludge using gasification process has been catching more attention from the researchers as growing technologies had emerged. Previously, most of the researchers focus on the gasification of biomass and only little focus on the sewage sludge. In Malaysia, the oil-palm solid waste gasification have been widely studied but only scarce studies dealing with gasification of sewage sludge. Moreover, a limited number of studies deal with updraft gasification of sewage sludge as compared to downdraft gasification of

sewage sludge. In addition, the studies on reactor temperature using updraft gasifier are rarely found as compared to the studies on equivalence ratio.

Therefore, to utilize energy from sewage sludge as well as to reduce environmental problem, gasification offers an attractive solution in which sewage sludge is converted to syngas or fuels. In this study, gasification of sewage sludge in updraft gasifier was conducted to investigate the effect of reactor temperature and equivalence ratio for potential production of syngas.

1.3 Research Objectives

The main aim of this study is to investigate the effect of gasification process parameters (reactor temperature and equivalence ratio) and gasifying agents (air and steam) on the conversion of sewage sludge into potential syngas, mainly on hydrogen via updraft gasification in a bench-scale fixed bed gasifier. The sub-objectives of this study are as follows:

- (a) To investigate the effect of reactor temperature at fixed equivalence ratio
- (b) To investigate the effect of equivalence ratio at optimum reactor temperature of maximum hydrogen yield
- (c) To study the effect of gasifying agents (air and steam)

1.4 Research Scopes & Limitations

To achieve the objectives of this study, the following scopes have been identified:

- (a) Preparation and characterization (ultimate and proximate analysis as well as calorific value) of sewage sludge

- (b) Conduction of air gasification experiments of sewage sludge at reactor temperature of 600 – 900°C and equivalence ratio of 0.10 – 0.20
- (c) Conduction of steam gasification experiments of sewage sludge at reactor temperature of 600 – 900°C at fixed steam to biomass ratio of 1.09
- (d) Collection and characterization of syngas by Residual Gas Analyzer (RGA)
- (e) Comparison and evaluation of the syngas production produced at different reactor temperature, equivalence ratio and gasifying agent

The limitations of this research are as follows:

- (a) The mass flow controller (MFC) of air can vary from 0 to 3000 standard cubic centimetre per minute (sccm)
- (b) The Residual Gas Analyzer (RGA) cannot precisely determine the nitrogen and carbon monoxide mass as both have overlapping peaks patterns at 28 amu. Thus, at the mass of 28, the total of N₂ and CO are applied (a mixture of N₂ + CO)

1.5 Significant of Study

A reuse and recover sewage by-product into potential syngas production for proper disposal management of sewage sludge. The findings of this study will redound to the benefit of society considering that the utilisation of sewage sludge as energy carrier via gasification technique is feasible and a good way to solve a problem related to sewage sludge disposal management.

Gasification offers a flexible and attractive way converting sewage sludge into potential syngas, which can be used for heat and power generation. The results of this study reveal that the optimum syngas production could be achieved through the use of gasifying agent. Depending on the process parameters (e.g: Temperature and ER), the final product also could be targeted.

1.6 Thesis Organization

Chapter 1 of introduction elucidates the research background, the problems related to this research area, research objectives, scopes of research, significant of study and research contribution.

Chapter 2 of literature review provides a comprehensive review covering gasification principles, gasification of biomass as well as gasification of sewage sludge and factors affecting the gasification process.

Chapter 3 of research methodology provides the experimental procedures such as sewage sludge preparations and characterizations, air and steam updraft gasification as well as characterization of syngas.

Chapter 4 of results and discussion explains the findings on the conversion of sewage sludge into potential syngas via air and steam updraft gasification process at various factors such as reactor temperature and equivalence ratio. The comparison of air and steam updraft gasification is also included in Chapter 4.

Finally, Chapter 5 concludes the findings and highlights the significance of this study. In addition, recommendations for the future works of this research are also suggested in Chapter 5.

REFERENCES

- Ahmed and Sinnathambi. (2013). Influence of operating conditions on the air gasification of dry refinery sludge in updraft gasifier. *IOP Conference Series: Earth and Environmental Science*, 16(1), 012068.
- Almeida, A., Neto, P., Pereira, I., Ribeiro, A. and Pilão, R. (2019). Effect of temperature on the gasification of olive bagasse particles. *Journal of the Energy Institute*, 92(1), 153-160.
- Alvarez, J., Kumagai, S., Wu, C., Yoshioka, T., Bilbao, J., Olazar, M. and Williams, P. T. (2014). Hydrogen production from biomass and plastic mixtures by pyrolysis-gasification. *International Journal of Hydrogen Energy*, 39(21), 10883-10891.
- Arena, U., Zaccariello, L. and Mastellone, M. L. (2010). Fluidized bed gasification of waste-derived fuels. *Waste Management*, 30(7), 1212-1219.
- Arjharh, W., Hinsui, T., Liplap, P. and Raghavan, G. S. V. (2013). Evaluation of an energy production system from sewage sludge using a pilot-scale downdraft gasifier. *Energy and Fuels*, 27(1), 229-236.
- Asadullah, M. (2014). Barriers of commercial power generation using biomass gasification gas: A review. *Renewable and Sustainable Energy Reviews*, 29, 201-215.
- Atnaw, S. M., Sulaiman, S. A. and Yusup, S. (2013). Syngas production from downdraft gasification of oil palm fronds. *Energy*, 61(Supplement C), 491-501.
- Aydin, E. S., Yucel, O. and Sadikoglu, H. (2019). Experimental study on hydrogen-rich syngas production via gasification of pine cone particles and wood pellets in a fixed bed downdraft gasifier. *International Journal of Hydrogen Energy*.
- Balat, H. and Kirtay, E. (2010). Hydrogen from biomass - Present scenario and future prospects. *International Journal of Hydrogen Energy*, 35(14), 7416-7426.
- Basu, P. (2013). Chapter 7 - Gasification theory. *Biomass gasification, pyrolysis and torrefaction*, 199-248.

- Bermudez, J. M. and Fidalgo, B. (2016). 15 - Production of bio-syngas and bio-hydrogen via gasification. In R. Luque, C. S. K. Lin, K. Wilson & J. Clark (Eds.), *Handbook of Biofuels Production (Second Edition)* (pp. 431-494): Woodhead Publishing.
- Bosmans, A., Vanderreydt, I., Geysen, D. and Helsen, L. (2013). The crucial role of waste-to-energy technologies in enhanced landfill mining: A technology review. *Journal of Cleaner Production*, 55, 10-23.
- Bridgwater, A. V. (2003). Renewable fuels and chemicals by thermal processing of biomass. *Chemical Engineering Journal*, 91(2), 87-102.
- Calvo, L. F., Garcia, A. I. and Otero, M. (2013). An experimental investigation of sewage sludge gasification in a fluidized bed reactor. *The Scientific World Journal*, 2013, 8.
- Chan, W. P. and Wang, J. Y. (2016). Comprehensive characterisation of sewage sludge for thermochemical conversion processes - Based on Singapore survey. *Waste Management*, 54, 131-142.
- Chanpeng, W. and Chunkaew, P. (2014). Comparative performance of updraft-gasified gas yields and gasoline fuel for water pumping. *Energy Procedia*, 56, 498-504.
- Chawdhury, M. A. and Mahkamov, K. (2010). Development of a small downdraft biomass gasifier for developing countries. *Journal of Scientific Research*, 3(1), 51.
- Choi, Y.-K., Ko, J.-H. and Kim, J.-S. (2018). Gasification of dried sewage sludge using an innovative three-stage gasifier: Clean and H₂-rich gas production using condensers as the only secondary tar removal apparatus. *Fuel*, 216, 810-817.
- Couto, N., Rouboa, A., Silva, V., Monteiro, E. and Bouziane, K. (2013). Influence of the biomass gasification processes on the final composition of syngas. *Energy Procedia*, 36(Supplement C), 596-606.
- De Andrés, J. M., Narros, A. and Rodríguez, M. E. (2011). Air-steam gasification of sewage sludge in a bubbling bed reactor: Effect of alumina as a primary catalyst. *Fuel Processing Technology*, 92(3), 433-440.
- Dogru, M., Howarth, C. R., Akay, G., Keskinler, B. and Malik, A. A. (2002). Gasification of hazelnut shells in a downdraft gasifier. *Energy*, 27(5), 415-427.

- Dogru, M., Midilli, A. and Howarth, C. R. (2002). Gasification of sewage sludge using a throated downdraft gasifier and uncertainty analysis. *Fuel Processing Technology*, 75(1), 55-82.
- Drani, A., Alam, M. Z. and Muyibi, S. A. (2011). Screening of potential strains and co-substrate for production of cellulase enzyme using sewage treatment plant sludge as major substrate. *Biotechnology(Faisalabad)*, 10(2), 197-202.
- E4tech. (2009). Review of technology for the gasification of biomass and wastes.
- Fauziah, S. H. and Agamuthu, P. (2010). *Landfills in Malaysia: Past, present and future*. Paper presented at the 1st International Conference on Final Sinks, Vienna
- Feng, Y., Xiao, B., Görner, K., Cheng, G. and Wang, J. (2011). *Influence of particle size and temperature on gasification performance in externally heated gasifier* (Vol. 281).
- Flaga, A. (2007). The aspects of sludge thermal utilization. *Institute of Heat Engineering and Air Protection, Cracow University of Technology*.
- Franco, C., Pinto, F., Gulyurtlu, I. and Cabrita, I. (2003). The study of reactions influencing the biomass steam gasification process. *Fuel*, 82(7), 835-842.
- Freda, C., Cornacchia, G., Romanelli, A., Valerio, V. and Grieco, M. (2018). Sewage sludge gasification in a bench scale rotary kiln. *Fuel*, 212, 88-94.
- Gai, C., Guo, Y., Liu, T., Peng, N. and Liu, Z. (2016). Hydrogen-rich gas production by steam gasification of hydrochar derived from sewage sludge. *International Journal of Hydrogen Energy*, 41(5), 3363-3372.
- Gil-Lalaguna, N., Sánchez, J. L., Murillo, M. B., Rodríguez, E. and Gea, G. (2014). Air-steam gasification of sewage sludge in a fluidized bed. Influence of some operating conditions. *Chemical Engineering Journal*, 248, 373-382.
- Gil, J., Corella, J., Aznar, M. a. P. and Caballero, M. A. (1999). Biomass gasification in atmospheric and bubbling fluidized bed: Effect of the type of gasifying agent on the product distribution. *Biomass and Bioenergy*, 17(5), 389-403.
- Gravalos, I., Xyradakis, P., Kateris, D., Gialamas, T., Bartzialis, D. and Giannoulis, K. (2016). An experimental determination of gross calorific value of different agroforestry species and bio-based industry residues. *Natural Resources*, Vol.07No.01, 12.
- Halder, P. K., Paul, N. and Beg, M. R. A. (2014). Assessment of biomass energy resources and related technologies practice in Bangladesh. *Renewable and*

Sustainable Energy Reviews, 39, 444-460.

- Hernández, J. J., Aranda, G., Barba, J. and Mendoza, J. M. (2012). Effect of steam content in the air-steam flow on biomass entrained flow gasification. *Fuel Processing Technology*, 99, 43-55.
- Hofbauer, H. and Rauch, R. (2008). Stoichiometric water consumption of steam gasification by the FICFB-gasification process (pp. 199-208).
- Hongrapipat, J., Saw, W. L. and Pang, S. (2015). Co-gasification of blended lignite and wood pellets in a dual fluidized bed steam gasifier: The influence of lignite to fuel ratio on NH₃ and H₂S concentrations in the producer gas. *Fuel*, 139, 494-501.
- Hosseini, M., Dincer, I. and Rosen, M. A. (2012). Steam and air fed biomass gasification: Comparisons based on energy and exergy. *International Journal of Hydrogen Energy*, 37(21), 16446-16452.
- Ismail, T. M. and El-Salam, M. A. (2017). Parametric studies on biomass gasification process on updraft gasifier high temperature air gasification. *Applied Thermal Engineering*, 112, 1460-1473.
- IWK. (2014). Sustainability Report 2012-2013.
- James, A. M., Yuan, W., Boyette, M. D. and Wang, D. (2015). *The effect of air flow rate and biomass type on the performance of an updraft biomass gasifier* (Vol. 10).
- Jayaraman, K. and Gökalp, I. (2015). Pyrolysis, combustion and gasification characteristics of miscanthus and sewage sludge. *Energy Conversion and Management*, 89, 83-91.
- Jayathilake, R. and Rudra, S. (2017). Numerical and experimental investigation of equivalence ratio (ER) and feedstock particle size on birchwood gasification. *Energies*, 10(8), 1232.
- Kaewpanha, M., Guan, G., Hao, X., Wang, Z., Kasai, Y., Kusakabe, K. and Abudula, A. (2014). Steam co-gasification of brown seaweed and land-based biomass. *Fuel Processing Technology*, 120, 106-112.
- Kaige, W., Yan, Z., Xifeng, Z., Catherine, B. and Robert, B. (2017). *Ex-situ catalytic pyrolysis of wastewater sewage sludge - A micro-pyrolysis study* (Vol. 232).
- Kang, W. Y. (2016). *Partial Replacement of Cement with Sewage Sludge Ash (SSA) in Mortar*. (Bachelor of Engineering (Hons.) Civil Engineering Undergraduates Project Papers), Universiti Malaysia Pahang.

- Khosasaeng, T. and Suntivarakorn, R. (2017). Effect of equivalence ratio on an efficiency of single throat downdraft gasifier using RDF from municipal solid waste. *Energy Procedia*, 138, 784-788.
- Kim, M., Lee, Y., Park, J., Ryu, C. and Ohm, T. I. (2016). Partial oxidation of sewage sludge briquettes in a updraft fixed bed. *Waste Management*, 49, 204-211.
- Kirnbauer, F., Wilk, V. and Hofbauer, H. (2013). Performance improvement of dual fluidized bed gasifiers by temperature reduction: The behavior of tar species in the product gas. *Fuel*, 108, 534-542.
- Kirsanovs, V., Blumberga, D., Veidenbergs, I., Rochas, C., Vigants, E. and Vigants, G. (2017). Experimental investigation of downdraft gasifier at various conditions. *Energy Procedia*, 128, 332-338.
- Kokalj, F., Arbiter, B. and Samec, N. (2017). Sewage sludge gasification as an alternative energy storage model. *Energy Conversion and Management*, 149, 738-747.
- Kumar, A., Jones, D. and Hanna, M. (2009). Thermochemical biomass gasification: A review of the current status of the technology. *Energies*, 2(3), 556.
- Lahijani, P. and Zainal, Z. A. (2011). Gasification of palm empty fruit bunch in a bubbling fluidized bed: A performance and agglomeration study. *Bioresource Technology*, 102(2), 2068-2076.
- Li, J., Zhang, X., Yang, W. and Blasiak, W. (2013). Effects of Flue Gas Internal Recirculation on NO_x and SO_x Emissions in a Co-Firing Boiler. *International Journal of Clean Coal and Energy*, Vol.02No.02, 9.
- Liu, H., Hu, J., Wang, H., Wang, C. and Li, J. (2012). Experimental studies of biomass gasification with air. *Journal of Natural Gas Chemistry*, 21(4), 374-380.
- Lucas, C., Szweczyk, D., Blasiak, W. and Mochida, S. (2004). High-temperature air and steam gasification of densified biofuels. *Biomass and Bioenergy*, 27(6), 563-575.
- Luo, S., Xiao, B., Hu, Z., Liu, S., Guan, Y. and Cai, L. (2010). Influence of particle size on pyrolysis and gasification performance of municipal solid waste in a fixed bed reactor. *Bioresource Technology*, 101(16), 6517-6520.
- Luo, S., Xiao, B., Hu, Z., Liu, S., Guo, X. and He, M. (2009). Hydrogen-rich gas from catalytic steam gasification of biomass in a fixed bed reactor: Influence

- of temperature and steam on gasification performance. *International Journal of Hydrogen Energy*, 34(5), 2191-2194.
- Ly, P. M., Xiong, Z. H., Chang, J., Wu, C. Z., Chen, Y. and Zhu, J. X. (2004). An experimental study on biomass air–steam gasification in a fluidized bed. *Bioresource Technology*, 95(1), 95-101.
- Malaysia, A. o. S. (2015). *Study on the current issues and needs for water supply and wastewater management in Malaysia* (Vol. 2): Academy of Sciences Malaysia.
- Manara, P. and Zabaniotou, A. (2012). Towards sewage sludge based biofuels via thermochemical conversion – A review. *Renewable and Sustainable Energy Reviews*, 16(5), 2566-2582.
- Mansaray, K. G., Ghaly, A. E., Al-Taweel, A. M., Hamdullahpur, F. and Ugursal, V. I. (1999). Air gasification of rice husk in a dual distributor type fluidized bed gasifier. *Biomass and Bioenergy*, 17(4), 315-332.
- Maris, K., Valdis, B. and Juris, B. (2018). Small scale gasification application and perspectives in circular economy. *Environmental and Climate Technologies*, 22(1), 42-54.
- Marrero, T. W., McAuley, B. P., Sutterlin, W. R., Steven Morris, J. and Manahan, S. E. (2004). Fate of heavy metals and radioactive metals in gasification of sewage sludge. *Waste Management*, 24(2), 193-198.
- Midilli, A., Dogru, M., Howarth, C. R., Ling, M. J. and Ayhan, T. (2001). Combustible gas production from sewage sludge with a downdraft gasifier. *Energy Conversion and Management*, 42(2), 157-172.
- Moghadam, R. A., Yusup, S., Uemura, Y., Chin, B. L. F., Lam, H. L. and Al Shoaibi, A. (2014). Syngas production from palm kernel shell and polyethylene waste blend in fluidized bed catalytic steam co-gasification process. *Energy*, 75, 40-44.
- Molino, A., Larocca, V., Chianese, S. and Musmarra, D. (2018). *Biofuels production by biomass gasification: A review* (Vol. 11).
- Motta, I. L., Miranda, N. T., Maciel Filho, R. and Wolf Maciel, M. R. (2018). Biomass gasification in fluidized beds: A review of biomass moisture content and operating pressure effects. *Renewable and Sustainable Energy Reviews*, 94, 998-1023.
- Nipattummakul, N., Ahmed, I. I., Kerdsuwan, S. and Gupta, A. K. (2010). Hydrogen

- and syngas production from sewage sludge via steam gasification. *International Journal of Hydrogen Energy*, 35(21), 11738-11745.
- Oladejo, J., Shi, K., Luo, X., Yang, G. and Wu, T. (2018). A Review of Sludge-to-Energy Recovery Methods. *Energies*, 12(1).
- Ong, Z., Cheng, Y., Maneerung, T., Yao, Z., Tong, Y. W., Wang, C.-H. and Dai, Y. (2015). Co-gasification of woody biomass and sewage sludge in a fixed-bed downdraft gasifier. *AIChE Journal*, 61(8), 2508-2521.
- Ongen, A., Ozcan, H. K. and Ozbas, E. E. (2016). Gasification of biomass and treatment sludge in a fixed bed gasifier. *International Journal of Hydrogen Energy*, 41(19), 8146-8153.
- Pang, S. (2016). 9 - Fuel flexible gas production: Biomass, coal and bio-solid wastes. In J. Oakey (Ed.), *Fuel Flexible Energy Generation* (pp. 241-269). Boston: Woodhead Publishing.
- Park, S.-W., Lee, S.-Y., Jeong, Y.-O., Han, G.-H. and Seo, Y.-C. (2018). Effects of oxygen enrichment in air oxidants on biomass gasification efficiency and the reduction of tar emissions. *Energies*, 11(10), 2664.
- Parthasarathy, P. and Narayanan, K. S. (2014). Hydrogen production from steam gasification of biomass: Influence of process parameters on hydrogen yield – A review. *Renewable Energy*, 66(Supplement C), 570-579.
- Peng, W.-X., Ge, S.-B., Ebadi, A. G., Hisoriev, H. and Esfahani, M. J. (2017). Syngas production by catalytic co-gasification of coal-biomass blends in a circulating fluidized bed gasifier. *Journal of Cleaner Production*, 168(Supplement C), 1513-1517.
- Pfeifer, C., Koppatz, S. and Hofbauer, H. (2011). Steam gasification of various feedstocks at a dual fluidised bed gasifier: Impacts of operation conditions and bed materials. *Biomass Conversion and Biorefinery*, 1(1), 39-53.
- Pinto, F., Franco, C., André, R. N., Tavares, C., Dias, M., Gulyurtlu, I. and Cabrita, I. (2003). Effect of experimental conditions on co-gasification of coal, biomass and plastics wastes with air/steam mixtures in a fluidized bed system. *Fuel*, 82(15-17), 1967-1976.
- Ponzio, A., Kalisz, S. and Blasiak, W. (2006). Effect of operating conditions on tar and gas composition in high temperature air/steam gasification (HTAG) of plastic containing waste. *Fuel Processing Technology*, 87(3), 223-233.
- Ramanan, V., Lakshmanan, E., Sethumadhavan, R. and Renganarayanan, S. (2008).

Performance prediction and validation of equilibrium modeling for gasification of cashew nut shell char (Vol. 25).

- Ramos, A., Monteiro, E., Silva, V. and Rouboa, A. (2018). Co-gasification and recent developments on waste-to-energy conversion: A review. *Renewable and Sustainable Energy Reviews*, 81(Part 1), 380-398.
- Rauch, R., Hrbek, J. and Hofbauer, H. (2014). *Biomass Gasification for Synthesis Gas Production and Applications of the Syngas* (Vol. 3).
- Reem, A., Mohan, S. C. and Usama, E. (2014). Dynamic studies of refinery sludge gasification in updraft reactor. *Applied Mechanics and Materials*, 625, 431-434.
- Richardson, Y., Drobek, M., Julbe, A., Blin, J. and Pinta, F. (2015). Chapter 8 - Biomass Gasification to Produce Syngas. In A. Pandey, T. Bhaskar, M. Stöcker & R. K. Sukumaran (Eds.), *Recent Advances in Thermo-Chemical Conversion of Biomass* (pp. 213-250). Boston: Elsevier.
- Roche, E., De Andrés, J. M., Narros, A. and Rodríguez, M. E. (2014). Air and air-steam gasification of sewage sludge. The influence of dolomite and throughput in tar production and composition. *Fuel*, 115, 54-61.
- Roslan, S. N., Ghazali, S. S. and Asli, N. M. (2013). Study on the characteristics and utilization of sewage sludge at Indah Water Konsortium (IWK) Sungai Udang, Melaka. *International Journal of Environmental, Chemical, Ecological, Geological and Geophysical Engineering*, 7, 543-548.
- Sadaka, S. (2012). *Gasification, producer gas and syngas*.
- Safuan, Z. M., Hassan, S. and Faizairi, M. (2014). Thermal drying of Malaysian sewage sludge *Journal of Advanced Research in Fluid Mechanics and Thermal Sciences*, 3(1), 5.
- Sahoo, A. and Ram, D. K. (2015). Gasifier performance and energy analysis for fluidized bed gasification of sugarcane bagasse. *Energy*, 90(Part 2), 1420-1425.
- Salam, M. A., Ahmed, K., Akter, N., Hossain, T. and Abdullah, B. (2018). A review of hydrogen production via biomass gasification and its prospect in Bangladesh. *International Journal of Hydrogen Energy*, 43(32), 14944-14973.
- Sansaniwal, S. K., Pal, K., Rosen, M. A. and Tyagi, S. K. (2017). Recent advances in the development of biomass gasification technology: A comprehensive

- review. *Renewable and Sustainable Energy Reviews*, 72(Supplement C), 363-384.
- Sansaniwal, S. K., Rosen, M. A. and Tyagi, S. K. (2017). Global challenges in the sustainable development of biomass gasification: An overview. *Renewable and Sustainable Energy Reviews*, 80(Supplement C), 23-43.
- Sattar, A., Leeke, G. A., Hornung, A. and Wood, J. (2014). Steam gasification of rapeseed, wood, sewage sludge and miscanthus biochars for the production of a hydrogen-rich syngas. *Biomass and Bioenergy*, 69, 276-286.
- Seggiani, M., Vitolo, S., Puccini, M. and Bellini, A. (2012). Cogasification of sewage sludge in an updraft gasifier. *Fuel*, 93, 486-491.
- Senthil, K. M. and Vivekanandan, S. (2016). Effect of design and operating parameters on the gasification process of biomass in an updraft fixed bed: A statistical study. *International Journal of Chemical Sciences*, 14(4), 23.
- Seswoya, R. and Abdul Karim, A. T. (2017). Organics characteristics of sludge from a full-scale anaerobic digester treating domestic mixed sewage sludge. *MATEC Web Conf*, 103, 06017.
- Sheth, P. N. and Babu, B. V. (2009). Experimental studies on producer gas generation from wood waste in a downdraft biomass gasifier. *Bioresource Technology*, 100(12), 3127-3133.
- Shoja, M. and Tavasoli, A. (2014). Hydrogen and syngas production via pyrolysis and steam gasification of bagasse in a dual bed reactor. *Petroleum & Coal*, 56(3), 307-313.
- Sikarwar, V., Zhao, M., Clough, P., Yao, J., Zhong, X., Memon, M. Z., . . . Fennell, P. (2016). *An overview of advances in biomass gasification* (Vol. 9).
- Susastriawan, A. A. P., Saptoadi, H. and Purnomo. (2017). Small-scale downdraft gasifiers for biomass gasification: A review. *Renewable and Sustainable Energy Reviews*, 76(Supplement C), 989-1003.
- Syed-Hassan, S. S. A., Wang, Y., Hu, S., Su, S. and Xiang, J. (2017). Thermochemical processing of sewage sludge to energy and fuel: Fundamentals, challenges and considerations. *Renewable and Sustainable Energy Reviews*, 80(Supplement C), 888-913.
- Ujang, Z. and Salmiati. (2011). Malaysia. In L. Spinosa (Ed.), *Wastewater sludge: a global overview of the current status and future prospects* (pp. 74-77).
- Vamvuka, D., Sfakiotakis, S. and Saxioni, S. (2015). Evaluation of urban wastes as

- promising co-fuels for energy production – A TG/MS study. *Fuel*, 147, 170-183.
- Vidadili, N., Suleymanov, E., Bulut, C. and Mahmudlu, C. (2017). Transition to renewable energy and sustainable energy development in Azerbaijan. *Renewable and Sustainable Energy Reviews*, 80(Supplement C), 1153-1161.
- Wang, L., Weller, C. L., Jones, D. D. and Hanna, M. A. (2008). Contemporary issues in thermal gasification of biomass and its application to electricity and fuel production. *Biomass and Bioenergy*, 32(7), 573-581.
- Warnecke, R. (2000). *Gasification of biomass: Comparison of fixed bed and fluidized bed gasifier* (Vol. 18).
- Watson, J., Zhang, Y., Si, B., Chen, W.-T. and de Souza, R. (2018). Gasification of biowaste: A critical review and outlooks. *Renewable and Sustainable Energy Reviews*, 83, 1-17.
- Werle, S. (2014a). *Impact of feedstock properties and operating conditions on sewage sludge gasification in a fixed bed gasifier* (Vol. 32).
- Werle, S. (2014b). *Sewage sludge as an environmental friendly energy source*.
- Werle, S. (2015a). Gasification of a dried sewage sludge in a laboratory scale fixed bed reactor. *Energy Procedia*, 66, 253-256.
- Werle, S. (2015b). Sewage sludge-to-energy management in eastern europe: A polish perspective. *Ecological Chemistry and Engineering*, 22(3), 459-469.
- Werle, S. and Dudziak, M. (2014). *Analysis of organic and inorganic contaminants in dried sewage sludge and by-products of dried sewage sludge gasification* (Vol. 7).
- Widjaya, E. R., Chen, G., Bowtell, L. and Hills, C. (2018). Gasification of non-woody biomass: A literature review. *Renewable and Sustainable Energy Reviews*, 89, 184-193.
- Wongsiriamnuay, T., Kannang, N. and Tippayawong, N. (2013). Effect of operating conditions on catalytic gasification of bamboo in a fluidized bed. *International Journal of Chemical Engineering*, 2013, 9.
- Xie, L.-p., Li, T., Gao, J.-d., Fei, X.-n., Wu, X. and Jiang, Y.-g. (2010). Effect of moisture content in sewage sludge on air gasification. *Journal of Fuel Chemistry and Technology*, 38(5), 615-620.
- Xuebin, W., Shuanghui, D., Houzhang, T., Adewale, A., Milan, V., Fuxin, Y. and Neven, D. (2016). Synergetic effect of sewage sludge and biomass co-

- pyrolysis: A combined study in thermogravimetric analyzer and a fixed bed reactor. *Energy Conversion and Management*, 118, 399-405.
- Yan, F., Zhang, L., Hu, Z., Cheng, G., Jiang, C., Zhang, Y., . . . Xiao, B. (2010). Hydrogen-rich gas production by steam gasification of char derived from cyanobacterial blooms (CDCB) in a fixed-bed reactor: Influence of particle size and residence time on gas yield and syngas composition. *International Journal of Hydrogen Energy*, 35(19), 10212-10217.
- Yip, K., Tian, F., Hayashi, J.-i. and Wu, H. (2010). Effect of alkali and alkaline earth metallic species on biochar reactivity and syngas compositions during steam gasification. *Energy & Fuels*, 24(1), 173-181.
- Yuan, Z. (2018). *Bioenergy: Principles and technologies* (Vol. 1). China.
- Zainal, Z. A., Rifau, A., Quadir, G. A. and Seetharamu, K. N. (2002). Experimental investigation of a downdraft biomass gasifier. *Biomass and Bioenergy*, 23(4), 283-289.
- Zakaria, M. S., Hassan, S. and Faizairi, M. (2015). Characterization of Malaysian sewage sludge dried using thermal dryer. *Journal of Advanced Research in Fluid Mechanics and Thermal Sciences*, 5(1), 24-29.
- Žandeckis, A., Kirsanovs, V., Blumberga, D. and Veidenbergs, I. (2014). *The influence of process temperature, equivalence ratio and fuel moisture content on gasification process: A review*.