

EVALUATION OF PRACTICAL STEEL WASTE DISPOSAL TECHNIQUES IN
MALAYSIAN CONSTRUCTION SITES

MUNDHER MOHAMMED SAEED ALSAMARRAIE

UNIVERSITI TEKNOLOGI MALAYSIA

EVALUATION OF PRACTICAL STEEL WASTE DISPOSAL TECHNIQUES IN
MALAYSIAN CONSTRUCTION SITES

MUNDHER MOHAMMED SAEED ALSAMARRAIE

A project report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering (Construction Management)

School of Civil Engineering
Faculty of Engineering
Universiti Teknologi Malaysia

JANUARY 2020

ACKNOWLEDGEMENT

In preparing this project report, I was in contact with many people, researchers, academicians, and practitioners. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main supervisor, Dr. Ali Tighnavard Balasbaneh, for encouragement, guidance, critics, motivation and friendship. Without his continued support and interest, this work would not have been the same as presented here.

Not forgetting my beloved family members and my dearest companion, indeed, their unfailing support, understanding, love has always been my best source of inspiration and faith to soar at greater heights.

Last but not least to the entire individual that has always been there throughout this research, a trillion thanks to you all. May Allah give his blessings in each and every one of you. Again thank you very much.

ABSTRACT

The construction industry is consuming substantial quantities of raw materials in processes, and it has a negative impact on the environment producing a huge amount of waste. Steel is one of the common wastes produced in the construction industry. These research paper analyses steel waste disposal techniques in the Malaysian construction sites related to environmental perspectives, and to sustain steel waste efficiently. The aim of this paper is to examine the practical disposal techniques of steel waste on construction using the 3R concept in terms of material sustainability. As many studies discussed by authors; hereby, a questionnaire methodology is effectively used and distributed randomly to evaluate the practical disposal techniques of steel waste on construction projects related to environmental indicators, in order to identify the techniques which, have the most capabilities to control and reduce waste on-site. The data has been analyzed using SPSS (statistical package for social science) software to decide whether the results meet our research objectives. The reduction technique which has the highest impact, and on the top of waste disposal hierarchy refer to the preliminary stages of a project estimating and stakeholder awareness of planning steel waste management, regarding that the results still unsatisfying. On the other hand, the results show that reusing technique in secondary stages of activities gave us a significant impact in minimizing CO₂ emissions arising from steel waste produced on-site and a preferable option for the construction stakeholders rather than recycling techniques which include certain processes rising up CO₂ emissions.

ABSTRAK

Industri pembinaan memakan kuantiti yang besar daripada bahan-bahan mentah dalam proses, dan ia mempunyai kesan negatif ke atas alam sekitar menghasilkan sejumlah besar sisa. Keluli adalah salah satu daripada bahan buangan yang biasa dihasilkan dalam industri pembinaan. Ini kertas penyelidikan menganalisis teknik pelupusan sisa keluli di tapak pembinaan Malaysia yang berkaitan dengan perspektif alam sekitar, dan untuk mengekalkan sisa keluli cekap. Objektif kajian ini adalah untuk mengkaji teknik pelupusan praktikal sisa keluli pembinaan menggunakan konsep 3R dari segi kemampuan material. Seperti banyak kajian dibincangkan oleh penulis; dengan ini, kaedah soal selidik adalah berkesan digunakan dan diedarkan secara rawak untuk menilai teknik pelupusan praktikal sisa keluli projek-projek pembinaan yang berkaitan dengan petunjuk alam sekitar, untuk mengenal pasti teknik yang, mempunyai keupayaan yang paling untuk mengawal dan mengurangkan sisa di lokasi. data telah dianalisis menggunakan SPSS (pakej statistik untuk sains sosial) perisian untuk membuat keputusan sama ada keputusan memenuhi objektif kajian. Teknik pengurangan yang mempunyai kesan yang paling tinggi, ke atas batu sisa pelupusan hierarki merujuk kepada peringkat awal projek menganggarkan dan kesedaran pihak berkepentingan pengurusan sisa keluli perancangan, mengenai bahawa keputusan masih tidak memuaskan. Sebaliknya, keputusan menunjukkan bahawa menggunakan semula teknik di peringkat menengah aktiviti memberikan kita kesan yang besar dalam mengurangkan pelepasan CO₂ timbul daripada sisa keluli yang dihasilkan di lokasi dan pilihan yang lebih baik untuk pihak berkepentingan pembinaan bukannya teknik kitar semula termasuk proses tertentu yang semakin meningkat pelepasan CO₂.

TABLE OF CONTENTS

| | TITLE | PAGE |
|----------------------|--|-------------|
| | DECLARATION | iii |
| | DEDICATION | iv |
| | ACKNOWLEDGEMENT | v |
| | ABSTRACT | vi |
| | ABSTRAK | vii |
| | TABLE OF CONTENTS | viii |
| | LIST OF TABLES | xii |
| | LIST OF ABBREVIATIONS | xiv |
| | LIST OF APPENDICES | xv |
| CHAPTER 1 | | |
| | INTRODUCTION | 1 |
| 1.1 | Introduction | 1 |
| 1.2 | Background of Study | 3 |
| 1.3 | Problem Statement | 4 |
| 1.4 | Aim and Study Objectives | 6 |
| 1.5 | Scope of Work | 7 |
| 1.6 | Significance of Research | 7 |
| 1.7 | Organization of Thesis | 8 |
| 1.8 | Expected Outcomes | 9 |
| CHAPTER 2 | | |
| | LITERATURE REVIEW | 11 |
| 2.1 | Introduction | 11 |
| 2.2 | Green Building Assessment | 13 |
| 2.2.1 | International Building Assessment System | 14 |
| 2.2.1.1 | BREEAM (United Kingdom) | 15 |

| | | |
|-----------|--|----|
| 2.2.1.2 | Malaysia's Green Building Index | 17 |
| 2.3 | Green Building Assessment Methodology | 20 |
| 2.4 | Environmental Issues and Co ₂ Emissions | 21 |
| 2.5 | Waste Management System | 22 |
| 2.5.1 | Construction Waste | 25 |
| 2.5.2 | Steel Waste | 27 |
| 2.5.3 | Waste Rate Estimation | 29 |
| 2.5.4 | Source of Construction Waste | 30 |
| 2.5.4.1 | Design Stage | 31 |
| 2.5.4.2 | Procurement Stage | 32 |
| 2.5.4.3 | Material Management | 32 |
| 2.5.4.4 | Construction Operation | 33 |
| 2.5.4.5 | Excessive Materials | 33 |
| 2.5.4.6 | Others | 34 |
| 2.5.5 | Construction Industry Challenges | 34 |
| 2.5.6 | Waste Management System Problems | 35 |
| 2.5.6.1 | Environment Different Nature-Related | 35 |
| 2.5.6.2 | Environment Consideration in Projects | 36 |
| 2.5.6.3 | Results-Oriented Policies | 36 |
| 2.5.6.4 | Culture and Attitude | 37 |
| 2.5.6.5 | Environmental Management Cost | 37 |
| 2.5.6.6 | Environmental Value Misunderstanding | 38 |
| 2.6 | Waste Management Sustainability | 38 |
| 2.6.1 | The Concept of Waste Management Hierarchy | 39 |
| 2.6.1.1 | Reduction at Source | 40 |
| 2.6.1.2 | Reuse Techniques | 40 |
| 2.6.1.2.1 | Reusing Barriers | 41 |
| 2.6.1.3 | Recycle Technique | 43 |
| 2.6.1.4 | Recovery Techniques | 43 |
| 2.6.1.5 | Disposal | 43 |
| 2.6.2 | Challenges of Waste Management Sustainability | 44 |
| 2.6.2.1 | Organization and Management | 44 |

| | | |
|---------|--|----|
| 2.6.2.2 | Building and Product | 44 |
| 2.6.2.3 | Consumption of Resources | 45 |
| 2.6.2.4 | Construction Impact Development | 45 |
| 2.6.2.5 | Economic, Cultural, and Social | 45 |
| 2.7 | Policy and Guidelines | 46 |
| 2.7.1 | MS ISO 14004:2004 System of Environmental | 46 |
| 2.7.2 | The Quality Act of Environment 1974 | 46 |
| 2.7.3 | Declaration of Langkawi 1989 | 47 |
| 2.7.4 | Environmental Accord, Kuala Lumpur 1990 | 47 |
| 2.7.5 | Declaration on Environment in Kuala Lumpur | 47 |
| 2.7.6 | Earth Summit Agenda 1992 | 48 |
| 2.7.7 | Environmental National Policy 2002 | 48 |
| 2.7.8 | Ministerial Forum of Infrastructure | 49 |

CHAPTER 3

| | | |
|-----------------------------|--|----|
| RESEARCH METHODOLOGY | 51 | |
| 3.1 | Introduction | 51 |
| 3.2 | Design of The Research | 52 |
| 3.2.1 | Operational Framework | 53 |
| 3.3 | Population, Location, and Sampling Techniques | 54 |
| 3.4 | Research Instrumentation | 55 |
| 3.4.1. | Section A | 56 |
| 3.4.2. | Section B | 56 |
| 3.4.3. | Section C | 57 |
| 3.4.4. | Section D | 57 |
| 3.5 | Research Instrument, Validity, and Reliability | 57 |
| 3.6 | Pilot Test | 58 |
| 3.7 | Data Collection | 59 |
| 3.8 | Discussion | 60 |
| 3.9. | Summary and Recommendation | 60 |

CHAPTER 4

| | |
|---|-----------|
| DATA ANALYSIS | 61 |
| 4.1 Introduction | 61 |
| 4.2 Reliability Test | 62 |
| 4.3 Background of the Respondents | 63 |
| 4.4 Comparison The Most Practical Techniques Used On-Site | 67 |

CHAPTER 5

| | |
|---|-----------|
| CONCLUSION AND RECOMMENDATIONS | 69 |
| 5.1 Introduction | 69 |
| 5.2 Discussion of Research Objectives | 69 |
| 5.2.1 To Estimate Steel Waste from Project Stages | 70 |
| 5.2.2 To Compare practical Steel waste techniques | 70 |
| 5.3 Conclusion | 71 |
| 5.4 Recommendation | 72 |
| REFERENCES | 75 |

LIST OF TABLES

| TABLE NO. | TITLE | PAGE |
|------------------|---|-------------|
| Table 2.1 | Assessing the high performance of green buildings | 15 |
| Table 2.2 | BREEAM schemes | 16 |
| Table 2.3 | Benchmark rating of BREEAM | 17 |
| Table 2.4 | Waste generation split by waste material UK and England | 28 |
| Table 3.1 | Likert scale questionnaire (McIntyre, 2005) | 56 |
| Table 4.1 | Reliability test for section 1 | 62 |
| Table 4.2 | Reliability test for section 2 | 62 |

LIST OF FIGURES

| FIGURE NO. | TITLE | PAGE |
|-------------------|--|-------------|
| Figure 1.1 | Work schedule/ approach of the study | 8 |
| Figure 2.1 | CO ₂ produced from fossil fuel | 22 |
| Figure 2.2 | Hierarchy of waste stages | 26 |
| Figure 2.3 | Steel consumption from 2000-2012by DOE(BAT, 2014) | 27 |
| Figure 2.4 | Breakdown estimation of steel scraps arising in the UK | 30 |
| Figure 2.5 | Waste management hierarchy | 39 |
| Figure 3.1 | Operational framework | 53 |
| Figure 4.1 | Position held by the respondent | 63 |
| Figure 4.2 | Years of Service for Companies | 64 |
| Figure 4.3 | Type of Buildings | 65 |
| Figure 4.4 | Steel waste Amount from project stages | 66 |
| Figure 4.5 | Disposal Techniques Ranking On-Site | 67 |

LIST OF ABBREVIATIONS

| | | |
|--------|---|---|
| CI | - | Construction industry |
| CIDB | - | Construction industry development board |
| CITP | - | Construction industry transformation plan |
| SWMP | - | Site waste management plan |
| BREEAM | - | Building research environmental assessment method |
| WARM | - | Waste reduction model |
| UTM | - | University Technology Malaysia |
| Leeds | - | Leadership in Energy and Environmental Designs |
| GHGs | - | Greenhouse gases |
| GBI | - | Green building index |
| LCA | - | Lifecycle assessment |
| AISI | - | American iron and steel institute |
| CCPI | - | Climate change performance index |
| GBCA | - | Green building council of Australia |
| CASBEE | - | Comprehensive Assessment System for Building Environmental Efficiency |
| GWP | - | Global warming potential |
| EU | - | Eutrophication |

LIST OF APPENDICES

| APPENDIX | TITLE | PAGE |
|-----------------|------------------|-------------|
| Appendix A | QUESTIONNAIRE | 81 |
| Appendix B | RELIABILITY TEST | 88 |

CHAPTER 1

INTRODUCTION

1.1 Introduction

The construction industry contributes to producing large amounts of unique waste materials from construction and demolition practices lead to an unbalanced state influencing environmental issues e.g. CO₂ emissions(Schütte, 2015). Management of construction waste is one of the most well-known obstacles we experience in a construction site; waste disposal became a problem due to the increasing numbers of construction projects, repetitive use of various building materials on-site, and land scarcity.

Nowadays, steel as a type of metals is one of the largest materials usages in the construction industry because of the special characteristics and the advantages of using it compared to other materials. Although steel is considered a great sustainable material compared to other materials, the intervention of steel fabrication and recycling processes make it more complicated material and not easy to manage.

Sustainability in the construction industry is a global concern, finding the most economical practices to reduce carbon footprints, conserve natural resources, and save the environment absolutely not easy. There are many progressive endeavours to decrease the depletion of natural resources, but achieving 100% use out of these resources is impossible, therefore sustainability must be considered during resource planning (Akhtar & Sarmah, 2018).

From one side, Construction industry experts are obviously knowing the need of environment, but on the other side construction industry stakeholders take in account environmental issues only if these issues come in accordance with their business benefits, and all that because construction industry does not emphasize on maintaining environment first, in spite of depending on updated pattern of construction management systems involving environment sustainability as an important dimension rather than a classic tradition of triangle components in construction management systems which is time, cost, and quality; except the limited application of this approach in developed countries.

Progressively, there are alternatives available in terms of recycling and reusing materials, reducing the amounts of the created waste in any situation, however, regardless of this, many construction wastes are still outcasted in landfills. landfill waste represents 32% which be as a result of construction and demolition activities of structures and has 13% of items that landfilled without having being used conveyed directly from construction sites (ref. Innovation Strategy Board).

As the 1996 Finance Act shows the work of waste disposal on the enlisted landfill locales in the UK which be very costly steps. To help handle this, a site waste management plan (SWMP) can be set up before construction commences, depicting the materials how it will be monitored and managed efficiently and outcasted legally through the construction processes, and illustrating how the materials recycling and re-use will be boosted. It might be conceivable to dispose of a specific amount of construction waste through cautious planning. For instance, steel formwork may be fit for being utilized for concrete work activities which would then be able to be reused somewhere else on the project instead of timber formwork which is classed as waste once it has been used.

Other sorts of construction waste might be equipped for being limited; for instance, items that are given with reduced packaging or those which are made out of recycled materials. There can likewise be chances to re-use materials and items which are in a reasonable condition (e.g. doors, windows, roof tiles, etc.), or change them for different materials with an alternate construction site. Materials and items which can't be dispensed with, minimized or reused may have to be discarded as waste. Prior to sending waste for disposal, it ought to be arranged and classified to enable waste contractors to oversee it successfully and guarantee that hazardous waste properly handled.

1.2 Background of Study

The construction industry became one of the most important sectors influences the environment by the high consumption of natural resources and extensive disposal of waste material. Moreover, it creates unbalanced ecological problems, potential sewage and the main CO₂ emissions issue which increases the risk of global warming through the extraction of materials, producing new ones and fabrication processes.

Steel is one of the materials that make a significant contribution to the solid waste construction industry; (Yahya & Boussabaine, 2016) Steel consumed in the buildings are typically subjected to various processing technologies, such as coating, heating with non-metallic substances, reacting with chemicals and doping with other metals. The production of steel is correlating to high levels of fuel consumption rates and subsequent CO₂ emissions. In recent years, this problem became wider due to the need for more urbanization, population growth, and economic activities.

This study will mainly discuss the evaluation of steel waste disposal practices to optimize CO₂ emissions to create sustainable waste management processes in the construction site.

Steel properties can be unchanged and recycled continuously. So, Steel has the ability to be one of the most recycled materials on earth. As the American iron and steel institute (AISI) stated. Other materials incorporating highly recycled properties aluminium, silver, copper, gold, brass. Because of metals characteristics, those materials are considered valuable can be recycled without losing their basic properties. So metals motivate people to collect for sale; an environmental goal with monetary incentives.

Steel recycling processes maintain natural resources while consuming less energy to process than the fabrication of new material using raw materials and stimulate less carbon dioxide and other harmful gases. Overall, only 30 percent of metals are recycled, 40 percent of worldwide steel production is fabricated by recycling method, crude steel forms 42 percent of steel materials recycled in the US; 400 million tons of metal are recycled worldwide every year.

1.3 Problem Statement

Steel is the second-highest material waste generated on-site(You, Be, & In, 2020). The extraction and consumption of raw materials through construction industry processes result in a final product and waste materials being continuously generated on-site. Regarding that, the construction industry contributes to the most influential environmental pollutants(Yahya & Boussabaine, 2010).

Steel waste production is one of the pollution causes (Yang & Liu, 2002). A different application of steel waste disposal practices implemented on-site, but it may not be the right choice related to environmental issues rather than an easy way to get rid of steel waste. The reduction is one of the most efficient methods to control and manage steel waste at construction and demolition stages, and it helps to reduce waste generation, transportation, cost, disposal and recycling (Poon, Yu, & Jaillon, 2004).

According to the reports by climate change performance index (CCPI) in 2018 and 2019, Malaysia came in the rank of 52 and 51 respectively of the assessment includes 60 countries related to the performance of 14 indicators on climate change categorized in four groups GHG emissions, renewable energy, energy use, and adherence to climate policy.

Wastes contain heavy metals (HMs) at low concentrations, somehow be useful in improving agricultural production, as they are essential to living organism growth. However, high concentrations of HMs have negative effects on the environment (Vongdala, 2018) The failure to handle hazardous waste, which comprises large components of toxic chemicals, heavy metals, or irradiation materials, is a considerable threat to human health and the environment (Kamaruddin & Aziz, 2017); Also, using inappropriate disposal practice exacerbate the problem of CO₂ emissions and increase the cost of ecological issues.

Two of the best environmental advantages are the protection of landfill space and a decrease in greenhouse gases. Landfills have become bigger throughout time proceed. As indicated by the Construction and Demolition Recycling Association, it has been determined that more than 4,000 sections of land could be saved every year through the recovery of mixed construction and demolition materials.

Construction and demolition recovery can likewise act to diminish greenhouse gases. At the point when materials are recycled into new materials, less energy is required than to deliver virgin materials. Recovered materials would themselves be able to be utilized as a fuel source, replacing consuming fossil fuels. The U.S. EPA has built up a Waste Reduction Model (WARM), which incorporates emission factors produced for PCC, black-top solid, wood, drywall, black-top shingles, block, and steel. For each 350 million tons recycled, more than 22 million metric huge amounts of CO₂ are kept away from annually. As far as energy saving funds, a sum of 500 trillion BTUs or what might be compared to more than 85 million barrels of oil can be saved. Likewise, we can maintain a strategic distance from the extraction, transportation, and preparing of crude materials which can damage the environment and create ecological issues. Construction & demolition waste contributes to 10-30% to the solid waste collected at many Landfills around the world(Saat, 2013).

1.4 Aim and Study Objectives

The aim of this study is to investigate the present steel waste disposal practices in the Malaysian construction industry and evaluate the practical disposal techniques in terms of optimizing CO₂ emissions. The objectives of this study are:

- 1.** To estimate project stages that contribute to higher steel waste production.
- 2.** To compare practical steel waste disposal techniques on construction sites.

For the first objective, the researcher will go through the construction project stages which really give an indication of higher steel waste production on site. In the second objective, an investigation will be done on reduce, reuse, recycling methods in the construction industry, and we try to identify the most used technique in the opinion of construction stakeholders to reduce steel waste amounts on-site.

1.5 Scope of Work

This research paper focuses only on the steel waste in construction sites due to the various types of construction waste exist there. Recently, steel represents a significant type of materials used in many construction sites and produce a considerable amount of waste. Focusing on steel waste allows us to assess the practices and achieve environmental sustainability. The scope of this work will cover construction sites in Malaysia. In addition, the most common types of construction projects (housing units, commercial, high residential, industrial) taken as a sample for this research.

1.6 Significance of Research

The importance of this study is to estimate the steel waste for different stages and the practices of disposing construction steel waste on-site related to environmental issues in Malaysia and to assess the performance of these techniques toward environmental sustainability and waste produced on-site.

1.7 Organization of Thesis




Figure 1.1 Work schedule/ approach of the study

Based on Figure 1.1 the thesis begins with statements of the purpose and objective of the study in chapter 1, together with the problems followed and studied in the importance of the study. Chapter 2 illustrates the literature review related to the waste management system and deal specifically with metal waste, and sustainable waste management systems. Secondary data of existing management and institutional situation in the country before focusing on the scope of the study; while

the primary data collected and related to this study are explained in chapter 3, along with methodology and approach of the study; the methodology part also explains statistical analysis used. Chapter 5 covers the analysis of the results, conclusion, and recommendation on future research findings.

1.8 Expected Outcomes

The expected result is to identify the practical disposal techniques and assess waste produced on-site from various stages, and whether if there are any exertion efforts in making sustainable construction steel waste disposal in Malaysian construction projects, the practices, rules, and regulations which followed there related to environmental issues, and carbon dioxide emissions. we found that reduce technique still hard to achieve in some companies due to conventional method processes compared to advanced companies which conduct its work through developed technologies, then the reuse technique takes a high impact in consuming steel waste when using the steel waste effectively in secondary activities, in companies dealing with construction buildings, they tend to reuse steel waste rather than recycle it, and this technique optimize and reduce the amount of waste transported out of the site.

REFERENCES

- Abutabenjeh, S., & Jaradat, R. (2018). Clarification of research design, research methods, and research methodology: A guide for public administration researchers and practitioners. *Teaching Public Administration*, 36(3), 237–258. <https://doi.org/10.1177/0144739418775787>
- Ajayi, S. O., Oyedele, L. O., Bilal, M., Akinade, O. O., Alaka, H. A., & Owolabi, H. A. (2017). Critical management practices influencing on-site waste minimization in construction projects. *Waste Management*, 59, 330–339. <https://doi.org/10.1016/j.wasman.2016.10.040>
- Akhtar, A., & Sarmah, A. K. (2018). Construction and demolition waste generation and properties of recycled aggregate concrete: A global perspective. *Journal of Cleaner Production*, 186, 262–281. <https://doi.org/10.1016/j.jclepro.2018.03.085>
- Al-Sari, M. I., Al-Khatib, I. A., Avraamides, M., & Fatta-Kassinou, D. (2012). A study on the attitudes and behavioural influence of construction waste management in occupied Palestinian territory. *Waste Management and Research*, 30(2), 122–136. <https://doi.org/10.1177/0734242X11423066>
- Assamoi, B., & Lawryshyn, Y. (2012). The environmental comparison of landfilling vs. incineration of MSW accounting for waste diversion. *Waste Management*, 32(5), 1019–1030. <https://doi.org/10.1016/j.wasman.2011.10.023>
- Bartlett, J. E., Kotrlik, J. W., & Higgins, C. C. (2001). Organizational Research : Determining Appropriate Sample Size in Survey Research, 19(1), 43–50.
- BAT. (2014). BEST AVAILABLE TECHNIQUES GUIDANCE DOCUMENT ON IRON & STEEL INDUSTRY.
- Begum, R. A., Siwar, C., Pereira, J. J., & Jaafar, A. H. (2009). Attitude and behavioral factors in waste management in the construction industry of Malaysia. *Resources, Conservation and Recycling*, 53(6), 321–328. <https://doi.org/10.1016/j.resconrec.2009.01.005>
- Clavreul, J., Guyonnet, D., & Christensen, T. H. (2012). Quantifying uncertainty in LCA-modelling of waste management systems. *Waste Management (New York, N.Y.)*, 32(12), 2482–2495. <https://doi.org/10.1016/j.wasman.2012.07.008>

- Cohen, L., Manion, L., & Morrison, K. (2000). *Research Methods in*.
<https://doi.org/10.4324/9780203489352>
- CONSTRUCTION INDUSTRY TRANSFORMATION. (2020), (September 2017).
- Di Maria, F., & Micale, C. (2014). A holistic life cycle analysis of waste management scenarios at increasing source segregation intensity: The case of an Italian urban area. *Waste Management*, 34(11), 2382–2392.
<https://doi.org/10.1016/j.wasman.2014.06.007>
- Ding, Z., Zhu, M., Tam, V. W. Y., Yi, G., & Tran, C. N. N. (2018). A system dynamics-based environmental benefit assessment model of construction waste reduction management at the design and construction stages. *Journal of Cleaner Production*, 176, 676–692. <https://doi.org/10.1016/j.jclepro.2017.12.101>
- Gálvez-Martos, J. L., Styles, D., Schoenberger, H., & Zeschmar-Lahl, B. (2018). Construction and demolition waste best management practice in Europe. *Resources, Conservation and Recycling*, 136(December 2017), 166–178.
<https://doi.org/10.1016/j.resconrec.2018.04.016>
- Gavilan, B. R. M., & Bernold, L. E. (1995). proportions in some Northeastern states (Spencer 1989). This may indicate that the concept of managing waste is a fairly new one to both legislators and the construction industry . Illegal dumping signifies a disregard for the law and the environment . , 120(3), 536–552.
- Ghafar, M. N. A. (1999). *Penyelidikan pendidikan*. Penerbit Universiti Teknologi Malaysia.
- Green Building Index. (2009). Malaysia - Green Building Index. *Green Building Index (GBI)*, <http://new.greenbuildingindex.org/resources>. Retrieved from <http://new.greenbuildingindex.org/resources>
- Grzesik, K. (2017). Comparative environmental impact assessment of the landfilling and incineration of residual waste in Krakow. *Environment Protection Engineering*, 43(4), 135–148. <https://doi.org/10.5277/epel70411>
- Hansen, W., Christopher, M., & Verbuecheln, M. (2002). EU Waste Policy and Challenges for Regional and Local Authorities. *Paper*, (December). Retrieved from http://www.ecologic.eu/download/projekte/1900-1949/1921-1922/1921-1922_background_paper_waste_en.PDF
- Heckathorn, D. D. (1997). Respondent-driven sampling: a new approach to the study of hidden populations. *Social Problems*, 44(2), 174–199.
- Heckathorn, D. D. (2002). Respondent-driven sampling II: deriving valid population

- estimates from chain-referral samples of hidden populations. *Social Problems*, 49(1), 11–34.
- Hossain, M. U., Wu, Z., & Poon, C. S. (2017). Comparative environmental evaluation of construction waste management through different waste sorting systems in Hong Kong. *Waste Management*, 69, 325–335.
<https://doi.org/10.1016/j.wasman.2017.07.043>
- Illankoon, I. M. C. S., Tam, V. W. Y., Le, K. N., & Shen, L. (2017). Key credit criteria among international green building rating tools. *Journal of Cleaner Production*, 164, 209–220. <https://doi.org/10.1016/j.jclepro.2017.06.206>
- Julander, A., Lundgren, L., Skare, L., Grandér, M., Palm, B., Vahter, M., & Lidén, C. (2014). Formal recycling of e-waste leads to increased exposure to toxic metals: AN occupational exposure study from Sweden. *Environment International*, 73, 243–251. <https://doi.org/10.1016/j.envint.2014.07.006>
- Kamaruddin, M. A., & Aziz. (2017). *Exploring municipal solid waste and landfill management: A systematic approach. Landfills: Environmental Impacts, Assessment and Management.*
- Kaplow, S. D. (2014). Can Green Building Law Save the Planet ?, 3(2).
- Kent, S. S. (2015). A Randomized Clinical Trial of Selective Laser Trabeculoplasty Versus Argon Laser Trabeculoplasty in Patients With Pseudoexfoliation. *Journal of Glaucoma*, 24(5), 344–347.
<https://doi.org/10.1097/IJG.0b013e31829e55e4>
- Khan, N. A., Hasan, Z., & Jhung, S. H. (2013). Adsorptive removal of hazardous materials using metal-organic frameworks (MOFs): A review. *Journal of Hazardous Materials*, 244–245, 444–456.
<https://doi.org/10.1016/j.jhazmat.2012.11.011>
- Martinuzzi, A., & Monteverchi, F. (2014). Research on waste reduction technologies in Europe: An analysis of FP7-funded projects and networks. *Management of Environmental Quality: An International Journal*, 25(2), 216–226.
<https://doi.org/10.1108/MEQ-06-2013-0070>
- McIntyre, D. (2005). Bridging the gap between research and practice. *Cambridge Journal of Education*, 35(3), 357–382.
<https://doi.org/10.1080/03057640500319065>
- Poon, C. S., Yu, A. T. W., & Jaillon, L. (2004). Reducing building waste at construction sites in Hong Kong. *Construction Management and Economics*,

- 22(5), 461–470. <https://doi.org/10.1080/0144619042000202816>
- Rilling, S. (2011). Introduction to Research Methods in Education by PUNCH, KEITH F. *The Modern Language Journal*, 95(3), 473–474.
https://doi.org/10.1111/j.1540-4781.2011.01212_16.x
- Saat, S. A. (2013). Solid waste management in Malaysia and ecological modernization theory perspective. *Journal of Sustainability Science and Management*, 8(2), 268–275.
- Sadi, M. A. K., & Abdullah. (2012). Reduce , Reuse , Recycle and Recovery in Sustainable Construction Waste Management, 449, 937–944.
<https://doi.org/10.4028/www.scientific.net/AMR.446-449.937>
- Sansom, M., & Avery, N. (2014). Briefing: Reuse and recycling rates of UK steel demolition arisings. *Proceedings of the Institution of Civil Engineers - Engineering Sustainability*, 167(3), 89–94.
<https://doi.org/10.1680/ensu.13.00026>
- Schütte, K. H. (2015). Wireless tri-axial trunk accelerometry detects deviations in dynamic center of mass motion due to running-induced fatigue. *PLoS ONE*, 10(10), e0141957. <https://doi.org/10.1371/journal.pone.0141957>
- Smith, J., & Wyatt, R. (1998). Criteria for Strategic Decision-Making At the Pre-Briefing Stage. *Association of Researchers in Construction Management*, 1(September), 9–11.
- Sylvester, K. E. (2007). Evaluation of Building Information Modeling (BIM) Estimating Methods in Construction Education.
- Um, N., Kang, Y. Y., Kim, K. H., Shin, S. K., & Lee, Y. (2018). Strategic environmental assessment for effective waste management in Korea: A review of the new policy framework. *Waste Management*, 82, 129–138.
<https://doi.org/10.1016/j.wasman.2018.10.025>
- Vongdala, N. (2018). Heavy Metal Accumulation in Water, Soil, and Plants of Municipal Solid Waste Landfill in Vientiane, Laos. *International Journal of Environmental Research and Public Health*, 16(1), 22.
<https://doi.org/10.3390/ijerph16010022>
- Vučijak, B., Kurtagić, S. M., & Silajdžić, I. (2016). Multicriteria decision making in selecting best solid waste management scenario: A municipal case study from Bosnia and Herzegovina. *Journal of Cleaner Production*, 130, 166–174.
<https://doi.org/10.1016/j.jclepro.2015.11.030>

- Yahya, K., & Boussabaine. (2016). Using life cycle assessment for estimating environmental impacts and eco-costs from the metal waste in the construction industry. *Management of Environmental Quality: An International Journal*, 27(2), 227–244. <https://doi.org/10.1108/MEQ-09-2014-0137>
- Yahya, K., & Boussabaine, H. (2010). Quantifying environmental impacts and eco-costs from brick waste. *Architectural Engineering and Design Management*, 6(3), 189–206. <https://doi.org/10.3763/aedm.2009.0106>
- Yang, J. X., & Liu, B. J. (2002). Life cycle inventory of steel products in China. *Acta Scientiae Circumstantiae (in Chinese)*, 22(4), 519–522.
- You, A., Be, M. A. Y., & In, I. (2020). The comparison of construction waste produced by conventional method against IBS : A case study in Pulau Pinang
The Comparison of Construction Waste Produced by Conventional Method Against IBS : A Case Study in Pulau, 020055(October 2018).
- Yuan, H. (2013). A SWOT analysis of successful construction waste management. *Journal of Cleaner Production*, 39, 1–8. <https://doi.org/10.1016/j.jclepro.2012.08.016>
- Yuan, H. P., Shen, L. Y., Hao, J. J. L., & Lu, W. S. (2011). A model for cost-benefit analysis of construction and demolition waste management throughout the waste chain. *Resources, Conservation and Recycling*, 55(6), 604–612. <https://doi.org/10.1016/j.resconrec.2010.06.004>
- Yuan, H., & Wang, J. (2014). A system dynamics model for determining the waste disposal charging fee in construction. *European Journal of Operational Research*, 237(3), 988–996. <https://doi.org/10.1016/j.ejor.2014.02.034>