

WIND TURBINE SYSTEM CONNECTED TO UPS ONBOARD
PLATFORM BATTERY

MOHD HAFIZULLAH BIN HASAN BASRI

A project report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering (Electrical Power)

School of Electrical Engineering
Faculty of Engineering
Universiti Teknologi Malaysia

JULY 2020

DEDICATION

This project report is dedicated to my mother, who taught me the important of continuing learning for better career in near future. It is also dedicated to my father who gave me a moral support and advise in order to complete this project report. It is also dedicated to my wife who always supporting me in any ways throughout my journey in Master Degree Engineering program. Last but not least, dedicated to Assoc Prof Dr Mohd Junaidi Abdul Aziz who always supervise, advise and monitor of my project report.

ACKNOWLEDGEMENT

In completing this project report, I was in contact with many people, researchers, academicians, and colleagues. They have contributed towards my understanding and thoughts. In particular, I wish to express my sincere appreciation to my main project report supervisor, Assoc Prof Dr. Mohd Junaidi Abdul Aziz for encouragement, guidance, critics and friendship. Without his continued support and interest, this project report would not have been the same as presented here.

My fellow postgraduate student should also be recognize for their support. My sincere appreciation also extends to all my colleagues and others who have provided assistance at various occasions. Their views and tips are useful indeed. Unfortunately, it is not possible to list all of them in this limited space. I am grateful to my entire family member.

ABSTRACT

Wind Turbine System is an alternative energy generator where it converting energy from wind energy into electrical energy. However, the gas generator plays as main power generation to supply electrical energy to the electrical loads for oil and gas platform in Malaysia. This work describes the implementation of Wind Turbine System coupled to an Uninterruptible Power Supply (UPS) at onboard-unmanned oil and gas platform. The existing system uses the Diesel Engine Generator (DEG) during black start it will charge the Uninterruptible Power Supply (UPS) batteries, which provide 24V DC power to telecommunication equipment, instruments and other essential electrical systems. The DEG shall run until the fuel gas for Gas Engine Generator (GEG) is available. At normal operation, Gas Engine Generator (GEG) is used to power all 400V AC motors, charging the battery bank of the 24V DC UPS system and other loads. In case the GEG fails, the DEG should be commenced automatically to supply power to the loads. In case of DEG also fails, all 24V DC loads depending on UPS system which can be sustained in 2.46 hours otherwise the 24V DC UPS battery will drain, which resulted to total shutdown operation. In this project, Wind Turbine system is applied and connected to the UPS battery onboard platform to prolong the UPS battery to keep charging as much as possible and to ensure the UPS battery is reliable and available at all time. Installation and maintenance cost will be calculated and analyzed as well for the total proposed overall project and the performance of the proposed system will be simulated by System Advisor Model (SAM) software.

ABSTRAK

Sistem Penjana Angin merupakan sebuah penjana tenaga alternatif di mana ia menukar tenaga dari tenaga angin kepada tenaga elektrik. Walau bagaimanapun, sumber gas berperanan sebagai sumber utama untuk membekalkan tenaga elektrik kepada peralatan elektrik untuk platform minyak dan gas di Malaysia. Kerja khusus ini menerangkan pelaksanaan Sistem Penjana Angin yang digabungkan dengan Bekalan Kuasa Tidak Terputus (BKTT) di atas platform minyak dan gas. Sistem yang tersedia menggunakan Penjana Enjin Diesel (PED) untuk mengecas bateri Kuasa Tidak Terputus (KTT), yang menyediakan kuasa 24V DC ke peralatan telekomunikasi, instrumen dan sistem elektrik penting yang lain. PED akan beroperasi sehingga sumber bahan bakar untuk Penjana Enjin Gas (PEG) tersedia. Secara normal operasi, Penjana Enjin Gas (PEG) digunakan untuk membekalkan tenaga kepada semua peralatan elektrik motor AC 400V, mengisi bateri sistem UPS 24V DC dan juga peralatan elektrik yang lain. Sekiranya PEG gagal diaktifkan, PED harus dimulakan secara automatik untuk membekalkan tenaga kepada peralatan elektrik. Sekiranya PED juga gagal diaktifkan, semua peralatan elektrik 24V DC bergantung pada sistem BKTT yang dapat bertahan dalam masa 2.46 jam dimana, bateri BKTT 24V DC akan habis, yang mengakibatkan operasi sesebuah platform itu kehabisan bekalan elektrik. Dalam projek ini, Sistem Penjana Angin diterapkan dan disambungkan ke platform bateri BKTT untuk memanjangkan keupayaan bateri BKTT agar terus mengecas sebanyak mungkin dan memastikan bateri BKTT boleh membekalkan tenaga dan tersedia sepanjang masa. Kos pemasangan dan penyelenggaraan akan dikira dan dianalisa bagi keseluruhan projek yang dicadangkan dan prestasi sistem yang dicadangkan akan disimulasikan oleh perisian Model Advisor Model (SAM).

TABLE OF CONTENTS

	TITLE	PAGE
	DECLARATION	iii
	DEDICATION	iv
	ACKNOWLEDGEMENT	v
	ABSTRACT	vi
	ABSTRAK	vii
	TABLE OF CONTENTS	viii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATIONS	xii
	LIST OF APPENDICES	xiii
CHAPTER 1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Problem Statement	3
	1.3 Objectives	4
	1.4 Scope of Project	4
CHAPTER 2	LITERATURE REVIEW	7
	2.1 Introduction	7
	2.2 Wind Turbine Concept for Offshore Platform	7
	2.3 Wind Turbine Power Mathematical Calculation	9
	2.4 Wind Turbine System Modeling	14
CHAPTER 3	RESEARCH METHODOLOGY	17
	3.1 Introduction	17
	3.2 Existing RWHP Electrical Power Reliability Data	18
	3.3 Real Wind Speed Data	20
	3.4 Wind Turbine Specification	21

3.5	Wind Turbine Connection Method	23
3.6	Simulation Work	24
CHAPTER 4	RESULT AND DISCUSSIONS	29
4.1	Introduction	29
4.2	Proposed Location of Wind Turbine Installation	29
4.3	Sustainable Power Generated from WT	30
CHAPTER 5	CONCLUSION	35
5.1	Research Outcomes	35
CHAPTER 6	PROJECT MANAGEMENT	37
6.1	Gantt Chart	37
REFERENCES		39
APPENDIX A-B		43-47

LIST OF TABLES

TABLE NO.	TITLE	PAGE
Table 3.1	Platform Reliability (2018)	19
Table 3.2	Platform Reliability (2019)	19
Table 3.3	Wind Speed Data	20
Table 3.4	Calculated Power Output	22
Table 4.1	Simulated Power Output	31
Table 4.2	Simulated Sustainable Power Output	33
Table 4.3	Simulated Sustainable Power Output	33
Table 6.1	Gantt chart for semester 1	37
Table 6.2	Gantt chart for semester 2	37

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
Figure 1.1	Overall RWHP Power Generation System	2
Figure 1.2	Figure of RWHP Power Generation System	3
Figure 2.1	Multiple turbine floater	8
Figure 2.2	Single turbine floater	9
Figure 2.3	Wind Turbine Power Coefficient Curve	13
Figure 2.4	Overall Wind Turbine Model	14
Figure 2.5	Block diagram of WT System	15
Figure 3.1	Overall Research Methodology	17
Figure 3.2	Platform Reliability (2018)	18
Figure 3.3	Platform Reliability (2019)	19
Figure 3.4	Wind Speed Data	20
Figure 3.5	Proposed Wind Turbine Specification.	21
Figure 3.6	Power Output of Wind Turbine Specification	21
Figure 3.7	Proposed Wind Turbine Connection	23
Figure 3.8	Simulation Wind Resource	24
Figure 3.9	Simulation Wind Resource	25
Figure 3.10	Simulation Power Output	26
Figure 3.11	Simulation Power Output	27
Figure 4.1	Main Deck of RWHP	30
Figure 4.2	Analysis of sustainable Power Output	32

LIST OF ABBREVIATIONS

DEG	-	Diesel Engine Generator
GEG	-	Gas Engine Generator
UPS	-	Uninterruptible Power Supply
CPP	-	Central Processing Platform
RWHP	-	Remote Wellhead Platform
DS	-	Distributed Storage
WTS	-	Wind Turbine System
UPS	-	Uninterruptible Power Supply
CSP	-	Control System Panel
SAM	-	System Advisor Model
LV	-	Low Voltage
AC	-	Alternative Current
CCVT	-	Combined Cycle Vapor Turbogenerator
TEG	-	Thermal Electric System
DC	-	Direct Current

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
Appendix A	Airdolphin Series of WT	43
Appendix B	Real Wind Speed Data	47

CHAPTER 1

INTRODUCTION

1.1 Introduction

Most of the Malaysia oil and gas Remote Wellhead Platform (RWHP) are located at offshore Peninsular Malaysia, Sabah and Sarawak where approximately around 200km away from onshore. Basically, Remote Wellhead Platforms are designed with various types of designs ranging from a very simple platform to more complex installation with processing equipment systems. Typically Remote Wellhead Platform is accessible via either helicopter, boat or both. Normally Remote Wellhead Platform (RWHP) is a standalone unmanned platform which is connected via in-field pipeline and tied back to Central Processing Platform (CPP).

Despite located in the middle of the ocean, typical RWHP is powered by Gas Engine Generator (GEG), Diesel Engine Generator (DEG), Solar Power System, Thermal Electric System (TEG), Combined Cycle Vapor Turbogenerator (CCVT), Uninterruptible Power Supply (UPS) and some of RWHP's are powered from Central Processing Platform via subsea composite cable. The power generation system on board Remote Wellhead Platform in this research study comprises of two (2) Gas Engine Generator (GEG) and one (1) Diesel Engine Generator (DEG) each rated 20kW (GEG) and 40kW (DEG) 3-phase nominal 400V AC, 50 Hz output where all generators are installed in non-hazardous area. As a start of the Diesel Engine Generator, some amount of diesel is utilized to run the DEG for black starting and emergency use. During black start scenario i.e when Gas Engine Generator (GEG) is completely down and need to be restarted, Diesel Engine Generator (DEG) will be started and will charge Uninterruptible Power Supply (UPS) batteries which provide 24V DC power to instruments, telecommunication and other electrical systems until the fuel gas from the wells become available so that GEG can be started up. In case the DEG becomes unavailable i.e tripped, the DEG batteries will

provide back-up power to DEG Generator Control Panel (GCP) for maximum one (1) hour before shutting down.

In normal operation, one (1) Gas Engine Generator A (GEG) continuously to provide power to 400V AC LV Switch rack, the 24V DC UPS system and other loads while the other one (1) Gas Engine Generator is on standby mode. In case of Gas Engine Generator A is shutting down, the standby Gas Engine Generator B (GEG) will take over automatically controlled by Control System Panel (CSP). If the second GEG B also trips due to any circumstances, the Diesel Engine Generator (DEG) will be remotely started from Central Processing Platform as backup power supply to 24V DC UPS system. Based on the observation, the DEG can supply a backup power to 24V DC UPS system before the DEG is shutting down due any circumstances. RWHP loads are depending to 24V DC UPS where its can sustain supply power 16.05 kW to all RWHP loads which is 2.46 hours of operation whereby the capacity of UPS batteries is around 39.6 kW. Based on this case, Wind Turbine System is proposed to design, study and evaluate either proposed Wind Turbine System manage to integrate with the UPS system to provide continuously charge the UPS batteries from the renewable energy source to ensure availability of UPS batteries at all times supplying the power to 24V DC loads prior to rectify GEG and DEG problems and start back.




Figure 1.1 Overall RWHP Power Generation System



Figure 1.2 Figure of RWHP Power Generation System

1.2 Problem Statement

Availability and Reliability of electrical power generation system is one of the important concerns on board Remote Wellhead Platform (RWHP) to make sure the platform is continuously live and operating. Non reliable platform power generation will affect production and delivery of oil and gas hydrocarbon from RWHP to CPP. Diesel Engine Generator (DEG) and Gas Engine Generator (GEG) plays as a main role of power generation system to supply power to 400V AC LV Switch rack in order all loads connected to 400V AC switch racks and 24V DC distribution board are fully functioning.

As mentioned, in normal operations Gas Engine Generator (GEG) is the main source of power generation to provide power to 400V AC LV Switch rack. In case both GEG are down or trip due to circumstances, DEG shall take over and supply back-up power to platform electrical loads. The problem is that if DEG is trips and if it not restarted, the DEG batteries will drain out. If DEG is running, the DEG batteries will still be continuously charged by the DEG. Various types of output 24V DC loads is depending on the UPS system that will only survive around 2.46 hours of functioning which UPS have to supply total power around 16.05 kWh to all RWHP loads before UPS battery is completely drain out. To have power generation

back online, the personnel or technicians have to travel to Remote Wellhead Platform approximately three (3) to four (4) hours journey via vessel where overall arrangement rectification and troubleshooting will incur cost of transportation. Cost of maintenance of the both generator GEG and DEG also should be considered part of overall arrangement rectification.

1.3 Objectives

In accordance to the problem statement, a most efficient and reliable to ensure 24V DC UPS batteries are always available at all times, for Uninterruptible Power Supply (UPS) system, Wind Turbine System is proposed to connect to the 24V DC UPS batteries where the 24V DC UPS batteries is continuously charged from renewable sources in the event of loss of main power supply GEG and DEG at RWHP. The objectives of the study are:

1. To analyse proposed Wind Turbine system to UPS system.
2. To design Wind Turbine system connected to the UPS battery.
3. To evaluate power generated from Wind Turbine System from existing WT specification.
4. To analyse prolong time of supplying power to RWHP electrical power generation.
5. Improve of reliability of the platform and low cost in maintenance in long term duration.

1.4 Scope of Project

Designing a Wind Turbine System is a very tedious and time-consuming work due to the number of basic components to be identified such as specification of existing Wind Turbine, Converter or Rectifier (AC to DC), Circuit Breaker and

Cables. On the other hand, suitable location of the Wind Turbine components or structure to be installed on board RWHP also need to be determined and considered in safe area where the system could receive maximum renewable energy source where in this case is wind speed velocity at the location of the Wind Turbine will be installed.

Many models of Wind Turbine System have been developed either onshore or offshore as a power generation system but in this project Wind Turbine System is connected to sustain supplying power to RWHP loads or as a solution to the UPS system generally. The scope for this project is to analyse sustainable power generated of Wind Turbine systems connect to UPS batteries simulated using System Advisor Model (SAM) software by applying the existing Wind Turbine specification and also to compare the power generated by mathematical calculation. The reason of implementation are evaluated and tested to reduce loss of power generation for platform and also to improve reliability of the platform and low cost in maintenance for long term duration.

This Wind Turbine system are modelled to simulate in the simulation System Advisor Model (SAM) software to get the desire power output by applying real wind speed velocity collected.

REFERENCES

- [1] D. McQueen, and S. Watson, "Validation of wind speed prediction methods at offshore sites," *Wind Energy*, vol. 9, pp. 75-85, 2006
- [2] L. Jing, W. Wei, and J. Xiang, "A Simple Sizing Algorithm for Stand Alone PV/Wind/Battery Hybrid Microgrids," *Energies*, vol.5, pp. 53075323, 2012.
- [3] Hwan Lim, "Optimal Combination and Sizing of a New and Renewable Hybrid Generation System," *International Journal of Future Generation Communication and Networking*, vol. 5, no. 2, pp.43-60, June, 2012.
- [4] Halfpenny, A., "Dynamic Analysis of Both On- and Off-Shore Wind-Turbines in the Frequency Domain," PhD Thesis, University College London, 2000.
- [5] Heronemus, W.E., and Stoddard, F., "Simple Arrays of Wind Turbines as a Practical Alternative to the Single Large Rotor Machines." Poster Presentation for Windpower 2003 Conference & Exhibition, May 18 – 21, Austin, TX.
- [6] Henderson, A.R., and Patel, M. H., "On the Modeling of a Floating Offshore Wind Turbine", *Wind Energy Journal* 2003; 6:53-86 (DOI: 10.1002/we.83), Copyright 2003 John Wiley and Sons, Ltd.
- [7] Jamieson, P., Workshop Presentation "Upscaling Issues for Large Turbines & Experience with Design of Floating Offshore Turbines", Workshop on Deep Water Offshore Wind Energy Systems, Washington DC, October 15-16, 2003
- [8] Y. Hongxing, Z. Wei, L. Lin, and F. Zhaohong, "Optimal sizing method for stand-alone hybrid solar–wind system with LPSP technology by using genetic algorithm," *Solar Energy*, vol. 82, pp. 354-367, 2008.
- [9] Y. Hongxing, Z. Wei, and L. Chengzhi, "Optimal design and technoeconomic analysis of a hybrid solar-wind power", *Applied Energy*, vol.
- [10] Y. A. Katsigiannis, P. S. Georgilakis, and E. S. Karapidakis, "Hybrid Simulated Annealing–Tabu Search Method for Optimal Sizing of Autonomous Power Systems With Renewables," *IEEE Trans. on sustainable energy*, vol. 3, no. 3, pp.330-338, July 2012.

- [11] Y. A. Katsigiannis, P. S. Georgilakis, and E. S. Karapidakis, "Genetic algorithm solution to optimal sizing problem of small autonomous hybrid power systems," *Lecture Notes Artif. Intell.*, vol. 6040, pp. 327332, 2010.
- [12] T.M. Layadi, M. Mostefai, G. Champenois, and D. Abbes, "Dimensioning a hybrid electrification system (PV / WT / DG + battery) using a dynamic simulation," *International Conference on Electrical Engineering and Software Applications (ICEESA)*, Hammamet, pp.1-6, 2013.
- [13] Mohamed, and T. Khatib, "Optimal sizing of a PV/wind/diesel hybrid energy system for Malaysia," *International Conference on Industrial Technology (ICIT)*, Cape Town, pp. 752-757, 2013.
- [14] Moriana, I. S. Martín, and P. Sanchis, "Wind-photovoltaic hybrid systems design," *International Symposium on Power Electronics Electrical Drives Automation and Motion (SPEEDAM)*, Pisa, pp. 610615, 2010.
- [15] B.S Borowy., and Z.M. Salameh, "Methodology for optimally sizing the combination of a battery bank and PV array in a wind/PV hybrid system," *IEEE Trans. on Energy Conversion*, vol. 11, no. 2, pp. 367373, 1996.
- [16] H.X. Yang, L. Burnett, and J. Lu, "Weather data and probability analysis of hybrid photovoltaic–wind power generation systems in Hong Kong. *Renewable Energy*," vol. 28, pp.1813-1824, 2003.
- [17] H.X. Yang, L. Lu, and W. Zhou, "A novel optimization sizing model for hybrid solar–wind power generation system. *Solar Energy*," vol. 81, no. 1, pp.76-84, 2007.
- [18] Studie naar haalbaarheid van en randvoorwaarden voor drijvende offshore windturbines. ECN, MARIN, Lagerwey the Windmaster, TNO, TUD, MSC, Dec. 2002.
- [19] Wind Turbine Power Calculation, RWE npower renewables, Mechanical and Electrical Engineering, Power Industry.
- [20] Amevi Acakpovi,Essel Ben Hagan, "A Wind Turbine System Model using a Doubly-Fed Induction Generator (DFIG)"*International Journal of Computer Applications (0975 – 8887)*,Volume 90 – No 15, March 2014
- [21] Akhmatov, V. 2002. Variable-Speed Wind Turbines with Doubly-Fed Induction Generators, Part I: Modelling in Dynamic Simulation Tools. *Wind Engineering* Vol. 26, No. 2.

- [22] Siano, P. 2007. Design and implementation of a fuzzy controller for wind generators performance optimisation. European Conference on Power Electronics and Applications, In proc. IEEE Power Electronics and Applications, European Conference, pp. 1-10.