

RADIO ACCESS POINT DESIGN FOR RADIO OVER FIBER TECHNOLOGY

MOHAMMOUD MUNSOR MOHAMMOUD HADOW

A project report submitted in partial fulfillment of the requirements for the award of
the degree of Master of Engineering (Electrical-Electronics & Telecommunications)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

APRIL 2008

ABSTRAK

Rangkaian kawasan tempatan wayarles (WLAN) adalah digunakan pada peningkatan bilangan tempat-tempat. Dalam bangunan-bangunan pejabat, hospital-hospital, lapangan terbang melepak, dan sebagainya. dengan kenaikan gaji laris untuk data berkelajuan lebih tinggi penghantaran, ini WLAN memerlukan untuk menyediakan lebih tinggi keupayaan-keupayaan pemindahan data, yang memerlukan frekuensi-frekuensi gelombang mikro tinggi. Oleh itu, jangkauan antena radio stesen mendapat lebih kecil dan apa saja lagi titik akses radio (KETUKAN) adalah diperlukan untuk meliputi satu kawasan tertentu. Untuk menyimpan stesen belanja dapat dikawal, stesen-stesen antena sepatutnya seperti mudah sebagai mungkin dan isyarat pemprosesan isyarat yang serupa sebagai mungkin dan banyak fungsi-fungsi harus bertumpu di stesen hujung kepala kemudian untuk dibawa lutsinar antara titik akses radio (KETUKAN) dan stesen hujung kepala. Satu mod gentian optikal, sebagai digunakan dengan meluas dalam jarak jauh 50 kilometer dan rangkaian metropolitan, menawarkan mencukupi lebar jalur untuk ini. Tetapi adalah mahal untuk penggunaan tertutup. Tujuan kajian ini adalah mereka bentuk dan menyerupai satu titik akses radio untuk radio atas teknologi gentian. Simulasi-simulasi telah diusahakan menggunakan optisystem. Komponen-komponen bermakna adalah electroabsoaption pemodulat (EAM) titik akses seperti radio daripada komponen Power Amplifier PA dan Band-pass Filter BPF. Titik akses radio adalah dibuat-buat di kekerapan 2.4 GHz.

ABSTRACT

Wireless local area network (WLAN) is being used at increasing number of places. In office buildings, hospitals, airport lounges, etc. with the raise in demand for higher speed data delivery, these WLAN need to provide higher data transfer capacities, which requires high microwave frequencies. Thus, the reach of the radio antenna station gets smaller and ever more radio access point(RAP) is needed to cover a certain area. To keep station's cost under control, the antenna stations should be as simple as possible and as much as possible signal processing signal functions should be centralized at the head end station. The modulated microwave signals need then to be carried transparently between the radio access point (RAP) and head end station. Single mode optical fiber, as extensively used in long distance 50 km and metropolitan network, offer adequate bandwidth for this. The purpose of this study is to design and simulate a radio access point for radio over fiber technology. The simulations were performed using Optisystem. The main components were electroabsorption modulator (EAM) as radio access point instead of the component Power Amplifier (PA) and Band-pass Filter (BPF). The radio access point is simulated at frequency of 2.4 GHz.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xi
	LIST OF FIGURES	xii
	LIST OF ABBREVIATIONS	xiv
1	INTRODUCTION	1
	1.1 Introduction	1
	1.2 Objective of Project	2
	1.3 Scope of Project	2
	1.4 Problem Statement	3
	1.5 Thesis outlines	3

2	LITERATURE REVIEW	5
	RADIO OVER FIBER(ROF)	
2.1	Introduction	5
2.2	Radio over Fiber Technology	5
2.3	Why RF-over fiber	7
2.4	Benefits of Radio over fiber system	8
	2.4.1 Low attenuation loss	8
	2.4.2 Large bandwidth	9
	2.4.3 Immunity to radio frequency interference	10
	2.4.4 Easy installation and maintenance	10
	2.4.5 Operational flexibility	11
	2.4.6 Reduced power consumption	11
	2.4.7 Millimeter waves	12
	2.4.7.1 Advantages of mm-waves	12
	2.4.7.2 Disadvantages of mm-waves	12
	2.4.8 Radio system functionality	13
2.5	Applications of Radio over fiber technology	13
	2.5.1 Cellular networks	13
	2.5.2 Satellite communications	14
	2.5.3 Video distribution systems	14
	2.5.4 Mobile broadband service	15
	2.5.5 Wireless LANs	15
	2.5.6 Vehicle communication and control	16
3	PROJECT BACKGROUND RADIO ACCESS POINT	17
	(RAP)	
3.1	Introduction	17
3.2	Optical transmission links	18
	3.2.1 Optical fiber	19
	3.2.1.1 Optical transmission in fiber	20
	3.2.1.2 Multimode versus single mode fiber	22

3.2.1.3	Attenuation in fiber	23
3.2.1.4	Dispersion in fiber	24
3.2.1.5	Nonlinearities in fiber	24
3.2.2	Optical transmitters	25
3.2.2.1	How a laser works	25
3.2.2.2	Semi-conductor diode laser	27
3.2.2.3	Optical modulation	28
3.2.3	Optical receivers	28
3.2.3.1	Photodetectors	28
3.2.4	Optical amplifiers	29
3.2.4.1	Doped fiber amplifier	30
3.3	Radio over fiber optical links	30
3.3.1	Introduction to ROF analog optical links	30
3.3.2	Basic radio signal generation and transportation methods	31
3.3.3	ROF link configurations	32
3.3.4	State –of-the Art Millimeter waves generation and transport technology	35
3.3.4.1	Optical heterodyning	35
3.3.4.2	External modulation	38
3.3.4.3	Up- and –down conversion	39
3.3.4.4	Optical transceiver	39
3.3.4.5	Comparison of mm-wave generation and transport techniques	40
4	METHODOLOGY	42
4.1	Introduction	42
4.2	Simulation using optisystem software	42
4.3	Simulation model	44
4.4	Simulation of the RAU	46

5	SIMULATION RESULTN AND DISCUSSION	48
	5.1 Introduction	48
	5.2 Optical Transmitters	49
	5.3 Parameter values of components	49
	5.4 External Mach-Zehnder modulator(MZM) with carriers wav	51
	5.5 Optical modulation converter and method for converting the modulation format of an optical signal	52
6	CONCLUSIONS AND RECOMMENDATIONS	61
	6.1 Conclusion	61
	6.2 Recommendation and future work	62
		64
	REFERENCES	

CHAPTER 1

1.1 Introduction

Wireless Communication is becoming an integral part of today's society. The proliferation of mobile and other wireless devices coupled with increased demand for broadband services are putting pressure on wireless systems to increase capacity. To achieve this, wireless systems must have increased feeder network capacity, operate at higher carrier frequencies, and cope with increased user population densities. However, raising the carrier frequency and thus reducing the radio cell size leads to costly radio systems while the high installation and maintenance costs associated with high-bandwidth silica fiber render it economically impractical for in-home and office environments.

Radio-over-fiber (RoF) technology has emerged as a cost effective approach for reducing radio system costs because it simplifies the remote antenna sites and enhances the sharing of expensive radio equipment located at appropriately sited (e.g. centrally located) Switching Centers (SC) or otherwise known as Central Sites/Stations (CS). On the other hand, Graded Index Polymer Optical Fiber (GIPOF) is promising higher capacity than copper cables, and lower installation and maintenance costs than conventional silica fiber.

Wireless access – fixed or mobile is regarded as an excellent way to achieve broadband services. Of course, it is the only possibility for mobile access (in particular if global mobility is required), however wide application of fixed wireless broadband access is also foreseen. It is well known that both due to unavailability of lower microwave frequencies and to the insufficient bandwidth of lower frequency ranges, next generation wireless access systems – both mobile and fixed – will operate in the upper microwave/millimeter wave frequency band. As in a cellular

system both increased traffic and propagation properties of millimeter-waves require small cells, further as millimeter-wave circuits are rather expensive, the cost of base stations (BSs) will be of determining role.

One emerging technology applicable in high capacity, broadband millimeter-wave access systems is Radio over Fiber called also (Fiber the Air). In this system in order to decrease the costs of BSs, most of signal processing (including coding, multiplexing, RF generation & modulation etc) is made in central stations (CSs) rather than in the BSs. The signal to and from these is transmitted in the optical band, via a fiber optic network. This architecture makes design of BS-s really simple, in the simplest case a BS doesn't comprise else than optical-to-electrical (O/E) and electrical-to-optical (E/O) converters, an antenna and some microwave circuitry (two amplifiers and a diplexer). Or, as it will be mentioned, in principle even the amplifiers can be omitted. In the last decade or so significant research work was done in this field with significant results; the number of publications is abundant. The most important results are summarized in a recent monograph [1]. While, architecture, techniques, benefits, as well as problems to be solved are extensively discussed in [1] and papers referred to in [1], not too much has been told about special problems of resource management and channel allocation. The aim of this report is, after presenting basic design and fields of application of the RoF concept, to give an, as far as known by the author, first short outline on these questions.

1.2 Objective of project

The objective of project is to simulate a low power radio access point (RAP) for transmission using optisystem simulation software. The main part in the radio access point is electro absorption modulator (EAM) as radio unit.

1.3 Scope of project

In this project, simulation model will be developed that integrates both radio frequency (RF) wireless and optical fiber systems that would be transparent to

different systems such as GSM, UMTS.etc. In this simulation models might consist of Pico cell base station and central end optical fiber link model that may use commercially available parameters and power control subsystem modeled in the optisystem are used to contact the whole heretical models.

First of all, the principle of radio over fiber (ROF) system characterized by fiber optic link and free space radio discussed. An electroabsorption modulator transceiver will be used for (RAP) designed. Thereby the (RAP) cost will be reduced. Once familiar with principle and the environment of the optisystem software low power (RAP), at the last the behavior of the system will be anal sized.

1.4 Problem statement

The difficulty which faces radio communication is limited available frequency spectrum. Also numerous reflection stationary objects such as wells, furniture and movable object such as people, animals cause hard environment for – high speed radio transmission. In addition using many components in radio access point make the system less reliability and cost, lastly poor signal coverage.

1.5 Thesis outlines

This is written to bring the reader step by step going in the main core of the content Chapter 1 Provides the introduction to this project where brief background of the study problem and to the statement of the problem. Followed by the Objective, and the scope of the study.

Chapter 2 reviews the literature, which includes introduction to the RoF, the benefits, and applications of the Radio over Fiber Technology in both satellite and mobile radio communications. In addition various types of RoF BS or radio access unit have also been covered.

Chapter 3 covers the basic optical fiber communication link and surveys the state of the art on RoF technologies with a special emphasis devoted to RoF system operating at mm-wave bands and provides information about the fiber characteristics, and structure of electroabsorption modulator which presented the main component in radio access point (RAP).

Chapter 4 describes the methodological processes by showing detailed diagram of the methods implemented as well as highlighting briefly the steps those have been followed to achieve the objective of this project.

Chapter 5 presents the results derived from the methods explained where some analyses and simulations were done based on the EAM effects. Finally the conclusions of the study, as well as some suggestions for future work were summed up in Chapter6.

REFERENCES

1. Hamed Al-Raweshidy, "Radio over Fiber Technologies for Mobile Communications Networks" , Artech House 2002
2. Anne Vilcot, Beatrice Cabon and Jean Chazelas, "Microwave photonics From components to Applications and system" Boston , Kluwer academic publishers, 2003
4. Robert J. Hoss, "Fiber Optic communications Design Hand Book" prentice hall, 1990
5. Y. Guo, "Nonlinear photonics: nonlinearities in optics, optoelectronics and fiber communications " , Berlin, Germany : Springer-Verlag, 2002.
6. Govind P. Agrawal, "Fiber-Optic communication system" McGraw-Hill December 2001
7. Robert C. Elsenpeter, "Optical Networking A beginner's guide" McGraw-Hill/Osborne 2004
8. Yannis Le Guennec, "New optical Microwave Up-Conversion Solution in Radio over Fiber Network" Journal of lightwave technology, vol 24, No 3, pp 1277-1282, March 2006
9. Antti Lamminpää, "Measurement of nonlinearity of optical fiber". Helsinki university of technology, Master thesis, 17th of July, 2003
10. Ajung Kim, Young Hun Joo, and Yungsoo Kim, "60GHz Wireless Communication Systems with Radio-over-Fiber Links for Indoor Wireless LANs" Journal of lightwave technology, vol 20, No 4, pp 517-521, March 2004
11. Gred keiser "optical fiber communications" McGraw-Hill , Inc, 1991
12. D C Green "Radio system Technology" long man and scientific & Technical, 1990
13. John E Mitchell "Techniques for Radio over Fiber Network" Telecommunication Research group, Department of Electronic and Electrical Engineering , university college London , Torrington place, London , WC1E7JE, UK.
14. Sub Hur, seungki Nam , Hanlim Lee, seongtaek Hwang, Yunje Oh "performance Evaluation of Electroabsorption Modulator as optical transceivers in Radio over fiber system" Associate member , IEEE.
15. Maury G., Hilt A., Berceli T., Cabon B., and Vilcot A., Microwave-Frequency Conversion Methods by Optical Interferometer and Photodiode, IEEE Trans. On Microwave Theory and Techniques, Vol. 45, No. 8, August, 1997

16. Hilt A., Marozsak T., Maury G., Berceli T., Cabon B., and Vilcot A., Radio-Node Up conversion in Millimeter-Wave Fiber-Radio Distribution Systems, in Proceedings of the 12th International Conference on Microwaves and Radar (MIKON '98), Poland, May 20-22, 1998
17. Guennec Le Y., Cabon B., and Maury G., Conversions of the Microwave Subcarriers of Digital Signals in Optical Links, in Proceedings of the 14th Annual Meeting of the IEEE Lasers and Electro-Optics Society, 2001, (LEOS 2001), Nov. 12-13, 2001
18. Lim C., Nirmalathas A., Novak D., and Waterhouse R., Millimeter-Wave Broad-Band Fiber-Wireless System Incorporating Baseband Data Transmission over Fiber and Remote LO Delivery, Journal. Of Light wave Technology, Vol. 18, No. 10, October 2000
19. Koike Y., Ishigure T., and Nihei E., High Bandwidth Graded-Index Polymer Optical Fiber; Journal of Light wave Technology, Vol. 13, No. 7; July, 1995
20. Khoe G.D., Koike Y., Ishigure T., Bennekom P.K.v., Boom H.P.A.v.d., Li W., and Yabre G., Status of GIPOF Systems and Related Technologies in Proceedings of the 25th European Conference on Optical Communication 1999 (ECOC'99), Nice, France, Sept. 26 – 30, 1999
21. Koike Y., and Ishigure T., Bandwidth and Transmission Distance Achieved by POF; The Institute of Electronics, Information and Communication Engineers (IEICE) Transaction on Communication, Vol. E82-B13, No. 8; pp 1475 – 1489, August 1999
22. Yabre G., Theoretical investigation on the Dispersion of Graded-Index Polymer Optical Fibers; Journal of Light wave Technology, Vol. 18, No. 6; June, 2000
23. Hills A., Large-Scale Wireless LAN Design; IEEE Communications Magazine, Nov., 2001
24. Cellular Coverage for Efficient Transmission Performance in MBS; Vehicular Technology Conference, 2000; IEEE VTS Fall VTC 2000; 52nd , Volume: 5 , 2000
25. Carbon B., Girod V. and Maury G. : Optical Generation Of Microwave Functions ; Proceedings of the Workshop on Microwave Photonics for Emission and Detection of Broadband Communication Signals, Graduate School in Electronics and Communications (GSEC), Louvain-la-Nueve, Belgium, April 2001.
26. Kitayama K., “Architectural considerations of fiber radio millimeter wave wireless access systems”, Fiber and Integrated Optics”, Vol. 19, pp. 167-186, 2000.

27. Lim C., Nirmalathas A., Novak D., Waterhouse R., and Yoffe G., "A WDM architecture for millimetre-wave fiber radio systems incorporating baseband transmission", *Microwave Photonics* 1999, pp. 127-130.
28. Attard, J.C. and Mitchell J.E. "Fibre radio mm-wave radio system configurations utilising a WDM overlay on a PON" in proc. FSAN Workshop & OHAN 2002, June 2002, Florence, Italy, pp 95-102
29. Mitchell J.E. and Attard, J.C "Design of Re-configurable WDM overlay fibre-radio access networks", in proc. IEE 1st International Conference on Photonic Access Technologies, December 2002, paper 16.
30. A. J. Cooper, "Fiber/Radio for the provision of cordless/mobile telephony services in the access network", *Electron. Lett.*, vol. 26, no. 24, pp. 2054-2056, Nov. 1990.
31. T.-S. Chu and M. J. Gans, "Fiber Optic Microcellular Radio", *IEEE Trans. Veh. Technol.*, vol. 40, no. 3, pp. 599-606, Aug. 1991.
32. Pekka Eskelinen, *Introduction to RF Equipment and System Design*, Artech House, Inc., 2004
33. Rowan Gilmore, Les Besser, *Practical RF Circuit Design for Modern Wireless Systems Volume II Active Circuits and Systems*, Artech House, 2003
34. Steve C. Cripps, *Advanced Techniques in RF Power Amplifier Design*, Artech House, 2002
35. Ian Hickman, *Practical Radio-Frequency Handbook Third edition*, Newnes, 2002
36. Jerry C. Whitaker, Editor, *The RF Transmission Systems Handbook*, CRC Press, 2002
37. J. J., Lane P. M., and Capstick M. H., "Optical Generation and Delivery of Modulated mm-waves For Mobile Communications", in *Analogue Optical Fiber Communications*, Editors: Wilson B., Ghassemlooy Z. and Darwazeh I., The Institution of Electrical Engineers, London, O'Reilly, 1995
38. Koike Y. "POF Technology for the 21st Century", in *Proceedings of the Plastic Optical Fibers (POF2001) Conference*, Amsterdam, Sept 27 – 30, 2001.