

**PRINTED DIVERSITY ANTENNA FOR ON-BODY
COMMUNICATION SYSTEMS**

IGBOAMALU FRANK NONSO

UNIVERSITI TEKNOLOGI MALAYSIA

ABSTRACT

On-body communication channels are used in an increasing number of applications, including headsets and wristwatch controllers for mobile phones, and systems for emergency personnel and for personal medical support. Multipath is one of the common phenomenon occurs in the mobile communication system. It can cause Intersymbol Interference (ISI) and signal distortion in digital and analogue communication, respectively. Diversity schemes such as space, pattern, frequency, time, polarization and field diversity are the well-known methods to overcome the multipath effects. Measurement results of space, and polarization diversity at 5.8 GHz, using two antenna types is presented and results indicate that useful diversity gain can be obtained, which is dependent on the specific channel and antenna type. This project will involve on preliminary measurements for the analysis of diversity techniques for on-body communication system and also diversity antenna design for WBANs, some simulation and hardware designs.

ABSTRAK

Saluran-saluran komunikasi On-body adalah digunakan dalam satu jumlah pertambahan aplikasi, termasuk fon kepala dan alat-alat kawalan jam tangan untuk telefon-telefon bimbit, dan sistem-sistem untuk kakitangan kecemasan dan untuk perubatan sokongan peribadi. Multipath adalah satu daripada fenomena biasa ini berlaku dalam sistem komunikasi kepergerakan. Ia boleh menyebabkan Intersymbol Interference (ISI) dan herotan isyarat dalam digital dan komunikasi analog. Kepelbagaian merangka seperti ruang, corak, frekuensi, masa, polarisasi dan kepelbagaian bidang adalah salah satu kaedah-kaedah untuk mengatasi kesan-kesan multipath. Keputusan ukuran ruang, dan kepelbagaian pengutuban pada 5.8 GHz, menggunakan dua jenis antena dibentangkan dan keputusan keuntungan kepelbagaian yang begitu berguna boleh didapati, yang adalah bergantung pada saluran khusus dan jenis antena. Projek ini akan melibatkan permulaan ukuran-ukuran untuk analisis kepelbagaian itu teknik-teknik untuk badan sistem komunikasi dan juga antena kepelbagaian reka bentuk untuk WBANs, beberapa bentuk simulasi dan juga reka bentuk perkakasan.

TABLE OF CONTENT

| CHAPTER | TITLE | PAGE |
|----------|------------------------------|------|
| | ABSTRACT | i |
| | DECLARATION | ii |
| | DEDICATION | iii |
| | ACKNOWLEDGEMENT | iv |
| | ABSTRACT | v |
| | ABSTRAK | vi |
| | TABLE OF CONTENTS | vii |
| | LIST OF TABLES | x |
| | LIST OF FIGURES | xi |
| | LIST OF SYMBOLS | xiv |
| | LIST OF APPENDICES | xvi |
| | LIST OF ABBREVIATIONS | xvii |
| 1 | INTRODUCTION | 1 |
| | 1.1 Introduction | 1 |
| | 1.2 Objectives | 3 |
| | 1.3 Scopes of project | 3 |
| | 1.4 Problem statement | 4 |

| | | |
|----------|-------------------------------------|-----------|
| 1.5 | Project outlines | 5 |
| 1.6 | Summary | 5 |
| 2 | LITERATURE REVIEW | 6 |
| 2.1 | Diversity Antenna | 6 |
| 2.1.1 | Space Diversity | 7 |
| 2.1.2 | Polarization Diversity | 8 |
| 2.1.3 | Pattern or Angle Diversity | 9 |
| 2.1.4 | Field Diversity Antenna | 10 |
| 2.2 | Antenna | 10 |
| 2.2.1 | Smart Antenna | 11 |
| 2.2.2 | Patch Antenna | 14 |
| 2.2.3 | Monopole Antenna | 16 |
| 2.2.4 | Dipole Antenna | 17 |
| 2.2.5 | PIFA-Planar Inverted F Antenna | 19 |
| 2.2.6 | Antenna Requirement and Performance | 20 |
| 2.2.7 | Basic Micro strip Antenna | 23 |
| 2.2.8 | Antenna Radiation Pattern | 25 |
| 2.3 | Diversity Combining | 26 |
| 2.3.1 | Selection Combining | 28 |
| 2.3.2 | Equal Gain Combining | 29 |
| 2.3.3 | Maximal Ratio Combining | 31 |
| 2.2.4 | Switch Combining | 33 |
| 3 | METHODOLOGY | 35 |
| 3.1 | Methodology | 35 |
| 3.2 | Correlation Coefficient | 37 |

| | | |
|-----------|--|-----------|
| 3.3 | Design Procedure | 39 |
| 3.3.1 | Design Structure Procedure | 39 |
| 3.3.2 | Space Diversity Antenna | 41 |
| 3.3.3 | Polarization Antenna | 42 |
| 3.4 | Summary | 44 |
| 4. | SIMULATION, FABRICATION AND MEASUREMENT | 46 |
| 4.1 | Introduction | 46 |
| 4.2 | Fabrication | 49 |
| 4.3 | Etching process | 50 |
| 4.4 | Connecting to the connector | 50 |
| 4.5 | Antenna measurement | 53 |
| 4.6 | Summary | 54 |
| 5. | RESULT AND DISCUSSION | 55 |
| 5.1 | Introduction | 55 |
| 5.2 | Simulation Result | 55 |
| 6 | CONCLUSION AND THE RECOMMEDATIONS | 67 |
| 6.1 | Introduction | 67 |
| 6.2 | Conclusion | 67 |
| 6.3 | Recommendation and future works | 68 |
| | REFERENCES | 69 |
| | Appendices A-D | 84-94 |

CHAPTER 1

INTRODUCTION

1.1 Introduction

On-body communication is gaining popularity and has a large scope for research. It is a branch on body communications in which two or more devices on the body communicate using the surface of the body as the communication channel. It is often being applied in medical diagnostics and real time patient monitoring. Diversity has been used over the last few decades as a very powerful tool to combat fading in mobile wireless communication channels. Fading will occur due to the large relative movement of the body parts, shadowing, polarization mismatch, and scattering due to the body and the surrounding environment. To improve the performance and overcome fading, diversity is a very powerful tool. The principle behind diversity is the use of more than one independent and hence uncorrelated branch. If the various branch signals (channels) are uncorrelated significantly, the fading caused in the diversity branches is independent. A correlation coefficient of 0.7 or below is considered as an acceptable value to provide an improvement in terms of diversity for most of the cases [1]. A description of various diversity schemes is given in [2]. The use of multiple antennas at the transmitter and/or receiver is by far the most popular technique for diversity.

Much work has been done to investigate the body channel at the ISM bands such as 2.45 GHz. At this frequency, electromagnetic propagation involves two main aspects. Firstly, propagation takes place over the surface of the body by creeping or surface waves. Such propagation may be significantly affected by the motion of the body. Secondly, multipath propagation around the body, which is due to reflections from the surrounding environment and the body parts, will also occur. Propagation through the body is negligible at this and higher frequencies.

Diversity can be achieved in various ways such as frequency diversity, time diversity, and antenna diversity. Antenna diversity involves the use of multiple antennas, different radiation patterns, and/or polarizations [3]. Space diversity is by far the most popular technique, [3-5]. Space diversity is achieved by using more than one antenna at the transmitter or receiver side. This technique does not consume extra spectrum [3, 4] and the basic issue is that of antenna spacing. The diversity branches in the other antenna diversity techniques can be achieved by using different radiation patterns in the same or separate antennas and by using a single antenna with orthogonal polarizations or separate antennas with orthogonal polarizations [6]. When two antennas are placed close to each other, mutual coupling between the antennas must be low to prevent the effect of one antenna on the other. A spacing of $\lambda/2$ is sufficient for most of the applications [3].

The improvement due to the use of diversity is usually measured in terms of diversity gain (DG). DG is an improvement in the signal strength or signal to noise ratio or bit error rate over a single antenna with no diversity, at a certain level of outage probability [5,6]. DG depends upon the correlation and power imbalance between the two branch signals. If the power imbalance is more, the diversity combiner will favor the strongest signal for most of the time and hence a negligible diversity gain will result. For the on-body communication channels, pattern and polarization diversity antennas must be designed carefully to prevent one antenna being dominant compared to the other, for various positions and postures of the body, otherwise the high power imbalance can

severely affect the diversity performance. Due to limited changes in the antenna orientations for most of the on-body channels, the power imbalance will be larger if either the pattern or polarization of the diversity antennas is different.

In this project, the diversity performance for on-body communication channels will be reviewed. Diversity gains and correlation coefficients will be reported for various diversity schemes using different combining techniques in receiving monopole antennas and the best among the combining techniques will be identified using cumulative distribution functions (CDF) which will be plotted for various movements of the body channels. In addition to the theoretical design procedure, numerical simulation was performed using CST microwave office suit at 5.8 GHz frequency to obtain design parameters such as S_{11} , S_{21} , feeding point location etc. The antennas have been fabricated and tested.

1.2 Objectives

The objectives of this project are:

- (a) To study the concept of diversity schemes in terms of various types of diversity such as space, polarization, field, pattern diversity.
- (b) To optimize, simulate, fabricate the space and polarization diversity antenna and investigate the data received from the simulation and measurement result by calculating its correlation coefficient and plotting the

CDF using various types of combining techniques in order to know the best diversity performance.

1.3 Scopes of project

The scopes of this project will be defined as follows;

- Understanding the antenna concept
- Design the monopole antenna for transmitter, two patch antennas for the receiver (space) and polarized patch antenna for the receiver.
- Performs numerical solution using CST microwave office suit software.
- Practical implementation of the antenna.
- Comparison the measurement and simulation result in terms of correlation coefficient and various combining techniques.

1.4 Problem statement

As in traditional wireless communication systems, where distinctions among indoor and outdoor, urban and rural propagation environments have been identified, a body posture classification can be developed for on-body communications, since the relative position of the transmitting and receiving antennas significantly influences the system performance. Postures with different levels of mobility have been taken into account and generally roughly classified in sitting and standing. Free movements are allowed for each part of the body: leaning down, turning the trunk, walking, kneeling, and moving arms.

All these will contribute to the effect of fading for the channels on body communication, factors causing fading of an on body channel include multipath due to scattering from the sounding object and body parts, variation of distance between the antennas, polarization mismatches, shadowing.

The study of diversity antenna is to improve the performance by placing two antennas in the receiver so that the best signal will be selected no matter the position of the body

1.5 Project outlines

Chapter 1 provides the introduction of the project where the background, objectives and scopes of project are presented. Then, the literature review of the project which include

the fundamental theories and concept of diversity schemes in terms of (space, polarization, field, pattern etc) diversity, various types of antenna used on wireless communication and the appropriate literature are all described in Chapter 2. For Chapter 3, the methodology is explained. This part emphasized in equation and algorithm used in combining techniques on body communication Proceed with Chapter 4 Result and discussion followed by conclusion in Chapter 5. The conclusion will be summarized all the finding of the project.

1.6 Summary

This is an introductory chapter that defines the literature review, the objectives, and research background of the thesis. The project report structure is explained and highlighted. In the following chapters, the project work performed is reported.

REFERENCES

- [1] Imdad khan, Liang Yu, Yuriy I. Nechayer, Peter S. Hall,” Space and pattern Diversity for on-body communication channels and indoor environment at 2.45GHz.”University of Birmingham, UK.
- [2] A.A.Serra, P. Nepa, G. Manara, P.S. Hall, Diversity for body Area networks. Dept. of Information Engineering, University of Pisa, Via G. Caruso 16,56122, Pisa, Italy.
- [3] P. Kildal, K. Rosengren, J. Byun, and J.lee,”Definition of effective diversity gain and how to measure it in a reverberation chamber” Microwave And Optical Technology Letter / Vol.34, No. 1, July 5 2002.
- [4] A.A.Serra, P. Nepa, G. Manara, P.S. Hall,” Diversity Gain Measurement for PIFAs on a Notebook computer”, IEEE 2006 Antennas and Propagation Society International Symp., 9-13 July 2006.
- [5] Hall, P 5 and Hao, Y, (editors) "Antennas and Propagation for Body Centric Communications Systems", (Artech House, Norwood, MA, USA, 2006, ISBN-10: 1-58053-493-7)
- [6] Franz Hirtenfelder1 1CST GmbH, Bad Nauheimer Strasse 19, D-64289 Darmstadt, Germany,

- [7] J. C. L. Ng, K. B. Letaief, and R. D. Murch, "Antenna diversity combining and finite-tap decision feedback equalization for high-speed data transmission," *IEEE J. Select. Areas Communication*, vol. 16, pp. 1367–1375, Oct. 1998.
- [8] J. H. Winters, "Signal acquisition and tracking with adaptive arrays in the digital mobile radio system IS-54 with flat fading," *IEEE Trans. Veh. Technol.*, vol. 42, pp. 377–384, Nov. 1993.
- [9] R. G. Vaughan, "On optimum combining at the mobile," *IEEE Trans. Vehicular Technol.*, vol. 37, pp. 181–188, Nov. 1988.
- [10] T. S. Rappaport, *Wireless Communications Principles and Practice*. Englewood Cliffs, NJ: Prentice Hall, 1996.
- [11] Kamarudin, M R, Nechayev, Y I and Hall, P S, "Angle of Arrival Estimation of On-Body Channels", 2nd European Conference on Antenna and Propagation, EuCAP07, Edinburgh, Nov 2007
- [12] Jami I., Ormondroyd R. F., "Improved method for estimating angle of arrival in multipath conditions using the 'MUSIC' algorithm", *IEEE-APS Conference on the Antennas and Propagation for Wireless Communications*, pp. 99 - 102 (2000)
- [13] Thudor F. and Louzir A., "An extremely Compact Diversity Antenna for WLAN", *Antennas and Propagation Society International Symposium, 2002.results IEEE Volume 4, Issue, 2002 Page(s): 60 - 63 vol.4*
- [14] I Khan, M R. Kamarudin, L Yu, Y. I. Nechayev,.P.S. Hall, "Comparison of space and pattern diversity for onbody channels", 5th European Workshop on Conformal Antennas, Bristol, UK, 10- 11 September 2007

- [15] A.A. Serra, A. Guraliuc, P. Nepa, G. Manara , I. Khan, P.S. Hall, “Diversity gain measurements for body-centric communication systems”, 11th International Symposium on Microwave and Optical Technology, December 17-21,2007
- [16] I Khan, L Yu, Y.I..Nechayev,.P.S.Hall, “Space and pattern diversity for on-body communication channels in an indoor environment at 2.45 GHz”, 2nd European Conference on Antennas and Propagation (EuCAP), Edinburgh,UK , 11-16 Nov 2007
- [17] A. A. Serra, A. R. Guraliuc, P. Nepa, G. Manara, “Dual-polarization and dual-pattern planar antenna for diversity in body-centric communications”, submitted at Antennas IEEE Transactions on Antennas and Propagation, special issue on Antennas and Propagation for Body-Centric Wireless Communications, 2008
- [18] S. Haykin and M. Moher, *Modern Wireless Communications*, Pearson Prentice Hall, Upper Saddle River, NJ, 2005.
- [19] R. Bose, A. Freedman, and B. D. Steinberg, “Sequence CLEAN: A modified deconvolution technique for microwave images of contiguous targets,” *IEEE Trans. Aerosp. Electron. Syst.*, vol. 38, no. 1, pp. 89–96, 2002.
- [20] L.-W. Chua, “A new UWB antenna with excellent time domain characteristics,”in *Proc. The European Conference on Wireless Technology*, Oct. 2005, pp. 531–534.
- [21] A. Fort, J. Ryckaert, C. Desset, P. De Doncker, P. Wambacq, and L. Van Biesen, “Ultra-wideband channel model for communication around the human body,” *IEEE J. Select. Areas Commun.*, vol. 24, no. 4, pp. 927–933, 2006.
- [22] W. Kissick, *The Temporal and Spectral Characteristics of Ultra Wideband Signals*, U.S. Department of Commerce, NTIA Report 01-383, 2001.

- [23] P. H. Lehne and M. Pettersen. An Overview of Smart Antenna Technology for Mobile Communications Systems. *IEEE Communications Surveys*, 2(4):2.13, 1999
- [24] Seong-Youp Suh, Warren L. Stutzman and William A. Davis, "A New Ultrawideband Printed Monopole Antenna: The Planar Inverted Cone Antenna (PICA)", *IEEE Transaction on Antennas and Propagation*, Vol. 52, No. 5, May 2004.
- [25] A.Saitou, T.Iwaki, K.Honjo, K.Sato, T.Koyama and K.Watanabe, "Practical Realization of Self-Complementary Broadband Antenna on Low-Loss Resin Substrate for UWB applications", 2004 IEEE MTT-S International Microwave Symposium, Fort Worth, Texas, June 2004.
- [26] P. Lukowicz, U. Anliker, J. Ward, G. Troster, E. Hirt, C. Neufelt, "AMON: a wearable medical computer for high risk patients," in *Proc. Sixth International Symposium on Wearable Computers 2002*, Seattle, Washington, Oct. 2002, pp.133 – 134
- [27] S. V. Hanly, "An algorithm for combined cell-site selection and power control to maximize cellular spread spectrum capacity," *IEEE J. Select.Areas Commun.*, vol. 13, pp. 1332–1340, Sept. 1995.
- [28] F. Rashid-Farrokhi, K. J. R. Liu, and L. Tassiulas, "Transmit beamforming and power control for cellular wireless systems," *IEEE J. Select. Areas Commun.*, vol. 16, pp. 1437–1450, Oct. 1998.
- [29] G. Ungerboeck, "Adaptive maximum likelihood receiver for CatTier modulated **data** transmission systems", *IEEE Trans. on Comm.*, vol.32,1984, pp. 624-636
- [30] **Q. Liu, Y. Wan**, "An adaptive MLSE receiver with dual diversity combining/selection", **Proc. IEEE PIMRC'92**, pp. 245-249