

HARMONIC FEMTOSECOND FIBER LASER BASED ON
SUPERCONTINUUM GENERATION WITH CARBON NANOTUBES
SATURABLE ABSORBER

SITI NORFARHA BINTI MAT RIFIN

UNIVERSITI TEKNOLOGI MALAYSIA

HARMONIC FEMTOSECOND FIBER LASER BASED ON
SUPERCONTINUUM GENERATION WITH CARBON NANOTUBES
SATURABLE ABSORBER

SITI NORFARHA BINTI MAT RIFIN

A thesis submitted in fulfilment of the
requirements for the award of the degree of
Doctor of Philosophy (Physics)

Faculty of Science
Universiti Teknologi Malaysia

AUGUST 2017

"Allah (Providers) light (to) heaven and earth. The parable of His Light is like a hole that niches wherein a lamp is. The lamp is in a glass (and) the glass is as if the stars (glowing) like pearls, which kindled from a tree blessing, (namely) the olive tree, neither of the east (a) nor in the west (her), whose oil (only) almost luminous, though fire scarce touched. Light upon light (layered), Allah guides to His light whom He pleases, and Allah sets forth parables for man-kind, and Allah knows all things. "

(An-Nur : 35)

Dedicated to

My beloved abah and mama and also my family that help me through this journey

ACKNOWLEDGEMENT

Bismillahirrahmannirrahim, Alhamdulillahirabbilalamin

All praise be to The Almighty, with His consent this thesis can be completed. Deepest appreciation and gratitude to my supervisor, Associate Professor Dr. Yusof Munajat for his support and advisory through all the years of my study. Big thanks to my external co-supervisor at Photonic Research Centre (PRC), University of Malaya, Dr. Mohd Zamani Zulkifli and also to the PRC Director, Professor Dr. Harith Ahmad for their willingness to collaborate, and allowed me to use the facilities in their lab. With their generosity in sharing their expertise, immense knowledge and experience in this field of photonics had given me an opportunity to seek knowledge and explore this field.

My sincere and heartfelt gratitude goes to my friends and entire lab mate in Department of Physics, Universiti Teknologi Malaysia and in Photonic Research Centre, University of Malaya for their generous help in the lab. Thank you for all the kind assistance, guidance, knowledge and sharing ideas that lead to the completion of this thesis.

My personal full-hearted appreciation also goes to my family, especially my parents, Mat Rifin Seman and Siti Zaharah Mohamad, as well as my siblings, Siti Fatimah and her husband Norhisham Wahab, Mohd Firdaus, Mohamad Fikri and Siti Fazlin for their fully understanding and encouragement to make sure that I could complete my Ph.D. degree till the end.

Also to those who have directly or indirectly contributed to the completion of this thesis, my gratitude goes to you.

ABSTRACT

An ultrashort pulse fiber laser has been proposed due to the problem of bulky size and high cost of the Titanium Sapphire laser and other commercial ultrashort pulse fiber lasers. Thus, this study focused on the development of a robust, compact and stable femtosecond mode-locked fiber laser via optical telecommunication components. This laser was designed to have a high repetition rate (80 - 100 MHz) and average output power (30 - 50 mW), and also a narrow pulse width (< 100 fs) which are crucial for a laser source used in all-fiber terahertz time domain spectroscopy system. A short cavity was needed in order to get a high repetition rate while the effect of optical dispersion in the cavity was included in order to produce a narrow pulse width. This design employed a passive mode-locked technique with a carbon nanotube thin film as the saturable absorber. Initially, a diode laser of 980 nm wavelength was used as a pumping source and a 0.4 m long of highly erbium-doped fiber with 110 dB/m peak absorption at wavelength of 1530 nm was utilised as a gain medium. Then, in order to achieve the desired parameters, the pump power was increased to raise the repetition rate of the pulse laser and a supercontinuum generation technique was adopted to compress the pulse width. The preliminary results of the designed laser show a fundamental repetition rate of 67.8 MHz at mode-locking threshold pump power of 63.5 mW. The average output power and pulse width obtained are 0.77 mW and 410 fs respectively. The increment of pump power to 104.2 mW significantly increased the fundamental repetition rate to 193.5 MHz which corresponds to the 3rd order harmonic and compressed the pulse width to 70 fs. The average output power after compressing the pulse width is 4.27 mW. As the conclusion, two of the targeted parameters of the laser have been successfully attained. This design however has not been able to produce the targeted average output power and to operate with the desired parameters simultaneously.

ABSTRAK

Satu laser gentian denyut ultra-pendek telah dicadangkan kerana masalah berhubung dengan saiz yang besar dan kos yang tinggi bagi laser Titanium Sapphire dan laser gentian denyut ultra-pendek komersial yang lain. Oleh itu, kajian ini menjurus kepada pembangunan laser gentian mod terkunci femto-saat yang tahan lasak, lebih kecil dan stabil menggunakan komponen telekomunikasi optik. Laser ini direka bentuk untuk mempunyai kadar pengulangan (80 - 100 MHz) dan kuasa output purata (30 - 50 mW) yang tinggi, dan juga lebar denyut yang sempit (< 100 fs) kesemuanya penting bagi satu sumber laser yang digunakan dalam sistem spektroskopi domain masa terahertz semua gentian. Satu rongga pendek diperlukan untuk menghasilkan kadar pengulangan yang tinggi manakala kesan penyebaran optik dalam rongga diambil kira untuk menghasilkan lebar denyut sempit. Reka bentuk ini menggunakan teknik mod terkunci pasif dengan filem nipis karbon bertub nano sebagai penyerap boleh tepu. Pada mulanya, laser diod dengan panjang gelombang 980 nm digunakan sebagai sumber pam dan gentian berdop erbium sepanjang 0.4 m dengan penyerapan puncak 110 dB/m pada panjang gelombang 1530 nm digunakan sebagai medium gandaan. Kemudian, untuk mencapai parameter yang dikehendaki, kuasa pam dinaikkan untuk meningkatkan kadar pengulangan denyut laser dan teknik penjanaan ultra-selanjat telah digunakan untuk memampatkan lebar denyut. Hasil awal laser yang direka bentuk menunjukkan kadar pengulangan asas ialah 67.8 MHz pada kuasa ambang pam mod terkunci 63.5 mW. Kuasa output purata dan lebar denyut yang diperolehi masing-masing ialah 0.77 mW dan 410 fs. Peningkatan kuasa pam kepada 104.2 mW telah meningkatkan kadar pengulangan asas dengan ketara kepada 193.5 MHz yang dipadankan dengan harmonik tertib ketiga dan memampatkan lebar denyut kepada 70 fs. Sebagai kesimpulannya dua parameter laser yang disasarkan telah berjaya diperolehi. Reka bentuk ini bagaimanapun tidak dapat menghasilkan kuasa output purata yang disasarkan dan beroperasi dengan parameter yang diinginkan secara serentak.

TABLE OF CONTENTS

| CHAPTER | TITLE | PAGE |
|----------------|---------------------------------------|-------------|
| | DECLARATION | ii |
| | DEDICATION | iii |
| | ACKNOWLEDGEMENT | iv |
| | ABSTRACT | v |
| | ABSTRAK | vi |
| | TABLE OF CONTENTS | vii |
| | LIST OF TABLES | xii |
| | LIST OF FIGURES | xiii |
| | LIST OF SYMBOLS | xviii |
| | LIST OF ABBREVIATIONS | xxi |
| | LIST OF APPENDICES | xxiv |
| 1 | INTRODUCTION | 1 |
| | 1.1 Background of Study | 1 |
| | 1.2 Problem Statement | 3 |
| | 1.3 Research Objectives | 3 |
| | 1.4 Scope of Study | 4 |
| | 1.5 Significances of Study | 5 |
| | 1.6 Thesis Structure and Organization | 5 |
| 2 | THEORY AND LITERATURE REVIEW | 7 |

| | | |
|--------|--|----|
| 2.1 | Overview | 7 |
| 2.2 | Fiber Lasers | 7 |
| 2.3 | Optical Gain Medium and Its Pumping Scheme | 8 |
| 2.3.1 | Erbium-doped Fiber | 9 |
| 2.4 | Cavity Design | 11 |
| 2.5 | Short Pulse Fiber Laser | 12 |
| 2.5.1 | Passively Mode-locking | 13 |
| 2.6 | Saturable Absorbers Mechanism | 14 |
| 2.7 | Carbon Nanotubes as Saturable Absorber | 16 |
| 2.7.1 | Modulation Depth or Saturable Absorption | 17 |
| 2.7.2 | Non-Saturable Loss | 18 |
| 2.7.3 | Saturation Intensity | 18 |
| 2.7.4 | Saturation Energy | 19 |
| 2.7.5 | Recovery Time | 20 |
| 2.8 | Self-starting Mode-locking | 21 |
| 2.8.1 | Bandwidth Broadening | 22 |
| 2.8.2 | High Repetition Rate of Pulses | 22 |
| 2.8.3 | Short Pulse Duration | 23 |
| 2.8.4 | High Peak Power | 24 |
| 2.8.5 | Time Bandwidth Product | 25 |
| 2.8.6 | Energy Fluctuations and Timing Jitter | 26 |
| 2.8.7 | Group Velocity Dispersion | 27 |
| 2.8.8 | Soliton Mode-locked | 31 |
| 2.9 | Harmonic Mode-locking Laser | 32 |
| 2.10 | Pulse Compression | 33 |
| 2.10.1 | High Order Nonlinear Effect | 34 |
| 2.10.2 | Supercontinuum Generation | 35 |

| | | |
|----------|---|-----------|
| 3 | METHODOLOGY | 37 |
| 3.1 | Overview | 37 |
| 3.2 | Continuous Wave Fiber Laser Assembled | 37 |
| 3.2.1 | Laser Diode as a Pump Source | 38 |
| 3.2.1.1 | Laser Pump Power Measurement | 42 |
| 3.2.2 | Lasing Medium | 42 |
| 3.2.2.1 | Experiment of the EDF Gain Measurement | 48 |
| 3.2.3 | Fiber Optic Components in Fiber Laser Cavity | 49 |
| 3.2.3.1 | Wavelength Division Multiplexer or Combiner | 49 |
| 3.2.3.2 | Optical Coupler | 51 |
| 3.2.3.3 | Optical Isolator | 53 |
| 3.2.4 | Erbium-doped Fiber Laser Experimental Setup | 57 |
| 3.3 | Construction of Mode-locked Fiber Laser | 58 |
| 3.3.1 | Saturable Absorber Preparation and Characterisation | 59 |
| 3.3.1.1 | Atomic Force Microscopy for Carbon Nanotubes Characterisation | 60 |
| 3.3.1.2 | Raman Spectroscopy for Carbon Nanotubes Characterisation | 61 |
| 3.3.1.3 | Nonlinear Saturable Absorption for Carbon Nanotubes Characterisation | 62 |
| 3.3.2 | Passively Mode-locking Erbium-doped Fiber Laser | 63 |
| 3.4 | Harmonic Mode-locking Erbium-doped Fiber Laser | 64 |
| 3.5 | Pulsed Narrowing via Supercontinuum Generation Technique | 65 |
| 3.6 | Analyser and Measurement Device | 66 |
| 3.6.1 | Optical Power Meter | 67 |
| 3.6.2 | Optical Spectrum Analyser | 68 |
| 3.6.3 | Digital Storage Oscilloscope | 69 |
| 3.6.4 | Radio Frequency Spectrum Analyser | 70 |

| | | |
|----------|--|-----------|
| | 3.6.5 Photodetector | 71 |
| | 3.6.6 Autocorrelator | 72 |
| | 3.7 Summary | 72 |
| 4 | RESULTS AND DISCUSSIONS | 73 |
| | 4.1 Overview | 73 |
| | 4.2 Assembly of Fiber Laser | 73 |
| | 4.2.1 Pump Power Measurement of Laser Diode | 74 |
| | 4.2.2 Gain Measurement of Erbium-doped Fiber | 76 |
| | 4.2.3 Erbium-doped Fiber Laser Continuous Wave | 81 |
| | 4.3 Development of Short Pulsed Fiber Laser | 85 |
| | 4.3.1 Characterisation of Carbon Nanotubes Thin Film as a Saturable Absorber | 85 |
| | 4.3.1.1 Atomic Force Microscopy Image | 85 |
| | 4.3.1.2 Raman Spectroscopy Spectra | 87 |
| | 4.3.1.3 Measurement of Nonlinear Saturable Absorption and Its Characterisation | 89 |
| | 4.3.2 Passively Mode-locking Erbium-doped Fiber Laser and Characterisation | 90 |
| | 4.3.2.1 Mode-locked Fiber Laser with Erbium-doped Fiber of Low Absorption | 91 |
| | 4.3.2.2 Mode-locked Fiber Laser with Erbium-doped Fiber of High Absorption | 100 |
| | 4.4 Harmonically Mode-locked Erbium-doped Fiber Laser for >100 MHz Repetition Rate | 107 |
| | 4.5 Supercontinuum Generation for Pulse Width Narrowing | 116 |
| | 4.5.1 Supercontinuum Generation of Mode-locked Laser with Low Absorption Erbium-doped Fiber | 116 |

| | | |
|----------|---|------------|
| | 4.5.2 Supercontinuum Generation of Mode-locked Laser with High Absorption Erbium-doped Fiber | 124 |
| 5 | CONCLUSION | 129 |
| | 5.1 Summary of Research Work | 129 |
| | 5.2 Problems and Limitations | 131 |
| | 5.3 Future Works | 131 |
| | REFERENCES | 132 |
| | Appendices A-B | 144-146 |

LIST OF TABLES

| TABLE NO. | TITLE | PAGE |
|------------------|---|-------------|
| 2.1 | Deconvolution factors, D_{AC} for the various shapes of laser pulses | 24 |
| 2.2 | K constant depends on the pulse shape | 26 |
| 2.3 | Fiber dispersion characteristics based on of the dispersion parameter sign of the fiber and the corresponding sign of the GVD coefficient | 31 |
| 2.4 | Different regimes of the mode-locked operation and the corresponding pulse shape fitting based on the sign of the total GVD of the cavity | 31 |
| 3.1 | Laser substrates, corresponding wavelength range and applications | 39 |
| 3.2 | Host materials of crystal and glass [80] | 43 |
| 3.3 | Specification of high concentration Erbium doped fiber | 47 |
| 3.4 | Specification of low concentration Erbium doped fiber | 47 |
| 3.5 | Fiber coupler 90/10 specification | 52 |
| 3.6 | Optical fiber isolator of wavelength 1550 nm | 56 |
| 4.1 | Characteristics of the mode-locked fiber laser with different length of gain medium | 103 |

LIST OF FIGURES

| FIGURE NO. | TITLE | PAGE |
|-------------------|---|-------------|
| 2.1 | Energy level of (a) three-level and (b) four-level pumping schemes. Wavy arrows indicate fast relaxation of the level population through non-radiative processes [29] | 9 |
| 2.2 | Energy level of Erbium ion in silica glasses [29] | 10 |
| 2.3 | Saturable absorber in a laser cavity mechanism [28] | 15 |
| 2.4 | Structure of carbon nanotubes | 17 |
| 3.1 | The laser diode converts electrical energy into energy in form of light. (www.Explainthatstuff.com) | 38 |
| 3.2 | (a) top view of laser diode pump, (b) content of a 14-pin butterfly package's fiber pigtail, (c) image of laser diode pump-14 pin butterfly package | 40 |
| 3.3 | Laser diode current and temperature controller driver with butterfly laser installed | 41 |
| 3.4 | Setup of laser pump power measurement | 42 |
| 3.5 | The energy levels of erbium in silica glasses [81]. | 44 |
| 3.6 | Erbium doped fiber (a) energy-level diagram, (b) before pumping and (c) after pumping process [82,83] | 45 |
| 3.7 | Erbium doped fiber cross section | 46 |
| 3.8 | Setup of gain measurement test | 48 |
| 3.9 | WDM principal for multiplexing and de-multiplexing | 49 |
| 3.10 | 980/1550 nm WDM fused fiber coupler; (a) The schematic diagram and (b) the image of WDM used in the setup | 50 |

| | | |
|------|---|----|
| 3.11 | 90/10 split ratio of optical fiber coupler with 1x2 ports (a) the schematic diagram and (b) the picture of optical coupler used in the setup. | 52 |
| 3.12 | In the isolator; Faraday rotator, with a polarizer and an analyser | 53 |
| 3.13 | Polarization dependent isolator; (a) Forward direction and | 54 |
| 3.14 | Polarization independent isolator; (a) Forward direction and (b) Backward direction | 55 |
| 3.15 | Fiber optic isolator 1550 nm; (a) schematic diagram and (b) image of isolator used in the setup | 56 |
| 3.16 | Erbium doped fiber laser setup | 58 |
| 3.17 | a) CNT thin film fixed to the FC/PC connector; b) CNT SA assembly | 59 |
| 3.18 | Optical couplant; index matching gel | 59 |
| 3.19 | SmartSPM TM -1000 (AIST-NT) scanning probe microscope main part | 60 |
| 3.20 | HORIBA Scientific: XploRA PLUS Raman microscope | 61 |
| 3.21 | Nonlinear absorbance measurement configurations | 63 |
| 3.22 | Configuration of passively mode-locking Erbium doped fiber laser (EDFL) | 64 |
| 3.23 | Experimental setup of the Supercontinuum generation | 66 |
| 3.24 | (a) integrating photodiode power sensor, (b) laser power and energy meter, USB Only Interface | 67 |
| 3.25 | YOKOGAWA optical spectrum analyser (OSA) | 68 |
| 3.26 | Tektronix TDS3052C Digital Phosphor Oscilloscope | 69 |
| 3.27 | Anritsu MS2638A Spectrum Analyser | 70 |
| 3.28 | Thorlabs; (a) Fiber-Coupled InGaAs Detectors and (b) SMA-to-BNC cable | 71 |
| 3.29 | Alnair Labs HAC200 autocorrelator | 72 |
| 4.1 | Optical pump power versus drive pump current | 75 |
| 4.2 | Spectrum of laser diode pump source | 75 |
| 4.3 | Variation of the gain with increasing pump power at different absorption peak and fiber length; a) EDF with low peak | |

| | | |
|------|---|----|
| | absorption of EDF length 3 m and b) EDF with high peak | |
| | absorption of EDF length 30 cm, 40 cm, and 50 cm | 77 |
| 4.4 | ASE power against the pump power; a) high absorption | |
| | EDF with length of 30 cm, 40 cm and 50 cm; b) low | |
| | absorption EDF with length of 300 cm | 79 |
| 4.5 | ASE spectrum at fixed pump power 66.5 mW of; a) high | |
| | absorption EDF with length of 30 cm, 40 cm and 50 cm; | |
| | b) low absorption EDF with length of 300 cm | 80 |
| 4.6 | Graph of laser output power (dBm) against the pump | |
| | current (mA); a) high absorption EDF and (b) low | |
| | absorption EDF. Graph of laser output power (mW) | |
| | against the pump power (mW); c) high absorption EDF | |
| | and d) low absorption EDF | 82 |
| 4.7 | Spectrum of continuous wave fiber laser at; a) high | |
| | absorption EDF and b) low absorption EDF | 84 |
| 4.8 | AFM topography images of CNT thin film | 86 |
| 4.9 | Raman scattering spectra of CNT thin film | 88 |
| 4.10 | Power dependent absorption data of the Carbon | |
| | nanotubes thin film saturable absorber. Inset graph; zoom | |
| | of the graph for clear view of the saturation intensity | |
| | value. | 89 |
| 4.11 | Mode-locked spectrum fiber laser of EDF with 3 meter | |
| | long | 92 |
| 4.12 | Spectra of mode-locked fiber laser with 3 meter long | |
| | EDF as gain medium against the increasing pump current | 93 |
| 4.13 | Pulse train output of mode-locked fiber laser with 3 meter | |
| | EDF gain medium | 94 |
| 4.14 | Radio frequency (RF) spectrum of the mode-locked | |
| | output pulses at 100 MHz span | 95 |
| 4.15 | RF spectra around (a) the fundamental repetition rate (f_1 | |
| | = 12.04 MHz), and (b) the seventh order of repetition rate | |
| | ($f_7 = 84.28$ MHz) | 97 |
| 4.16 | Plotted graph of autocorrelation trace of the mode locked | |
| | pulse with pulse width of 400 fs | 99 |

| | | |
|------|--|-----|
| 4.17 | Pulse duration at FWHM, τ_P of 400 fs obtained from Alnair-HAC 200 software | 99 |
| 4.18 | Optical spectrum and output pulse train of MLFL at high absorption EDF gain medium of different length; a), b): 30 cm, c), d): 40 cm and e), f): 50 cm | 101 |
| 4.19 | RF spectrum of MLFL of EDF 40 cm at a) fundamental repetition rate; b) RF spectrum up to 1 GHz | 104 |
| 4.20 | Autocorrelation trace of the mode locked fiber laser pulse of EDF length a) 30 cm, b) 40 cm, and c) 50 cm | 106 |
| 4.21 | Spectra of mode-locked fiber laser of EDF 40 cm before harmonic mode-locked obtained | 108 |
| 4.22 | (a) mode-locked spectrum at pump power of 75.3 mW before harmonic mode-locked occurred, Pulse train at fundamental repetition rate of 67.7 MHz; (b) in time scale of 500 ns and (c) in time scale of 100 ns | 110 |
| 4.23 | (a) Harmonic mode-locked spectrum at pump power of 81.3 mW, Pulse train at second order of harmonic with repetition rate of 97.7 MHz; (b) in time scale of 500 ns and (c) in time scale of 100 ns | 111 |
| 4.24 | (a) Harmonic mode-locked spectrum at maximum power of 104.2 mW, Pulse train at third order of harmonic with repetition rate of 193.5 MHz; (b) in time scale of 500 ns and (c) in time scale of 100 ns | 112 |
| 4.25 | Repetition rate and pulse energy of the harmonic mode locked pulse against pump power | 113 |
| 4.26 | Output spectra of different orders of harmonics at different pump powers | 114 |
| 4.27 | 3dB spectral bandwidth of harmonic mode-locked fiber laser against pump power | 115 |
| 4.28 | (a) 3 dB bandwidth spectrum of the amplified seed laser (MLFL of low absorption EDF 30 cm length) \sim 18.72 nm. (b) autocorrelation trace with Gaussian fitting of amplified seed laser (MLFL of low absorption EDF 30 cm length) pulse width 0.44 ps | 118 |

| | | |
|------|---|-----|
| 4.29 | (a) The Supercontinuum spectra developed from a HNLF seeded by MLFL with low absorption EDF. (b) Amplified launched peak power of the fiber laser source. | 120 |
| 4.30 | The supercontinuum pulse width of 70 fs | 122 |
| 4.31 | The spectra from the MLFL, amplified MLFL and SC of HNLF | 123 |
| 4.32 | Amplified mode-locked fiber laser of 40 cm length high absorption EDF | 125 |
| 4.33 | The SC spectra developed from a HNLF seeded by MLFL with high absorption EDF | 126 |
| 4.34 | a) The plotted SC pulse width; b) Screen short of SC pulse width from the autocorrelation trace software. | 127 |
| 4.35 | Combined spectra of SC spectrum in HNLF, MLFL spectrum and amplified MLFL spectrum | 128 |

LIST OF SYMBOLS

| | | |
|------------------|---|--|
| ω | - | Angular frequency |
| τ | - | Pulse width |
| σ | - | Absorption cross-section |
| ν | - | Phase velocity |
| $\alpha(i)$ | - | Nonlinear absorption coefficient |
| $\alpha(I)$ | - | Intensity dependent |
| $q(t)$ | - | Fast saturable absorber |
| f | - | Pulse repetition rate |
| $T(I)$, | - | Optical transmittance |
| $R(t)$ | - | Reflection |
| E_P | - | Pulse energy |
| τ_P | - | Pulse duration |
| λ_0 | - | Central wavelength |
| λ | - | Wavelength |
| $\Delta\lambda$ | - | Spectral bandwidth at full width half maximum |
| Yb^{3+} | - | Ytterbium ions |
| Tm^{3+} | - | Thulium ions |
| T | - | Cavity period |
| Sa^{3+} | - | Samarium ions |
| Pr^{3+} | - | Praseodymium ions |
| Nd^{3+} | - | Neodymium ions |
| N | - | Concentration of carbon nanotubes saturable absorber |
| n | - | Refractive index of the medium |
| n | - | Harmonic order |

| | | |
|------------------|---|---|
| l | - | Gain medium length |
| L | - | Total cavity length |
| k | - | Constant factor |
| Ho^{3+} | - | Holmium ions |
| \hbar | - | Photon |
| Er^{3+} | - | Erbium ions |
| E | - | Energy |
| D | - | Dispersion parameter |
| c | - | Speed of light |
| $A(t)$ | - | Effective area |
| $\Delta\tau$ | - | Temporal pulse width at full width half maximum |
| $\Delta\nu$ | - | Spectral pulse width at full width half maximum |
| ΔE | - | Change of output pulse energy |
| ΔP | - | Power ratio |
| Δf_{Res} | - | Resolution bandwidth of the spectrum analyser in Hz |
| Δf | - | Frequency width |
| τ_{rex} | - | Energy relaxation time |
| τ_{SA} | - | Recovery time |
| τ_{AC} | - | Pulse width autocorrelation |
| λ_D | - | Zero dispersion wavelength |
| $\gamma_0(\nu)$ | - | Signal gain coefficient |
| β_2 | - | Group velocity dispersion coefficient |
| α_{ns} | - | Non-saturation absorption |
| α_0 | - | Linear absorption |
| q_0 | - | Non-saturated saturable loss |
| l_0 | - | Linear non-saturable loss |
| V_g | - | Group velocity |
| P_{SA} | - | Saturation power |
| P_P | - | Peak power |
| I_{sat} | - | Saturation intensity |
| $G_0(\nu)$ | - | Signal gain |
| E_{SA} | - | Saturation energy |

- D_{AC} - Deconvolution factor
- ω_l - Laser frequency

LIST OF ABBREVIATIONS

| | | |
|-------|---|--------------------------------|
| AFM | - | Atomic force microscopy |
| ASE | - | Amplified spontaneous emission |
| BFA | - | Brillouin fiber amplifier |
| BNC | - | Bayonet Neill–Concelman |
| CNT | - | Carbon nanotubes |
| CW | - | Continuous wave |
| dBm | - | Decibel per milliwatts |
| dB/m | - | Decibel per meter |
| DCF | - | Dispersion compensating fiber |
| DSO | - | Digital storage oscilloscope |
| EDF | - | Erbium-doped fiber |
| EDFL | - | Erbium-doped fiber laser |
| EMI | - | Electromagnetic interference |
| FC/PC | - | Flat physical contact |
| FELs | - | Free electron laser |
| FWHM | - | Full width at half maximum |
| FWM | - | Four wave mixing |
| GVD | - | Group velocity dispersion |
| HNLF | - | Highly nonlinear fiber |
| LD | - | Laser diode |
| L-I | - | Light– Current |
| mA | - | Milliampere |
| MHz | - | Megahertz |
| MI | - | Modulation instability |
| MLFL | - | Mode-locked fiber laser |

| | | |
|---------|---|---|
| mW | - | Milliwatts |
| NA | - | Numerical aperture |
| NIR | - | Near-infrared |
| NPR | - | Nonlinear polarization rotation |
| OPM | - | Optical power meter |
| OSA | - | Optical spectrum analyser |
| PC | - | Personal computer |
| PD | - | Photo diode |
| PDL | - | Polarization dependent loss |
| POP | - | Plane of polarization |
| QHML | - | Quasi-harmonic mode-locked |
| RBM | - | Radial breathing mode |
| RFA | - | Raman fiber amplifier |
| RFSA | - | Radio frequency spectrum analyser |
| SA-CNT | - | Carbon nanotubes saturable absorber |
| SBR | - | Saturable Bragg reflector |
| SC | - | Supercontinuum |
| SCG | - | Supercontinuum generation |
| SESAM | - | Semiconductor saturable absorber mirror |
| SMA | - | Sub-miniature version A |
| SNR | - | Signal-to-noise ratio |
| SOA | - | Semiconductor optical amplifier |
| SPM | - | Self-phase modulation |
| SPM | - | Scanning probe microscopes |
| SRS | - | Stimulated Raman scattering |
| SSFS | - | Soliton self-frequency shift |
| SWCNT | - | Single-walled carbon nanotubes |
| TDS | - | Time-domain spectroscopy |
| TEC | - | Thermoelectric cooler |
| THz | - | Terahertz |
| THz-TDS | - | Terahertz time-domain spectroscopy |
| TLS | - | Tunable laser source |

| | | |
|-----|---|---------------------------------|
| TOD | - | Third order dispersion |
| TPA | - | Two photon absorption |
| VOA | - | Variable optical attenuator |
| WDM | - | Wavelength division multiplexer |
| XPM | - | Cross-phase modulation |
| ZDW | - | Zero dispersion wavelength |

LIST OF APPENDICES

| APPENDIX | TITLE | PAGE |
|-----------------|---|-------------|
| A | Dispersion profile of a 100 m length of HNFLF (NL1016-B) provided by the manufacturer (OELabs) | 144 |
| B | List of Publications | 145 |

CHAPTER 1

INTRODUCTION

1.1 Background of Study

The laser invention in 1960 had sparked the interest in optical physics, and among the arising research field is ultrafast optics fields where generations of nanosecond (10^{-9}) pulses by the first mode-locked laser is initiated. Yet, the generation of ultrafast pulses are remained as the active research subject thus led to the variety of designs including assembly of time scale pulses of femtosecond (10^{-15}). The short pulse laser system had explored through a wide range of areas including scientific research field, medical and industrial applications. This system with ultrashort pulses had been studied in time resolves studies in chemistry, two photon and CARS spectroscopy and microscopy, optical coherence tomography and terahertz generation. In the medical field, the applications that related to short laser pulses are including eye laser surgery and dentist drill. For industry applications, ultrafast lasers are implied in micro-machining and marking [1].

Generally, for terahertz generation, multi-wavelengths lasers such as dual-wavelength lasers with closely spaced lines are required, either as a high-power continuous wave (CW) or pulse laser sources. One of the developments of the femtosecond laser that mostly been constructed for terahertz generation is Titanium Sapphire femtosecond lasers [2–5]. A solid state laser known as Titanium Sapphire

(Ti: sapphire) have operating wavelength at spectral range of 0.75 μm to 1.0 μm . This laser is most extensively utilised as an ultrafast optical source due to the large bandwidth and superior thermal properties of the laser. However, this laser came with bulky, complicated system, and very expensive. Therefore, due to this problem, a compact and cost-effective laser source should be considered, and the idea of femtosecond laser generation using fiber had been carried out. Fiber based sources commonly used for telecommunications in the wavelength region of 1.5 μm . Erbium doped fiber (EDF) is desirable as a gain medium in this region due to the development of wavelength division multiplexed systems (WDMs). Femtosecond fiber lasers offer several advantages over bulk solid-state lasers, including greater stability, reduced alignment sensitivity, and compact design [6–8]. Furthermore, fiber lasers are efficient and these qualities make short pulse fiber lasers more attractive.

Femtosecond fiber laser can also be achieved using electro-optics components integrate with the laser cavity which is known as the active approach. However, this approach introduces high loss and increased complexity to the setup. As an alternative, passive mode-locking is preferable compared to the active counterpart due to the compactness, simplicity, and reliability of a saturable absorber (SA) in the laser cavity design. Recently, single wall carbon nanotubes (CNTs) have emerged as a promising SA due to their low saturation intensity, sub-picosecond recovery time, and environmental robustness [9]. By contrast, the predominant SAs, for example, semiconductor saturable mirrors, are limited by their narrow tuning range for only a few nanometers (nm), high cost in the fabrication process and packaging [10]. Fabrication of these materials can be challenging in the 1.3–1.5 μm region for optical communication purposes [11,12].

Therefore, this work focused on the development of ultrashort femtosecond fiber laser pulses used as a laser source for terahertz wave generations. Research on the development of a robust, compact and stable of the laser is performed.

1.2 Problem Statement

Currently, fiber lasers are the alternative way to solid state lasers as they offer ultrashort pulse duration with good consistency, compactness, alignment free and excellent beam quality. Common techniques for prompting the mode-locked operation of a fiber laser is nonlinear polarization evolution (NPE) and semiconductor saturable absorber mirror (SESAM). Both techniques had limitations as they suffer from high-intensity losses, limited operation bandwidth and a complex and expensive fabrication process. Therefore, to overcome the issues, unconventional and new saturable absorbers such as carbon nanotubes, graphene and few-layer molybdenum disulfide (MoS_2) had been employed since they are broadband and cost-effective. Then, high repetition rate pulses in mode locked fiber lasers could be achieved either by shortening the cavity in centimeter scale or employed harmonic mode locking (HML). Synthesized carbon nanotubes microfiber saturable absorber in the laser cavity had generated pulse width of a passively mode-locked fiber laser. However, by compressing the designed passively mode-locked fiber laser using nonlinear dispersive media, it can narrow the pulse width and gives a superbly broadens spectrum known as supercontinuum generation. Thus, this believes can gives high repetition rate pulses in mode locked fiber lasers with narrow pulse width.

1.3 Research Objectives

The main aim of this study is to develop a femtosecond fiber laser system with simple cavity design. This work is measured based on the performance of the designed fiber laser, where it is divided into four sequence objectives given as follows;

1. To characterise the erbium-doped fiber (EDF) as the gain medium and modes of the laser operation.
2. To attain ultra-short pulse fiber laser via the passively mode-locked technique using carbon nanotubes saturable absorber.
3. To determine the high pulse repetition rate ~80 to 100 MHz with harmonic mode-locked methods.
4. To narrow the pulse width from picosecond into femtosecond by using supercontinuum generation technique.

1.4 Scope of Study

This work is conducted to develop a femtosecond fiber laser and the scope is focused on using a passively mode-locking technique. It is preferable to the active counterpart owing to the compactness, simplicity, and reliability of a saturable absorber (SA) in the laser cavity design. A carbon nanotubes thin film is employed as a promising saturable absorber due to the low saturation intensity, sub-picosecond recovery time, and environmental robustness. A laser diode of InGaAs at the wavelength of 980 nm is efficiently pumping for compact and reliable of laser source at wavelength 1.5 -1.6 μm . Erbium doped fiber (EDF) gain medium operating in the telecommunication wavelength region of 1.55 μm is utilised because it has the simplest approach to designing fiber laser system, and potential to deliver high-quality mode-locked pulses. The gain medium has two different absorption peak power of 16 dB/m with length fixed at 300 cm and 110 dB/m with length varied from 30 cm, 40 cm, to 50 cm. These gain medium lengths are depending on the total cavity length for laser generation. A hundred meters of highly nonlinear fiber is employed as dispersive media for pulse narrowing thru supercontinuum generation due to its zero dispersion wavelengths at 1568 nm, which corresponds to the region of injected mode-locked erbium doped fiber laser (ML-EDFL).

1.5 Significances of Study

Generation of the femtosecond fiber laser had facilitated in improving the laser technology and move away from Titanium; Sapphire solid state laser into compact pulse fiber laser. The primary contributions of this study are occupying the demands of low-cost compact fiber laser as a source of all fiber system terahertz time domain spectroscopy. Through this study, it will benefit to the other researchers in understanding and construct the femtosecond fiber laser step by step. Researchers may vary the technique used for femtosecond fiber laser generation and also improvise using novel theory and method.

1.6 Thesis Structure and Organization

The thesis outline has begun with the introduction to the work in Chapter 1. Divide into several subtopics, the study frameworks are discussed through the problem statements, followed by objectives of the research. Then, scopes of study applied are stated in detail and contributions of this study are identified in the subtopic of significance of the study.

In Chapter 2, the theoretical aspects of this work are highlighted, including the theoretical background of pulse propagation in optical fibers, rate equation of erbium doped fiber (EDF) as the gain medium, mode operation of the laser; continuous wave and pulse wave. Also, possible techniques of pulse generations include; Q-switching, mode-locking and Q-switched mode locking. Most focus is on passively mode locking since the objective is the mode locked generation using this technique. This chapter also concisely introduced with theoretical equations and the essential parameters of the mode locked output characterization.

Chapter 3 introduces the optical instrument or components utilised in this work. Optical properties, including pump laser diode, Erbium doped fiber absorption properties, carbon nanotubes saturable absorber characterization method based on a literature review, and setup for a series of the experiment are graphically explained and presented in this chapter.

The experimental results taken based on the presented setup in chapter 3 and data analyses are covered in Chapter 4. This chapter starts with a basic characterization of pump laser diode, then different length of Erbium doped fiber which acts as a gain medium with different absorption are analysed. The output performance of the constructed simple ring cavity of Erbium doped fiber laser (EDFL) with different length and Erbium-doped concentration is analysed and discussed. Afterward, the characterization of the pulse wave laser generated by inserting the carbon nanotubes saturable absorber known as a passively mode-locking generation is obtained and discussed. To generate a high repetition rate of the mode-locked laser, harmonic mode locking at a particular pump power is observed. Further development of the femtosecond fiber laser, the EDFL based carbon nanotubes saturable absorber is demonstrated as a pulse source for supercontinuum (SC) generation, and 100 m of highly nonlinear fiber (HNLF) is being required as the nonlinear medium.

Chapter 5 summarized all the results and discussions on the generation of the ultrashort pulse fiber laser. The outlook and aim of this work are again highlighted. The problems and limitation occurred during the research work are discussed as well as the future work needed to overcome the problems are suggested.

REFERENCES

1. Nielsen, C. K. *Mode Locked Fiber Lasers : Theoretical and Experimental Developments*. Ph.D. Thesis. University of Aarhus, Demark; 2006.
2. Curley, P. F., Ferguson, A. I., White, J. G., Amos, W. B., Application of a Femtosecond Self-sustaining Mode-locked Ti:sapphire Laser to the Field of Laser Scanning Confocal Microscopy. *Opt. Quantum Electron.* 1992, 24, 851–859.
3. Keller, U., 'tHooft, G. W., Knox, W. H., Cunningham, J. E. Femtosecond Pulses from a Continuously Self-starting Passively Mode-locked Ti:sapphire Laser. *Opt. Lett.* 1991, 16: 1022.
4. Cerullo, G., De Silvestri, S., Magni, V., Pallaro, L., Resonators for Kerr-lens Mode-locked Femtosecond Ti:sapphire Lasers. *Opt. Lett.* 1994, 19: 807–809.
5. Bartels, A., Heinecke, D., Diddams, S. A. Passively Mode-locked 10 GHz Femtosecond Ti:sapphire Laser. *Opt. Lett.* 2008, 33: 1905–7.
6. Ilday, F. O., Wise, F. W., Sosnowski, T. High-Energy Femtosecond Stretched-pulse Fiber Laser with a Nonlinear Optical Loop Mirror. *Opt. Lett.* 2002, 27: 1531–1533.
7. Isomäki, A., Okhotnikov, O. G. Femtosecond Soliton Mode-locked Laser based on Ytterbium-doped Photonic Bandgap Fiber. *Conf. Proc. - Lasers Electro-Optics Soc. Annu. Meet.* 2007. 394–395.
8. Jang, H., Jang, Y. S., Kim, S., Lee, K., et al. Polarization Maintaining Linear Cavity Er-doped Fiber Femtosecond Laser. *Laser Phys. Lett.* 2015, 12: 105102.
9. Sun, Z., Hasan, T., Ferrari, A.C. Ultrafast Lasers Mode-locked by Nanotubes and Graphene. *Phys. E Low-Dimensional Syst. Nanostructure.* 2012, 44: 1082–1091.

10. Yusoff, A. R. B. M., Dai, L., Cheng, H. M., Liu, J. Graphene based Energy Devices. *Nanoscale*. 2015, 7: 6881–6882.
11. Calvez, S., Hopkins, J. M., Smith, S. A., Clark, A. H., et al. GaInNAs/GaAs Bragg-mirror-based Structures for Novel 1.3 μ m Device Applications. *J. Cryst. Growth*. 2004, 268: 457–465.
12. Vainionpää, A., Suomalainen, S., Isomäki, A., Tengvall, O., et al. Semiconductor Saturable Absorber Mirror with Wavelength Tailored Distributed Bragg Reflector, *J. Cryst. Growth*. 2005, 278: 751–755.
13. Agrawal G. Chapter 5: Fiber Lasers. In; *Appl. Nonlinear Fiber Opt.* Theodbold's Road, London: Academic Press. 179–244; 2008.
14. Kurosaki, Y., Satoh, K. A Fiber Laser Welding of Plastics Assisted by Transparent Solid Heat Sink to Prevent the Surface Thermal Damages. *Phys. Procedia*. 2010, 5: 173–181.
15. Fermann, M. E., Hartl, I. Ultrafast Fiber Laser Technology. *IEEE J. Sel. Top. Quantum Electron*. 2009, 15: 191–206.
16. Baumeister, M., Dickmann, K., Houtl, T. Fiber Laser Micro-cutting of Stainless Steel Sheets. *Appl. Phys. A*. 2006, 85: 121–124.
17. Farah Diana binti Muhammad. *Graphene as Saturable Absorber for Photonics Applications*. Ph.D. Thesis. University of Malaya, Malaysia; 2015.
18. Siti Nadirah binti Mohamed Hassan. *Multiwall Carbon Nanotube (MWCNT) as a Saturable Absorber for Generation of High Q-Factor in Erbium Doped Fiber Laser (EDFL)*. Master Degree Thesis. University of Malaya, Malaysia; 2016.
19. Agrawal, G.P. *Applications of Nonlinear Fiber Optics*. 2nd. ed. Theodbold's Road, London: Academic Press. 2001.
20. Çokrak, A. C., Altuncu, A. Gain and Noise Figure Performance of Erbium Doped Fiber Amplifiers (EDFA). *J. Electr. Electron. Eng.* 2004, 4: 1111–1122.
21. Becker, P. C., Olsson, N. A., Simpson, J. R. Erbium Doped Fiber Amplifier. In; *Erbium-Doped Fiber Amplifiers Fundamentals and Technology*. London: Academic Press. 401–427: 1999.
22. Suemune, T., Takahashi, Y. SOA Fiber Ring Laser and Its Application to

- Electric Field Sensing in Frequency Domain. *Opt. Lasers Eng.* 2007, 45: 789–794.
23. Wang, F., Zhang, X. L., Yu, Y., Huang, X. 82 Channel Multi-wavelength Comb Generation in a SOA Fiber Ring Laser. *Opt. Laser Technol.* 2010, 42: 285–288.
 24. Qian, L., Fen, D., Xie, H., Sun, J. A Novel Tunable Multi-wavelength Brillouin Fiber Laser with Switchable Frequency Spacing. *Opt. Commun.* 2015, 340:74–79.
 25. Ou, Z., Bao, X., Li, Y., Saxena, B., Chen, L. Ultra-narrow Linewidth Brillouin Fiber Laser. *IEEE Photonics Technol. Lett.* 2014, 26: 2058–2061.
 26. Feng, Y., Taylor, L. R., Calia, D. B. 150W Highly-Efficient Raman Fiber Laser. *Opt. Express.* 2009, 17: 23678–23683.
 27. Turitsyn, S. K., Ania Castan, J. D., Babin, S. A., Karalekas, V., et al. 270-km Ultralong Raman Fiber Laser. *Phys. Rev. Lett.* 2009, 103.
 28. Johnstone, W., Culshaw, B., Walsh, D., Moodie, D. G., Mauchline, I. S. Student Laboratory Experiments on Erbium-Doped Fiber Amplifiers and Lasers. *Spie.* 2000, 44:259.
 29. Brandstätter, B., McClung, A., Schüppert, K., Casabone, B., et al. Integrated Fiber-Mirror Ion Trap for Strong Ion-Cavity Coupling. *Rev. Sci. Instrum.* 2013, 84(12): 1-17.
 30. Jeong, H., Choi, S., Oh, K. Continuous Wave Single Transverse Mode Laser Oscillation in a Nd-Doped Large Core Double Clad Fiber Cavity with Concatenated Adiabatic Tapers. *Opt. Commun.* 2002, 213: 33–37.
 31. Takahashi, M., Tai, S., Kyuma, K., Hamanaka, K. Fiber Optic Passive Ring Resonator Gyroscope using an External Cavity Laser Diode. *Opt. Lett.* 1988, 13: 236–238.
 32. Ponikvar, D. R., Ezekiel, S. Stabilized Single Frequency Stimulated Brillouin Fiber Ring Laser. *Opt. Lett.* 1981, 6: 398–400.
 33. Boguslawski, J., Sotor, J., Sobon, G., Abramski, K. M. 80 fs Passively Modelocked Er-doped Fiber Laser. *Laser Phys.* 2015, 25: 065104.
 34. Sobon, G., Sotor, J., Jagiello, J., Kozinski, R., et al. Graphene Oxide vs . Reduced Graphene Oxide as Saturable Absorbers for Er-doped Passively

- Mode-locked Fiber Laser. *Opt. Express*. 2012, 20(17): 19463–19473.
35. Zhang, H., Lu, S. B., Zheng, J., Du, J., et al. Molybdenum disulfide (MoS_2) as a Broadband Saturable Absorber for Ultrafast Photonics. *Opt. Express*. 2014, 22(72): 49–60.
 36. Ahmad, H., Thambiratnam, K., Muhammad, F.D., Zulkifli, M.Z., et al. QSwitching and Mode-locking in Highly Doped $\text{Zr}_2\text{O}_3\text{-Al}_2\text{O}_3\text{-Er}_2\text{O}_3$ -Doped Fiber Lasers Using Graphene as a Saturable Absorber. *IEEE J. Sel. Top. Quantum Electron*. 2014, 20: 9–16.
 37. Liu, J., Wang, Y., Qu, Z., Fan, X. $2\mu\text{m}$ Passive Q-Switched Mode-Locked Tm^{3+} :YAP Laser with Single-Walled Carbon Nanotube Absorber. *Opt. Laser Technol*. 2012, 44: 960–962.
 38. Michael Eckerle, Christelle Kieleck, J. Š., Jackson, S. D., Mazé, G., and Eichhorn, M. Actively Q-switched and Tm^{3+} Doped Silicate 2 Mikrometer Fiber Laser for Supercontinuum Generation in Fluoride Fiber. *Opt. Lett*. 2012, 37: 512–514.
 39. Nielsen, C. K., Keiding, S. R., All-Fiber Mode-Locked Fiber Laser. *Opt. Lett*. 2007, 32: 1474–1476.
 40. Collings, B. C., Bergman, K., Cundiff, S. T., Tsuda, S., et al. Short Cavity Erbium/Ytterbium Fiber Lasers Mode-Locked with a Saturable Bragg Reflector. *IEEE J. Sel. Top. Quantum Electron*. 1997, 3: 1065–1074.
 41. Matsas, V. J., Richardson, D. J., Newson, T. P., Payne, D. N., Characterization of a Self-starting, Passively Mode-Locked Fiber Ring Laser that Exploits Nonlinear Polarization Evolution. *Opt. Lett*. 1993, 18: 358–360.
 42. Dvoretzkiy, D. A., Sazonkin, S. G., Voropaev, V. S., Leonov, S. O., et al. Dispersion-managed Soliton Generation in the Hybrid Mode-Locked ErbiumDoped All-Fiber Ring Laser. *Proc. Int. Conf. Laser Opt*. 2016, 128.
 43. Kashiwagi, K., Yamashita, S., Deposition of Carbon Nanotubes around Microfiber via Evanescent Light. *Opt. Express*. 2009, 17: 8364–18370.
 44. Sun, Z., Hasan, T., Wang, F., Rozhin, A. G., et al. Ultrafast Stretched-pulse Fiber Laser Mode-locked by Carbon Nanotubes. *Nano Res*. 2010, 3: 404–411.
 45. Yamashita, S., Inoue, Y., Maruyama, S., Murakami, Y., et al. Saturable Absorbers Incorporating Carbon Nanotubes Directly Synthesized onto

- Substrates and Fibers and Their Application to Mode-Locked Fiber Lasers. *Opt. Lett.* 2004, 29(158): 1–3.
46. Sun, Z., Rozhin, A.G., Wang, F., Hasan, T., et al. A Compact, High Power, Ultrafast Laser Mode-Locked by Carbon Nanotubes. *Appl. Phys. Lett.* 2009, 95: 2009–2011.
 47. Li, X., Wu, K., Sun, Z., Meng, B., Wang, Y., Yu, X., Yu, X., Zhang, Y. Single-wall Carbon Nanotubes and Graphene Oxide-Based Saturable Absorbers for Low Phase Noise Mode-Locked Fiber Lasers. *Sci. Rep.* 2015, 6: 1–9.
 48. Chiu, J., Lan, Y., Chang, C., Chen, X., et al. Concentration Effect of Carbon Nanotube Based Saturable Absorber on Stabilizing and Shortening Mode-Locked Pulse. *Opt. Express.* 2010, 18(4): 3592–3600.
 49. Von, V., Shchatsinin, I., Chapter 5 Femtosecond Laser Pulses. In: *Free Clust. Free Mol. strong, shaped laser fields*. Berlin: Freien Universit“. 51-78; 2010.
 50. Grahelj, D., Poberaj, I. Solitons in Optics. University of Ljubljana, Ljubljana. 2010, 1–15.
 51. Liu, X., Han, D., Sun, Z., Zeng, C., et al. Versatile Multi-wavelength Ultrafast Fiber Laser Mode-Locked by Carbon Nanotubes. *Sci. Rep.* 2013, 3: 2718.
 52. Kuriakose, V. C., Porsezian, K. Elements of Optical Solitons: An Overview. *Resonance.* 2010, 15(7): 643–666.
 53. Abramczyk, H. *Dispersion Phenomena in Optical Fibers*. Unpublished note. Technical University of Lodz, Poland.
 54. Salgado, H. 2007. *Dispersion in Optical Fibers*. Unpublished note.
 55. Li, H. F., Zhang, S. M., Du, J., Meng, Y. C., et al., Passively Harmonic Mode-locked Fiber Laser with Controllable Repetition Rate based on a Carbon Nanotubes Saturable Absorber. *Opt. Commun.* 2012, 285: 1347–1351.
 56. Dupriez, P., Piper, A., Malinowski, A., Sahu, J. K., et al. High Average Power, High Repetition Rate, Picosecond Pulsed Fiber Master Oscillator Power Amplifier Source Seeded by a Gain-Switched Laser Diode at 1060 nm. *IEEE Photonics Technol. Lett.* 2006, 18: 1013–1015.
 57. Habruseva, T., Mou, C., Rozhin, A., Sergeyev, S. V. Polarization Attractors in Harmonic Mode-Locked Fiber Laser. *Opt. Express.* 2014, 22: 15211–15217.

58. Grudinin, A. B., Gray, S. Passive Harmonic Mode Locking in Soliton Fiber Lasers. *J. Opt. Soc. Am. B.* 1997, 14: 144.
59. Chen, T., Liao, C. R., Wang, D. N., Wang, Y. P. Polarization-Locked Vector Solitons in a Mode-Locked Fiber Laser Using Polarization-Sensitive FewLayer Graphene Deposited D-Shaped Fiber Saturable Absorber. *J. Opt. Soc. Am. B-Optical Phys.* 2014, 31: 1377–1382.
60. Mou, C., Arif, R., Rozhin, A., Turitsyn, S., Passively Harmonic Mode-locked Erbium-doped Fiber Soliton Laser with Carbon Nanotubes based Saturable Absorber. *Opt. Materials Express.* 2012, 2: 884–890.
61. Martinez, A., Zhou, K., Bennion, I., Yamashita, S., Passive Mode-Locked Lasing by Injecting a Carbon Nanotube-Solution in the Core of an Optical Fiber. *Opt. Express.* 2010, 18: 11008.
62. Agrawal, G. P. Chapter 6 Pulse Compression. In: *Appl. Nonlinear Fiber Opt.*, London: Academic Press. 263–318; 2001.
63. Lin, S. S., Hwang, S. K., Liu, J. M. Supercontinuum Generation in Highly Nonlinear Fibers Using Amplified Noise-Like Optical Pulses. *Opt. Express.* 2014, 22: 4152–4160.
64. Takayanagi, J., Nishizawa, N., Generation of Widely and Flatly Broadened, Low-Noise and High-Coherence Supercontinuum in All-Fiber System. *Japanese J. Appl. Physics, Part 2 Lett.* 2006, 45.
65. Head, C. R., Chan, H., Feehan, J. S., Shepherd, D. P., et al. Supercontinuum Generation with Femtosecond Pulse Fiber Amplified VECSELS. 2013, 86(6): 1–8.
66. Krčmarík, D., Slavík, R., Park, Y., Azaña, J. Nonlinear Pulse Compression of Picosecond Parabolic-Like Pulses Synthesized with a Long Period Fiber Grating Filter. *Opt. Express.* 2009, 17(70): 74–87.
67. Chang, G., Norris, T. B., Winful, H. G., Optimization of Supercontinuum Generation in Photonic Crystal Fibers for Pulse Compression. *Opt. Lett.* 2003, 28: 546.
68. Genty, G., Coen, S., Dudley, J. M., Fiber Supercontinuum Sources (Invited). *J. Opt. Soc. Am. B.* 2007, 24: 1771.
69. Hideyuki, S., Supercontinuum Generation and Its Applications. *J. Natl. Inst.*

- Inf. Commun. Technol.* 2006, 53: 33–40.
70. Lehtonen, M., Genty, G., Ludvigsen, H., Kaivola, M. Supercontinuum Generation in a Highly Birefringent Microstructured Fiber. *Appl. Phys. Lett.* 2003, 82: 2197–2199.
 71. Dudley, J. M., Genty, G., Coen, S., Supercontinuum Generation in Photonic Crystal Fiber. *Rev. Mod. Phys.* 2006, 78: 1135–1184.
 72. Buczynski, R., Sobon, G., Sotor, J., Stepniewski, G., et al. Infrared Supercontinuum Generation in Soft-Glass Photonic Crystal Fiber Pumped with a Femtosecond Er-Doped Fiber Laser Mode-Locked by Grapheme Saturable Absorber. *Conf. Lasers Electro-Optics Eur. Int. Quantum Electron.* 2013, 105106.
 73. Torrey Hills Technologies. *Tungsten, Tungsten Alloy, Tungsten Carbide, Molybdenum, Heat Sinks, Equipment.*
 74. Kokyo Inc., *Chapter 2: Package of Laser Diode | Laser Diode Selection.* 2015.
 75. Rydberg, S. *Rare Earth Elements in Optical Materials and Design of High Power Ytterbium Fiber Laser for Frequency Doubling Using Nonlinear Crystal.* Ph. D. Thesis. Mid Sweden University; 2010.
 76. Desurvire, E. Erbium-Doped Fiber Amplifiers: Principles and Applications. *Phys. Today.* 1995, 48: 56.
 77. Jeng, C., Chen, J., Sheu, F. Green Up-conversion Emissions of an Erbium Doped Fiber Pumped by Infrared Lasers. *Int. Conf. Opt. Photonics.* 2008, 2: 3–5.
 78. Corporation, N. NTT Network Innovation Laboratories Organization; About Optical Amplifiers, Technology Supporting Photonic Networks. *Nippon Telegr. Teleph. Corp.* 2016.
 79. Paschotta, R., Encyclopedia of Laser Physics and Technology-wavelength Division Multiplexing. *RP Photonics Consult. GmbH.* 2012.
 80. Fu, L., Yu, M. Carbon Nanotubes Based Thin Films: Fabrication, Characterization and Applications. *Rev. Adv. Mater. Sci.* 2014, 36: 40–61..
 81. Law, C. *Semiconductor Laser Device-Level Characteristics.* Master Degree Thesis. California Polytechnic State University; 2011.

82. Xu, J., Wu, S., Li, H., Liu, J., et al. Dissipative Soliton Generation from a Graphene Oxide Mode-Locked Er-Doped Fiber Laser. *Opt. Express*. 2012, 20(21): 23653-23658.
83. Luo, Z. Q., Wang, J. Z., Zhou, M., Xu, H. Y., et al. Multiwavelength ModeLocked Erbium-Doped Fiber Laser based on the Interaction of Graphene and Fiber-Taper Evanescent Field. *Laser Phys. Lett.* 2012, 9: 229–233.
84. Zhu, W., Qian, L., Helmy, A. S., Implementation of Three Functional Devices using Erbium-Doped Fibers: An Advanced Photonics Lab. *Proc. SPIE*. 2015, 9665: 10–11.
85. Al-Mansoori, M. H., Al-Ghaithi, W. S. 56.6 dB High Gain L-Band EDFA Utilizing Short-Length Highly-Doped Erbium Rare-Earth Material. *J. Eur. Opt. Soc. Publ.* 2014, 9: 4–7.
86. Gangwar, R., Singh, S.P., Singh, N. Gain Optimization of an Erbium-Doped Fiber Amplifier and Two-Stage Gain-Flattened EDFA with 45 nm Flat Bandwidth in the L-Band. *Opt. Int. J. Light Electron Opt.* 2010, 121: 77–79.
87. Cristofori, V., Lali-Dastjerdi, Z., Lund-Hansen, T., Peucheret, C., Rottwitz, K. Experimental Investigation of Saturation Effect on Pump-to-Signal Intensity Modulation Transfer in Single Pump Phase Insensitive Fiber Optic Parametric Amplifiers Valentina. *J. Opt. Soc. Am. B.* 2013, 30: 884–888.
88. Shirazi, M. R., Harun, S. W., Ahmad, H. Effective use of an EDFA and Raman Pump Residual Powers via Bi-EDF in L-Band Multi-wavelength Fiber Laser Generation. *Laser Phys.* 2015, 25: 015104.
89. Jusoh, Z., Harun S. W., Shahabudin N. S., Ahmad H., Paul M. C., Das S., Dhar A. Dual-Wavelength Erbium-Ytterbium Co-Doped Fiber Laser Operating at 1064 and 1534 nm. *Ukr. J. Phys. Opt.* 2014, 15: 118–122.
90. Coherent Inc., Lasers: Understanding the Basics | Photonics Handbook® | EDU.Photonics.com n.d.
91. Kwon, C. H., Chun, K. Y., Kim, S. H., Lee, J. H., et al., Torsional Behaviors of Polymer-Infiltrated Carbon Nanotube Yarn Muscles Studied with Atomic Force Microscopy. *Nanoscale*. 2015, 7: 2489–2496.
92. Souier, T., Stefancich, M., Chiesa, M. Characterization of Multi-Walled Carbon Nanotube–Polymer Nanocomposites by Scanning Spreading

- Resistance Microscopy. *Nanotechnology*. 2012, 23: 405704.
93. Dresselhaus, M. S., Jorio, A., Hofmann, M., Dresselhaus, G., Saito, R. Perspectives on Carbon Nanotubes and Graphene Raman Spectroscopy. *Nano Lett.* 2010, 10: 751–758.
 94. Jorio, A., Pimenta, M. A., Souza Filho, A. G., Saito, R. Characterizing Carbon Nanotube Samples with Resonance Raman Scattering. *New J. Phys.* 2012, 5: 1–11.
 95. Wang, F., Rozhin, A.G., Sun, Z., Scardaci, V., et al. Soliton Fiber Laser Mode-Locked by a Single-wall Carbon Nanotube-Polymer Composite. *Phys. Status Solidi Basic Res.* 2008, 245: 2319–2322.
 96. Scardaci, V., Sun, Z., Wang, F., Rozhin, A.G., et al. Carbon Nanotube Polycarbonate Composites for Ultrafast Lasers. *Adv. Mater.* 2008, 20: 4040–4043
 97. Martinez, A., Fuse, K., Xu, B., Yamashita, S. Optical Deposition of Graphene and Carbon Nanotubes in a Fiber Ferrule for Passive Mode- Locked Lasing. *Opt. Express*. 2010, 18: 2242–2244.
 98. Yamashita, S., Martinez, A., Xu, B., Short Pulse Fiber Lasers Mode-Locked by Carbon Nanotubes and Graphene. *Opt. Fiber Technol.* 2014, 20: 702–713.
 99. Luo, D., Li, W., Liu, Y., Wang, C., et al. High power Self-similar Amplification Seeded by a 1 GHz Harmonically Mode-Locked Yb-Fiber Laser. *Appl. Phys. Express*. 2016, 9: 1-4.
 100. Tan, W. D., Tang, D. Y., Zhang, J., Shen, D. Y., et al. Dissipative Soliton Operation of an $\text{Yb}^{3+}:\text{Sc}_2\text{SiO}_5$ Laser in the Vicinity of Zero Group Velocity Dispersion. *Opt. Photonics Lett.* 2012, 5: 1250001.
 101. Okhotnikov, O., Grudinin, A., Pessa, M. Ultra-Fast Fiber Laser Systems based on SESAM Technology: New Horizons and Applications. *New J. Phys.* 2004, 6, 1–22.
 102. Hönninger, C., Paschotta, R., Morier-Genoud, F., Moser, M., Keller, U. Q-switching Stability Limits of Continuous-Wave Passive Mode Locking. *J. Opt. Soc. Am. B.* 1999, 16: 46.
 103. Yu, Z., Wang, Y., Zhang, X., Dong, X., et al. A 66 fs Highly Stable Single Wall Carbon Nanotubes Mode-locked Fiber Laser. *Laser Phys.* 2014, 24:

- 15105.
104. Sobon, G., Sotor, J., Pasternak, I., Grodecki, K., et al. Er-Doped Fiber Laser Mode-Locked by CVD Graphene Saturable Absorber. *J. Light. Technol.* 2012, 30: 2770–2775.
 105. Limpert, J., Schreiber, T., Nolte, S., Zellmer, H., Tünnermann, A. All Fiber Chirped-Pulse Amplification System based on Compression in Air-Guiding Photonic Bandgap Fiber. *Opt. Express* 2003, 11: 3332.
 106. Herda, R., Isoma, A., Okhotnikov, O. G. Soliton Sidebands in Photonic Bandgap Fiber Lasers. *Electron. Lett.* 2006, 42: 1025–1027.
 107. Usechak, N.G. *Mode Locking of Fiber Lasers at High Repetition Rates*. Ph. D. Thesis. University of Rochester, 2006.
 108. Silfvast, W. T. *Fundamental of Photonics*, University of Connecticut, Orlando, Florida, 2011.
 109. Islam, M. K., Chu, P. L., Stability Analysis of Mode Locked Figure-eight Fiber Laser. *Prog. Electromagn. Res. Symp.* 2005, 416–419.
 110. Ismail, M. A., Tan, S. J., Shahabuddin, N. S., Harun, S. W., et al. Performance Comparison of Mode-Locked Erbium-Doped Fiber Laser with Nonlinear Polarization Rotation and Saturable Absorber Approaches. *Chinese Phys. Lett.* 2012, 29: 054216.
 111. Sakakibara, Y., Rozhin, A. G., Kataura, H., Achiba, Y., Tokumoto, M., Carbon Nanotube-Polyvinylalcohol Nanocomposite Film Devices : Applications for Femtosecond Fiber Laser Mode Lockers and Optical Amplifier Noise Suppressors. *Jpn. J. Appl. Phys.* 2005, 44: 1621–1625.
 112. Li, W. L., Kong, Y. C., Chen, G. W., Yang, H. R., Coexistence of Conventional Solitons and Stretched Pulses in a Fiber Laser Mode-Locked by Carbon Nanotubes. *Laser Phys.* 2015, 25: 45103.
 113. Zhang, Z., Kuang, Q., Sang, M. Passive Harmonically Mode-Locked ErbiumDoped Fiber Laser. *SPIE-OSA-IEEE Asia Commun. and Photonics*. Nanchang, China: SPIEE. 2009. 7630:1–7.
 114. Dong, X., Zhang, S., Lu, F., Yang, X., et al. Repetition Rate Switchable Passively Mode-Locked Fiber Laser for Ultrahigh-Speed Optical Communication. 2006, 8–11.

115. Grudinin, A. B., Richardson, D. J., Payne, D. N. Passive Harmonic Mode-locking of a Fiber Soliton Ring Laser. *Electron. Lett.* 1993, 29: 1860–1861.
116. Luo, Y., Li, L., Zhao, L., Sun, Q., et al. Dynamics of Dissipative Solitons in a High-Repetition-Rate Normal Dispersion Erbium-Doped Fiber Laser. *IEEE Photonics J.* 2016, 8: 1–8.
117. Wu, C., Dutta, N. K. High-Repetition-Rate Optical Pulse Generation using a Rational Harmonic Mode-Locked Fiber Laser 2000, 36: 145–150.
118. Hou, L., Haji, M., Marsh, J. H. 240 GHz Pedestal Free Colliding Pulse ModeLocked Laser with a Wide Operation Range. *Laser Phys. Lett.* 2014, 11: 115804.
119. He W., Pang M., Menyuk C. R., Russell, P. S. J. Sub-100-fs 1.87 GHz Mode-locked Fiber Laser Using Stretched-Soliton Effects. *Optica.* 2016, 3: 1366–1372.
120. Dudley, J. M., Cherif, R., Stephane, C. G., Goery, G. in: Dudley JM (Ed.), *Ultrafast Nonlinear Opt.* Springer International Publishing Switzerland, Switzerland. 2013, 177–193.
121. Hori, T., Takayanagi, J., Nishizawa, N., Goto, T. Flatly Broadened, Wideband and Low Noise Supercontinuum Generation in Highly Nonlinear Hybrid Fiber. *Opt. Express.* 2004, 12(3): 17–24.
122. Moghaddam, M. R. A., Harun, S. W., Akbari, R., Ahmad, H. Flatly Broadened Supercontinuum Generation in Nonlinear Fibers using a Mode Locked Bismuth Oxide based Erbium doped Fiber Laser. *Laser Phys. Lett.* 2011, 8: 369–375.
123. Renninger, W. H., Chong, A., Wise, F. W. Pulse Shaping and Evolution in Normal-Dispersion Mode-Locked Fiber Lasers. *IEEE J. Sel. Top. Quantum Electron.* 2012, 18: 389–398.
124. Hooper, L. E., Mosley, P. J., Muir, A. C., Wadsworth, W. J., Knight, J. C. Coherent Supercontinuum Generation in Photonic Crystal Fiber with AllNormal Group Velocity Dispersion. *Opt. Express.* 2011, 19: 4902–4907.
125. Ahmad, H., Awang, N. A., Zulkifli, M. Z., Thambiratnam, K., et al. Supercontinuum from Zr-EDF using Zr-EDF Mode-Locked Fiber Laser. *Laser Phys. Lett.* 2012, 9:44–49.

126. Ouyang, D. Q., Guo, C. Y., Ruan, S. C., Yan, P. G. et al. Optimized Flat Supercontinuum Generation in High Nonlinear Fibers Pumped by a Nanosecond Er/Yb Co-Doped Fiber Amplifier. *Laser Phys.* 2014, 24: 045104.